

Chapter I

This is a Demonstration 中國皇帝

A Section Title I 中國皇帝

 14°OO [illegible]

A Section Title 2 中國皇帝

[illegible]

A Section Title 3 中國皇帝

[illegible]

MKTS Regions 中國皇帝

To indicate the start of an MKTS-MD Region, place a triple at-sign @@@ at the start of a line, immediately followed by a command name such as `keep-lines` or `single-column`. The end of a region is indicated by a triple at-sign without a command name. Nested regions are possible; for example,

you can put a `@@@keep-lines` region inside a `@@@single-column` region as done here:

Here are some formulas: `u-cjk/4e36` 、 ●

`u-cjk/4e37` ヽ ● 、 ノ

`u-cjk/4e38` 丸 ⑨ 九 、

`u-cjk/4e39` 丹 ⑨ 冂 ● 、 一

`u-cjk/4e3a` 为 ⑨ 、 ⑩ 力 、

`u-cjk/4e3b` 主 ● 、 王

`u-cjk/4e3b` 主 ● ㄣ 土

`u-cjk/4e3c` 井 ● 井 、

`u-cjk-xb/250b7` 盥 ● 告巨皿

`u-cjk-xb/250b8` 盥 ● 楊皿

At this point, a line consisting of a triple at-sign `@@@` indicates the end of the `keep-lines` region; since the `single-column` region is still active, however, this paragraph runs across the entire width of the documents text area.

xxxx

Chapter 3

Regions

Keep-Lines Regions

A-before A-within
A-within
A-within
A-after
% $\Delta\Delta\Delta$ end

B-before
B-within
B-within
B-within

B-after

C-before

C-within
C-within
C-within

C-after

D-before

D-within
D-within
D-within

D-after