

Schema Reference — Inkglass Odyssey

Complete field definitions for all JSON schemas. Read before creating or modifying any schema file in /schemas/.

Cross-references: docs/combat_system.md (combat field context), docs/economy_balance.md (item field context), docs/companion_system.md (companion_data context), docs/faction_system.md (faction field context).

character_sheet.json

Fields: id (string), player_id (string), world_id (string), name (string), level (int, 1–20), specialisation_path_id (string), ability_scores (map of canonical score → int), skill_proficiencies (array of skill IDs), saving_throw_proficiencies (array of two canonical score IDs, from specialisation path), hp_current (int), hp_max (int, computed from hit die + level + CON modifier), ac (int, computed from equipped gear + DEX), passive_checks (map of skill_id → computed value: 10 + ability mod + proficiency if proficient), conditions (array of {condition_id, duration_turns or expiry_turn, source}), exhaustion_level (int, 0–6), resources (map of resource_type → current/max, schema per world_config.json), wallet (map of world_id → currency amount), inventory (array of {item_id, quantity, binding_state}), equipped_gear (map of slot → item_id), known_recipes (array of recipe IDs), companions (array of {npc_id, behavior_type, loyalty_strain}), rp_voice_notes (string, player-authored), relationships (map of npc_id → relationship_score), faction_standing (map of faction_id → int, -100 to 100), created_at (ISO datetime), updated_at (ISO datetime).

npc_personality.json

Identity: id (string), world_id (string), name (string), entity_class (humanoid | creature | spirit | construct), role (string), level (int, 1–20), hit_die (6/8/10/12).

Narrative fields (passed to LLM): personality_background (string), goals (object: immediate (array of strings), long_term (array of strings)), weaknesses_fears (string), communication_style (string), power_narrative (string), knowledge_boundaries (object: knows (array of strings), does_not_know (array of strings)), relationships (array of {npc_id, relationship_type (ally | rival | subordinate | mentor | family | trading_partner | unknown), description (string)}), secrets (array of {content (string), reveal_condition (relationship_threshold | quest_flag | check_type_and_dc | never), secret_type (information

| identity))).

Voice examples: few_shot_examples (array of {player_input, npc_response, context_tag (optional: casual | tense | hostile | transactional)} — minimum five for Admin Workshop / global defaults, minimum two for DM Workshop / room-local NPCs), manipulation_resistance_examples (array of {player_input, npc_refusal} — minimum one).

Physical presence: animation_profile (object: default_stance, default_gaze, emotional_state_to_animation map with minimum three entries, movement_triggers), world_position (object: region_id, coordinates), schedule (array of {time_range, position}).

Mechanical stat block (relay only, never passed to LLM): ability_scores (map of canonical score → int), ac (int), saving_throw_proficiencies (array of two canonical score IDs), skill_proficiencies (array of skill IDs), hp_max (int, computed from level + hit_die + CON modifier), resistances (array of damage type strings), vulnerabilities (array of damage type strings), immunities (array of damage type strings), conditions (array of active conditions with duration), notable_equipment (array of item IDs).

Conditional sections:

shop_data (shop NPCs only): inventory (array of {item_id, stock_quantity, markup_percentage}), pricing_policy (string), restock_schedule (daily | weekly | never), access_prerequisites (object: faction_standing_threshold, level_requirement, quest_flags).

transport_data (transport NPCs only): routes (array of {origin_region, destination_region, fare}), vessel_type (string), passenger_capacity (int), schedule (string).

companion_data (companion NPCs only): recruitment (object: affection_threshold (int), recruitment_scenario_id (string), recruitment_conditions (array of world-state flags)), combat_profile (object: behavior_type (aggressive | supportive | defensive), abilities (array of 2–3 ability IDs), directive_vocabulary (map of recognised prose commands → behavior mappings)), ambient_behavior (object: comment_frequency, trigger_categories array, mood_modifier), loyalty_strain_threshold (int, default 3), world_event_reactions (array of {event_id, relationship_modifier, ambient_comment}), farewell_template (string), reunion_template (string), dismissal_relationship_modifier (int).

ability.json

Fields: id (string), world (string), name (string), description (string — narrative; AI reads this, relay does not), ability_score (canonical — governs check), modifier_source (canonical score added to damage/healing rolls), damage_dice (optional, dice notation), damage_type (optional), healing_dice (optional, dice notation — separate from damage_dice), save_type (optional — defender's ability), save_dc_source (optional — attacker's ability for DC), applies_condition (optional — condition_id + duration), cost (object: resource_type,

amount), cooldown_turns (optional, int), level_requirement (int), tags (array of strings).

item.json

Fields: id (string), world (string), name (string), type (weapon | armour | shield | consumable | material | tool | quest), rarity (common | uncommon | rare | legendary), weight (float), value (int, gc equivalent), description_prose (string — narrative, passed to LLM), binding (unbound | bind_on_equip | bind_on_acquire), unique (boolean), stats (object, structure varies by type — see docs/economy_balance.md for full breakdown).

recipe.json

Fields: id (string), world (string), name (string), output_item_id (string), output_quantity (int), input_materials (array of {item_id, quantity}), required_station_type (string), required_skill (string), skill_dc (int), discovery_method (taught | found | experimentation), level_requirement (int).

quest.json

Fields: id (string), world (string), name (string), description (string), objectives (array of {id, description, completion_condition}), rewards (object: xp, currency, items), prerequisite_questions (array of quest IDs), prerequisite_level (int), faction_id (optional), repeatable (boolean).

faction.json

Fields: id (string), world (string), name (string), description (string), allied_factions (array of faction IDs), rival_factions (array of faction IDs), reputation_thresholds (map of tier label → minimum value), shop_price_modifiers (map of tier label → price multiplier), notable_npcs (array of npc_ids).

scene_state.json

Fields: scene_id, session_id, scenario_id, participants (array of player/NPC IDs), current_beat (string), emotional_temperature (float, 0.0–1.0), active_checks (array), environment_state (object, scenario-specific), environmental_effects (array of effect objects), turn_history_summary (string, compressed), pending_turn (object: player_input, stage enum [pending | analysis_complete | checks_resolved | response_generated | committed], scene_snapshot), director_signals (array of signal objects from Narrative Director), updated_at.

world_config.json

Fields: world_id (string), display_name (string), content_rating (moderate | mature), rp_system_prompt_addendum (string), traversal_config (array of traversal_mode IDs), currency_id (string), ability_score_map (map of world-specific name → canonical identifier), equipment_slots (optional array of slot IDs — overrides default set if present), resource_model (object), time_of_day_cycle (object), max_active_companions (int, default 1), specialisation_paths (array of specialisation_path objects), rest_rules (object: short_rest_hp_percent, short_rest_hit_dice_formula, long_rest_hp_percent, long_rest_exhaustion_reduction), economy_config (object: earning_rates, price_ranges, sell_back_ratio, crafting_margin_target, transport_fare_ranges), environmental_effects_registry (array of available effect definitions).

specialisation_path (embedded in world_config.json)

Fields: id (string), world (string), display_name (string), path_archetype (scholar | balanced | martial | tank), hit_die (6 | 8 | 10 | 12), saving_throw_proficiencies (array of exactly two canonical score IDs), primary_ability_scores (array of 1–2 canonical score IDs), available_skill_proficiencies (array of skill IDs), description (string — narrative framing).

world_events.json

Canonical specification: docs/narrative-control-ui.pdf Section 6.

Fields per event: id (string), label (string), world (ref to world_id), description (string), is_default (boolean, default true), is_suppressible (boolean, default true), default_timing (object: type (sequence | scenario_completion | flag_condition), after_event, delay_sessions, required_scenario, required_flags), prerequisites (object — world-state flags), consequences (object: world_flags_set, scenarios_unlocked, scenarios_locked, npc_relationship_modifiers, companion_triggers), variant_outcomes (array of {condition, consequences}), foreshadowing_signals (array of strings), narrator_prompt_addendum (string).