

# UNIVERSITY COLLEGE OF ENGINEERING KAKINADA, (AUTONOMOUS) JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY KAKINADA

Pithapuram Road, Kakinada-533003

Phone: Off: 0884-2300823 Fax: 0884-2386516

### Tender Notice No. JNTUK-UCEK/ Equipment/2017

Date: 01/09/2017

### **TENDER SCHEDULE**

### **GENERAL CONDITIONS:**

- Please quote your lowest rates for each item described. The quotation should reach this office on or before 20/09/2017 by 03:00 P.M. Sealed covers should be submitted for the items super scribing as "Tender Notice No.", "Description of item" & "Item Number(s)". The sealed covers should be sent by the Registered Post (or) to be dropped in the sealed box provided in the office of the Principal. The tender will be opened on 20/09/2017 at 04:00 P.M. by the undersigned/his nominee in the presence of the committee members and available tenderers or their representatives.
- 2. Separate tender forms should be submitted for each item as per the specifications mentioning with the additional features if any.
- 3. E.M.D: The tender documents should be submitted along with earnest money deposit Rs.5,000/- in the form of Demand Draft in favor of "The Principal, JNTUK, University College of Engineering, Kakinada" to be payable at State Bank of India, JNTU Campus Branch, Kakinada. The Demand Draft pertaining to E.M.D. of unsuccessful party will be returned.
- 4. **PRICES:** The price should be F.O.R. destination inclusive of taxes, packing & forwarding charges, freight and delivery charges. Items on rate contract; if any together with the terms and conditions may please be furnished.
- 5. **PAYMENT:** 100% payment will be made within a reasonable time only after the receipt of all items in good condition and installation as per given specifications and after testing for satisfactory working and on receipt of the company's invoice with all Supporting vouchers such as copy of G S T Registration certificate etc. **No advance will be paid in any case either in part or in full.**
- 6. **ACCEPTANCE:** It is not binding on the university/ institution to accept the lowest of the tenders. The university/ institution reserves the right to place orders for individual items with different tenderers.
- 7. **SPECIFICATIONS:** Full specifications along with the description and make should be mentioned in the tender.
- 8. Warranty/Guaranty: Warranty/Guaranty period should be mentioned by the tenderer.

- DELIVERY: The period of delivery at destination from date of placing orders is FOUR WEEKS.
- 10. VALIDITY: The quotations should be valid for at least 90 days.
- 11. The Institution reserves the right to cancel the tender without assigning any reason.
- 12. The tenderer should produce copy of Service tax certificate and PAN card.
- 13. Those who purchased tender schedule officially by paying **Rs. 500/-** in the form of Demand Draft drawn in favor of Principal, JNTUK University College of Engineering, payable at Kakinada are only eligible to participate in the tender. Those who have downloaded the tender schedule from the JNTUK website (<a href="www.jntuk.edu.in">www.jntuk.edu.in</a>) should submit a separate DD for **Rs.500/-** along with the quotation.
- 14. This Institution being Government educational institution is exempted from payment of Central/State Excise Duty.
- 15. Since the college is Government institution whatever conditions are applicable to any Government institute shall be applicable even if not specified.
- Any tender that is received after due date will not be accepted. The college is not responsible for any postal delay.
- 17. List of Major Customers should be provided.
- 18. Either Colour Letter head or white paper with round seal and signature is compulsory while quoting the tender price.
- 19. Wherever possible, buyback procedure should be adopted.



Dr. G.V.R. PRASADA RAJU
PRINCIPAL
University College of Engineering, Kakinada
Jawaharlal Nehru Technological University Kakinada
Kakinada-533 003

### **FORMAT OF QUOTATION\***

### (To be filled in concerned firm letterhead)

To The Principal, University College of Engineering Kakinada (A), JNT University Kakinada, Kakinada.

petros aparento se o	Total	Am

Date:

		Qty	Unit	Quoted Unit rate in Rs.	Total Amount	
	Specifications)				In figures	In words
		de communicações de manago, paradida de				100000000000000000000000000000000000000
PARAMETER (NEW YORK) PROPERTY AND A				00 11 1 10 1 16 10 1 10 1 10 1 10 1 10		

Gross Total cost:

We agree to supply the above good the total contract price of Rs.	ds in accordance with the technical specifications for (Amount in figures) (Rupees
	within the period specified in the Invitation for
Quotations.	
apply to the offered goods'	commercial warranty / guarantee of months shall
We hereby certify that we have tak our behalf will engage in bribery.	ten steps to ensure that no person acting for us or on
Signature of Supplier	
Name :	Mobile No

• Applicable while the bids are being invited for more than one item and would be evaluated for all the items together. Modify where evaluation would be made for each item separately.

### Training and Placement Office Specifications for

### 1.5 Ton Air Conditioners

S.No.		Quantity
1.	Supply, Installation, Testing and Commissioning of 1.5 TR 5 Star split AC unit with hyper tropical compressor using R410A refrigerant and capable of delivering 21600 BTU/hr with high wall mounted indoor unit and outdoor condensing unit Hermetically sealed compressor suitable for operation on 230V, 50Hz, 1Phase AC supply capable of performing cooling dehumidifying air circulating and filtering with cooling and condensing units and 4 mts of 3 core copper flexible cable between indoor and outdoor units including built-in stabilizer (Voltage range 160-264 volts) and cordless remote control.  Additional accessories: Supply and fixing of 5.0 KVA Stabilizer and AC Stand.	6 No's

# Training and Placement Office Specifications for

### 2 Ton Air Conditioner

S.No.	Description of the Item	Quantity
1.	Supply, Installation, Testing and Commissioning of 2.0 TR 5 Star split AC unit capable of delivering 21600 BTU/hr and above with operating on refrigerant R-22 / R- 410A with high wall mounted indoor unit and outdoor condensing unit Hermetically sealed compressor suitable for operation on 230V, 50Hz, 1Phase AC supply capable of performing cooling dehumidifying air circulating and filtering with cooling and condensing units and 4 mts of 3 core copper flexible cable between indoor and outdoor units including built-in stabilizer (Voltage range 160-264 volts) and cordless remote control etc complete.  Additional accessories: Supply and fixing of 5.0 KVA Stabilizer and AC Stand.	1 No

# Item No: 3 Training and Placement Office Specifications for LCD-Projector

Brightness	2800 ANSI Lumens
Technology	3 LCD Technology
Projection Type	Short Throw
Projection Size	53 Inches-116 Inches
Color Light Output and White Light Output	2800
Contrast	16000:1
Resolution	1280×800, 16:10
Input Connectivity	VGA, HDMI, RS-232, RCA
Wired LAN	Standard
Inbuilt Speakers	16W
Lamp Hours	6000 lamphour10,000 hr. ECO mode
USB Connectivity	Type A & Type B 2.0
Noise Level	28 d Blow Noise
Weight	3.7 Kgs or lesser
Wi Fi	Yes
Warranty	3 Years
OEM	Authorization Letter to be Enclosed

## 1. Technical specifications of 250 LPH RO plant with Membrane auto flushing and auto on off controls

Raw Water Pump

Capacity
Type
MOC
Drive

Pressure

Make

**Dual Media filter** 

Size MOC

Multiport valve

pipeline Media

Make

Anti scalant dosing

Flow rate Pump type

Operating pressure

Volume and MOC of dosing tank

Make

Micron cartridge filter

Size

MOC: Housing/filter

Type of filter

High-pressure pump

Capacity Pressure Type

Make

RO system

Size. of pressure tubes No. of pressure tubes MOC of pressure tubes Size of membranes No. of membranes

Make

Low pressure Pipe line and fittings High pressure Pipe line and fittings RO skid One

1 m<sup>3</sup>/hr

Monoblock centrifugal pump

CI 0.5 HP 3 kg/cm<sup>2</sup> CRI/equivalent

One

12" Dia. x 48"0 mm HOS

FRP 20 NB 25 NB

Pebbles, Silex, Fine sand.,

Carbon

Aventura/Equivalent

One

0-4 lph

Diaphragm type 4 kg/cm<sup>2</sup>

50 liters, HDPE Milton Roy-Asia LMI

Two

4"x 20" length PVC / PP

rvc / rr

Spun wound PP 10 µ

One

0.8 m<sup>3</sup>/hr 9-12 kg/cm<sup>2</sup>

Multistage vertical centrifugal

CRI/eq.

One

4" x 40"

One

SS 304, 16 kg/cm<sup>2</sup>

4" x 40"

One

Toray/GE/ Eq.

UPVC, CPVC SS 304

UV sterilizer	One
Capacity	250 m <sup>3</sup> /hr
Make	Alfa
Electrical and Instrumentation	
Panel board-LED display, TDS meters, auto on /off.	One
Pressure gauges	Two
Rotameters- UKL	Two
Flow sensors- FLOWTEC	One
SV- U flow	One
Level sensor-	One
LPS and HPS- Danfos	TWO

Raw water tank	One
Capacity	500 lts
MOC	HDPE

### Pure water tank Capacity

MOC

### One

500 lts

Stainless steel

### Key Features of the plant

- > Automatic Membrane Auto flushing system
- > Plant Automatic on/off control system
- Digital TDS and flow display
- SS 304 skid
- > Complete Auto logic panel with GSM

### RO Plant operating data

Based on the raw water characteristics and desired output, the operating parameter of the 250 LPH RO plant shall be as given below:

Raw water flow	$0.75  \text{m}^3/\text{hr}$
Product water flow	$0.25 \text{ m}^3/\text{hr}$
Reject water flow	$0.5 \text{ m}^3/\text{hr}$

% of recovery 30-35 % approximately

# 1. Technical specifications of 1000 LPH RO plant with Membrane Auto flushing and auto/off control system

Raw Water Pump

Capacity
Type
MOC
Drive
Pressure

Make

Pressure sand Filter

Size
MOC
Multiport valve
UPVC pipeline
Media
Make

**Activated Carbon Filter** 

Size MOC Multiport valve UPVC pipeline Media Make

Anti scalant dosing

Flow rate
Pump type
Operating pressure
Volume and MOC of dosing tank

Make

Micron cartridge filter

Size MOC: Housing/filter Type of filter

High-pressure pump

Capacity Pressure Type Make

RO system

Size. of pressure tubes
No. of pressure tubes
MOC of pressure tubes
Size of membranes
No. of membranes
Type & make

One

3 m³/hr

Monoblock centrifugal pump

CI 1.0 HP 3 kg/cm<sup>2</sup> CRI/equivalent

One

13" Dia. x 54"0 mm HOS

FRP 25 NB 25 NB

Pebbles, Silex, Fine sand Pentair/ Aventura/Equivalent

One

13" Dia. x 54"0 mm HOS

FRP 25 NB 25 NB

activated carbon Pentair/ Equivalent

One

0 – 4 lph Diaphragm type 4 kg/cm<sup>2</sup> 50 liters, HDPE Miltonroy-Asia lmi

Two

2.5"x 20" length PVC / PP

Spun wound PP 10 µ

One

2.5 m<sup>3</sup>/hr 9-12 kg/cm<sup>2</sup>

Multistage vertical centrifugal

CRI

One

8" x 40" One

FRP, 16 kg/cm<sup>2</sup>

8" x 40" One

Spiral wound; GE / Eq.

Low pressure Pipe line and fittings High pressure Pipe line and fittings

RO skid

UPVC, **CPVC** 

304 Stainless Steel

**UV** sterilizer One

Capacity 1000 m3/hr

Make Alfa One

Raw water tank

2000 Its Capacity

MOC HDPE

Pure water tank One Capacity 2000 lts

MOC Stainless steel

Electrical and Instrumentation Qty board-LED display, TDS One

meters, auto on /off.

Two Pressure gauges Rotameters- UKL Two Flow sensors- FLOWTEC One SV- U flow One Level sensor-One LPS and HPS- Danfos TWO

#### 2. RO Plant operating data

Based on the raw water characteristics and desired output, the operating parameter of the 1000 LPH RO plant shall be as given below:

Raw water flow 3.00 m3/hr Product water flow 1.00 m<sup>3</sup>/hr Reject water flow 2.00 m<sup>3</sup>/hr 30-35 % % of recovery

### Key Features of the plant

- > Automatic Membrane Auto flushing system
- > Plant Automatic on/off control system
- > Digital TDS and flow display
- SS 304 skid
- Complete Auto logic panel with GSM