

Contents

1	15-command-reference	1
2	glossary	5

1 15-command-reference

15 - Reference commandes

Chaque commande indique le role minimal. Les actions marquees Approval peuvent etre preparees par Service mais executees seulement apres approbation Admin.

Commande	Role	Confirmation	Description
---	---	---	---
`auth whoami`	Service	Non	Affiche l'identite Linux/SekaiLink et capabilities.
`dashboard`	Service	Non	Affiche la matrice locale Core Access MVP.
`commands list`	Service	Non	Liste le registre de commandes connu du binaire.
`commands search <query>`	Service	Non	Recherche dans le registre de commandes.
`server status <server all> --execute`	Service	Non	Statut CPU/RAM/disk/uptime/services; live read-only si gate e
`server services <server>`	Service	Non	Liste services systemd connus.
`server agent-health [server all] --execute`	Service	Non	Lit `/health` des admin-agents loopback via SSH; gate r
`server agent-system [server all] --execute`	Service	Non	Lit `/system` des admin-agents avec token serveur et ga
`server agent-services [server all] --execute`	Service	Non	Lit `/services` des admin-agents avec token serveur e
`server agent-service <server> <service> --execute`	Service	Non	Lit etat/state d'un service declare dans l'admin
`server agent-logs <server> <service> --execute`	Service	Non	Lit le tail JSON expose par l'admin-agent pour un s
`nexus services --execute`	Service	Non	Liste les services connus par le private Nexus admin-agent; dry-run par d
`server logs <server> <service> --follow --execute`	Service	Non	Suit les logs d'un service; execution distante b
`server restart <server> <service> --confirm <server>:<service>:restart --execute`	Admin	Oui	Redemarre un servic
`server start <server> <service> --confirm <server>:<service>:start --execute`	Admin	Oui	Demarre un service decl
`server stop <server> <service> --confirm <server>:<service>:stop --execute`	Admin	Oui	Arrete un service declare
`server update plan <server>`	Admin	Non	Prepare un plan d'update.
`server update apply <server>`	Admin	Oui	Applique un update apres backup gate.
`ssh open <server>`	Admin	Oui	Ouvre une session SSH explicite.
`health probe <server all> --execute`	Service	Non	Lance/verifie une sonde health; dry-run par default.
`logs list`	Service	Non	Liste les sources logs.
`logs list --by-server`	Service	Non	Vue logs par serveur/service.
`logs list --by-incident`	Service	Non	Vue logs correlees incident.
`logs tail <source> --execute`	Service	Non	Suit une source log; dry-run par default.
`logs search <query> [source all] --execute`	Service	Non	Recherche read-only dans les logs allowlistes; dry-run
`logs filter <term...> source:<source all> --execute`	Service	Non	Filtre read-only par user/lobby/room/correlati
`logs pin <source> <text>`	Service	Non	Epingle une ligne ou un extrait comme preuve locale.
`logs note <source> <text>`	Service	Non	Cree une note locale ciblee `log:<source>`.
`logs export [query] --format <md jsonl txt> --file <name>`	Service	Non	Exporte pins et notes logs locaux.
`audit export [query] [file-name]`	Service	Non	Exporte des lignes d'audit locales dans le dossier exports Core A
`note add <target> <text>`	Service	Non	Ajoute une note locale liee a un incident, log, user, lobby ou room.
`note list [query]`	Service	Non	Liste les notes locales, optionnellement filtrees.
`note export [query] [file-name]`	Service	Non	Exporte des notes locales dans le dossier exports Core Access.
`approval request <command> <reason>`	Service	Non	Demande une approbation Admin pour une commande sensible.
`approval list`	Service	Non	Liste les demandes et decisions locales.
`approval approve <id> [reason]`	Admin	Oui	Approuve localement une demande existante, sans execution serveur en
`incident open <label> <severity> <summary>`	Service	Non	Ouvre un workspace incident local append-only.
`incident list [query]`	Service	Non	Liste les events incidents locaux, optionnellement filtrees.
`incident status <label>`	Service	Non	Affiche etat, events, notes et pins locaux d'un incident.
`incident note <label> <text>`	Service	Non	Ajoute une note locale ciblee `incident:<label>`.
`incident pin <label> <source> <text>`	Service	Non	Attache une preuve log locale a un incident.
`incident export <label> --file <name>`	Service	Non	Exporte le workspace incident local en Markdown.
`incident close <label> <resolution>`	Service	Non	Ferme localement le workspace incident.
`ops snapshot [label]`	Service	Non	Cree un snapshot Markdown local avec dashboard, logs, services, audit, notes
`ops timeline [query]`	Service	Non	Affiche une timeline locale audit/incidents/notes/pins/approvals/drafts.
`ops handoff [label] --file <name>`	Service	Non	Exporte un rapport Markdown local de releve de shift.
`ops doctor [--verbose]`	Service	Non	Verifie localement l'etat du cockpit, outils, env gates, stores, docs et PD

```

| `ops paths` | Service | Non | Liste les chemins locaux Core Access utiles pour audit, notes, incidents, exports et doc
| `ops exports [query]` | Service | Non | Liste les exports locaux Core Access par date, taille et fichier. |
| `user search <query> --execute` | Service | Non | Recherche utilisateur via Nexus Identity read-only; dry-run par defa
| `user open <user> --execute` | Service | Non | Ouvre fiche utilisateur via Nexus Identity read-only; ajoute une trace
| `user create <user> <email> <role> --password-env ENV --confirm user:<user>:create --execute` | Admin | Oui | Cree un
| `user edit <user> key=value --confirm user:<user>:edit --execute` | Admin | Oui | Modifie un utilisateur via Nexus Ide
| `user disable <user> --confirm user:<user>:disable --execute` | Admin | Oui | Desactive un utilisateur et revoke sessi
| `user sessions <user> --execute` | Service | Non | Liste sessions via Nexus Identity read-only; ajoute une trace audit
| `user devices <user> --execute` | Service | Non | Liste devices via Nexus Identity read-only; ajoute une trace audit s
| `user audit <user> --execute` | Service | Non | Liste audit utilisateur via Nexus Identity read-only; ajoute une trace
| `user revoke-sessions <user> --confirm user:<user>:revoke-sessions --execute` | Admin | Oui | Revoque toutes les sessi
| `user force-password-reset <user> --confirm user:<user>:force-password-reset --execute` | Admin | Oui | Declenche un r
| `user configs <user_id> [game_key] [--execute]` | Service | Non | Liste configs utilisateur via seed-config API. |
| `user config open <user_id> <config_id> [--execute]` | Service | Non | Ouvre une config via liste filtree. |
| `user config diff <user_id> <config_id> <version>` | Service | Non | Draft diff version. |
| `user config export <user_id> <config_id> --format yaml [--execute]` | Service | Non | Exporte YAML. |
| `user config edit <user_id> <config_id> key=value [key=value...] --confirm user-config:<user_id>:<config_id>:edit` | A
| `lobby list --execute` | Service | Non | Liste les lobbies via Nexus lobby-admin read-only; dry-run par default. |
| `lobby open <lobby> --execute` | Service | Non | Ouvre un detail lobby via Nexus lobby-admin read-only; dry-run par de
| `lobby create` | Admin | Oui | Cree lobby manuel. |
| `lobby edit <lobby>` | Admin | Oui | Modifie lobby. |
| `lobby close <lobby>` | Service/Admin | Oui/Approval | Ferme lobby selon policy. |
| `lobby lock <lobby>` | Service | Oui | Verrouille lobby. |
| `lobby unlock <lobby>` | Service | Oui | Deverrouille lobby. |
| `lobby chat <lobby>` | Service | Non | Ouvre chat. |
| `lobby join-secret <lobby>` | Admin | Oui | Observe lobby invisiblement pour joueurs. |
| `lobby broadcast <lobby> <message>` | Service | Oui | Broadcast lobby. |
| `room list` | Service | Non | Liste rooms. |
| `room open <room>` | Service | Non | Ouvre room. |
| `room summary <room>` | Service | Non | Resume room. |
| `room events <room>` | Service | Non | Evenements room. |
| `room logs <room> --follow` | Service | Non | Logs room/AP. |
| `room snapshot <room>` | Service | Non | Snapshot et archive etat. |
| `room sync <room>` | Admin | Oui | Force sync payload. |
| `room pending-items <room>` | Service | Non | Items en attente. |
| `room client-reports <room>` | Service | Non | Rapports clients. |
| `room request-sklmi-reconnect <room> <player>` | Service | Oui | Demande reconnect SKLMI. |
| `room disconnect-runtime <room> <player>` | Admin | Oui | Deconnecte runtime. |
| `room give-item <room> <target> <item>` | Admin | Oui | Injecte item live. |
| `client broadcast <user|all> <message> --confirm client:broadcast:<target>` | Service | Oui | Cree un draft audite de
| `client maintenance-banner <user|all> <message> --confirm client:maintenance-banner:<target>` | Admin | Oui | Cree un
| `client force-update-prompt <user|all> <version|message> --confirm client:force-update-prompt:<target>` | Admin | Oui
| `client request-relogin <user|all> <reason> --confirm client:request-relogin:<target>` | Service | Oui | Cree un draft
| `client refresh-lobby <user|all> [lobby]` | Service | Non | Cree un draft audite de refresh lobby; aucun signal envoye
| `client refresh-room <user|all> [room]` | Service | Non | Cree un draft audite de refresh room; aucun signal envoye. |
| `client request-sklmi-reconnect <user|all> <reason> --confirm client:request-sklmi-reconnect:<target>` | Service | Oui
| `client restart-runtime <user|all> <reason> --confirm client:restart-runtime:<target>` | Admin | Oui | Cree un draft a
| `client clear-cache-request <user|all> <reason> --confirm client:clear-cache-request:<target>` | Service | Approval |
| `client diagnostics-request <user> <incident> <reason> --include <set>` | Service | Consentement | Prepare une demande
| `client diagnostics-list [query]` | Service | Non | Liste les demandes locales de diagnostics client. |
| `client diagnostics-export [query] --file <name>` | Service | Non | Exporte les demandes diagnostics et le contrat de
| `broadcast global <message> --confirm broadcast:global:all` | Admin | Oui | Cree un draft audite global; aucun broadca
| `broadcast server <server> <message> --confirm broadcast:server:<server>` | Admin | Oui | Cree un draft audite cible s
| `broadcast lobby <lobby> <message> --confirm broadcast:lobby:<lobby>` | Service | Oui | Cree un draft audite lobby; au
| `broadcast room <room> <message> --confirm broadcast:room:<room>` | Service | Oui | Cree un draft audite room; aucun b
| `broadcast role <role> <message> --confirm broadcast:role:<role>` | Admin | Oui | Cree un draft audite role; aucun bro
| `broadcast version <version> <message> --confirm broadcast:version:<version>` | Admin | Oui | Cree un draft audite ver
| `broadcast game <game> <message> --confirm broadcast:game:<game>` | Service | Oui | Cree un draft audite jeu; aucun br
| `maintenance status` | Service | Non | Etat maintenance. |
| `maintenance enable <scope> <message> --confirm maintenance:<scope>:enable` | Admin | Oui | Cree un draft audite d'act
| `maintenance disable <scope> [reason] --confirm maintenance:<scope>:disable` | Admin | Oui | Cree un draft audite de d
| `maintenance schedule <scope> <start> <end>` | Admin | Oui | Planifie maintenance. |
| `maintenance broadcast <scope> <message> --confirm maintenance:<scope>:broadcast` | Admin | Oui | Cree un draft audite

```

```

| `maintenance history` | Service | Non | Historique. |
| `release current` | Service | Non | Affiche le dernier manifeste local client update-bundle et ses URLs/fallbacks. |
| `release list` | Service | Non | Liste les manifestes locaux dedupliques par date/version/channel/build. |
| `release verify [latest|version|date|manifest] [--fast]` | Service | Non | Verifie existence, taille et SHA-256 des ar
| `release verify-cdn [channel] [platform|all] --execute` | Service | Non | Probe l'API publique `release-latest`; dry-r
| `release compare <a> <b>` | Service | Non | Compare deux manifestes locaux par version, URL, artefacts, tailles et has
| `release publish <manifest|version|date> --confirm release:<version>:publish` | Admin | Oui | Cree un draft audite de
| `release rollback <version> --confirm release:<version>:rollback` | Admin | Oui | Cree un draft audite de rollback; ne
| `release schedule <manifest|version|date> <datetime> --confirm release:<version>:schedule` | Admin | Oui | Cree un dra
| `release notes [version|date|manifest]` | Service | Non | Affiche le manifeste local et les drafts release lies. |
| `release audit [version|date|manifest]` | Service | Non | Affiche le manifeste local et les drafts release lies. |
| `client-banner list` | Service | Non | Liste 3 slots. |
| `client-banner edit <slot>` | Admin | Oui | Edite slot. |
| `client-banner preview <slot>` | Service | Non | Preview. |
| `client-banner publish <slot> --confirm banner:<slot>:publish` | Admin | Oui | Cree un draft audite de publication ban
| `client-banner rollback <slot> --confirm banner:<slot>:rollback` | Admin | Oui | Cree un draft audite rollback banner;
| `client-banner disable <slot> --confirm banner:<slot>:disable` | Admin | Oui | Cree un draft audite disable banner; au
| `pack repo list` | Service | Non | Liste repos packs. |
| `pack repo add <id> <url> <game> [notes] --confirm pack-repo:<id>:add` | Admin | Oui | Cree un draft repo pack; aucun
| `pack repo edit <id> key=value --confirm pack-repo:<id>:edit` | Admin | Oui | Cree un draft edition repo pack; aucun p
| `pack repo disable <id> [reason] --confirm pack-repo:<id>:disable` | Admin | Oui | Cree un draft disable repo pack; au
| `pack repo delete <id> [reason] --confirm pack-repo:<id>:delete` | Admin | Oui | Cree un draft delete repo pack; aucun
| `pack check <id> [notes]` | Service | Non | Cree un draft check pack; aucun fetch reseau. |
| `pack validate <id> [notes]` | Service | Non | Cree un draft validate pack; aucune logique Lua executee. |
| `pack stage <id> [notes] --confirm pack:<id>:stage` | Admin | Oui | Cree un draft stage pack; aucun artifact CDN stage
| `pack publish <id> [notes] --confirm pack:<id>:publish` | Admin | Oui | Cree un draft publish pack; aucun artifact CDN
| `pack rollback <id> <version> --confirm pack:<id>:rollback:<version>` | Admin | Oui | Cree un draft rollback pack; auc
| `pack schedule-check <id> <cron|interval> --confirm pack:<id>:schedule-check` | Admin | Oui | Cree un draft scheduler
| `schedule list` | Service | Non | Liste jobs. |
| `schedule calendar` | Service | Non | Vue calendrier. |
| `schedule add <name> <when> <command> --confirm schedule:<name>:add` | Admin | Oui | Ajoute un draft job local; job no
| `schedule edit <job> key=value --confirm schedule:<job>:edit` | Admin | Oui | Cree un draft edition scheduler; aucun j
| `schedule pause <job> [reason] --confirm schedule:<job>:pause` | Admin | Oui | Cree un draft pause scheduler; aucun jo
| `schedule resume <job> [reason] --confirm schedule:<job>:resume` | Admin | Oui | Cree un draft resume scheduler; aucun
| `schedule run-now <job> [reason] --confirm schedule:<job>:run-now` | Admin | Oui | Cree un draft run-now; aucun job ex
| `schedule history` | Service | Non | Historique local des jobs/drafts scheduler. |
| `discord status [--execute]` | Service | Non | Statut bot Discord via service allowliste. |
| `discord reload --confirm discord:reload:bot` | Admin | Oui | Draft reload bot. |
| `discord announce <channel> <message> --confirm discord:announce:<channel>` | Service | Oui | Draft annonce Discord. |
| `discord sync-roles --confirm discord:sync-roles:all` | Admin | Oui | Draft sync roles. |
| `discord command list` | Service | Non | Liste commandes. |
| `discord command enable <name> [detail] --confirm discord:command:<name>:enable` | Admin | Oui | Draft activation comm
| `discord command disable <name> [detail] --confirm discord:command:<name>:disable` | Admin | Oui | Draft desactivation
| `discord command edit <name> [detail] --confirm discord:command:<name>:edit` | Admin | Oui | Draft edition commande. |
| `discord timer list` | Service | Non | Liste timers. |
| `discord timer edit <id> key=value [key=value...] --confirm discord:timer:<id>:edit` | Admin | Oui | Draft edition tim
| `discord incident-post <incident> [channel] [message] --confirm discord:incident-post:<incident>` | Service | Oui | Dr
| `discord logs [--follow] [--execute]` | Service | Non | Logs Discord. |
| `twitch status [--execute]` | Service | Non | Statut bot Twitch via service allowliste. |
| `twitch connect <channel> [reason] --confirm twitch:connect:<channel>` | Admin | Oui | Draft connexion channel. |
| `twitch disconnect <channel> [reason] --confirm twitch:disconnect:<channel>` | Admin | Oui | Draft deconnexion channel
| `twitch announce <channel> <message> --confirm twitch:announce:<channel>` | Service | Oui | Draft annonce Twitch. |
| `twitch command list` | Service | Non | Liste commandes. |
| `twitch command enable <name> [detail] --confirm twitch:command:<name>:enable` | Admin | Oui | Draft activation comman
| `twitch command disable <name> [detail] --confirm twitch:command:<name>:disable` | Admin | Oui | Draft desactivation c
| `twitch command edit <name> [detail] --confirm twitch:command:<name>:edit` | Admin | Oui | Draft edition commande. |
| `twitch timer list` | Service | Non | Liste timers. |
| `twitch timer edit <id> key=value [key=value...] --confirm twitch:timer:<id>:edit` | Admin | Oui | Draft edition timer
| `twitch lobby announce <lobby> [message] --confirm twitch:lobby:<lobby>:announce` | Service | Oui | Draft annonce lobb
| `twitch stream set-title-hint [channel] <title>` | Service | Non | Draft aide titre stream. |
| `twitch logs [--follow] [--execute]` | Service | Non | Logs Twitch. |
| `cleanup plan logs` | Admin | Non | Cree un draft plan cleanup logs; aucun scan/suppression. |
| `cleanup plan db` | Admin | Non | Cree un draft plan cleanup DB; aucune mutation DB. |

```

```
| `cleanup plan spool` | Admin | Non | Cree un draft plan cleanup spool; aucune suppression. |
| `cleanup plan all` | Admin | Non | Cree un draft plan cleanup global; aucun scan/suppression. |
| `cleanup apply <plan_id> --confirm cleanup:<plan_id>:apply` | Admin | Oui | Cree un draft apply cleanup; aucune mutati
| `cleanup history` | Service | Non | Liste les drafts cleanup locaux. |
| `cleanup rollback <id> --confirm cleanup:<id>:rollback` | Admin | Oui | Cree un draft rollback cleanup; aucune mutatio
| `audit search` | Service | Non | Recherche audit. |
```

2 glossary

Glossaire

****Admin****: role complet avec actions dangereuses, approvals et maintenance.

****Approval queue****: file de demandes preparees par Service et approuvees par Admin.

****Bastion Nexus****: serveur Nexus utilise comme point d'entree SSH et hote de Core Access.

****Client Core****: app desktop SekaiLink utilisateur.

****Core Access****: cockpit TUI admin. Ne pas confondre avec Client Core ou les libretro cores.

****Evolution****: role distribution, CDN, assets, packs et releases.

****Link****: API publique, lobbies, chat, room passthrough, release-latest.

****Nexus****: identite, users, configs, audit, scheduler et source de confiance.

****Ops commit****: entree atomique d'audit pour une action.

****Pulse****: assistant/config helper.

****Room****: session runtime/live associee a une sync.

****Sekaiemu****: emulator renderer/runtime visuel.

****Service****: role support/moderation puissant, avec approvals pour actions dangereuses.

****SKLMI****: companion tracker/runtime qui possede la logique tracker.

****Worlds****: generation service.