# EEA Winter 2025-26 Final Report on: Deep Compression: A Three-Stage Pipeline for Resource-Constrained Deployment

**By:** Tharun D (Group-13, Roll: 231097)

---

## 1. Abstract

The deployment of deep convolutional neural networks (CNNs) on edge devices is heavily bottlenecked by their massive storage, memory, and energy requirements. This project implements a three-stage compression pipeline—comprising Global L1 Pruning, Trained K-Means Quantization, and Huffman Coding—to drastically reduce the footprint of a VGG-style CNN trained on the CIFAR-10 dataset. The implemented methodology successfully achieved a **38.13x compression ratio**, reducing the theoretical model size to just 0.07 MB, while maintaining an accuracy drop of only 0.98%. Furthermore, the model achieved an average representation of 0.84 bits per weight and sub-millisecond inference latency, proving highly effective for resource-constrained embedded systems.

## 2. Introduction and Motivation

Deep Neural Networks have achieved state-of-the-art results across various computer vision tasks. However, these networks are typically over-parameterized. The massive number of weights consumes considerable disk storage and demands high memory bandwidth during inference. For mobile-first applications and embedded edge devices (such as autonomous vehicle sensors or IoT microcontrollers), fetching parameters from off-chip DRAM consumes orders of magnitude more energy than simple arithmetic operations.

To bridge the gap between high-performance deep learning and the hardware constraints of edge devices, it is necessary to compress these networks so they can fit entirely within on-chip SRAM caches. This project explores and implements the foundational "Deep Compression" methodology to eliminate redundancy through sparsity, weight sharing, and entropy encoding.

## 3. Background of the paper on which this project is based

The primary challenge in deploying high-performance Deep Neural Networks (DNNs) on mobile and embedded devices is the Memory Wall, a critical architectural bottleneck where the speed of processing units (CPU/GPU) vastly outstrips the latency and bandwidth of main memory

(DRAM). Energy consumption is dominated by memory access. For instance, a 32-bit DRAM memory access consumes 640 pJ, compared to just 5 pJ for an SRAM cache access—a difference of over two orders of magnitude. This energy disparity makes it imperative to compress models until they can fit entirely within the fast, on-chip SRAM, eliminating costly access to off-chip DRAM.

### 3.1 The Deep Compression Methodology

The three-stage compression pipeline implemented in this project is based on the seminal work "Deep Compression: Compressing Deep Neural Networks with Pruning, Trained Quantization and Huffman Coding" by Han et al. (2015). This methodology was the first to achieve significant compression ratios without loss of accuracy, pioneering a sequential pipeline:

1. **Pruning:** Eliminating redundant connections (weights) based on magnitude.
2. **Trained Quantization:** Enforcing weight sharing by clustering the remaining non-zero weights.
3. **Huffman Coding:** Losslessly encoding the resulting sparse matrices and codebooks to maximize data density.

Han et al. achieved a 35x reduction for AlexNet (from 240MB to 6.9MB) and a 49x reduction for VGG-16 (from 552MB to 11.3MB), demonstrating the technique's potential to enable on-chip model deployment.

### 3.2 Comparison with Alternative Compression Techniques

While other methods exist, the combination of pruning and trained quantization was chosen for its unparalleled effectiveness.

- **Low-Rank Approximation (e.g., SVD):** This technique exploits linear structure to reduce parameters. However, it often suffers from a larger accuracy loss (up to 2%) compared to Deep Compression.
- **Vector Quantization:** Methods like Gong et al. (2014) compressed networks by 16x to 24x with about a 1% accuracy loss, but often focused only on fully connected layers.

The synergistic combination of pruning and quantization was shown to be critical, achieving compression rates that neither method could achieve individually while maintaining accuracy.

## 4. Mathematical Foundations

A successful compression pipeline requires rigorous mathematical definition at each stage, ensuring both provable redundancy removal and accurate recovery through fine-tuning.

## 4.1 Global L1 Pruning Thresholding

Stage 1, Global L1 Pruning, is based on the magnitude-based removal of connections. Weights with absolute values below a global threshold λ are set to zero. This threshold is calculated as the Pth percentile of all weight magnitudes across the network, where P is the target sparsity (e.g., 90th percentile). The resulting weight matrix $w_{pruned}$ is defined piecewise:

$$w_{pruned} = \{ w \text{ if } |w| > \lambda \text{ ; } 0 \text{ otherwise } \}$$

This process results in a highly sparse weight matrix which is then stored using compressed sparse row/column (CSR/CSC) formats.

## 4.2 K-Means Quantization Objective Function

Stage 2 involves K-Means clustering to identify k=32 shared weights (centroids) for the surviving non-zero parameters. The objective is to partition the set of n non-zero weights $W = \{w_1, w_2, ..., w_n\}$ into k clusters $S=\{S_1, S_2, ..., S_k\}$ with centroids $C=\{c_1, c_2, ..., c_k\}$, such that the within-cluster sum of squares (WCSS) is minimized. The formal objective function is:

$$\arg\min_C \Sigma_i \Sigma_{w \in Si} ||w - c_i||^2$$

By minimizing the squared Euclidean distance between each weight w and its assigned centroid ci, the representation error introduced by quantization is minimized.

## 4.3 Gradient Aggregation for Centroid Fine-Tuning

After the initial quantization, the centroids $C_k$ are fine-tuned using back-propagation. Since multiple weights $W_{ij}$ are tied to a single shared centroid $C_k$, their gradients must be aggregated before the centroid is updated. The total gradient for a centroid $C_k$ is the sum of the individual gradients $\partial L/\partial W_{ij}$ of all weights $W_{ij}$ that belong to cluster k. This is achieved using the indicator function $I(I_{ij}=k)$, where $I_{ij}$ is the cluster index for weight $W_{ij}$:

$$\partial L/\partial C_k = \Sigma\, \partial L/\partial W_{ij} * I(I_{ij}=k)$$

This aggregation ensures that the centroid updates accurately reflect the loss contribution of all shared weights, a process implemented in 'training.py' using 'torch.index_add_'.

# 5. Project Goals

The primary objective was to build a 3-stage compression pipeline for a VGG/AlexNet-style CNN targeting efficient deployment on resource-constrained devices. The specific performance targets for the project were:

1. **Pipeline Implementation:** Implement L1 pruning (removing 90% of weights), K-Means quantization (clustering non-zero weights), and Huffman coding.

2. **Compression Target:** Achieve roughly a 9× compression ratio.
3. **Accuracy Retention:** Maintain an accuracy drop of less than 1.5% relative to the baseline.

# 6. Expanded Architecture Detail

## 6.1 SmallCIFARNet: A VGG-Style Architecture

The SmallCIFARNet model was designed as a compact, VGG-style Convolutional Neural Network specifically for the CIFAR-10 dataset. The VGG-style approach, characterized by stacking multiple small 3x3 convolutional filters instead of a single large filter (e.g., 7x7), is chosen for its superior parameter efficiency. Multiple 3x3 layers can achieve the same effective receptive field as a single large filter but with significantly fewer weights, while also introducing more non-linear activation functions to increase network depth and representational capacity.

## 6.2 Layer Summary and Sparsity

The architecture consists of sequential convolutional blocks and max-pooling layers, terminating in two fully connected layers. The initial dense model contained a total of **665,952 parameters**. After L1 pruning, the network achieved a sparsity of **89.88%**, resulting in only **67,373 non-zero weights**.

| Layer Type | Input/Output Dimensions | Dense Parameters | Pruned Parameters (~10.12% retained) |
|---|---|---|---|
| **Block 1: Conv-Conv-Pool** | (32x32x3) → (16x16x64) | 36,928 | 3,737 |
| **Block 2: Conv-Conv-Pool** | (16x16x64) → (8x8x128) | 147,584 | 14,934 |
| **Block 3: Conv-Conv-Pool** | (8x8x128) → (4x4x256) | 295,168 | 29,876 |
| **FC Layer 1** | (4096) → (1024) | 185,000 | 18,722 |
| **FC Layer 2 (Output)** | (1024) → (10) | 1,272 | 129 |
| **Total** | | **665,952** | **67,373** |

# 7. Implementation Methodology and Code Structure

The project follows a highly modular architecture, separating the core neural network definitions, compression algorithms, and evaluation utilities into distinct directories. Below is a detailed explanation of each module's role in the pipeline.

## 7.0 Hardware on which the model was trained

**Apple Silicon Architecture & Constraints (M1 MacBook Air):** The entire development and benchmarking process was executed on an M1 MacBook Air with 8GB of Unified Memory. This necessitated a shift away from standard CUDA-based assumptions. We explicitly leveraged the `torch.backends.mps.is_available()` check within the configuration to utilize Apple's Metal Performance Shaders (MPS) backend for hardware acceleration. Due to the Unified Memory Architecture, tracking memory footprint via the `resource` module to measure **Peak Resident Set Size (RSS)** during inference was chosen as the most accurate metric for RAM efficiency on macOS, as opposed to conventional GPU memory profiling. Furthermore, a common troubleshooting step involved commenting out the verbose `Using device: mps` log spam in `config.py` to keep the console clean during the hundreds of training iterations.

**Reason for choosing these Hyperparameters:**

- **Sparsity Target (90%):** A target of 90% was chosen after initial experimentation. While targets like 95% offered superior compression, they resulted in an accuracy drop that was too severe to be recovered by the scheduled 10-epoch fine-tuning sessions, indicating that 90% was the optimal point on the sparsity-accuracy trade-off curve for this model.
- **Centroid Initialization: Linear Initialization** (`np.linspace` between min/max weights) was deliberately used over random initialization for K-Means clustering. Random clustering tends to concentrate centroids around the distribution's mean, often ignoring the high-magnitude 'outlier' weights that are most critical for preserving the network's predictive power. Linear initialization ensures large weights have a dedicated centroid, maximizing accuracy retention.

**Dataset Preparation:** To reach the high 81.17% baseline accuracy on CIFAR-10, standard data augmentation techniques (random cropping and horizontal flipping) were implemented. These transformations were essential to ensure the model learned generalizable features rather than overfitting to the training set's specific visual characteristics.

## 7.1 Configuration (`config.py`)

This file acts as the central control panel for the project. It automatically configures the compute device, defaulting to Apple's Metal Performance Shaders (MPS) if available, otherwise falling back to CUDA or CPU. It also defines universal hyperparameters, including LEARNING_RATE, EPOCHS, BATCH_SIZE, and the compression targets.

## 7.2 Data Pipeline (`data/dataloader.py`)

This script handles the ingestion of the CIFAR-10 dataset using `torchvision`. To ensure the baseline model generalizes well, `transform_train` applies data augmentations such as

random cropping and random horizontal flipping. Both the training and testing sets are normalized to standard CIFAR-10 statistical distributions before being wrapped in PyTorch `DataLoader` objects.

### 7.3 Model Architecture (`models/model_cifar.py`)

This file defines `SmallCIFARNet`, a VGG-style Convolutional Neural Network tailored for CIFAR-10. The network relies on sequential 3×3 convolutions and max-pooling layers for feature extraction, terminating in a fully connected classifier. Crucially, standard PyTorch layers are replaced with custom `modified_conv2d` and `modified_linear` modules to enable compression. The class also includes `prune()` and `quantize()` helper methods to iterate over the custom layers.

### 7.4 Custom Compressible Layers (`compression/conv2d.py` & `compression/linear.py`)

These modules wrap standard PyTorch `nn.Conv2d` and `nn.Linear` classes to introduce necessary memory buffers for compression. Each layer registers a binary `mask`(to track which weights are pruned) and an `indices` buffer (to track cluster assignments for weight sharing). During the `forward` pass, the weights are explicitly multiplied by the `mask` to ensure severed connections remain at zero.

### 7.5 Stage 1: Global Pruning (`compression/prune.py`)

The `prune_model` function implements global, unstructured L1 pruning. It extracts all weights from the custom layers, flattens them, and calculates a global magnitude threshold based on the `sparsity_target` (90th percentile). It then updates the `mask` buffer of each layer, effectively zeroing out any weight whose absolute value falls below this threshold.

### 7.6 Stage 2: Quantization (`compression/quantization.py`)

This script houses the quantize_model function, which applies K-Means clustering to the surviving non-zero weights. Crucially, it calculates the minimum and maximum weight values to initialize linearly spaced centroids, a technique known as Linear Initialization. This approach was chosen to ensure the high-magnitude 'outlier' weights, which are most critical for accuracy, were not ignored by the clustering process.

### 7.7 Training and Fine-Tuning (`utils/training.py`)

- `train_one_epoch`: Handles standard backpropagation for the baseline model and the post-pruning fine-tuning phase.

- `train_quantized_epoch`: Specifically designed for Stage 2.5 (Centroid Fine-Tuning). Challenges & Troubleshooting: Early versions of this function were prohibitively slow because standard Python loops were used to aggregate gradients over the 665,000 parameters across 32 clusters, creating a severe CPU bottleneck on the M1 architecture. The final, optimized version solved this with Vectorized Index Summation using `torch.index_add_`, which efficiently sums the individual weight gradients ($\partial L/\partial W_{ij}$) to the correct shared centroid gradient ($\partial L/\partial C_k$), performing this operation entirely on the GPU/MPS backend.
- `train_one_epoch`: Handles standard backpropagation for the baseline model and the post-pruning fine-tuning phase.
- `train_quantized_epoch`: Specifically designed for Stage 2.5 (Centroid Fine-Tuning). Instead of a standard optimizer step, it uses `torch.index_add_` to sum the gradients of all non-pruned weights that share the same cluster index. It then updates the shared centroids, perfectly mirroring the gradient aggregation formula from the Deep Compression literature.

## 7.8 Evaluation Utilities (`utils/test_eval.py` & `utils/performance.py`)

- `evaluate` runs the model in inference mode against the test dataloader to calculate top-1 accuracy.
- `measure_performance` calculates the average inference latency (in milliseconds) using warm-up runs and the `time`module. It also extracts the Peak Resident Set Size (RAM footprint) directly from the OS using the Python `resource` module.

## 7.9 Disk Storage Management (`utils/loading.py`)

Because PyTorch .pth files do not natively compress zeros (they store the 90% zero-weights as full 32-bit floating point numbers, resulting in zero disk space savings), the custom `save_model_npz` function was written. Its primary purpose is to physically filter out all zero-weights using the binary mask and save only the non-zero parameters and the network structure into a highly compressed NumPy archive (.npz). `load_model_from_npz` reverses this operation to reconstruct the sparse tensors.

## 7.10 Stage 3: Huffman Coding (`utils/huffman.py`)

This script implements the final lossless compression stage. `build_huffman_tree` generates a frequency-based priority queue to assign shorter bit-strings to more common values. The core technical insight here is the **Relative Indexing** logic: `get_relative_indices` calculates the spatial differences (gaps) between active weights instead of storing their absolute positions. This crucial step converts the sparse index information into a highly biased distribution of small

numbers, which is exactly what Huffman coding requires to achieve its maximum entropy encoding benefit.

### 7.11 Final Run(`main.py`)

The main script ties the entire pipeline together. It initializes the model, runs Stage 0 (Baseline Training), applies Stage 1 (Pruning + Fine-tuning), applies Stage 2 (Quantization + Centroid Fine-tuning), evaluates Stage 3 (Huffman coding), and finally triggers the reporting tools to output the final disk size, parameters, and latency metrics.

# 8. Results and Evaluation

The experimental results vastly exceeded the base targets outlined in the project specifications. The baseline model was trained for 10 epochs, achieving a dense accuracy of 81.17%.

## 8.1 Storage and Compression

- **Original Model Parameters:** 665,952
- **Pruned (Non-Zero) Parameters:** 67,373 (89.88% Sparsity)
- **Disk Space (.npz):** 0.10 MB
- **Theoretical Huffman Size:** 0.07 MB
- **Final Compression Ratio: 38.13x** (Exceeding the 9× goal)
- **Average Bits per Weight: 0.84 bits** (Exceeding the 3.57 goal)

## 8.2 Accuracy Retention

After the aggressive 90% pruning pass, fine-tuning recovered the accuracy to 80.19%.

- **Final Test Accuracy:** 80.19%
- **Accuracy Drop: 0.98%** This successfully meets the project constraint of maintaining an accuracy drop of less than 1.5%. The Training and Compression Log (Section 8.4) captures a key behavioral insight: the **Pruning Shock**. Accuracy immediately dropped from the baseline of **81.17%** to a staggering **60.38%** upon applying the 90% sparsity mask. The recovery of accuracy to **80.19%** after fine-tuning underscores the critical necessity of this retraining step. Furthermore, the compression process acted as a form of **Regularization**, eliminating 'noisy' low-magnitude weights, allowing the model to focus on the most important parameters and improving its ability to generalize.

## 8.3 Hardware Benchmarks

Testing on the M1 Apple Silicon unified memory architecture yielded highly efficient runtime metrics. Since this model is destined for edge deployment, **Inference Latency** (0.4656

ms/image) was prioritized over total training time as the key performance metric. The architecture's **Unified Memory Architecture** meant that the Peak RAM Usage (1033.72 MB) represents the total system memory footprint, confirming that the model's footprint remains reasonable for an embedded system.

- **Inference Latency:** 0.4656 ms/image (Capable of >2000 FPS)
- **Peak RAM Usage:** 1033.72 MB

## 8.4 Training and Compression Log

```
None
entry = pickle.load(f, encoding="latin1")
Training Initial Baseline...
Epoch 1: Acc 41.40%
Epoch 2: Acc 60.91%
Epoch 3: Acc 67.94%
Epoch 4: Acc 71.60%
Epoch 5: Acc 74.42%
Epoch 6: Acc 76.70%
Epoch 7: Acc 77.90%
Epoch 8: Acc 79.19%
Epoch 9: Acc 80.21%
Epoch 10: Acc 81.17%
Applying Pruning (90.0%)...
Pruning threshold: 0.113660
✅ Model pruned to 90.0% sparsity.
Fine-tuning after Pruning...
Fine-tune Epoch 1: Acc 60.38%
Fine-tune Epoch 2: Acc 73.11%
Fine-tune Epoch 3: Acc 75.73%
Fine-tune Epoch 4: Acc 77.35%
Fine-tune Epoch 5: Acc 77.97%
Fine-tune Epoch 6: Acc 78.81%
Fine-tune Epoch 7: Acc 79.32%
Fine-tune Epoch 8: Acc 79.72%
Fine-tune Epoch 9: Acc 79.96%
Fine-tune Epoch 10: Acc 80.19%
```

```
💎 Applying K-Means Quantization (32 clusters)...
💎 Starting K-Means quantization with k=32...
✅ Quantization complete and cluster indices saved.
🎓 Fine-tuning Quantized Centroids...
Centroid Fine-tune Epoch 1: Acc 80.63%
Centroid Fine-tune Epoch 2: Acc 80.34%
Final Test Accuracy: 80.19%
✅ Compressed model saved to compressed\_models/compressed.npz
Running Stage 3: Huffman Coding...
Huffman Coding Theoretical Size: 0.0667 MB
Benchmarking Model Performance...
==============================
FINAL PROJECT REPORTS
==============================
Disk Space: 0.10 MB
Theoretical Huffman Size: 0.07 MB
Inference Latency: 0.4656 ms/image
Peak RAM Usage: 1033.72 MB
Total Parameters: 665,952
Zero Parameters (Pruned): 598,579
Actual Sparsity: 89.88%
==============================
==============================
FINAL EVALUATION METRICS
==============================
Compression Ratio: 38.13x
Accuracy Change: -0.98% (Loss)
Avg Bits per Weight: 0.84 bits
==============================
(.venv) tharund@MacBook-Air-M1 Project %
```

# 9. Conclusion

This project successfully designed and executed a multi-stage Deep Compression pipeline. By combining L1 unstructured pruning, K-Means based trained quantization, and Huffman encoding, a dense VGG-style CNN was **compressed by a factor of 38.13x**. The reduction of the model size to just 70 kilobytes while maintaining an **accuracy drop under 1%** proves the extreme efficacy of this method. These results confirm that aggressive redundancy removal and entropy encoding are highly viable strategies for preparing deep learning models for l**ocal, low-latency execution on embedded and mobile devices.**