

Object-Oriented Programming (CS F213)

Module III: Inheritance and Polymorphism in Java CS F213 RL 11.1: Java Type System

BITS Pilani

Dr. Pankaj Vyas Department of Computer Science, BITS-Pilani, Pilani Campus



CS F213 RL 11.1 : Topics

Java Type System

Java Type System

• What is type in Java?

Set of Values with a set of Operations that can be applied to the values.

☐ Java is Strongly Typed Language.

Type checking is done both at Compile and Run Time.

- If a Type Check Fails at Compile Time → Compile Time Error
- If a Type Check Fails at Run Time → RunTime Exception



Various Types in Java

- 1. Primitive Type (int, float, double, byte, char, boolean, short, long)
- 2. A class Type [BOX, String, Arrays , Student etc]
- 3. An interface Type [Either User Defined OR Libarary interfaces such as Comparable]
- 4. An array type
- 5. null type

Note:

- 1. Arrays have a component type (Type of array elements) e.g

 String[] array has component type as String int[] array has

 Component type as int
- 2. void is not a type in java. [only a keyword to denote that a method does not return anything]
- 3. Object[] names = new String[10]; What's Array Type and its component type.

Various Types of Values in Java



- 1. A Value of Primitive type
- 2. A reference to an object
- 3. reference to an array
- 4. Null


```
Examples :
```

```
10 , 10.35 , true [Primitive Type Values]
  new BOX(10,6,8); [ Class Type Value]
  new int[] { 10,6,8}[Array Type value]
      null [null Type Value]
Note : You can not have a value of type interface.
```



What are Sub-Types in Java?

Sub type specifies the inheritance relationship either by extending a class or implementing an interface



Similarly X is super type for Y and Y is sub type for X.

You can substitute a value of subtype whenever supertype value is expected



Java Type System: Example

What's Expected

X x1 = new

x1 is reference variable of type X and 'X' is not primitive type?

If X is an interface Then

RHS can be an instance of any class implementing the interface X.

If X is an abstract class Then

RHS can be an instance of any concrete (complete) subclass of X

If X is a concrete (complete) class Then


RHS can be either an instance of X or any of its concrete subclass

S is a subtype of T if

- 1. S and T are the same type
- 2. S and T are both class types, and T is a direct or indirect superclass of S
- 3.S is a class type, T is an interface type, and S or one of its superclasses implements T
- 4. S and T are both interface types, and T is a direct or indirect superinterface of S
- 5. S and T are both array types, and the component type of S is a subtype of the component type of T
- 6. S is not a primitive type and T is the type Object
- 7. S is an array type and T is Cloneable or Serializable
- 8. S is the null type and T is not a primitive type

innovate achieve lead

Sub-Types : Examples





Sub-Types: Examples ...

9. Is int[] is a subtype of Object[]? NO

10. Is int[] is a subtype of Object?

1. Is Container is a subtype of Component?. TRUE
2. Is JButton is a subtype of Component? TRUE
3. Is FlowLayout is a subtype of LayoutManager? TRUE
4. Is ListIterator is a subtype of Iterator? TRUE
5. Is Rectangle[] is a subtype of Shape[]? TRUE
6. Is int[] is a subtype of Object? TRUE
7. Is int is subtype of long? NO
8. Is long is a subtype of int? NO

Primitive Types are not implemented as Objects

YES

ArrayStoreException


•Rectangle[] is a subtype of Shape[]?. TRUE

- Can assign Rectangle[] value to Shape[] variable:
- Rectangle[] r = new Rectangle[10];
 Shape[] s = r;
- Both r and s are references to the same array
- The assignment
 s[0] = new Polygon(); compiles
 But Throws an ArrayStoreException at runtime
- Each array remembers its component type



ArrayStoreException ...

Array References



Thank You