

C Program Structure

Programming in C

Shirley B. Chu

`shirley.chu@delasalle.ph`

College of Computer Studies
De La Salle University

November 4, 2021

Writing C programs

What you need...

- editor such as Notepad++, or

Writing C programs

What you need...

- editor such as Notepad++, or
- compiler

Writing C programs

What you need...

- editor such as Notepad++, or
- compiler
- IDE (Integrated development environment); and

Writing C programs

What you need...

- editor such as Notepad++, or
- compiler
- IDE (Integrated development environment); and

Saving your source code...

Writing C programs

What you need...

- editor such as Notepad++, or
- compiler
- IDE (Integrated development environment); and

Saving your source code...

- file name without space/s

Writing C programs

What you need...

- editor such as Notepad++, or
- compiler
- IDE (Integrated development environment); and

Saving your source code...

- file name without space/s
- file extension: **.c**

Semicolon ;

- ; is used to mark the end of a statement, and the beginning of another statement.

Semicolon ;

- ; is used to mark the end of a statement, and the beginning of another statement.
- All C statements must end with a semi-colon.

Sample C Program

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- enclosed in `/*` and `*/`

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- enclosed in `/*` and `*/`
- starts with `//`

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- enclosed in `/*` and `*/`
- starts with `//`
- can be placed anywhere in the program

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- enclosed in `/*` and `*/`
- starts with `//`
- can be placed anywhere in the program
- are treated as white spaces by the compiler

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- enclosed in `/*` and `*/`
- starts with `//`
- can be placed anywhere in the program
- are treated as white spaces by the compiler
- used to put notes


```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- enclosed in `/*` and `*/`
- starts with `//`
- can be placed anywhere in the program
- are treated as white spaces by the compiler
- used to put notes
- used to temporarily remove a statement or groups of statements

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- enclosed in `/*` and `*/`
- starts with `//`
- can be placed anywhere in the program
- are treated as white spaces by the compiler
- used to put notes
- used to temporarily remove a statement or groups of statements
- **Introductory comment** : usually contains the name of the author/s, date, assumptions, and description of the program

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- Syntax:

`#include<header_file>`

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- Syntax:
 #include<header_file>
- #include

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- Syntax:
 #include<header_file>
- #include
 - a preprocessor directive;

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- Syntax:
 #include<header_file>
- #include
 - a preprocessor directive;
 - compiler inserts the contents of the indicated file

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- Syntax:
 #include<header_file>
- #include
 - a preprocessor directive;
 - compiler inserts the contents of the indicated file
- *header_file*

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- Syntax:
 #include<header_file>
- #include
 - a preprocessor directive;
 - compiler inserts the contents of the indicated file
- header_file
 - file extension: .h


```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- Syntax:
`#include<header_file>`
- `#include`
 - a preprocessor directive;
 - compiler inserts the contents of the indicated file
- `header_file`
 - file extension: `.h`
 - contains definitions that are required to run the program

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- Syntax:
`#include<header_file>`
- `#include`
 - a preprocessor directive;
 - compiler inserts the contents of the indicated file
- `header_file`
 - file extension: **.h**
 - contains definitions that are required to run the program
- All necessary header files must be explicitly included.

```
/* This is a sample program. */
```

```
#include<stdio.h>
```

```
#define MSG "Hi There"
```

```
#define SIZE 50
```

```
void displayMessage ()
```

```
{  
    printf (MSG);    /*displays Hi*/  
}
```

```
int main ()
```

```
{  
    int nVal = 5;  
    displayMessage ();  
    printf ("Number is %d\n", nVal);  
    return 0;  
}
```

- allows constant values to be declared and used throughout the code

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- allows constant values to be declared and used throughout the code
- value cannot be changed by the code in the program

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- allows constant values to be declared and used throughout the code
- value cannot be changed by the code in the program
- convention: identifiers are in all uppercase letters and may have underscores

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- subroutines created by the programmer

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- subroutines created by the programmer
- performs a specific task

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- entry point of a C program


```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}
```

- entry point of a C program
- may contain:

```
int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}
```

```
int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- entry point of a C program
- may contain:
 - variable declarations;

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- entry point of a C program
- may contain:
 - variable declarations;
 - statements;

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- entry point of a C program
- may contain:
 - variable declarations;
 - statements;
 - function calls

```
/* This is a sample program. */

#include<stdio.h>

#define MSG "Hi There"
#define SIZE 50

void displayMessage ()
{
    printf (MSG);    /*displays Hi*/
}

int main ()
{
    int nVal = 5;
    displayMessage ();
    printf ("Number is %d\n", nVal);
    return 0;
}
```

- entry point of a C program
- may contain:
 - variable declarations;
 - statements;
 - function calls

Compiling and Running a C Program

1. Run Notepad++

Compiling and Running a C Program

1. Run Notepad++
2. Start typing.

Compiling and Running a C Program

1. Run Notepad++
2. Start typing.
3. Save your file as **MyFirstProgram.c**

Compiling and Running a C Program

1. Run Notepad++
2. Start typing.
3. Save your file as **MyFirstProgram.c**
4. Run the Command Prompt.

Compiling and Running a C Program

1. Run Notepad++
2. Start typing.
3. Save your file as **MyFirstProgram.c**
4. Run the Command Prompt.
5. Change directory to where your source code is saved.

Compiling and Running a C Program

1. Run Notepad++
2. Start typing.
3. Save your file as **MyFirstProgram.c**
4. Run the Command Prompt.
5. Change directory to where your source code is saved.
6. To compile your program, type
`gcc -Wall MyFirstProgram.c -o MyFirstProgram`

Compiling and Running a C Program

1. Run Notepad++
2. Start typing.
3. Save your file as **MyFirstProgram.c**
4. Run the Command Prompt.
5. Change directory to where your source code is saved.
6. To compile your program, type
`gcc -Wall MyFirstProgram.c -o MyFirstProgram`
7. If there are errors, go back to your code and fix them.
Compile again.

Compiling and Running a C Program

1. Run Notepad++
2. Start typing.
3. Save your file as **MyFirstProgram.c**
4. Run the Command Prompt.
5. Change directory to where your source code is saved.
6. To compile your program, type
`gcc -Wall MyFirstProgram.c -o MyFirstProgram`
7. If there are errors, go back to your code and fix them.
Compile again.
8. Once compilation is successful, i.e. no errors, run the program:

`MyFirstProgram`

😊 Thank you! 😊