

Tokens

Programming in C

Shirley B. Chu

`shirley.chu@delasalle.ph`

College of Computer Studies
De La Salle University

October 26, 2021

Programming Language

A **programming language** is a formal language that is used to give instructions to a computer in the form of a program or code.

Like any natural language, C has its own set of vocabulary and grammar. The words in C are called **tokens** and the grammar is called **syntax**.

Terms

White spaces refer to blanks (space), tabs, newlines, and comments.

Terms

White spaces refer to blanks (space), tabs, newlines, and comments.

A **token** is a series of contiguous characters that the compiler treats as a unit.

Terms

White spaces refer to blanks (space), tabs, newlines, and comments.

A **token** is a series of contiguous characters that the compiler treats as a unit.

- literals

Terms

White spaces refer to blanks (space), tabs, newlines, and comments.

A **token** is a series of contiguous characters that the compiler treats as a unit.

- literals
- identifiers

Terms

White spaces refer to blanks (space), tabs, newlines, and comments.

A **token** is a series of contiguous characters that the compiler treats as a unit.

- literals
- identifiers
- keywords

Literals

- used to represent fixed values

Literals

- used to represent fixed values
- Classifications:
 - Numeric
 - ▶ whole numbers ([integers](#))
 - ▶ real numbers ([floating-point numbers](#))

Literals

- used to represent fixed values
- Classifications:
 - Numeric
 - ▶ whole numbers ([integers](#))
 - ▶ real numbers ([floating-point numbers](#))
 - Non-numeric
 - ▶ [characters](#)
 - ▶ [strings](#)

Integers

✓ consists of a sequence of digits

Integers

- ✓ consists of a sequence of digits
- ✓ may be signed, i.e. may have $+$ or $-$ preceding the number

Integers

- ✓ consists of a sequence of digits
- ✓ may be signed, i.e. may have $+$ or $-$ preceding the number
- ✓ none of the following

Integers

- ✓ consists of a sequence of digits
- ✓ may be signed, i.e. may have $+$ or $-$ preceding the number
- ✓ none of the following
 - ✗ space/s in between digits or sign

Integers

- ✓ consists of a sequence of digits
- ✓ may be signed, i.e. may have $+$ or $-$ preceding the number
- ✓ none of the following
 - ✗ space/s in between digits or sign
 - ✗ comma

Integers

- ✓ consists of a sequence of digits
- ✓ may be signed, i.e. may have $+$ or $-$ preceding the number
- ✓ none of the following
 - ✗ space/s in between digits or sign
 - ✗ comma
 - ✗ decimal point

Integers

- ✓ consists of a sequence of digits
- ✓ may be signed, i.e. may have $+$ or $-$ preceding the number
- ✓ none of the following
 - ✗ space/s in between digits or sign
 - ✗ comma
 - ✗ decimal point

Note that, in C:

Integers

- ✓ consists of a sequence of digits
- ✓ may be signed, i.e. may have $+$ or $-$ preceding the number
- ✓ none of the following
 - ✗ space/s in between digits or sign
 - ✗ comma
 - ✗ decimal point

Note that, in C:

- a series of digits that starts with a zero 0 is considered *octal*.

Integers

- ✓ consists of a sequence of digits
- ✓ may be signed, i.e. may have $+$ or $-$ preceding the number
- ✓ none of the following
 - ✗ space/s in between digits or sign
 - ✗ comma
 - ✗ decimal point

Note that, in C:

- a series of digits that starts with a zero 0 is considered *octal*.
- a series of digits preceded by $0x$ or $0X$ is considered *hexadecimal*.

Floating-point Numbers

- consists of an integer part, a decimal point, and a fraction part.

3.5, -27.5, 4.0

Floating-point Numbers

- consists of an integer part, a decimal point, and a fraction part.
3.5, -27.5, 4.0
- may be expressed using the scientific notation.
2.25e4 to mean 2.25×10^4 , equivalent to 22500.0
2E-4 to mean 2×10^{-4} , equivalent to 0.0002

Character Literals

- consist of a single character enclosed in single quotation marks.

'x', 'a', '9'

¹<http://www.asciitable.com/>

Character Literals

- consist of a single character enclosed in single quotation marks.

'x', 'a', '9'

- has an equivalent numeric value (a.k.a. *ASCII value*¹)
ASCII value of 'A' is 65, 'B' is 66, ... and 'a' is 97, 'b' is 98,

¹<http://www.asciitable.com/>

Character Literals

- consist of a single character enclosed in single quotation marks.

`'x', 'a', '9'`

- has an equivalent numeric value (a.k.a. *ASCII value*¹)
ASCII value of 'A' is 65, 'B' is 66, ... and 'a' is 97, 'b' is 98,
- may be a special character (a.k.a. *escape sequence*)

¹<http://www.asciitable.com/>

Character Literals

- consist of a single character enclosed in single quotation marks.

'x', 'a', '9'

- has an equivalent numeric value (a.k.a. *ASCII value*¹)
ASCII value of 'A' is 65, 'B' is 66, ... and 'a' is 97, 'b' is 98,
- may be a special character (a.k.a. *escape sequence*)
 - enclosed in single quotation marks

¹<http://www.asciitable.com/>

Character Literals

- consist of a single character enclosed in single quotation marks.

`'x', 'a', '9'`

- has an equivalent numeric value (a.k.a. *ASCII value*¹)
ASCII value of 'A' is 65, 'B' is 66, ... and 'a' is 97, 'b' is 98,
- may be a special character (a.k.a. *escape sequence*)
 - enclosed in single quotation marks
 - preceded by a backslash \

Special Character	Meaning
<code>'\n'</code>	newline
<code>'\t'</code>	tab
<code>'\b'</code>	backspace
<code>'\''</code>	single quote

¹<http://www.asciitable.com/>

String Literals

- consists of zero or more characters enclosed in double quotation marks.

`"hello there!"`

String Literals

- consists of zero or more characters enclosed in double quotation marks.

`"hello there!"`

- Escape sequences within a string must be preceded by a backslash.

`"Good morning!\n"`

String Literals

- consists of zero or more characters enclosed in double quotation marks.

`"hello there!"`

- Escape sequences within a string must be preceded by a backslash.

`"Good morning!\n"`

- double quotation mark within a string literal must be preceded by a backslash

`"She said, \" hello there!\""`

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**
nice

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**
nice ✓

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**
nice ✓
idno.

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



idno.



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit

idno.



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



3rdno

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



3rdno



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit

3rdno



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_



- cannot be one of the reserved words

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_



- cannot be one of the reserved words

case

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice

✓

first_digit

✓

idno.

✗

email addr

✗

- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4

✓

_1stdigit

✓

3rdno

✗

a_

✓

- cannot be one of the reserved words

case

✗

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_



- cannot be one of the reserved words

case



Case

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_



- cannot be one of the reserved words

case



Case



Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_



- cannot be one of the reserved words

case



Case



- cannot be a defined identifier in the C standard library

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_



- cannot be one of the reserved words

case



Case



- cannot be a defined identifier in the C standard library

printf

Identifiers

Identifiers are used to give names to memory locations (data), and subroutines.

Rules on naming identifiers:

- consists of letters **A–Z**, **a–z**, digits **0–9**, or underscores **_**

nice



first_digit



idno.



email addr



- is case-sensitive

idno and **Idno** are different identifiers.

- cannot begin with a digit

friend4



_1stdigit



3rdno



a_



- cannot be one of the reserved words

case



Case



- cannot be a defined identifier in the C standard library

printf



Identifiers

- Variables

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.
 - Its value **may change** at any point within the duration of the program.

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.
 - Its value **may change** at any point within the duration of the program.
- Constants

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.
 - Its value **may change** at any point within the duration of the program.
- Constants
 - Constant can hold a value.

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.
 - Its value **may change** at any point within the duration of the program.
- Constants
 - Constant can hold a value.
 - Its value is **fixed** throughout the duration of the program

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.
 - Its value **may change** at any point within the duration of the program.
- Constants
 - Constant can hold a value.
 - Its value is **fixed** throughout the duration of the program
- Keywords²

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.
 - Its value **may change** at any point within the duration of the program.
- Constants
 - Constant can hold a value.
 - Its value is **fixed** throughout the duration of the program
- Keywords²
 - Keywords are reserved words of the programming language

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.
 - Its value **may change** at any point within the duration of the program.
- Constants
 - Constant can hold a value.
 - Its value is **fixed** throughout the duration of the program
- Keywords²
 - Keywords are reserved words of the programming language
 - These words have special meanings, and are used by the language for processing.

²<https://en.cppreference.com/w/c/keyword>

Identifiers

- Variables
 - Variable can hold a value.
 - Its value **may change** at any point within the duration of the program.
- Constants
 - Constant can hold a value.
 - Its value is **fixed** throughout the duration of the program
- Keywords²
 - Keywords are reserved words of the programming language
 - These words have special meanings, and are used by the language for processing.
 - These words **cannot** be redefined by the programmer.

²<https://en.cppreference.com/w/c/keyword>

😊 Thank you! 😊