**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-MFY-06S INTELLIGENT SEALING INSTRUMENT




## TEST PROJECT

1. Sealability of anti-theft cap (carbonate cap, non-carbonate cap)
2. Disengagement force of end cap of cylindrical composite tank
3. Rapid leakage test of cylindrical composite tank

## STANDARDS

GB 10440, GB 18454, GB 19741, GB 8368, YY/T0681, YY 0285, ASTM F1140, ASTM F2054, ISO 11607-1, ISO 11607-2, GB/T 19633, GB/T 17876, BB/T 0025, QB/T 1871, YBB 00252005-2015, YBB 00162002-2015 and etc.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

## FEATURES

1. It can test the sealing performance of the anti-theft bottle cap and the detachment force of the cylindrical compound tank end cap. By equipping with different auxiliary equipment, it also needs to meet the requirements of the rapid leakage of the compound tank, the sealing of the air mist valve, the sealing of the hose and the air tightness of the steel lifting barrel.
2. Instrument host needs LCD test process curve and test result.
3. Professional computer software operating system, equipped with mini printers to print experimental results quickly.

## TECHNICAL PARAMETERS

| **Item** | **Specification** |
|---|---|
| Measuring Range | 0～1.2MPa; 0～174.24psi (standard) |
| Measuring Accuracy | ±1% |
| Connector of Air Source | Φ8mm polyurethane tube |
| Dimension (L*W*H) | 480*330*150mm |
| Weight | 8kg |
| Working Temp. | 15--50℃ |
| RH | max 80% without condensation |
| Pressure of Air Source | 0.4MPa～1.3MPa (equipped by customers) |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

| **Item** | **Specification** |
|---|---|
| Standard Configuration | Main body<br>Test device of plastic anti-theft bottle cap sealing performance<br>Sealing barrel<br>Micro printer |
| Optional Configuration | Test Accessories:<br>Restraint plate test device<br>Open packaging test device<br>Large leakage test device<br>Test frame<br>Hose sealing performance test device<br>End cap release force device<br>Rapid leakage device |

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-NLY-20U DIGITAL TORQUE TESTER




## TEST PROJECT

Automatic test of opening force and locking force of bottle cap
(belonging to full automatic bottle cap torque meter)

## STANDARDS

GB/T17876, BB/T0025, BB/T0034(GB/T14803), ASTMD2063, ASTMD3198, ASTMD3474, YBBOOl12002-2015, YBB00122002-2015, YBB00262002-2015 and etc.

## FEATURES

1. Double mode design of locking force and opening force, full automatic test of bidirectional torque value of anti-theft bottle cap.
2. The instrument mainframe needs LCD to display the test process curve. The professional computer software supports the display of the test results in various units, the graphical display of the test process, the output and printing functions.
3. Micro printer quickly print test results, including test software.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

## TECHNICAL PARAMETERS

| Item | Specification |
|---|---|
| Stroke Range | 5Nm (10Nm is optional) |
| Measuring Accuracy | level 1 |
| Resolution Ratio | 0.1N.cm |
| Clamp Range | Φ15mm～Φ170mm (It can be customized.) |
| Data Storage | 1-500 group (s) |
| Dimension (L*W*H) | 370*220*125mm |
| Weight | 8.4kg |
| Working Temp. | 15--50℃ |
| RH | max 80% without condensation |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

Main body, micro printer and touch screen.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-YLY-03 POLARIZING STRESS TESTER



## TEST PROJECT

Determination internal stress value for all kinds of glassware,PET preform, glass containers, optical glass

## STANDARDS

YBB00332002-2015, YBB00162003-2015, GB12415, GB4545 and etc.

## FEATURES

1. Qualitative and quantitative two test models for a wide range.
2. Touch screen display optical path difference and the value of real-time stress.
3. User manage rights ensure data integrity and standardization.
4. Equipped with micro-printer, fast printing result of each measurement and statistical maximum, minimum, average.
5. Instrument can store at least 100 sets of data, each data 20 measured values.
6. Adjustable test space for a wide range products.
7. The system program includes ISP online update function, which provides personalized service.
8. High-speed processing chip, running much faster.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

## TECHNICAL PARAMETERS

| Item | Specification |
|---|---|
| Indicating Value | 0.1nm |
| Measuring Accuracy | 2nm |
| Diameter of Polarization Field | 150mm |
| Rotation Angle of Analyzer Plate | 360° |
| Edge Brightness of Light Field | ＞120cd/m² |
| Dimension (L*W*H) | 220*370*480mm |
| Weight | 5kg |
| Working Temp. | 15--50℃ |
| RH | max 80% without condensation |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

Main body, micro printer and touch screen.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-CHY-B1 WALL THICKNESS TESTER




## TEST PROJECT

Thickness of bottle wall and bottom

## STANDARDS

GGB12415-90, GB2641-90, GB2639-90, QB/T 1868, QB/T 2357, QB/T 2665 and etc.

## FEATURES

1. Adopt capacitive grid sensing technology, with digital display function.
2. It can detect two control indexes of bottom thickness and wall thickness of glass bottle, one machine can be used for both purposes.
3. Convenient, practical and cost-effective.
4. The test accuracy is 0.001mm, and the value is accurate and stable.

## TECHNICAL PARAMETERS

| Item | Specification |
|---|---|
| Thickness Range | 0--12.5mm |
| Division Value | 0.001mm |
| Sample Diameter | high pole: 5-230mm (It can be customized.)<br>short pole: 5-25mm (It can be customized.) |
| Sample Height | high pole: 10-320mm (It can be customized.)<br>short pole: 0-100mm (It can be customized.) |
| Dimension (L*W*H) | high pole: 230*180*600mm<br>short pole: 230*180*380mm |
| Weight | high pole: 8kg<br>short pole: 4kg |
| Working Temp. | 15--50℃ |
| RH | max 80% without condensation |
| Power | battery |

## PRODUCT CONFIGURATION

| Item | Specification |
|---|---|
| Standard Configuration | Main body<br>Measuring head |
| Optional Configuration | Testing software<br>Telecommunication cable |

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-DL-1000 BOTTLE DROP TESTER



## TEST PROJECT

Drop performance

## STANDARDS

GB/T 17876, QB 2357, QB/T 1868, QB/T2665 and etc.

## FEATURES

1. Used for drop test of specified height and angle in the standard of no-steam, gas, hot-filled beverage bottle and anti-theft bottle cap. Pneumatic clamping sample, automatic release.
2. With infrared height positioning device to ensure accuracy of test results.
3. The angle of holding is 0-90 degrees adjustable.

## TECHNICAL PARAMETERS

| Item | Specification |
|---|---|
| Drop Height | 1000--2000mm (adjustable) |
| Sample Volume | 0--2.5L |
| Clamp Angle | 0°, 30°, 90° (adjustable) |
| Sample Clamp | pneumatic |
| Rising Method | automatic |
| Dimension (L*W*H) | 800*800mm*2700mm |
| Weight | 195kg |
| Working Temp. | 15--50℃ |
| RH | max 80% without condensation |
| Pressure of Air Source | 0.5-0.7MPa (equipped by customers) |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

Main body, positioning device and controller.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-ZPY-60U ELECTRONIC SHAFT DEVIATION MEASURING INSTRUMENT



## TEST PROJECT

Thickness of bottle wall and bottom

## STANDARDS

YBB60402012-2015, YBB00332002-2015, YBB00192003-2015, GB 8452, GB 8452, GB 2639, QB 2357, QB/T 1868, QB/T2665 and etc.

## FEATURES

1. For verticality deviation test of various round or square plastic bottles, automatic electronic measurement mode. The measuring head automatically rises and falls, adjusts the location of the measuring points, and does not adjust the height manually.
2. The maximum, minimum and deviation values can be automatically counted, and the minimum value of the instrument is not less than 0.001mm.
3. Contains micro printers and testing software to facilitate data analysis and preservation.

## TECHNICAL PARAMETERS

| Item | Specification |
|---|---|
| Sample Diameter | 3--160mm |
| Stroke | 0--12.5mm |
| Division Value | 0.001mm |
| Measuring Height | 5--400mm |
| Rising Method of Measuring Head | electric |
| Dimension (L*W*H) | 436*320*690mm |
| Weight | 40kg |
| Working Temp. | 15--50℃ |
| RH | max 80% without condensation |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

Main body, touch screen, measuring head, micro printer, wrench, testing software and telecommunication cable.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-ZY-500 INTELLIGENT VERTICAL LOAD PRESSURE TESTER



## TEST PROJECT

Thickness of bottle wall and bottom

## STANDARDS

GB/T 17200, QB/T 1868, GB/T10440, QB 2357, QB/T 2665, BB/T 0044, QB/T266 and etc.

## FEATURES

1. For all kinds of plastic bottles vertical load capacity test, microcomputer control, large LCD screen display.
2. Meet double operation mode.
3. Continuously variable speed test to achieve speed test in 1-500mm/min.

## TECHNICAL PARAMETERS

| Item | Specification |
|---|---|
| Load | 500N, 1000N, 1500N (optional) |
| Accuracy | level 1 |
| Testing Speed | 1-300mm/min stepless speed regulation |
| Stroke Accuracy | ±2% |
| Sample Diameter | ≤150 mm |
| Sample Height | ≤600mm |
| Dimension (L*W*H) | 450*300*1350mm |
| Weight | 78kg |
| Working Temp. | 23℃±2℃ |
| RH | max 80% without condensation |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

Main body, pressure clamps, testing software and telecommunication cable.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-WD-120 HAZE TRANSMITTANCE TESTER



## TEST PROJECT

Transmittance & Haze

## STANDARDS

GB 2410-2008, ASTM D1003, JIS K7105-81, QB/T 1868, QB/T 2357, QB/T2665 and etc.

## FEATURES

1. For plastic bottle transmittance test, microcomputer control, LED digital display.
2. Test the transmittance and haze value at one time, convenient and quick.
3. Equipped with professional calibration device, fog, transmittance, automatic switching, measurement and correction.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

## TECHNICAL PARAMETERS

| Item | Specification |
|---|---|
| Measuring Range | transmittance: 0～100.0%<br>haze: 0～30.00% |
| Accuracy | ≤1% |
| Repeatability | 0.5 unit |
| Minimum Reading | 0.01 unit |
| Sample Dimension | ≤150mm |
| Light Source | CIE-A, CIE-C, CIE-D65 |
| Data Storage | 20,000 numerical value |
| Size of Lighting and Sample Aperture | 16.5mm/ 21mm |
| Dimension (L*W*H) | 310*215*540mm |
| Weight | 5kg |
| Working Temp. | 23℃±2℃ |
| RH | max 60% without condensation |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

Main body, pressure clamps, testing software and telecommunication cable.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-CJY-03 GLASS BOTTLE IMPACT RESISTANCE TESTER



## TEST PROJECT

Impact resistance

## FEATURES

1. LCD touch screen, can set the impact energy, impact angle and other indicators.
2. Electronic measurement mode, accuracy is 0.01J.
3. Pendulum pneumatic clamping and release, avoid human error.
4. Adjust the impact position according to the sample size.
5. The system statistical test data automatically.
6. Fast print ,test results permanent preservation.

## TECHNICAL PARAMETERS

| Item | Specification |
|---|---|
| Sample diameter range | ϕ20～165mm |
| Bottle position height | 20～180mm |
| Impact energy | 0～2.5N·m |
| Pendulum clamping way | pneumatic |
| Resolution | 0.01N.m |
| Dimension | 420*330*500mm |
| Weight | 28kg |
| Work Temp. | 15-35℃ |
| RH | max 80% without condensation |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

Main body

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

# HD-RCY-03 GLASS BOTTLE HEATING SHOCK RESISTANCE TESTER











## TEST PROJECT

Heating shock resistance

## STANDARDS

ASTM C149-86, ISO/TC 63, ISO 7459:2004, BS EN 1183:1997, BS EN ISO7459, ISO/IEC 17025:2005 and etc.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

## FEATURES

1. Microcomputer control technology, the experiment process automation degree is high.
2. Color large LCD touch screen display, the test process is clear and easy to operate.
3. Heating tank, cooling tank, sample cage adopt stainless steel material, durable.
4. The instrument can store not less than 500 sets of data, and historical data can be querying.
5. Stainless steel is used for heating tank, refrigeration tank and sample basket.
6. Sample cage uses electric hoist is convenient to use and reduce staff strength.
7. Glass bottle heating shock resistance tester with leakage protection device, safe and reliable performance.
8. Hot and cold water respectively automatic cycle, with double window thermostat, easy to operate.

## TECHNICAL PARAMETERS

| **Item** | **Specification** |
|---|---|
| Difference Measuring Range | 0～60℃ |
| Precision of Temperature Control | 1℃ |
| Capacity | high temperature tank: 31L<br>low temperature tank: 56L |
| Dimension | 880*530*1300mm |
| Weight | 48kg |
| Work Temp. | 5--40℃ |
| RH | max 80% without condensation |
| Power | 220V/ 50Hz |

## PRODUCT CONFIGURATION

Main body, bottle basket, and top & bottom water pipe.

**Haida International Equipment**
No.13 Daxin Street, Daluosha Industrial Zone, Daojiao Town, Dongguan City, Guangdong Province, China
Post Code: 523170

## Company Introduction:

HAIDA INTERNATIONAL is a professional manufacturer of various kinds of testing equipment over 15 years. HAIDA products are widely used in paper products, packaging, ink printing, adhesive tapes, bags, footwear, leather products, environment, toys, baby products, hardware, electronic products, plastic products, rubber products and other industries, and applicable to all scientific research units, quality inspection institutions and academic fields.

## See what company you will work with?

1. **Professional Manufacturer** of various kinds of testing equipment over **15 years**, defect rate is controlled under **0.02%.**
2. **Completely** Production Line. From Raw Material to Delivery, **all links** are under our control. The **quality** can be assured.
3. **ISO 9001:2008** Quality Management System Certificate.
4. **OEM/ODM** Service. Just tell us your idea! Our R&D Team is standing by…
5. Our Marketing Investigation Department will send **Marketing Research Report** to you each season.
6. We are trusted by SCS, INTERTEK, HST, COFCO, ESC, KBMC, LENOVO, PANASONIC, EMC, etc.
7. We accept **100%** inspection.
8. Guarantee Period: **365** days, **After Sales Service** Department provides professional service with you, any questions, just contact us.

## Partner:

