

DDL COMMANDS :

1. TABLE CREATION

```
create database employee;  
use employee;
```

```
create table Departments (department_id int, department_name varchar(100));
```

```
create table Location (location_id int, location varchar(30));
```

```
create table Employees ( employee_id int, employee_name varchar(50), gender enum('m', 'f'), age int,  
hire_date date, designation varchar(100), department_id int, location_id int, salary decimal(10,2));
```

2. TABLE ALTERATION

```
alter table Employees  
add email varchar(100);
```

```
alter table Employees  
modify designation varchar(200);
```

```
alter table Employees  
drop column age;
```

3. TABLE RENAMING

```
alter table Employees  
rename column hire_date to date_of_joining;
```

```
rename table Departments to Departments_info;
```

```
rename table Location to Locations;
```

4. TABLE TRUNCATION

```
truncate table Employees;
```

5. DATABASE & TABLE DROPPING

```
drop table Employees;
```

```
drop database employee;
```

CONSTRAINTS :

1. DATABASE RECREATION:

```
create database employee;  
use employee;
```

2. Departments TABLE:

```
create table departments (department_id int primary key, department_name varchar(100) not null  
unique);
```

3. Location TABLE:

create table location (location_id int auto_increment primary key, location varchar(30) not null unique);

4. Employees TABLE:

create table employees (employee_id int primary key, employee_name varchar(50) not null, gender enum('m', 'f'), age int check (age >= 18), hire_date date default (current_date), designation varchar(100), department_id int, location_id int, salary decimal(10,2), foreign key (department_id) references departments(department_id), foreign key (location_id) references location(location_id));