Taopix Customer Account API v2.0

Compatible with TAOPIX™ Control Centre 2019r2

Author: Taopix Development

Date: 27th August 2019

File: Taopix Customer Account API v2.0.docx

Revision History

27th August 2019	V2	Renamed document from Taopix Address Verification API v1.0 to Taopix Customer Account API v2.0. Added new customerAccountOverride functionality

Contents

Revision History 2
Introduction 4
Installation & Configuration 5
Sample Code 5
Taopix Licensee Software Development / Skills Required 6
Customer Account API 7
verifyAddress 7
autoSuggest 9
configureAddressForm 11
customerAccountOverride 13

Introduction

The Taopix Customer Account API is appropriate for licensees who want to apply custom validation to a customer's address.

The API provides the following functionality:

- Allows the licensee to apply custom validation to an address entered by the user in the Taopix shopping cart.
- Allows the licensee to implement an auto suggest feature within the Taopix internal address forms helping to enforce address validity.
- Allows the licensee to flag specific address fields to be compulsory within the Taopix internal address forms.
- Allows the licensee to apply custom logic to override certain Taopix customer account settings.

In order for a licensee to make use of the Taopix Customer Account API they must be running Taopix version 2019r2 or later.

Installation & Configuration

To make use of the Customer Account API, the provided EDL_TaopixCustomerAccountAPI.php file must be copied into the following location on the Taopix Control Centre server:

MediaAlbumWeb/Customise/scripts

With this in place the Taopix will call the API functions in order to apply custom validation and also retrieve auto suggestions for address fields.

Sample Code

The documentation comes complete with an example script that demonstrates the key concepts of the Customer Account API.

The example EDL_ TaopixCustomerAccountAPI.php file demonstrates the following:

- Address verification for a US based address using address information in the TaxCalculation.tab file.
- Auto suggestions for the state, county and city address fields for a US based address using address information in the TaxCalculation.tab file.
- Customising the compulsory address fields by returning the county as an additional field for a US based address.
- Overriding customer account settings to assign a specific currency to a customer based off their address country code.

To test this example, you need to rename the file from:

EDL_ TaopixCustomerAccountAPIExample.php

To:

EDL_ TaopixCustomerAccountAPI.php

NOTE: This example is should not be used in a production environment as it is for demonstration purposes only.

Upgrading from the AddressVerification API

This section only applies to customers currently using the Taopix Address Verification API

Prior to version 2019r2, this API was named the AddressVerification API. Once upgraded to 2019r2, the Taopix Customer Account API must now be used. In order to upgrade, simply follow these steps:

1. Locate your current EDL_AddressVerification.php in MediaAlbumWeb/Customise/scripts
2. Rename the file to EDL_TaopixCustomerAccountAPI.php
3. Open the file for editing
4. Find the line that reads **class AddressVerificationAPI**
5. Change to **class CustomerAccountAPI**
6. Save and close the file

Taopix Licensee Software Development / Skills Required

1. PHP

The contents of the script will require the logic to be implemented in order to validate a customers address as well logic to implement the auto suggest suggestions returned to the address forms.

2. Additional Knowledge

Some further areas of knowledge that may also be required in order to implement the Customer Account API:

- Taopix Address Formats

Customer Account API

verifyAddress

This API is called in an attempt to verify the address a user has entered. It is used to verify a users address when they first register for an account, change their billing or shipping address within the Taopix shopping cart or when updating their address details from the user account pages. Any invalid address fields returned from this API call will be flagged with a customisable error message in the Taopix address form.

Function Input (Array)

Name	Type	Information
brandcode	varchar(50)	The brand code the end user belongs to.
groupcode	varchar(50)	The license key code the end user belongs to.
groupdata	varchar(50)	Custom meta-data string from either the Taopix Online product URL or from the Taopix Internet License Key Scripting API if implemented.
browserlanguagecode	varchar(10)	The browser language code the user is currently running under.
addresstype	varchar(20)	The address the user is currently updating. I.e. shipping or billing. Note: When a user register for a new account addressType will be set to billing.
address	array	An array containing the address in relation to the address form that is being modified.

Function Output (Array)

Name	Type	Information
invalidaddressfields	array	An associative array indicating which address fields are invalid as well as a description. Example: $resultArray['invalidaddressfields']['city'] = 'Unable to match city'; $resultArray['invalidaddressfields']['postcode'] = 'Unable to match postcode'; If all address fields have passed validation then the invalidaddressfields should be returned as en ampty array: Example: $resultArray['invalidaddressfields'] = array();

autoSuggest

This API is called in an attempt to validate user input on the Taopix address form for a corresponding address field and returns a list of possible matches which a user can choose from.

Function Input (Array)

Name	Type	Information
brandcode	varchar(50)	The brand code the end user belongs to.
groupcode	varchar(50)	The license key code the end user belongs to.
groupdata	varchar(50)	Custom meta-data string from either the Taopix Online product URL or from the Taopix Internet License Key Scripting API if implemented.
browserlanguagecode	varchar(10)	The browser language code the user is currently running under.
addresstype	varchar(20)	The address the user is currently updating. I.e. shipping or billing. Note: When a user register for a new account addressType will be set to billing.
address	array	An array containing the address in relation to the address form that is being modified.
addressfield	varchar(10)	The address field ID the auto suggest is to be performed on. Potential values are: city, county and state.
addressfileduserinput	varchar	User input text for the corresponding address field.
limit	int(11)	The limit of address field suggestions to be returned. Currently the default set by Taopix is 20.

Function Output (Array)

Name	Type	Information
suggestions	array	An array containing suggestions for the corresponding address field. Example: $resultArray['suggestions'][0][‘Newbury’]; $resultArray['suggestions'][1][‘Newcastle’]; $resultArray['suggestions'][2][‘Newquay’];

configureAddressForm

This API is called in an attempt to retrieve additional compulsory address fields for a given country. Taopix already has address formats where, for a certain country some fields are already marked as compulsory. This API allows the licensee to flag extra address fields on the address form as compulsory.

Function Input (Array)

Name	Type	Information
brandcode	varchar(50)	The brand code the end user belongs to.
groupcode	varchar(50)	The license key code the end user belongs to.
groupdata	varchar(50)	Custom meta-data string from either the Taopix Online product URL or from the Taopix Internet License Key Scripting API if implemented.
browserlanguagecode	varchar(10)	The browser language code the user is currently running under.
addresstype	varchar(20)	The address the user is currently updating. I.e. shipping or billing. Note: When a user register for a new account addressType will be set to billing.
countrycode	Varchar(2)	The 2 letter ISO code for the country currently selected on the address form.
addressfields	array	An associatve array of address fields for the given country. For each address field there is also a compulsory flag identify if this field is compulsory. $pParamArray['addressfields']['address1']['compulsory'] = true. This highlights that the address filed 1 is already a compulsory field.

Function Output (Array)

Name	type	Information
addressfields	array	An associatve array of address fields for this country. This could simply be the address fields that were passed into the function so that the current address formats are respected and no additional fields have been flagged. However a modified list of compulsory address fields could be returned that highlighted additional fields as to be flagged as compulsory.

customerAccountOverride

This API allows licensees to override certain Taopix customer account settings based on custom logic. This API is called when a customer registers for an account, updates their account details or when a Taopix admin user creates or updates a Taopix customer account. Below is a list of fields that are passed into the function that can be modified which in turn will be stored against the customer account within the Taopix database.

Common Parameters:

Name	Type	Modify	Information
reason	integer	Y	This indicates the reason why the function was called: 0 – Customer registration 1 – Customer updating their account details from the account details page. 2 – Customer prompted to update their address during an order. 3 – Customer account created via Taopix admin within Control Centre. 4 – Customer account details updated via Taopix admin within Control Centre.
brandcode	varchar(50)	N	The code for the Taopix brand that the customer account is being created for.
groupcode	varchar(50)	N	The code for the Taopix License Key that is assigned to the customer account.
countrycode	varchar(10)	Y	The *iso2* country code that matches a value within the Taopix *COUNTRIES* database table.
contactfirstname	varchar(200)	Y	Contact first name
contactlastname	varchar(200)	Y	Contact last name
companyname	varchar(50)	Y	Company name

address1	varchar(200)	Y	Address line 1
address2	varchar(200)	Y	Address line 2
address3	varchar(200)	Y	Address line 3
address4	varchar(200)	Y	Address line 4
city	varchar(200)	Y	City
state	varchar(200)	Y	State
county	varchar(50)	Y	County
regioncode	varchar(20)	Y	Region code
region	varchar(10)	Y	Region field code
postcode	varchar(200)	Y	Postcode / Zipcode
countryname	varchar(50)	Y	The name of the country that matches the *iso2* country code.
telephonenumber	varchar(50)	Y	Telephone number
emailaddress	varchar(50)	Y	Email address
sendmarketinginfo	integer	Y	The status of the *Can Send Marketing Information* flag: 0 = No, 1 = Yes

registeredtaxnumbertype	integer	Y	The tax number type for the customer. Values greater than 0 are currently only supported for addresses in Brazil. 0 = Not applicable 1 = Personal 2 = Corporate
registeredtaxnumber	varchar(50)	Y	The tax number in the format specified by *registeredtaxnumbertype* when *registeredtaxnumbertype* is not 0.
canmodifyshippingaddress	integer	Y	0 = The shipping address cannot be modified. 1 = The shipping address can be modified. NOTE This option only applies if *defaultaddresscontrol* is 0.
canmodifybillingaddress	integer	Y	0 = The billing address cannot be modified. 1 = The billing address can be modified. NOTE This option only applies if *defaultaddresscontrol* is 0.
canmodifycontactdetails	integer	Y	0 = The shipping address contact details cannot be modified. 1 = The shipping address contact details can be modified. NOTE This option only applies if *defaultaddresscontrol* is 0 and *canmodifyshippingaddress* is 0.
usedefaultcurrency	integer	Y	0 = The customer record will ignore the license key currency setting and instead use the value passed in the currency code parameter. 1 = The customer record will ignore the value passed in the currency code parameter and instead use the currency set against the license key.
currencycode	varchar(50)	Y	A valid Taopix Control Centre currency code if applying a custom currency to the customer account or empty if usedefaultcurrency is set to 1.

Customer Registration Additional Parameters:

Name	Type	Modify	Information
canmodifypassword	integer	Y	0 = The password cannot be modified by the user. 1 = The password can be modified by the user.
defaultaddresscontrol	integer	Y	0 = The address / email settings are customised for this user account. 1 = The address / email settings are controlled by the license key.
useremaildestination	integer	Y	0 = Send confirmation emails to order billing address. 1 = Send confirmation emails to order shipping address. 2 = Send confirmation emails to order shipping address and bcc order billing address. 3 = Send confirmation emails to order billing address and bcc order shipping address. **NOTE** This option only applies if *defaultaddresscontrol* is 0.
usedefaultpaymentmethods	integer	Y	0 = Use custom set of payment methods 1 = Use default payment methods
paymentmethods	varchar(100)	Y	A comma separated list of Taopix payment method codes when using *usedefaultpaymentmethods* is 0.
creditlimit	decimal	Y	The credit limit in the currency specified by Taopix as the system currency.
accountbalance	decimal	Y	The account balance in the currency specified by Taopix as the system currency.
giftcardbalance	decimal	Y	The gift card balance in the currency specified by Taopix as the system currency.
uselicensekeyforshippingaddress	integer	Y	0 = The user account address is used for the shipping address. 1 = The address held in the license key is used for the shipping address. **NOTE** This option only applies if *defaultaddresscontrol* is 0.

uselicensekeyforbillingaddress	integer	Y	0 = The user account address is used for the billing address. 1 = The address held in the license key is used for the billing address. **NOTE** This option only applies if *defaultaddresscontrol* is 0.
taxcode	varchar(20)	Y	A valid Taopix Control Centre tax rate code if applying a custom product tax rate to the customer account or empty if Taopix should determine the product tax rate.
shippingtaxcode	varchar(20)	Y	A valid Taopix Control Centre tax rate code if applying a custom shipping tax rate to the customer account or empty if Taopix should determine the shipping tax rate.
isactive	integer	Y	0 = Account not active 1 = Account active

Customer Registration & Update Details From Taopix Admin Additional Parameters:

Name	Type	Modify	Information
canmodifypassword	integer	Y	0 = The password cannot be modified by the user. 1 = The password can be modified by the user.
defaultaddresscontrol	integer	Y	0 = The address / email settings are customised for this user account. 1 = The address / email settings are controlled by the license key.
useremaildestination	integer	Y	0 = Send confirmation emails to order billing address. 1 = Send confirmation emails to order shipping address. 2 = Send confirmation emails to order shipping address and bcc order billing address. 3 = Send confirmation emails to order billing address and bcc order shipping address. **NOTE** This option only applies if *defaultaddresscontrol* is 0.

usedefaultpaymentmethods	integer	Y	0 = Use custom set of payment methods 1 = Use default payment methods
paymentmethods	varchar(100)	Y	A comma separated list of Taopix payment method codes when using *usedefaultpaymentmethods* is 0.
creditlimit	decimal	Y	The credit limit in the currency specified by Taopix as the system currency.
accountbalance	decimal	Y	The account balance in the currency specified by Taopix as the system currency.
uselicensekeyforshippingaddress	integer	Y	0 = The user account address is used for the shipping address. 1 = The address held in the license key is used for the shipping address. NOTE This option only applies if *defaultaddresscontrol* is 0.
uselicensekeyforbillingaddress	integer	Y	0 = The user account address is used for the billing address. 1 = The address held in the license key is used for the billing address. NOTE This option only applies if *defaultaddresscontrol* is 0.
taxcode	varchar(20)	Y	A valid Taopix Control Centre tax rate code if applying a custom product tax rate to the customer account or empty if Taopix should determine the product tax rate.
shippingtaxcode	varchar(20)	Y	A valid Taopix Control Centre tax rate code if applying a custom shipping tax rate to the customer account or empty if Taopix should determine the shipping tax rate.
protectfromredaction	integer	Y	0 = The customer account can be anonymised via the redaction process. 1 = The customer account cannot be anonymised via the redaction process.
usedefaultvouchersettings	integer	Y	0 = The customer record will ignore the license key voucher settings and instead use the value passed in the allowvouchers and allowgiftcards parameters

			1 = The customer record will ignore the value passed in the allowvouchers and allowgiftcards parameters and instead use the voucher settings from the license key.
allowvouchers	integer	Y	0 = Does not allow the customer to apply vouchers to the Taopix shopping cart. 1 = Allows the customer to apply vouchers to the Taopix shopping cart.
allowgiftcards	integer	Y	0 = Does not allow the customer to apply gift cards to their Taopix account. 1 = Allows the customer to apply gift cards to their Taopix account.
isactive	integer	Y	0 = Account not active 1 = Account active