# Taopix E-Commerce Integration API v3.3

## Compatible with TAOPIX™ Control Centre 2021r1

Author: Taopix Development
Date: 30 October 2020
Document Name: Taopix E-Commerce Integration API v3.3.docx

PRIVATE & CONFIDENTIAL

# Revision History

| | | |
|---|---|---|
| 24th April | V3 | Revision history added.<br>ClearProjectBatchRef now returns an error if no projectrefs are passed to it. |
| 16th September | V3 | Added the ability to open a project in preview mode.<br>Added User Project List.<br>Added the ability to share a project. |
| 23rd October | V3.1 | Updated the device detection example for ipadOS |
| 31st July | V3.2 | Added devicesettings |
| 30th October | V3.3 | Added information about the projectpreviewthumbnail key in the output of getUsersProjectList. |

# Contents


Revision History ..... 2

IMPORTANT ..... 4

E-Commerce Integration API/Low Level API ..... 4

Introduction ..... 5

Important Points ..... 7

- Taopix Control Centre – Existing Customer Login Functionality ..... 7
- Device Detection ..... 8
- Online Designer Order Button ..... 8
- Project Locking ..... 8
- Exiting The Online Designer ..... 8
- Authentication ..... 8
- Embedded Online Designer ..... 8
- Data Retention Policy ..... 8
- Pricing ..... 9
- Order Data Availability ..... 9

API Overview ..... 10

E-Commerce Integration (Low Level API) ..... 11

- CreateProject2 ..... 11
- EditProject ..... 23
- PreviewProject ..... 28
- RenameProject ..... 28
- DuplicateProject ..... 31
- DeleteProject ..... 33
- DeleteUnflagProject ..... 36
- TouchProject ..... 38
- ExternalCheckout ..... 40
  - NOTE ..... 42
- ClearProjectBatchRef ..... 43

UnlockProject ..... 45
LockProject ..... 47
Online Designer Post Flight-Check Callback ..... 49
queryOrderStatus ..... 50
reorder ..... 52
checkDataAvailable ..... 54
View Users Project List APIs ..... 55
getUsersProjectList ..... 55
viewUsersProjectList ..... 56
usersProjectListInit ..... 57
usersProjectList ..... 58
leaveUsersProjectList ..... 59
generateSharePreviewLink ..... 60
Online Order Generation Changes ..... 62
Potential User Actions / Data Flow With E-Commerce Integration API ..... 63
Notifications from Taopix Control Centre ..... 65

# IMPORTANT

Taopix Limited is supplying this information to help you plan for the adoption of the technologies and programming interfaces described herein.

# E-Commerce Integration API/Low Level API

Throughout this document the API will be referred to as the E-Commerce Integration API. This is the marketing name for the API but within the code it can also be referred to as the Low Level API. These are referring to the same API.

# Introduction

The current Taopix Online order workflow is as follows:

```
Product Selector > Create Project > Order > Flight-Check > Checkout
```

or

```
Project Browser > Open Project > Order > Flight-Check > Checkout
```

There are three known restrictions with this workflow:

1. It is not possible to order multiple Taopix Online projects in a single transaction.
2. It is not possible to integrate Taopix Online into an eCommerce workflow that differs from the above basic workflow (for example, directly integrated into Magento or a cart belonging to a retailer).
3. It is not possible to integrate Taopix Online into a workflow where authentication is not important while designing and can simply be handled during an external cart checkout.

The purpose of the Taopix E-Commerce Integration API is to address these restrictions by providing a set of functions that can be used by licensees to extend their systems and integrate Taopix Online in the appropriate way.

Once the API has been implemented it will be possible to implement more sophisticated workflows including the following:

```
Product Selector > Create Project > Click Order > Flight-Check > Add To Cart
^                                                                            |
|___________________________________<<_________________________________v


Project Browser  >  Open Project  >  Click Order > Flight-Check > Add To Cart
^                                                                            |
|___________________________________<-<_________________________________v


Checkout In External System > Complete Order
```

To implement these workflows we need a new API:

Low-Level API

The low-level APIs would be appropriate for licensees who have the majority of the required infrastructure already in place (cart / basket etc…) or when the Online Designer needs to be integrated into an eCommerce environment that sells non-Taopix based products (ie: Magento based cart). Authentication and user management will not be the responsibility of Taopix (ie: no sign-in / register within the Online Designer).

This API is not designed to implement multi-line orders within the Taopix shopping cart.

# Important Points

## Taopix Control Centre – Existing Customer Login Functionality

1. Viewing Orders

   The E-Commerce Integration API will need to manage this and it will not be the responsibility of Control Centre. This option should be disabled within Control Centre.

2. Re-Ordering

   The E-Commerce Integration API will need to manage this and it will not be the responsibility of Control Centre. This option should be disabled within Control Centre.

3. Previewing

   Currently, there is no solution to do this using the E-Commerce Integration API. Additional APIs would be required for this.

4. Social Sharing

   Currently, there is no solution to do this using the E-Commerce Integration API. Additional APIs would be required for this.

5. Open Existing Projects

   This will be replaced by the options in the product selector. Accessing this will most likely break the integration so needs to be prevented.

6. User Details

   It is expected that the licensee will manage this outside of Taopix.

## Device Detection

There will be a requirement for the process invoking the CreateProject2 / EditProject APIs to perform the device detection that normally occurs when creating / editing a project within Taopix Online. This will involve Taopix Limited supplying some Javascript code that the external product selector / cart can run and provide the information via a dd parameter on the API URL.

## Online Designer Order Button

In some of these scenarios clicking the Order button will not transfer you to the cart but will eventually transfer you back to the product selector. This makes the button an Add To Cart function. The existing flight-check and validation processes that occur at this point will still take place before confirming that the project can be added to the cart.

## Project Locking

When a customer checks-out it is imperative that they cannot perform actions on their projects. In the situation that the cart / basket cannot control this the API will need to be able to lock projects for a specific period of time. This will prevent actions (both user driven / API driven) from being performed on a project until the lock expires.

## Exiting The Online Designer

The API will provide access to a new feature that allows the user to redirect their browser back to a specific URL. The API will also allow the name of this option to be specified. It is expected that the option will appear in the top-left menu on small screen devices. A solution for large screen devices will need to be determined.

## Authentication

The ability to authenticate within the Taopix Online designer will be controllable via the API. If this is disabled it could mean that a project spends its entire life as a guest project until it is ordered. It is expected that users of the E-Commerce Integration API will manage users completely outside of Taopix.

## Embedded Online Designer

It is currently not possible to embed the Taopix Online Designer within an iFrame. This may be available in a future version but for now, the Online Designer should be opened either via a HTTP redirect or within a new browser window.

## Data Retention Policy

Taopix Online has a project purge feature that deletes projects based on a last accessed time and a specific criteria (guest / unsaved / not-ordered). As it stands, this feature is unsuitable as it means projects could be purged while they are sitting in someone's basket.

To solve this problem we will introduce a data retention period for projects. This period will be the minimum number of days that a project can exist before being purged from the system. The number of days will be stored in the project and used to calculate the minimum purge date (also stored in the project) every time the project is touched / project dates are updated. This minimum purge date would be taken into account by the current purge processes.

## Pricing

The low-level API is not designed to provide price data back to the basket.

## Order Data Availability

Taopix Control Centre has the ability to clean up old order data files (production files, order data files, preview thumbnails) and redact order data records. This means that an reordering an ordered project may not be possible due to the files needed to produce the order not being present. When attempting to invoke Reorder endpoint, the API will warn you that the order files have been cleaned up via the dataavailable item. The API also allows for the availability of the data for multiple orders to be queried via the CheckDataAvailable endpoint.

# API Overview

This API is HTTP(s) based. It requires that the licensee's systems transmit requests to the Taopix Control Centre server to initiate an action. This in turn, invokes a PHP script on the Taopix Control Centre server (EDL_ONLINEBASKETAPI.php) that the licensee must create. The purpose of this script is to interpret the data (parameters) transmitted to the API and convert them into the parameters required by Taopix. This allows the licensee to fully control the method in which they send the parameters and how they are protected.

# E-Commerce Integration (Low Level API)

## CreateProject2

This API starts a design session for a new project. This is similar to the existing CreateProject API used by a standard Taopix Online system but with additional functionality.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| groupcode | The Taopix License Key code for the project. | Y |
| groupdata | The optional groupdata tracking data. | N |
| collectioncode | The Taopix Product Collection code for the project. | Y |
| productcode | The Taopix Product code for the project. | Y |
| guestworkflowmode | The optional guest workflow mode override. | N |
| projectname | The default name for the Online project. | N |
| devicedetection | The device detection data. | Y |
| smallscreenwizardmode | Specifies the wizard mode on small screen. Value determined by the setting on the URL or the brand<br><br>0 – The product will open using the wizard mode set within the product in Taopix Creator<br><br>2 – The product will open on mobile devices using the Replace Layout wizard mode<br><br>3 – The product will open on mobile devices using the Keep Layout wizard mode<br><br>- defaults to -1. | N |
| largescreenwizardmode | Specifies the wizard mode on large screen.<br><br>Value determined by the setting on the URL | N |

| | | |
|---|---|---|
| | 0 – The product will open using the wizard mode option set to Off (non wizard product)<br><br>1 – The product will open on large screen devices using the Picture Selection only wizard mode<br><br>2 – The product will open on large screen devices using the Replace Layout wizard mode<br><br>3 – The product will open on large screen devices using the Keep Layout wizard mode<br><br>- defaults to -1. | |
| devicesettings | Value determined by detection of users device.<br><br>smallscreen - a small screen device was used to create the project.<br><br>largescreen – a large screen device was used to create the project.<br><br>unknown – Taopix was unable to determine the device type. | N |
| enableswitchingeditor | Specifies if the Switch To Easy/Advanced editor optio will show on large screen .<br><br>Value determined by the setting on the URL<br><br>0 – The project will not display the Switch option<br><br>1 – The project will display the Switch option<br><br>- defaults to -1. | N |
| pagestyle | Specify which layout will be applied to pages during the creation process.<br><br>Read Taopix Modify Project Creation v2.0 for more details. | N |
| txt_xxxx | Specify which tags will be replaced by a text value during the creation process.<br><br>xxxx is the tag name from Taopix Creator and cannot contain txt_.<br><br>Read Taopix Modify Project Creation v2.0 for more details. | N |

## Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |
| id | Decodes to groupcode, collectioncode, layoutcode |
| gd | groupdata |
| gwm | Guestworkflowmode |
| dd | devicedetection |

## API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| resultmessage | Corresponding error message for result code. |
| brandcode | The Taopix Brand code for the project. |
| groupcode | The Taopix License Key code for the project. |
| groupdata | The optional groupdata tracking data. |
| collectioncode | The Taopix Product Collection code for the project. |
| collectionname | The Taopix Product Collection name for the project. |
| productcode | The Taopix Product code for the project. |
| productname | The Taopix Product name for the project. |
| projectref | The Online Project Ref. |
| projectname | The Online Project name. |
| designurl | The URL to the Taopix Online Designer. |

The project will not exist until the designurl is invoked but this allows the originator of the call to add the project to their own projects list prior to invoking the designurl.

Invoking this API will execute the existing code which decrypts the product URL into it's various components: collection code, layout code, group code etc…

However, before continuing to process the request it will call the CreateProject function within EDL_ONLINEBASKETAPI. This function will receive the decoded parameters and will allow the function to modify and return them. It will be these values that Taopix will use when performing any validation / creating the project:

## Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| brandcode | The Taopix Brand code if one could be determined from the API input. |
| groupcode | The Taopix License Key code if one could be determined from the API input. |
| groupdata | The optional groupdata tracking data if one has been provided on the URL. |
| collectioncode | The Taopix Product Collection code from the encrypted URL data. |
| productcode | The Taopix Product Layout code from the encrypted URL data. |
| guestworkflowmode | If the Licence Key is available then the final guestworkflowmode (based on License Key & gwm parameter).<br><br>If the License Key is not available then the gwm parameter.<br><br>If neither available then set to disabled. |

| | |
|---|---|
| projectname | The default name for the Online project – defaults to empty. |
| devicedetection | The device detection data. |
| minlife | The minimum life of the project in days – defaults to 0.<br><br>This will be stored against the project so that anything which touches the project can update the purge date. |
| checkoutname | The name of the button associated with the Order button – defaults to empty. |
| abandonurl | The URL that can be used to invoke a back / abandon option within the Online Designer – defaults to empty. |
| abandonname | The name of the button associated with the abandon URL – defaults to empty. |
| cansignin | Specifies if the user can sign-in within the Online Designer – defaults to 1.<br><br>If the user is not allowed to sign-in then all sign-in related functions must be removed from the GUI.<br><br>If the project belongs to a guest then all functions that require a sign-in user (ie: pictures from existing projects) must also be removed. |
| cansignout | Specifies if the user can sign-out within the Online Designer- defaults to 1. |
| disablebackbutton | Specifies if clicking the browser back button within the Online Designer should be prevented – defaults to 0. |
| editprojectnameonfirstsave | Specifies if the user is able to overwrite the project name on first save. Defaults to 1. |

| | |
|---|---|
| smallscreenwizardmode | Specifies the wizard mode on a small screen<br>Value determined by the setting on the URL<br>the brand<br><br>0 – The product will open using the wizard mode set within the product in Taopix Creator<br><br>2 – The product will open on mobile devices using the Replace Layout wizard mode<br><br>3 – The product will open on mobile devices using the Keep Layout wizard mode<br><br>- defaults to -1. |
| largescreenwizardmode | Specifies the wizard mode on large screen.<br><br>Value determined by the setting on the URL<br><br>0 – The product will open using the wizard mode option set to Off (non wizard product)<br><br>1 – The product will open on large screen devices using the Picture Selection only wizard mode<br><br>2 – The product will open on large screen devices using the Replace Layout wizard mode<br><br>3 – The product will open on large screen devices using the Keep Layout wizard mode<br><br>- defaults to -1. |
| devicesettings | Value determined by detection of users device.<br><br>smallscreen - a small screen device was used to create the project.<br><br>largescreen – a large screen device was used to create the project.<br><br>unknown – Taopix was unable to determine the device type. |

| | |
|---|---|
| enableswitchingeditor | Specifies if the Switch To Easy/Advanced editor option will show on large screen .<br><br>Value determined by the setting on the URL<br><br>0 – The project will not display the Switch option<br><br>1 – The project will display the Switch option<br><br>- defaults to -1. |
| onlineeditormode | Specifies if the editor opens in either Easy o Advanced editor.<br><br>Value determined by the setting on the URL<br><br>0 – Easy Editor<br><br>1 – Advanced Editor<br><br>-defaults to -1 |
| onlinedesignerlogolinkurl | The Online Designer logo link URL is where the user is directed when they click the logo in the Online Designer.<br><br>Defaults to setting in brand or license key |
| onlinedesignerlogolinktooltip | The logo tool tip is the tooltip that appears when the end user hovers over the logo in t Online Designer.<br><br>Defaults to setting in brand or license key |
| pagestyle | Specify which layout will be applied to pages during the creation process.<br><br>This parameter is passed only if the parameter is part of an encrypted URL Data<br><br>Read Taopix Modify Project Creation v2.0 for more details. |
| txt_xxxx | Specify which tags will be replaced by a text value during the creation process. |

| | |
|---|---|
| | xxxx is the tag name from Taopix Creator and cannot contain txt_.<br><br>Read Taopix Modify Project Creation v2.0 for more details. |

## Function Output

| Name | Information | Modify |
|---|---|---|
| result | Empty to continue or a localized error message to return. | Y |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | Y |
| brandcode | Same as function input. | N |
| groupcode | The Taopix License Key code for the project. | Y |
| groupdata | The optional groupdata tracking data. | Y |
| collectioncode | The Taopix Product Collection code for the project. | Y |
| layoutcode | The Taopix Product Layout code for the project. | Y |
| guestworkflowmode | The Taopix guest workflow mode override setting. | Y |
| projectname | The default name for the Online project. | Y |
| devicedetection | The device detection data. | Y |
| minlife | The minimum life of the project in days. | Y |
| checkoutname | The name of the button associated with the Order button in Taopix multi-lingual string format. If this is empty then the default name is used. | Y |
| abandonurl | The URL that can be used to invoke a back / abandon option within the Online Designer. | Y |
| abandonname | The name of the button associated with the abandon URL in Taopix multi-lingual string format. | Y |

| | | |
|---|---|---|
| cansignin | Specifies if the user can sign-in within the Online Designer. | Y |
| cansignout | Specifies if the user can sign-out within the Online Designer. | Y |
| disablebackbutton | Specifies if clicking the browser back button within the Online Designer should be prevented. | Y |
| editprojectnameonfirstsave | Specifies if the user is able to overwrite the project name on first save. | Y |
| useraccount | Should be returned as an empty array if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| updategroupcode | Should be returned as an integer set to 0 if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| updateaccountdetails | Should be returned as an integer set to 0 if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| updateaccountbalance | Should be returned as an integer set to 0 if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| updategiftcardbalance | Should be returned as an integer set to 0 if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |

| | | |
|---|---|---|
| ssotoken | Should be returned as an empty string if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| ssoprivatedata | Should be returned as an empty array if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| assetservicedata | Should be returned as an empty array if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| ssoexpiredate | Should be returned as an empty string if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| smallscreenwizardmode | Specifies the wizard mode on a small screen. Value determined by the setting on the URL or the brand<br><br>0 – The product will open using the wizard mode set within the product in Taopix Creator<br><br>2 – The product will open on mobile devices using the Replace Layout wizard mode<br><br>3 – The product will open on mobile devices using the Keep Layout wizard mode<br><br>- defaults to -1. | |
| largescreenwizardmode | Specifies the wizard mode on large screen.<br><br>Value determined by the setting on the URL<br><br>0 – The product will open using the wizard mode option set to Off (non wizard product) | |

| | | |
|---|---|---|
| | 1 – The product will open on large screen devices using the Picture Selection only wizard mode<br><br>2 – The product will open on large screen devices using the Replace Layout wizard mode<br><br>3 – The product will open on large screen devices using the Keep Layout wizard mode<br><br>- defaults to -1. | |
| enableswitchingeditor | Specifies if the Switch To Easy/Advanced editor option w show on large screen .<br><br>Value determined by the setting on the URL<br><br>0 – The project will not display the Switch option<br><br>1 – The project will display the Switch option<br><br>- defaults to -1. | Y |
| onlineeditormode | Specifies if the editor opens in either Easy or Advanced editor.<br><br>Value determined by the setting on the URL<br><br>0 – Easy Editor<br><br>1 – Advanced Editor<br><br>-defaults to -1 | Y |
| onlinedesignerlogolinkurl | The Online Designer logo link URL is where the user is directed when they click the logo in the Online Designer | Y |
| onlinedesignerlogolinktooltip | The logo tool tip is the tooltip that appears when the en user hovers over the logo in the Online Designer.<br><br>Defaults to setting in brand or license key | Y |
| pagestyle | Specify which layout will be applied to pages during the creation process.<br><br>This parameter needs to respect a specific format.<br><br>Read Taopix Modify Project Creation v2.0 for more details. | N |

| | | |
|---|---|---|
| txt_xxxx | Specify which tags will be replaced by a text value during the creation process.<br><br>xxxx is the tag name from Taopix Creator and cannot contain txt_.<br><br>Read Taopix Modify Project Creation v2.0 for more details. | N |

Introducing this function allows a licensee more control over how a new project is created.

For example, they may decide not to use the Taopix encrypted URLs and instead, provide the data via different URL parameters that the function can convert into the necessary data. The function will also allow control over features that are not normally available when creating a new project. This means that the standard features currently available when creating projects may not be present.

If the device detection data is empty or invalid the API should fail. It should not attempt to use the Cookie or perform a re-direct like CreateProject. The device validation should also be performed during the API stage so that an error is returned rather than the user being re-directed to the Online Designer, which then displays an error (non API calls should still do this though).

If the standard Taopix Product URL has been provided then the License Key code will be available. This will allow the brand code and final guest workflow mode to be determined. If the License Key code is not available then the system should attempt to determine the brand from the source URL. The guest workflow mode in this situation would be whatever was provided by the gwm parameter or disabled if not present). The brand code here is for reference as it should be determined from the groupcode returned.

If a project name is provided, this should be used as long as it only contains the characters we deem valid. Invalid characters should result in the API failing. If no project name is provided then we should auto-generate an Untitled name.

By default projects will always start as guest. Depending on the cansignin option, the project may be a guest project for it's entire life even at the point which it is saved. This means the data retention period is very important to avoid purging projects too early.

If the script sets cansignin to zero, Taopix must force the automatic guest workflow mode no matter what has been specified elsewhere.

If the owner of the project is known in advance then the useraccount (especially ACCOUNTCODE) can be populated by the script which will either insert / update an existing Taopix user account.

## EditProject

This API starts a design session for an existing project.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectref | The Online Project Ref. | Y |
| canunlock | Can a locked project be unlocked when performing this operation? | N |
| devicedetection | The device detection data. | Y |
| forcekill | Used to forcekill design sessions and shopping cart sessions | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |
| dd | devicedetection |

### API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| resultmessage | Corresponding error message for result code. |
| brandcode | The Taopix Brand code for the project. |
| groupcode | The Taopix License Key code for the project. |
| collectioncode | The Taopix Product Collection code for the project. |
| collectionname | The Taopix Product Collection name for the project. |

| | |
|---|---|
| productcode | The Taopix Product code for the project. |
| productname | The Taopix Product name for the project. |
| projectname | The Online Project name. |
| projectref | The Online Project Ref. |
| designurl | The URL to the Taopix Online Designer. |

Invoking this API will execute the existing code which starts the continue editing process. All validation that normally occurs when a user clicks the Continue Editing button should still occur. If the project is currently locked and canunlock is 0 then the request should also fail.

However, the first task that the request should do is call the EditProject function within EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform the validation and design session initialisation.

## Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectref | The Online Project Ref. |
| canunlock | Can a locked project be unlocked when performing this operation – defaults to 0 if the input parameter is not present. |
| devicedetection | The device detection data. |
| minlife | The new minimum number of days to purge the project after<br><br>–defaults to -1 which means use the existing value in the project.<br><br>Assigning this will calculate a new purgedate. |
| checkoutname | The name of the button associated with the Order button – defaults to empty. |
| abandonurl | The URL that can be used to invoke a back / abandon option within the Online Designer – defaults to empty. |

| | |
|---|---|
| abandonname | The name of the button associated with the abandon URL – defaults to empty. |
| disablebackbutton | Specifies if clicking the browser back button within the Online Designer should be prevented – defaults to 0. |
| forcekill | Used to forcekill design sessions and shopping cart sessions.<br><br>Defaults to 0. |
| editprojectnameonfirstsave | Specifies if the user is able to overwrite the project name on first save. Defaults to 1. |
| previewmode | Specifies the reason editProject has been called.<br><br>If the editProject API endpoint is invoked, this parameter is set to false. If the previewProject API endpoint is invoked, this parameter is set to true. |

## Function Output

| Name | Information | Modify |
|---|---|---|
| result | Empty to continue or a localized error message to return. | Y |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | Y |
| projectref | The Online Project Ref. | Y |
| canunlock | Can a locked project be unlocked when performing this operation? | Y |
| devicedetection | The device detection data. | Y |
| minlife | The minimum life of the project in days. | Y |
| checkoutname | The name of the button associated with the Order button in Taopix multi-lingual string format. If this is empty then the default name is used. | Y |

| | | |
|---|---|---|
| abandonurl | The URL that can be used to invoke a back / abandon option within the Online Designer. | Y |
| abandonname | The name of the button associated with the abandon URL in Taopix multi-lingual string format. | Y |
| disablebackbutton | Specifies if clicking the browser back button within the Online Designer should be prevented. | Y |
| forcekill | Used to forcekill design sessions and shopping cart sessions | Y |
| editprojectnameonfirstsave | Specifies if the user is able to overwrite the project name on first save. | Y |
| useraccount | Should be returned as an empty array if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| updategroupcode | Should be returned as an integer set to 0 if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| updateaccountdetails | Should be returned as an integer set to 0 if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| updateaccountbalance | Should be returned as an integer set to 0 if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| updategiftcardbalance | Should be returned as an integer set to 0 if not using Single Sign-On. It is Mandatory to return this parameter. | Y |

| | | |
|---|---|---|
| | If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | |
| ssotoken | Should be returned as an empty string if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| ssoprivatedata | Should be returned as an empty array if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| assetservicedata | Should be returned as an empty array if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| ssoexpiredate | Should be returned as an empty string if not using Single Sign-On. It is Mandatory to return this parameter.<br><br>If using Single Sign-On Please refer to the Taopix External Customer Account Scripting v4.0 document. | Y |
| onlinedesignerlogolinkurl | The Online Designer logo link URL is where the user is directed when they click the logo in the Online Designer | Y |
| onlinedesignerlogolinktooltip | The logo tool tip is the tooltip that appears when the en user hovers over the logo in the Online Designer.<br><br>Defaults to setting in brand or license key | Y |

Introducing this function allows a licensee more control over how the continue editing function operates.

For example, they may decide not to use the standard URL parameters and instead, provide the data via different URL parameters that the function can convert into the necessary data. The function will also allow control over features that are not normally available when continuing to edit a project. This means that the standard features currently available when editing existing projects may not be present.

If the device detection data is empty or invalid the API should fail. It should not attempt to use the Cookie or perform a re-direct like CreateProject. The device validation should also be performed during the API stage so that an error is returned rather than the user being re-directed to the Online Designer, which then displays an error (non API calls should still do this though).

The project can be assigned to a user by populating the useraccount array (especially ACCOUNTCODE). This should only occur if the project is assigned to a guest user – ie: you cannot change the owner of a project once they have been assigned.

## PreviewProject

This API will return a URL link to a preview of a project. This works exactly the same as editProject API (see previous section) but navigating to the url in the JSON data will redirect the user to a preview of the project rather than and editable version. The editProject EDL function is called with the same parameters except the previewmode parameter is set to true instead of false.

## RenameProject

This API will rename an existing project.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectref | The Online Project Ref. | Y |
| newname | The new Project name. | Y |
| canunlock | Can a locked project be unlocked when performing this operation? | N |
| ccnotificationsenabled | Should a new CCNotification event be generated for this operation? | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

## API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| resultmessage | Corresponding error message for result code. |

Invoking this API will execute the existing code that renames the project. All validation that normally occurs when a user clicks the Rename button should still occur. If the project is currently locked and canunlock is 0 then the request should also fail.

However, the first thing that the request should do is call the RenameProject function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform the validation (including valid name characters) and perform the rename.

## Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectref | The Online Project Ref. |
| newname | The new Project name. |
| canunlock | Can a locked project be unlocked when performing this operation – defaults to 0 if the input parameter is not present. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectref | The Online Project Ref. |
| newname | The new Project name. |
| canunlock | Can a locked project be unlocked when performing this operation? |

| | |
|---|---|
| ccnotificationsenabled | Should a new CCNotification event be generated for this operation? |

Introducing this function allows a licensee more control over how the rename project function operates.

For example, they may decide not to use the standard URL parameters and instead, provide the data via different URL parameters that the function can convert into the necessary data.

## DuplicateProject

This API will duplicate an existing project.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectref | The Online Project Ref. | Y |
| projectname | The new Project name. | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| resultmessage | Corresponding error message for result code. |
| projectref | The new Online Project Ref. |
| projectname | The new Project name. |

Invoking this API will execute the existing code that duplicates the project. All validation that normally occurs when a user clicks the Duplicate button should still occur.

However, the first thing that the request should do is call the DuplicateProject function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform the validation (including valid name characters) and perform the duplication.

## Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectref | The Online Project Ref. |
| newname | The new Project name. |
| minlife | The minimum life of the project in days – defaults to 0.<br><br>This will be stored against the project so that anything which touches the project can update the purge date. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectref | The Online Project Ref. |
| projectname | The new Project name. |
| minlife | The minimum life of the project in days. |

Introducing this function allows a licensee more control over how the duplicate project function operates.

For example, they may decide not to use the standard URL parameters and instead, provide the data via different URL parameters that the function can convert into the necessary data.

The supplied project name must only contain the project name characters we deem as valid. If it contains other characters then this should fail.

If the new project name is empty we should attempt to auto-create one.

## DeleteProject

This API will delete one or more projects.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectreflist[] | A list of Online Project Refs. | Y |
| purgedays | The number of days to purge the project after. | Y |
| canunlock | Can a locked project be unlocked when performing this operation? | N |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| resultlist[] | A list of projects and their result.<br>[projectref:<br>result:<br>resultmessage:<br>] |

Invoking this API will first call the DeleteProject function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and perform the deletion or the flagging (ie: the order is not active in production etc…).

## Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |
| purgedays | The number of days to purge the project after. |
| canunlock | Can a locked project be unlocked when performing this operation – defaults to 0 if the input parameter is not present. |
| forcekill | Used to forcekill design sessions and shopping cart sessions.<br><br>Defaults to 0. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |
| purgedays | The number of days to purge the project after. |
| canunlock | Can a locked project be unlocked when performing this operation? |
| forcekill | Used to forcekill design sessions and shopping cart sessions. |

*The purgedays parameter will instruct Taopix how the projects should be deleted.*

| | |
|---|---|
| -1 | The projects will be deleted immediately. This should perform the same checks as the existing Delete button. |
| > -1 | The projects will be flagged for deletion after the specific number of days. |

Introducing this function allows a licensee more control over project deletion.

For example, they may decide not to use the standard URL parameters and instead, provide the data via different URL parameters that the function can convert into the necessary data.

If any of the projects are currently locked then the request should fail unless canunlock is 1.

## DeleteUnflagProject

This API will attempt to unflag the projects which have previously been flagged for deletion.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectreflist[] | A list of Online Project Refs. | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| resultlist[] | A list of projects and their result.<br><br>[projectref:<br><br>result:<br><br>resultmessage:<br><br>] |

Invoking this API will first call the DeleteUnflagProject function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and perform the deletion. Unflagging a project should also update the minimum purge date.

### Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |

## TouchProject

This API will attempt to refresh to earliest purge date based on the project's data retention period.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectreflist[] | A list of Online Project Refs. | Y |
| newminlife | The new minimum number of days to purge the project after. | N |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| resultlist[] | A list of projects and their result.<br>[projectref:<br>result:<br>resultmessage:<br>] |

Invoking this API will first call the TouchProject function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and update the dates. Touching a project should also unflag it from deletion if it has been flagged.

## Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |
| newminlife | The new minimum number of days to purge the project after - defaults to -1 which means use existing value. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |
| newminlife | The number of days to purge the project after. |

## ExternalCheckout

This informs Taopix that a checkout process that does not involve Taopix Control Centre (Taopix Cart / Shopping Cart Breakout) is about to start.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectreflist[] | A list of Online Project Refs. | Y |
| lockperiod | The number of minutes that the projects should be locked for. | N |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| resultlist[] | A list of projects and their cart data.<br><br>[projectref:<br><br>result:<br><br>resultmessage:<br><br>cartdata: []<br><br>] |

Invoking this API will first call the ExternalCheckout function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and lock the projects.

## Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |
| lockperiod | The number of minutes that the projects should be locked for – defaults to 0. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |
| cartdata[] | An array of project data for each item in the cart. The data for each project should be the same data that was passed to the inititialise function in the EDL_ONLINEBASKETAPI script. |
| lockperiod | The number of minutes that the projects should be locked for – defaults to 0. |

The main purpose of this function is to allow Taopix to confirm to the checkout that the projects are valid. The tests should involve:

- The project exists.
- The project has no open design sessions.
- The project has passed the flight-check successfully.
- No external assets have expired.
- The project ref does not already exist in an order item.
- The project's product configuration is still valid.

If any projects fail the validation then the checkout process should not continue.

If all projects pass this validation they will be locked for the specified number of minutes. If a project is already locked then the lock time will be updated.

## NOTE

This API call is optional. If the checkout process can already prevent illegal access to projects then there is no need to call this API. The data which it returns will also be available during the callback (see later in this specification).

## ClearProjectBatchRef

This API will delete the sales order record for an existing project that has been added to the end users basket.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| Projectreflist[] | A list of Online Project Refs. | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| resultmessage | Corresponding error message for result code. |

The first thing that the request will do is call the ClearProjectBatchRef function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them.

### Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist | The Online Project Ref. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist | A list of Online Project Refs. |

This is a mandatory API call and must be called when an end user removes a project from their basket. If no projectrefs are passed the call will return an invalid parameter error.

This API call is to inform Taopix that the project has been removed from the end users cart. The Taopix system will then delete the sales order record for the corresponding projects.

A new sales order record will then be created when the end user decides to add the project back into their basket.

## UnlockProject

This API will attempt to unlock the specified projects so that they can be manipulated.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectreflist[] | A list of Online Project Refs. | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| resultlist[] | A list of projects and their result.<br>[projectref:<br>result:<br>resultmessage:<br>] |

Invoking this API will first call the UnlockProject function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and update the dates.

### Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |

## LockProject

This API will attempt to lock the specified projects so that they can't be manipulated.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectreflist[] | A list of Online Project Refs. | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| resultlist[] | A list of projects and their result.<br>[projectref:<br>result:<br>resultmessage:<br>] |

Invoking this API will first call the lockProject function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and update the dates.

### Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |
| lockperiod | The number of minutes that the projects should be locked for – defaults to 0. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs. |
| lockperiod | The number of minutes that the projects should be locked for. |

## Online Designer Post Flight-Check Callback

When the flight-check is passed and the Online Designer communicates with Control Centre it will build the data that is normally used to initiate the cart.

However, before returning back to the Online Designer, Control Centre will call the initialise function within EDL_ONLINEBASKETAPI. This function will receive this data and will allow the external system to be informed that a new item is available to add to the cart along with the data that describes the product.

### Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectref | The Online Project Ref. |
| cartdata | The cart data array. |
| useraccount[] | The Taopix user account for an authenticated user (empty if not authenticated). |

### Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| url | The url to re-direct the Online Designer to. This could be the URL to a product selector or left empty to invoke the normal Taopix shopping cart process. |

If the result is not empty, the Online Designer will display the error message and will not allow the user to progress.

## queryOrderStatus

This API will attempt retrieve the order status for the specified projects and will also determine if they can be manipulated.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectreflist[] | A list of Online Project Refs. | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| resultlist[] | A list of projects and their result.<br>[projectref:<br>result:<br>resultmessage:<br>canedit:<br>status:<br>] |

Invoking this API will first call the queryOrderStatus function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and retrieve the order status for the projects.

### Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |

| | |
|---|---|
| projectreflist[] | A list of Online Project Refs. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectreflist[] | A list of Online Project Refs and a corresponding order item ID.<br><br>[projectref: orderitemid]<br><br>Although projectref is mandatory it is not mandatory to set the corresponding orderitemid. If not specifiying orderitemid then it should be set to 0.<br><br>Using the projectref on its own means that only the first version of the order data will be retrieved. However using it in conjunction with the orderitemid means that we can retrieve a specific version of the order data. |

## reorder

This API call will build the data that is normally used to initiate the cart for a reorder.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| projectref | A list of Online Project Refs. | Y |
| orderitemid | Corresponding order item ID for the project ref above. | N |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| resultmessage | Corresponding error message for result code. |

Invoking this API will first call the prepareReorderInit function within the EDL_ONLINEBASKETAPI. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and prepare the reorder data which will then be passed to the prepareReorderResult function also within the EDL_ONLINEBASKETAPI.

### Function Input

| | |
|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectref | The Online Project Ref. |
| orderitemid | Corresponding order item ID for the online project. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |
| languagecode | The language that the Online Designer / initialisation error messages should appear in. |
| projectref | The Online Project Ref. |
| orderitemid | Although projectref is mandatory it is not mandatory to set the corresponding orderitemid. If not specifiying orderitemid then it should be set to 0.<br><br>Using the projectref on its own means that only the first version of the order data will be retrieved. However using it in conjunction with the orderitemid means that we can retrieve a specific version of the order data. |

If an error has not occurred Taopix will then pass on the data that is normally used to initiate the cart for a reorder to the prepareReorderResult function within the EDL_ONLINEBASKETAPI.

This function will receive this data and will allow the external system to be informed that a new item is available to add to the cart along with the data that describes the product.

## Function Input

| | |
|---|---|
| cartdata | The cart data array used to initiate the cart for a reorder. Included in the cartdata is the dataavailable flag. This informs you if the reorder can proceed. If this flag is set to 1 then the order data is available and the reorder can be performed. If it is set to 0 them the order data is not available and reorder cannot occur and you should populate the result item with a message. |

## Function Output

| | |
|---|---|
| result | empty to continue or a localized error message to return. |

## checkDataAvailable

This API call will check the availability of the order data and of a list of order item ids

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| languagecode | The language that the Online Designer / initialisation error messages should appear in. | N |
| orderitemids | A list of order item ids. | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| orders | An array containing an item for each order item id you have queried specifying the data availability. The follow table explains the data structure. |

### Order Item (JSON)

| | |
|---|---|
| orderitemid | The order item id corresponding with the each orderitemids item. |
| dataavailable | 1 = The order data is available, 0 = The order data is not available |
| result | 0 = No error, 37 = Order doesn't exist |

## View Users Project List APIs

This set of APIs have been developed to make producing a list of users projects easier to implement in Taopix using the E-Commerce Integration API.

The API can be implemented in two ways: getUsersProjectList or viewUsersProjectList.

### getUsersProjectList

This endpoint will return a JSON string of projects for the user which has been selected via the usersProjectsListInit EDL function.

Using this option allows you to implement your own project list using HTML/Javascript.

#### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

#### API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| The data from the getUserProjectList EDL function | |

## viewUsersProjectList

This endpoint will redirect the user to an out-the-box implementation of the project list.

You can add a copy of this template to your 'customise' or 'branding' folders to make any changes, or you can use the template to see how to write your own.

The template will consume other E-Commerce Integration API endpoints to achieve all functionality; editProject, deleteProject, renameProject, duplciateProject, sharePreview.

The template is made up of two Smarty templates: templates/customer/projectlist.tpl and templates/customer/projectlist_row.tpl. Should you need to make a logical decision when leaving the project list (SSO, dynamic URL), the URL to leave the page goes through the leaveUsersProjectList endpoint.

As well as userProjectListInit EDL function there is also usersProjectList EDL function. This is used to modify the projects which are returned as JSON or displayed. You can remove items from the list or modify the data i.e. Rename projects.

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (HTML)

| |
|---|
| Redirected to the projectlist.tpl output. |

## usersProjectListInit

This function needs to be implemented for the getUsersProjectList or viewUsersProjectList to work. The main functionality of this function is for you to return the user identification of the user the project list is for.

The mode parameter passes in the reason the function is being called. This is either TPX_USER_PROJECT_LIST_MODE_VIEW (when viewUsersProjectList API is invoked) or TPX_USER_PROJECT_LIST_MODE_GET (when getUsersProjectList API is invoked).

The function must return either a TAOPIX user id (if known) or an account code. The account code is the common link between a Taopix user and the same user in your own user/customer database.

### Function Input

| | |
|---|---|
| mode | This is either TPX_USER_PROJECT_LIST_MODE_VIEW or TPX_USER_PROJECT_LIST_MODE_GET depending on whether the getUsersProjectList or viewUsersProjectList endpoints are being called. |
| languagecode | The language code which has been determined. |
| ssoprivatedata | If your user has been accessing your system using SSO and you have previously set some SSO private data, this will be passed back into this function. |

### Function Output

| | |
|---|---|
| languagecode | The language code if different to the one passed in. |
| ssoprivatedata | If your user has been accessing your system using SSO and you have previously set some SSO private data, you can set the SSO private data to be used later. |
| returntext | Multilingual string used for link to leave the projects list e.g.<br>en Back<p>fr Retour |
| userid | The TAOPIX user id of the user you wish to display the projects list for. |
| accountcode | The account code of the user in the TAOPIX users database. This is the common link between TAOPIX and your own users database. Usually this is your users ID. |

## usersProjectList

This function is not mandatory for getUsersProjectList or viewUsersProjectList to work. Its purpose is to allow you to modify the list of projects which are to be returned to the user or as a JSON packet.

The function has one parameter which is an array of projects as described in the following table. This table only contains items which are relevant to this call. There are other attributes and items but these can be ignored for this purpose:

### Function Input

| | |
|---|---|
| count | The amount of projects which are contained in the projects item. |
| projects | An array of project items. |
| **Project Item** | |
| projectref | The reference to the project item. |
| name | The name the user has given the project. |
| productname | The name of the product the project is based on. |
| datandtimecreated | The date and time the project was first created. |
| collectionname | The name of the product collection the product is linked to. |
| workflowtype | The type of product the project is:<br>0 = Photo book.<br>2 = Photo Print.<br>3 = Calendar.<br>200 = A Photo book in easy editor mode. |
| wizardmode | The wizard mode setting user:<br>0 = Off.<br>1 = Picture Selection Only.<br>2 = Replace Layout.<br>3 = Keep Layout. |

| | |
|---|---|
| projectpreviewthumbnail | The URL to the project preview thumbnail, if the project has one. This URL is signed and will expire after the time defined by the URLEXPIRES setting from the Taopix Online config file so it is recommended to download and store the thumbnail elsewhere if needed for longer periods. |
| canedit | 0 = The project cannot be edited. This will be due to it already being ordered<br><br>1 = The project can be edited. |
| candelete | 0 = The project cannot be deleted.<br><br>1 = The project can be deleted. |

## leaveUsersProjectList

This function is only relevant for the viewUsersProjectList endpoint since it controls how a user leaves the project list page.

At the top of the page next to the logo there is a back button. Pressing this will invoke this function. This function needs to return the URL the user will be redirected to.

A use case for this would be if you have move from one domain another and you need to swap access keys, token or codes between the two, or the URL could be generated dynamically. Calling this endpoint will invoke the leaveUsersProjectList EDL function. This is where you can put your logic.

### Function Input

| | |
|---|---|
| ssoprivatedata | If your user has been accessing your system using SSO and you have previously set some SSO private data, this will be passed back into this function. |

### Function Ouput

| | |
|---|---|
| ssoprivatedata | If your user has been accessing your system using SSO and you have previously set some SSO private data, you can set the SSO private data to be used later. |
| redirecturl | The URL you wish to redirect the user to. |

## generateSharePreviewLink

This API is only relevant to viewUsersProjectList API. It is designed to allow you to return a URL which will consume the previewProject API.

The function will need to return a link which a user can share with a friend or family member to display a preview of their project. The URL which is returned can be to any domain. We have provided an example of what this page could do along with this documentation.

The URL which is returned from the previewProject API is only valid for 72 hours. Linking directly to this URL, in most cases, won't work because the person visiting the link may do so after this time period.

The URL which this function returns will then have to consume the previewProject API and redirect the user. This can be done in an iFrame or by redirecting the whole page to the preview. Going to the preview this way also gives you the chance to encrypt the projectref or to implement a password for the link. Implementing a password would require you making changes to the projectlist.tpl template and are currently out of scope of this API.

### Key Input Parameters

| Name | Information | Mandatory |
|---|---|---|
| projectref | The project ref of the project which you want to generate the share URL for. | Y |

### Input Parameters Automatically Retrieved (Pre-Populated) From $_GET

| | |
|---|---|
| l | languagecode |

### API Output (JSON)

| | |
|---|---|
| result | Result code – Returns 0 if no error has occurred. |
| sharelink | The URL which the user will be presented with in the viewUserProjectsList template. |

### Function Input

| | |
|---|---|
| projectref | The project ref of the project which you want to generate the share URL for. |

## Function Output

| | |
|---|---|
| sharelink | The URL which the user will be presented with in the viewUserProjectsList template. |

## Online Order Generation Changes

When an order that originated from the Online Designer is created in Taopix Control Centre, an event is used to trigger dbconvproc within Taopix Online. dbconvproc then generates the production order files and transfers them back to Taopix Control Centre.

If the Online project has been created using the standard non-API method, it will already be assigned to a Taopix user.

However, if the Online project has been created using the API, then it could still be assigned to a guest user.

To prevent ordered projects from being mis-identified as guest projects and thus purged, there is a need for the project needs to be automatically re-assigned to a Taopix user.

## Potential User Actions / Data Flow With E-Commerce Integration API

1. User creates new project via product selector
    - External system calls CreateProject2 API and stores data in it's own project list.
    - If the user adds to the cart and the flight-check passes then the external system will add the project to their basket.
    - If the user does not add to the cart the project will remain in the external system's project list.
2. User edits project in external system's basket
    - External system calls EditProject API and on success removes the project from the basket and back into the project list.
    - If the user adds to the cart and the flight-check passes then the external system will add the project to their basket.
    - If the user does not add to the cart the project will remain in the external system's project list.
3. User edits project in external system's project list
    - External system calls EditProject API and on success removes the project from the basket and back into its project list.
    - If the user adds to the cart and the flight-check passes then the external system will add the project to their basket.
    - If the user does not add to the cart the project will remain in the external system's project list.
4. User duplicates project in basket
    - External system calls DuplicateProject API and on success adds the project into it's project list.
    - If the user adds to the cart and the flight-check passes, then the external system will add the project to their basket.
    - If the user does not add to the cart the project will remain in the external system's project list.
5. User removes project from basket
    - External system will remove the project from it's basket and back into its project list.
6. User checks-out in external system and confirms order

- External system would use Taopix DataAPI to insert order + new APIs to associate projects with user before triggering the order.

## Notifications from Taopix Control Centre

The E-Commerce Integration (Low Level) API now has the ability to receive project updates when certain user actions have occurred. Notifications will occur when a project has been saved for the first time, renamed or a user has changed the product within the Taopix Online designer.

When the TAOPIX_CCNOTIFICATION task in Control Centre runs notifications are then relayed to the *projectNotifications* function within the EDL_ONLINEBASKETAPI.php.

The *projectNotifications* function receives an array in the following format. This data can then be used by a third party system to update their systems with the new project data.

```
Array
(
    [0] => Array
        (
            [id] => 53
            [datecreated] => 2016-07-15 13:52:57
            [target] => LLAPI
            [action] => SAVEPROJECT
            [data] => Array
                (
                    [projectref] => 74_1462366365
                )

        )

    [1] => Array
        (
            [id] => 54
            [datecreated] => 2016-07-15 13:52:57
            [target] => LLAPI
            [action] => RENAMEPROJECT
            [data] => Array
                (
                    [projectref] => 74_1462366365
                    [newprojectname] => This is a new project name
                )

        )

      [1] => Array
        (
            [id] => 54
            [datecreated] => 2016-07-15 13:52:57
            [target] => LLAPI
            [action] => CHANGEPRODUCT
            [data] => Array
                (
                    [projectref] => 74_1462366365
                    [productcode] => A4LANDSCAPEHARD
                    [productname] => A4 Landscape Hard Cover
                )

        )
)
```