Taopix Multiline Basket API

Version 2.0.11

Author: Taopix R&D

Date: 20/10/2021

File: Taopix Multiline Basket API Manual_2021r3.1_October 2021.docx

Revision History

24th April 2019	V2.0.7	Revision history added.
18th September 2019	V2.0.7	Multiline example files updated due to bug fixes
5th December 2019	V2.0.8	Added functionality to share saved projects.
8th October 2020	V2.0.9	Multiline example files updated due to bug fixes
2nd November 2020	V2.0.10	Added the project preview thumbnail URL is returned by tpxHighLevelGetBasketContentsView. Multiline example files updated to display project preview thumbnail in basket and projects list
20th October 2021	V2.0.11	Added details for purge date & keep project

Table of Contents

Revision History 2

Introduction 5

Installation 6

Converting original style product URLs to Multiline Basket Product URLs 7

Single Sign-On Support 8

Initialising the Basket 9

tpxHighLevelBasketInitialise() 9

Create Project 10

tpxHighLevelCreateProjectControl(pURLParams) 10

tpxHighLevelCreateProjectView(pJsonResponseObject) 18

Edit Project 19

tpxHighLevelEditProjectControl(pProjectRef, pCanUnlock, pForceKill) 19

tpxHighLevelEditProjectView(pJsonResponseObject) 22

Rename Project 23

tpxHighLevelRenameProjectControl(pItemID, pProjectRef, pFromProjectList) 23

tpxHighLevelRenameProjectView(pJsonResponseObject, pFromProjectList) 24

Duplicate Project 25

tpxHighLevelDuplicateProjectControl(pProjectRef, pCurrentProjectName) 25

tpxHighLevelDuplicateProjectView(pJsonResponseObject) 26

Delete Project 27

tpxHighLevelDeleteProjectControl(pItemID, pProjectRef, pProjectName, pCanUnlock, pForceKill) 27

tpxHighLevelDeleteProjectView(pJsonResponseObject) 29

Share Project 30

tpxHighLevelShareProjectControl (pProjectRef) 30

tpxHighLevelShareProjectView (pJsonResponseObject) 30

Keep Project 31

tpxHighLevelKeepProjectControl (pProjectRef) 31

tpxHighLevelKeepProjectView (pJsonResponseObject) 31

Get Project List 32

tpxHighLevelGetProjectListControl() 32

tpxHighLevelGetProjectListView(pJsonResponseObject) 32

Get Basket Contents 34

tpxHighLevelGetBasketContentsControl() 34

tpxHighLevelGetBasketContentsView(pJsonResponseObject) 35

Remove Item from Basket 36

tpxHighLevelRemoveItemFromBasketControl(pItemID, pProjectRef) 36

tpxHighLevelRemoveItemFromBasketView(pJsonResponseObject) 37

Empty Basket **38**
tpxHighLevelEmptyBasketControl() 38
tpxHighlevelEmptyBasketView(pJsonResponseObject) 38
Checkout **39**
tpxHighLevelCheckoutControl() 39
tpxHighLevelCheckoutView(pJsonResponseObject) 39
Sign In **40**
tpxHighLevelSignInInitControl() 40
tpxHighLevelSignInInitView (pJsonResponseObject) 40
Registering **41**
tpxHighLevelRegisterInitControl() 41
tpxHighLevelRegisterInitView(pJsonResponseObject) 41
My Account **42**
tpxHighLevelMyAccountInitControl() 42
tpxHighLevelMyAccountInitView(pJsonResponseObject) 42
Logout **43**
tpxHighLevelLogoutControl() 43
tpxHighLevelLogoutView(pJsonResponseObject) 43
Is the User Signed In? **44**
tpxHighLevelLoggedInStatusCallBack(pIsSignedIn) 44
Localising the Basket **45**
tpxHighLevelBasketLocalise() 45
Internal Functions **46**

Introduction

The Taopix Multiline Basket API is appropriate for licensees who want to allow end-users to buy multiple Taopix products in the same order and checkout via the Taopix Shopping Cart or an external Shopping Cart*.

The API provides functionality that allows end-users to add Taopix projects to a basket and gives licensees the ability to include a basket feature in their website where the user can review their order and checkout.

It also includes functionality to give end-users the ability to continue editing, rename, duplicate or delete any projects they have created, all from within the licensee's website.

In order for a licensee to make use of the Taopix Multiline Basket API v2.0.11 they must be running at least Taopix version 2021r3.1.

** Integration with an external shopping cart requires use of the Taopix External Shopping Cart API.*

Please note: The Taopix External Shopping Cart API is a licensable feature within Taopix Control Centre that allows the built-in shopping cart to be bypassed and replaced by an external shopping cart. As each external shopping cart will perform differently it is not possible to build a direct link within Taopix Control Centre. Instead, an API is available within Taopix Control Centre that will allow 3rd party integrators to link the two systems together.

Installation

With the Taopix 2020r1 release there is a JavaScript file that must be included into the head of the licensee's website or product selector. The JavaScript file provided is the tpxMultilineBasketAPI.js. This JavaScript file contains core functions that are needed in order to interact with the API.

In the Taopix 2020r1 Control Centre version there is a configuration file called onlinebaskethighlevelapi.conf.example.

This file can be found in the following folder: MediaAlbumWeb/config/

Once all of the parameters within the file have been modified the file needs renamed to onlinebaskethighlevelapi.conf. Failure to do this will prevent the Multiline Basket API from working.

As well as the Javascript file there is also a PHP file provided called EDL_OnlineHighLevelBasketAPI.php. This is an optional file that can be included into the Taopix Control Centre folder structure. This gives the licensee more control of the parameters used in certain API calls. For example, when creating a project if the EDL_OnlineHighLevelBasketAPI.php file is present in the Control Centre folder structure then all parameters that are used for creating the project will be passed to the createProject function within the EDL_OnlineHighLevelBasketAPI.php file. The createProject function within the EDL_OnlineHighLevelBasketAPI.php can then modify and return the parameters. It will be these values that Taopix will use when performing any validation / creating the project.

To make use of the EDL_OnlineHighLevelBasketAPI.php file it needs to be copied to the following folder: MediaAlbumWeb/customise/scripts.

Each core JavaScript function has a control and a view. For example, there is a function that deals with handling the creation of a new project.

In this example it would be the tpxHighLevelCreateProjectControl function. The view function that relates to this control function is the tpxHighLevelCreateProjectView function. This view functions are to be used by the licensee so that they can process and format data returned via the Taopix Multiline Basket API requests.

In order for the control functions to process the request they call a protected JavaScript function. This function is called tpxHighLevelProcessRequest. This function deals with the communication between the product selector and Taopix Control Centre. This function should not be modified. Each control function must call the tpxHighLevelProcessRequest function with two parameters. The first parameter is the name of the calling function and the second is a param array.

Converting original style product URLs to Multiline Basket Product URLs

With the Taopix 2020r1 release there is also an html file provided named hlcreate.html. This should be placed on your web server in the same directory as your product selector webpages. This file is needed in order to convert any previously published original style product URLS to become compatible with the Multiline Basket API product URL format. They are converted at the time they are invoked from the product selector.

The file does not have to be named hlcreate.html however the HIGHLEVELBASKETAPIREDIRECTPAGE variable in the onlinebaskethighlevelapi.conf should reflect its name.

Single Sign-On Support

Within the tpxMultilineBasketAPI.js file there has been two new global variables added which are needed in order for the Multi Line Basket API to support Single Sign-On. These are gSSOEnabled and gSSOToken.

Three new constants have also been added which can be used to set the value of the new gSSOEnabled variable.

gSSOEnabled	This variable currently defaults to the constant kSSOOff. However, it can take the value of one of the three constants below: kSSOOff – Single Sign-On not implemented. Normal Taopix User Authentication will occur via Taopix Control Centre. kSSOSignIn – Single Sign-On implemented in conjunction with the Sign In functionality this API offers. This means Single Sign-On authentication will occur via a third party system after a user has clicked the Sign In button on the product selector/website. kSSOAutomatic - Single Sign-On implemented without the Sign In functionality provided by this API. This means that Signle Sign-On authentication will occur via a third party system every time the product selector/website loads.
gSSOToken	The ssoToken variable is a variable which allows you to store any token information you might want to make visible to Taopix which identifies your session with your system. This data is never read by Taopix code but is stored against the session record and is provided to the Taopix Online system upon creating or editing a project. This token is also passed on to the Library Link API to allow for Single Sign-On authentication to work for any asset management systems. As the ssoToken will be displayed in Javascript code make sure the data within is not sensitive data which should not be exposed. Currently we do not support the ssoToken expiring so it is important to make sure that the lifespan of the token is unlimited or you are able to increase it when needed.

For more information regarding Single Sign-on please refer to the Taopix External Customer Account Scripting v5.0 document.

Initialising the Basket

tpxHighLevelBasketInitialise()

This JavaScript function deals with initialising the basket for that browser session. This function should be called by the body onLoad event on the product page. If it is not called each time the document loads then the Taopix Multiline Basket may not function correctly.

This function deals with creating cookies that enable the basket API to function correctly. This is a private function and should not be modified in anyway.

Create Project

tpxHighLevelCreateProjectControl(pURLParams)

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with creating a basket for the end user as well starting a design session for a new project.

Key Input Parameters

Name	Information	Mandatory
pURLParams	This is a string of URL GET parameters. The string must contain the id parameter and its encrypted value. This can be taken from an existing Taopix Online Product URL.	Y

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
id	Should be populated with the value of pURLParams	Y
ssoenabled	Indicates whether or not Single Sign-On is Enabled.	Y

Code example

```
var paramArray = new Object();
paramArray['id'] = pURLParams;
paramArray['ssoenabled'] = gSSOEnabled;
tpxHighLevelProcessRequest('tpxHighLevelCreateProjectControl', true,
paramArray, {});
```

Invoking this API will execute the existing code which decrypts the product URL into its various components: collection code, layout code, group code etc....

However, before continuing to process the request it will call the CreateProject function within EDL_ EDL_OnlineHighLevelBasketAPI.php. This function will receive the decoded parameters and will allow the function to modify and return them. It will be these values that Taopix will use when performing any validation / creating the project.

Function Input

langcode	The language that the Online Designer / initialisation error messages should appear in.
brandcode	The Taopix Brand code if one could be determined from the API input.
groupcode	The Taopix License Key code if one could be determined from the API input.
groupdata	The optional groupdata tracking data if one has been provided on the URL.
collectioncode	The Taopix Product Collection code from the encrypted URL data.
layoutcode	The Taopix Product Layout code from the encrypted URL data.
guestworkflowmode	If the Licence Key is available then the final guestworkflowmode (based on License Key & *gwm* parameter). If the License Key is not available then the *gwm* parameter. If neither are set then guestworkflowmode will be disabled.
projectname	The default name for the Online project – defaults to empty.
minlife	The minimum life of the project in days – defaults to 0. This will be stored against the project so that anything that touches the project can update the purge date.

checkoutname	The name of the button associated with the Order button – defaults to empty.
abandonurl	The URL that can be used to invoke a back / abandon option within the Online Designer – defaults to empty. External content for online designer must be enabled.
abandonname	The name of the button associated with the abandon URL – defaults to empty. External content for online designer must be enabled.
cansignin	Specifies if the user can sign-in within the Online Designer – defaults to 1. If the user is not allowed to sign-in then all sign-in related functions must be removed from the GUI. If the project belongs to a guest then all functions that require a sign-in user (ie: pictures from existing projects) must also be removed.
cansignout	Specifies if the user can sign-out within the Online Designer - defaults to 1.
disablebackbutton	Specifies if clicking the browser back button within the Online Designer should be prevented – defaults to 0.
smallscreenwizardmode	Specifies the wizard mode on a small screen. Value determined by the setting on the URL or the brand 0 – The product will open using the wizard mode set within the product in Taopix Creator 2 – The product will open on mobile devices using the Replace Layout wizard mode 3 – The product will open on mobile devices using the Keep Layout wizard mode - defaults to -1.

largescreenwizardmode	Specifies the wizard mode on large screen. Value determined by the setting on the URL **0** – The product will open using the wizard mode option set to Off (non wizard product) **1** – The product will open on large screen devices using the Picture Selection only wizard mode **2** – The product will open on large screen devices using the Replace Layout wizard mode **3** – The product will open on large screen devices using the Keep Layout wizard mode - defaults to -1.
devicesettings	Value determined by detection of users device
enableswitchingeditor	Specifies if the Switch To Easy/Advanced editor option will show on large screen . Value determined by the setting on the URL **0** – The project will not display the Switch option **1** – The project will display the Switch option - defaults to -1.
onlineeditormode	Specifies if the editor opens in either Easy or Advanced editor. Value determined by the setting on the URL **0** – Easy Editor **1** – Advanced Editor -defaults to -1
onlinedesignerlogolinkurl	The Online Designer logo link URL is where the user is directed when they click the logo in the Online Designer. Defaults to setting in brand or license key

onlinedesignerlogolinktooltip	The logo tool tip is the tooltip that appears when the end user hovers over the logo in the Online Designer. Defaults to setting in brand or license key
pagestyle	Specify which layout will be applied to pages during the creation process. This parameter is passed only if the parameter is part of an encrypted URL Data Read Taopix Modify Project Creation v2.0 for more details.
txt_xxxx	Specify which tags will be replaced by a text value during the creation process. xxxx is the tag name from Taopix Creator and cannot contain txt_. This parameter is passed only if the parameter is part of an encrypted URL Data Read Taopix Modify Project Creation v2.0 for more details.

Function Output

Name	Information	Modify
result	empty to continue or a localized error message to return.	Y
langcode	The language that the Online Designer / initialisation error messages should appear in.	Y
brandcode	Same as function input.	N
groupcode	The Taopix License Key code for the project.	Y
groupdata	The optional groupdata tracking data.	Y

collectioncode	The Taopix Product Collection code for the project.	Y
layoutcode	The Taopix Product Layout code for the project.	Y
guestworkflowmode	The Taopix guest workflow mode override setting.	Y
projectname	The default name for the Online project.	Y
minlife	The minimum life of the project in days.	Y
checkoutname	The name of the button associated with the Order button in Taopix multi-lingual string format. If this is empty then the default name is used.	Y
abandonurl	The URL that can be used to invoke a back / abandon option within the Online Designer.	Y
abandonname	The name of the button associated with the abandon URL in Taopix multi-lingual string format.	Y
cansignin	Specifies if the user can sign-in within the Online Designer.	Y
cansignout	Specifies if the user can sign-out within the Online Designer.	Y
disablebackbutton	Specifies if clicking the browser back button within the Online Designer should be prevented.	Y
onlinedesignerlogolinkurl	The URL that clicking the Online Designer logo will take the user.	Y
onlinedesignerlogolinktooltip	Tool tip text in Taopix multi-lingual string format that appears when the user hovers their mouse over the Online Designer	Y

	logo. Will only appear if onlinedesignerlogolinkurl is set.	
smallscreenwizardmode	Specifies the wizard mode on a small screen. Value determined by the setting on the URL or the brand 0 – The product will open using the wizard mode set within the product in Taopix Creator 2 – The product will open on mobile devices using the Replace Layout wizard mode 3 – The product will open on mobile devices using the Keep Layout wizard mode - defaults to -1.	Y
largescreenwizardmode	Specifies the wizard mode on large screen. Value determined by the setting on the URL 0 – The product will open using the wizard mode option set to Off (non wizard product) 1 – The product will open on large screen devices using the Picture Selection only wizard mode 2 – The product will open on large screen devices using the Replace Layout wizard mode 3 – The product will open on large screen devices using the Keep Layout wizard mode - defaults to -1.	Y
enableswitchingeditor	Specifies if the Switch To Easy/Advanced editor option will show on large screen . Value determined by the setting	

	on the URL 0 – The project will not display the Switch option 1 – The project will display the Switch option - defaults to -1.	
onlineeditormode	Specifies if the editor opens in either Easy or Advanced editor. Value determined by the setting on the URL 0 – Easy Editor 1 – Advanced Editor -defaults to -1	Y
onlinedesignerlogolinkurl	The Online Designer logo link URL is where the user is directed when they click the logo in the Online Designer	Y
onlinedesignerlogolinktooltip	The logo tool tip is the tooltip that appears when the end user hovers over the logo in the Online Designer. Defaults to setting in brand or license key	Y
pagestyle	Specify which layout will be applied to pages during the creation process. This parameter needs to respect a specific format. Read Taopix Modify Project Creation v2.0 for more details.	N
txt_xxxx	Specify which tags will be replaced by a text value during the creation process. xxxx is the tag name from Taopix Creator and cannot contains	N

	txt_. Read Taopix Modify Project Creation v2.0 for more details.	

tpxHighLevelCreateProjectView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelCreateProjectControl API call response (pJsonResponseObject) in a JSON format. Before this function is called a basket cookie would have been created if one did not exists. The value of the cookie is a unique basketref.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
brandcode	The Taopix Brand code for the project.
groupcode	The Taopix License Key code for the project.
groupdata	The optional groupdata tracking data.
collectioncode	The Taopix Product Collection code for the project.
collectionname	The Taopix Product Collection name for the project.
productcode	The Taopix Product code for the project.
layoutname	The Taopix Product Layout name for the project.
projectref	The Online Project Ref.
projectname	The Online Project name.
designurl	The URL to the Taopix Online Designer.

Edit Project

tpxHighLevelEditProjectControl(pProjectRef, pCanUnlock, pForceKill)

This JavaScript function will call Taopix Control Centre to make the API request.

This API starts a design session for an existing project based on the given project ref.

Key Input Parameters

Name	Information	Mandatory
pProjectRef	The Online Project Ref.	Y
pCanUnlock	Can a locked project be unlocked when performing this operation?	Y
pForceKill	Used to forcekill design sessions and shopping cart sessions	Y

Invoking this API will execute the existing code which starts the continue editing process.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
projectref	The Taopix Online project ref	Y
forcekill	Used to forcekill design sessions and shopping cart sessions 0 = Design or shopping cart sessions should not be killed. 1 = Force design or shopping cart sessions to be killed/	Y
canunlock	Can a locked project be unlocked when performing this operation? 0 = Project cannot be unlocked. 1 = Project can be unlocked.	Y

ssoenabled	Indicates whether or not Single Sign-On is Enabled.	Y

Code example

```
var paramArray = new Object();
paramArray['projectref'] = pProjectRef;
paramArray['forcekill'] = pForceKill;
paramArray['canunlock'] = pCanUnlock;
paramArray['ssoenabled'] = gSSOEnabled;

tpxHighLevelProcessRequest(tpxHighLevelEditProjectControl, true,
paramArray, {});
```

However, the first task that the request will do is call the EditProject function within EDL_ EDL_OnlineHighLevelBasketAPI.php. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform the validation and design session initialisation.

Function Input

langcode	The language that the Online Designer / initialisation error messages should appear in.
projectref	The Online Project Ref.
canunlock	Can a locked project be unlocked when performing this operation – defaults to 0 if the input parameter is not present.
minlife	The new minimum number of days to purge the project after - defaults to -1 which means use the existing value in the project. Assigning this will calculate a new purgedate.
checkoutname	The name of the button associated with the Order button – defaults to empty.
abandonurl	The URL that can be used to invoke a back / abandon option within the Online Designer – defaults to

	empty.
abandonname	The name of the button associated with the abandon URL – defaults to empty.
disablebackbutton	Specifies if clicking the browser back button within the Online Designer should be prevented – defaults to 0.

Function Output

Name	Information	Modify
result	empty to continue or a localized error message to return.	Y
langcode	The language that the Online Designer / initialisation error messages should appear in.	Y
canunlock	Can a locked project be unlocked when performing this operation?	Y
minlife	The minimum life of the project in days.	Y
checkoutname	The name of the button associated with the Order button in Taopix multi-lingual string format. If this is empty then the default name is used.	Y
abandonurl	The URL that can be used to invoke a back / abandon option within the Online Designer.	Y
abandonname	The name of the button associated with the abandon URL in Taopix multi-lingual string format.	Y
disablebackbutton	Specifies if clicking the browser back button within the Online Designer should be prevented.	Y

onlinedesignerlogolinkurl	The URL that clicking the Online Designer logo will take the user.	Y
onlinedesignerlogolinktooltip	Tool tip text in Taopix multi-lingual string format that appears when the user hovers their mouse over the Online Designer logo. Will only appear if onlinedesignerlogolinkurl is set.	Y

tpxHighLevelEditProjectView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelEditProjectControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	**Result code – Returns 0 if no error has occurred.**
resultmessage	Corresponding error message for result code.
brandcode	The Taopix Brand code for the project.
groupcode	The Taopix License Key code for the project.
groupdata	The optional groupdata tracking data.
collectioncode	The Taopix Product Collection code for the project.
collectionname	The Taopix Product Collection name for the project.
layoutcode	The Taopix Product Layout code for the project.
layoutname	The Taopix Product Layout name for the project.
projectref	The Online Project Ref.
projectname	The Online Project name.
designurl	The URL to the Taopix Online Designer.

Rename Project

tpxHighLevelRenameProjectControl(pItemID, pProjectRef, pFromProjectList)

This JavaScript function will call Taopix Control Centre to make the API request

Key Input Parameters

Name	Information	Mandatory
pItemID	The HTML element ID for the project we are renaming	Y
pProjectRef	The Online Project ref.	Y
pFromProjectList	Is the rename action attached to the project list or basket list. True = Rename action from project list. False = Rename action from basket list.	Y

Invoking this API will execute the existing code that renames the project.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
projectref	The Taopix Online project ref	Y
basketitemidtoupdate	Used to forcekill design sessions and shopping cart sessions	Y
newname	Can a locked project be unlocked when performing this operation?	Y

fromprojectlist	Is the rename action attached to the project list or basket list. True = Rename action from project list. False = Rename action from basket list.	Y

Code example

```
var paramArray = new Object();
paramArray['projectref'] = pProjectRef;
paramArray['basketitemidtoupdate'] = 1;
paramArray['newname'] = 'new project name';
paramArray['fromprojectlist'] = true;

tpxHighLevelProcessRequest(tpxHighLevelRenameProjectControl, false,
paramArray, {});
```

tpxHighLevelRenameProjectView(pJsonResponseObject, pFromProjectList)

This JavaScript function will receive the tpxHigheLevelRenameProjectControl API call response (pJsonResponseObject) in a JSON format. As well as the pJsonResponseObject parameter this function also receives the pFromProjectList parameter. This can be used to determine if we are renaming from the projectlist or the basket list.

API Output (JSON)

result	**Result code – Returns 0 if no error has occurred.**
resultmessage	Corresponding error message for result code.
newprojectname	The New Taopix Online Project Name
basketitemidtoupdate	The HTML element ID for the project we are renaming.

Duplicate Project

tpxHighLevelDuplicateProjectControl(pProjectRef, pCurrentProjectName)

This JavaScript function will call Taopix Control Centre to make the API request

Key Input Parameters

Name	Information	Mandatory
pProjectRef	The Online Project Ref.	Y
pCurrentProjectName	The name of the project that is being duplicated.	Y

Invoking this API will execute the existing code that duplicates the project.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
projectref	The Taopix Online project ref	Y
projectname	The name of the new duplicated project	Y

Code example

```
var paramArray = new Object();
paramArray['projectref'] = pProjectRef;
paramArray['projectname'] = 'new duplicated project;

tpxHighLevelProcessRequest(tpxHighLevelDuplicateProjectControl, false,
paramArray, {});
```

However, the first task that the request will do is call the duplicateProject function within EDL_ EDL_OnlineHighLevelBasketAPI.php. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform the validation and design session initialisation.

Function Input

langcode	The language that the Online Designer / initialisation error messages should appear in.
projectref	The Online Project Ref.
newname	The new Project name.

Function Output

result	empty to continue or a localized error message to return.
langcode	The language that the Online Designer / initialisation error messages should appear in.
projectref	The Online Project Ref.
projectname	The new Project name.

tpxHighLevelDuplicateProjectView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelDuplicateProjectControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
projectref	The New Taopix Online Project Ref.
projectname	The New Taopix Project Name.

Delete Project

tpxHighLevelDeleteProjectControl(pItemID, pProjectRef, pProjectName, pCanUnlock, pForceKill)

This JavaScript function will call Taopix Control Centre to make the API request

Key Input Parameters

Name	Information	Mandatory
pItemID	The HTML element ID for the project we are renaming	Y
pProjectRef	The Online Project Ref.	Y
pProjectName	The name of the online project. To be used for confirmation message purposes.	Y
pCanUnlock	Can a locked project be unlocked when performing this operation?	Y
pForceKill	Used to forcekill design sessions and shopping cart sessions	Y

Invoking this API will execute the existing code that deletes the project.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
projectref	The Taopix Online project ref	Y
forcekill	Used to forcekill design sessions and shopping cart sessions 0 = Design or shopping cart sessions should not be killed. 1 = Force design or shopping cart sessions to be killed	Y

canunlock	Can a locked project be unlocked when performing this operation? 0 = Project cannot be unlocked. 1 = Project can be unlocked.	Y
basketitemidtoremove	The HTML element ID for the project we are deleting.	Y

Code example

```
var paramArray = new Object();
paramArray['projectref'] = pProjectRef;
paramArray['forcekill'] = pForceKill;
paramArray['canunlock;'] = pCanUnlock;
paramArray['baskeetitemidtoremove'] = pItemID;

tpxHighLevelProcessRequest(tpxHighLevelDeleteProjectControl, false,
paramArray, {});
```

Invoking this API will first call the *DeleteProject* function within the *EDL_OnlineHighLevelBasketAPI.php*. This function will receive the standard parameters and will allow the function to modify and return them. It will be these values that Taopix will use to perform any validation and perform the deletion or the flagging (ie: the order is not active in production etc…).

Function Input

langcode	The language that the Online Designer / initialisation error messages should appear in.
projectref	The Taopix Online Project ref.
purgedays	The number of days to purge the project after.
canunlock	Can a locked project be unlocked when performing this operation – defaults to 0 if the input parameter is not present. 0 = Project cannot be unlocked. 1 = Project can be unlocked.

Function Output

result	empty to continue or a localized error message to return.
langcode	The language that the Online Designer / initialisation error messages should appear in.
projectref	The Taopix Online project Ref.
purgedays	The number of days to purge the project after.
canunlock	Can a locked project be unlocked when performing this operation?

The *purgedays* parameter will instruct Taopix how the projects should be deleted.

-1	The projects will be deleted immediately.
> -1	The projects will be flagged for deletion after the specific number of days.

tpxHighLevelDeleteProjectView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelDeleteProjectControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
projectref	The Taopix Online Project Ref that was deleted
basketitemidtoremove	The HTML element ID for the project we are deleting.

Share Project

tpxHighLevelShareProjectControl (pProjectRef)

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with retrieving a preview URL for a project a user wishes to share.

Key Input Parameters

Name	Information	Mandatory
pProjectRef	The Online Project Ref.	Y

Code example

```
var paramArray = new Object();
paramArray['projectref'] = pProjectRef;

tpxHighLevelProcessRequest(tpxHighLevelShareProjectControl, false,
paramArray, {});
```

tpxHighLevelShareProjectView (pJsonResponseObject)

This JavaScript function will receive the tpxHighLevelShareProjectControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
link	The share URL that allows for the online project to be opened in preview mode.

Keep Project

tpxHighLevelKeepProjectControl (pProjectRef)

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with retrieving a preview URL for a project a user wishes to share.

Key Input Parameters

Name	Information	Mandatory
pProjectRef	The Online Project Ref.	Y

Code example

```
var paramArray = new Object();
paramArray['projectref'] = pProjectRef;

tpxHighLevelProcessRequest(tpxHighLevelKeepProjectControl, false,
paramArray, {});
```

tpxHighLevelKeepProjectView (pJsonResponseObject)

This JavaScript function will receive the tpxHighLevelKeepProjectControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

status	Boolean value of the status of this request true if successful, false if failed.
projectref	Project ref for the project the keep request was made for.

Get Project List

tpxHighLevelGetProjectListControl()

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with retrieving a list of projects for a user that are not in the basket.

The only parameter that needs to be sent to the tpxHighLevelProcessRequest in this case is the method name. The second parameter should be an empty object.

Code example

```
tpxHighLevelProcessRequest(tpxHighLevelGetProjectListControl, false,
{}, {});
```

tpxHighLevelGetProjectListView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelGetProjectsListControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
basketcount	The total number of items for that project list
items	A list of projects and project data [items : projectref: The Taopix Online projectref for the project. projectname: The name of the Taopix Online project. collectioncode: The Taopix Product Collection code for the project. collectionname: The Taopix Product Collection name for the project. layoutcode: The Taopix Product Layout Code for the project. layoutname: The Taopix Product Layout Name for

	the project. projectsaved: Indicates whether or not the project has been saved by the user. 0 – Unsaved project 1 – Saved project previewthumbnail: URL to the project preview thumbnail if the project has one. layoutthumbnail: URL to the product thumbnail if one has been assigned. dateofpurge: Date this project is due to be deleted on, empty if the project is not due to be deleted.]

Get Basket Contents

tpxHighLevelGetBasketContentsControl()

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with retrieving the basket contents for the given basket ref.

The only parameter that needs to be sent to the tpxHighLevelProcessRequest in this case is the method name. The second parameter should be an empty object.

Code example

```
tpxHighLevelProcessRequest(tpxHighLevelGetBasketContentsControl,
false, {}, {});
```

tpxHighLevelGetBasketContentsView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelGetBasketContentsControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
basketcount	The total number of items for that basket
items	A list of projects and project data [items : projectref: The Taopix Online Project ref. projectname: The name of the Taopix Online project. collectioncode: The Taopix Product Collection code for the project. collectionname: the Taopix Product Collection name for the project. layoutcode: The Taopix Product Layout Code for the project. layoutname: The Taopix Product Layout Name for the project. projectpreviewthumbnail: URL to the project preview thumbnail if the project has one. layoutthumbnail: URL to the product thumbnail if one has been assigned.]

Remove Item from Basket

tpxHighLevelRemoveItemFromBasketControl(pItemID, pProjectRef)

This JavaScript function will call Taopix Control Centre to make the API request

Key Input Parameters

Name	Information	Mandatory
pItemID	The HTML element ID for the project we are renaming	Y
pProjectRef	The Online Project Ref.	Y
pForceKill	Used to forcekill design sessions and shopping cart sessions	Y

Invoking this API will execute the code that removes the project from a users basket.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
projectref	The Taopix Online project ref	Y
itemtoremoveid	The name of the new duplicated project	Y
forcekill	Used to forcekill design sessions and shopping cart sessions 0 = Design or shopping cart sessions should not be killed. 1 = Force design or shopping cart sessions to be killed	Y

Code example

```
var paramArray = new Object();
paramArray['projectref'] = pProjectRef;
paramArray[' itemtoremoveid'] = pItemID
paramArray[' forcekill] = pForceKill


tpxHighLevelProcessRequest(tpxHighLevelRemoveItemFromBasketControl,
false, paramArray, {});
```

tpxHighLevelRemoveItemFromBasketView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelRemoveItemFromBasketControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.

Empty Basket

tpxHighLevelEmptyBasketControl()

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with emptying the basket for the given basket ref.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
forcekill	Used to forcekill design sessions and shopping cart sessions 0 = Design or shopping cart sessions should not be killed. 1 = Force design or shopping cart sessions to be killed	Y

Code example

```
var paramArray = new Object();
paramArray[' forcekill'] = 0;

tpxHighLevelProcessRequest(tpxHighLevelEmptyBasketControl, false,
paramArray, {});
```

tpxHighlevelEmptyBasketView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelEmptyBasketControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

Result	Result code – Returns 0 if no error has occurred.
Resultmessage	Corresponding error message for result code.

Checkout

tpxHighLevelCheckoutControl()

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with retrieving the basket contents for checkout for the given basket ref and redirecting the user to the Taopix Shopping Cart or an external cart if the External Cart API is being utilized.

The only parameter that needs to be sent to the tpxHighLevelProcessRequest in this case is the method name. The second parameter should be an empty object.

Code example

```
var paramArray = new Object();
paramArray['ssoenabled'] = gSSOEnabled;
tpxHighLevelProcessRequest(tpxHighLevelCheckoutControl, true,
paramArray, {});
```

tpxHighLevelCheckoutView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelRemoveItemFromBasketControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
shoppingcarturl	The URL to the Taopix Shopping cart or an external shopping cart if used in conjuction with the External Shopping Cart API

Sign In

tpxHighLevelSignInInitControl()

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with retrieving a signin URL for a user to be redirected to.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
groupcode	A valid Taopix Control Centre License Key Code. This should be the license key the user is signing in against.	Y
ssoenabled	Indicates whether or not Single Sign-On is Enabled.	Y

Code example

```
var paramArray = new Object();
paramArray['groupcode'] = 'MYTESTGROUPCODE';
paramArray['ssoenabled'] = gSSOEnabled;
```

Code example

```
tpxHighLevelProcessRequest(tpxHighLevelSignInInitControl, true,
paramArray, {});
```

tpxHighLevelSignInInitView (pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelSignInInitControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
signinurl	The URL to the Taopix Control Centre Signin Page.

Registering

tpxHighLevelRegisterInitControl()

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with retrieving a register URL for a user to be redirected to.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
groupcode	A valid Taopix Control Centre License Key Code. This should be the license key the user is registering against.	Y

Code example

```
var paramArray = new Object();
paramArray['groupcode'] = 'MYTESTGROUPCODE';
```

Code example

```
tpxHighLevelProcessRequest(tpxHighLevelRegisterInitControl, false,
paramArray, {});
```

tpxHighLevelRegisterInitView(pJsonResponseObject)

This JavaScript function will receive the tpxHighLevelRegisterInitControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
signinurl	The URL to the Taopix Control Centre Register/Sign In Page.

My Account

tpxHighLevelMyAccountInitControl()

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with retrieving a redirect URL so a user can be redirected to their account pages within Taopix Control Centre.

tpxHighLevelProcessRequest function call parameters

Name	Information	Mandatory
groupcode	A valid Taopix Control Centre License Key Code. This should be a license key code assigned to the current brand.	Y

Code example

```
tpxHighLevelProcessRequest(tpxHighLevelMyAccountInitControl, false,
{}, {});
```

tpxHighLevelMyAccountInitView(pJsonResponseObject)

This JavaScript function will receive the tpxHighLevelMyAccountInitControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.
myaccounturl	The URL to the Taopix Control Centre My Account Page.

Logout

tpxHighLevelLogoutControl()

This JavaScript function will call Taopix Control Centre to make the API request.

This API request deals with killing the bsket session within the Taopix Control Centre Database. It is also responsible for removing the basket cookie stored in the users browser.

The only parameter that needs to be sent to the tpxHighLevelProcessRequest in this case is the method name. The second parameter should be an empty object.

Code example

```
tpxHighLevelProcessRequest(tpxHighLevelLogoutControl, false, {}, {});
```

tpxHighLevelLogoutView(pJsonResponseObject)

This JavaScript function will receive the tpxHigheLevelLogoutControl API call response (pJsonResponseObject) in a JSON format.

API Output (JSON)

result	Result code – Returns 0 if no error has occurred.
resultmessage	Corresponding error message for result code.

Is the User Signed In?

tpxHighLevelLoggedInStatusCallBack(pIsSignedIn)

This JavaScript function is designed for licensee's to use in order to update the DOM of the product selector/website to either show the SignIn and Register buttons or the My Account and Logout buttons.

This function is called when the *tpxHighLevelBasketInitialise*() is called on the page load. It is also suggested that this function be called from the *tpxHighLevelLogoutView* function when the user has logged out.

Function Input

pIsSignedIn	0 - User is no longer signed in. 1 - User is currently signed in.

Localising the Basket

tpxHighLevelBasketLocalise()

This JavaScript function is designed for licensee's who want to show a localised version of the basket using the supplied Taopix Multilingual strings.

This function is called when the *tpxHighLevelBasketInitialise*() is called on the page load.

Internal Functions

Within the tpxMultilineBasketAPI.js file, there are a series of functions which have not been documented above as they are Taopix Internal functions. These are functions that are private to Taopix and should not be modified in anyway.

Internal Functions

Name	Description
tpxGetBrowserLocale	Determine the browser locale from the browser.
tpxGetLocaleString	Returns the correct language string.
tpxGetXMLHTTP	Returns a XMLHttpRequest object.
tpxReadCookie	Returns the value of a cookie.
tpxGenerateID	Generates Unique ID.
tpxCreateMAWHLUIDCookie	Creates the *mawhluid* cookie.
tpxIsEmpty	Determines if a given object is empty.
tpxParamString	Substitutes parameter place holders (^0) in a given string with parameters.