



Section Cheat Sheet (PPT)

Model-View-Controller (MVC) Pattern

"Model-View-Controller" (MVC) is an architectural pattern that separates application code into three main components: Models, Views and Controllers.



1. Controller invokes Business Model.
2. Controller creates object of View Model.
3. Controller invokes View.
4. View accesses View Model.

Responsibilities of Model-View-Controller

Controller

- Receives HTTP request data.
- Invoke business model to execute business logic.

Business Model

- Receives input data from the controller.
- Performs business operations such as retrieving / inserting data from database.
- Sends data of the database back to the controller.

Controller

- Creates object of ViewModel and files data into its properties.
- Selects a view & invokes it & also passes the object of ViewModel to the view.

View

- Receives the object of ViewModel from the controller.
- Accesses properties of ViewModel to render data in html code.

- After the view renders, the rendered view result will be sent as response.


Benefits / Goals of MVC architectural pattern

- Clean separation of concerns
- Each component (model, view and controller) performs single responsibility.
- Identifying and fixing errors will be easy.
- Each component (model, view and controller) can be developed independently.
- In practical, both view and controller depend on the model.
- Model doesn't depend on neither view nor the controller.
- This is one of the key benefits of the 'clean separation'.
- This separation allows the model to be built and tested independently.
- Unit testing each individual component is easier.

Views

View is a web page (.cshtml) that is responsible for containing presentation logic that merges data along with static design code (HTML).

- Controller creates an object of ViewModel and fills data in its properties.
- Controller selects an appropriate view and invokes the same view & supplies object of ViewModel to the View.
- View access the ViewModel.



- View contains HTML markup with Razor markup (C# code in view to render dynamic content).
- Razor is the view engine that defines syntax to write C# code in the view. @ is the syntax of Razor syntax.
- View is NOT supposed to have lots of C# code. Any code written in the view should relate to presenting the content (presentation logic).
- View should neither directly call the business model, nor call the controller's action methods. But it can send requests to controllers.

Razor View Engine

Razor Code Block

```
1 | @{  
2 |  
3 |     C# / html code here  
4 |  
5 | }
```

Razor code block is a C# code block that contains one or more lines of C# code that can contain any statements and local functions.

Razor Expressions

```
1 | @Expression
2 | --or--
3 | @(Expression)
```

Razor expression is a C# expression (accessing a field, property or method call) that returns a value.

Razor - If

```
1 | @if (condition) {
2 |     C# / html code here
3 | }
```

Razor - if...else

```
1 | @if (condition) {
2 |     C# / html code here
3 | }
4 | else {
5 |     C# / html code here
6 | }
```

Else...if and nested-if also supported.

Razor - Switch

```
1 | @switch (variable) {
2 |     case value1: C# / html code here; break;
3 |     case value2: C# / html code here; break;
4 |     default: C# / html code here; break;
5 | }
```

Razor - foreach

```
1 | @foreach (var variable in collection ) {
2 |     C# / html code here
3 | }
```

Razor - for

```
1 | @for (initialization; condition; iteration) {  
2 |     C# / html code here  
3 | }
```

Razor - Literal

```
1 | @{  
2 |     @: static text  
3 | }
```

Razor - Literal

```
<text>static text</text>
```

Razor - Local Functions

```
1 | @{  
2 |     return_type method_name(arguments) {  
3 |         C# / html code here  
4 |     }  
5 | }
```

The local functions are callable within the same view.

Razor - Members

Razor - Methods, Properties, Fields

```
1 | @functions {  
2 |     return_type method_name(arguments) {  
3 |         C# / html code here  
4 |     }  
5 |  
6 |     data_type field_name;  
7 |  
8 |     data_type property_name  
9 |     {  
10 |         set { ... }  
11 |         get { ... }  
12 |     }
```

The members of razor view can be accessible within the same view.

Html.Raw()

```


1 | @{
2 |     string variable = "html code";
3 | }
4 |
5 | @Html.Raw(variable) //prints the html markup without encoding
   (converting html tags into plain text)

```

ViewData

ViewData is a dictionary object that is automatically created up on receiving a request and will be automatically deleted before sending response to the client.

It is mainly used to send data from controller to view.



ViewData is a property of Microsoft.AspNetCore.Mvc.Controller class and Microsoft.AspNetCore.Mvc.Razor.RazorPage class.

It is of Microsoft.AspNetCore.Mvc.ViewFeatures.ViewDataDictionary type.

```

1 | namespace Microsoft.AspNetCore.Mvc
2 | {
3 |     public abstract class Controller : ControllerBase
4 |     {
5 |         public ViewDataDictionary ViewData { get; set; }

```

```
6 |   }  
7 |   }
```

- It is derived from `IDictionary<KeyValuePair<string, object>>` type.
- That means, it acts as a dictionary of key/value pairs.
- Key is of string type.
- Value is of object type.


ViewData - Properties and Methods

- `int Count { get; set; }` //gets the number of elements.
- `[string Key]` //Gets or sets an element.
- `Add(string key, object value)` //Adds a new element.
- `ContainsKey(string key)` //Determines whether the specified key exists or not.
- `Clear()` //Clears (removes) all elements.

ViewBag

ViewBag is a property of Controller and View, that is used to access the ViewData easily.

ViewBag is 'dynamic' type.



ViewBag is a property of `Microsoft.AspNetCore.Mvc.Controller` class and `Microsoft.AspNetCore.Mvc.Razor.RazorPageBase` class.

It is of dynamic type.

```
1 | namespace Microsoft.AspNetCore.Mvc
2 | {
3 |     public abstract class Controller : ControllerBase
4 |     {
5 |         public dynamic ViewBag { get; set; }
6 |     }
7 | }
```

The 'dynamic' type similar to 'var' keyword.

But, it checks the data type and at run time, rather than at compilation time.

If you try to access a non-existing property in the ViewBag, it returns null.

```
[string Key] //Gets or sets an element.
```

Benefits of 'ViewBag' over ViewData

ViewBag's syntax is easier to access its properties than ViewData.

Eg: `ViewBag.property` [vs] `ViewData["key"]`

You need NOT type-cast the values while reading it.

Eg: `ViewBag.object_name.property`


[vs]

`(ViewData["key"] as ClassName).Property`

Strongly Typed Views

Strongly Typed View is a view that is bound to a specified model class.

It is mainly used to access the model object / model collection easily in the view.



Benefits of Strongly Typed Views

- You will get Intellisense while accessing model properties in strongly typed views, since the type of model class was mentioned at @model directive.
- Property names are compile-time checked; and shown as errors in case of misspelled / non-existing properties in strongly typed views.

- You will have only one model per one view in strongly typed views.
- Easy to identify which model is being accessed in the view.


Helper methods in Controller to invoke a View

- `return View();` //View name is the same name as the current action method.
- `return View(object Model);` //View name is the same name as the current action method & the view can be a strongly-typed view to receive the supplied model object.
- `return View(string ViewName);` //View name is explicitly specified.
- `return View(string ViewName, object Model);` //View name is explicitly specified & the view can be a strongly-typed view to receive the supplied model object.

Strongly Typed Views

Strongly Typed View can be bound to a single model directly.


But that model class can have reference to objects of other model classes.




ViewImports.cshtml

ViewImports.cshtml is a special file in the "Views" folder or its subfolder, which executes automatically before execution of a view.

It is mainly used to import common namespaces that are to be imported in a view.






Shared Views

Shared views are placed in "Shared" folder in "Views" folder.

They are accessible from any controller, if the view is NOT present in the "Views\ControllerName" folder.



View Resolution

