

Invisible No More

Common sense visualization with ggplot

Leon Rauschning

May 1, 2025

LMU und TU Munich

Why do we visualize data?

Why do we visualize data?

When we visualize data,
we do this to **communicate** it

Thinking of plotting as a form of communication allows us to draw an analogy to languages.

A formal language can be fully described by specifying their *grammar* and *lexicon*.

Why do we care to do this?

Formally defining a grammar allows us to

Why do we care to do this?

Formally defining a grammar allows us to

- Describe plots systematically
- Understand plots we see
- Flexibly modify existing or invent new plots
- Translate our intentions to a plotting engine

Why do we care to do this?

Formally defining a grammar allows us to

- Describe plots systematically
- Understand plots we see
- Flexibly modify existing or invent new plots
- Translate our intentions to a plotting engine

It does not provide advice for making beautiful or useful plots!

Grammar of Graphics: Components

In the (layered) grammar of graphics, a plot consists of:

- Data, (Transformations)
- Aesthetics/Mappings
- Geometries
- Stats
- Scales
- Coordinates

Grammar of Graphics: Components

In the (layered) grammar of graphics, a plot consists of:

- Data, (Transformations)
- Aesthetics/Mappings
- Geometries
- Stats
- Scales
- Coordinates

These components can be swapped or altered individually, and composed to make a plot. In practice, many of these have sensible default values.

- *Base* of the plot
- A plot may integrate multiple datasets

Stat(istics)

- Usually aggregates data
- May output new/other values
- Has a default associated geom

- Usually aggregates data
- May output new/other values
- Has a default associated geom
- Examples:

- Usually aggregates data
- May output new/other values
- Has a default associated geom
- Examples:
 - Identity
 - Count
 - Mean/Median
 - Smoothing, Regressions

- Graphical primitives the plot is constructed from
- May have different modifiable attributes
- Has a default stat

- Graphical primitives the plot is constructed from
- May have different modifiable attributes
- Has a default stat
- Examples:

- Graphical primitives the plot is constructed from
- May have different modifiable attributes
- Has a default stat
- Examples:
 - Points
 - Line
 - Bars
 - Boxes

- Describes the *how* of mapping variables to aesthetics
- Controls of guides
- Can be discrete/continuous, in number/colour/other spaces

- Describes the *how* of mapping variables to aesthetics
- Controls of guides
- Can be discrete/continuous, in number/colour/other spaces
- Examples:

- Describes the *how* of mapping variables to aesthetics
- Controls of guides
- Can be discrete/continuous, in number/colour/other spaces
- Examples:
 - Linear
 - Log
 - Various colourscales
 - Binning

- Maps scale values onto plotting coordinates
- Examples:

- Maps scale values onto plotting coordinates
- Examples:
 - Cartesian, 2D/3D
 - Polar
- Commonly cartesian, polar, 3D

- Which variable gets plotted how after which transformation, and how?
- *Glue* of ggplot

**How do these components combine
to make a plot?**

Assembling a ggplot

- A plot may be multiple layers
- Each layer has one data, stat, geom and aesthetics
- These pass information along to render the plot

Assembling a ggplot

- A plot may be multiple layers
- Each layer has one data, stat, geom and aesthetics
- These pass information along to render the plot
- In practice, defaults often work well

Let's have a look at how this looks like in some plots!



ggplot2: Implementing a grammar of graphics

Now, let's make some plots ourselves!

