

Listings

1	<b>CODE HASHES</b>	1	39	Prime Sieve Mobius	16
2	hash.sh	1	40	Row Reduce	16
3	<b>GRAPHS</b>	1	41	Solve Linear Equations MOD	16
4	Bridges and Cuts	1	42	Matrix Inverse	17
5	Block Vertex Tree	2	43	Euler’s Totient Phi Function	17
6	Centroid	2	44	<b>MAX FLOW</b>	17
7	Dijkstra	3	45	Dinic	17
8	Floyd Warshall	3	46	Hungarian	18
9	HLD	3	47	Min Cost Max Flow	18
10	Hopcroft Karp	4	48	<b>MISC</b>	19
11	LCA	4	49	Disjoint Set	19
12	SCC	5	50	PBDS	19
13	<b>RANGE DATA STRUCTURES</b>	5	51	Monotonic Stack	20
14	Segment Tree	5	52	Count Rectangles	20
15	Fenwick Tree	6	53	Longest Increasing Subsequence	20
16	Sparse Table	7	54	Safe Hash	20
17	Implicit Lazy Segment Tree	7			
18	Range Updates, Point Queries	8			
19	Kth Smallest	8			
20	Number Distinct Elements	8			
21	Buckets	9			
22	Persistent Lazy Segment Tree	10			
23	Merge Sort Tree	10			
24	<b>STRINGS</b>	11			
25	Suffix Array	11			
26	Longest Common Prefix Array	12			
27	Prefix Function	12			
28	KMP	12			
29	Trie	13			
30	Binary Trie	13			
31	Longest Common Prefix Query	14			
32	<b>MATH</b>	14			
33	BIN EXP MOD	14			
34	Fibonacci	14			
35	Matrix Mult and Pow	15			
36	N Choose K MOD	15			
37	Partitions	15			
38	Derangements	16			

Listing 1: CODE HASHES

Listing 2: hash.sh

```
# Hashes a file, ignoring all whitespace, comments, and includes. Use for
# verifying that code was correctly typed.

# usage:
#   chmod u+x hash.sh
#   cat <file> | ./hash.sh
# or just copy this command:
#   cat <file> | sed -r '/^#(include|pragma)/d' | cpp -fpreprocessed -P | tr -d
#     ↳ '[:space:]' | md5sum | cut -c-6
sed -r '/^#(include|pragma)/d' | cpp -fpreprocessed -P | tr -d '[:space:]' | md5sum |
  ↳ cut -c-6
```

Listing 3: GRAPHS

Listing 4: Bridges and Cuts

```
//cat bridges_and_cuts.h | ./hash.sh
//ab1b32
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/biconnected_components,
  ↳ https://judge.yosupo.jp/problem/two_edge_connected_components
//with asserts checking correctness of isBridge and isCut
//O(n+m) time & space
//2 edge cc and bcc stuff doesn't depend on each other, so delete whatever is not needed
//handles multiple edges
//example initialization of 'adj':
//for (int i = 0; i < m; i++) {
//  int u, v;
//  cin >> u >> v;
//  u--, v--;
//  adj[u].emplace_back(v, i);
//  adj[v].emplace_back(u, i);
//}
struct info {
  //2 edge connected component stuff (e.g. components split by bridge edges)
  ↳ https://cp-algorithms.com/graph/bridge-searching.html
  int num2EdgeCCs;
  vector<bool> isBridge; //edge id -> true iff bridge edge
  vector<int> TwoEdgeCCID; //node -> ID of 2-edge component (which are labeled 0, 1,
    ↳ ..., 'num2EdgeCCs'-1)
  //bi-connected component stuff (e.g. components split by cut/articulation nodes)
  ↳ https://cp-algorithms.com/graph/cutpoints.html
  int numBCCs;
  vector<bool> isCut; //node -> true iff cut node
  vector<int> bccID; //edge id -> ID of BCC (which are labeled 0, 1, ..., 'numBCCs'-1)
};
info bridge_and_cut(const vector<vector<pair<int/*neighbor*/, int/*edge id*/>>>&
  ↳ adj/*undirected graph*/, int m/*number of edges*/) {
  //stuff for both (always keep)
  int n = adj.size(), timer = 1;
  vector<int> tin(n, 0);
  //2 edge CC stuff (delete if not needed)
  int num2EdgeCCs = 0;
```

```
vector<bool> isBridge(m, false);
vector<int> TwoEdgeCCID(n), nodeStack;
//BCC stuff (delete if not needed)
int numBCCs = 0;
vector<bool> isCut(n, false);
vector<int> bccID(m), edgeStack;
auto dfs = [&](auto self, int v, int pId) -> int {
  int low = tin[v] = timer++;
  int deg = 0;
  nodeStack.push_back(v);
  for (auto [to, eId] : adj[v]) {
    if (eId == pId) continue;
    if (!tin[to]) {
      edgeStack.push_back(eId);
      int lowCh = self(self, to, eId);
      if (lowCh >= tin[v]) {
        isCut[v] = true;
        while (true) {
          int edge = edgeStack.back();
          edgeStack.pop_back();
          bccID[edge] = numBCCs;
          if (edge == eId) break;
        }
        numBCCs++;
      }
      low = min(low, lowCh);
      deg++;
    } else if (tin[to] < tin[v]) {
      edgeStack.push_back(eId);
      low = min(low, tin[to]);
    }
  }
  if (pId == -1) isCut[v] = (deg > 1);
  if (tin[v] == low) {
    if (pId != -1) isBridge[pId] = true;
    while (true) {
      int node = nodeStack.back();
      nodeStack.pop_back();
      TwoEdgeCCID[node] = num2EdgeCCs;
      if (node == v) break;
    }
    num2EdgeCCs++;
  }
  return low;
};
for (int i = 0; i < n; i++) {
  if (!tin[i])
    dfs(dfs, i, -1);
}
return {num2EdgeCCs, isBridge, TwoEdgeCCID, numBCCs, isCut, bccID};
}
```

Listing 5: Block Vertex Tree

```
//cat block_vertex_tree.h | ./hash.sh
//8d0753
#pragma once
#include "bridges_and_cuts.h"
//library checker tests: https://judge.yosupo.jp/problem/biconnected_components
//(asserts checking correctness of commented-example-usage-loops)
```

```
//returns adjacency list of block vertex tree
//usage:
// info cc = bridge_and_cut(adj, m);
// vector<vector<int>> bvt = block_vertex_tree(adj, cc);
//to loop over each *unique* BCC containing a node i:
// for(int bccid : bvt[i]) {
//     bccid -= n;
//     ...
// }
//to loop over each *unique* node inside a BCC:
// for(int i : bvt[bccid + n]) {
//     ...
// }
vector<vector<int>> block_vertex_tree(const vector<vector<pair<int, int>>>& adj, const
    ↪ info& cc) {
    int n = adj.size();
    vector<vector<int>> tree(n + cc.numBCCs);
    vector<int> cnt(cc.numBCCs, 0);
    for (int i = 0; i < n; i++) {
        for (auto [_, eId] : adj[i]) {
            int bcc = cc.bccID[eId];
            if (cnt[bcc]++ == 0) {
                tree[i].push_back(bcc + n); // Add edge between original node, and BCC
                ↪ node
                tree[bcc + n].push_back(i);
            }
        }
        for (auto [_, eId] : adj[i])
            cnt[cc.bccID[eId]]--;
    }
    return tree;
}
```

Listing 6: Centroid

```
//cat centroid.h | ./hash.sh
//8d9ba5
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/frequency_table_of_tree_distance
//with asserts checking depth of tree <= log2(n)
//returns array 'par' where 'par[i]' = parent of node 'i' in centroid tree
//'par[root]' is -1
//0-based nodes
//O(n log n)
//example usage:
// vector<int> parent = getCentroidTree(adj);
// vector<vector<int>> childs(n);
// int root;
// for (int i = 0; i < n; i++) {
//     if (parent[i] == -1)
//         root = i;
//     else
//         childs[parent[i]].push_back(i);
// }
vector<int> getCentroidTree(const vector<vector<int>>&& adj /*unrooted tree*/) {
    int n = adj.size();
    vector<int> sizes(n);
    vector<bool> vis(n, false);
    auto dfsSz = [&](auto self, int node, int par) -> void {
        sizes[node] = 1;
```

```
        for (int to : adj[node]) {
            if (to != par && !vis[to]) {
                self(self, to, node);
                sizes[node] += sizes[to];
            }
        }
    };
    auto findCentroid = [&](int node) -> int {
        dfsSz(dfsSz, node, node);
        int sizeCap = sizes[node] / 2, par = -1;
        while (true) {
            bool found = false;
            for (int to : adj[node]) {
                if (to != par && !vis[to] && sizes[to] > sizeCap) {
                    found = true;
                    par = node;
                    node = to;
                    break;
                }
            }
            if (!found) return node;
        }
    };
    vector<int> parent(n);
    auto dfs = [&](auto self, int node, int par) -> void {
        node = findCentroid(node);
        parent[node] = par;
        vis[node] = true;
        for (int to : adj[node]) {
            if (!vis[to])
                self(self, to, node);
        }
    };
    dfs(dfs, 0, -1);
    return parent;
}
```

Listing 7: Dijkstra

```
//cat dijkstra.h | ./hash.sh
//27560a
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/shortest_path
//returns array 'len' where 'len[i]' = shortest path from node 'startNode' to node i
//For example len[startNode] will always = 0
const long long INF = 1e18;
vector<long long> dijkstra(const vector<vector<pair<int, long long>>>& adj /*directed or
    ↪ undirected, weighted graph*/, int startNode) {
    vector<long long> len(adj.size(), INF);
    len[startNode] = 0;
    set<pair<long long /*weight*/, int /*node*/>> q;
    q.insert({0LL, startNode});
    while (!q.empty()) {
        auto it = q.begin();
        int node = it->second;
        q.erase(it);
        for (auto [to, weight] : adj[node])
            if (len[to] > weight + len[node]) {
                q.erase({len[to], to});
                len[to] = weight + len[node];
            }
    }
}
```

```
        q.insert({len[to], to});
    }
    return len;
}
```

Listing 8: Floyd Warshall

```
//cat floydWarshall.h | ./hash.sh
//84799a
#pragma once
//status: not tested
/**for directed graphs only** if you initialize len[i][i] to infinity, then
//afterward floyds, len[i][i] = length of shortest cycle including node 'i'
//
//another trick: change 'len' to 2d array of *bools* where len[i][j] = true if
//there exists an edge from i -> j in initial graph. Also do:
//'len[i][j] != len[i][k] & len[k][j]'
//Then after floyds, len[i][j] = true iff there's exists some path from node
//'i' to node 'j'
//
//Changing the order of for-loops to i-j-k (instead of the current k-i-j)
//results in min-plus matrix multiplication. If adjacency matrix is M, then
//after computing M^k (with binary exponentiation), M[i][j] = min length path
//from i to j with at most k edges.
for (int k = 0; k < n; k++)
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            len[i][j] = min(len[i][j], len[i][k] + len[k][j]);
```

Listing 9: HLD

```
//cat hld.h | ./hash.sh
//ce8f71
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/lca,
//    https://judge.yosupo.jp/problem/vertex_add_path_sum,
//    https://judge.yosupo.jp/problem/vertex_add_subtree_sum
//source: https://codeforces.com/blog/entry/53170
//assumes a single tree, 1-based nodes is possible by passing in 'root' in range [1, n]
struct hld {
    int n;
    vector<int> Size, par, timeIn, Next;
    hld(vector<vector<int>>& adj /*single unrooted tree*/, int root) :
        n(adj.size()), Size(n, 1), par(n, root), timeIn(n), Next(n, root) {
        dfs1(root, adj);
        int Time = 0;
        dfs2(root, adj, Time);
    }
    void dfs1(int node, vector<vector<int>>& adj) {
        for (int& to : adj[node]) {
            if (to == par[node]) continue;
            par[to] = node;
            dfs1(to, adj);
            Size[node] += Size[to];
            if (Size[to] > Size[adj[node][0]] || adj[node][0] == par[node])
                swap(to, adj[node][0]);
        }
    }
}
```

```
void dfs2(int node, const vector<vector<int>>& adj, int& Time) {
    timeIn[node] = Time++;
    for (int to : adj[node]) {
        if (to == par[node]) continue;
        Next[to] = (Time == timeIn[node] + 1 ? Next[node] : to);
        dfs2(to, adj, Time);
    }
}
// Returns intervals (of timeIn's) corresponding to the path between u and v, not
//    necessarily in order
// This can answer queries for "is some node 'x' on some path" by checking if the
//    timeIn[x] is in any of these intervals
vector<pair<int, int>> path(int u, int v) const {
    vector<pair<int, int>> res;
    for (; v = par[Next[v]]; ) {
        if (timeIn[v] < timeIn[u]) swap(u, v);
        if (timeIn[Next[v]] <= timeIn[u]) {
            res.emplace_back(timeIn[u], timeIn[v]);
            return res;
        }
        res.emplace_back(timeIn[Next[v]], timeIn[v]);
    }
}
// Returns interval (of timeIn's) corresponding to the subtree of node i
// This can answer queries for "is some node 'x' in some other node's subtree" by
//    checking if timeIn[x] is in this interval
pair<int, int> subtree(int i) const {
    return {timeIn[i], timeIn[i] + Size[i] - 1};
}
// Returns lca of nodes u and v
int lca(int u, int v) const {
    for (; v = par[Next[v]]; ) {
        if (timeIn[v] < timeIn[u]) swap(u, v);
        if (timeIn[Next[v]] <= timeIn[u]) return u;
    }
}
};
```

Listing 10: Hopcroft Karp

```
//cat hopcroftKarp.h | ./hash.sh
//28fe68
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/bipartitematching
//with asserts checking correctness of min vertex cover
//Modified from
//    https://github.com/foreverbell/acm-icpc-cheat-sheet/blob/master/src/graph-algorithms/
//Worst case O(E*sqrt(V)) but faster in practice
struct match {
    // # of edges in matching (which = size of min vertex cover by König's theorem)
    int sizeOfMatching;
    //an arbitrary max matching is found. For this matching:
    //if ml[nodeLeft] == -1:
    //    'nodeLeft' is not in matching
    //else:
    //    the edge 'nodeLeft' <=> ml[nodeLeft] is in the matching
    //
    //similarly for mr with edge mr[nodeRight] <=> nodeRight in matching if
    //    mr[nodeRight] != -1
    //matchings stored in ml and mr are the same matching
```

```
//provides way to check if any node is in matching
vector<int> ml, mr;
//an arbitrary min vertex cover is found. For this MVC: leftMVC['left node'] is true
    ⇨ iff 'left node' is in the min vertex cover (same for rightMVC)
//if leftMVC['left node'] is false, then 'left node' is in the corresponding maximal
    ⇨ independent set
vector<bool> leftMVC, rightMVC;
};
//Think of the bipartite graph as having a left side (with size lSz) and a right side
    ⇨ (with size rSz).
//Nodes on left side are indexed 0,1,...,lSz-1
//Nodes on right side are indexed 0,1,...,rSz-1
//
//'adj' is like a directed adjacency list containing edges from left side -> right side:
//To initialize 'adj': For every edge nodeLeft <=> nodeRight, do:
    ⇨ adj[nodeLeft].push_back(nodeRight)
match hopcroftKarp(const vector<vector<int>>& adj/*bipartite graph*/, int rSz/*number of
    ⇨ nodes on right side*/) {
    int sizeOfMatching = 0, lSz = adj.size();
    vector<int> ml(lSz, -1), mr(rSz, -1);
    while (true) {
        queue<int> q;
        vector<int> level(lSz, -1);
        for (int i = 0; i < lSz; i++) {
            if (ml[i] == -1) level[i] = 0, q.push(i);
        }
        bool found = false;
        vector<bool> leftMVC(lSz, true), rightMVC(rSz, false);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            leftMVC[u] = false;
            for (int x : adj[u]) {
                rightMVC[x] = true;
                int v = mr[x];
                found |= v == -1;
                if (v != -1 && level[v] < 0) {
                    level[v] = level[u] + 1;
                    q.push(v);
                }
            }
        }
        if (!found) return {sizeOfMatching, ml, mr, leftMVC, rightMVC};
        auto dfs = [&](auto self, int u) -> bool {
            for (int x : adj[u]) {
                int v = mr[x];
                if (v == -1 || (level[u] + 1 == level[v] && self(self, v))) {
                    ml[u] = x;
                    mr[x] = u;
                    return true;
                }
            }
            level[u] = 1e9; //acts as visited array
            return false;
        };
        for (int i = 0; i < lSz; i++)
            sizeOfMatching += (ml[i] == -1 && dfs(dfs, i));
    }
}
```

Listing 11: LCA

```
//cat lca.h | ./hash.sh
//fa1e99
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/lca
//https://codeforces.com/blog/entry/74847
//assumes a single tree, 1-based nodes is possible by passing in 'root' in range [1, n]
struct lca {
    int n;
    vector<int> jmp, jmpEdges, par, depth;
    vector<long long> dist;
    lca(const vector<vector<pair<int, long long>>>& adj, int root) :
        n(adj.size()), jmp(n, root), jmpEdges(n, 1), par(n, root), depth(n, 0), dist(n,
            ⇨ 0LL) {
        dfs(root, adj);
    }
    void dfs(int node, const vector<vector<pair<int, long long>>>& adj) {
        for (auto [ch, w] : adj[node]) {
            if (ch == par[node]) continue;
            par[ch] = node;
            depth[ch] = 1 + depth[node];
            dist[ch] = w + dist[node];
            if (depth[node] > 0 && jmpEdges[node] == jmpEdges[jmp[node]])
                jmp[ch] = jmp[jmp[node]], jmpEdges[ch] = 2 * jmpEdges[node] + 1;
            else
                jmp[ch] = node;
            dfs(ch, adj);
        }
    }
    //traverse up k edges in O(log(k)). So with k=1 this returns 'node's parent
    int kthPar(int node, int k) const {
        k = min(k, depth[node]);
        while (k > 0) {
            if (jmpEdges[node] <= k) {
                k -= jmpEdges[node];
                node = jmp[node];
            } else {
                k--;
                node = par[node];
            }
        }
        return node;
    }
    int getLca(int x, int y) const {
        if (depth[x] < depth[y]) swap(x, y);
        x = kthPar(x, depth[x] - depth[y]);
        while (x != y) {
            if (jmp[x] != jmp[y])
                x = jmp[x], y = jmp[y];
            else
                x = par[x], y = par[y];
        }
        return x;
    }
    int distEdges(int x, int y) const {
        return depth[x] + depth[y] - 2 * depth[getLca(x, y)];
    }
    long long distWeight(int x, int y) const {
        return dist[x] + dist[y] - 2 * dist[getLca(x, y)];
    }
}
```

```
};
```

Listing 12: SCC

```
//cat scc.h | ./hash.sh
//d56944
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/scc
struct sccInfo {
    int numSCCs;
    //scc's are labeled 0,1,...,'numSCCs-1'
    //sccId[i] is the id of the scc containing node 'i'
    //for each edge i -> j: sccId[i] >= sccId[j]
    vector<int> sccId;
};

sccInfo getSCCs(const vector<vector<int>>& adj /*directed, unweighted graph*/) {
    int n = adj.size(), timer = 1, numSCCs = 0;
    vector<int> tin(n, 0), sccId(n, -1), nodeStack;
    auto dfs = [&](auto self, int v) -> int {
        int low = tin[v] = timer++;
        nodeStack.push_back(v);
        for (int to : adj[v]) {
            if (sccId[to] < 0)
                low = min(low, tin[to] ? tin[to] : self(self, to));
        }
        if (tin[v] == low) {
            while (true) {
                int node = nodeStack.back();
                nodeStack.pop_back();
                sccId[node] = numSCCs;
                if (node == v) break;
            }
            numSCCs++;
        }
        return low;
    };
    for (int i = 0; i < n; i++) {
        if (!tin[i])
            dfs(dfs, i);
    }
    return {numSCCs, sccId};
}
```

Listing 13: RANGE DATA STRUCTURES

Listing 14: Segment Tree

```
//cat segTree.h | ./hash.sh
//a9b5a9
#pragma once
//stress tests: tests/stress-tests/range_data_structures/segTree.cpp
const long long inf = 1e18;
struct segTree {
    struct Node {
        long long sum, mx, mn;
        long long lazy;
        int l, r;
    };
    vector<Node> tree;
```

```
    int len() const {
        return r - l + 1;
    }
    //returns 1 + (# of nodes in left child's subtree)
    //https://cp-algorithms.com/data_structures/segment_tree.html#memory-efficient-implementation
    int rCh() const {
        return ((r - l) & ~1) + 2;
    }
};

vector<Node> tree;
//There's no constructor 'segTree(int size)' because how to initialize l,r in nodes
//  ↳ without calling build?
//the whole point of 'segTree(int size)' was to be simpler by not calling build
segTree(const vector<long long>& arr) : tree(2 * (int)arr.size() - 1) {
    build(arr, 0, 0, (int)arr.size() - 1);
}

void build(const vector<long long>& arr, int v, int tl, int tr) {
    if (tl == tr) {
        tree[v] = {
            arr[tl],
            arr[tl],
            arr[tl],
            0,
            tl,
            tr
        };
    } else {
        int tm = tl + (tr - tl) / 2;
        build(arr, v + 1, tl, tm);
        build(arr, v + 2 * (tm - tl + 1), tm + 1, tr);
        tree[v] = combine(tree[v + 1], tree[v + 2 * (tm - tl + 1)]);
    }
}

static Node combine(const Node& L, const Node& R) {
    return {
        L.sum + R.sum,
        max(L.mx, R.mx),
        min(L.mn, R.mn),
        0,
        L.l,
        R.r
    };
}

//what happens when 'add' is applied to every index in range [tree[v].l, tree[v].r]?
void apply(int v, long long add) {
    tree[v].sum += tree[v].len() * add;
    tree[v].mx += add;
    tree[v].mn += add;
    if (tree[v].len() > 1) {
        tree[v + 1].lazy += add;
        tree[v + tree[v].rCh()].lazy += add;
    }
}

void push(int v) {
    if (tree[v].lazy) {
        apply(v, tree[v].lazy);
        tree[v].lazy = 0;
    }
}

//update range [l,r] with 'add'
void update(int l, int r, long long add) {
```

```
    update(0, l, r, add);
}
void update(int v, int l, int r, long long add) {
    push(v);
    if (tree[v].r < l || r < tree[v].l)
        return;
    if (l <= tree[v].l && tree[v].r <= r)
        return apply(v, add);
    update(v + 1, l, r, add);
    update(v + tree[v].rch(), l, r, add);
    tree[v] = combine(tree[v + 1], tree[v + tree[v].rch()]);
}
//range [l,r]
Node query(int l, int r) {
    return query(0, l, r);
}
Node query(int v, int l, int r) {
    if (tree[v].r < l || r < tree[v].l)
        return {0, -inf, inf, 0, 0, 0};
    push(v);
    if (l <= tree[v].l && tree[v].r <= r)
        return tree[v];
    return combine(query(v + 1, l, r),
        query(v + tree[v].rch(), l, r));
}
};
```

Listing 15: Fenwick Tree

```
//cat fenwickTree.h | ./hash.sh
//3d4557
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/point_add_range_sum,
    ↪ https://judge.yosupo.jp/problem/vertex_add_path_sum,
    ↪ https://judge.yosupo.jp/problem/vertex_add_subtree_sum,
    ↪ https://judge.yosupo.jp/problem/predecessor_problem
template<class T>
struct fenwickTree {
    vector<T> bit;
    fenwickTree(int n) : bit(n, 0) {}
    fenwickTree(const vector<T>& a) : bit(a.size()) {
        if (a.empty()) return;
        bit[0] = a[0];
        for (int i = 1; i < (int)a.size(); i++)
            bit[i] = bit[i - 1] + a[i];
        for (int i = (int)a.size() - 1; i > 0; i--) {
            int lower_i = (i & (i + 1)) - 1;
            if (lower_i >= 0)
                bit[i] -= bit[lower_i];
        }
    }
    void update(int idx, const T& d) {
        for (; idx < (int)bit.size(); idx = idx | (idx + 1))
            bit[idx] += d;
    }
    T sum(int r) const {
        T ret = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret += bit[r];
        return ret;
    }
};
```

```
    }
    T sum(int l, int r) const {
        return sum(r) - sum(l - 1);
    }
    //Returns min pos such that sum of [0, pos] >= sum
    //Returns bit.size() if no sum is >= sum, or -1 if empty sum is.
    //Doesn't work with negatives (since it's greedy), counterexample: array: {1, -1},
        ↪ sum: 1, this returns 2, but should return 0
    int lower_bound(T sum) const {
        if (sum <= 0) return -1;
        int pos = 0;
        for (int pw = 1 << (31 - __builtin_clz(bit.size() | 1)); pw; pw >>= 1) {
            if (pos + pw <= (int)bit.size() && bit[pos + pw - 1] < sum)
                pos += pw, sum -= bit[pos - 1];
        }
        return pos;
    }
};
```

Listing 16: Sparse Table

```
//cat sparseTable.h | ./hash.sh
//912bbe
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/staticrmq,
    ↪ https://judge.yosupo.jp/problem/zalgorithm,
    ↪ https://judge.yosupo.jp/problem/enumerate_palindromes,
    ↪ https://judge.yosupo.jp/problem/cartesian_tree
//usage:
// vector<long long> arr;
// ...
// sparseTable<long long> st(arr, [](auto x, auto y) { return min(x,y); });
//
//to also get index of min element, do:
// sparseTable<pair<long long,int>> st(arr, [](auto x, auto y) { return min(x,y); });
//and initialize 'second's to index. If there are multiple indexes of min element,
//it'll return the smallest (left-most) one
template <class T>
struct sparseTable {
    vector<vector<T>> dp;
    function<T(const T&, const T&)> func;
    sparseTable(const vector<T>& arr, const function<T(const T&, const T&)>& _func) :
        ↪ dp(1, arr), func(_func) {
        int n = arr.size();
        for (int pw = 1, k = 1; pw * 2 <= n; pw *= 2, k++) {
            dp.emplace_back(n - pw * 2 + 1);
            for (int j = 0; j < (int)dp[k].size(); j++)
                dp[k][j] = func(dp[k - 1][j], dp[k - 1][j + pw]);
        }
    }
    //inclusive range [l, r]
    T query(int l, int r) const {
        int lg = 31 - __builtin_clz(r - l + 1);
        return func(dp[lg][l], dp[lg][r - (1 << lg) + 1]);
    }
};
```

Listing 17: Implicit Lazy Segment Tree



```
//cat implicitSegTree.h | ./hash.sh
//c19ef1
#pragma once
//stress tests: tests/stress-tests/range_data_structures/implicitSegTree.cpp
//see TODO for lines of code which usually need to change (not a complete list)
const int N = 1.5e7; //TODO
struct Node {
    long long val; //could represent max, sum, etc
    long long lazy;
    int lCh, rCh; // children, indexes into 'tree', -1 for null
} tree[N];
struct implicitSegTree {
    int NEW_NODE, rootL, rootR; // [rootL, rootR] defines range of root node; handles
    ⇨ negatives
    implicitSegTree(int l, int r) : NEW_NODE(0), rootL(l), rootR(r) {
        tree[NEW_NODE++] = {0, 0, -1, -1}; //TODO
    }
    static long long combine(long long val_l, long long val_r) {
        return val_l + val_r; //TODO
    }
    void apply(int v, int tl, int tr, long long add) {
        tree[v].val += (tr - tl + 1) * add; //TODO
        if (tl != tr) {
            tree[tree[v].lCh].lazy += add; //TODO
            tree[tree[v].rCh].lazy += add;
        }
    }
    void push(int v, int tl, int tr) {
        if (tl != tr && tree[v].lCh == -1) {
            assert(NEW_NODE + 1 < N);
            tree[v].lCh = NEW_NODE;
            tree[NEW_NODE++] = {0, 0, -1, -1}; //TODO
            tree[v].rCh = NEW_NODE;
            tree[NEW_NODE++] = {0, 0, -1, -1};
        }
        if (tree[v].lazy) {
            apply(v, tl, tr, tree[v].lazy);
            tree[v].lazy = 0;
        }
    }
    //update range [l,r] with 'add'
    void update(int l, int r, long long add) {
        update(0, rootL, rootR, l, r, add);
    }
    void update(int v, int tl, int tr, int l, int r, long long add) {
        push(v, tl, tr);
        if (tr < l || r < tl)
            return;
        if (l <= tl && tr <= r)
            return apply(v, tl, tr, add);
        int tm = tl + (tr - tl) / 2;
        update(tree[v].lCh, tl, tm, l, r, add);
        update(tree[v].rCh, tm + 1, tr, l, r, add);
        tree[v].val = combine(tree[tree[v].lCh].val, tree[tree[v].rCh].val);
    }
    //query range [l,r]
    //for more complicated query which doesn't allocate new nodes, see:
    //https://github.com/lrvidickis/Programming-Team-Code/blob/dc659297850440b65af2550a834cc42af84a265/intro/range_data_structures/implicitLazySegTree.h
    long long query(int l, int r) {
        return query(0, rootL, rootR, l, r);
    }
};
```

```
long long query(int v, int tl, int tr, int l, int r) {
    if (tr < l || r < tl)
        return 0; //TODO
    push(v, tl, tr);
    if (l <= tl && tr <= r)
        return tree[v].val;
    int tm = tl + (tr - tl) / 2;
    return combine(query(tree[v].lCh, tl, tm, l, r),
        query(tree[v].rCh, tm + 1, tr, l, r));
}
};
```

Listing 18: Range Updates, Point Queries

```
//cat fenwickInv.h | ./hash.sh
//6009e6
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/vertex_add_subtree_sum,
⇨ https://judge.yosupo.jp/problem/point_add_range_sum
#include "../fenwickTree.h"
template<class T>
struct fenwickInv {
    fenwickTree<T> ft;
    fenwickInv(int n) : ft(n) {}
    fenwickInv(const vector<T>& arr) : ft(init(arr)) {}
    fenwickTree<T> init(vector<T> arr /*intentional pass by value*/) const {
        for (int i = (int)arr.size() - 1; i >= 1; i--)
            arr[i] -= arr[i - 1];
        return fenwickTree<T>(arr);
    }
    //add 'add' to inclusive range [l, r]
    void update(int l, int r, const T& add) {
        ft.update(l, add);
        if (r + 1 < (int)ft.bit.size())
            ft.update(r + 1, -add);
    }
    //get value at index 'idx'
    T query(int idx) const {
        return ft.sum(idx);
    }
};
```

Listing 19: Kth Smallest

```
//cat kth_smallest.h | ./hash.sh
//7fa26d
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/range_kth_smallest
//modified from
⇨ https://cp-algorithms.com/data_structures/segment_tree.html#preserving-the-history-o
struct kth_smallest {
    struct Node {
        int sum;
        int lCh, rCh; // children, indexes into 'tree'
    };
    int mn, mx;
    vector<Node> tree;
    deque<Node> roots;
    kth_smallest(const vector<int>& arr) : mn(INT_MAX), mx(INT_MIN), roots(arr.size() +
        ⇨ 1, 0) {}
};
```



```
tree.push_back({0, 0, 0}); //acts as null
for (int val : arr) mn = min(mn, val), mx = max(mx, val);
for (int i = 0; i < (int)arr.size(); i++)
    roots[i + 1] = update(roots[i], mn, mx, arr[i]);
}
int update(int v, int tl, int tr, int idx) {
    if (tl == tr) {
        tree.push_back({tree[v].sum + 1, 0, 0});
        return tree.size() - 1;
    }
    int tm = tl + (tr - tl) / 2;
    int lCh = tree[v].lCh;
    int rCh = tree[v].rCh;
    if (idx <= tm)
        lCh = update(lCh, tl, tm, idx);
    else
        rCh = update(rCh, tm + 1, tr, idx);
    tree.push_back({tree[lCh].sum + tree[rCh].sum, lCh, rCh});
    return tree.size() - 1;
}
/* find (k+1)th smallest number among arr[l], arr[l+1], ..., arr[r]
 * k is 0-based, so query(l,r,0) returns the min
 */
int query(int l, int r, int k) const {
    assert(0 <= k && k < r - l + 1); //note this condition implies L <= R
    assert(0 <= l && r + 1 < (int)roots.size());
    return query(roots[l], roots[r + 1], mn, mx, k);
}
int query(int vl, int vr, int tl, int tr, int k) const {
    if (tl == tr)
        return tl;
    int tm = tl + (tr - tl) / 2;
    int left_count = tree[tree[vr].lCh].sum - tree[tree[vl].lCh].sum;
    if (left_count > k) return query(tree[vl].lCh, tree[vr].lCh, tl, tm, k);
    return query(tree[vl].rCh, tree[vr].rCh, tm + 1, tr, k - left_count);
}
};
```

Listing 20: Number Distinct Elements

```
//cat distinct_query.h | ./hash.sh
//0cb2c5
#pragma once
//stress tests: tests/stress-tests/range_data_structures/distinct_query.cpp
//modified from
↳ https://cp-algorithms.com/data_structures/segment_tree.html#preserving-the-history-of-its-values-lazy-segment-tree
//works with negatives
//O(n log n) time and space
struct distinct_query {
    struct Node {
        int sum;
        int lCh, rCh; //children, indexes into 'tree'
    };
    vector<int> roots;
    deque<Node> tree;
    distinct_query(const vector<int>& arr) : roots(arr.size() + 1, 0) {
        tree.push_back({0, 0, 0}); //acts as null
        map<int, int> lastIdx;
        for (int i = 0; i < (int)arr.size(); i++) {
            roots[i + 1] = update(roots[i], 0, arr.size(), lastIdx[arr[i]]);
        }
    }
};
```

```
lastIdx[arr[i]] = i + 1;
}
}
int update(int v, int tl, int tr, int idx) {
    if (tl == tr) {
        tree.push_back({tree[v].sum + 1, 0, 0});
        return tree.size() - 1;
    }
    int tm = (tl + tr) / 2;
    int lCh = tree[v].lCh;
    int rCh = tree[v].rCh;
    if (idx <= tm)
        lCh = update(lCh, tl, tm, idx);
    else
        rCh = update(rCh, tm + 1, tr, idx);
    tree.push_back({tree[lCh].sum + tree[rCh].sum, lCh, rCh});
    return tree.size() - 1;
}
//returns number of distinct elements in range [l,r]
int query(int l, int r) const {
    return query(roots[l], roots[r + 1], 0, (int)roots.size() - 1, l + 1);
}
int query(int vl, int vr, int tl, int tr, int idx) const {
    if (tree[vr].sum == 0 || idx <= tl)
        return 0;
    if (tr < idx)
        return tree[vr].sum - tree[vl].sum;
    int tm = (tl + tr) / 2;
    return query(tree[vl].lCh, tree[vr].lCh, tl, tm, idx) +
        query(tree[vl].rCh, tree[vr].rCh, tm + 1, tr, idx);
}
};
```

Listing 21: Buckets

```
//cat buckets.h | ./hash.sh
//db53a3
#pragma once
//stress tests: tests/stress-tests/range_data_structures/buckets.cpp
//this code isn't the best. It's meant as a rough start for sqrt-decomposition, and to
↳ be modified
//doesn't handle overflow
struct buckets {
    const int BUCKET_SIZE = 50; //TODO: change - small value for testing
    struct bucket {
        int sumLazy = 0; //lazy segment-tree
        int sumBucket = 0;
        int l, r; //inclusive range of bucket
        int len() const {
            return r - l + 1;
        }
    };
    vector<int> values;
    vector<bucket> _buckets;
    buckets(const vector<int>& initial) : values(initial) {
        int numBuckets = ((int)values.size() + BUCKET_SIZE - 1) / BUCKET_SIZE;
        _buckets.resize(numBuckets);
        for (int i = 0; i < numBuckets; i++) {
            _buckets[i].sumLazy = 0;
            _buckets[i].sumBucket = 0;
        }
    }
};
```

```
        _buckets[i].l = i * BUCKET_SIZE;
        _buckets[i].r = min((i + 1) * BUCKET_SIZE, (int)values.size()) - 1;
        for (int j = _buckets[i].l; j <= _buckets[i].r; j++)
            _buckets[i].sumBucket += values[j];
    }
}

void pushLazy(int bIdx) {
    bucket& b = _buckets[bIdx];
    if (!b.sumLazy) return;
    for (int i = b.l; i <= b.r; i++)
        values[i] += b.sumLazy;
    b.sumLazy = 0;
}

//update range [L,R]
void update(int L, int R, int diff) {
    int startBucket = L / BUCKET_SIZE;
    int endBucket = R / BUCKET_SIZE;
    if (startBucket == endBucket) { //range contained in same bucket case
        for (int i = L; i <= R; i++) {
            values[i] += diff;
            _buckets[startBucket].sumBucket += diff;
        }
        return;
    }
    for (int bIdx : {
        startBucket, endBucket
    }) { //handle "endpoint" buckets
        bucket& b = _buckets[bIdx];
        for (int i = max(b.l, L); i <= min(b.r, R); i++) {
            values[i] += diff;
            b.sumBucket += diff;
        }
    }
    for (int i = startBucket + 1; i < endBucket; i++) { //handle all n/B buckets in
        ↪ middle
        bucket& b = _buckets[i];
        b.sumLazy += diff;
        b.sumBucket += b.len() * diff;
    }
}

//sum of range [L,R]
int query(int L, int R) {
    int startBucket = L / BUCKET_SIZE;
    int endBucket = R / BUCKET_SIZE;
    if (startBucket == endBucket) { //range contained in same bucket case
        pushLazy(startBucket);
        int sum = 0;
        for (int i = L; i <= R; i++)
            sum += values[i];
        return sum;
    }
    int sum = 0;
    for (int bIdx : {
        startBucket, endBucket
    }) { //handle "endpoint" buckets
        bucket& b = _buckets[bIdx];
        pushLazy(bIdx);
        for (int i = max(b.l, L); i <= min(b.r, R); i++)
            sum += values[i];
    }
    for (int i = startBucket + 1; i < endBucket; i++) //handle all n/B buckets in
```

```
        ↪ middle
        sum += _buckets[i].sumBucket;
        return sum;
    }
};
```

Listing 22: Persistent Lazy Segment Tree

```
//cat persistentLazySegTree.h | ./hash.sh
//87eace
#pragma once
//status: not tested
struct persistentLazySegTree {
    struct Node {
        int lCh, rCh; //children, indexes into 'tree'
        int sum;
        bool lazyTog;
    };
    int sz;
    deque<Node> tree;
    vector<int> roots;
    //implicit
    persistentLazySegTree(int _sz) : sz(_sz) {
        tree.push_back({0, 0, 0, 0}); //acts as null
        roots.push_back(0);
    }
    void push(int v, int tl, int tr) {
        if (tl != tr) {
            tree.push_back(tree[tree[v].lCh]);
            tree[v].lCh = tree.size() - 1;
            tree.push_back(tree[tree[v].rCh]);
            tree[v].rCh = tree.size() - 1;
        }
        if (tree[v].lazyTog) {
            tree[v].sum = (tr - tl + 1) - tree[v].sum;
            tree[v].lazyTog = false;
            if (tl != tr) {
                tree[tree[v].lCh].lazyTog ^= 1;
                tree[tree[v].rCh].lazyTog ^= 1;
            }
        }
    }
    void set(int idx, int new_val) {
        tree.push_back(tree[roots.back()]); //allocate top down
        roots.push_back(tree.size() - 1);
        set(roots.back(), 0, sz - 1, idx, new_val);
    }
    void set(int v, int tl, int tr, int idx, int new_val) {
        push(v, tl, tr);
        if (tr < idx || idx < tl)
            return;
        if (idx <= tl && tr <= idx) {
            tree[v].sum = new_val;
            return;
        }
        int tm = (tl + tr) / 2;
        int lCh = tree[v].lCh;
        int rCh = tree[v].rCh;
        set(lCh, tl, tm, idx, new_val);
        set(rCh, tm + 1, tr, idx, new_val);
    }
};
```

```
    tree[v].sum = tree[lCh].sum + tree[rCh].sum;
}
void toggleRange(int l, int r) {
    tree.push_back(tree[roots.back()]); //allocate top down
    roots.push_back(tree.size() - 1);
    toggleRange(roots.back(), 0, sz - 1, l, r);
}
void toggleRange(int v, int tl, int tr, int l, int r) {
    push(v, tl, tr);
    if (tr < l || r < tl)
        return;
    int lCh = tree[v].lCh;
    int rCh = tree[v].rCh;
    if (l <= tl && tr <= r) {
        tree[v].sum = (tr - tl + 1) - tree[v].sum;
        if (tl != tr) {
            tree[lCh].lazyTog ^= 1;
            tree[rCh].lazyTog ^= 1;
        }
        return;
    }
    int tm = (tl + tr) / 2;
    toggleRange(lCh, tl, tm, l, r);
    toggleRange(rCh, tm + 1, tr, l, r);
    tree[v].sum = tree[lCh].sum + tree[rCh].sum;
}
//let's use implementation trick described here
//↪ https://codeforces.com/blog/entry/72626
//so that we don't have to propagate lazy vals and thus we don't have to allocate
//↪ new nodes
int query(int l, int r) const {
    int version = roots.size() - 1;
    int root = roots[version];
    return query(root, 0, sz - 1, l, r, tree[root].lazyTog);
}
int query(int v, int tl, int tr, int l, int r, bool tog) const {
    if (v == 0 || tr < l || r < tl)
        return 0;
    if (l <= tl && tr <= r) {
        int sum = tree[v].sum;
        if (tree[v].lazyTog) sum = (tr - tl + 1) - sum;
        return sum;
    }
    int tm = (tl + tr) / 2;
    tog ^= tree[v].lazyTog;
    return query(tree[v].lCh, tl, tm, l, r, tog) +
        query(tree[v].rCh, tm + 1, tr, l, r, tog);
}
};
```

Listing 23: Merge Sort Tree

```
//cat mergeSortTree.h | ./hash.sh
//67bc79
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/static_range_frequency,
//↪ https://judge.yosupo.jp/problem/range_kth_smallest
//For point updates: either switch to policy based BST, or use sqrt decomposition
struct MergeSortTree {
    struct Node {
```

```
vector<int> vals;
int l, r;
//returns 1 + (# of nodes in left child's subtree)
//https://cp-algorithms.com/data_structures/segment_tree.html#memory-efficient-imple
int rCh() const {
    return ((r - l) & ~1) + 2;
}
};
vector<Node> tree;
//RTE's when 'arr' is empty
MergeSortTree(const vector<int>& arr) : tree(2 * (int)arr.size() - 1) {
    build(arr, 0, 0, (int)arr.size() - 1);
}
void build(const vector<int>& arr, int v, int tl, int tr) {
    if (tl == tr) {
        tree[v] = {
            {arr[tl]},
            tl,
            tr
        };
    } else {
        int tm = tl + (tr - tl) / 2;
        build(arr, v + 1, tl, tm);
        build(arr, v + 2 * (tm - tl + 1), tm + 1, tr);
        tree[v] = combine(tree[v + 1], tree[v + 2 * (tm - tl + 1)]);
    }
}
Node combine(const Node& L, const Node& R) const {
    vector<int> par(L.vals.size() + R.vals.size());
    merge(L.vals.begin(), L.vals.end(), R.vals.begin(), R.vals.end(), par.begin());
    return {par, L.l, R.r};
}
//How many of arr[l], arr[l+1], ..., arr[r] are < x?
//O(log^2(n))
int query(int l, int r, int x) const {
    return query(0, l, r, x);
}
int query(int v, int l, int r, int x) const {
    if (tree[v].r < l || r < tree[v].l)
        return 0;
    if (l <= tree[v].l && tree[v].r <= r) {
        const vector<int>& vals = tree[v].vals;
        return lower_bound(vals.begin(), vals.end(), x) - vals.begin();
    }
    return query(v + 1, l, r, x) +
        query(v + tree[v].rCh(), l, r, x);
}
};
```

Listing 24: STRINGS

```
//cat suffix_array.h | ./hash.sh
//46840a
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/suffixarray,
//↪ https://judge.yosupo.jp/problem/zalgorithm,
```

Listing 25: Suffix Array

```
↪ https://judge.yosupo.jp/problem/number_of_substrings,
↪ https://judge.yosupo.jp/problem/enumerate_palindromes
//modified from here: https://judge.yosupo.jp/submission/37410
//
// SA-IS, linear-time suffix array construction
// Reference:
// G. Nong, S. Zhang, and W. H. Chan,
// Two Efficient Algorithms for Linear Time Suffix Array Construction
template<class T>
vector<int> sa_is(const T& s, int upper/*max element of 's'; for std::string, pass in
↪ 255*/) {
    int n = (int)s.size();
    if (n == 0) return {};
    if (n == 1) return {0};
    if (n == 2) {
        if (s[0] < s[1]) {
            return {0, 1};
        } else {
            return {1, 0};
        }
    }
    vector<int> sa(n);
    vector<bool> ls(n);
    for (int i = n - 2; i >= 0; i--)
        ls[i] = (s[i] == s[i + 1]) ? ls[i + 1] : (s[i] < s[i + 1]);
    vector<int> sum_l(upper + 1), sum_s(upper + 1);
    for (int i = 0; i < n; i++) {
        if (!ls[i])
            sum_s[s[i]]++;
        else
            sum_l[s[i] + 1]++;
    }
    for (int i = 0; i <= upper; i++) {
        sum_s[i] += sum_l[i];
        if (i < upper) sum_l[i + 1] += sum_s[i];
    }
    vector<int> buf(upper + 1);
    auto induce = [&](const vector<int>& lms) {
        fill(sa.begin(), sa.end(), -1);
        fill(buf.begin(), buf.end(), 0);
        copy(sum_s.begin(), sum_s.end(), buf.begin());
        for (auto d : lms) {
            if (d == n) continue;
            sa[buf[s[d]]++] = d;
        }
        copy(sum_l.begin(), sum_l.end(), buf.begin());
        sa[buf[s[n - 1]]++] = n - 1;
        for (int i = 0; i < n; i++) {
            int v = sa[i];
            if (v >= 1 && !ls[v - 1])
                sa[buf[s[v - 1]]++] = v - 1;
        }
        copy(sum_l.begin(), sum_l.end(), buf.begin());
        for (int i = n - 1; i >= 0; i--) {
            int v = sa[i];
            if (v >= 1 && ls[v - 1])
                sa[--buf[s[v - 1] + 1]] = v - 1;
        }
    };
    vector<int> lms_map(n + 1, -1);
    int m = 0;
```

```
for (int i = 1; i < n; i++) {
    if (!ls[i - 1] && ls[i])
        lms_map[i] = m++;
}
vector<int> lms;
lms.reserve(m);
for (int i = 1; i < n; i++) {
    if (!ls[i - 1] && ls[i])
        lms.push_back(i);
}
induce(lms);
if (m) {
    vector<int> sorted_lms;
    sorted_lms.reserve(m);
    for (int v : sa) {
        if (lms_map[v] != -1) sorted_lms.push_back(v);
    }
    vector<int> rec_s(m);
    int rec_upper = 0;
    rec_s[lms_map[sorted_lms[0]]] = 0;
    for (int i = 1; i < m; i++) {
        int l = sorted_lms[i - 1], r = sorted_lms[i];
        int end_l = (lms_map[l] + 1 < m) ? lms[lms_map[l] + 1] : n;
        int end_r = (lms_map[r] + 1 < m) ? lms[lms_map[r] + 1] : n;
        bool same = true;
        if (end_l - 1 != end_r - r)
            same = false;
        else {
            while (l < end_l) {
                if (s[l] != s[r])
                    break;
                l++;
                r++;
            }
            if (l == n || s[l] != s[r]) same = false;
        }
        if (!same) rec_upper++;
        rec_s[lms_map[sorted_lms[i]]] = rec_upper;
    }
    auto rec_sa =
        sa_is(rec_s, rec_upper);
    for (int i = 0; i < m; i++)
        sorted_lms[i] = lms[rec_sa[i]];
    induce(sorted_lms);
}
return sa;
}
```

Listing 26: Longest Common Prefix Array

```
//cat longest_common_prefix.h | ./hash.sh
//396173
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/zaalgorithm,
↪ https://judge.yosupo.jp/problem/number_of_substrings,
↪ https://judge.yosupo.jp/problem/enumerate_palindromes
//modified from here: https://judge.yosupo.jp/submission/37410
//
// Reference:
// T. Kasai, G. Lee, H. Arimura, S. Arikawa, and K. Park,
```

```
// Linear-Time Longest-Common-Prefix Computation in Suffix Arrays and Its
// Applications
template<class T>
vector<int> lcp_array(const T& s, const vector<int>& sa) {
    int n = s.size(), k = 0;
    vector<int> lcp(n, 0);
    vector<int> rank(n, 0);
    for (int i = 0; i < n; i++) rank[sa[i]] = i;
    for (int i = 0; i < n; i++, k ? k-- : 0) {
        if (rank[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = sa[rank[i] + 1];
        while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
        lcp[rank[i]] = k;
    }
    return lcp;
}
```

Listing 27: Prefix Function

```
//cat prefix_function.h | ./hash.sh
//aa0518
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/zalgorithn
//stress tests: tests/stress-tests/strings/kmp.cpp
//source: https://cp-algorithms.com/string/prefix-function.html#implementation
template <class T>
vector<int> prefix_function(const T& s) {
    int n = s.size();
    vector<int> pi(n, 0);
    for (int i = 1; i < n; i++) {
        int j = pi[i - 1];
        while (j > 0 && s[i] != s[j]) j = pi[j - 1];
        pi[i] = j + (s[i] == s[j]);
    }
    return pi;
}
```

Listing 28: KMP

```
//cat kmp.h | ./hash.sh
//dd5c08
#pragma once
//stress tests: tests/stress-tests/strings/kmp.cpp
#include "prefix_function.h"
//usage:
// string needle;
// ...
// KMP_Match kmp(needle);
//or
// vector<int> needle;
// ...
// KMP_Match kmp(needle);
//kmp-doubling-trick: to check if 2 arrays are rotationally equivalent: run kmp
//with one array as the needle and the other array doubled as the haystack
//or just use kactl's min rotation code
template <class T>
```

```
struct KMP_Match {
    KMP_Match(const T& needle_) : pi(prefix_function(needle_)), needle(needle_) {}
    // if haystack = "bananas"
    // needle = "ana"
    //
    // then we find 2 matches:
    // bananas
    // _ana_
    // __ana_
    // 0123456 (indexes)
    // and KMP_Match::find returns {1,3} - the indexes in haystack where
    // each match starts.
    //
    // You can also pass in false for "all" and KMP_Match::find will only
    // return the first match: {1}. Useful for checking if there exists
    // some match:
    //
    // KMP_Match::find(<haystack>,false).size() > 0
    vector<int> find(const T& haystack, bool all = true) const {
        vector<int> matches;
        for (int i = 0, j = 0; i < (int)haystack.size(); i++) {
            while (j > 0 && needle[j] != haystack[i]) j = pi[j - 1];
            if (needle[j] == haystack[i]) j++;
            if (j == (int)needle.size()) {
                matches.push_back(i - (int)needle.size() + 1);
                if (!all) return matches;
                j = pi[j - 1];
            }
        }
        return matches;
    }
    vector<int> pi; //prefix function
    T needle;
};
```

Listing 29: Trie

```
//cat trie.h | ./hash.sh
//6ed273
#pragma once
//status: not tested
//source: https://cp-algorithms.com/string/aho_corasick.html#construction-of-the-trie
//intended to be a base template and to be modified
const int K = 26; //character size
struct trie {
    const char minCh = 'a'; // 'A' for uppercase, '0' for digits
    struct node {
        int next[K], id, p = -1;
        char pch;
        bool leaf = 0;
        node(int _p = -1, char ch = '#') : p(_p), pch(ch) {
            fill(next, next + K, -1);
        }
    };
    vector<node> t;
    trie() : t(1) {}
    void add_string(const string& s, int id) {
        int c = 0;
        for (char ch : s) {
            int v = ch - minCh;
```

```
        if (t[c].next[v] == -1) {
            t[c].next[v] = t.size();
            t.emplace_back(c, ch);
        }
        c = t[c].next[v];
    }
    t[c].leaf = 1;
    t[c].id = id;
}

void remove_string(const string& s) {
    int c = 0;
    for (char ch : s) {
        int v = ch - minCh;
        if (t[c].next[v] == -1)
            return;
        c = t[c].next[v];
    }
    t[c].leaf = 0;
}

int find_string(const string& s) {
    int c = 0;
    for (char ch : s) {
        int v = ch - minCh;
        if (t[c].next[v] == -1)
            return -1;
        c = t[c].next[v];
    }
    if (!t[c].leaf) return -1;
    return t[c].id;
}

};
```

Listing 30: Binary Trie

```
//cat binaryTrie.h | ./hash.sh
//113a91
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/set_xor_min
struct binaryTrie {
    const int mxBit = 62;
    struct node {
        long long val = -1;
        int subSz = 0; //number of inserted values in subtree
        int next[2] = {-1, -1};
    };
    vector<node> t;
    binaryTrie() : t(1) {}
    //delta = 1 to insert val, -1 to remove val
    void update(long long val, int delta) {
        int c = 0;
        t[0].subSz += delta;
        for (int bit = mxBit; bit >= 0; bit--) {
            bool v = (val >> bit) & 1;
            if (t[c].next[v] == -1) {
                t[c].next[v] = t.size();
                t.emplace_back();
            }
            c = t[c].next[v];
            t[c].subSz += delta;
        }
    }
};
```

```
        t[c].val = val;
    }
    //returns # of val's in this data structure
    int cnt(long long val) const {
        int c = 0;
        for (int bit = mxBit; bit >= 0; bit--) {
            bool v = (val >> bit) & 1;
            if (t[c].next[v] == -1)
                return 0;
            c = t[c].next[v];
        }
        return t[c].subSz;
    }
    int size() const {
        return t[0].subSz;
    }
    //returns x such that:
    // x is in this data structure
    // value of (x ^ val) is minimum
    long long min_xor(long long val) const {
        assert(size() > 0);
        int c = 0;
        for (int bit = mxBit; bit >= 0; bit--) {
            bool v = (val >> bit) & 1;
            int ch = t[c].next[v];
            if (ch != -1 && t[ch].subSz > 0)
                c = ch;
            else
                c = t[c].next[!v];
        }
        return t[c].val;
    }
};
```

Listing 31: Longest Common Prefix Query

```
//cat lcp_queries.h | ./hash.sh
//839d2c
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/zaalgorithm,
// https://judge.yosupo.jp/problem/enumerate_palindromes
#include "suffix_array.h"
#include "longest_common_prefix.h"
#include "../range_data_structures/sparseTable.h"
//computes suffix array, lcp array, and then sparse table over lcp array
//O(n log n)
struct lcp_queries {
    lcp_queries(const string& s) : sa(sa_is(s, 255)), inv_sa(s.size()), lcp(lcp_array(s,
        sa)), st(lcp, [](int x, int y) {
            return min(x, y);
        }) {
        for (int i = 0; i < (int)s.size(); i++)
            inv_sa[sa[i]] = i;
    }
    //length of longest common prefix of suffixes s[idx1 ... n-1], s[idx2 ... n-1],
    // 0-based indexing
    //
    //You can check if two substrings s[L1..R1], s[L2..R2] are equal in O(1) by:
    //R2-L2 == R1-L1 && longest_common_prefix(L1, L2) >= R2-L2+1
    int longest_common_prefix(int idx1, int idx2) const {
```

```
    if (idx1 == idx2) return (int)sa.size() - idx1;
    idx1 = inv_sa[idx1];
    idx2 = inv_sa[idx2];
    if (idx1 > idx2) swap(idx1, idx2);
    return st.query(idx1, idx2 - 1);
}
//returns true if suffix s[idx1 ... n-1] < s[idx2 ... n-1]
//(so false if idx1 == idx2)
bool less(int idx1, int idx2) const {
    return inv_sa[idx1] < inv_sa[idx2];
}
vector<int> sa, inv_sa, lcp;
sparseTable<int> st;
};
```

Listing 32: MATH

Listing 33: BIN EXP MOD

```
//cat exp_mod.h | ./hash.sh
//deca76
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/system_of_linear_equations,
//    https://judge.yosupo.jp/problem/binomial_coefficient,
//    https://judge.yosupo.jp/problem/matrix_det,
//    https://judge.yosupo.jp/problem/inverse_matrix
//stress tests: tests/stress-tests/math/exp_mod.cpp
//returns (base^pw)%mod in O(log(pw)), but returns 1 for 0^0
//
//What if base doesn't fit in long long?
//Since (base^pw)%mod == ((base%mod)^pw)%mod we can calculate base under mod of 'mod'
//
//What if pw doesn't fit in long long?
//case 1: mod is prime
//(base^pw)%mod == (base^(pw%(mod-1)))%mod (from Fermat's little theorem)
//so calculate pw under mod of 'mod-1'
//
//case 2: non-prime mod
//let t = totient(mod)
//if pw >= log2(mod) then (base^pw)%mod == (base^(t+(pw/t)))%mod (proof
//    https://cp-algorithms.com/algebra/phi-function.html#generalization)
//so calculate pw under mod of 't'
//incidentally, totient(p) = p - 1 for every prime p, making this a more generalized
//    version of case 1
int fastPow(long long base, long long pw, int mod) {
    assert(0 <= pw && 0 <= base && 1 <= mod);
    int res = 1;
    base %= mod;
    while (pw > 0) {
        if (pw & 1) res = res * base % mod;
        base = base * base % mod;
        pw >>= 1;
    }
    return res;
}
```

Listing 34: Fibonacci

```
//cat fib.h | ./hash.sh
//9ac293
#pragma once
//stress tests: tests/stress-tests/math/fib_matrix_expo.cpp
//https://codeforces.com/blog/entry/14516
unordered_map<long long, int> table;
int fib(long long n, int mod) { /**O(log(n))**
    if (n < 2) return 1;
    if (table.find(n) != table.end()) return table[n];
    table[n] = (1LL * fib((n + 1) / 2, mod) * fib(n / 2, mod) + 1LL * fib((n - 1) / 2,
        mod) * fib((n - 2) / 2, mod)) % mod;
    return table[n];
}
```

Listing 35: Matrix Mult and Pow

```
//cat matrixMultPow.h | ./hash.sh
//e2b9c4
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/matrix_product
//stress tests: tests/stress-tests/math/fib_matrix_expo.cpp
//empty matrix -> RTE
vector<vector<int>> mult(const vector<vector<int>>& a, const vector<vector<int>>& b, int
    mod) {
    assert(a[0].size() == b.size());
    int n = a.size(), m = b[0].size(), inner = b.size();
    vector<vector<int>> prod(n, vector<int>(m, 0));
    for (int i = 0; i < n; i++) {
        for (int k = 0; k < inner; k++) {
            for (int j = 0; j < m; j++)
                prod[i][j] = (prod[i][j] + 1LL * a[i][k] * b[k][j]) % mod;
        }
    }
    return prod;
}
vector<vector<int>> power(vector<vector<int>> matrix/*intentional pass by value*/, long
    long pw, int mod) {
    int n = matrix.size();
    vector<vector<int>> prod(n, vector<int>(n, 0));
    for (int i = 0; i < n; i++)
        prod[i][i] = 1;
    while (pw > 0) {
        if (pw % 2 == 1) prod = mult(prod, matrix, mod);
        matrix = mult(matrix, matrix, mod);
        pw /= 2;
    }
    return prod;
}
```

Listing 36: N Choose K MOD

```
//cat n_choose_k_mod.h | ./hash.sh
//db2a09
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/binomial_coefficient
//only the tests with prime mod
//for mod inverse
#include "exp_mod.h"
// usage:
```



```
// NchooseK nk(n, 1e9+7) to use 'choose', 'inv' with inputs < n
// or:
// NchooseK nk(mod, mod) to use 'chooseWithLucasTheorem'
struct NchooseK {
    // 'factSz' is the size of the factorial array, so only call 'choose', 'inv' with n
    ↪ < factSz
    NchooseK(int factSz, int currMod) : mod(currMod), fact(factSz, 1), invFact(factSz,
    ↪ 1) {
        //this implementation doesn't work if factSz > mod because n! % mod = 0 when n
        ↪ >= mod. So 'invFact' array will be all 0's
        assert(max(factSz, 2) <= mod);
        //assert mod is prime. mod is intended to fit inside an int so that
        //multiplications fit in a longlong before being modded down. So this
        //will take sqrt(2^31) time
        for (int i = 2; i * i <= mod; i++) assert(mod % i);
        for (int i = 2; i < factSz; i++)
            fact[i] = 1LL * fact[i - 1] * i % mod;
        invFact.back() = fastPow(fact.back(), mod - 2, mod);
        for (int i = factSz - 2; i >= 2; i--)
            invFact[i] = 1LL * invFact[i + 1] * (i + 1) % mod;
    }
    //classic n choose k
    //fails when n >= mod
    int choose(int n, int k) const {
        if (k < 0 || k > n) return 0;
        //now we know 0 <= k <= n so 0 <= n
        return 1LL * fact[n] * invFact[k] % mod * invFact[n - k] % mod;
    }
    //lucas theorem to calculate n choose k in O(log(k))
    //need to calculate all factorials in range [0,mod), so O(mod) time&space, so need
    ↪ smallish prime mod (< 1e6 maybe)
    //handles n >= mod correctly
    int chooseWithLucasTheorem(long long n, long long k) const {
        if (k < 0 || k > n) return 0;
        if (k == 0 || k == n) return 1;
        return 1LL * chooseWithLucasTheorem(n / mod, k / mod) * choose(n % mod, k % mod)
        ↪ % mod;
    }
    //returns inverse of n in O(1)
    int inv(int n) const {
        assert(1 <= n); //don't divide by 0 :)
        return 1LL * fact[n - 1] * invFact[n] % mod;
    }
    int mod;
    vector<int> fact, invFact;
};
```

Listing 37: Partitions

```
//cat partitions.h | ./hash.sh
//3356f6
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/partition_function
//https://oeis.org/A000041
//O(n sqrt n) time, but small-ish constant factor (there does exist a O(n log n)
↪ solution too)
vector<int> partitions(int n/*size of dp array*/, int mod) {
    vector<int> dp(n, 1);
    for (int i = 1; i < n; i++) {
        long long sum = 0;
```

```
for (int j = 1, pent = 1, sign = 1; pent <= i; j++, pent += 3 * j - 2, sign =
    ↪ -sign) {
    if (pent + j <= i) sum += dp[i - pent - j] * sign + mod;
    sum += dp[i - pent] * sign + mod;
}
dp[i] = sum % mod;
}
return dp;
}
```

Listing 38: Derangements

```
//cat derangements.h | ./hash.sh
//c221bb
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/montmort_number_mod
//https://oeis.org/A000166
//
//for a permutation of size i:
//there are (i-1) places to move 0 to not be at index 0. Let's say we moved 0 to index j
↪ (j>0).
//If we move value j to index 0 (forming a cycle of length 2), then there are dp[i-2]
↪ derangements of the remaining i-2 elements
//else there are dp[i-1] derangements of the remaining i-1 elements (including j)
vector<int> derangements(int n/*size of dp array*/, int mod) {
    vector<int> dp(n, 0);
    dp[0] = 1;
    for (int i = 2; i < n; i++)
        dp[i] = 1LL * (i - 1) * (dp[i - 1] + dp[i - 2]) % mod;
    return dp;
}
```

Listing 39: Prime Sieve Mobius

```
//cat primeSieveMobius.h | ./hash.sh
//07739a
#pragma once
//stress tests: tests/stress-tests/math/prime_sieve_mobius.cpp
//status: not tested
//mobius[i] = 0 iff there exists a prime p s.t. i%(p^2)=0
//mobius[i] = -1 iff i has an odd number of distinct prime factors
//mobius[i] = 1 iff i has an even number of distinct prime factors
const int N = 2e6 + 10;
int mobius[N];
void calcMobius() {
    mobius[1] = 1;
    for (int i = 1; i < N; i++)
        for (int j = i + i; j < N; j += i)
            mobius[j] -= mobius[i];
}
//aPrime[val] = some random prime factor of 'val'
//to get all prime factors of a number 'val':
// while(val > 1) {
//     int p = aPrime[val];
//     //p is some prime factor of val
//     val /= p;
// }
int aPrime[N];
void calcSeive() {
```

```
iota(aPrime, aPrime + N, 0);
for (int i = 2; i * i < N; i++)
    if (aPrime[i] == i)
        for (int j = i * i; j < N; j += i)
            aPrime[j] = i;
}
```

Listing 40: Row Reduce

```
//cat row_reduce.h | ./hash.sh
//ad11ab
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/system_of_linear_equations,
    ↪ https://judge.yosupo.jp/problem/matrix_det,
    ↪ https://judge.yosupo.jp/problem/inverse_matrix
//for mod inverse
#include "exp_mod.h"
//First 'cols' columns of A represents a matrix to be left in reduced row echelon form
//Row operations will be performed to all later columns
//
//example usage:
// row_reduce(A, A[0].size(), mod) //row reduce matrix with no extra columns
pair<int/*rank*/, int/*determinant*/> row_reduce(vector<vector<int>>& A, const int cols,
    ↪ const int mod) {
    int n = A.size(), m = A[0].size(), rank = 0, det = 1;
    assert(cols <= m);
    for (int col = 0; col < cols && rank < n; col++) {
        //find arbitrary pivot and swap pivot to current row
        for (int i = rank; i < n; i++)
            if (A[i][col] != 0) {
                if (rank != i) det = det == 0 ? 0 : mod - det;
                swap(A[i], A[rank]);
                break;
            }
        if (A[rank][col] == 0) {
            det = 0;
            continue;
        }
        det = (1LL * det * A[rank][col]) % mod;
        //make pivot 1 by dividing row by inverse of pivot
        const int aInv = fastPow(A[rank][col], mod - 2, mod);
        for (int j = 0; j < m; j++)
            A[rank][j] = (1LL * A[rank][j] * aInv) % mod;
        //zero-out all numbers above & below pivot
        for (int i = 0; i < n; i++)
            if (i != rank && A[i][col] != 0) {
                const int val = A[i][col];
                for (int j = 0; j < m; j++) {
                    A[i][j] -= 1LL * A[rank][j] * val % mod;
                    if (A[i][j] < 0) A[i][j] += mod;
                }
            }
        rank++;
    }
    assert(rank <= min(n, cols));
    return {rank, det};
}
```

Listing 41: Solve Linear Equations MOD

```
//cat solve_linear_mod.h | ./hash.sh
//e458de
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/system_of_linear_equations
#include "row_reduce.h"
struct matrixInfo {
    int rank, det;
    vector<int> x;
};
//Solves A * x = b under prime mod.
//A is a n (rows) by m (cols) matrix, b is a length n column vector, x is a length m
    ↪ column vector.
//assumes n,m >= 1, else RTE
//Returns rank of A, determinant of A, and x (solution vector to A * x = b). x is empty
    ↪ if no solution. If multiple solutions, an arbitrary one is returned.
//Leaves A in reduced row echelon form (unlike kactl) with b appended.
//O(n * m * min(n,m))
matrixInfo solve_linear_mod(vector<vector<int>>& A, const vector<int>& b, const int mod)
    ↪ {
    assert(A.size() == b.size());
    int n = A.size(), m = A[0].size();
    for (int i = 0; i < n; i++)
        A[i].push_back(b[i]);
    auto [rank, det] = row_reduce(A, m, mod); //row reduce not including the last column
    //check if solution exists
    for (int i = rank; i < n; i++) {
        if (A[i].back() != 0) return {rank, det, {}}; //no solution exists
    }
    //initialize solution vector ('x') from row-reduced matrix
    vector<int> x(m, 0);
    for (int i = 0, j = 0; i < rank; i++) {
        while (A[i][j] == 0) j++; //find pivot column
        x[j] = A[i].back();
    }
    return {rank, det, x};
}
```

Listing 42: Matrix Inverse

```
//cat matrix_inverse.h | ./hash.sh
//7f9c8c
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/inverse_matrix
#include "row_reduce.h"
//returns inverse of square matrix A, empty if no inverse
vector<vector<int>> matrix_inverse(vector<vector<int>> A/*intentional pass by value*/,
    ↪ const int mod) {
    int n = A.size();
    assert(n == (int)A[0].size());
    //append identity matrix
    for (int i = 0; i < n; i++) {
        A[i].resize(2 * n, 0);
        A[i][i + n] = 1;
    }
    auto [rank, det] = row_reduce(A, n, mod); //row reduce first n columns, leaving
    ↪ inverse in last n columns
    if (rank < n) return {}; //no inverse
    for (int i = 0; i < n; i++)
        A[i].erase(A[i].begin(), A[i].begin() + n);
    return A;
}
```

```
}

```

Listing 43: Euler’s Totient Phi Function

```
//cat totient.h | ./hash.sh
//36bd41
#pragma once
//stress tests: tests/stress-tests/math/totient.cpp
//Euler's totient function counts the positive integers
//up to a given integer n that are relatively prime to n.
//
//To improve, use Pollard-rho to find prime factors
int totient(int n) {
    int res = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            while (n % i == 0) n /= i;
            res -= res / i;
        }
    }
    if (n > 1) res -= res / n;
    return res;
}
```

Listing 44: MAX FLOW

Listing 45: Dinic

```
//cat dinic.h | ./hash.sh
//44e407
#pragma once
//status: not tested
struct maxflow {
    typedef long long ll;
    ll n, s, t;
    maxflow(int _n, int _s, int _t) : n(_n), s(_s), t(_t), d(n), ptr(n), q(n), g(n) {}
    void addedge(ll a, ll b, ll cap) {
        edgeMap[a * n + b] = e.size();
        edge e1 = { a, b, cap, 0 };
        edge e2 = { b, a, 0, 0 };
        g[a].push_back((ll) e.size());
        e.push_back(e1);
        g[b].push_back((ll) e.size());
        e.push_back(e2);
    }
    ll getflow() {
        ll flow = 0;
        for (;;) {
            if (!bfs()) break;
            ptr.assign(ptr.size(), 0);
            while (ll pushed = dfs(s, inf))
                flow += pushed;
        }
        return flow;
    }
    ll getFlowForEdge(ll a, ll b) {
        return e[edgeMap[a * n + b]].flow;
    }
};
```

```
}
const ll inf = 1e18;
struct edge {
    ll a, b, cap, flow;
};
unordered_map<int, ll> edgeMap;
vector<ll> d, ptr, q;
vector<edge> e;
vector<vector<ll>> g;
bool bfs() {
    ll qh = 0, qt = 0;
    q[qt++] = s;
    d.assign(d.size(), -1);
    d[s] = 0;
    while (qh < qt && d[t] == -1) {
        ll v = q[qh++];
        for (size_t i = 0; i < g[v].size(); i++) {
            ll id = g[v][i],
                to = e[id].b;
            if (d[to] == -1 && e[id].flow < e[id].cap) {
                q[qt++] = to;
                d[to] = d[v] + 1;
            }
        }
    }
    return d[t] != -1;
}
ll dfs(ll v, ll flow) {
    if (!flow) return 0;
    if (v == t) return flow;
    for (; ptr[v] < (ll) g[v].size(); ptr[v]++) {
        ll id = g[v][ptr[v]];
        ll to = e[id].b;
        if (d[to] != d[v] + 1) continue;
        ll pushed = dfs(to, min(flow, e[id].cap - e[id].flow));
        if (pushed) {
            e[id].flow += pushed;
            e[id ^ 1].flow -= pushed;
            return pushed;
        }
    }
    return 0;
}
};
```

Listing 46: Hungarian

```
//cat hungarian.h | ./hash.sh
//81e134
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/assignment
//source: https://e-maxx.ru/algo/assignment_hungary
//
//input: cost[1..n][1..m] with n <= m
//n workers, indexed 1, 2, ..., n
//m jobs, indexed 1, 2, ..., m
//it costs 'cost[i][j]' to assign worker i to job j (1<=i<=n, 1<=j<=m)
//this returns *min* total cost to assign each worker to some distinct job
//O(n^2 * m)
//
```

```
//trick 1: set 'cost[i][j]' to INF to say: "worker 'i' cannot be assigned job 'j'"
//trick 2: 'cost[i][j]' can be negative, so to instead find max total cost over all
    ↪ matchings: set all 'cost[i][j]' to '-cost[i][j]'.
//Now max total cost = - HungarianMatch(cost).minCost
const long long inf = 1e18;
struct match {
    long long minCost;
    vector<int> matching; //worker 'i' (1<=i<=n) is assigned to job 'matching[i]'
    ↪ (1<=matching[i]<=m)
};

match HungarianMatch(const vector<vector<long long>>& cost) {
    int n = cost.size() - 1, m = cost[0].size() - 1;
    assert(n <= m);
    vector<int> p(m + 1), way(m + 1);
    vector<long long> u(n + 1), v(m + 1);
    for (int i = 1; i <= n; i++) {
        p[0] = i;
        int j0 = 0;
        vector<long long> minv(m + 1, inf);
        vector<bool> used(m + 1, false);
        do {
            used[j0] = true;
            int i0 = p[j0], j1 = 0;
            long long delta = inf;
            for (int j = 1; j <= m; j++)
                if (!used[j]) {
                    long long cur = cost[i0][j] - u[i0] - v[j];
                    if (cur < minv[j])
                        minv[j] = cur, way[j] = j0;
                    if (minv[j] < delta)
                        delta = minv[j], j1 = j;
                }
            for (int j = 0; j <= m; j++)
                if (used[j])
                    u[p[j]] += delta, v[j] -= delta;
                else
                    minv[j] -= delta;
            j0 = j1;
        } while (p[j0] != 0);
        do {
            int j1 = way[j0];
            p[j0] = p[j1];
            j0 = j1;
        } while (j0);
    }
    vector<int> ans(n + 1);
    for (int j = 1; j <= m; j++)
        ans[p[j]] = j;
    return {-v[0], ans};
}
```

Listing 47: Min Cost Max Flow

```
//cat minCostMaxFlow.h | ./hash.sh
//7c6851
#pragma once
//status: not tested
const long long inf = 1e18;
struct mincostmaxflow {
    typedef long long ll;
```

```
struct edge {
    ll a, b, cap, cost, flow;
    size_t back;
};
vector<edge> e;
vector<vector<ll>> g;
ll n, s, t;
ll k = inf; // The maximum amount of flow allowed
mincostmaxflow(int _n, int _s, int _t) : n(_n), s(_s), t(_t) {
    g.resize(n);
}

void addedge(ll a, ll b, ll cap, ll cost) {
    edge e1 = {a, b, cap, cost, 0, g[b].size() };
    edge e2 = {b, a, 0, -cost, 0, g[a].size() };
    g[a].push_back((ll) e.size());
    e.push_back(e1);
    g[b].push_back((ll) e.size());
    e.push_back(e2);
}

// Returns {flow, cost}
pair<ll, ll> getflow() {
    ll flow = 0, cost = 0;
    while (flow < k) {
        vector<ll> id(n, 0);
        vector<ll> d(n, inf);
        vector<ll> q(n);
        vector<ll> p(n);
        vector<size_t> p_edge(n);
        ll qh = 0, qt = 0;
        q[qt++] = s;
        d[s] = 0;
        while (qh != qt) {
            ll v = q[qh++];
            id[v] = 2;
            if (qh == n) qh = 0;
            for (size_t i = 0; i < g[v].size(); i++) {
                edge& r = e[g[v][i]];
                if (r.flow < r.cap && d[v] + r.cost < d[r.b]) {
                    d[r.b] = d[v] + r.cost;
                    if (id[r.b] == 0) {
                        q[qt++] = r.b;
                        if (qt == n) qt = 0;
                    } else if (id[r.b] == 2) {
                        if (--qh == -1) qh = n - 1;
                        q[qh] = r.b;
                    }
                }
                id[r.b] = 1;
                p[r.b] = v;
                p_edge[r.b] = i;
            }
        }
        ll addflow = k - flow;
        for (ll v = t; v != s; v = p[v]) {
            ll pv = p[v];
            size_t pr = p_edge[v];
            addflow = min(addflow, e[g[pv][pr]].cap - e[g[pv][pr]].flow);
        }
        for (ll v = t; v != s; v = p[v]) {
            ll pv = p[v];
```

```
        size_t pr = p_edge[v], r = e[g[pv][pr]].back;
        e[g[pv][pr]].flow += addflow;
        e[g[v][r]].flow -= addflow;
        cost += e[g[pv][pr]].cost * addflow;
    }
    flow += addflow;
}
return {flow, cost};
};
```

Listing 48: MISC

Listing 49: Disjoint Set

```
//cat disjointSet.h | ./hash.sh
//8369d6
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/unionfind
//stress tests: tests/stress-tests/graphs/disjointSet.cpp
struct disjointSet {
    int numSets;
    vector<int> par;
    disjointSet(int n) : numSets(n), par(n, -1) {}
    disjointSet(const disjointSet& rhs) : numSets(rhs.numSets), par(rhs.par) {}
    int find(int x) {
        return par[x] < 0 ? x : par[x] = find(par[x]);
    }
    int sizeOfSet(int x) {
        return -par[find(x)];
    }
    bool merge(int x, int y) {
        if ((x = find(x)) == (y = find(y))) return false;
        if (par[y] < par[x]) swap(x, y);
        par[x] += par[y];
        par[y] = x;
        numSets--;
        return true;
    }
};
```

Listing 50: PBDS

```
//cat policy_based_data_structures.h | ./hash.sh
//807de9
#pragma once
//status: not tested
//place these includes *before* the '#define int long long' else compile error
//not using <bits/extc++.h> as it compile errors on codeforces c++20 compiler
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
//BST with extra functions https://codeforces.com/blog/entry/11080
//order_of_key - # of elements *strictly* less than given element
//find_by_order - find kth largest element, k is 0 based so find_by_order(0) returns min
    ↪ element
template<class T>
```

```
using indexed_set = tree<T, null_type, less<T>, rb_tree_tag,
    ↪ tree_order_statistics_node_update>;
//example initialization:
indexed_set<pair<long long, int>> is;
//hash table (apparently faster than unordered_map):
    ↪ https://codeforces.com/blog/entry/60737
//example initialization:
gp_hash_table<string, long long> ht;
```

Listing 51: Monotonic Stack

```
//cat monotonic_stack.h | ./hash.sh
//90f107
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/cartesian_tree
//stress tests: tests/stress-tests/misc/cntRectangles.cpp
//calculates array 'left' with:
//for every index j with left[i] < j < i: arr[j] > arr[i]
//and
//arr[left[i]] <= arr[i] if left[i] != -1
//
//O(n)
template<class T>
vector<int> monotonic_stack(const vector<T>& arr) {
    int n = arr.size();
    vector<int> left(n);
    for (int i = 0; i < n; i++) {
        int& j = left[i] = i - 1;
        while (j >= 0 && arr[j] > arr[i]) j = left[j];
    }
    return left;
}
```

Listing 52: Count Rectangles

```
//cat cntRectangles.h | ./hash.sh
//9510fe
#pragma once
#include "monotonic_stack.h"
//stress tests: tests/stress-tests/misc/cntRectangles.cpp
//given a 2D boolean matrix, calculate cnt[i][j]
//cnt[i][j] = the number of times an (i * j) rectangle appears in the matrix
//such that all cells in the rectangle are true
//Note cnt[0][j] and cnt[i][0] will contain garbage values
//O(R*C)
vector<vector<int>> getNumRectangles(const vector<vector<bool>>& grid) {
    const int n = grid.size(), m = grid[0].size();
    vector<vector<int>> cnt(n + 1, vector<int>(m + 1, 0));
    vector<int> arr(m, 0);
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++)
            arr[j] = grid[i][j] * (arr[j] + 1);
        vector<int> left = monotonic_stack(arr);
        vector<pair<int, int>> arrRev(m);
        for (int j = 0; j < m; j++)
            arrRev[m - 1 - j] = {arr[j], j};
        vector<int> right = monotonic_stack(arrRev);
        for (int j = 0; j < m; j++) {
            int rig = (m - 1 - right[m - 1 - j]) - j - 1, lef = j - left[j] - 1;
```

```
        cnt[arr[j]][rig + lef + 1]++;
        cnt[arr[j]][lef]--;
        cnt[arr[j]][rig]--;
    }
}
for (int i = 1; i <= n; i++)
    for (int k = 0; k < 2; k++)
        for (int j = m - 1; j >= 1; j--)
            cnt[i][j] += cnt[i][j + 1];
for (int j = 1; j <= m; j++)
    for (int i = n - 1; i >= 1; i--)
        cnt[i][j] += cnt[i + 1][j];
return cnt;
}
```

```
    x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
    return x ^ (x >> 31);
}
size_t operator()(uint64_t x) const {
    static const uint64_t FIXED_RANDOM =
        chrono::steady_clock::now().time_since_epoch().count();
    return splitmix64(x + FIXED_RANDOM);
}
};
//usage:
unordered_map<long long, int, custom_hash> safe_map;
#include "policy_based_data_structures.h"
gp_hash_table<long long, int, custom_hash> safe_hash_table;
```

Listing 53: Longest Increasing Subsequence

```
//cat longest_increasing_subsequence.h | ./hash.sh
//d47c52
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/static_range_lis_query
//returns array of indexes representing the longest *strictly* increasing subsequence
//for non-decreasing: pass in a vector<pair<T, int>> where second is 0, 1, ..., n-1
//alternatively, there's this https://codeforces.com/blog/entry/13225
template<class T>
vector<int> lis(const vector<T>& arr) {
    if (arr.empty()) return {};
    vector<int> dp{0}/*array of indexes into 'arr'*/, prev(arr.size(), -1);
    for (int i = 1; i < (int)arr.size(); i++) {
        auto it = lower_bound(dp.begin(), dp.end(), i, [&](int x, int y) -> bool {
            return arr[x] < arr[y];
        });
        if (it == dp.end()) {
            prev[i] = dp.back();
            dp.push_back(i);
        } else {
            prev[i] = it == dp.begin() ? -1 : *(it - 1);
            *it = i;
        }
        //here, dp.size() = length of LIS of prefix of arr ending at index i
    }
    vector<int> res(dp.size());
    for (int i = dp.back(), j = dp.size(); i != -1; i = prev[i])
        res[--j] = i;
    return res;
}
```

Listing 54: Safe Hash

```
//cat safehash.h | ./hash.sh
//d9ea53
#pragma once
//status: not tested
//source: https://codeforces.com/blog/entry/62393
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
```