

Listings

1	<b>CONTEST</b> . . . . .	1	38	Max Rectangle in Histogram . . . . .	13
2	Tips and Tricks . . . . .	1	39	Monotonic Stack . . . . .	13
3	Hash codes . . . . .	1	40	GCD Convolution . . . . .	13
4	Test on random inputs . . . . .	2	41	Iterate Chooses . . . . .	13
5	<b>MAX FLOW</b> . . . . .	2	42	Iterate Submasks . . . . .	13
6	Hungarian . . . . .	2	43	Iterate Supermasks . . . . .	14
7	Min Cost Max Flow . . . . .	2	44	Number of Distinct Subsequences DP . . . . .	14
8	<b>GRAPHS</b> . . . . .	3	45	PBDS . . . . .	14
9	Block Vertex Tree . . . . .	3	46	Random . . . . .	14
10	Bridge Tree . . . . .	3	47	Safe Hash . . . . .	14
11	Bridges and Cuts . . . . .	3	48	<b>RANGE DATA STRUCTURES</b> . . . . .	15
12	Strongly Connected Components . . . . .	4	49	Number Distinct Elements . . . . .	15
13	Centroid Decomposition . . . . .	5	50	Implicit Lazy Segment Tree . . . . .	15
14	Frequency Table of Tree Distance . . . . .	5	51	Kth Smallest . . . . .	16
15	Count Paths Per Node . . . . .	6	52	Merge Sort Tree . . . . .	16
16	Dijkstra . . . . .	6	53	BIT . . . . .	17
17	HLD . . . . .	6	54	RMQ . . . . .	17
18	Hopcroft Karp . . . . .	7	55	Lazy Segment Tree . . . . .	17
19	Kth Node on Path . . . . .	8	56	<b>STRINGS</b> . . . . .	18
20	LCA . . . . .	8	57	Binary Trie . . . . .	18
21	Rooted Tree Isomorphism . . . . .	8	58	Prefix Function . . . . .	19
22	<b>MATH</b> . . . . .	9	59	KMP String Matching . . . . .	19
23	Derangements . . . . .	9	60	Suffix Array . . . . .	19
24	Binary Exponentiation MOD . . . . .	9	61	LCP Array . . . . .	20
25	Fibonacci . . . . .	9	62	Longest Common Prefix Query . . . . .	20
26	Matrix Multiplication . . . . .	9	63	Palindrome Query . . . . .	21
27	Mobius Inversion . . . . .	10	64	Trie . . . . .	21
28	N Choose K MOD . . . . .	10			
29	Partitions . . . . .	10			
30	Prime Sieve . . . . .	10			
31	Row Reduce . . . . .	11			
32	Solve Linear Equations MOD . . . . .	11			
33	Euler’s Totient Phi Function . . . . .	12			
34	Tetration MOD . . . . .	12			
35	<b>MISC</b> . . . . .	12			
36	Cartesian Tree . . . . .	12			
37	Count Rectangles . . . . .	12			

CONTEST

Tips and Tricks

```
## Tips and Tricks
- [C++ tips and tricks](https://codeforces.com/blog/entry/74684)
- invokes RTE (Run Time Error) upon integer overflow
...

#pragma GCC optimize "trapv"
...

- invoke RTE for input error (e.g. reading a long long into an int)
...
cin.exceptions(cin.failbit);
...

- use pramgas for C++ speed boost
...

#pragma GCC optimize("O3,unroll-loops")
#pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
...

### Troubleshooting
...

/* stuff you should look for
 * int overflow, array bounds
 * special cases (n=1?)
 * do smth instead of nothing and stay organized
 * WRITE STUFF DOWN
 * DON'T GET STUCK ON ONE APPROACH
 */
...

Author: Benq

- refer to [KACTL
  ↳ Troubleshoot](https://github.com/kth-competitive-programming/kactl/blob/main/content/contest/tips_and_tricks.md)

## Sources

- [[Tutorial] GCC Optimization Pragmas](https://codeforces.com/blog/entry/96344)
- [Don't use rand(): a guide to random number generators in
  ↳ C++](https://codeforces.com/blog/entry/61587)
```

Hash codes

```
#!/bin/bash
#Hashes a file, ignoring all:
# - whitespace
# - comments
# - asserts
# - includes
# - pragmas
#Use to verify that code was correctly typed.

#usage:
#  chmod +x hash.sh
#  cat a.cpp | ./hash.sh
#or just copy this command:
```

```
#  cat a.cpp | sed -r '/(assert|include|pragma)/d' | cpp -fpreprocessed -P | tr -d
  ↳ '[:space:]' | md5sum | cut -c-6
sed -r '/(assert|include|pragma)/d' | cpp -fpreprocessed -P | tr -d '[:space:]' | md5sum | cut
  ↳ -c-6
```

Test on random inputs

```
#!/bin/bash
#runs 2 programs against each other on random inputs until they output different results
#source: https://github.com/Errichto/youtube/blob/master/testing/s.sh
#usage:
#  chmod +x test.sh
#  ./test.sh
for((i = 1; ; ++i)); do
    echo $i
    ./test.out > in
    diff --ignore-all-space <./a.out < in <<./brute.out < in || break
done
```

MAX FLOW

Hungarian

```
//cat hungarian.hpp | ./hash.sh
//935a16
#pragma once
//source: https://e-maxx.ru/algo/assignment_hungary
//
//input: cost[1...n][1...m] with 1 <= n <= m
//n workers, indexed 1, 2, ..., n
//m jobs, indexed 1, 2, ..., m
//it costs `cost[i][j]` to assign worker i to job j (1<=i<=n, 1<=j<=m)
//find minimum total cost to assign each worker to some distinct job
//0(n^2 * m)
//
//trick 1: set `cost[i][j]` to INF to say: "worker `i` cannot be assigned job `j`"
//trick 2: `cost[i][j]` can be negative, so to instead find max total cost over all matchings:
  ↳ set all `cost[i][j]` to `-cost[i][j]`.
//Now max total cost = - hungarian(cost).min_cost
const long long INF = 1e18;
struct weighted_match {
    long long min_cost;
    vector<int> matching;//worker `i` (1<=i<=n) is assigned to job `matching[i]`
    ↳ (1<=matching[i]<=m)
};
weighted_match hungarian(const vector<vector<long long>>& cost) {
    int n = ssize(cost) - 1, m = ssize(cost[0]) - 1;
    assert(n <= m);
    vector<int> p(m + 1), way(m + 1);
    vector<long long> u(n + 1), v(m + 1);
    for (int i = 1; i <= n; i++) {
        p[0] = i;
        int j0 = 0;
        vector<long long> minv(m + 1, INF);
        vector<bool> used(m + 1, 0);
        do {
```

```
used[j0] = 1;
int i0 = p[j0], j1 = 0;
long long delta = INF;
for (int j = 1; j <= m; j++)
    if (!used[j]) {
        long long cur = cost[i0][j] - u[i0] - v[j];
        if (cur < minv[j])
            minv[j] = cur, way[j] = j0;
        if (minv[j] < delta)
            delta = minv[j], j1 = j;
    }
for (int j = 0; j <= m; j++)
    if (used[j])
        u[p[j]] += delta, v[j] -= delta;
    else
        minv[j] -= delta;
j0 = j1;
} while (p[j0] != 0);
do {
    int j1 = way[j0];
    p[j0] = p[j1];
    j0 = j1;
} while (j0);
}
vector<int> ans(n + 1);
for (int j = 1; j <= m; j++)
    ans[p[j]] = j;
return {-v[0], ans};
}
```

Min Cost Max Flow

```
//cat min_cost_max_flow.hpp | ./hash.sh
//9dd6b6
#pragma once
//source: https://e-maxx.ru/algo/min_cost_flow
const long long INF = 1e18;
struct mcmf {
    using ll = long long;
    struct edge {
        int a, b;
        ll cap, cost, flow;
        int back;
    };
    const int N;
    vector<edge> e;
    vector<vector<int>> g;
    mcmf(int a_n : N(a_n), g(N) {}
    void add_edge(int a, int b, ll cap, ll cost) {
        edge e1 = {a, b, cap, cost, 0, ssize(g[b])};
        edge e2 = {b, a, 0, -cost, 0, ssize(g[a])};
        g[a].push_back(ssize(e));
        e.push_back(e1);
        g[b].push_back(ssize(e));
        e.push_back(e2);
    }
    pair<ll, ll> get_flow(int s, int t, ll total_flow) {
        ll flow = 0, cost = 0;
```

```
while (flow < total_flow) {
    vector<ll> d(N, INF);
    vector<int> p_edge(N), id(N, 0), q(N), p(N);
    int qh = 0, qt = 0;
    q[qt++] = s;
    d[s] = 0;
    while (qh != qt) {
        int v = q[qh++];
        id[v] = 2;
        if (qh == N)
            qh = 0;
        for (int i = 0; i < ssize(g[v]); i++) {
            const edge& r = e[g[v][i]];
            if (r.flow < r.cap && d[v] + r.cost < d[r.b]) {
                d[r.b] = d[v] + r.cost;
                if (id[r.b] == 0) {
                    q[qt++] = r.b;
                    if (qt == N)
                        qt = 0;
                } else if (id[r.b] == 2) {
                    if (--qh == -1)
                        qh = N - 1;
                    q[qh] = r.b;
                }
                id[r.b] = 1;
                p[r.b] = v;
                p_edge[r.b] = i;
            }
        }
    }
    if (d[t] == INF)
        break;
    ll addflow = total_flow - flow;
    for (int v = t; v != s; v = p[v]) {
        int pv = p[v], pr = p_edge[v];
        addflow = min(addflow, e[g[pv][pr]].cap - e[g[pv][pr]].flow);
    }
    for (int v = t; v != s; v = p[v]) {
        int pv = p[v], pr = p_edge[v], r = e[g[pv][pr]].back;
        e[g[pv][pr]].flow += addflow;
        e[g[v][r]].flow -= addflow;
        cost += e[g[pv][pr]].cost * addflow;
    }
    flow += addflow;
}
return {flow, cost};
};
```

GRAPHS

Block Vertex Tree

```
//cat block_vertex_tree.hpp | ./hash.sh
//a5c2b9
#pragma once
#include "bridges_and_cuts.hpp"
```

```
//returns adjacency list of block vertex tree
//usage:
// graph_info cc = bridge_and_cut(adj, m);
// vector<vector<int>> bvt = block_vertex_tree(adj, cc);
//to loop over each *unique* bcc containing a node v:
// for (int bccid : bvt[v]) {
//     bccid -= n;
//     ...
// }
//to loop over each *unique* node inside a bcc:
// for (int v : bvt[bccid + n]) {
//     ...
// }
vector<vector<int>> block_vertex_tree(const vector<vector<pair<int, int>>& adj, const
    graph_info& cc) {
    int n = ssize(adj);
    vector<vector<int>> bvt(n + cc.num_bccs);
    vector<bool> vis(cc.num_bccs, 0);
    for (int v = 0; v < n; v++) {
        for (auto [_, e_id] : adj[v]) {
            int bccid = cc.bcc_id[e_id];
            if (!vis[bccid]) {
                vis[bccid] = 1;
                bvt[v].push_back(bccid + n); //add edge between original node, and bcc node
                bvt[bccid + n].push_back(v);
            }
        }
        for (int bccid : bvt[v])
            vis[bccid - n] = 0;
    }
    return bvt;
}
```

Bridge Tree

```
//cat bridge_tree.hpp | ./hash.sh
//8eb014
#pragma once
#include "bridges_and_cuts.hpp"
//never adds multiple edges as bridges_and_cuts.hpp correctly marks them as non-bridges
//usage:
// graph_info cc = bridge_and_cut(adj, m);
// vector<vector<int>> bt = bridge_tree(adj, cc);
vector<vector<int>> bridge_tree(const vector<vector<pair<int, int>>& adj, const graph_info&
    cc) {
    vector<vector<int>> tree(cc.num_2_edge_ccs);
    for (int i = 0; i < ssize(adj); i++)
        for (auto [to, e_id] : adj[i])
            if (cc.is_bridge[e_id])
                tree[cc.two_edge_ccid[i]].push_back(cc.two_edge_ccid[to]);
    return tree;
}
```

Bridges and Cuts

```
//cat bridges_and_cuts.hpp | ./hash.sh
//3f21b9
```

```
#pragma once
//O(n+m) time & space
//2 edge cc and bcc stuff doesn't depend on each other, so delete whatever is not needed
//handles multiple edges
//
//example initialization of `adj`:
//for (int i = 0; i < m; i++) {
//    int u, v;
//    cin >> u >> v;
//    u--, v--;
//    adj[u].emplace_back(v, i);
//    adj[v].emplace_back(u, i);
//}
struct graph_info {
    //2 edge connected component stuff (e.g. components split by bridge edges)
    //↳ https://cp-algorithms.com/graph/bridge-searching.html
    int num_2_edge_ccs;
    vector<bool> is_bridge; //edge id -> 1 iff bridge edge
    vector<int> two_edge_ccid; //node -> id of 2 edge component (which are labeled 0, 1, ...,
        //↳ `num_2_edge_ccs`-1)
    //bi connected component stuff (e.g. components split by cut/articulation nodes)
    //↳ https://cp-algorithms.com/graph/cutpoints.html
    int num_bccs;
    vector<bool> is_cut; //node -> 1 iff cut node
    vector<int> bcc_id; //edge id -> id of bcc (which are labeled 0, 1, ..., `num_bccs`-1)
};
graph_info bridge_and_cut(const vector<vector<pair<int/*neighbor*/, int/*edge id*/>>&
    adj/*undirected graph*/, int m/*number of edges*/) {
    //stuff for both (always keep)
    int n = ssize(adj), timer = 1;
    vector<int> tin(n, 0);
    //2 edge cc stuff (delete if not needed)
    int num_2_edge_ccs = 0;
    vector<bool> is_bridge(m, 0);
    vector<int> two_edge_ccid(n), node_stack;
    node_stack.reserve(n);
    //bcc stuff (delete if not needed)
    int num_bccs = 0;
    vector<bool> is_cut(n, 0);
    vector<int> bcc_id(m), edge_stack;
    edge_stack.reserve(m);
    auto dfs = [&](auto self, int v, int p_id) -> int {
        int low = tin[v] = timer++; deg = 0;
        node_stack.push_back(v);
        for (auto [to, e_id] : adj[v]) {
            if (e_id == p_id)
                continue;
            if (!tin[to]) {
                edge_stack.push_back(e_id);
                int low_ch = self(self, to, e_id);
                if (low_ch >= tin[v]) {
                    is_cut[v] = 1;
                    while (1) {
                        int edge = edge_stack.back();
                        edge_stack.pop_back();
                        bcc_id[edge] = num_bccs;
                        if (edge == e_id)
                            break;
                    }
                }
            }
        }
    };
}
```

```
        num_bccs++;
    }
    low = min(low, low_ch);
    deg++;
} else if (tin[to] < tin[v]) {
    edge_stack.push_back(e_id);
    low = min(low, tin[to]);
}
}
if (p_id == -1)
    is_cut[v] = (deg > 1);
if (tin[v] == low) {
    if (p_id != -1)
        is_bridge[p_id] = 1;
    while (1) {
        int node = node_stack.back();
        node_stack.pop_back();
        two_edge_ccid[node] = num_2_edge_ccs;
        if (node == v)
            break;
    }
    num_2_edge_ccs++;
}
return low;
};
for (int i = 0; i < n; i++)
    if (!tin[i])
        dfs(dfs, i, -1);
return {num_2_edge_ccs, is_bridge, two_edge_ccid, num_bccs, is_cut, bcc_id};
}
```

Strongly Connected Components

```
//cat strongly_connected_components.hpp | ./hash.sh
//69acd7
#pragma once
//source: https://github.com/kth-competitive-programming/
// kactl/blob/main/content/graph/SCC.h
struct scc_info {
    int num_sccs;
    //scc's are labeled 0,1,...,`num_sccs-1`
    //scc_id[i] is the id of the scc containing node `i`
    //for each edge i -> j: scc_id[i] >= scc_id[j] (reverse topo order of scc's)
    vector<int> scc_id;
};
//NOLINTNEXTLINE(readability-identifier-naming)
scc_info SCC(const vector<vector<int>>& adj/*directed, unweighted graph*/) {
    int n = ssize(adj), timer = 1, num_sccs = 0;
    vector<int> tin(n, 0), scc_id(n, -1), node_stack;
    node_stack.reserve(n);
    auto dfs = [&](auto self, int v) -> int {
        int low = tin[v] = timer++;
        node_stack.push_back(v);
        for (int to : adj[v]) {
            if (scc_id[to] < 0)
                low = min(low, tin[to] ? tin[to] : self(self, to));
        }
        if (tin[v] == low) {

```

```
            while (1) {
                int node = node_stack.back();
                node_stack.pop_back();
                scc_id[node] = num_sccs;
                if (node == v)
                    break;
            }
            num_sccs++;
        }
        return low;
    };
    for (int i = 0; i < n; i++) {
        if (!tin[i])
            dfs(dfs, i);
    }
    return {num_sccs, scc_id};
}
```

Centroid Decomposition

```
//cat centroid_decomposition.hpp | ./hash.sh
//71e2e5
#pragma once

// Time and Space complexity are given in terms of n where n is the number of nodes in the
//   ⇐ forest
// Time complexity O(n log n)
// Space complexity O(n)

// Given an unweighted, undirected forest and a function,
// centroid_decomp runs the function on every decomposition

// Example usage:
// centroid_decomp decomp(adj, [&](const vector<vector<int>>& adj_removed_edges, int cent) ->
//   ⇐ void {
//     ...
// });
template <typename F> struct centroid_decomp {
    vector<vector<int>> adj;
    F func;
    vector<int> sub_sz;
    centroid_decomp(const vector<vector<int>>& a_adj/*undirected forest*/, const F& a_func)
        : adj(a_adj), func(a_func), sub_sz(ssize(adj), -1) {
        for (int i = 0; i < ssize(adj); i++)
            if (sub_sz[i] == -1)
                dfs(i);
    }
    void calc_subtree_sizes(int u, int p = -1) {
        sub_sz[u] = 1;
        for (int v : adj[u]) {
            if (v == p)
                continue;
            calc_subtree_sizes(v, u);
            sub_sz[u] += sub_sz[v];
        }
    }
    void dfs(int u) {
        calc_subtree_sizes(u);

```

```
for (int p = -1, sz_root = sub_sz[u];) {
    auto big_ch = find_if(adj[u].begin(), adj[u].end(), [&](int v) -> bool {
        return v != p && 2 * sub_sz[v] > sz_root;
    });
    if (big_ch == adj[u].end())
        break;
    p = u, u = *big_ch;
}
func(adj, u);
for (int v : adj[u]) {
    //each node is adjacent to O(logn) centroids
    adj[v].erase(find(adj[v].begin(), adj[v].end(), u));
    dfs(v);
}
};
```

Frequency Table of Tree Distance

```
//cat count_paths_per_length.hpp | ./hash.sh
//182b70
#pragma once
#include "../kactl/content/numerical/FastFourierTransform.h"
#include "centroid_decomposition.hpp"
//returns array `num_paths` where `num_paths[i]` = # of paths in tree with `i` edges
//O(n log^2 n)
vector<long long> count_paths_per_length(const vector<vector<int>>& adj/*unrooted, connected
    ⇨ tree*/) {
    vector<long long> num_paths(ssize(adj), 0);
    centroid_decomp decomp(adj, [&](const vector<vector<int>>& adj_removed_edges, int cent) ->
        ⇨ void {
        vector<vector<double>> child_depths;
        for (int to : adj_removed_edges[cent]) {
            child_depths.emplace_back(1, 0.0);
            for (queue<pair<int, int>> q({{to, cent}}); !q.empty();) {
                child_depths.back().push_back(ssize(q));
                queue<pair<int, int>> new_q;
                while (!q.empty()) {
                    auto [curr, par] = q.front();
                    q.pop();
                    for (int ch : adj_removed_edges[curr]) {
                        if (ch == par)
                            continue;
                        new_q.emplace(ch, curr);
                    }
                }
                swap(q, new_q);
            }
        }
    sort(child_depths.begin(), child_depths.end(), [&](const auto & x, const auto & y) {
        return x.size() < y.size();
    });
    vector<double> total_depth(1, 1.0);
    for (const auto& cnt_depth : child_depths) {
        auto prod = conv(total_depth, cnt_depth);
        for (int i = 1; i < ssize(prod); i++)
            num_paths[i] += llround(prod[i]);
        total_depth.resize(ssize(cnt_depth), 0.0);
    }
}
```

```
for (int i = 1; i < ssize(cnt_depth); i++)
    total_depth[i] += cnt_depth[i];
}
return num_paths;
}
```

Count Paths Per Node

```
//cat count_paths_per_node.hpp | ./hash.sh
//2077d2
#pragma once
#include "centroid_decomposition.hpp"
//0-based nodes
//returns array `num_paths` where `num_paths[i]` = number of paths with k edges where node `i`
    ⇨ is on the path
//O(n log n)
vector<long long> count_paths_per_node(const vector<vector<int>>& adj/*unrooted tree*/, int k)
    ⇨ {
    vector<long long> num_paths(ssize(adj));
    centroid_decomp decomp(adj, [&](const vector<vector<int>>& adj_removed_edges, int cent) ->
        ⇨ void {
        vector<int> pre_d(1, 1), cur_d(1);
        auto dfs = [&](auto self, int u, int p, int d) -> long long {
            if (d > k)
                return 0;
            if (ssize(cur_d) <= d)
                cur_d.push_back(0);
            cur_d[d]++;
            long long cnt = 0;
            if (k - d < ssize(pre_d))
                cnt += pre_d[k - d];
            for (int v : adj_removed_edges[u])
                if (v != p)
                    cnt += self(self, v, u, d + 1);
            num_paths[u] += cnt;
            return cnt;
        };
        auto dfs_child = [&](int child) -> long long {
            long long cnt = dfs(dfs, child, cent, 1);
            pre_d.resize(ssize(cur_d));
            for (int i = 1; i < ssize(cur_d) && cur_d[i]; i++)
                pre_d[i] += cur_d[i], cur_d[i] = 0;
            return cnt;
        };
        for (int child : adj_removed_edges[cent])
            num_paths[cent] += dfs_child(child);
        pre_d = vector<int>(1);
        cur_d = vector<int>(1);
        for (auto it = adj_removed_edges[cent].rbegin(); it != adj_removed_edges[cent].rend();
            ⇨ it++)
            dfs_child(*it);
    });
    return num_paths;
}
```

```
//cat dijkstra.hpp | ./hash.sh
//aa6eda
#pragma once
//returns array `len` where `len[i]` = shortest path from node `start` to node `i`
//For example `len[start]` will always = 0
const long long INF = 1e18;
vector<long long> dijkstra(const vector<vector<pair<int, long long>>>& adj /*directed or
    ↳ undirected, weighted graph*/, int start) {
    using node = pair<long long, int>;
    vector<long long> len(ssize(adj), INF);
    len[start] = 0;
    priority_queue<node, vector<node>, greater<node>> q;
    q.emplace(0, start);
    while (!q.empty()) {
        auto [curr_len, v] = q.top();
        q.pop();
        if (len[v] < curr_len)
            continue; //important check: O(n*m) without it
        for (auto [to, weight] : adj[v])
            if (len[to] > weight + len[v]) {
                len[to] = weight + len[v];
                q.emplace(len[to], to);
            }
    }
    return len;
}
```

HLD

```
//cat hld.hpp | ./hash.sh
//d30c4a
#pragma once
//source: https://codeforces.com/blog/entry/53170
//mnemonic: Heavy Light Decomposition
//NOLINTNEXTLINE(readability-identifier-naming)
struct HLD {
    struct node {
        int sub_sz = 1, par = -1, time_in = -1, next = -1;
    };
    vector<node> tree;
    HLD(vector<vector<int>>& adj /*forest of unrooted trees*/) : tree(ssize(adj)) {
        for (int i = 0, timer = 0; i < ssize(adj); i++) {
            if (tree[i].next == -1) { //lowest indexed node in each tree becomes root
                tree[i].next = i;
                dfs1(i, adj);
                dfs2(i, adj, timer);
            }
        }
    }
    void dfs1(int v, vector<vector<int>>& adj) {
        auto par = find(adj[v].begin(), adj[v].end(), tree[v].par);
        if (par != adj[v].end())
            adj[v].erase(par);
        for (int& to : adj[v]) {
            tree[to].par = v;
            dfs1(to, adj);
            tree[v].sub_sz += tree[to].sub_sz;
            if (tree[to].sub_sz > tree[adj[v][0]].sub_sz)
```

```
                swap(to, adj[v][0]);
        }
    }
    void dfs2(int v, const vector<vector<int>>& adj, int& timer) {
        tree[v].time_in = timer++;
        for (int to : adj[v]) {
            tree[to].next = (timer == tree[v].time_in + 1 ? tree[v].next : to);
            dfs2(to, adj, timer);
        }
    }
    // Returns inclusive-exclusive intervals (of time_in's) corresponding to the path between
    ↳ u and v, not necessarily in order
    // This can answer queries for "is some node `x` on some path" by checking if the
    ↳ tree[x].time_in is in any of these intervals
    // u, v must be in the same component
    vector<pair<int, int>> path(int u, int v) const {
        vector<pair<int, int>> res;
        for (; v = tree[tree[v].next].par) {
            if (tree[v].time_in < tree[u].time_in)
                swap(u, v);
            if (tree[tree[v].next].time_in <= tree[u].time_in) {
                res.emplace_back(tree[u].time_in, tree[v].time_in + 1);
                return res;
            }
            res.emplace_back(tree[tree[v].next].time_in, tree[v].time_in + 1);
        }
    }
    // Returns interval (of time_in's) corresponding to the subtree of node i
    // This can answer queries for "is some node `x` in some other node's subtree" by checking
    ↳ if tree[x].time_in is in this interval
    pair<int, int> subtree(int i) const {
        return {tree[i].time_in, tree[i].time_in + tree[i].sub_sz};
    }
    // Returns lca of nodes u and v
    // u, v must be in the same component
    int lca(int u, int v) const {
        for (; v = tree[tree[v].next].par) {
            if (tree[v].time_in < tree[u].time_in)
                swap(u, v);
            if (tree[tree[v].next].time_in <= tree[u].time_in)
                return u;
        }
    }
};
```

Hopcroft Karp

```
//cat hopcroft_karp.hpp | ./hash.sh
//5d1682
#pragma once
//source: https://github.com/foreverbell/acm-icpc-cheat-sheet/
// blob/master/src/graph-algorithm/hopcroft-karp.cpp
//Worst case O(E*sqrt(V)) but faster in practice
struct match {
    // # of edges in matching (which = size of min vertex cover by König's theorem)
    int size_of_matching;
    //an arbitrary max matching is found. For this matching:
    //if l_to_r[node_left] == -1:
```

```
// node_left is not in matching
//else:
// the edge `node_left` <=> l_to_r[node_left] is in the matching
//
//similarly for r_to_l with edge r_to_l[node_right] <=> node_right in matching if
    ↪ r_to_l[node_right] != -1
//matchings stored in l_to_r and r_to_l are the same matching
//provides way to check if any node/edge is in matching
vector<int> l_to_r, r_to_l;
//an arbitrary min vertex cover is found. For this mvc: mvc_l[node_left] is 1 iff
    ↪ node_left is in the min vertex cover (same for mvc_r)
//if mvc_l[node_left] is 0, then node_left is in the corresponding maximal independent set
vector<bool> mvc_l, mvc_r;
};
//Think of the bipartite graph as having a left side (with size lsz) and a right side (with
    ↪ size rsz).
//Nodes on left side are indexed 0,1,...,lsz-1
//Nodes on right side are indexed 0,1,...,rsz-1
//
//`adj` is like a directed adjacency list containing edges from left side -> right side:
//To initialize `adj`: For every edge node_left <=> node_right, do:
    ↪ adj[node_left].push_back(node_right)
match hopcroft_karp(const vector<vector<int>>& adj/*bipartite graph*/, int rsz/*number of
    ↪ nodes on right side*/) {
    int size_of_matching = 0, lsz = ssize(adj);
    vector<int> l_to_r(lsz, -1), r_to_l(rsz, -1);
    while (1) {
        queue<int> q;
        vector<int> level(lsz, -1);
        for (int i = 0; i < lsz; i++)
            if (l_to_r[i] == -1)
                level[i] = 0, q.push(i);
        bool found = 0;
        vector<bool> mvc_l(lsz, 1), mvc_r(rsz, 0);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            mvc_l[u] = 0;
            for (int x : adj[u]) {
                mvc_r[x] = 1;
                int v = r_to_l[x];
                if (v == -1)
                    found = 1;
                else if (level[v] == -1) {
                    level[v] = level[u] + 1;
                    q.push(v);
                }
            }
        }
        if (!found)
            return {size_of_matching, l_to_r, r_to_l, mvc_l, mvc_r};
        auto dfs = [&](auto self, int u) -> bool {
            for (int x : adj[u]) {
                int v = r_to_l[x];
                if (v == -1 || (level[u] + 1 == level[v] && self(self, v))) {
                    l_to_r[u] = x;
                    r_to_l[x] = u;
                    return 1;
                }
            }
        };
    }
```

```
    }
    level[u] = 1e9; //acts as visited array
    return 0;
};
for (int i = 0; i < lsz; i++)
    size_of_matching += (l_to_r[i] == -1 && dfs(dfs, i));
}
```

Kth Node on Path

```
//cat kth_node_on_path.hpp | ./hash.sh
//c59307
#pragma once
#include "lca.hpp"
//consider path {u, u's par, ..., LCA(u,v), ..., v's par, v}. This returns the node at index k
//assumes 0 <= k <= number of edges on path from u to v
// u, v must be in the same component
//
//To loop over all nodes on a path from u to v:
//kth_node_on_path kpath(adj);
//for (int i = 0; i <= kpath.lca.dist_edges(u, v); i++) {
//    int node = kpath.query(u, v, i);
//    ...
struct kth_node_on_path {
    LCA lca;
    kth_node_on_path(const vector<vector<pair<int, long long>>&& adj/*forest of weighted
        ↪ trees*/): lca(adj) {}
    int query(int u, int v, int k) const {
        int lca_uv = lca.get_lca(u, v);
        int u_lca = lca.tree[u].depth - lca.tree[lca_uv].depth;
        int v_lca = lca.tree[v].depth - lca.tree[lca_uv].depth;
        assert(0 <= k && k <= u_lca + v_lca);
        return k <= u_lca ? lca.kth_par(u, k) : lca.kth_par(v, u_lca + v_lca - k);
    }
};
```

LCA

```
//cat lca.hpp | ./hash.sh
//b28532
#pragma once
//https://codeforces.com/blog/entry/74847
//mnemonic: Least/Lowest Common Ancestor
//NOLINTNEXTLINE(readability-identifier-naming)
struct LCA {
    struct node {
        int jmp = -1, jmp_edges = 0, par = -1, depth = 0;
        long long dist = 0LL;
    };
    vector<node> tree;
    LCA(const vector<vector<pair<int, long long>>&& adj/*forest of weighted trees*/):
        ↪ tree(ssize(adj)) {
        for (int i = 0; i < ssize(adj); i++) {
            if (tree[i].jmp == -1) { //lowest indexed node in each tree becomes root
                tree[i].jmp = i;
                dfs(i, adj);
            }
        }
    }
```



```
    }
}
}
void dfs(int v, const vector<vector<pair<int, long long>>& adj) {
    int jmp, jmp_edges;
    if (tree[v].jmp != v && tree[v].jmp_edges == tree[tree[v].jmp].jmp_edges)
        jmp = tree[tree[v].jmp].jmp, jmp_edges = 2 * tree[v].jmp_edges + 1;
    else
        jmp = v, jmp_edges = 1;
    for (auto [ch, w] : adj[v]) {
        if (ch == tree[v].par)
            continue;
        tree[ch] = {
            jmp,
            jmp_edges,
            v,
            1 + tree[v].depth,
            w + tree[v].dist
        };
        dfs(ch, adj);
    }
}
//traverse up k edges in O(log(k)). So with k=1 this returns `v`'s parent
int kth_par(int v, int k) const {
    k = min(k, tree[v].depth);
    while (k > 0) {
        if (tree[v].jmp_edges <= k) {
            k -= tree[v].jmp_edges;
            v = tree[v].jmp;
        } else {
            k--;
            v = tree[v].par;
        }
    }
    return v;
}
// x, y must be in the same component
int get_lca(int x, int y) const {
    if (tree[x].depth < tree[y].depth)
        swap(x, y);
    x = kth_par(x, tree[x].depth - tree[y].depth);
    while (x != y) {
        if (tree[x].jmp != tree[y].jmp)
            x = tree[x].jmp, y = tree[y].jmp;
        else
            x = tree[x].par, y = tree[y].par;
    }
    return x;
}
int dist_edges(int x, int y) const {
    return tree[x].depth + tree[y].depth - 2 * tree[get_lca(x, y)].depth;
}
long long dist_weight(int x, int y) const {
    return tree[x].dist + tree[y].dist - 2 * tree[get_lca(x, y)].dist;
}
};
```

Rooted Tree Isomorphism

```
//cat subtree_isomorphism.hpp | ./hash.sh
//455aef
#pragma once

// Complexity given in terms of n where n is the number of nodes in the forest
// Time complexity O(n log n)
// Space complexity O(n)

// Given an undirected or directed rooted forest
// subtree_iso classifies each rooted subtree
// minimum label of each tree becomes root
struct iso_info {
    int num_distinct_subtrees; //0 <= id[i] < num_distinct_subtrees for all i
    vector<int> id; //id[u] == id[v] iff subtree u is isomorphic to subtree v
};

iso_info subtree_iso(const vector<vector<int>>& adj) {
    vector<int> id(ssize(adj), -1);
    map<vector<int>, int> hashes;
    auto dfs = [&](auto self, int u, int p) -> int {
        vector<int> ch_ids;
        ch_ids.reserve(ssize(adj[u]));
        for (int v : adj[u]) {
            if (v != p)
                ch_ids.push_back(self(self, v, u));
        }
        sort(ch_ids.begin(), ch_ids.end());
        auto it = hashes.find(ch_ids);
        if (it == hashes.end())
            return id[u] = hashes[ch_ids] = ssize(hashes);
        return id[u] = it->second;
    };
    for (int i = 0; i < ssize(adj); i++)
        if (id[i] == -1)
            dfs(dfs, i, i);
    return {ssize(hashes), id};
}
```

MATH

Derangements

```
//cat derangements.hpp | ./hash.sh
//64d325
#pragma once
//https://oeis.org/A000166
//
//for a permutation of size i:
//there are (i-1) places to move 0 to not be at index 0. Let's say we moved 0 to index j (j>0).
//If we move value j to index 0 (forming a cycle of length 2), then there are dp[i-2]
//    ↳ derangements of the remaining i-2 elements
//else there are dp[i-1] derangements of the remaining i-1 elements (including j)
vector<long long> derangements(int n, long long mod) {
    vector<long long> dp(n, 0);
    dp[0] = 1;
    for (int i = 2; i < n; i++)
```

```
    dp[i] = (i - 1) * (dp[i - 1] + dp[i - 2]) % mod;
    return dp;
}
```

Binary Exponentiation MOD

```
//cat binary_exponentiation_mod.hpp | ./hash.sh
//92a3ef
#pragma once
//returns (base^pw)%mod in O(log(pw)), but returns 1 for 0^0
//
//What if base doesn't fit in long long?
//Since (base^pw)%mod == ((base%mod)^pw)%mod we can calculate base under mod of `mod`
//
//What if pw doesn't fit in long long?
//assuming mod is prime:
//((base^pw)%mod == (base^(pw%(mod-1))))%mod (from Fermat's little theorem)
//so calculate pw under mod of `mod-1`
//note `mod-1` is not prime, so you need to be able to calculate `pw%(mod-1)` without division
long long bin_exp(long long base, long long pw, long long mod) {
    assert(0 <= pw && 0 <= base && 1 <= mod);
    long long res = 1;
    base %= mod;
    while (pw > 0) {
        if (pw & 1)
            res = res * base % mod;
        base = base * base % mod;
        pw >>= 1;
    }
    return res;
}
```

Fibonacci

```
//cat fibonacci.hpp | ./hash.sh
//78a41f
#pragma once
//https://codeforces.com/blog/entry/14516
//O(log(n))
unordered_map<long long, long long> table;
long long fib(long long n, long long mod) {
    if (n < 2)
        return 1;
    if (table.find(n) != table.end())
        return table[n];
    table[n] = (fib((n + 1) / 2, mod) * fib(n / 2, mod) + fib((n - 1) / 2, mod) * fib((n - 2) / 2, mod)) % mod;
    return table[n];
}
```

Matrix Multiplication

```
//cat matrix_mult.hpp | ./hash.sh
//910018
#pragma once
```

```
// source: https://codeforces.com/blog/entry/80195

// generic matrix multiplication (not overflow safe)
// will RTE if the given matrices are not compatible
// Time: O(n * m * inner)
// Space: O(n * m)

template <typename T> vector<vector<T>> operator * (const vector<vector<T>>& a, const
    ⇨ vector<vector<T>>& b) {
    assert(ssize(a[0]) == ssize(b));
    int n = ssize(a), m = ssize(b[0]), inner = ssize(b);
    vector<vector<T>> c(n, vector<T>(m));
    for (int i = 0; i < n; i++)
        for (int k = 0; k < inner; k++)
            for (int j = 0; j < m; j++)
                c[i][j] += a[i][k] * b[k][j];

    return c;
}
```

Mobius Inversion

```
//cat mobius_inversion.hpp | ./hash.sh
//811515
#pragma once
//mobius[i] = 0 iff there exists a prime p s.t. i%(p^2)=0
//mobius[i] = -1 iff i has an odd number of distinct prime factors
//mobius[i] = 1 iff i has an even number of distinct prime factors
const int N = 1e6 + 10;
int mobius[N];
void calc_mobius() {
    mobius[1] = 1;
    for (int i = 1; i < N; i++)
        for (int j = i + i; j < N; j += i)
            mobius[j] -= mobius[i];
}
```

N Choose K MOD

```
//cat n_choose_k_mod.hpp | ./hash.sh
//c7fb35
#pragma once
//for mod inverse
#include "binary_exponentiation_mod.hpp"
// usage:
//     n_choose_k nk(n, 1e9+7) to use `choose`, `inv` with inputs strictly < n
// or:
//     n_choose_k nk(mod, mod) to use `choose_lucas` with arbitrarily large inputs
struct n_choose_k {
    n_choose_k(int n, long long a_mod) : mod(a_mod), fact(n, 1), inv_fact(n, 1) {
        //this implementation doesn't work if n > mod because n! % mod = 0 when n >= mod. So
        ⇨ `inv_fact` array will be all 0's
        assert(max(n, 2) <= mod);
        //assert mod is prime. mod is intended to fit inside an int so that
        //multiplications fit in a longlong before being modded down. So this
        //will take sqrt(2^31) time
        for (int i = 2; i * i <= mod; i++)
            assert(mod % i);
    }
```

```
for (int i = 2; i < n; i++)
    fact[i] = fact[i - 1] * i % mod;
inv_fact.back() = bin_exp(fact.back(), mod - 2, mod);
for (int i = n - 2; i >= 2; i--)
    inv_fact[i] = inv_fact[i + 1] * (i + 1) % mod;
}
//classic n choose k
//fails when n >= mod
long long choose(int n, int k) const {
    if (k < 0 || k > n)
        return 0;
    //now we know 0 <= k <= n so 0 <= n
    return fact[n] * inv_fact[k] % mod * inv_fact[n - k] % mod;
}
//lucas theorem to calculate n choose k in O(log(k))
//need to calculate all factorials in range [0,mod), so O(mod) time&space, so need
    ↪ smallish prime mod (< 1e6 maybe)
//handles n >= mod correctly
long long choose_lucas(long long n, long long k) const {
    if (k < 0 || k > n)
        return 0;
    if (k == 0 || k == n)
        return 1;
    return choose_lucas(n / mod, k / mod) * choose(int(n % mod), int(k % mod)) % mod;
}
//returns x such that x * n % mod == 1
long long inv(int n) const {
    assert(1 <= n); //don't divide by 0 :)
    return fact[n - 1] * inv_fact[n] % mod;
}
long long mod;
vector<long long> fact, inv_fact;
};
```

Partitions

```
//cat partitions.hpp | ./hash.sh
//e7ae42
#pragma once
//https://oeis.org/A000041
//O(n sqrt n) time, but small-ish constant factor (there does exist a O(n log n) solution as
    ↪ well)
vector<long long> partitions(int n, long long mod) {
    vector<long long> dp(n, 1);
    for (int i = 1; i < n; i++) {
        long long sum = 0;
        for (int j = 1, pent = 1, sign = 1; pent <= i; j++, pent += 3 * j - 2, sign = -sign) {
            if (pent + j <= i)
                sum += dp[i - pent - j] * sign + mod;
            sum += dp[i - pent] * sign + mod;
        }
        dp[i] = sum % mod;
    }
    return dp;
}
```

Prime Sieve

```
//cat prime_sieve.hpp | ./hash.sh
//25a877
#pragma once
bool is_prime(int val, const vector<int>& sieve) {
    assert(val < ssize(sieve));
    return val >= 2 && sieve[val] == val;
}
vector<int> get_prime_factors(int val, const vector<int>& sieve) {
    assert(val < ssize(sieve));
    vector<int> factors;
    while (val > 1) {
        int p = sieve[val];
        factors.push_back(p);
        val /= p;
    }
    return factors;
}
//returns array `sieve` where `sieve[i]` = some prime factor of `i`
vector<int> get_sieve(int n) {
    vector<int> sieve(n);
    iota(sieve.begin(), sieve.end(), 0);
    for (int i = 2; i * i < n; i++)
        if (sieve[i] == i)
            for (int j = i * i; j < n; j += i)
                sieve[j] = i;
    return sieve;
}
```

Row Reduce

```
//cat row_reduce.hpp | ./hash.sh
//c812f1
#pragma once
//for mod inverse
#include "binary_exponentiation_mod.hpp"
//First `cols` columns of mat represents a matrix to be left in reduced row echelon form
//Row operations will be performed to all later columns
//
//example usage:
// auto [rank, det] = row_reduce(mat, ssize(mat[0]), mod) //row reduce matrix with no extra
    ↪ columns
pair<int/*rank*/, long long/*determinant*/> row_reduce(vector<vector<long long>>& mat, int
    ↪ cols, long long mod) {
    int n = ssize(mat), m = ssize(mat[0]), rank = 0;
    long long det = 1;
    assert(cols <= m);
    for (int col = 0; col < cols && rank < n; col++) {
        //find arbitrary pivot and swap pivot to current row
        for (int i = rank; i < n; i++)
            if (mat[i][col] != 0) {
                if (rank != i)
                    det = det == 0 ? 0 : mod - det;
                swap(mat[i], mat[rank]);
                break;
            }
        if (mat[rank][col] == 0) {
            det = 0;
            continue;
        }
    }
}
```

```
    }
    det = det * mat[rank][col] % mod;
    //make pivot 1 by dividing row by inverse of pivot
    long long a_inv = bin_exp(mat[rank][col], mod - 2, mod);
    for (int j = 0; j < m; j++)
        mat[rank][j] = mat[rank][j] * a_inv % mod;
    //zero-out all numbers above & below pivot
    for (int i = 0; i < n; i++)
        if (i != rank && mat[i][col] != 0) {
            long long val = mat[i][col];
            for (int j = 0; j < m; j++) {
                mat[i][j] -= mat[rank][j] * val % mod;
                if (mat[i][j] < 0)
                    mat[i][j] += mod;
            }
        }
    rank++;
}
assert(rank <= min(n, cols));
return {rank, det};
}
```

Solve Linear Equations MOD

```
//cat solve_linear_mod.hpp | ./hash.sh
//0a302e
#pragma once
#include "row_reduce.hpp"
struct matrix_info {
    int rank;
    long long det;
    vector<long long> x;
};
//Solves mat * x = b under prime mod.
//mat is a n (rows) by m (cols) matrix, b is a length n column vector, x is a length m vector.
//assumes n,m >= 1, else RTE
//Returns rank of mat, determinant of mat, and x (solution vector to mat * x = b).
//x is empty if no solution. If rank < m, there are multiple solutions and an arbitrary one is
    ↪ returned.
//Leaves mat in reduced row echelon form (unlike kactl) with b appended.
//Trick: Number of unique solutions = (size of domain) ^ (# of free variables).
//# of free variables is generally equivalent to n - rank.
//O(n * m * min(n,m))
matrix_info solve_linear_mod(vector<vector<long long>>& mat, const vector<long long>& b, long
    ↪ long mod) {
    assert(ssize(mat) == ssize(b));
    int n = ssize(mat), m = ssize(mat[0]);
    for (int i = 0; i < n; i++)
        mat[i].push_back(b[i]);
    auto [rank, det] = row_reduce(mat, m, mod); //row reduce not including the last column
    //check if solution exists
    for (int i = rank; i < n; i++) {
        if (mat[i].back() != 0)
            return {rank, det, {}}; //no solution exists
    }
    //initialize solution vector (`x`) from row-reduced matrix
    vector<long long> x(m, 0);
    for (int i = 0, j = 0; i < rank; i++) {
```

```
        while (mat[i][j] == 0)
            j++; //find pivot column
        x[j] = mat[i].back();
    }
    return {rank, det, x};
}
```

Euler’s Totient Phi Function

```
//cat totient.hpp | ./hash.sh
//36bd41
#pragma once
//Euler's totient function counts the positive integers
//up to a given integer n that are relatively prime to n.
//
//To improve, pre-calc prime factors or use Pollard-rho to find prime factors.
int totient(int n) {
    int res = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            while (n % i == 0)
                n /= i;
            res -= res / i;
        }
    }
    if (n > 1)
        res -= res / n;
    return res;
}
```

Tetration MOD

```
//cat tetration_mod.hpp | ./hash.sh
//e2153e
#pragma once
#include "binary_exponentiation_mod.hpp"
#include "totient.hpp"
//to calculate (base^pw)%mod with huge pw and non-prime mod:
//let t = totient(mod)
//if log2(mod) <= pw then (base^pw)%mod == (base^(t+(pw/t)))%mod
//source: https://cp-algorithms.com/algebra/phi-function.html#generalization
//
//returns base ^ (base ^ (base ^ ... )) % mod, where the height of the tower is pw
long long tetration(long long base, long long pw, long long mod) {
    if (mod == 1)
        return 0;
    if (base == 0)
        return (pw + 1) % 2 % mod;
    if (base == 1 || pw == 0)
        return 1;
    if (pw == 1)
        return base % mod;
    if (base == 2 && pw == 2)
        return 4 % mod;
    if (base == 2 && pw == 3)
        return 16 % mod;
    if (base == 3 && pw == 2)
```

```
    return 27 % mod;
//need enough base cases such that the following is true
//log2(mod) <= tetration(base, pw - 1) (before modding)
int t = totient(int(mod));
long long exp = tetration(base, pw - 1, t);
return bin_exp(base, exp + t, mod);
}
```

MISC

Cartesian Tree

```
//cat cartesian_tree.hpp | ./hash.sh
//204c45
#pragma once
#include "monotonic_stack.hpp"
//min cartesian tree
vector<int> cartesian_tree(const vector<int>& arr) {
    int n = ssize(arr);
    auto rv /*reverse*/ = [&](int i) -> int {
        return n - 1 - i;
    };
    vector<int> left = monotonic_stack<int>(arr, greater());
    vector<int> right = monotonic_stack<int>(vector<int>(arr.rbegin(), arr.rend()), greater());
    vector<int> par(n);
    for (int i = 0; i < n; i++) {
        int le = left[i], ri = rv(right[rv(i)]);
        if (le >= 0 && ri < n)
            par[i] = arr[le] > arr[ri] ? le : ri;
        else if (le >= 0)
            par[i] = le;
        else if (ri < n)
            par[i] = ri;
        else
            par[i] = i;
    }
    return par;
}
```

Count Rectangles

```
//cat count_rectangles.hpp | ./hash.sh
//8990f7
#pragma once
#include "monotonic_stack.hpp"
//given a 2D boolean matrix, calculate cnt[i][j]
//cnt[i][j] = the number of times an i-by-j rectangle appears in the matrix such that all i*j
//    -> cells in the rectangle are 1
//Note cnt[0][j] and cnt[i][0] will contain garbage values
//O(n*m)
vector<vector<int>>> count_rectangles(const vector<vector<bool>>& grid) {
    int n = ssize(grid), m = ssize(grid[0]);
    vector<vector<int>>> cnt(n + 1, vector<int>(m + 1, 0));
    vector<int> arr(m, 0);
    auto rv /*reverse*/ = [&](int j) -> int {
        return m - 1 - j;
    };
    for (int i = 0; i < n; i++) {
        vector<int> left = monotonic_stack<int>(arr, greater());
        vector<int> right = monotonic_stack<int>(vector<int>(arr.rbegin(), arr.rend()), greater());
        for (int j = 0; j < m; j++) {
            int le = left[j], ri = rv(right[rv(j)]);
            if (le >= 0 && ri < m)
                cnt[i + 1][j] += cnt[i][j] + 1;
            else if (le >= 0)
                cnt[i + 1][le]++;
            else if (ri < m)
                cnt[i + 1][ri]++;
            else
                cnt[i + 1][j]++;
        }
    }
    return cnt;
}
```

```
};
for (int i = 0; i < n; i++) {
    for (int j = 0; j < m; j++)
        arr[j] = grid[i][j] * (arr[j] + 1);
    vector<int> left = monotonic_stack<int>(arr, greater());
    vector<int> right = monotonic_stack<int>(vector<int>(arr.rbegin(), arr.rend()),
        -> greater_equal());
    for (int j = 0; j < m; j++) {
        int le = j - left[j] - 1, ri = rv(right[rv(j)]) - j - 1;
        cnt[arr[j]][le + ri + 1]++;
        cnt[arr[j]][le]--;
        cnt[arr[j]][ri]--;
    }
}
for (int i = 1; i <= n; i++)
    for (int k = 0; k < 2; k++)
        for (int j = m - 1; j >= 1; j--)
            cnt[i][j] += cnt[i][j + 1];
for (int j = 1; j <= m; j++)
    for (int i = n - 1; i >= 1; i--)
        cnt[i][j] += cnt[i + 1][j];
return cnt;
}
```

Max Rectangle in Histogram

```
//cat max_rect_histogram.hpp | ./hash.sh
//95288f
#pragma once
#include "monotonic_stack.hpp"
long long max_rect_histogram(const vector<int>& arr) {
    auto rv /*reverse*/ = [&](int i) -> int {
        return ssize(arr) - 1 - i;
    };
    vector<int> left = monotonic_stack<int>(arr, greater_equal());
    vector<int> right = monotonic_stack<int>(vector<int>(arr.rbegin(), arr.rend()),
        -> greater_equal());
    long long max_area = 0;
    for (int i = 0; i < ssize(arr); i++) {
        int le = left[i], ri = rv(right[rv(i)]); //arr[i] is the max of range (le, ri)
        max_area = max(max_area, 1LL * arr[i] * (ri - le - 1));
    }
    return max_area;
}
```

Monotonic Stack

```
//cat monotonic_stack.hpp | ./hash.sh
//35c95c
#pragma once
//usages:
// vector<int> le = monotonic_stack<int>(arr, less()); //or replace `less` with: less_equal,
//    -> greater, greater_equal
// vector<int> le = monotonic_stack<int>(arr, [&](int x, int y) {return x < y;});
//
//returns array `le` where `le[i]` = max index such that:
// `le[i]` < i && !op(arr[le[i]], arr[i])
```

```
//or -1 if no index exists
//O(n)
template <typename T> vector<int> monotonic_stack(const vector<T>& arr, const
    ↪ function<bool(const T&, const T&)>& op) {
    vector<int> le(ssize(arr));
    for (int i = 0; i < ssize(arr); i++) {
        le[i] = i - 1;
        while (le[i] >= 0 && op(arr[le[i]], arr[i]))
            le[i] = le[le[i]];
    }
    return le;
}
```

GCD Convolution

```
//cat gcd_convolution.hpp | ./hash.sh
//d92c44
#pragma once
// c[k] = the sum for all pairs where gcd(i,j) == k of a[i] * b[j]
template<int MOD> vector<int> gcd_convolution(const vector<int>& a, const vector<int>& b) {
    assert(ssize(a) == ssize(b));
    int n = ssize(a);
    vector<int> c(n);
    for (int gcd = n - 1; gcd >= 1; gcd--) {
        int sum_a = 0, sum_b = 0;
        for (int i = gcd; i < n; i += gcd) {
            sum_a = (sum_a + a[i]) % MOD, sum_b = (sum_b + b[i]) % MOD;
            c[gcd] = (c[gcd] - c[i] + MOD) % MOD;
        }
        c[gcd] = int((c[gcd] + 1LL * sum_a * sum_b) % MOD);
    }
    return c;
}
```

Iterate Chooses

```
//cat iterate_chooses.hpp | ./hash.sh
//c79083
#pragma once

// source: https://github.com/kth-competitive-programming/
// kactl/blob/main/content/various/chapter.tex
// iterates all bitmasks of size n with k bits set
// Time Complexity: O(n choose k)
// Space Complexity: O(1)

int next_subset(int mask) {
    int c = mask & -mask, r = mask + c;
    return r | (((r ^ mask) >> 2) / c);
}

void iterate_chooses(int n, int k, const function<void(int)>& func) {
    for (int mask = (1 << k) - 1; mask < (1 << n); mask = next_subset(mask))
        func(mask);
}
```

Iterate Submasks

```
//cat iterate_submasks.hpp | ./hash.sh
//084c05
#pragma once

// iterates all submasks of mask
// Time Complexity: O(3^n) to iterate every submask of every mask of size n
// Space Complexity: O(1)

void iterate_submasks(int mask, const function<void(int)>& func) {
    for (int submask = mask; submask; submask = (submask - 1) & mask)
        func(submask);
}
```

Iterate Supermasks

```
//cat iterate_supermasks.hpp | ./hash.sh
//76b38f
#pragma once

// iterates all supermasks of mask
// Time Complexity: O(3^n) to iterate every supermask of every mask of size n
// Space Complexity: O(1)

void iterate_supermasks(int mask, int n, const function<void(int)>& func) {
    for (int supermask = mask; supermask < (1 << n); supermask = (supermask + 1) | mask)
        func(supermask);
}
```

Number of Distinct Subsequences DP

```
//cat num_distinct_subsequences.hpp | ./hash.sh
//d94bdc
#pragma once
//returns number of distinct subsequences
//the empty subsequence is counted
int num_subsequences(const vector<int>& arr, int mod) {
    vector<int> dp(ssize(arr) + 1, 1);
    map<int, int> last;
    for (int i = 0; i < ssize(arr); i++) {
        int& curr = dp[i + 1] = 2 * dp[i];
        if (curr >= mod)
            curr -= mod;
        auto it = last.find(arr[i]);
        if (it != last.end()) {
            curr -= dp[it->second];
            if (curr < 0)
                curr += mod;
            it->second = i;
        } else
            last[arr[i]] = i;
    }
    return dp.back();
}
```

PBDS

```
//cat policy_based_data_structures.hpp | ./hash.sh
//a777d7
#pragma once
//place these includes *before* the `#define int long long` else compile error
//not using <bits/extc++.h> as it compile errors on codeforces c++20 compiler
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
//BST with extra functions https://codeforces.com/blog/entry/11080
//order_of_key - # of elements *strictly* less than given element
//find_by_order - find kth largest element, k is 0 based so find_by_order(0) returns min
    ↪ element
template <typename T> using indexed_set = tree<T, null_type, less<T>, rb_tree_tag,
    ↪ tree_order_statistics_node_update>;
//example initialization:
indexed_set<pair<long long, int>> is;
//hash table (apparently faster than unordered_map): https://codeforces.com/blog/entry/60737
//example initialization:
gp_hash_table<string, long long> ht;
```

Random

```
//cat random.hpp | ./hash.sh
//ab9111
#pragma once

//source: https://codeforces.com/blog/entry/61675

mt19937 rng(chrono::steady_clock::now().time_since_epoch().count());

//intended types: int, unsigned, long long
//returns a random number in range [le, ri)
template <typename T> inline T get_rand(T le, T ri) {
    assert(le < ri);
    return uniform_int_distribution<T>(le, ri - 1)(rng);
}

//vector<int> a;
//shuffle(a.begin(), a.end(), rng);
```

Safe Hash

```
//cat safe_hash.hpp | ./hash.sh
//d9ea53
#pragma once
//source: https://codeforces.com/blog/entry/62393
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM =
            ↪ chrono::steady_clock::now().time_since_epoch().count();
```

```
        return splitmix64(x + FIXED_RANDOM);
    }
};
//usage:
unordered_map<long long, int, custom_hash> safe_map;
#include "policy_based_data_structures.hpp"
gp_hash_table<long long, int, custom_hash> safe_hash_table;
```

RANGE DATA STRUCTURES

Number Distinct Elements

```
//cat distinct_query.hpp | ./hash.sh
//79534f
#pragma once
//source: https://cp-algorithms.com/data_structures/segment_tree.html
// #preserving-the-history-of-its-values-persistent-segment-tree
//works with negatives
//O(n log n) time and space
struct distinct_query {
    struct node {
        int sum;
        int lch, rch; //children, indexes into `tree`
        node(int a_sum, int a_lch, int a_rch) : sum(a_sum), lch(a_lch), rch(a_rch) {}
    };
    const int N;
    vector<int> roots;
    deque<node> tree;
    distinct_query(const vector<int>& arr) : N(ssize(arr)), roots(N + 1, 0) {
        tree.emplace_back(0, 0, 0); //acts as null
        map<int, int> last_idx;
        for (int i = 0; i < N; i++) {
            roots[i + 1] = update(roots[i], 0, N, last_idx[arr[i]]);
            last_idx[arr[i]] = i + 1;
        }
    }
    int update(int v, int tl, int tr, int idx) {
        if (tr - tl == 1) {
            tree.emplace_back(tree[v].sum + 1, 0, 0);
            return ssize(tree) - 1;
        }
        int tm = tl + (tr - tl) / 2;
        int lch = tree[v].lch;
        int rch = tree[v].rch;
        if (idx < tm)
            lch = update(lch, tl, tm, idx);
        else
            rch = update(rch, tm, tr, idx);
        tree.emplace_back(tree[lch].sum + tree[rch].sum, lch, rch);
        return ssize(tree) - 1;
    }
    //returns number of distinct elements in range [le,ri)
    int query(int le, int ri) const {
        assert(0 <= le && le <= ri && ri <= N);
        return query(roots[le], roots[ri], 0, N, le + 1);
    }
    int query(int vl, int vr, int tl, int tr, int idx) const {
```

```

    if (tree[vr].sum == 0 || idx <= tl)
        return 0;
    if (tr <= idx)
        return tree[vr].sum - tree[vl].sum;
    int tm = tl + (tr - tl) / 2;
    return query(tree[vl].lch, tree[vr].lch, tl, tm, idx) +
           query(tree[vl].rch, tree[vr].rch, tm, tr, idx);
}
};
```

Implicit Lazy Segment Tree

```

//cat implicit_seg_tree.hpp | ./hash.sh
//ab5eb9
#pragma once
//example initialization:
// implicit_seg_tree<10'000'000> ist(le, ri);
template <int N> struct implicit_seg_tree {
    using dt = array<long long, 2>; //min, number of mins
    using ch = long long;
    static dt combine(const dt& le, const dt& ri) {
        if (le[0] == ri[0])
            return {le[0], le[1] + ri[1]};
        return min(le, ri);
    }
    static constexpr dt UNIT{(long long)1e18, 0LL};
    struct node {
        dt val;
        ch lazy = 0;
        int lch = -1, rch = -1; // children, indexes into `tree`, -1 for null
    } tree[N];
    int ptr = 0, root_l, root_r; // [root_l, root_r) defines range of root node; handles
    ⇨ negatives
    implicit_seg_tree(int le, int ri) : root_l(le), root_r(ri) {
        tree[ptr++].val = {0, ri - le};
    }
    void apply(int v, ch add) {
        tree[v].val[0] += add;
        tree[v].lazy += add;
    }
    void push(int v, int tl, int tr) {
        if (tr - tl > 1 && tree[v].lch == -1) {
            int tm = tl + (tr - tl) / 2;
            assert(ptr + 1 < N);
            tree[v].lch = ptr;
            tree[ptr++].val = {0, tm - tl};
            tree[v].rch = ptr;
            tree[ptr++].val = {0, tr - tm};
        }
        if (tree[v].lazy) {
            apply(tree[v].lch, tree[v].lazy);
            apply(tree[v].rch, tree[v].lazy);
            tree[v].lazy = 0;
        }
    }
    //update range [le,ri)
    void update(int le, int ri, ch add) {
        update(0, root_l, root_r, le, ri, add);
    }
};
```

```

}
void update(int v, int tl, int tr, int le, int ri, ch add) {
    if (ri <= tl || tr <= le)
        return;
    if (le <= tl && tr <= ri)
        return apply(v, add);
    push(v, tl, tr);
    int tm = tl + (tr - tl) / 2;
    update(tree[v].lch, tl, tm, le, ri, add);
    update(tree[v].rch, tm, tr, le, ri, add);
    tree[v].val = combine(tree[tree[v].lch].val,
                          tree[tree[v].rch].val);
}
//query range [le,ri)
dt query(int le, int ri) {
    return query(0, root_l, root_r, le, ri);
}
dt query(int v, int tl, int tr, int le, int ri) {
    if (ri <= tl || tr <= le)
        return UNIT;
    if (le <= tl && tr <= ri)
        return tree[v].val;
    push(v, tl, tr);
    int tm = tl + (tr - tl) / 2;
    return combine(query(tree[v].lch, tl, tm, le, ri),
                  query(tree[v].rch, tm, tr, le, ri));
}
};
```

Kth Smallest

```

//cat kth_smallest.hpp | ./hash.sh
//b86dd0
#pragma once
//source: https://cp-algorithms.com/data_structures/segment_tree.html
// #preserving-the-history-of-its-values-persistent-segment-tree
struct kth_smallest {
    struct node {
        int sum;
        int lch, rch; //children, indexes into `tree`
        node(int a_sum, int a_lch, int a_rch) : sum(a_sum), lch(a_lch), rch(a_rch) {}
    };
    int mn = INT_MAX, mx = INT_MIN;
    vector<int> roots;
    deque<node> tree;
    kth_smallest(const vector<int>& arr) : roots(ssize(arr) + 1, 0) {
        tree.emplace_back(0, 0, 0); //acts as null
        for (int val : arr)
            mn = min(mn, val), mx = max(mx, val + 1);
        for (int i = 0; i < ssize(arr); i++)
            roots[i + 1] = update(roots[i], mn, mx, arr[i]);
    }
    int update(int v, int tl, int tr, int idx) {
        if (tr - tl == 1) {
            tree.emplace_back(tree[v].sum + 1, 0, 0);
            return ssize(tree) - 1;
        }
        int tm = tl + (tr - tl) / 2;
```



```
int lch = tree[v].lch;
int rch = tree[v].rch;
if (idx < tm)
    lch = update(lch, tl, tm, idx);
else
    rch = update(rch, tm, tr, idx);
tree.emplace_back(tree[lch].sum + tree[rch].sum, lch, rch);
return ssize(tree) - 1;
}
/* find (k+1)th smallest number in range [le, ri)
 * k is 0-based, so query(le,ri,0) returns the min
 */
int query(int le, int ri, int k) const {
    assert(0 <= k && k < ri - le); //note this condition implies le < ri
    assert(0 <= le && ri < ssize(root));
    return query(root[l], root[r], mn, mx, k);
}
int query(int vl, int vr, int tl, int tr, int k) const {
    assert(tree[vr].sum > tree[vl].sum);
    if (tr - tl == 1)
        return tl;
    int tm = tl + (tr - tl) / 2;
    int left_count = tree[tree[vr].lch].sum - tree[tree[vl].lch].sum;
    if (left_count > k)
        return query(tree[vl].lch, tree[vr].lch, tl, tm, k);
    return query(tree[vl].rch, tree[vr].rch, tm, tr, k - left_count);
}
};
```

Merge Sort Tree

```
//cat merge_sort_tree.hpp | ./hash.sh
//e110ed
#pragma once
//For point updates: either switch to policy based BST, or use sqrt decomposition
struct merge_sort_tree {
    const int N, S/*smallest power of 2 >= N*/;
    vector<vector<int>> tree;
    merge_sort_tree(const vector<int>& arr) : N(ssize(arr)), S(N ? 1 << __lg(2 * N - 1) : 0),
        tree(2 * N) {
        for (int i = 0; i < N; i++)
            tree[i + N] = {arr[i]};
        rotate(tree.rbegin(), tree.rbegin() + S - N, tree.rbegin() + N);
        for (int i = N - 1; i >= 1; i--) {
            const auto& le = tree[2 * i];
            const auto& ri = tree[2 * i + 1];
            tree[i].reserve(ssize(le) + ssize(ri));
            merge(le.begin(), le.end(), ri.begin(), ri.end(), back_inserter(tree[i]));
        }
    }
    int value(int v, int x) const {
        return int(lower_bound(tree[v].begin(), tree[v].end(), x) - tree[v].begin());
    }
    int to_leaf(int i) const {
        i += S;
        return i < 2 * N ? i : 2 * (i - N);
    }
    //How many values in range [le, ri) are < x?
```

```
//O(log^2(n))
int query(int le, int ri, int x) const {
    int res = 0;
    for (le = to_leaf(le), ri = to_leaf(ri); le < ri; le >>= 1, ri >>= 1) {
        if (le & 1)
            res += value(le++, x);
        if (ri & 1)
            res += value(--ri, x);
    }
    return res;
}
};
```

BIT

```
//cat bit.hpp | ./hash.sh
//ab7995
#pragma once
//mnemonic: Binary Indexed Tree
//NOLINTNEXTLINE(readability-identifier-naming)
template <typename T> struct BIT {
    vector<T> bit;
    BIT(int n) : bit(n, 0) {}
    BIT(const vector<T>& a) : bit(a) {
        for (int i = 0; i < ssize(a); i++) {
            int j = i | (i + 1);
            if (j < ssize(a))
                bit[j] += bit[i];
        }
    }
    void update(int i, const T& d) {
        assert(0 <= i && i < ssize(bit));
        for (; i < ssize(bit); i |= i + 1)
            bit[i] += d;
    }
    T sum(int ri) const { //sum of range [0, ri)
        assert(0 <= ri && ri <= ssize(bit));
        T ret = 0;
        for (; ri > 0; ri &= ri - 1)
            ret += bit[ri - 1];
        return ret;
    }
    T sum(int le, int ri) const { //sum of range [le, ri)
        assert(0 <= le && le <= ri && ri <= ssize(bit));
        return sum(ri) - sum(le);
    }
    //Returns min pos (0<=pos<=ssize(bit)+1) such that sum of [0, pos) >= sum
    //Returns ssize(bit) + 1 if no sum is >= sum, or 0 if empty sum is.
    //Doesn't work with negatives
    int lower_bound(T sum) const {
        if (sum <= 0)
            return 0;
        int pos = 0;
        for (int pw = 1 << __lg(ssize(bit) | 1); pw; pw >>= 1)
            if (pos + pw <= ssize(bit) && bit[pos + pw - 1] < sum)
                pos += pw, sum -= bit[pos - 1];
        return pos + 1;
    }
};
```

```
};
```

RMQ

```
//cat rmq.hpp | ./hash.sh
//a7bca5
#pragma once
//source: https://github.com/kth-competitive-programming/
// kactl/blob/main/content/data-structures/RMQ.h
//usage:
// vector<long long> arr;
// ...
// RMQ<long long> rmq(arr, [&](auto x, auto y) { return min(x,y); });
//
//to also get index of min element, do:
// RMQ<pair<T, int>> rmq(arr, [&](auto x, auto y) { return min(x,y); });
//and initialize arr[i].second = i (0<=i<n)
//If there are multiple indexes of min element, it'll return the smallest
//(left-most) one
//mnemonic: Range Min/Max Query
//NOLINTNEXTLINE(readability-identifier-naming)
template <typename T> struct RMQ {
    vector<vector<T>> dp;
    function<T(const T&, const T&>> op;
    RMQ(const vector<T>& arr, const function<T(const T&, const T&>& a_op) : dp(1, arr),
        op(a_op) {
        for (int pw = 1, k = 1; 2 * pw <= ssize(arr); pw *= 2, k++) {
            dp.emplace_back(ssize(arr) - 2 * pw + 1);
            for (int j = 0; j < ssize(dp.back()); j++)
                dp[k][j] = op(dp[k - 1][j], dp[k - 1][j + pw]);
        }
    }
    //inclusive-exclusive range [le, ri)
    T query(int le, int ri) const {
        assert(0 <= le && le < ri && ri <= ssize(dp[0]));
        int lg = __lg(ri - le);
        return op(dp[lg][le], dp[lg][ri - (1 << lg)]);
    }
};
```

Lazy Segment Tree

```
//cat lazy_segment_tree.hpp | ./hash.sh
//96535f
#pragma once
//source: https://codeforces.com/blog/entry/18051,
// https://github.com/ecnerwala/cp-book/blob/master/src/seg_tree.hpp,
// https://github.com/yosupo06/Algorithm/blob/master/src/datastructure/segtree.hpp
//rotating leaves makes it a single complete binary tree (instead of a set of perfect binary
// trees)
//so standard implementations of
// - recursive seg tree
// - tree walks AKA binary search
//still work
struct seg_tree {
    using dt = long long;
    using ch = long long;
```

```
static dt combine(const dt& le, const dt& ri) {
    return min(le, ri);
}
static const dt UNIT = 1e18;
struct node {
    dt val;
    ch lazy;
    int le, ri; //[le, ri)
};
const int N, S/*smallest power of 2 >= N*/;
vector<node> tree;
seg_tree(const vector<dt>& arr) : N(ssize(arr)), S(N ? 1 << __lg(2 * N - 1) : 0), tree(2 *
    S) {
    for (int i = 0; i < N; i++)
        tree[i + N] = {arr[i], 0, i, i + 1};
    rotate(tree.rbegin(), tree.rbegin() + S - N, tree.rbegin() + N);
    for (int i = N - 1; i >= 1; i--) {
        tree[i] = {
            combine(tree[2 * i].val, tree[2 * i + 1].val),
            0,
            tree[2 * i].le,
            tree[2 * i + 1].ri
        };
    }
}
void apply(int v, ch change) {
    tree[v].val += change;
    tree[v].lazy += change;
}
void push(int v) {
    if (tree[v].lazy) {
        apply(2 * v, tree[v].lazy);
        apply(2 * v + 1, tree[v].lazy);
        tree[v].lazy = 0;
    }
}
void build(int v) {
    tree[v].val = combine(tree[2 * v].val, tree[2 * v + 1].val);
}
int to_leaf(int i) const {
    i += S;
    return i < 2 * N ? i : 2 * (i - N);
}
//update range [le, ri)
void update(int le, int ri, ch change) {
    assert(0 <= le && le <= ri && ri <= N);
    le = to_leaf(le), ri = to_leaf(ri);
    int lca_l_r = __lg((le - 1) ^ ri);
    for (int lg = __lg(le); lg > __builtin_ctz(le); lg--)
        push(le >> lg);
    for (int lg = lca_l_r; lg > __builtin_ctz(ri); lg--)
        push(ri >> lg);
    for (int x = le, y = ri; x < y; x >>= 1, y >>= 1) {
        if (x & 1)
            apply(x++, change);
        if (y & 1)
            apply(--y, change);
    }
    for (int lg = __builtin_ctz(ri) + 1; lg <= lca_l_r; lg++)
```

```
        build(ri >> lg);
    for (int lg = __builtin_ctz(le) + 1; lg <= __lg(le); lg++)
        build(le >> lg);
}

void update(int v/* = 1*/, int le, int ri, ch change) {
    if (ri <= tree[v].le || tree[v].ri <= le)
        return;
    if (le <= tree[v].le && tree[v].ri <= ri)
        return apply(v, change);
    push(v);
    update(2 * v, le, ri, change);
    update(2 * v + 1, le, ri, change);
    build(v);
}

//query range [le, ri)
dt query(int le, int ri) {
    assert(0 <= le && le <= ri && ri <= N);
    le = to_leaf(le), ri = to_leaf(ri);
    int lca_l_r = __lg((le - 1) ^ ri);
    for (int lg = __lg(le); lg > __builtin_ctz(le); lg--)
        push(le >> lg);
    for (int lg = lca_l_r; lg > __builtin_ctz(ri); lg--)
        push(ri >> lg);
    dt resl = UNIT, resr = UNIT;
    for (; le < ri; le >>= 1, ri >>= 1) {
        if (le & 1)
            resl = combine(resl, tree[le++].val);
        if (ri & 1)
            resr = combine(tree[--ri].val, resr);
    }
    return combine(resl, resr);
}

dt query(int v/* = 1*/, int le, int ri) {
    if (ri <= tree[v].le || tree[v].ri <= le)
        return UNIT;
    if (le <= tree[v].le && tree[v].ri <= ri)
        return tree[v].val;
    push(v);
    return combine(query(2 * v, le, ri), query(2 * v + 1, le, ri));
}

};
```

STRINGS

Binary Trie

```
//cat binary_trie.hpp | ./hash.sh
//88fa9c
#pragma once
struct binary_trie {
    const int MX_BIT = 62;
    struct node {
        long long val = -1;
        int sub_sz = 0; //number of inserted values in subtree
        array<int, 2> next = {-1, -1};
    };
    vector<node> t;
```

```
    binary_trie() : t(1) {}
    //delta = 1 to insert val, -1 to remove val, 0 to get the # of val's in this data structure
    int update(long long val, int delta) {
        int c = 0;
        t[0].sub_sz += delta;
        for (int bit = MX_BIT; bit >= 0; bit--) {
            bool v = (val >> bit) & 1;
            if (t[c].next[v] == -1) {
                t[c].next[v] = ssize(t);
                t.emplace_back();
            }
            c = t[c].next[v];
            t[c].sub_sz += delta;
        }
        t[c].val = val;
        return t[c].sub_sz;
    }
    int size() const {
        return t[0].sub_sz;
    }
    //returns x such that:
    // x is in this data structure
    // value of (x ^ val) is minimum
    long long min_xor(long long val) const {
        assert(size() > 0);
        int c = 0;
        for (int bit = MX_BIT; bit >= 0; bit--) {
            bool v = (val >> bit) & 1;
            int ch = t[c].next[v];
            if (ch != -1 && t[ch].sub_sz > 0)
                c = ch;
            else
                c = t[c].next[!v];
        }
        return t[c].val;
    }
};
```

Prefix Function

```
//cat prefix_function.hpp | ./hash.sh
//65fea7
#pragma once
//source: https://cp-algorithms.com/string/prefix-function.html#implementation
template <typename T> vector<int> prefix_function(const T& s) {
    vector<int> pi(ssize(s), 0);
    for (int i = 1; i < ssize(s); i++) {
        int j = pi[i - 1];
        while (j > 0 && s[i] != s[j])
            j = pi[j - 1];
        pi[i] = j + (s[i] == s[j]);
    }
    return pi;
}
```

KMP String Matching

```
//cat kmp.hpp | ./hash.sh
//ab4dba
#pragma once
//mnemonic: Knuth Morris Pratt
#include "prefix_function.hpp"
//usage:
// string needle;
// ...
// KMP kmp(needle);
//or
// vector<int> needle;
// ...
// KMP kmp(needle);
//kmp doubling trick: to check if 2 arrays are rotationally equivalent: run kmp
//with one array as the needle and the other array doubled (excluding the first
//& last characters) as the haystack or just use kactl's min rotation code
//
// if haystack = "bananas"
// needle = "ana"
//
// then we find 2 matches:
// bananas
// _ana___
// __ana_
// 0123456 (indexes)
// and KMP::find returns {1,3} - the indexes in haystack where
// each match starts.
//
// You can also pass in 0 for "all" and KMP::find will only
// return the first match: {1}. Useful for checking if there exists
// some match:
//
// ssize(KMP::find(<haystack>,0)) > 0
//NOLINTNEXTLINE(readability-identifier-naming)
template <typename T> struct KMP {
    T needle;
    vector<int> pi;
    KMP(const T& a_needle) : needle(a_needle), pi(prefix_function(needle)) {}
    vector<int> find(const T& haystack, bool all = 1) const {
        vector<int> matches;
        for (int i = 0, j = 0; i < ssize(haystack); i++) {
            while (j > 0 && needle[j] != haystack[i])
                j = pi[j - 1];
            if (needle[j] == haystack[i])
                j++;
            if (j == ssize(needle)) {
                matches.push_back(i - ssize(needle) + 1);
                if (!all)
                    return matches;
                j = pi[j - 1];
            }
        }
        return matches;
    }
};
```

Suffix Array

```
//cat suffix_array.hpp | ./hash.sh
//da54ac
#pragma once
//source: https://judge.yosupo.jp/submission/63467
//time: O(n + max_val)
template <typename T> vector<int> suffix_array(const T& s, int max_val) {
    int n = ssize(s);
    if (n == 0)
        return {};
    if (n == 1)
        return {0};
    if (n == 2)
        return {(s[0] >= s[1]), (s[0] < s[1])};
    vector<int> sa(n, 0), is_s(n, 0);
    for (int i = n - 2; i >= 0; i--)
        is_s[i] = (s[i] < s[i + 1] || (s[i] == s[i + 1] && is_s[i + 1]));
    vector<int> head(max_val + 1, 0), tail(max_val + 1, 0);
    for (int i = 0; i < n; i++)
        head[s[i] + 1]++, tail[s[i]] += !is_s[i];
    partial_sum(head.begin(), head.end(), head.begin());
    for (int i = 0; i <= max_val; i++)
        tail[i] += head[i];
    vector<int> tmp(max_val + 1, 0);
    auto induce = [&](const vector<int>& lms) {
        fill(sa.begin(), sa.end(), -1);
        copy(tail.begin(), tail.end(), tmp.begin());
        for (int i : lms)
            sa[tmp[s[i]]++] = i;
        copy(head.begin(), head.end(), tmp.begin());
        sa[tmp[s[n - 1]]++] = n - 1;
        for (int i = 0; i < n; i++)
            if (int j = sa[i]; j > 0 && !is_s[j - 1])
                sa[tmp[s[j - 1]]++] = j - 1;
        copy(head.begin(), head.end(), tmp.begin());
        for (int i = n - 1; i >= 0; i--)
            if (int j = sa[i]; j > 0 && is_s[j - 1])
                sa[--tmp[s[j - 1] + 1]] = j - 1;
    };
    vector<int> lms_idx(n, -1), lms(0, 0);
    for (int i = 1; i < n; i++)
        if (is_s[i] && !is_s[i - 1])
            lms_idx[i] = ssize(lms), lms.push_back(i);
    induce(lms);
    if (ssize(lms)) {
        vector<int> s2(ssize(lms), 0), sorted_lms;
        copy_if(sa.begin(), sa.end(), back_inserter(sorted_lms), [&](int i) -> bool {
            return lms_idx[i] != -1;
        });
        int max_val2 = 0;
        for (int i = 1; i < ssize(lms); i++) {
            int a = sorted_lms[i - 1], b = sorted_lms[i];
            max_val2 += !equal(s.begin() + a, s.begin() + (lms_idx[a] + 1 == ssize(lms) ? n :
                ⇨ lms[lms_idx[a] + 1]),
                ⇨ s.begin() + b, s.begin() + (lms_idx[b] + 1 == ssize(lms) ? n :
                ⇨ lms[lms_idx[b] + 1]));
            s2[lms_idx[b]] = max_val2;
        }
        auto sa2 = suffix_array(s2, max_val2 + 1);
        for (int i = 0; i < ssize(lms); i++)
```

```
        sorted_lms[i] = lms[sa2[i]];
        induce(sorted_lms);
    }
    return sa;
}
```

LCP Array

```
//cat longest_common_prefix.hpp | ./hash.sh
//0c613c
#pragma once
template <typename T> vector<int> calc_lcp(const T& s, const vector<int>& sa) {
    int n = ssize(s);
    vector<int> inv_sa(n), lcp(n - 1, 0);
    for (int i = 0; i < n; i++)
        inv_sa[sa[i]] = i;
    for (int i = 0, k = 0; i < n; i++) {
        if (inv_sa[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = sa[inv_sa[i] + 1];
        while (i + k < n && j + k < n && s[i + k] == s[j + k])
            k++;
        lcp[inv_sa[i]] = k;
        if (k)
            k--;
    }
    return lcp;
}
```

Longest Common Prefix Query

```
//cat longest_common_prefix_query.hpp | ./hash.sh
//f53119
#pragma once
#include "suffix_array.hpp"
#include "longest_common_prefix.hpp"
#include "../range_data_structures/rmq.hpp"
//computes suffix array, lcp array, and then sparse table over lcp array
//O(n log n)
template <typename T> struct lcp_query {
    const int N;
    vector<int> sa, inv_sa, lcp;
    RMQ<int> rmq;
    lcp_query(const T& s, int max_val) : N(ssize(s)), sa(suffix_array(s, max_val)), inv_sa(N),
        ↳ lcp(calc_lcp(s, sa)), rmq(lcp, [](int i, int j) -> int {return min(i, j);}) {
        for (int i = 0; i < N; i++)
            inv_sa[sa[i]] = i;
    }
    //length of longest common prefix of suffixes s[idx1 ... N), s[idx2 ... N), 0-based
    ↳ indexing
    //
    //You can check if two substrings s[l1..r1), s[l2..r2) are equal in O(1) by:
    //r1-l1 == r2-l2 && longest_common_prefix(l1, l2) >= r1-l1
    int get_lcp(int idx1, int idx2) const {
        if (idx1 == idx2)
```

```
        return N - idx1;
        auto [le, ri] = minmax(inv_sa[idx1], inv_sa[idx2]);
        return rmq.query(le, ri);
    }
    //returns 1 if suffix s[idx1 ... N) < s[idx2 ... N)
    //(so 0 if idx1 == idx2)
    bool less(int idx1, int idx2) const {
        return inv_sa[idx1] < inv_sa[idx2];
    }
};
```

Palindrome Query

```
//cat palindrome_query.hpp | ./hash.sh
//68c8e1
#pragma once
#include "../kactl/content/strings/Manacher.h"
struct pal_query {
    const int N;
    array<vi, 2> pal_len;
    pal_query(const string& s) : N(ssize(s)), pal_len(manacher(s)) {}
    //returns 1 if substring s[le...ri) is a palindrome
    //(returns 1 when le == ri)
    bool is_pal(int le, int ri) const {
        assert(0 <= le && le <= ri && ri <= N);
        int len = ri - le;
        return pal_len[len & 1][le + len / 2] >= len / 2;
    }
};
```

Trie

```
//cat trie.hpp | ./hash.sh
//2aa8c6
#pragma once
//source: https://cp-algorithms.com/string/aho_corasick.html#construction-of-the-trie
const int K = 26; //alphabet size
struct trie {
    const char MIN_CH = 'A'; // 'a' for lowercase, '0' for digits
    struct node {
        int next[K], cnt_words = 0, par = -1;
        char ch;
        node(int a_par = -1, char a_ch = '#') : par(a_par), ch(a_ch) {
            fill(next, next + K, -1);
        }
    };
    vector<node> t;
    trie() : t(1) {}
    void insert(const string& s) {
        int v = 0;
        for (char ch : s) {
            int let = ch - MIN_CH;
            if (t[v].next[let] == -1) {
                t[v].next[let] = ssize(t);
                t.emplace_back(v, ch);
            }
            v = t[v].next[let];
        }
```

```
    }
    t[v].cnt_words++;
}
int find(const string& s) const {
    int v = 0;
    for (char ch : s) {
        int let = ch - MIN_CH;
        if (t[v].next[let] == -1)
            return 0;
        v = t[v].next[let];
    }
    return t[v].cnt_words;
}
};
```