

Listings

1	Contest	2	39	Mobius Inversion	14
2	Hash codes	2	40	Row Reduce	15
3	Test on random inputs	2	41	Solve Linear Equations MOD	15
4	GRAPHS	2	42	Matrix Inverse	15
5	Bridges and Cuts	2	43	Euler’s Totient Phi Function	16
6	Block Vertex Tree	3	44	MAX FLOW	16
7	Bridge Tree	3	45	Dinic	16
8	Frequency Table of Tree Distance	3	46	Hungarian	16
9	Dijkstra	4	47	Min Cost Max Flow	17
10	HLD	4	48	MISC	17
11	Hopcroft Karp	5	49	PBDS	17
12	LCA	5	50	Monotonic Stack	18
13	Kth Node on Path	6	51	Count Rectangles	18
14	SCC	6	52	LIS	18
15	RANGE DATA STRUCTURES	6	53	Number of Distinct Subsequences DP	19
16	Lazy Segment Tree	6	54	Safe Hash	19
17	BIT	7			
18	RMQ	7			
19	Implicit Lazy Segment Tree	8			
20	Kth Smallest	8			
21	Number Distinct Elements	9			
22	Merge Sort Tree	9			
23	STRINGS	10			
24	Suffix Array	10			
25	LCP	11			
26	KMP	11			
27	Trie	11			
28	Binary Trie	12			
29	Longest Common Prefix Query	12			
30	Palindrome Query	13			
31	MATH	13			
32	BIN EXP MOD	13			
33	Fibonacci	13			
34	Matrix Mult and Pow	13			
35	N Choose K MOD	13			
36	Partitions	14			
37	Derangements	14			
38	Prime Sieve	14			

Listing 1: Contest

```
#!/usr/bin/env bash
#Hashes a file, ignoring all:
# - whitespace
# - comments
# - asserts
# - includes
# - pragmas
#Use to verify that code was correctly typed.

#usage:
#  chmod +x hash.sh
#  cat <file> | ./hash.sh
#or just copy this command:
#  cat <file> | sed -r '/(assert|include|pragma)/d' | cpp -fpreprocessed -P | tr -d
#    ↪ '[:space:]' | md5sum | cut -c-6
sed -r '/(assert|include|pragma)/d' | cpp -fpreprocessed -P | tr -d '[:space:]' | md5sum
  ↪ | cut -c-6
```

Listing 2: Hash codes

Listing 3: Test on random inputs

```
#!/usr/bin/env bash
#runs 2 programs against each other on random inputs until they output different results
#source: https://github.com/Errichto/youtube/blob/master/testing/s.sh
#usage:
#  chmod +x test.sh
#  ./test.sh
for((i = 1; ; ++i)); do
  echo $i
  ./test.out > in
  diff --ignore-all-space <(. /a.out < in) <(. /brute.out < in) || break
done
```

Listing 4: GRAPHS

Listing 5: Bridges and Cuts

```
//cat bridges_and_cuts.h | ./hash.sh
//1310ef
#pragma once
//O(n+m) time & space
//2 edge cc and bcc stuff doesn't depend on each other, so delete whatever is not needed
//handles multiple edges
//
//example initialization of 'adj':
//for (int i = 0; i < m; i++) {
//  int u, v;
//  cin >> u >> v;
//  u--, v--;
//  adj[u].emplace_back(v, i);
//  adj[v].emplace_back(u, i);
//}
struct info {
```

```
//2 edge connected component stuff (e.g. components split by bridge edges)
  ↪ https://cp-algorithms.com/graph/bridge-searching.html
int num_2_edge_ccs;
vector<bool> is_bridge;//edge id -> 1 iff bridge edge
vector<int> two_edge_ccid;//node -> id of 2 edge component (which are labeled 0, 1,
  ↪ ..., 'num_2_edge_ccs'-1)
//bi connected component stuff (e.g. components split by cut/articulation nodes)
  ↪ https://cp-algorithms.com/graph/cutpoints.html
int num_bccs;
vector<bool> is_cut;//node -> 1 iff cut node
vector<int> bcc_id;//edge id -> id of bcc (which are labeled 0, 1, ..., 'num_bccs'-1)
};
info bridge_and_cut(const vector<vector<pair<int/*neighbor*/, int/*edge id*/>>>&
  ↪ adj/*undirected graph*/, int m/*number of edges*/) {
//stuff for both (always keep)
int n = adj.size(), timer = 1;
vector<int> tin(n, 0);
//2 edge cc stuff (delete if not needed)
int num_2_edge_ccs = 0;
vector<bool> is_bridge(m, 0);
vector<int> two_edge_ccid(n), node_stack;
//bcc stuff (delete if not needed)
int num_bccs = 0;
vector<bool> is_cut(n, 0);
vector<int> bcc_id(m), edge_stack;
auto dfs = [&](auto self, int v, int p_id) -> int {
    int low = tin[v] = timer++, deg = 0;
    node_stack.push_back(v);
    for (auto [to, e_id] : adj[v]) {
        if (e_id == p_id) continue;
        if (!tin[to]) {
            edge_stack.push_back(e_id);
            int low_ch = self(self, to, e_id);
            if (low_ch >= tin[v]) {
                is_cut[v] = 1;
                while (1) {
                    int edge = edge_stack.back();
                    edge_stack.pop_back();
                    bcc_id[edge] = num_bccs;
                    if (edge == e_id) break;
                }
                num_bccs++;
            }
            low = min(low, low_ch);
            deg++;
        } else if (tin[to] < tin[v]) {
            edge_stack.push_back(e_id);
            low = min(low, tin[to]);
        }
    }
}
if (p_id == -1) is_cut[v] = (deg > 1);
if (tin[v] == low) {
    if (p_id != -1) is_bridge[p_id] = 1;
    while (1) {
        int node = node_stack.back();
        node_stack.pop_back();
        two_edge_ccid[node] = num_2_edge_ccs;
        if (node == v) break;
    }
    num_2_edge_ccs++;
}
```



```
        q.pop();
        for (int ch : adj[curr]) {
            if (ch == par || vis[ch]) continue;
            new_q.emplace(ch, curr);
        }
        swap(q, new_q);
    }
}
{
    vector<double> prod = conv(total_depth, cnt_depth);
    for (int i = 1; i < (int)prod.size(); i++) cnt_paths[i] += (long
        ⇨ long)(prod[i] + 0.5);
    }
    if (total_depth.size() < cnt_depth.size())
        ⇨ total_depth.resize(cnt_depth.size(), 0.0);
    for (int i = 1; i < (int)cnt_depth.size(); i++) total_depth[i] +=
        ⇨ cnt_depth[i];
    self(self, to);
}
};
dfs(dfs, 0);
return cnt_paths;
}
```

Listing 9: Dijkstra

```
//cat dijkstra.h | ./hash.sh
//56a477
#pragma once
//returns array 'len' where 'len[i]' = shortest path from node v to node i
//For example len[v] will always = 0
const long long INF = 1e18;
vector<long long> dijkstra(const vector<vector<pair<int, long long>>>& adj /*directed or
    ⇨ undirected, weighted graph*/, int v) {
    vector<long long> len(adj.size(), INF);
    len[v] = 0;
    set<pair<long long /*weight*/, int /*node*/>> q;
    q.insert({0LL, v});
    while (!q.empty()) {
        auto it = q.begin();
        int node = it->second;
        q.erase(it);
        for (auto [to, weight] : adj[node])
            if (len[to] > weight + len[node]) {
                q.erase({len[to], to});
                len[to] = weight + len[node];
                q.insert({len[to], to});
            }
    }
    return len;
}
```

Listing 10: HLD

```
//cat hld.h | ./hash.sh
//8a1639
#pragma once
```

```
//source: https://codeforces.com/blog/entry/53170
//assumes a single tree, 1-based nodes is possible by passing in 'root' in range [1, n]
//mnemonic: Heavy Light Decomposition
//NOLINTNEXTLINE(readability-identifier-naming)
struct HLD {
    struct node {
        int sub_sz, par, time_in, next;
    };
    vector<node> tree;
    HLD(vector<vector<int>>& adj /*single unrooted tree*/, int root) : tree(adj.size(), {
        1, root, (int)adj.size(), root
    }) {
        dfs1(root, adj);
        int timer = 0;
        dfs2(root, adj, timer);
    }
    void dfs1(int v, vector<vector<int>>& adj) {
        for (int& to : adj[v]) {
            if (to == tree[v].par) continue;
            tree[to].par = v;
            dfs1(to, adj);
            tree[v].sub_sz += tree[to].sub_sz;
            if (tree[to].sub_sz > tree[adj[v][0]].sub_sz || adj[v][0] == tree[v].par)
                swap(to, adj[v][0]);
        }
    }
    void dfs2(int v, const vector<vector<int>>& adj, int& timer) {
        tree[v].time_in = timer++;
        for (int to : adj[v]) {
            if (to == tree[v].par) continue;
            tree[to].next = (timer == tree[v].time_in + 1 ? tree[v].next : to);
            dfs2(to, adj, timer);
        }
    }
    // Returns inclusive-exclusive intervals (of time_in's) corresponding to the path
    ⇨ between u and v, not necessarily in order
    // This can answer queries for "is some node 'x' on some path" by checking if the
    ⇨ tree[x].time_in is in any of these intervals
    vector<pair<int, int>> path(int u, int v) const {
        vector<pair<int, int>> res;
        for (; v = tree[tree[v].next].par) {
            if (tree[v].time_in < tree[u].time_in) swap(u, v);
            if (tree[tree[v].next].time_in <= tree[u].time_in) {
                res.emplace_back(tree[u].time_in, tree[v].time_in + 1);
                return res;
            }
            res.emplace_back(tree[tree[v].next].time_in, tree[v].time_in + 1);
        }
    }
    // Returns interval (of time_in's) corresponding to the subtree of node i
    // This can answer queries for "is some node 'x' in some other node's subtree" by
    ⇨ checking if tree[x].time_in is in this interval
    pair<int, int> subtree(int i) const {
        return {tree[i].time_in, tree[i].time_in + tree[i].sub_sz};
    }
    // Returns lca of nodes u and v
    int lca(int u, int v) const {
        for (; v = tree[tree[v].next].par) {
            if (tree[v].time_in < tree[u].time_in) swap(u, v);
            if (tree[tree[v].next].time_in <= tree[u].time_in) return u;
        }
    }
}
```

```
    }  
};
```

Listing 11: Hopcroft Karp

```
//cat hopcroft_karp.h | ./hash.sh  
//de75d7  
#pragma once  
//source:  
    ↪ https://github.com/foreverbell/acm-icpc-cheat-sheet/blob/master/src/graph-algorithms/hopcroft-karp.cpp  
//Worst case  $O(E\sqrt{V})$  but faster in practice  
struct match {  
    //# of edges in matching (which = size of min vertex cover by König's theorem)  
    int size_of_matching;  
    //an arbitrary max matching is found. For this matching:  
    //if l_to_r[node_left] == -1:  
    //    node_left is not in matching  
    //else:  
    //    the edge 'node_left' <=> l_to_r[node_left] is in the matching  
    //  
    //similarly for r_to_l with edge r_to_l[node_right] <=> node_right in matching if  
    //    ↪ r_to_l[node_right] != -1  
    //matchings stored in l_to_r and r_to_l are the same matching  
    //provides way to check if any node/edge is in matching  
    vector<int> l_to_r, r_to_l;  
    //an arbitrary min vertex cover is found. For this mvc: mvc_l[node_left] is 1 iff  
    //    ↪ node_left is in the min vertex cover (same for mvc_r)  
    //if mvc_l[node_left] is 0, then node_left is in the corresponding maximal  
    //    ↪ independent set  
    vector<bool> mvc_l, mvc_r;  
};  
//Think of the bipartite graph as having a left side (with size lsz) and a right side  
    ↪ (with size rsz).  
//Nodes on left side are indexed 0,1,...,lsz-1  
//Nodes on right side are indexed 0,1,...,rsz-1  
//  
//'adj' is like a directed adjacency list containing edges from left side -> right side:  
//To initialize 'adj': For every edge node_left <=> node_right, do:  
    ↪ adj[node_left].push_back(node_right)  
match hopcroft_karp(const vector<vector<int>>& adj /*bipartite graph*/, int rsz /*number  
    ↪ of nodes on right side*/) {  
    int size_of_matching = 0, lsz = adj.size();  
    vector<int> l_to_r(lsz, -1), r_to_l(rsz, -1);  
    while (1) {  
        queue<int> q;  
        vector<int> level(lsz, -1);  
        for (int i = 0; i < lsz; i++)  
            if (l_to_r[i] == -1)  
                level[i] = 0, q.push(i);  
        bool found = 0;  
        vector<bool> mvc_l(lsz, 1), mvc_r(rsz, 0);  
        while (!q.empty()) {  
            int u = q.front();  
            q.pop();  
            mvc_l[u] = 0;  
            for (int x : adj[u]) {  
                mvc_r[x] = 1;  
                int v = r_to_l[x];  
                if (v == -1) found = 1;  
                else if (level[v] == -1) {  
                    level[v] = level[u] + 1;  
                    q.push(v);  
                }  
            }  
        }  
        if (!found) return {size_of_matching, l_to_r, r_to_l, mvc_l, mvc_r};  
        auto dfs = [&](auto self, int u) -> bool {  
            for (int x : adj[u]) {  
                int v = r_to_l[x];  
                if (v == -1 || (level[u] + 1 == level[v] && self(self, v))) {  
                    l_to_r[u] = x;  
                    r_to_l[x] = u;  
                    return 1;  
                }  
            }  
            level[u] = 1e9; //acts as visited array  
            return 0;  
        };  
        for (int i = 0; i < lsz; i++)  
            size_of_matching += (l_to_r[i] == -1 && dfs(dfs, i));  
    }  
}
```

```
        level[v] = level[u] + 1;  
        q.push(v);  
    }  
}  
}  
if (!found) return {size_of_matching, l_to_r, r_to_l, mvc_l, mvc_r};  
auto dfs = [&](auto self, int u) -> bool {  
    for (int x : adj[u]) {  
        int v = r_to_l[x];  
        if (v == -1 || (level[u] + 1 == level[v] && self(self, v))) {  
            l_to_r[u] = x;  
            r_to_l[x] = u;  
            return 1;  
        }  
    }  
    level[u] = 1e9; //acts as visited array  
    return 0;  
};  
for (int i = 0; i < lsz; i++)  
    size_of_matching += (l_to_r[i] == -1 && dfs(dfs, i));  
}  
}
```

Listing 12: LCA

```
//cat lca.h | ./hash.sh  
//22246e  
#pragma once  
//https://codeforces.com/blog/entry/74847  
//assumes a single tree, 1-based nodes is possible by passing in 'root' in range [1, n]  
//mnemonic: Least/Lowest Common Ancestor  
//NOLINTNEXTLINE(readability-identifier-naming)  
struct LCA {  
    struct node {  
        int jmp, jmp_edges, par, depth;  
        long long dist;  
    };  
    vector<node> tree;  
    LCA(const vector<vector<pair<int, long long>>>& adj, int root) : tree(adj.size(), {  
        root, 1, root, 0, 0LL  
    }) {  
        dfs(root, adj);  
    }  
    void dfs(int v, const vector<vector<pair<int, long long>>>& adj) {  
        int jmp, jmp_edges;  
        if (tree[v].depth > 0 && tree[v].jmp_edges == tree[tree[v].jmp].jmp_edges)  
            jmp = tree[tree[v].jmp].jmp, jmp_edges = 2 * tree[v].jmp_edges + 1;  
        else  
            jmp = v, jmp_edges = 1;  
        for (auto [ch, w] : adj[v]) {  
            if (ch == tree[v].par) continue;  
            tree[ch] = {  
                jmp,  
                jmp_edges,  
                v,  
                1 + tree[v].depth,  
                w + tree[v].dist  
            };  
            dfs(ch, adj);  
        }  
    }  
}
```

```

}
//traverse up k edges in O(log(k)). So with k=1 this returns 'v's parent
int kth_par(int v, int k) const {
    k = min(k, tree[v].depth);
    while (k > 0) {
        if (tree[v].jmp_edges <= k) {
            k -= tree[v].jmp_edges;
            v = tree[v].jmp;
        } else {
            k--;
            v = tree[v].par;
        }
    }
    return v;
}

int get_lca(int x, int y) const {
    if (tree[x].depth < tree[y].depth) swap(x, y);
    x = kth_par(x, tree[x].depth - tree[y].depth);
    while (x != y) {
        if (tree[x].jmp != tree[y].jmp)
            x = tree[x].jmp, y = tree[y].jmp;
        else
            x = tree[x].par, y = tree[y].par;
    }
    return x;
}

int dist_edges(int x, int y) const {
    return tree[x].depth + tree[y].depth - 2 * tree[get_lca(x, y)].depth;
}

long long dist_weight(int x, int y) const {
    return tree[x].dist + tree[y].dist - 2 * tree[get_lca(x, y)].dist;
}
};
```

Listing 13: Kth Node on Path

```
//cat kth_node_on_path.h | ./hash.sh
//7a4c3c
#pragma once
#include "lca.h"
struct kth_node_on_path {
    LCA lca;
    kth_node_on_path(const vector<vector<pair<int, long long>>>& adj, int root) :
        ↪ lca(adj, root) {}
    //consider path {u, u's par, ..., LCA(u,v), ..., v's par, v}. This returns the node
        ↪ at index k
    //assumes 0 <= k <= number of edges on path from u to v
    int query(int u, int v, int k) const {
        int lca_uv = lca.get_lca(u, v);
        int u_lca = lca.tree[u].depth - lca.tree[lca_uv].depth;
        int v_lca = lca.tree[v].depth - lca.tree[lca_uv].depth;
        assert(0 <= k && k <= u_lca + v_lca);
        return k <= u_lca ? lca.kth_par(u, k) : lca.kth_par(v, u_lca + v_lca - k);
    }
};
```

Listing 14: SCC

```
//cat scc.h | ./hash.sh
```

```
//ee9331
#pragma once
//source:
    ↪ https://github.com/kth-competitive-programming/kactl/blob/main/content/graph/SCC.h
//mnemonic: Strongly Connected Component
struct scc_info {
    int num_sccs;
    //scc's are labeled 0,1,...,'num_sccs-1'
    //scc_id[i] is the id of the scc containing node 'i'
    //for each edge i -> j: scc_id[i] >= scc_id[j] (topo order of scc's)
    vector<int> scc_id;
};
//NOLINTNEXTLINE(readability-identifier-naming)
scc_info SCC(const vector<vector<int>>& adj /*directed, unweighted graph*/) {
    int n = adj.size(), timer = 1, num_sccs = 0;
    vector<int> tin(n, 0), scc_id(n, -1), node_stack;
    auto dfs = [&](auto self, int v) -> int {
        int low = tin[v] = timer++;
        node_stack.push_back(v);
        for (int to : adj[v]) {
            if (scc_id[to] < 0)
                low = min(low, tin[to] ? tin[to] : self(self, to));
        }
        if (tin[v] == low) {
            while (1) {
                int node = node_stack.back();
                node_stack.pop_back();
                scc_id[node] = num_sccs;
                if (node == v) break;
            }
            num_sccs++;
        }
        return low;
    };
    for (int i = 0; i < n; i++) {
        if (!tin[i])
            dfs(dfs, i);
    }
    return {num_sccs, scc_id};
}
```

Listing 15: RANGE DATA STRUCTURES

Listing 16: Lazy Segment Tree

```
//cat seg_tree.h | ./hash.sh
//4d91a7
#pragma once
//source: https://codeforces.com/blog/entry/18051,
    ↪ https://github.com/ecnerwala/cp-book/blob/master/src/seg_tree.hpp,
    ↪ https://github.com/yosupo06/Algorithm/blob/master/src/datastructure/segtree.hpp
struct seg_tree {
    using dt = long long;
    using ch = long long;
    static dt combine(const dt& l, const dt& r) {
        return min(l, r);
    }
    static const dt INF = 1e18;
```

```
struct node {
    dt val;
    ch lazy;
    int l, r; //[l, r)
};

const int N, S /*smallest power of 2 >= N*/;
vector<node> tree;
//doesn't work with empty array
seg_tree(const vector<dt>& arr) : N(arr.size()), S(1 << __lg(2 * N - 1)), tree(2 *
    ↪ N) {
    for (int i = 0; i < N; i++)
        tree[i + N] = {arr[i], 0, i, i + 1};
    rotate(tree.rbegin(), tree.rbegin() + S - N, tree.rbegin() + N);
    for (int i = N - 1; i >= 1; i--) {
        tree[i] = {
            combine(tree[2 * i].val, tree[2 * i + 1].val),
            0,
            tree[2 * i].l,
            tree[2 * i + 1].r
        };
    }
}

void apply(int v, ch change) {
    tree[v].val += change;
    tree[v].lazy += change;
}

void push(int v) {
    if (tree[v].lazy) {
        apply(2 * v, tree[v].lazy);
        apply(2 * v + 1, tree[v].lazy);
        tree[v].lazy = 0;
    }
}

void build(int v) {
    tree[v].val = combine(tree[2 * v].val, tree[2 * v + 1].val);
}

int to_leaf(int i) const {
    i += S;
    return i < 2 * N ? i : 2 * (i - N);
}

//update range [l, r)
void update(int l, int r, ch change) {
    l = to_leaf(l), r = to_leaf(r);
    int lca_l_r = __lg((l - 1) ^ r);
    for (int lg = __lg(l); lg > __builtin_ctz(l); lg--) push(l >> lg);
    for (int lg = lca_l_r; lg > __builtin_ctz(r); lg--) push(r >> lg);
    for (int x = l, y = r; x < y; x >>= 1, y >>= 1) {
        if (x & 1) apply(x++, change);
        if (y & 1) apply(--y, change);
    }
    for (int lg = __builtin_ctz(r) + 1; lg <= lca_l_r; lg++) build(r >> lg);
    for (int lg = __builtin_ctz(l) + 1; lg <= __lg(l); lg++) build(l >> lg);
}

//query range [l, r)
dt query(int l, int r) {
    l = to_leaf(l), r = to_leaf(r);
    int lca_l_r = __lg((l - 1) ^ r);
    for (int lg = __lg(l); lg > __builtin_ctz(l); lg--) push(l >> lg);
    for (int lg = lca_l_r; lg > __builtin_ctz(r); lg--) push(r >> lg);
    dt resl = INF, resr = INF;
    for (; l < r; l >>= 1, r >>= 1) {
```

```
        if (l & 1) resl = combine(resl, tree[l++].val);
        if (r & 1) resr = combine(tree[--r].val, resr);
    }
    return combine(resl, resr);
};
```

Listing 17: BIT

```
//cat bit.h | ./hash.sh
//83059d
#pragma once
//mnemonic: Binary Indexed Tree
//NOLINTNEXTLINE(readability-identifier-naming)
template<class T> struct BIT {
    const int N;
    vector<T> bit;
    BIT(int a_n) : N(a_n), bit(N, 0) {}
    BIT(const vector<T>& a) : BIT(a.size()) {
        for (int i = 0; i < N; i++) {
            bit[i] += a[i];
            int j = i | (i + 1);
            if (j < N) bit[j] += bit[i];
        }
    }
    void update(int i, const T& d) {
        assert(0 <= i && i < N);
        for (; i < N; i |= i + 1) bit[i] += d;
    }
    T sum(int r) const { //sum of range [0, r)
        assert(0 <= r && r <= N);
        T ret = 0;
        for (; r > 0; r &= r - 1) ret += bit[r - 1];
        return ret;
    }
    T sum(int l, int r) const { //sum of range [l, r)
        assert(0 <= l && l <= r && r <= N);
        return sum(r) - sum(l);
    }
    //Returns min pos (0<=pos<=N+1) such that sum of [0, pos) >= sum
    //Returns N + 1 if no sum is >= sum, or 0 if empty sum is.
    //Doesn't work with negatives
    int lower_bound(T sum) const {
        if (sum <= 0) return 0;
        int pos = 0;
        for (int pw = 1 << __lg(N | 1); pw; pw >>= 1)
            if (pos + pw <= N && bit[pos + pw - 1] < sum)
                pos += pw, sum -= bit[pos - 1];
        return pos + 1;
    }
};
```

Listing 18: RMQ

```
//cat rmq.h | ./hash.sh
//a90b91
#pragma once
//source:
    ↪ https://github.com/kth-competitive-programming/kactl/blob/main/content/data-structure
```



```
//usage:
// vector<long long> arr;
// ...
// RMQ<long long> rmq(arr, [0](auto x, auto y) { return min(x,y); });
//
//to also get index of min element, do:
// RMQ<pair<T, int>> rmq(arr, [0](auto x, auto y) { return min(x,y); });
//and initialize arr[i].second = i (0<=i<n)
//If there are multiple indexes of min element, it'll return the smallest
//(left-most) one
//mnemonic: Range Min/Max Query
//NOLINTNEXTLINE(readability-identifier-naming)
template <class T> struct RMQ {
    vector<vector<T>> dp;
    function<T(const T&, const T&)> func;
    RMQ(const vector<T>& arr, const function<T(const T&, const T&)>& a_func) : dp(1,
        ↳ arr), func(a_func) {
        for (int pw = 1, k = 1, n = arr.size(); 2 * pw <= n; pw *= 2, k++) {
            dp.emplace_back(n - 2 * pw + 1);
            for (int j = 0; j < n - 2 * pw + 1; j++)
                dp[k][j] = func(dp[k - 1][j], dp[k - 1][j + pw]);
        }
    }
    //inclusive-exclusive range [l, r)
    T query(int l, int r) const {
        assert(0 <= l && l < r && r <= (int)dp[0].size());
        int lg = __lg(r - l);
        return func(dp[lg][l], dp[lg][r - (1 << lg)]);
    }
};
```

Listing 19: Implicit Lazy Segment Tree

```
//cat implicit_seg_tree.h | ./hash.sh
//d5be85
#pragma once
//example initialization:
// implicit_seg_tree<10'000'000> ist(l, r);
template <int N> struct implicit_seg_tree {
    using dt = array<long long, 2>; //min, number of mins
    using ch = long long;
    static dt combine(const dt& l, const dt& r) {
        if (l[0] == r[0]) return {l[0], l[1] + r[1]};
        return min(l, r);
    }
    static constexpr dt UNIT{(long long)1e18, 0LL};
    struct node {
        dt val;
        ch lazy;
        int lch, rch; // children, indexes into 'tree', -1 for null
        node() {}
        node(const dt& a_val) : val(a_val), lazy(0), lch(-1), rch(-1) {}
    } tree[N];
    int ptr, root_l, root_r; // [root_l, root_r) defines range of root node; handles
        ↳ negatives
    implicit_seg_tree(int l, int r) : ptr(0), root_l(l), root_r(r) {
        tree[ptr++] = node(dt{0, r - l});
    }
    void apply(int v, ch add) {
        tree[v].val[0] += add;
```

```
        tree[v].lazy += add;
    }
    void push(int v, int tl, int tr) {
        if (tr - tl > 1 && tree[v].lch == -1) {
            int tm = tl + (tr - tl) / 2;
            assert(ptr + 1 < N);
            tree[v].lch = ptr;
            tree[ptr++] = node(dt{0, tm - tl});
            tree[v].rch = ptr;
            tree[ptr++] = node(dt{0, tr - tm});
        }
        if (tree[v].lazy) {
            apply(tree[v].lch, tree[v].lazy);
            apply(tree[v].rch, tree[v].lazy);
            tree[v].lazy = 0;
        }
    }
    //update range [l,r)
    void update(int l, int r, ch add) {
        update(0, root_l, root_r, l, r, add);
    }
    void update(int v, int tl, int tr, int l, int r, ch add) {
        if (r <= tl || tr <= l)
            return;
        if (l <= tl && tr <= r)
            return apply(v, add);
        push(v, tl, tr);
        int tm = tl + (tr - tl) / 2;
        update(tree[v].lch, tl, tm, l, r, add);
        update(tree[v].rch, tm, tr, l, r, add);
        tree[v].val = combine(tree[tree[v].lch].val,
            tree[tree[v].rch].val);
    }
    //query range [l,r)
    dt query(int l, int r) {
        return query(0, root_l, root_r, l, r);
    }
    dt query(int v, int tl, int tr, int l, int r) {
        if (r <= tl || tr <= l)
            return UNIT;
        if (l <= tl && tr <= r)
            return tree[v].val;
        push(v, tl, tr);
        int tm = tl + (tr - tl) / 2;
        return combine(query(tree[v].lch, tl, tm, l, r),
            query(tree[v].rch, tm, tr, l, r));
    }
};
```

Listing 20: Kth Smallest

```
//cat kth_smallest.h | ./hash.sh
//f8ce8b
#include <bits/stdc++.h>
using namespace std;
#pragma once
//source:
        ↳ https://cp-algorithms.com/data_structures/segment_tree.html#preserving-the-history-o
struct kth_smallest {
    struct node {
```



```
int sum;
int lch, rch;//children, indexes into 'tree'
};
int mn, mx;
vector<int> roots;
deque<node> tree;
kth_smallest(const vector<int>& arr) : mn(INT_MAX), mx(INT_MIN), roots(arr.size() +
    ⇨ 1, 0) {
    tree.push_back({0, 0, 0}); //acts as null
    for (int val : arr) mn = min(mn, val), mx = max(mx, val + 1);
    for (int i = 0; i < (int)arr.size(); i++)
        roots[i + 1] = update(roots[i], mn, mx, arr[i]);
}
int update(int v, int tl, int tr, int idx) {
    if (tr - tl == 1) {
        tree.push_back({tree[v].sum + 1, 0, 0});
        return tree.size() - 1;
    }
    int tm = tl + (tr - tl) / 2;
    int lch = tree[v].lch;
    int rch = tree[v].rch;
    if (idx < tm)
        lch = update(lch, tl, tm, idx);
    else
        rch = update(rch, tm, tr, idx);
    tree.push_back({tree[lch].sum + tree[rch].sum, lch, rch});
    return tree.size() - 1;
}
/* find (k+1)th smallest number in range [l, r)
 * k is 0-based, so query(l,r,0) returns the min
 */
int query(int l, int r, int k) const {
    assert(0 <= k && k < r - 1); //note this condition implies l < r
    assert(0 <= l && r < (int)roots.size());
    return query(roots[l], roots[r], mn, mx, k);
}
int query(int vl, int vr, int tl, int tr, int k) const {
    assert(tree[vr].sum > tree[vl].sum);
    if (tr - tl == 1)
        return tl;
    int tm = tl + (tr - tl) / 2;
    int left_count = tree[tree[vr].lch].sum - tree[tree[vl].lch].sum;
    if (left_count > k) return query(tree[vl].lch, tree[vr].lch, tl, tm, k);
    return query(tree[vl].rch, tree[vr].rch, tm, tr, k - left_count);
}
};
```

Listing 21: Number Distinct Elements

```
//cat distinct_query.h | ./hash.sh
//6dfaad
#pragma once
//source:
⇨ https://cp-algorithms.com/data_structures/segment_tree.html#preserving-the-history-of-it
//works with negatives
//O(n log n) time and space
struct distinct_query {
    struct node {
        int sum;
        int lch, rch;//children, indexes into 'tree'
```

```
};
const int N;
vector<int> roots;
deque<node> tree;
distinct_query(const vector<int>& arr) : N(arr.size()), roots(N + 1, 0) {
    tree.push_back({0, 0, 0}); //acts as null
    map<int, int> last_idx;
    for (int i = 0; i < N; i++) {
        roots[i + 1] = update(roots[i], 0, N, last_idx[arr[i]]);
        last_idx[arr[i]] = i + 1;
    }
}
int update(int v, int tl, int tr, int idx) {
    if (tr - tl == 1) {
        tree.push_back({tree[v].sum + 1, 0, 0});
        return tree.size() - 1;
    }
    int tm = tl + (tr - tl) / 2;
    int lch = tree[v].lch;
    int rch = tree[v].rch;
    if (idx < tm)
        lch = update(lch, tl, tm, idx);
    else
        rch = update(rch, tm, tr, idx);
    tree.push_back({tree[lch].sum + tree[rch].sum, lch, rch});
    return tree.size() - 1;
}
//returns number of distinct elements in range [l,r)
int query(int l, int r) const {
    assert(0 <= l && l <= r && r <= N);
    return query(roots[l], roots[r], 0, N, 1 + 1);
}
int query(int vl, int vr, int tl, int tr, int idx) const {
    if (tree[vr].sum == 0 || idx <= tl)
        return 0;
    if (tr <= idx)
        return tree[vr].sum - tree[vl].sum;
    int tm = tl + (tr - tl) / 2;
    return query(tree[vl].lch, tree[vr].lch, tl, tm, idx) +
        query(tree[vl].rch, tree[vr].rch, tm, tr, idx);
}
};
```

Listing 22: Merge Sort Tree

```
//cat merge_sort_tree.h | ./hash.sh
//a84032
#pragma once
//For point updates: either switch to policy based BST, or use sqrt decomposition
struct merge_sort_tree {
    const int N, S/*smallest power of 2 >= N*/;
    vector<vector<int>> tree;
    //doesn't work with empty array
    merge_sort_tree(const vector<int>& arr) : N(arr.size()), S(1 << __lg(2 * N - 1)),
        ⇨ tree(2 * N) {
        for (int i = 0; i < N; i++)
            tree[i + N] = {arr[i]};
        rotate(tree.rbegin(), tree.rbegin() + S - N, tree.rbegin() + N);
        for (int i = N - 1; i >= 1; i--) {
            const auto& l = tree[2 * i];
```

```
const auto& r = tree[2 * i + 1];
tree[i].reserve(l.size() + r.size());
merge(l.begin(), l.end(), r.begin(), r.end(), back_inserter(tree[i]));
}
}
int value(int v, int x) const {
    return lower_bound(tree[v].begin(), tree[v].end(), x) - tree[v].begin();
}
int to_leaf(int i) const {
    i += S;
    return i < 2 * N ? i : 2 * (i - N);
}
//How many values in range [l, r) are < x?
//O(log^2(n))
int query(int l, int r, int x) const {
    int res = 0;
    for (l = to_leaf(l), r = to_leaf(r); l < r; l >>= 1, r >>= 1) {
        if (l & 1) res += value(l++, x);
        if (r & 1) res += value(--r, x);
    }
    return res;
}
};
```

Listing 23: STRINGS

Listing 24: Suffix Array

```
//cat suffix_array.h | ./hash.sh
//52332b
#pragma once
//source: https://judge.yosupo.jp/submission/37410
//O(n)
//mnemonic: Suffix Array Induced Sorting
template<class T> vector<int> sa_is(const T& s, int upper /*max element of 's'; for
    ↪ std::string, pass in 255*/) {
    int n = (int)s.size();
    if (n == 0) return {};
    if (n == 1) return {0};
    if (n == 2) {
        if (s[0] < s[1]) {
            return {0, 1};
        } else {
            return {1, 0};
        }
    }
    vector<int> sa(n);
    vector<bool> ls(n);
    for (int i = n - 2; i >= 0; i--)
        ls[i] = (s[i] == s[i + 1]) ? ls[i + 1] : (s[i] < s[i + 1]);
    vector<int> sum_l(upper + 1), sum_s(upper + 1);
    for (int i = 0; i < n; i++) {
        if (!ls[i])
            sum_s[s[i]]++;
        else
            sum_l[s[i] + 1]++;
    }
    for (int i = 0; i <= upper; i++) {
```

```
sum_s[i] += sum_l[i];
if (i < upper) sum_l[i + 1] += sum_s[i];
}
vector<int> buf(upper + 1);
auto induce = [&](const vector<int>& lms) {
    fill(sa.begin(), sa.end(), -1);
    fill(buf.begin(), buf.end(), 0);
    copy(sum_s.begin(), sum_s.end(), buf.begin());
    for (auto d : lms) {
        if (d == n) continue;
        sa[buf[s[d]]++] = d;
    }
    copy(sum_l.begin(), sum_l.end(), buf.begin());
    sa[buf[s[n - 1]]++] = n - 1;
    for (int i = 0; i < n; i++) {
        int v = sa[i];
        if (v >= 1 && !ls[v - 1])
            sa[buf[s[v - 1]]++] = v - 1;
    }
    copy(sum_l.begin(), sum_l.end(), buf.begin());
    for (int i = n - 1; i >= 0; i--) {
        int v = sa[i];
        if (v >= 1 && ls[v - 1])
            sa[--buf[s[v - 1] + 1]] = v - 1;
    }
};
vector<int> lms_map(n + 1, -1);
int m = 0;
for (int i = 1; i < n; i++) {
    if (!ls[i - 1] && ls[i])
        lms_map[i] = m++;
}
vector<int> lms;
lms.reserve(m);
for (int i = 1; i < n; i++) {
    if (!ls[i - 1] && ls[i])
        lms.push_back(i);
}
induce(lms);
if (m) {
    vector<int> sorted_lms;
    sorted_lms.reserve(m);
    for (int v : sa) {
        if (lms_map[v] != -1) sorted_lms.push_back(v);
    }
    vector<int> rec_s(m);
    int rec_upper = 0;
    rec_s[lms_map[sorted_lms[0]]] = 0;
    for (int i = 1; i < m; i++) {
        int l = sorted_lms[i - 1], r = sorted_lms[i];
        int end_l = (lms_map[l] + 1 < m) ? lms[lms_map[l] + 1] : n;
        int end_r = (lms_map[r] + 1 < m) ? lms[lms_map[r] + 1] : n;
        bool same = 1;
        if (end_l - 1 != end_r - r)
            same = 0;
        else {
            while (l < end_l) {
                if (s[l] != s[r])
                    break;
                l++;
                r++;
            }
        }
    }
}
```

```
        }
        if (l == n || s[l] != s[r]) same = 0;
    }
    if (!same) rec_upper++;
    rec_s[lms_map[sorted_lms[i]]] = rec_upper;
}
auto rec_sa =
    sa_is(rec_s, rec_upper);
for (int i = 0; i < m; i++)
    sorted_lms[i] = lms[rec_sa[i]];
    induce(sorted_lms);
}
return sa;
}
```

Listing 25: LCP

```
//cat lcp.h | ./hash.sh
//193e7c
#pragma once
//source: https://judge.yosupo.jp/submission/37410
//mnemonic: Longest Common Prefix
//NOLINTNEXTLINE(readability-identifier-naming)
template<class T> vector<int> LCP(const T& s, const vector<int>& sa, const vector<int>&
    ↪ sa_inv) {
    int n = s.size();
    vector<int> lcp(n, 0);
    for (int i = 0, k = 0; i < n; i++, k ? k-- : 0) {
        if (sa_inv[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = sa[sa_inv[i] + 1];
        while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
        lcp[sa_inv[i]] = k;
    }
    return lcp;
}
```

Listing 26: KMP

```
//cat kmp.h | ./hash.sh
//73f1be
#pragma once
//mnemonic: Knuth Morris Pratt
#include "../../kactl/content/strings/KMP.h"
//usage:
// string needle;
// ...
// KMP kmp(needle);
//or
// vector<int> needle;
// ...
// KMP kmp(needle);
//kmp doubling trick: to check if 2 arrays are rotationally equivalent: run kmp
//with one array as the needle and the other array doubled (excluding the first
//8 last characters) as the haystack or just use kactl's min rotation code
//NOLINTNEXTLINE(readability-identifier-naming)
template <class T> struct KMP {
```

```
KMP(const T& a_needle) : needle(a_needle), pf(pi(needle)) {}
// if haystack = "bananas"
// needle = "ana"
//
// then we find 2 matches:
// bananas
// _ana_
// _ _ana_
// 0123456 (indexes)
// and KMP::find returns {1,3} - the indexes in haystack where
// each match starts.
//
// You can also pass in 0 for "all" and KMP::find will only
// return the first match: {1}. Useful for checking if there exists
// some match:
//
// KMP::find(<haystack>,0).size() > 0
vector<int> find(const T& haystack, bool all = 1) const {
    vector<int> matches;
    for (int i = 0, j = 0; i < (int)haystack.size(); i++) {
        while (j > 0 && needle[j] != haystack[i]) j = pf[j - 1];
        if (needle[j] == haystack[i]) j++;
        if (j == (int)needle.size()) {
            matches.push_back(i - (int)needle.size() + 1);
            if (!all) return matches;
            j = pf[j - 1];
        }
    }
    return matches;
}
T needle;
vector<int> pf; //prefix function
};
```

Listing 27: Trie

```
//cat trie.h | ./hash.sh
//10777e
#pragma once
//source: https://cp-algorithms.com/string/aho_corasick.html#construction-of-the-trie
//intended to be a base template and to be modified
const int K = 26; //alphabet size
struct trie {
    const char MIN_CH = 'a'; // 'A' for uppercase, '0' for digits
    struct node {
        int next[K], id, p = -1;
        char ch;
        bool leaf = 0;
        node(int a_p = -1, char a_ch = '#') : p(a_p), ch(a_ch) {
            fill(next, next + K, -1);
        }
    };
    vector<node> t;
    trie() : t(1) {}
    void add_string(const string& s, int id) {
        int c = 0;
        for (char ch : s) {
            int v = ch - MIN_CH;
            if (t[c].next[v] == -1) {
                t[c].next[v] = t.size();
```

```
        t.emplace_back(c, ch);
    }
    c = t[c].next[v];
}
t[c].leaf = 1;
t[c].id = id;
}
void remove_string(const string& s) {
    int c = 0;
    for (char ch : s) {
        int v = ch - MIN_CH;
        if (t[c].next[v] == -1)
            return;
        c = t[c].next[v];
    }
    t[c].leaf = 0;
}
int find_string(const string& s) const {
    int c = 0;
    for (char ch : s) {
        int v = ch - MIN_CH;
        if (t[c].next[v] == -1)
            return -1;
        c = t[c].next[v];
    }
    if (!t[c].leaf) return -1;
    return t[c].id;
}
};
```

Listing 28: Binary Trie

```
//cat binary_trie.h | ./hash.sh
//33aa3a
#pragma once
struct binary_trie {
    const int MX_BIT = 62;
    struct node {
        long long val = -1;
        int sub_sz = 0; //number of inserted values in subtree
        array<int, 2> next = {-1, -1};
    };
    vector<node> t;
    binary_trie() : t(1) {}
    //delta = 1 to insert val, -1 to remove val, 0 to get the # of val's in this data
    //    -> structure
    int update(long long val, int delta) {
        int c = 0;
        t[0].sub_sz += delta;
        for (int bit = MX_BIT; bit >= 0; bit--) {
            bool v = (val >> bit) & 1;
            if (t[c].next[v] == -1) {
                t[c].next[v] = t.size();
                t.emplace_back();
            }
            c = t[c].next[v];
            t[c].sub_sz += delta;
        }
        t[c].val = val;
        return t[c].sub_sz;
    }
};
```

```
    }
    int size() const {
        return t[0].sub_sz;
    }
    //returns x such that:
    // x is in this data structure
    // value of (x ^ val) is minimum
    long long min_xor(long long val) const {
        assert(size() > 0);
        int c = 0;
        for (int bit = MX_BIT; bit >= 0; bit--) {
            bool v = (val >> bit) & 1;
            int ch = t[c].next[v];
            if (ch != -1 && t[ch].sub_sz > 0)
                c = ch;
            else
                c = t[c].next[!v];
        }
        return t[c].val;
    }
};
```

Listing 29: Longest Common Prefix Query

```
//cat lcp_query.h | ./hash.sh
//5a7bfe
#pragma once
#include "suffix_array.h"
#include "lcp.h"
#include "../range_data_structures/rmq.h"
//computes suffix array, lcp array, and then sparse table over lcp array
//O(n log n)
struct lcp_query {
    vector<int> sa, inv_sa, lcp;
    RMQ<int> st;
    lcp_query(const string& s) : sa(sa_is(s, 255)), inv_sa(init_inv()), lcp(LCP(s, sa,
        //    -> inv_sa)), st(lcp, [](int x, int y) {
        //    -> return min(x, y);
    }) {}
    vector<int> init_inv() const {
        vector<int> inv(sa.size());
        for (int i = 0; i < (int)sa.size(); i++) inv[sa[i]] = i;
        return inv;
    }
    //length of longest common prefix of suffixes s[idx1 ... n), s[idx2 ... n), 0-based
    //    -> indexing
    //
    //You can check if two substrings s[l1..r1), s[l2..r2) are equal in O(1) by:
    //r1-l1 == r2-l2 iff longest_common_prefix(l1, l2) >= r1-l1
    int longest_common_prefix(int idx1, int idx2) const {
        if (idx1 == idx2) return (int)sa.size() - idx1;
        idx1 = inv_sa[idx1];
        idx2 = inv_sa[idx2];
        if (idx1 > idx2) swap(idx1, idx2);
        return st.query(idx1, idx2);
    }
    //returns 1 if suffix s[idx1 ... n) < s[idx2 ... n)
    //(so 0 if idx1 == idx2)
    bool less(int idx1, int idx2) const {
        return inv_sa[idx1] < inv_sa[idx2];
    }
};
```

```
    }
};
```

Listing 30: Palindrome Query

```
//cat palindrome_query.h | ./hash.sh
//7326d0
#pragma once
#include "../kactl/content/strings/Manacher.h"
struct pal_query {
    const int N;
    array<vi, 2> pal_len;
    pal_query(const string& s) : N(s.size()), pal_len(manacher(s)) {}
    //returns 1 if substring s[l...r] is a palindrome
    bool is_pal(int l, int r) const {
        assert(0 <= l && l <= r && r <= N);
        int len = r - l;
        return pal_len[len & 1][l + len / 2] >= len / 2;
    }
};
```

Listing 31: MATH

Listing 32: BIN EXP MOD

```
//cat exp_mod.h | ./hash.sh
//3be256
#pragma once
//returns (base^pw)%mod in O(log(pw)), but returns 1 for 0^0
//
//What if base doesn't fit in long long?
//Since (base^pw)%mod == ((base%mod)^pw)%mod we can calculate base under mod of 'mod'
//
//What if pw doesn't fit in long long?
//case 1: mod is prime
//((base^pw)%mod == (base^(pw%(mod-1))))%mod (from Fermat's little theorem)
//so calculate pw under mod of 'mod-1'
//note 'mod-1' is not prime, so you need to be able to calculate 'pw%(mod-1)' without
//    ↪ division
//
//case 2: non-prime mod
//let t = totient(mod)
//if pw >= log2(mod) then (base^pw)%mod == (base^(t+(pw%t)))%mod (proof
//    ↪ https://cp-algorithms.com/algebra/phi-function.html#generalization)
//so calculate pw under mod of 't'
//incidentally, totient(p) = p - 1 for every prime p, making this a more generalized
//    ↪ version of case 1
int pow(long long base, long long pw, int mod) {
    assert(0 <= pw && 0 <= base && 1 <= mod);
    int res = 1;
    base %= mod;
    while (pw > 0) {
        if (pw & 1) res = res * base % mod;
        base = base * base % mod;
        pw >>= 1;
    }
    return res;
}
```

Listing 33: Fibonacci

```
//cat fib.h | ./hash.sh
//9ac293
#pragma once
//https://codeforces.com/blog/entry/14516
//O(log(n))
unordered_map<long long, int> table;
int fib(long long n, int mod) {
    if (n < 2) return n;
    if (table.find(n) != table.end()) return table[n];
    table[n] = (1LL * fib((n + 1) / 2, mod) * fib(n / 2, mod) + 1LL * fib((n - 1) / 2,
        ↪ mod) * fib((n - 2) / 2, mod)) % mod;
    return table[n];
}
```

Listing 34: Matrix Mult and Pow

```
//cat matrix_expo.h | ./hash.sh
//2edd34
#pragma once
//empty matrix -> RTE
vector<vector<int>> mult(const vector<vector<int>>& a, const vector<vector<int>>& b, int
    ↪ mod) {
    assert(a[0].size() == b.size());
    int n = a.size(), m = b[0].size(), inner = b.size();
    vector<vector<int>> prod(n, vector<int>(m, 0));
    for (int i = 0; i < n; i++) {
        for (int k = 0; k < inner; k++) {
            for (int j = 0; j < m; j++)
                prod[i][j] = (prod[i][j] + 1LL * a[i][k] * b[k][j]) % mod;
        }
    }
    return prod;
}
vector<vector<int>> power(vector<vector<int>> mat/*intentional pass by value*/, long
    ↪ long pw, int mod) {
    int n = mat.size();
    vector<vector<int>> prod(n, vector<int>(n, 0));
    for (int i = 0; i < n; i++)
        prod[i][i] = 1;
    while (pw > 0) {
        if (pw % 2 == 1) prod = mult(prod, mat, mod);
        mat = mult(mat, mat, mod);
        pw /= 2;
    }
    return prod;
}
```

Listing 35: N Choose K MOD

```
//cat n_choose_k_mod.h | ./hash.sh
//f3a1a9
#pragma once
//for mod inverse
#include "exp_mod.h"
// usage:
//     n_choose_k nk(n, 1e9+7) to use 'choose', 'inv' with inputs strictly < n
// or:
```

```
//      n_choose_k nk(mod, mod) to use 'choose_with_lucas_theorem' with arbitrarily large
//      ↪ inputs
struct n_choose_k {
    n_choose_k(int n, int a_mod) : mod(a_mod), fact(n, 1), inv_fact(n, 1) {
        //this implementation doesn't work if n > mod because n! % mod = 0 when n >=
        //mod. So 'inv_fact' array will be all 0's
        assert(max(n, 2) <= mod);
        //assert mod is prime. mod is intended to fit inside an int so that
        //multiplications fit in a longlong before being modded down. So this
        //will take sqrt(2^31) time
        for (int i = 2; i * i <= mod; i++) assert(mod % i);
        for (int i = 2; i < n; i++)
            fact[i] = 1LL * fact[i - 1] * i % mod;
        inv_fact.back() = pow(fact.back(), mod - 2, mod);
        for (int i = n - 2; i >= 2; i--)
            inv_fact[i] = inv_fact[i + 1] * (i + 1LL) % mod;
    }
    //classic n choose k
    //fails when n >= mod
    int choose(int n, int k) const {
        if (k < 0 || k > n) return 0;
        //now we know 0 <= k <= n so 0 <= n
        return 1LL * fact[n] * inv_fact[k] % mod * inv_fact[n - k] % mod;
    }
    //lucas theorem to calculate n choose k in O(log(k))
    //need to calculate all factorials in range [0,mod), so O(mod) time&space, so need
    //    ↪ smallish prime mod (< 1e6 maybe)
    //handles n >= mod correctly
    int choose_with_lucas_theorem(long long n, long long k) const {
        if (k < 0 || k > n) return 0;
        if (k == 0 || k == n) return 1;
        return 1LL * choose_with_lucas_theorem(n / mod, k / mod) * choose(n % mod, k %
            ↪ mod) % mod;
    }
    //returns x such that x * n % mod == 1
    int inv(int n) const {
        assert(1 <= n); //don't divide by 0 :)
        return 1LL * fact[n - 1] * inv_fact[n] % mod;
    }
    int mod;
    vector<int> fact, inv_fact;
};
```

Listing 36: Partitions

```
//cat partitions.h | ./hash.sh
//3356f6
#pragma once
//https://oeis.org/A000041
//O(n sqrt n) time, but small-ish constant factor (there does exist a O(n log n)
//    ↪ solution too)
vector<int> partitions(int n, int mod) {
    vector<int> dp(n, 1);
    for (int i = 1; i < n; i++) {
        long long sum = 0;
        for (int j = 1, pent = 1, sign = 1; pent <= i; j++, pent += 3 * j - 2, sign =
            ↪ -sign) {
            if (pent + j <= i) sum += dp[i - pent - j] * sign + mod;
            sum += dp[i - pent] * sign + mod;
        }
    }
```

```
        dp[i] = sum % mod;
    }
    return dp;
}
```

Listing 37: Derangements

```
//cat derangements.h | ./hash.sh
//c221bb
#pragma once
//https://oeis.org/A000166
//
//for a permutation of size i:
//there are (i-1) places to move 0 to not be at index 0. Let's say we moved 0 to index j
//    ↪ (j>0).
//If we move value j to index 0 (forming a cycle of length 2), then there are dp[i-2]
//    ↪ derangements of the remaining i-2 elements
//else there are dp[i-1] derangements of the remaining i-1 elements (including j)
vector<int> derangements(int n, int mod) {
    vector<int> dp(n, 0);
    dp[0] = 1;
    for (int i = 2; i < n; i++)
        dp[i] = 1LL * (i - 1) * (dp[i - 1] + dp[i - 2]) % mod;
    return dp;
}
```

Listing 38: Prime Sieve

```
//cat prime_sieve.h | ./hash.sh
//45fc23
#pragma once
//a_prime[val] = some random prime factor of 'val'
//
//to check if 'val' is prime:
//    if (a_prime[val] == val)
//
//to get all prime factors of a number 'val' in O(log(val)):
//    while (val > 1) {
//        int p = a_prime[val];
//        //p is some prime factor of val
//        val /= p;
//    }
const int N = 1e6 + 10;
int a_prime[N];
void calc_seive() {
    iota(a_prime, a_prime + N, 0);
    for (int i = 2; i * i < N; i++)
        if (a_prime[i] == i)
            for (int j = i * i; j < N; j += i)
                a_prime[j] = i;
}
```

Listing 39: Mobius Inversion

```
//cat mobius_inversion.h | ./hash.sh
//811515
#pragma once
//mobius[i] = 0 iff there exists a prime p s.t. i%(p^2)=0
```

```
//mobius[i] = -1 iff i has an odd number of distinct prime factors
//mobius[i] = 1 iff i has an even number of distinct prime factors
const int N = 1e6 + 10;
int mobius[N];
void calc_mobius() {
    mobius[1] = 1;
    for (int i = 1; i < N; i++)
        for (int j = i + i; j < N; j += i)
            mobius[j] -= mobius[i];
}
```

Listing 40: Row Reduce

```
//cat row_reduce.h | ./hash.sh
//1d7c3e
#pragma once
//for mod inverse
#include "exp_mod.h"
//First 'cols' columns of mat represents a matrix to be left in reduced row echelon form
//Row operations will be performed to all later columns
//
//example usage:
// row_reduce(mat, mat[0].size(), mod) //row reduce matrix with no extra columns
pair<int/*rank*/, int/*determinant*/> row_reduce(vector<vector<int>>& mat, int cols, int
    ↪ mod) {
    int n = mat.size(), m = mat[0].size(), rank = 0, det = 1;
    assert(cols <= m);
    for (int col = 0; col < cols && rank < n; col++) {
        //find arbitrary pivot and swap pivot to current row
        for (int i = rank; i < n; i++)
            if (mat[i][col] != 0) {
                if (rank != i) det = det == 0 ? 0 : mod - det;
                swap(mat[i], mat[rank]);
                break;
            }
        if (mat[rank][col] == 0) {
            det = 0;
            continue;
        }
        det = (1LL * det * mat[rank][col]) % mod;
        //make pivot 1 by dividing row by inverse of pivot
        int a_inv = pow(mat[rank][col], mod - 2, mod);
        for (int j = 0; j < m; j++)
            mat[rank][j] = (1LL * mat[rank][j] * a_inv) % mod;
        //zero-out all numbers above & below pivot
        for (int i = 0; i < n; i++)
            if (i != rank && mat[i][col] != 0) {
                int val = mat[i][col];
                for (int j = 0; j < m; j++) {
                    mat[i][j] -= 1LL * mat[rank][j] * val % mod;
                    if (mat[i][j] < 0) mat[i][j] += mod;
                }
            }
        rank++;
    }
    assert(rank <= min(n, cols));
    return {rank, det};
}
```

Listing 41: Solve Linear Equations MOD

```
//cat solve_linear_mod.h | ./hash.sh
//44cc6e
#pragma once
#include "row_reduce.h"
struct matrix_info {
    int rank, det;
    vector<int> x;
};
//Solves mat * x = b under prime mod.
//mat is a n (rows) by m (cols) matrix, b is a length n column vector, x is a length m
    ↪ vector.
//assumes n,m >= 1, else RTE
//Returns rank of mat, determinant of mat, and x (solution vector to mat * x = b).
//x is empty if no solution. If rank < m, there are multiple solutions and an arbitrary
    ↪ one is returned.
//Leaves mat in reduced row echelon form (unlike kactl) with b appended.
//O(n * m * min(n,m))
matrix_info solve_linear_mod(vector<vector<int>>& mat, const vector<int>& b, int mod) {
    assert(mat.size() == b.size());
    int n = mat.size(), m = mat[0].size();
    for (int i = 0; i < n; i++)
        mat[i].push_back(b[i]);
    auto [rank, det] = row_reduce(mat, m, mod); //row reduce not including the last column
    //check if solution exists
    for (int i = rank; i < n; i++) {
        if (mat[i].back() != 0) return {rank, det, {}}; //no solution exists
    }
    //initialize solution vector ('x') from row-reduced matrix
    vector<int> x(m, 0);
    for (int i = 0, j = 0; i < rank; i++) {
        while (mat[i][j] == 0) j++; //find pivot column
        x[j] = mat[i].back();
    }
    return {rank, det, x};
}
```

Listing 42: Matrix Inverse

```
//cat matrix_inverse.h | ./hash.sh
//3056ad
#pragma once
#include "row_reduce.h"
//returns inverse of square matrix mat, empty if no inverse
vector<vector<int>> matrix_inverse(vector<vector<int>> mat/*intentional pass by value*/,
    ↪ int mod) {
    int n = mat.size();
    assert(n == (int)mat[0].size());
    //append identity matrix
    for (int i = 0; i < n; i++) {
        mat[i].resize(2 * n, 0);
        mat[i][i + n] = 1;
    }
    auto [rank, det] = row_reduce(mat, n, mod); //row reduce first n columns, leaving
    ↪ inverse in last n columns
    if (rank < n) return {}; //no inverse
    for (int i = 0; i < n; i++)
        mat[i].erase(mat[i].begin(), mat[i].begin() + n);
    return mat;
}
```


Listing 43: Euler’s Totient Phi Function

```
//cat totient.h | ./hash.sh
//36bd41
#pragma once
//Euler’s totient function counts the positive integers
//up to a given integer n that are relatively prime to n.
//
//To improve, use Pollard-rho to find prime factors
int totient(int n) {
    int res = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            while (n % i == 0) n /= i;
            res -= res / i;
        }
    }
    if (n > 1) res -= res / n;
    return res;
}
```

Listing 44: MAX FLOW

Listing 45: Dinic

```
//cat dinic.h | ./hash.sh
//33307f
#pragma once
struct max_flow {
    typedef long long ll;
    const ll INF = 1e18;
    struct edge {
        int a, b;
        ll cap, flow;
    };
    vector<edge> e;
    vector<vector<int>>> g;
    vector<int> q, d, ptr;
    max_flow(int n) : g(n), q(n), d(n), ptr(n) {}
    void add_edge(int a, int b, ll cap) {
        edge e1 = { a, b, cap, 0 };
        edge e2 = { b, a, 0, 0 };
        g[a].push_back(e1);
        e1.push_back(e2);
        g[b].push_back(e2);
        e2.push_back(e1);
    }
    ll get_flow(int s, int t) {
        ll flow = 0;
        for (;;) {
            if (!bfs(s, t)) break;
            ptr.assign(ptr.size(), 0);
            while (ll pushed = dfs(s, INF, t))
                flow += pushed;
        }
        return flow;
    }
};
```

```

    }
    bool bfs(int s, int t) {
        int qh = 0, qt = 0;
        q[qt++] = s;
        d.assign(d.size(), -1);
        d[s] = 0;
        while (qh < qt && d[t] == -1) {
            int v = q[qh++];
            for (int i = 0; i < (int)g[v].size(); i++) {
                int id = g[v][i], to = e[id].b;
                if (d[to] == -1 && e[id].flow < e[id].cap) {
                    q[qt++] = to;
                    d[to] = d[v] + 1;
                }
            }
        }
        return d[t] != -1;
    }
}
ll dfs(int v, ll flow, int t) {
    if (!flow) return 0;
    if (v == t) return flow;
    for (; ptr[v] < (int)g[v].size(); ptr[v]++) {
        int id = g[v][ptr[v]], to = e[id].b;
        if (d[to] != d[v] + 1) continue;
        ll pushed = dfs(to, min(flow, e[id].cap - e[id].flow), t);
        if (pushed) {
            e[id].flow += pushed;
            e[id ^ 1].flow -= pushed;
            return pushed;
        }
    }
    return 0;
}
};
```

Listing 46: Hungarian

```
//cat hungarian.h | ./hash.sh
//625431
#pragma once
//source: https://e-maxx.ru/algo/assignment_hungary
//
//input: cost[1...n][1...m] with 1 <= n <= m
//n workers, indexed 1, 2, ..., n
//m jobs, indexed 1, 2, ..., m
//it costs ‘cost[i][j]’ to assign worker i to job j (1<=i<=n, 1<=j<=m)
//this returns *min* total cost to assign each worker to some distinct job
//O(n^2 * m)
//
//trick 1: set ‘cost[i][j]’ to INF to say: “worker ‘i’ cannot be assigned job ‘j’”
//trick 2: ‘cost[i][j]’ can be negative, so to instead find max total cost over all
//    ⇨ matchings: set all ‘cost[i][j]’ to ‘-cost[i][j]’.
//Now max total cost = - hungarian(cost).min_cost
const long long INF = 1e18;
struct match {
    long long min_cost;
    vector<int> matching; //worker ‘i’ (1<=i<=n) is assigned to job ‘matching[i]’
    //    ⇨ (1<=matching[i]<=m)
};
match hungarian(const vector<vector<long long>>& cost) {
```

```
int n = cost.size() - 1, m = cost[0].size() - 1;
assert(n <= m);
vector<int> p(m + 1), way(m + 1);
vector<long long> u(n + 1), v(m + 1);
for (int i = 1; i <= n; i++) {
    p[0] = i;
    int j0 = 0;
    vector<long long> minv(m + 1, INF);
    vector<bool> used(m + 1, 0);
    do {
        used[j0] = 1;
        int i0 = p[j0], j1 = 0;
        long long delta = INF;
        for (int j = 1; j <= m; j++)
            if (!used[j]) {
                long long cur = cost[i0][j] - u[i0] - v[j];
                if (cur < minv[j])
                    minv[j] = cur, way[j] = j0;
                if (minv[j] < delta)
                    delta = minv[j], j1 = j;
            }
        for (int j = 0; j <= m; j++)
            if (used[j])
                u[p[j]] += delta, v[j] -= delta;
            else
                minv[j] -= delta;
        j0 = j1;
    } while (p[j0] != 0);
    do {
        int j1 = way[j0];
        p[j0] = p[j1];
        j0 = j1;
    } while (j0);
}
vector<int> ans(n + 1);
for (int j = 1; j <= m; j++)
    ans[p[j]] = j;
return {-v[0], ans};
}
```

Listing 47: Min Cost Max Flow

```
//cat min_cost_max_flow.h | ./hash.sh
//a88ec1
#pragma once
const long long INF = 1e18;
struct min_cost_max_flow {
    typedef long long ll;
    struct edge {
        int a, b;
        ll cap, cost, flow;
        int back;
    };
    const int N;
    vector<edge> e;
    vector<vector<int>> g;
    min_cost_max_flow(int a_n) : N(a_n), g(N) {}
    void add_edge(int a, int b, ll cap, ll cost) {
        edge e1 = {a, b, cap, cost, 0, (int)g[b].size() };
        edge e2 = {b, a, 0, -cost, 0, (int)g[a].size() };
    }
};
```

```
g[a].push_back(e.size());
e.push_back(e1);
g[b].push_back(e.size());
e.push_back(e2);
}
//returns minimum cost to send 'total_flow' flow through the graph, or -1 if
↳ impossible
ll get_flow(int s, int t, ll total_flow) {
    ll flow = 0, cost = 0;
    while (flow < total_flow) {
        vector<ll> d(N, INF);
        vector<int> p_edge(N), id(N, 0), q(N), p(N);
        int qh = 0, qt = 0;
        q[qt++] = s;
        d[s] = 0;
        while (qh != qt) {
            int v = q[qh++];
            id[v] = 2;
            if (qh == N) qh = 0;
            for (int i = 0; i < (int)g[v].size(); i++) {
                const edge& r = e[g[v][i]];
                if (r.flow < r.cap && d[v] + r.cost < d[r.b]) {
                    d[r.b] = d[v] + r.cost;
                    if (id[r.b] == 0) {
                        q[qt++] = r.b;
                        if (qt == N) qt = 0;
                    } else if (id[r.b] == 2) {
                        if (--qh == -1) qh = N - 1;
                        q[qh] = r.b;
                    }
                    id[r.b] = 1;
                    p[r.b] = v;
                    p_edge[r.b] = i;
                }
            }
        }
        if (d[t] == INF) break;
        ll addflow = total_flow - flow;
        for (int v = t; v != s; v = p[v]) {
            int pv = p[v], pr = p_edge[v];
            addflow = min(addflow, e[g[pv][pr]].cap - e[g[pv][pr]].flow);
        }
        for (int v = t; v != s; v = p[v]) {
            int pv = p[v], pr = p_edge[v], r = e[g[pv][pr]].back;
            e[g[pv][pr]].flow += addflow;
            e[g[v][r]].flow -= addflow;
            cost += e[g[pv][pr]].cost * addflow;
        }
        flow += addflow;
    }
    return flow < total_flow ? -1 : cost;
}
};
```

Listing 48: MISC

Listing 49: PBDS

```
//cat policy_based_data_structures.h | ./hash.sh
//807de9
#pragma once
//place these includes *before* the '#define int long long' else compile error
//not using <bits/extc++.h> as it compile errors on codeforces c++20 compiler
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
//BST with extra functions https://codeforces.com/blog/entry/11080
//order_of_key - # of elements *strictly* less than given element
//find_by_order - find kth largest element, k is 0 based so find_by_order(0) returns min
    ↪ element
template<class T> using indexed_set = tree<T, null_type, less<T>, rb_tree_tag,
    ↪ tree_order_statistics_node_update>;
//example initialization:
indexed_set<pair<long long, int>> is;
//hash table (apparently faster than unordered_map):
    ↪ https://codeforces.com/blog/entry/60737
//example initialization:
gp_hash_table<string, long long> ht;
```

Listing 50: Monotonic Stack

```
//cat monotonic_stack.h | ./hash.sh
//90f107
#pragma once
//calculates array 'left' with:
//for every index j with left[i] < j < i: arr[j] > arr[i]
//and
//arr[left[i]] <= arr[i] if left[i] != -1
//
//trick: pass in vector<pair<T/*value*/, int/*index*/>> with arr[i].second = i (0<=i<n)
    ↪ to simulate arr[j] >= arr[i]
//
//O(n)
template<class T> vector<int> monotonic_stack(const vector<T>& arr) {
    int n = arr.size();
    vector<int> left(n);
    for (int i = 0; i < n; i++) {
        int& j = left[i] = i - 1;
        while (j >= 0 && arr[j] > arr[i]) j = left[j];
    }
    return left;
}
```

Listing 51: Count Rectangles

```
//cat count_rectangles.h | ./hash.sh
//9873d2
#pragma once
#include "monotonic_stack.h"
//given a 2D boolean matrix, calculate cnt[i][j]
//cnt[i][j] = the number of times an i-by-j rectangle appears in the matrix such that
    ↪ all i*j cells in the rectangle are 1
//Note cnt[0][j] and cnt[i][0] will contain garbage values
//O(n*m)
vector<vector<int>> count_rectangles(const vector<vector<bool>>& grid) {
    int n = grid.size(), m = grid[0].size();
    vector<vector<int>> cnt(n + 1, vector<int>(m + 1, 0));
```

```
vector<int> arr(m, 0);
auto rv /*reverse*/ = [&](int j) -> int {
    return m - 1 - j;
};
for (int i = 0; i < n; i++) {
    vector<pair<int, int>> arr_rev(m);
    for (int j = 0; j < m; j++) {
        arr[j] = grid[i][j] * (arr[j] + 1);
        arr_rev[rv(j)] = {arr[j], j};
    }
    vector<int> left = monotonic_stack(arr);
    vector<int> right = monotonic_stack(arr_rev);
    for (int j = 0; j < m; j++) {
        int l = j - left[j] - 1, r = rv(right[rv(j)]) - j - 1;
        cnt[arr[j]][l + r + 1]++;
        cnt[arr[j]][l]--;
        cnt[arr[j]][r]--;
    }
}
for (int i = 1; i <= n; i++)
    for (int k = 0; k < 2; k++)
        for (int j = m; j > 1; j--)
            cnt[i][j - 1] += cnt[i][j];
for (int j = 1; j <= m; j++)
    for (int i = n; i > 1; i--)
        cnt[i - 1][j] += cnt[i][j];
return cnt;
}
```

Listing 52: LIS

```
//cat lis.h | ./hash.sh
//a243e1
#pragma once
//returns array of indexes representing the longest *strictly* increasing subsequence
//for non-decreasing: pass in a vector<pair<T, int>> with arr[i].second = i (0<=i<n)
//alternatively, there's this https://codeforces.com/blog/entry/13225
//mnemonic: Longest Increasing Subsequence
//NOLINTNEXTLINE(readability-identifier-naming)
template<class T> vector<int> LIS(const vector<T>& arr) {
    if (arr.empty()) return {};
    vector<int> dp{0}/*array of indexes into 'arr'*/, prev(arr.size(), -1);
    for (int i = 1; i < (int)arr.size(); i++) {
        auto it = lower_bound(dp.begin(), dp.end(), i, [&](int x, int y) -> bool {
            return arr[x] < arr[y];
        });
        if (it == dp.end()) {
            prev[i] = dp.back();
            dp.push_back(i);
        } else {
            prev[i] = it == dp.begin() ? -1 : *(it - 1);
            *it = i;
        }
    }
    //here, dp.size() = length of LIS of prefix of arr ending at index i
}
vector<int> res(dp.size());
for (int i = dp.back(), j = dp.size(); i != -1; i = prev[i])
    res[--j] = i;
return res;
}
```

Listing 53: Number of Distinct Subsequences DP

```
//cat num_distinct_subsequences.h | ./hash.sh
//9542f5
#pragma once
//returns number of distinct subsequences
//the empty subsequence is counted
int num_subsequences(const vector<int>& arr, int mod) {
    int n = arr.size();
    vector<int> dp(n + 1, 1);
    map<int, int> last;
    for (int i = 0; i < n; i++) {
        int& curr = dp[i + 1] = 2 * dp[i];
        if (curr >= mod) curr -= mod;
        auto it = last.find(arr[i]);
        if (it != last.end()) {
            curr -= dp[it->second];
            if (curr < 0) curr += mod;
            it->second = i;
        } else last[arr[i]] = i;
    }
    return dp[n];
}
```

Listing 54: Safe Hash

```
//cat safe_hash.h | ./hash.sh
//d9ea53
#pragma once
//source: https://codeforces.com/blog/entry/62393
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM =
            chrono::steady_clock::now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};
//usage:
unordered_map<long long, int, custom_hash> safe_map;
#include "policy_based_data_structures.h"
gp_hash_table<long long, int, custom_hash> safe_hash_table;
```