

Listings

1	CODE HASHES	2	39	Prime Sieve Mobius	16
2	hash.sh	2	40	Row Reduce	17
3	GRAPHS	2	41	Solve Linear Equations MOD	17
4	Bridges and Cuts	2	42	Matrix Inverse	17
5	Block Vertex Tree	2	43	Euler’s Totient Phi Function	18
6	Centroid	3	44	MAX FLOW	18
7	Dijkstra	3	45	Dinic	18
8	Floyd Warshall	4	46	Hungarian	18
9	HLD	4	47	Min Cost Max Flow	19
10	Hopcroft Karp	4	48	MISC	20
11	LCA	5	49	Disjoint Set	20
12	SCC	6	50	PBDS	20
13	RANGE DATA STRUCTURES	6	51	Monotonic Stack	20
14	Segment Tree	6	52	Count Rectangles	20
15	Fenwick Tree	7	53	Longest Increasing Subsequence	21
16	Sparse Table	7	54	Safe Hash	21
17	Implicit Lazy Segment Tree	7			
18	Range Updates, Point Queries	8			
19	Kth Smallest	8			
20	Number Distinct Elements	9			
21	Buckets	9			
22	Persistent Lazy Segment Tree	10			
23	Merge Sort Tree	11			
24	STRINGS	11			
25	Suffix Array	11			
26	Longest Common Prefix Array	12			
27	Prefix Function	13			
28	KMP	13			
29	Trie	13			
30	Binary Trie	14			
31	Longest Common Prefix Query	14			
32	MATH	15			
33	BIN EXP MOD	15			
34	Fibonacci	15			
35	Matrix Mult and Pow	15			
36	N Choose K MOD	15			
37	Partitions	16			
38	Derangements	16			

Listing 1: CODE HASHES

Listing 2: hash.sh

```
# Hashes a file, ignoring all whitespace, comments, and includes. Use for
# verifying that code was correctly typed.

# usage:
#   chmod u+x hash.sh
#   cat <file> | ./hash.sh
# or just copy this command:
#   cat <file> | sed -r '/^#(include|pragma)/d' | cpp -fpreprocessed -P | tr -d
#       ↳ '[:space:]' | md5sum | cut -c-6
sed -r '/^#(include|pragma)/d' | cpp -fpreprocessed -P | tr -d '[:space:]' | md5sum |
    ↳ cut -c-6
```

Listing 3: GRAPHS

Listing 4: Bridges and Cuts

```
//cat bridges_and_cuts.h | ./hash.sh
//3c13d9
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/biconnected_components,
    ↳ https://judge.yosupo.jp/problem/two_edge_connected_components
//with asserts checking correctness of is_bridge and is_cut
//O(n+m) time & space
//2 edge cc and bcc stuff doesn't depend on each other, so delete whatever is not needed
//handles multiple edges
//example initialization of 'adj':
//for (int i = 0; i < m; i++) {
//    int u, v;
//    cin >> u >> v;
//    u--, v--;
//    adj[u].emplace_back(v, i);
//    adj[v].emplace_back(u, i);
//}
struct info {
    //2 edge connected component stuff (e.g. components split by bridge edges)
    ↳ https://cp-algorithms.com/graph/bridge-searching.html
    int num_2_edge_ccs;
    vector<bool> is_bridge; //edge id -> true iff bridge edge
    vector<int> two_edge_ccid; //node -> ID of 2-edge component (which are labeled 0, 1,
        ↳ ..., 'num_2_edge_ccs'-1)
    //bi-connected component stuff (e.g. components split by cut/articulation nodes)
    ↳ https://cp-algorithms.com/graph/cutpoints.html
    int num_bccs;
    vector<bool> is_cut; //node -> true iff cut node
    vector<int> bcc_id; //edge id -> ID of BCC (which are labeled 0, 1, ..., 'num_bccs'-1)
};
info bridge_and_cut(const vector<vector<pair<int/*neighbor*/, int/*edge id*/>>>&
    ↳ adj/*undirected graph*/, int m/*number of edges*/) {
    //stuff for both (always keep)
    int n = adj.size(), timer = 1;
    vector<int> tin(n, 0);
    //2 edge CC stuff (delete if not needed)
    int num_2_edge_ccs = 0;
```

```
vector<bool> is_bridge(m, false);
vector<int> two_edge_ccid(n), node_stack;
//BCC stuff (delete if not needed)
int num_bccs = 0;
vector<bool> is_cut(n, false);
vector<int> bcc_id(m), edge_stack;
auto dfs = [&](auto self, int v, int p_id) -> int {
    int low = tin[v] = timer++;
    int deg = 0;
    node_stack.push_back(v);
    for (auto [to, e_id] : adj[v]) {
        if (e_id == p_id) continue;
        if (!tin[to]) {
            edge_stack.push_back(e_id);
            int low_ch = self(self, to, e_id);
            if (low_ch >= tin[v]) {
                is_cut[v] = true;
                while (true) {
                    int edge = edge_stack.back();
                    edge_stack.pop_back();
                    bcc_id[edge] = num_bccs;
                    if (edge == e_id) break;
                }
                num_bccs++;
            }
            low = min(low, low_ch);
            deg++;
        } else if (tin[to] < tin[v]) {
            edge_stack.push_back(e_id);
            low = min(low, tin[to]);
        }
    }
    if (p_id == -1) is_cut[v] = (deg > 1);
    if (tin[v] == low) {
        if (p_id != -1) is_bridge[p_id] = true;
        while (true) {
            int node = node_stack.back();
            node_stack.pop_back();
            two_edge_ccid[node] = num_2_edge_ccs;
            if (node == v) break;
        }
        num_2_edge_ccs++;
    }
    return low;
};
for (int i = 0; i < n; i++) {
    if (!tin[i])
        dfs(dfs, i, -1);
}
return {num_2_edge_ccs, is_bridge, two_edge_ccid, num_bccs, is_cut, bcc_id};
}
```

Listing 5: Block Vertex Tree

```
//cat block_vertex_tree.h | ./hash.sh
//567ff1
#pragma once
#include "bridges_and_cuts.h"
//library checker tests: https://judge.yosupo.jp/problem/biconnected_components
//(asserts checking correctness of commented-example-usage-loops)
```

```
//returns adjacency list of block vertex tree
//usage:
// info cc = bridge_and_cut(adj, m);
// vector<vector<int>> bvt = block_vertex_tree(adj, cc);
//to loop over each *unique* BCC containing a node i:
// for(int bccid : bvt[i]) {
//     bccid -= n;
//     ...
// }
//to loop over each *unique* node inside a BCC:
// for(int i : bvt[bccid + n]) {
//     ...
// }
vector<vector<int>> block_vertex_tree(const vector<vector<pair<int, int>>>& adj, const
    ↪ info& cc) {
    int n = adj.size();
    vector<vector<int>> tree(n + cc.num_bccs);
    vector<int> cnt(cc.num_bccs, 0);
    for (int i = 0; i < n; i++) {
        for (auto [_, e_id] : adj[i]) {
            int bcc = cc.bcc_id[e_id];
            if (cnt[bcc]++ == 0) {
                tree[i].push_back(bcc + n); // Add edge between original node, and BCC
                ↪ node
                tree[bcc + n].push_back(i);
            }
        }
        for (auto [_, e_id] : adj[i])
            cnt[cc.bcc_id[e_id]]--;
    }
    return tree;
}
```

Listing 6: Centroid

```
//cat centroid.h | ./hash.sh
//4ba5e4
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/frequency_table_of_tree_distance
//with asserts checking depth of tree <= log2(n)
//returns array 'par' where 'par[i]' = parent of node 'i' in centroid tree
//'par[root]' is -1
//0-based nodes
//O(n log n)
//example usage:
// vector<int> parent = get_centroid_tree(adj);
// vector<vector<int>> childs(n);
// int root;
// for (int i = 0; i < n; i++) {
//     if (parent[i] == -1)
//         root = i;
//     else
//         childs[parent[i]].push_back(i);
// }
vector<int> get_centroid_tree(const vector<vector<int>>& adj /*unrooted tree*/) {
    int n = adj.size();
    vector<int> sizes(n);
    vector<bool> vis(n, false);
    auto dfs_sz = [&](auto self, int node, int par) -> void {
        sizes[node] = 1;
```

```
        for (int to : adj[node]) {
            if (to != par && !vis[to]) {
                self(self, to, node);
                sizes[node] += sizes[to];
            }
        }
    };
    auto find_centroid = [&](int node) -> int {
        dfs_sz(dfs_sz, node, node);
        int size_cap = sizes[node] / 2, par = -1;
        while (true) {
            bool found = false;
            for (int to : adj[node]) {
                if (to != par && !vis[to] && sizes[to] > size_cap) {
                    found = true;
                    par = node;
                    node = to;
                    break;
                }
            }
            if (!found) return node;
        }
    };
    vector<int> parent(n);
    auto dfs = [&](auto self, int node, int par) -> void {
        node = find_centroid(node);
        parent[node] = par;
        vis[node] = true;
        for (int to : adj[node]) {
            if (!vis[to])
                self(self, to, node);
        }
    };
    dfs(dfs, 0, -1);
    return parent;
}
```

Listing 7: Dijkstra

```
//cat dijkstra.h | ./hash.sh
//6b6195
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/shortest_path
//returns array 'len' where 'len[i]' = shortest path from node 'startNode' to node i
//For example len[startNode] will always = 0
const long long inf = 1e18;
vector<long long> dijkstra(const vector<vector<pair<int, long long>>>& adj /*directed or
    ↪ undirected, weighted graph*/, int v) {
    vector<long long> len(adj.size(), inf);
    len[v] = 0;
    set<pair<long long /*weight*/, int /*node*/>> q;
    q.insert({0LL, v});
    while (!q.empty()) {
        auto it = q.begin();
        int node = it->second;
        q.erase(it);
        for (auto [to, weight] : adj[node])
            if (len[to] > weight + len[node]) {
                q.erase({len[to], to});
                len[to] = weight + len[node];
            }
    }
}
```

```
        q.insert({len[to], to});
    }
    return len;
}
```

Listing 8: Floyd Warshall

```
//cat floyd_warshall.h | ./hash.sh
//84799a
#pragma once
//status: not tested
/**for directed graphs only** if you initialize len[i][i] to infinity, then
//afterward floyds, len[i][i] = length of shortest cycle including node 'i'
//
//another trick: change 'len' to 2d array of *bools* where len[i][j] = true if
//there exists an edge from i -> j in initial graph. Also do:
//'len[i][j] != len[i][k] & len[k][j]'
//Then after floyds, len[i][j] = true iff there's exists some path from node
//'i' to node 'j'
//
//Changing the order of for-loops to i-j-k (instead of the current k-i-j)
//results in min-plus matrix multiplication. If adjacency matrix is M, then
//after computing M^k (with binary exponentiation), M[i][j] = min length path
//from i to j with at most k edges.
for (int k = 0; k < n; k++)
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            len[i][j] = min(len[i][j], len[i][k] + len[k][j]);
```

Listing 9: HLD

```
//cat hld.h | ./hash.sh
//103dab
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/lca,
//    https://judge.yosupo.jp/problem/vertex_add_path_sum,
//    https://judge.yosupo.jp/problem/vertex_add_subtree_sum
//source: https://codeforces.com/blog/entry/53170
//assumes a single tree, 1-based nodes is possible by passing in 'root' in range [1, n]
struct HLD { //NOLINT(readability-identifier-naming)
    int n;
    vector<int> sub_sz, par, time_in, next;
    HLD(vector<vector<int>>& adj /*single unrooted tree*/, int root) :
        n(adj.size()), sub_sz(n, 1), par(n, root), time_in(n), next(n, root) {
        dfs1(root, adj);
        int timer = 0;
        dfs2(root, adj, timer);
    }
    void dfs1(int node, vector<vector<int>>& adj) {
        for (int& to : adj[node]) {
            if (to == par[node]) continue;
            par[to] = node;
            dfs1(to, adj);
            sub_sz[node] += sub_sz[to];
            if (sub_sz[to] > sub_sz[adj[node][0]] || adj[node][0] == par[node])
                swap(to, adj[node][0]);
        }
    }
}
```

```
void dfs2(int node, const vector<vector<int>>& adj, int& timer) {
    time_in[node] = timer++;
    for (int to : adj[node]) {
        if (to == par[node]) continue;
        next[to] = (timer == time_in[node] + 1 ? next[node] : to);
        dfs2(to, adj, timer);
    }
}
// Returns intervals (of time_in's) corresponding to the path between u and v, not
//    necessarily in order
// This can answer queries for "is some node 'x' on some path" by checking if the
//    time_in[x] is in any of these intervals
vector<pair<int, int>> path(int u, int v) const {
    vector<pair<int, int>> res;
    for (; v = par[next[v]]; ) {
        if (time_in[v] < time_in[u]) swap(u, v);
        if (time_in[next[v]] <= time_in[u]) {
            res.emplace_back(time_in[u], time_in[v]);
            return res;
        }
        res.emplace_back(time_in[next[v]], time_in[v]);
    }
}
// Returns interval (of time_in's) corresponding to the subtree of node i
// This can answer queries for "is some node 'x' in some other node's subtree" by
//    checking if time_in[x] is in this interval
pair<int, int> subtree(int i) const {
    return {time_in[i], time_in[i] + sub_sz[i] - 1};
}
// Returns lca of nodes u and v
int lca(int u, int v) const {
    for (; v = par[next[v]]; ) {
        if (time_in[v] < time_in[u]) swap(u, v);
        if (time_in[next[v]] <= time_in[u]) return u;
    }
}
};
```

Listing 10: Hopcroft Karp

```
//cat hopcroft_karp.h | ./hash.sh
//e42443
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/bipartitematching
//with asserts checking correctness of min vertex cover
//Modified from
//    https://github.com/foreverbell/acm-icpc-cheat-sheet/blob/master/src/graph-algorithms/
//Worst case O(E*sqrt(V)) but faster in practice
struct match {
    //# of edges in matching (which = size of min vertex cover by öKnig's theorem)
    int size_of_matching;
    //an arbitrary max matching is found. For this matching:
    //if match_l[nodeLeft] == -1:
    //    'nodeLeft' is not in matching
    //else:
    //    the edge 'nodeLeft' <=> match_l[nodeLeft] is in the matching
    //
    //similarly for match_r with edge match_r[nodeRight] <=> nodeRight in matching if
    //    match_r[nodeRight] != -1
    //matchings stored in match_l and match_r are the same matching
```

```

//provides way to check if any node is in matching
vector<int> match_l, match_r;
//an arbitrary min vertex cover is found. For this MVC: mvc_l['left node'] is true
    ⇨ iff 'left node' is in the min vertex cover (same for mvc_r)
//if mvc_l['left node'] is false, then 'left node' is in the corresponding maximal
    ⇨ independent set
vector<bool> mvc_l, mvc_r;
};
//Think of the bipartite graph as having a left side (with size l_sz) and a right side
    ⇨ (with size r_sz).
//Nodes on left side are indexed 0,1,...,l_sz-1
//Nodes on right side are indexed 0,1,...,r_sz-1
//
//'adj' is like a directed adjacency list containing edges from left side -> right side:
//To initialize 'adj': For every edge nodeLeft <=> nodeRight, do:
    ⇨ adj[nodeLeft].push_back(nodeRight)
match hopcroft_karp(const vector<vector<int>>& adj/*bipartite graph*/, int r_sz/*number
    ⇨ of nodes on right side*/) {
    int size_of_matching = 0, l_sz = adj.size();
    vector<int> match_l(l_sz, -1), match_r(r_sz, -1);
    while (true) {
        queue<int> q;
        vector<int> level(l_sz, -1);
        for (int i = 0; i < l_sz; i++) {
            if (match_l[i] == -1) level[i] = 0, q.push(i);
        }
        bool found = false;
        vector<bool> mvc_l(l_sz, true), mvc_r(r_sz, false);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            mvc_l[u] = false;
            for (int x : adj[u]) {
                mvc_r[x] = true;
                int v = match_r[x];
                found |= v == -1;
                if (v != -1 && level[v] < 0) {
                    level[v] = level[u] + 1;
                    q.push(v);
                }
            }
        }
        if (!found) return {size_of_matching, match_l, match_r, mvc_l, mvc_r};
        auto dfs = [&](auto self, int u) -> bool {
            for (int x : adj[u]) {
                int v = match_r[x];
                if (v == -1 || (level[u] + 1 == level[v] && self(self, v))) {
                    match_l[u] = x;
                    match_r[x] = u;
                    return true;
                }
            }
            level[u] = 1e9; //acts as visited array
            return false;
        };
        for (int i = 0; i < l_sz; i++)
            size_of_matching += (match_l[i] == -1 && dfs(dfs, i));
    }
}

```

Listing 11: LCA

```

//cat lca.h | ./hash.sh
//90ab04
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/lca
//https://codeforces.com/blog/entry/74847
//assumes a single tree, 1-based nodes is possible by passing in 'root' in range [1, n]
struct LCA { //NOLINT(readability-identifier-naming)
    int n;
    vector<int> jmp, jmp_edges, par, depth;
    vector<long long> dist;
    LCA(const vector<vector<pair<int, long long>>>& adj, int root) :
        n(adj.size()), jmp(n, root), jmp_edges(n, 1), par(n, root), depth(n, 0), dist(n,
            ⇨ 0LL) {
        dfs(root, adj);
    }
    void dfs(int node, const vector<vector<pair<int, long long>>>& adj) {
        for (auto [ch, w] : adj[node]) {
            if (ch == par[node]) continue;
            par[ch] = node;
            depth[ch] = 1 + depth[node];
            dist[ch] = w + dist[node];
            if (depth[node] > 0 && jmp_edges[node] == jmp_edges[jmp[node]])
                jmp[ch] = jmp[jmp[node]], jmp_edges[ch] = 2 * jmp_edges[node] + 1;
            else
                jmp[ch] = node;
            dfs(ch, adj);
        }
    }
    //traverse up k edges in O(log(k)). So with k=1 this returns 'node's parent
    int kth_par(int node, int k) const {
        k = min(k, depth[node]);
        while (k > 0) {
            if (jmp_edges[node] <= k) {
                k -= jmp_edges[node];
                node = jmp[node];
            } else {
                k--;
                node = par[node];
            }
        }
        return node;
    }
    int get_lca(int x, int y) const {
        if (depth[x] < depth[y]) swap(x, y);
        x = kth_par(x, depth[x] - depth[y]);
        while (x != y) {
            if (jmp[x] != jmp[y])
                x = jmp[x], y = jmp[y];
            else
                x = par[x], y = par[y];
        }
        return x;
    }
    int dist_edges(int x, int y) const {
        return depth[x] + depth[y] - 2 * depth[get_lca(x, y)];
    }
    long long dist_weight(int x, int y) const {
        return dist[x] + dist[y] - 2 * dist[get_lca(x, y)];
    }
}

```

```
};
```

Listing 12: SCC

```
//cat scc.h | ./hash.sh
//8fa337
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/scc
struct scc_info {
    int num_sccs;
    //scc's are labeled 0,1,...,'numSCCs-1'
    //scc_id[i] is the id of the scc containing node 'i'
    //for each edge i -> j: scc_id[i] >= scc_id[j]
    vector<int> scc_id;
};
scc_info SCC(const vector<vector<int>>& adj /*directed, unweighted graph*/) {
    ↪ //NOLINT(readability-identifier-naming)
    int n = adj.size(), timer = 1, num_sccs = 0;
    vector<int> tin(n, 0), scc_id(n, -1), node_stack;
    auto dfs = [&](auto self, int v) -> int {
        int low = tin[v] = timer++;
        node_stack.push_back(v);
        for (int to : adj[v]) {
            if (scc_id[to] < 0)
                low = min(low, tin[to] ? tin[to] : self(self, to));
        }
        if (tin[v] == low) {
            while (true) {
                int node = node_stack.back();
                node_stack.pop_back();
                scc_id[node] = num_sccs;
                if (node == v) break;
            }
            num_sccs++;
        }
        return low;
    };
    for (int i = 0; i < n; i++) {
        if (!tin[i])
            dfs(dfs, i);
    }
    return {num_sccs, scc_id};
}
```

Listing 13: RANGE DATA STRUCTURES

Listing 14: Segment Tree

```
//cat seg_tree.h | ./hash.sh
//97e591
#pragma once
//stress tests: tests/stress_tests/range_data_structures/seg_tree.cpp
const long long inf = 1e18;
struct seg_tree {
    struct node {
        long long sum, mx, mn;
        long long lazy;
```

```
int l, r;
int len() const {
    return r - l + 1;
}
//returns 1 + (# of nodes in left child's subtree)
//https://cp-algorithms.com/data_structures/segment_tree.html#memory-efficient-implementation
int r_ch() const {
    return ((r - l) & ~1) + 2;
}
};
vector<node> tree;
//There's no constructor 'segTree(int size)' because how to initialize l,r in nodes
    ↪ without calling build?
//the whole point of 'segTree(int size)' was to be simpler by not calling build
seg_tree(const vector<long long>& arr) : tree(2 * (int)arr.size() - 1) {
    build(arr, 0, 0, (int)arr.size() - 1);
}
void build(const vector<long long>& arr, int v, int tl, int tr) {
    if (tl == tr) {
        tree[v] = {
            arr[tl],
            arr[tl],
            arr[tl],
            0,
            tl,
            tr
        };
    } else {
        int tm = tl + (tr - tl) / 2;
        build(arr, v + 1, tl, tm);
        build(arr, v + 2 * (tm - tl + 1), tm + 1, tr);
        tree[v] = combine(tree[v + 1], tree[v + 2 * (tm - tl + 1)]);
    }
}
static node combine(const node& l, const node& r) {
    return {
        l.sum + r.sum,
        max(l.mx, r.mx),
        min(l.mn, r.mn),
        0,
        l.l,
        r.r
    };
}
//what happens when 'add' is applied to every index in range [tree[v].l, tree[v].r]?
void apply(int v, long long add) {
    tree[v].sum += tree[v].len() * add;
    tree[v].mx += add;
    tree[v].mn += add;
    if (tree[v].len() > 1) {
        tree[v + 1].lazy += add;
        tree[v + tree[v].r_ch()].lazy += add;
    }
}
void push(int v) {
    if (tree[v].lazy) {
        apply(v, tree[v].lazy);
        tree[v].lazy = 0;
    }
}
//update range [l,r] with 'add'
```

```
void update(int l, int r, long long add) {
    update(0, l, r, add);
}
void update(int v, int l, int r, long long add) {
    push(v);
    if (tree[v].r < l || r < tree[v].l)
        return;
    if (l <= tree[v].l && tree[v].r <= r)
        return apply(v, add);
    update(v + 1, l, r, add);
    update(v + tree[v].r_ch(), l, r, add);
    tree[v] = combine(tree[v + 1], tree[v + tree[v].r_ch()]);
}
//range [l,r]
node query(int l, int r) {
    return query(0, l, r);
}
node query(int v, int l, int r) {
    if (tree[v].r < l || r < tree[v].l)
        return {0, -inf, inf, 0, 0, 0};
    push(v);
    if (l <= tree[v].l && tree[v].r <= r)
        return tree[v];
    return combine(query(v + 1, l, r),
        query(v + tree[v].r_ch(), l, r));
}
};
```

Listing 15: Fenwick Tree

```
//cat bit.h | ./hash.sh
//516197
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/point_add_range_sum,
    ↪ https://judge.yosupo.jp/problem/vertex_add_path_sum,
    ↪ https://judge.yosupo.jp/problem/vertex_add_subtree_sum,
    ↪ https://judge.yosupo.jp/problem/predecessor_problem
template<class T>
struct BIT { //NOLINT(readability-identifier-naming)
    vector<T> bit;
    BIT(int n) : bit(n, 0) {}
    BIT(const vector<T>& a) : bit(a.size()) {
        if (a.empty()) return;
        bit[0] = a[0];
        for (int i = 1; i < (int)a.size(); i++)
            bit[i] = bit[i - 1] + a[i];
        for (int i = (int)a.size() - 1; i > 0; i--) {
            int lower_i = (i & (i + 1)) - 1;
            if (lower_i >= 0)
                bit[i] -= bit[lower_i];
        }
    }
    void update(int idx, const T& d) {
        for (; idx < (int)bit.size(); idx = idx | (idx + 1))
            bit[idx] += d;
    }
    T sum(int r) const {
        T ret = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret += bit[r];
    }
};
```

```
return ret;
}
T sum(int l, int r) const {
    return sum(r) - sum(l - 1);
}
//Returns min pos such that sum of [0, pos] >= sum
//Returns bit.size() if no sum is >= sum, or -1 if empty sum is.
//Doesn't work with negatives (since it's greedy), counterexample: array: {1, -1},
    ↪ sum: 1, this returns 2, but should return 0
int lower_bound(T sum) const {
    if (sum <= 0) return -1;
    int pos = 0;
    for (int pw = 1 << (31 - __builtin_clz(bit.size() | 1)); pw; pw >>= 1) {
        if (pos + pw <= (int)bit.size() && bit[pos + pw - 1] < sum)
            pos += pw, sum -= bit[pos - 1];
    }
    return pos;
}
};
```

Listing 16: Sparse Table

```
//cat rmq.h | ./hash.sh
//dfa815
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/staticrmq,
    ↪ https://judge.yosupo.jp/problem/zalgorithm,
    ↪ https://judge.yosupo.jp/problem/enumerate_palindromes,
    ↪ https://judge.yosupo.jp/problem/cartesian_tree
//usage:
// vector<long long> arr;
// ...
// sparseTable<long long> st(arr, [](auto x, auto y) { return min(x,y); });
//
//to also get index of min element, do:
// sparseTable<pair<long long,int>> st(arr, [](auto x, auto y) { return min(x,y); });
//and initialize 'second's to index. If there are multiple indexes of min element,
//it'll return the smallest (left-most) one
template <class T>
struct RMQ { //NOLINT(readability-identifier-naming)
    vector<vector<T>> dp;
    function<T(const T&, const T&)> func;
    RMQ(const vector<T>& arr, const function<T(const T&, const T&)>& a_func) : dp(1,
        ↪ arr), func(a_func) {
        int n = arr.size();
        for (int pw = 1, k = 1; pw * 2 <= n; pw *= 2, k++) {
            dp.emplace_back(n - pw * 2 + 1);
            for (int j = 0; j < (int)dp[k].size(); j++)
                dp[k][j] = func(dp[k - 1][j], dp[k - 1][j + pw]);
        }
    }
    //inclusive range [l, r]
    T query(int l, int r) const {
        int lg = 31 - __builtin_clz(r - l + 1);
        return func(dp[lg][l], dp[lg][r - (1 << lg) + 1]);
    }
};
```

Listing 17: Implicit Lazy Segment Tree


```
//cat implicit_seg_tree.h | ./hash.sh
//f7b8f3
#pragma once
//stress tests: tests/stress_tests/range_data_structures/implicit_seg_tree.cpp
//see TODO for lines of code which usually need to change (not a complete list)
const int sz = 1.5e7; //TODO
struct node {
    long long val; //could represent max, sum, etc
    long long lazy;
    int l_ch, r_ch; // children, indexes into 'tree', -1 for null
} tree[sz];
struct implicit_seg_tree {
    int ptr, root_l, root_r; // [root_l, root_r] defines range of root node; handles
    ↪ negatives
    implicit_seg_tree(int l, int r) : ptr(0), root_l(l), root_r(r) {
        tree[ptr++] = {0, 0, -1, -1}; //TODO
    }
    static long long combine(long long val_l, long long val_r) {
        return val_l + val_r; //TODO
    }
    void apply(int v, int tl, int tr, long long add) {
        tree[v].val += (tr - tl + 1) * add; //TODO
        if (tl != tr) {
            tree[tree[v].l_ch].lazy += add; //TODO
            tree[tree[v].r_ch].lazy += add;
        }
    }
    void push(int v, int tl, int tr) {
        if (tl != tr && tree[v].l_ch == -1) {
            assert(ptr + 1 < sz);
            tree[v].l_ch = ptr;
            tree[ptr++] = {0, 0, -1, -1}; //TODO
            tree[v].r_ch = ptr;
            tree[ptr++] = {0, 0, -1, -1};
        }
        if (tree[v].lazy) {
            apply(v, tl, tr, tree[v].lazy);
            tree[v].lazy = 0;
        }
    }
    //update range [l,r] with 'add'
    void update(int l, int r, long long add) {
        update(0, root_l, root_r, l, r, add);
    }
    void update(int v, int tl, int tr, int l, int r, long long add) {
        push(v, tl, tr);
        if (tr < l || r < tl)
            return;
        if (l <= tl && tr <= r)
            return apply(v, tl, tr, add);
        int tm = tl + (tr - tl) / 2;
        update(tree[v].l_ch, tl, tm, l, r, add);
        update(tree[v].r_ch, tm + 1, tr, l, r, add);
        tree[v].val = combine(tree[tree[v].l_ch].val, tree[tree[v].r_ch].val);
    }
    //query range [l,r]
    //for more complicated query which doesn't allocate new nodes, see:
    //https://github.com/lrvidickis/Programming-Team-Code/blob/dc659297850440b65af2550a834cc42af88320554int roots;
    long long query(int l, int r) {
        return query(0, root_l, root_r, l, r);
    }
};
```

```
long long query(int v, int tl, int tr, int l, int r) {
    if (tr < l || r < tl)
        return 0; //TODO
    push(v, tl, tr);
    if (l <= tl && tr <= r)
        return tree[v].val;
    int tm = tl + (tr - tl) / 2;
    return combine(query(tree[v].l_ch, tl, tm, l, r),
        query(tree[v].r_ch, tm + 1, tr, l, r));
}
};
```

Listing 18: Range Updates, Point Queries

```
//cat fenwick_inv.h | ./hash.sh
//e1114e
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/vertex_add_subtree_sum,
    ↪ https://judge.yosupo.jp/problem/point_add_range_sum
#include "../bit.h"
template<class T>
struct fenwick_inv {
    BIT<T> ft;
    fenwick_inv(int n) : ft(n) {}
    fenwick_inv(const vector<T>& arr) : ft(init(arr)) {}
    BIT<T> init(vector<T> arr /*intentional pass by value*/) const {
        for (int i = (int)arr.size() - 1; i >= 1; i--)
            arr[i] -= arr[i - 1];
        return BIT<T>(arr);
    }
    //add 'add' to inclusive range [l, r]
    void update(int l, int r, const T& add) {
        ft.update(l, add);
        if (r + 1 < (int)ft.bit.size())
            ft.update(r + 1, -add);
    }
    //get value at index 'idx'
    T query(int idx) const {
        return ft.sum(idx);
    }
};
```

Listing 19: Kth Smallest

```
//cat kth_smallest.h | ./hash.sh
//ec9b13
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/range_kth_smallest
//modified from
    ↪ https://cp-algorithms.com/data_structures/segment_tree.html#preserving-the-history-o-
struct kth_smallest {
    struct node {
        int sum;
        int l_ch, r_ch; //children, indexes into 'tree'
    };
    int mn, mx;
    //range_data_structures/implicitLazySegTree.h
    deque<node> tree;
    kth_smallest(const vector<int>& arr) : mn(INT_MAX), mx(INT_MIN), roots(arr.size() +
        ↪ 1, 0) {}
```



```
tree.push_back({0, 0, 0}); //acts as null
for (int val : arr) mn = min(mn, val), mx = max(mx, val);
for (int i = 0; i < (int)arr.size(); i++)
    roots[i + 1] = update(roots[i], mn, mx, arr[i]);
}
int update(int v, int tl, int tr, int idx) {
    if (tl == tr) {
        tree.push_back({tree[v].sum + 1, 0, 0});
        return tree.size() - 1;
    }
    int tm = tl + (tr - tl) / 2;
    int l_ch = tree[v].l_ch;
    int r_ch = tree[v].r_ch;
    if (idx <= tm)
        l_ch = update(l_ch, tl, tm, idx);
    else
        r_ch = update(r_ch, tm + 1, tr, idx);
    tree.push_back({tree[l_ch].sum + tree[r_ch].sum, l_ch, r_ch});
    return tree.size() - 1;
}
/* find (k+1)th smallest number among arr[l], arr[l+1], ..., arr[r]
 * k is 0-based, so query(l,r,0) returns the min
 */
int query(int l, int r, int k) const {
    assert(0 <= k && k < r - l + 1); //note this condition implies L <= R
    assert(0 <= l && r + 1 < (int)roots.size());
    return query(roots[l], roots[r + 1], mn, mx, k);
}
int query(int vl, int vr, int tl, int tr, int k) const {
    if (tl == tr)
        return tl;
    int tm = tl + (tr - tl) / 2;
    int left_count = tree[tree[vr].l_ch].sum - tree[tree[vl].l_ch].sum;
    if (left_count > k) return query(tree[vl].l_ch, tree[vr].l_ch, tl, tm, k);
    return query(tree[vl].r_ch, tree[vr].r_ch, tm + 1, tr, k - left_count);
}
};
```

Listing 20: Number Distinct Elements

```
//cat distinct_query.h | ./hash.sh
//06174f
#pragma once
//stress tests: tests/stress_tests/range_data_structures/distinct_query.cpp
//modified from
↳ https://cp-algorithms.com/data_structures/segment_tree.html#preserving-the-history-of-its-values-lazy-segment-tree
//works with negatives
//O(n log n) time and space
struct distinct_query {
    struct node {
        int sum;
        int l_ch, r_ch; //children, indexes into 'tree'
    };
    vector<int> roots;
    deque<node> tree;
    distinct_query(const vector<int>& arr) : roots(arr.size() + 1, 0) {
        tree.push_back({0, 0, 0}); //acts as null
        map<int, int> last_idx;
        for (int i = 0; i < (int)arr.size(); i++) {
            roots[i + 1] = update(roots[i], 0, arr.size(), last_idx[arr[i]]);
```

```
last_idx[arr[i]] = i + 1;
        }
    }
    int update(int v, int tl, int tr, int idx) {
        if (tl == tr) {
            tree.push_back({tree[v].sum + 1, 0, 0});
            return tree.size() - 1;
        }
        int tm = (tl + tr) / 2;
        int l_ch = tree[v].l_ch;
        int r_ch = tree[v].r_ch;
        if (idx <= tm)
            l_ch = update(l_ch, tl, tm, idx);
        else
            r_ch = update(r_ch, tm + 1, tr, idx);
        tree.push_back({tree[l_ch].sum + tree[r_ch].sum, l_ch, r_ch});
        return tree.size() - 1;
    }
    //returns number of distinct elements in range [l,r]
    int query(int l, int r) const {
        return query(roots[l], roots[r + 1], 0, (int)roots.size() - 1, l + 1);
    }
    int query(int vl, int vr, int tl, int tr, int idx) const {
        if (tree[vr].sum == 0 || idx <= tl)
            return 0;
        if (tr < idx)
            return tree[vr].sum - tree[vl].sum;
        int tm = (tl + tr) / 2;
        return query(tree[vl].l_ch, tree[vr].l_ch, tl, tm, idx) +
            query(tree[vl].r_ch, tree[vr].r_ch, tm + 1, tr, idx);
    }
};
```

Listing 21: Buckets

```
//cat buckets.h | ./hash.sh
//6d8842
#pragma once
//stress tests: tests/stress_tests/range_data_structures/buckets.cpp
//this code isn't the best. It's meant as a rough start for sqrt-decomposition, and to
↳ be modified
//doesn't handle overflow
struct buckets {
    const int bucket_size = 50; //TODO: change - small value for testing
    struct node {
        int sum_lazy = 0;
        int sum_bucket = 0;
        int l, r; //inclusive range of bucket
        int len() const {
            return r - l + 1;
        }
    };
    vector<int> values;
    vector<node> bucket;
    buckets(const vector<int>& initial) : values(initial) {
        int numbucket = ((int)values.size() + bucket_size - 1) / bucket_size;
        bucket.resize(numbucket);
        for (int i = 0; i < numbucket; i++) {
            bucket[i].sum_lazy = 0;
            bucket[i].sum_bucket = 0;
```

```
        bucket[i].l = i * bucket_size;
        bucket[i].r = min((i + 1) * bucket_size, (int)values.size()) - 1;
        for (int j = bucket[i].l; j <= bucket[i].r; j++)
            bucket[i].sum_bucket += values[j];
    }
}

void push(int b_idx) {
    node& b = bucket[b_idx];
    if (!b.sum_lazy) return;
    for (int i = b.l; i <= b.r; i++)
        values[i] += b.sum_lazy;
    b.sum_lazy = 0;
}

//update range [l,r]
void update(int l, int r, int diff) {
    int start_bucket = l / bucket_size;
    int end_bucket = r / bucket_size;
    if (start_bucket == end_bucket) { //range contained in same bucket case
        for (int i = l; i <= r; i++) {
            values[i] += diff;
            bucket[start_bucket].sum_bucket += diff;
        }
        return;
    }
    for (int b_idx : {
        start_bucket, end_bucket
    }) { //handle "endpoint" buckets
        node& b = bucket[b_idx];
        for (int i = max(b.l, l); i <= min(b.r, r); i++) {
            values[i] += diff;
            b.sum_bucket += diff;
        }
    }
    for (int i = start_bucket + 1; i < end_bucket; i++) { //handle all n/B buckets
        ↪ in middle
        node& b = bucket[i];
        b.sum_lazy += diff;
        b.sum_bucket += b.len() * diff;
    }
}

//sum of range [l,r]
int query(int l, int r) {
    int start_bucket = l / bucket_size;
    int end_bucket = r / bucket_size;
    if (start_bucket == end_bucket) { //range contained in same bucket case
        push(start_bucket);
        int sum = 0;
        for (int i = l; i <= r; i++)
            sum += values[i];
        return sum;
    }
    int sum = 0;
    for (int b_idx : {
        start_bucket, end_bucket
    }) { //handle "endpoint" buckets
        node& b = bucket[b_idx];
        push(b_idx);
        for (int i = max(b.l, l); i <= min(b.r, r); i++)
            sum += values[i];
    }
    for (int i = start_bucket + 1; i < end_bucket; i++) //handle all n/B buckets in
```

```
        ↪ middle
        sum += bucket[i].sum_bucket;
        return sum;
    }
};
```

Listing 22: Persistent Lazy Segment Tree

```
//cat persistent_lazy_seg_tree.h | ./hash.sh
//b9c2ca
#pragma once
//status: not tested
struct persistent_lazy_seg_tree {
    struct node {
        int l_ch, r_ch; //children, indexes into 'tree'
        int sum;
        bool lazy_tog;
    };
    int sz;
    deque<node> tree;
    vector<int> roots;
    //implicit
    persistent_lazy_seg_tree(int a_sz) : sz(a_sz) {
        tree.push_back({0, 0, 0, 0}); //acts as null
        roots.push_back(0);
    }
    void push(int v, int tl, int tr) {
        if (tl != tr) {
            tree.push_back(tree[tree[v].l_ch]);
            tree[v].l_ch = tree.size() - 1;
            tree.push_back(tree[tree[v].r_ch]);
            tree[v].r_ch = tree.size() - 1;
        }
        if (tree[v].lazy_tog) {
            tree[v].sum = (tr - tl + 1) - tree[v].sum;
            tree[v].lazy_tog = false;
            if (tl != tr) {
                tree[tree[v].l_ch].lazy_tog ^= 1;
                tree[tree[v].r_ch].lazy_tog ^= 1;
            }
        }
    }
    void set(int idx, int new_val) {
        tree.push_back(tree[roots.back()]); //allocate top down
        roots.push_back(tree.size() - 1);
        set(roots.back(), 0, sz - 1, idx, new_val);
    }
    void set(int v, int tl, int tr, int idx, int new_val) {
        push(v, tl, tr);
        if (tr < idx || idx < tl)
            return;
        if (idx <= tl && tr <= idx) {
            tree[v].sum = new_val;
            return;
        }
        int tm = (tl + tr) / 2;
        int l_ch = tree[v].l_ch;
        int r_ch = tree[v].r_ch;
        set(l_ch, tl, tm, idx, new_val);
        set(r_ch, tm + 1, tr, idx, new_val);
    }
};
```

```
    tree[v].sum = tree[l_ch].sum + tree[r_ch].sum;
}
void toggle_range(int l, int r) {
    tree.push_back(tree[roots.back()]); //allocate top down
    roots.push_back(tree.size() - 1);
    toggle_range(roots.back(), 0, sz - 1, l, r);
}
void toggle_range(int v, int tl, int tr, int l, int r) {
    push(v, tl, tr);
    if (tr < l || r < tl)
        return;
    int l_ch = tree[v].l_ch;
    int r_ch = tree[v].r_ch;
    if (l <= tl && tr <= r) {
        tree[v].sum = (tr - tl + 1) - tree[v].sum;
        if (tl != tr) {
            tree[l_ch].lazy_tog ^= 1;
            tree[r_ch].lazy_tog ^= 1;
        }
        return;
    }
    int tm = (tl + tr) / 2;
    toggle_range(l_ch, tl, tm, l, r);
    toggle_range(r_ch, tm + 1, tr, l, r);
    tree[v].sum = tree[l_ch].sum + tree[r_ch].sum;
}
//let's use implementation trick described here
//↪ https://codeforces.com/blog/entry/72626
//so that we don't have to propagate lazy vals and thus we don't have to allocate
//↪ new nodes
int query(int l, int r) const {
    int version = roots.size() - 1;
    int root = roots[version];
    return query(root, 0, sz - 1, l, r, tree[root].lazy_tog);
}
int query(int v, int tl, int tr, int l, int r, bool tog) const {
    if (v == 0 || tr < l || r < tl)
        return 0;
    if (l <= tl && tr <= r) {
        int sum = tree[v].sum;
        if (tree[v].lazy_tog) sum = (tr - tl + 1) - sum;
        return sum;
    }
    int tm = (tl + tr) / 2;
    tog ^= tree[v].lazy_tog;
    return query(tree[v].l_ch, tl, tm, l, r, tog) +
        query(tree[v].r_ch, tm + 1, tr, l, r, tog);
}
};
```

Listing 23: Merge Sort Tree

```
//cat merge_sort_tree.h | ./hash.sh
//52e191
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/static_range_frequency,
//↪ https://judge.yosupo.jp/problem/range_kth_smallest
//For point updates: either switch to policy based BST, or use sqrt decomposition
struct merge_sort_tree {
    struct node {
```

```
vector<int> vals;
int l, r;
//returns 1 + (# of nodes in left child's subtree)
//https://cp-algorithms.com/data_structures/segment_tree.html#memory-efficient-imple
int r_ch() const {
    return ((r - l) & ~1) + 2;
}
};
vector<node> tree;
//RTE's when 'arr' is empty
merge_sort_tree(const vector<int>& arr) : tree(2 * (int)arr.size() - 1) {
    build(arr, 0, 0, (int)arr.size() - 1);
}
void build(const vector<int>& arr, int v, int tl, int tr) {
    if (tl == tr) {
        tree[v] = {
            {arr[tl]},
            tl,
            tr
        };
    } else {
        int tm = tl + (tr - tl) / 2;
        build(arr, v + 1, tl, tm);
        build(arr, v + 2 * (tm - tl + 1), tm + 1, tr);
        tree[v] = combine(tree[v + 1], tree[v + 2 * (tm - tl + 1)]);
    }
}
node combine(const node& l, const node& r) const {
    vector<int> par(l.vals.size() + r.vals.size());
    merge(l.vals.begin(), l.vals.end(), r.vals.begin(), r.vals.end(), par.begin());
    return {par, l.l, r.r};
}
//How many of arr[l], arr[l+1], ..., arr[r] are < x?
//O(log^2(n))
int query(int l, int r, int x) const {
    return query(0, l, r, x);
}
int query(int v, int l, int r, int x) const {
    if (tree[v].r < l || r < tree[v].l)
        return 0;
    if (l <= tree[v].l && tree[v].r <= r) {
        const vector<int>& vals = tree[v].vals;
        return lower_bound(vals.begin(), vals.end(), x) - vals.begin();
    }
    return query(v + 1, l, r, x) +
        query(v + tree[v].r_ch(), l, r, x);
}
};
```

Listing 24: STRINGS

```
//cat suffix_array.h | ./hash.sh
//46840a
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/suffixarray,
//↪ https://judge.yosupo.jp/problem/zalgorithm,
```

Listing 25: Suffix Array

```
↪ https://judge.yosupo.jp/problem/number_of_substrings,
↪ https://judge.yosupo.jp/problem/enumerate_palindromes
//modified from here: https://judge.yosupo.jp/submission/37410
//
// SA-IS, linear-time suffix array construction
// Reference:
// G. Nong, S. Zhang, and W. H. Chan,
// Two Efficient Algorithms for Linear Time Suffix Array Construction
template<class T>
vector<int> sa_is(const T& s, int upper/*max element of 's'; for std::string, pass in
↪ 255*/) {
    int n = (int)s.size();
    if (n == 0) return {};
    if (n == 1) return {0};
    if (n == 2) {
        if (s[0] < s[1]) {
            return {0, 1};
        } else {
            return {1, 0};
        }
    }
    vector<int> sa(n);
    vector<bool> ls(n);
    for (int i = n - 2; i >= 0; i--)
        ls[i] = (s[i] == s[i + 1]) ? ls[i + 1] : (s[i] < s[i + 1]);
    vector<int> sum_l(upper + 1), sum_s(upper + 1);
    for (int i = 0; i < n; i++) {
        if (!ls[i])
            sum_s[s[i]]++;
        else
            sum_l[s[i] + 1]++;
    }
    for (int i = 0; i <= upper; i++) {
        sum_s[i] += sum_l[i];
        if (i < upper) sum_l[i + 1] += sum_s[i];
    }
    vector<int> buf(upper + 1);
    auto induce = [&](const vector<int>& lms) {
        fill(sa.begin(), sa.end(), -1);
        fill(buf.begin(), buf.end(), 0);
        copy(sum_s.begin(), sum_s.end(), buf.begin());
        for (auto d : lms) {
            if (d == n) continue;
            sa[buf[s[d]]++] = d;
        }
        copy(sum_l.begin(), sum_l.end(), buf.begin());
        sa[buf[s[n - 1]]++] = n - 1;
        for (int i = 0; i < n; i++) {
            int v = sa[i];
            if (v >= 1 && !ls[v - 1])
                sa[buf[s[v - 1]]++] = v - 1;
        }
        copy(sum_l.begin(), sum_l.end(), buf.begin());
        for (int i = n - 1; i >= 0; i--) {
            int v = sa[i];
            if (v >= 1 && ls[v - 1])
                sa[--buf[s[v - 1] + 1]] = v - 1;
        }
    };
    vector<int> lms_map(n + 1, -1);
    int m = 0;
```

```
for (int i = 1; i < n; i++) {
    if (!ls[i - 1] && ls[i])
        lms_map[i] = m++;
}
vector<int> lms;
lms.reserve(m);
for (int i = 1; i < n; i++) {
    if (!ls[i - 1] && ls[i])
        lms.push_back(i);
}
induce(lms);
if (m) {
    vector<int> sorted_lms;
    sorted_lms.reserve(m);
    for (int v : sa) {
        if (lms_map[v] != -1) sorted_lms.push_back(v);
    }
    vector<int> rec_s(m);
    int rec_upper = 0;
    rec_s[lms_map[sorted_lms[0]]] = 0;
    for (int i = 1; i < m; i++) {
        int l = sorted_lms[i - 1], r = sorted_lms[i];
        int end_l = (lms_map[l] + 1 < m) ? lms[lms_map[l] + 1] : n;
        int end_r = (lms_map[r] + 1 < m) ? lms[lms_map[r] + 1] : n;
        bool same = true;
        if (end_l - 1 != end_r - r)
            same = false;
        else {
            while (l < end_l) {
                if (s[l] != s[r])
                    break;
                l++;
                r++;
            }
            if (l == n || s[l] != s[r]) same = false;
        }
        if (!same) rec_upper++;
        rec_s[lms_map[sorted_lms[i]]] = rec_upper;
    }
    auto rec_sa =
        sa_is(rec_s, rec_upper);
    for (int i = 0; i < m; i++)
        sorted_lms[i] = lms[rec_sa[i]];
    induce(sorted_lms);
}
return sa;
}
```

Listing 26: Longest Common Prefix Array

```
//cat lcp.h | ./hash.sh
//064842
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/zaalgorithm,
↪ https://judge.yosupo.jp/problem/number_of_substrings,
↪ https://judge.yosupo.jp/problem/enumerate_palindromes
//modified from here: https://judge.yosupo.jp/submission/37410
//
// Reference:
// T. Kasai, G. Lee, H. Arimura, S. Arikawa, and K. Park,
```

```
// Linear-Time Longest-Common-Prefix Computation in Suffix Arrays and Its
// Applications
template<class T>
vector<int> LCP(const T& s, const vector<int>& sa) {
    ⇨ //NOLINT(readability-identifier-naming)
    int n = s.size(), k = 0;
    vector<int> lcp(n, 0);
    vector<int> rank(n, 0);
    for (int i = 0; i < n; i++) rank[sa[i]] = i;
    for (int i = 0; i < n; i++, k ? k-- : 0) {
        if (rank[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = sa[rank[i] + 1];
        while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
        lcp[rank[i]] = k;
    }
    return lcp;
}
```

Listing 27: Prefix Function

```
//cat prefix_function.h | ./hash.sh
//aa0518
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/zalgorithn
//stress tests: tests/stress_tests/strings/kmp.cpp
//source: https://cp-algorithms.com/string/prefix-function.html#implementation
template <class T>
vector<int> prefix_function(const T& s) {
    int n = s.size();
    vector<int> pi(n, 0);
    for (int i = 1; i < n; i++) {
        int j = pi[i - 1];
        while (j > 0 && s[i] != s[j]) j = pi[j - 1];
        pi[i] = j + (s[i] == s[j]);
    }
    return pi;
}
```

Listing 28: KMP

```
//cat kmp.h | ./hash.sh
//9d70ad
#pragma once
//stress tests: tests/stress_tests/strings/kmp.cpp
#include "prefix_function.h"
//usage:
// string needle;
// ...
// KMP_Match kmp(needle);
//or
// vector<int> needle;
// ...
// KMP_Match kmp(needle);
//kmp-doubling-trick: to check if 2 arrays are rotationally equivalent: run kmp
//with one array as the needle and the other array doubled as the haystack
//or just use kactl's min rotation code
```

```
template <class T>
struct KMP { //NOLINT(readability-identifier-naming)
    KMP(const T& a_needle) : pi(prefix_function(a_needle)), needle(a_needle) {}
    // if haystack = "bananas"
    // needle = "ana"
    //
    // then we find 2 matches:
    // bananas
    // _ana_
    // _ana_
    // 0123456 (indexes)
    // and KMP_Match::find returns {1,3} - the indexes in haystack where
    // each match starts.
    //
    // You can also pass in false for "all" and KMP_Match::find will only
    // return the first match: {1}. Useful for checking if there exists
    // some match:
    //
    // KMP_Match::find(<haystack>,false).size() > 0
    vector<int> find(const T& haystack, bool all = true) const {
        vector<int> matches;
        for (int i = 0, j = 0; i < (int)haystack.size(); i++) {
            while (j > 0 && needle[j] != haystack[i]) j = pi[j - 1];
            if (needle[j] == haystack[i]) j++;
            if (j == (int)needle.size()) {
                matches.push_back(i - (int)needle.size() + 1);
                if (!all) return matches;
                j = pi[j - 1];
            }
        }
        return matches;
    }
    vector<int> pi; //prefix function
    T needle;
};
```

Listing 29: Trie

```
//cat trie.h | ./hash.sh
//57ce2c
#pragma once
//status: not tested
//source: https://cp-algorithms.com/string/aho_corasick.html#construction-of-the-trie
//intended to be a base template and to be modified
const int k = 26; //character size
struct trie {
    const char min_ch = 'a'; // 'A' for uppercase, '0' for digits
    struct node {
        int next[k], id, p = -1;
        char ch;
        bool leaf = 0;
        node(int a_p = -1, char a_ch = '#') : p(a_p), ch(a_ch) {
            fill(next, next + k, -1);
        }
    };
    vector<node> t;
    trie() : t(1) {}
    void add_string(const string& s, int id) {
        int c = 0;
        for (char ch : s) {
```

```
        int v = ch - min_ch;
        if (t[c].next[v] == -1) {
            t[c].next[v] = t.size();
            t.emplace_back(c, ch);
        }
        c = t[c].next[v];
    }
    t[c].leaf = 1;
    t[c].id = id;
}

void remove_string(const string& s) {
    int c = 0;
    for (char ch : s) {
        int v = ch - min_ch;
        if (t[c].next[v] == -1)
            return;
        c = t[c].next[v];
    }
    t[c].leaf = 0;
}

int find_string(const string& s) {
    int c = 0;
    for (char ch : s) {
        int v = ch - min_ch;
        if (t[c].next[v] == -1)
            return -1;
        c = t[c].next[v];
    }
    if (!t[c].leaf) return -1;
    return t[c].id;
}
};
```

Listing 30: Binary Trie

```
//cat binary_trie.h | ./hash.sh
//d13f33
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/set_xor_min
struct binary_trie {
    const int mx_bit = 62;
    struct node {
        long long val = -1;
        int sub_sz = 0; //number of inserted values in subtree
        int next[2] = {-1, -1};
    };
    vector<node> t;
    binary_trie() : t(1) {}
    //delta = 1 to insert val, -1 to remove val
    void update(long long val, int delta) {
        int c = 0;
        t[0].sub_sz += delta;
        for (int bit = mx_bit; bit >= 0; bit--) {
            bool v = (val >> bit) & 1;
            if (t[c].next[v] == -1) {
                t[c].next[v] = t.size();
                t.emplace_back();
            }
            c = t[c].next[v];
            t[c].sub_sz += delta;
        }
    }
};
```

```
    }
    t[c].val = val;
}
//returns # of val's in this data structure
int cnt(long long val) const {
    int c = 0;
    for (int bit = mx_bit; bit >= 0; bit--) {
        bool v = (val >> bit) & 1;
        if (t[c].next[v] == -1)
            return 0;
        c = t[c].next[v];
    }
    return t[c].sub_sz;
}

int size() const {
    return t[0].sub_sz;
}

//returns x such that:
// x is in this data structure
// value of (x ^ val) is minimum
long long min_xor(long long val) const {
    assert(size() > 0);
    int c = 0;
    for (int bit = mx_bit; bit >= 0; bit--) {
        bool v = (val >> bit) & 1;
        int ch = t[c].next[v];
        if (ch != -1 && t[ch].sub_sz > 0)
            c = ch;
        else
            c = t[c].next[!v];
    }
    return t[c].val;
}
};
```

Listing 31: Longest Common Prefix Query

```
//cat lcp_queries.h | ./hash.sh
//a4013c
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/zalgorith,
//↳ https://judge.yosupo.jp/problem/enumerate_palindromes
#include "suffix_array.h"
#include "lcp.h"
#include "../range_data_structures/rmq.h"
//computes suffix array, lcp array, and then sparse table over lcp array
//O(n log n)
struct lcp_queries {
    lcp_queries(const string& s) : sa(sa_is(s, 255)), inv_sa(s.size()), lcp(LCP(s, sa)),
        st(st(lcp, [](int x, int y) {
            return min(x, y);
        })) {}
    for (int i = 0; i < (int)s.size(); i++)
        inv_sa[sa[i]] = i;
}

//length of longest common prefix of suffixes s[idx1 ... n-1], s[idx2 ... n-1],
//↳ 0-based indexing
//
//You can check if two substrings s[L1..R1], s[L2..R2] are equal in O(1) by:
//R2-L2 == R1-L1 && longest_common_prefix(L1, L2) >= R2-L2+1
```

```
int longest_common_prefix(int idx1, int idx2) const {
    if (idx1 == idx2) return (int)sa.size() - idx1;
    idx1 = inv_sa[idx1];
    idx2 = inv_sa[idx2];
    if (idx1 > idx2) swap(idx1, idx2);
    return st.query(idx1, idx2 - 1);
}
//returns true if suffix s[idx1 ... n-1] < s[idx2 ... n-1]
//so false if idx1 == idx2
bool less(int idx1, int idx2) const {
    return inv_sa[idx1] < inv_sa[idx2];
}
vector<int> sa, inv_sa, lcp;
RMQ<int> st;
};
```

Listing 32: MATH



Listing 33: BIN EXP MOD

```
//cat exp_mod.h | ./hash.sh
//f6e76e
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/system_of_linear_equations,
    ↪ https://judge.yosupo.jp/problem/binomial_coefficient,
    ↪ https://judge.yosupo.jp/problem/matrix_det,
    ↪ https://judge.yosupo.jp/problem/inverse_matrix
//stress tests: tests/stress_tests/math/exp_mod.cpp
//returns (base^pw)%mod in O(log(pw)), but returns 1 for 0^0
//
//What if base doesn't fit in long long?
//Since (base^pw)%mod == ((base%mod)^pw)%mod we can calculate base under mod of 'mod'
//
//What if pw doesn't fit in long long?
//case 1: mod is prime
//((base^pw)%mod == (base^(pw%(mod-1))))%mod (from Fermat's little theorem)
//so calculate pw under mod of 'mod-1'
//
//case 2: non-prime mod
//let t = totient(mod)
//if pw >= log2(mod) then (base^pw)%mod == (base^(t+(pw%t)))%mod (proof
    ↪ https://cp-algorithms.com/algebra/phi-function.html#generalization)
//so calculate pw under mod of 't'
//incidentally, totient(p) = p - 1 for every prime p, making this a more generalized
    ↪ version of case 1
int pow(long long base, long long pw, int mod) {
    assert(0 <= pw && 0 <= base && 1 <= mod);
    int res = 1;
    base %= mod;
    while (pw > 0) {
        if (pw & 1) res = res * base % mod;
        base = base * base % mod;
        pw >>= 1;
    }
    return res;
}
```

Listing 34: Fibonacci

```
//cat fib.h | ./hash.sh
//9ac293
#pragma once
//stress tests: tests/stress_tests/math/fib_matrix_expo.cpp
//https://codeforces.com/blog/entry/14516
unordered_map<long long, int> table;
int fib(long long n, int mod) { /**O(log(n))**
    if (n < 2) return 1;
    if (table.find(n) != table.end()) return table[n];
    table[n] = (1LL * fib((n + 1) / 2, mod) * fib(n / 2, mod) + 1LL * fib((n - 1) / 2,
        ↪ mod) * fib((n - 2) / 2, mod)) % mod;
    return table[n];
}
```

Listing 35: Matrix Mult and Pow

```
//cat matrix_expo.h | ./hash.sh
//424a12
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/matrix_product
//stress tests: tests/stress_tests/math/fib_matrix_expo.cpp
//empty matrix -> RTE
vector<vector<int>> mult(const vector<vector<int>>& a, const vector<vector<int>>& b, int
    ↪ mod) {
    assert(a[0].size() == b.size());
    int n = a.size(), m = b[0].size(), inner = b.size();
    vector<vector<int>> prod(n, vector<int>(m, 0));
    for (int i = 0; i < n; i++) {
        for (int k = 0; k < inner; k++) {
            for (int j = 0; j < m; j++)
                prod[i][j] = (prod[i][j] + 1LL * a[i][k] * b[k][j]) % mod;
        }
    }
    return prod;
}
vector<vector<int>> power(vector<vector<int>> mat/*intentional pass by value*/, long
    ↪ long pw, int mod) {
    int n = mat.size();
    vector<vector<int>> prod(n, vector<int>(n, 0));
    for (int i = 0; i < n; i++)
        prod[i][i] = 1;
    while (pw > 0) {
        if (pw % 2 == 1) prod = mult(prod, mat, mod);
        mat = mult(mat, mat, mod);
        pw /= 2;
    }
    return prod;
}
```

Listing 36: N Choose K MOD

```
//cat n_choose_k_mod.h | ./hash.sh
//2c3f33
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/binomial_coefficient
//only the tests with prime mod
//for mod inverse
#include "exp_mod.h"
```



```
// usage:
//      n_choose_k nk(n, 1e9+7) to use 'choose', 'inv' with inputs < n
// or:
//      n_choose_k nk(mod, mod) to use 'chooseWithLucasTheorem'
struct n_choose_k {
    n_choose_k(int n, int a_mod) : mod(a_mod), fact(n, 1), inv_fact(n, 1) {
        //this implementation doesn't work if n > mod because n! % mod = 0 when n >=
        //  mod. So 'inv_fact' array will be all 0's
        assert(max(n, 2) <= mod);
        //assert mod is prime. mod is intended to fit inside an int so that
        //multiplications fit in a longlong before being modded down. So this
        //will take sqrt(2^31) time
        for (int i = 2; i * i <= mod; i++) assert(mod % i);
        for (int i = 2; i < n; i++)
            fact[i] = 1LL * fact[i - 1] * i % mod;
        inv_fact.back() = pow(fact.back(), mod - 2, mod);
        for (int i = n - 2; i >= 2; i--)
            inv_fact[i] = 1LL * inv_fact[i + 1] * (i + 1) % mod;
    }
    //classic n choose k
    //fails when n >= mod
    int choose(int n, int k) const {
        if (k < 0 || k > n) return 0;
        //now we know 0 <= k <= n so 0 <= n
        return 1LL * fact[n] * inv_fact[k] % mod * inv_fact[n - k] % mod;
    }
    //lucas theorem to calculate n choose k in O(log(k))
    //need to calculate all factorials in range [0,mod), so O(mod) time&space, so need
    //  smallish prime mod (< 1e6 maybe)
    //handles n >= mod correctly
    int choose_with_lucas_theorem(long long n, long long k) const {
        if (k < 0 || k > n) return 0;
        if (k == 0 || k == n) return 1;
        return 1LL * choose_with_lucas_theorem(n / mod, k / mod) * choose(n % mod, k %
            mod) % mod;
    }
    //returns inverse of n in O(1)
    int inv(int n) const {
        assert(1 <= n); //don't divide by 0 :)
        return 1LL * fact[n - 1] * inv_fact[n] % mod;
    }
    int mod;
    vector<int> fact, inv_fact;
};
```

Listing 37: Partitions

```
//cat partitions.h | ./hash.sh
//3356f6
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/partition_function
//https://oeis.org/A000041
//O(n sqrt n) time, but small-ish constant factor (there does exist a O(n log n)
//  solution too)
vector<int> partitions(int n/*size of dp array*/, int mod) {
    vector<int> dp(n, 1);
    for (int i = 1; i < n; i++) {
        long long sum = 0;
        for (int j = 1, pent = 1, sign = 1; pent <= i; j++, pent += 3 * j - 2, sign =
            -sign) {
```

```
            if (pent + j <= i) sum += dp[i - pent - j] * sign + mod;
            sum += dp[i - pent] * sign + mod;
        }
        dp[i] = sum % mod;
    }
    return dp;
}
```

Listing 38: Derangements

```
//cat derangements.h | ./hash.sh
//c221bb
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/montmort_number_mod
//https://oeis.org/A000166
//
//for a permutation of size i:
//there are (i-1) places to move 0 to not be at index 0. Let's say we moved 0 to index j
//  (j>0).
//If we move value j to index 0 (forming a cycle of length 2), then there are dp[i-2]
//  derangements of the remaining i-2 elements
//else there are dp[i-1] derangements of the remaining i-1 elements (including j)
vector<int> derangements(int n/*size of dp array*/, int mod) {
    vector<int> dp(n, 0);
    dp[0] = 1;
    for (int i = 2; i < n; i++)
        dp[i] = 1LL * (i - 1) * (dp[i - 1] + dp[i - 2]) % mod;
    return dp;
}
```

Listing 39: Prime Sieve Mobius

```
//cat prime_sieve_mobius.h | ./hash.sh
//4986da
#pragma once
//stress tests: tests/stress_tests/math/prime_sieve_mobius.cpp
//status: not tested
//mobius[i] = 0 iff there exists a prime p s.t. i%(p^2)=0
//mobius[i] = -1 iff i has an odd number of distinct prime factors
//mobius[i] = 1 iff i has an even number of distinct prime factors
const int sz = 2e6 + 10;
int mobius[sz];
void calc_mobius() {
    mobius[1] = 1;
    for (int i = 1; i < sz; i++)
        for (int j = i + i; j < sz; j += i)
            mobius[j] -= mobius[i];
}
//a_prime[val] = some random prime factor of 'val'
//to get all prime factors of a number 'val':
//  while(val > 1) {
//      int p = a_prime[val];
//      //p is some prime factor of val
//      val /= p;
//  }
int a_prime[sz];
void calc_seive() {
    iota(a_prime, a_prime + sz, 0);
    for (int i = 2; i * i < sz; i++)
```

```
    if (a_prime[i] == i)
        for (int j = i * i; j < sz; j += i)
            a_prime[j] = i;
}
```

Listing 40: Row Reduce

```
//cat row_reduce.h | ./hash.sh
//b0a08a
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/system_of_linear_equations,
    ↪ https://judge.yosupo.jp/problem/matrix_det,
    ↪ https://judge.yosupo.jp/problem/inverse_matrix
//for mod inverse
#include "exp_mod.h"
//First 'cols' columns of A represents a matrix to be left in reduced row echelon form
//Row operations will be performed to all later columns
//
//example usage:
// row_reduce(A, A[0].size(), mod) //row reduce matrix with no extra columns
pair<int/*rank*/, int/*determinant*/> row_reduce(vector<vector<int>>& mat, const int
    ↪ cols, const int mod) {
    int n = mat.size(), m = mat[0].size(), rank = 0, det = 1;
    assert(cols <= m);
    for (int col = 0; col < cols && rank < n; col++) {
        //find arbitrary pivot and swap pivot to current row
        for (int i = rank; i < n; i++)
            if (mat[i][col] != 0) {
                if (rank != i) det = det == 0 ? 0 : mod - det;
                swap(mat[i], mat[rank]);
                break;
            }
        if (mat[rank][col] == 0) {
            det = 0;
            continue;
        }
        det = (1LL * det * mat[rank][col]) % mod;
        //make pivot 1 by dividing row by inverse of pivot
        const int a_inv = pow(mat[rank][col], mod - 2, mod);
        for (int j = 0; j < m; j++)
            mat[rank][j] = (1LL * mat[rank][j] * a_inv) % mod;
        //zero-out all numbers above & below pivot
        for (int i = 0; i < n; i++)
            if (i != rank && mat[i][col] != 0) {
                const int val = mat[i][col];
                for (int j = 0; j < m; j++) {
                    mat[i][j] -= 1LL * mat[rank][j] * val % mod;
                    if (mat[i][j] < 0) mat[i][j] += mod;
                }
            }
        rank++;
    }
    assert(rank <= min(n, cols));
    return {rank, det};
}
```

Listing 41: Solve Linear Equations MOD

```
//cat solve_linear_mod.h | ./hash.sh
```

```
//3cbee8
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/system_of_linear_equations
#include "row_reduce.h"
struct matrix_info {
    int rank, det;
    vector<int> x;
};
//Solves A * x = b under prime mod.
//A is a n (rows) by m (cols) matrix, b is a length n column vector, x is a length m
    ↪ column vector.
//assumes n,m >= 1, else RTE
//Returns rank of A, determinant of A, and x (solution vector to A * x = b). x is empty
    ↪ if no solution. If multiple solutions, an arbitrary one is returned.
//Leaves A in reduced row echelon form (unlike kactl) with b appended.
//O(n * m * min(n,m))
matrix_info solve_linear_mod(vector<vector<int>>& mat, const vector<int>& b, const int
    ↪ mod) {
    assert(mat.size() == b.size());
    int n = mat.size(), m = mat[0].size();
    for (int i = 0; i < n; i++)
        mat[i].push_back(b[i]);
    auto [rank, det] = row_reduce(mat, m, mod); //row reduce not including the last column
    //check if solution exists
    for (int i = rank; i < n; i++) {
        if (mat[i].back() != 0) return {rank, det, {}}; //no solution exists
    }
    //initialize solution vector ('x') from row-reduced matrix
    vector<int> x(m, 0);
    for (int i = 0; i < rank; i++) {
        while (mat[i][j] == 0) j++; //find pivot column
        x[j] = mat[i].back();
    }
    return {rank, det, x};
}
```

Listing 42: Matrix Inverse

```
//cat matrix_inverse.h | ./hash.sh
//5a5324
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/inverse_matrix
#include "row_reduce.h"
//returns inverse of square matrix mat, empty if no inverse
vector<vector<int>> matrix_inverse(vector<vector<int>> mat/*intentional pass by value*/,
    ↪ const int mod) {
    int n = mat.size();
    assert(n == (int)mat[0].size());
    //append identity matrix
    for (int i = 0; i < n; i++) {
        mat[i].resize(2 * n, 0);
        mat[i][i + n] = 1;
    }
    auto [rank, det] = row_reduce(mat, n, mod); //row reduce first n columns, leaving
    ↪ inverse in last n columns
    if (rank < n) return {}; //no inverse
    for (int i = 0; i < n; i++)
        mat[i].erase(mat[i].begin(), mat[i].begin() + n);
    return mat;
}
```

Listing 43: Euler’s Totient Phi Function

```
//cat totient.h | ./hash.sh
//36bd41
#pragma once
//stress tests: tests/stress_tests/math/totient.cpp
//Euler's totient function counts the positive integers
//up to a given integer n that are relatively prime to n.
//
//To improve, use Pollard-rho to find prime factors
int totient(int n) {
    int res = n;
    for (int i = 2; i * i <= n; i++) {
        if (n % i == 0) {
            while (n % i == 0) n /= i;
            res -= res / i;
        }
    }
    if (n > 1) res -= res / n;
    return res;
}
```

Listing 44: MAX FLOW

Listing 45: Dinic

```
//cat dinic.h | ./hash.sh
//23e871
#pragma once
//status: not tested
struct max_flow {
    typedef long long ll;
    ll n, s, t;
    max_flow(int a_n, int a_s, int a_t) : n(a_n), s(a_s), t(a_t), d(n), ptr(n), q(n),
        ↪ g(n) {}
    void add_edge(ll a, ll b, ll cap) {
        edge_map[a * n + b] = e.size();
        edge e1 = { a, b, cap, 0 };
        edge e2 = { b, a, 0, 0 };
        g[a].push_back((ll) e.size());
        e.push_back(e1);
        g[b].push_back((ll) e.size());
        e.push_back(e2);
    }
    ll get_flow() {
        ll flow = 0;
        for (;;) {
            if (!bfs()) break;
            ptr.assign(ptr.size(), 0);
            while (ll pushed = dfs(s, inf))
                flow += pushed;
        }
        return flow;
    }
    ll get_flow_for_edge(ll a, ll b) {
        return e[edge_map[a * n + b]].flow;
    }
}
const ll inf = 1e18;
struct edge {
```

```
    ll a, b, cap, flow;
};
unordered_map<int, ll> edge_map;
vector<ll> d, ptr, q;
vector<edge> e;
vector<vector<ll>> g;
bool bfs() {
    ll qh = 0, qt = 0;
    q[qt++] = s;
    d.assign(d.size(), -1);
    d[s] = 0;
    while (qh < qt && d[qt] == -1) {
        ll v = q[qh++];
        for (size_t i = 0; i < g[v].size(); i++) {
            ll id = g[v][i],
                to = e[id].b;
            if (d[to] == -1 && e[id].flow < e[id].cap) {
                q[qt++] = to;
                d[to] = d[v] + 1;
            }
        }
    }
    return d[t] != -1;
}
ll dfs(ll v, ll flow) {
    if (!flow) return 0;
    if (v == t) return flow;
    for (; ptr[v] < (ll) g[v].size(); ptr[v]++) {
        ll id = g[v][ptr[v]];
        ll to = e[id].b;
        if (d[to] != d[v] + 1) continue;
        ll pushed = dfs(to, min(flow, e[id].cap - e[id].flow));
        if (pushed) {
            e[id].flow += pushed;
            e[id ^ 1].flow -= pushed;
            return pushed;
        }
    }
    return 0;
}
};
```

Listing 46: Hungarian

```
//cat hungarian.h | ./hash.sh
//8ea32c
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/assignment
//source: https://e-mazw.ru/algo/assignment_hungary
//
//input: cost[1..n][1..m] with n <= m
//n workers, indexed 1, 2, ..., n
//m jobs, indexed 1, 2, ..., m
//it costs 'cost[i][j]' to assign worker i to job j (1<=i<=n, 1<=j<=m)
//this returns *min* total cost to assign each worker to some distinct job
//O(n^2 * m)
//
//trick 1: set 'cost[i][j]' to INF to say: "worker 'i' cannot be assigned job 'j'"
//trick 2: 'cost[i][j]' can be negative, so to instead find max total cost over all
    ↪ matchings: set all 'cost[i][j]' to '-cost[i][j]'.
```

```
//Now max total cost = - HungarianMatch(cost).minCost
const long long inf = 1e18;
struct match {
    long long min_cost;
    vector<int> matching;//worker 'i' (1<=i<=n) is assigned to job 'matching[i]'
    ↪ (1<=matching[i]<=m)
};
match hungarian(const vector<vector<long long>>& cost) {
    int n = cost.size() - 1, m = cost[0].size() - 1;
    assert(n <= m);
    vector<int> p(m + 1), way(m + 1);
    vector<long long> u(n + 1), v(m + 1);
    for (int i = 1; i <= n; i++) {
        p[0] = i;
        int j0 = 0;
        vector<long long> minv(m + 1, inf);
        vector<bool> used(m + 1, false);
        do {
            used[j0] = true;
            int i0 = p[j0], j1 = 0;
            long long delta = inf;
            for (int j = 1; j <= m; j++)
                if (!used[j]) {
                    long long cur = cost[i0][j] - u[i0] - v[j];
                    if (cur < minv[j])
                        minv[j] = cur, way[j] = j0;
                    if (minv[j] < delta)
                        delta = minv[j], j1 = j;
                }
            for (int j = 0; j <= m; j++)
                if (used[j])
                    u[p[j]] += delta, v[j] -= delta;
                else
                    minv[j] -= delta;
            j0 = j1;
        } while (p[j0] != 0);
        do {
            int j1 = way[j0];
            p[j0] = p[j1];
            j0 = j1;
        } while (j0);
    }
    vector<int> ans(n + 1);
    for (int j = 1; j <= m; j++)
        ans[p[j]] = j;
    return {-v[0], ans};
}
```

Listing 47: Min Cost Max Flow

```
//cat min_cost_max_flow.h | ./hash.sh
//805596
#pragma once
//status: not tested
const long long inf = 1e18;
struct min_cost_max_flow {
    typedef long long ll;
    struct edge {
        ll a, b, cap, cost, flow;
        size_t back;
```

```
};
vector<edge> e;
vector<vector<ll>> g;
ll n, s, t;
ll k = inf; // The maximum amount of flow allowed
min_cost_max_flow(int a_n, int a_s, int a_t) : n(a_n), s(a_s), t(a_t) {
    g.resize(n);
}
void add_edge(ll a, ll b, ll cap, ll cost) {
    edge e1 = {a, b, cap, cost, 0, g[b].size() };
    edge e2 = {b, a, 0, -cost, 0, g[a].size() };
    g[a].push_back((ll) e.size());
    e.push_back(e1);
    g[b].push_back((ll) e.size());
    e.push_back(e2);
}
// Returns {flow,cost}
pair<ll, ll> get_flow() {
    ll flow = 0, cost = 0;
    while (flow < k) {
        vector<ll> id(n, 0), d(n, inf), q(n), p(n);
        vector<size_t> p_edge(n);
        ll qh = 0, qt = 0;
        q[qt++] = s;
        d[s] = 0;
        while (qh != qt) {
            ll v = q[qh++];
            id[v] = 2;
            if (qh == n) qh = 0;
            for (size_t i = 0; i < g[v].size(); i++) {
                edge& r = e[g[v][i]];
                if (r.flow < r.cap && d[v] + r.cost < d[r.b]) {
                    d[r.b] = d[v] + r.cost;
                    if (id[r.b] == 0) {
                        q[qt++] = r.b;
                        if (qt == n) qt = 0;
                    } else if (id[r.b] == 2) {
                        if (--qh == -1) qh = n - 1;
                        q[qh] = r.b;
                    }
                    id[r.b] = 1;
                    p[r.b] = v;
                    p_edge[r.b] = i;
                }
            }
        }
        if (d[t] == inf) break;
        ll addflow = k - flow;
        for (ll v = t; v != s; v = p[v]) {
            ll pv = p[v];
            size_t pr = p_edge[v];
            addflow = min(addflow, e[g[pv][pr]].cap - e[g[pv][pr]].flow);
        }
        for (ll v = t; v != s; v = p[v]) {
            ll pv = p[v];
            size_t pr = p_edge[v], r = e[g[pv][pr]].back;
            e[g[pv][pr]].flow += addflow;
            e[g[v][r]].flow -= addflow;
            cost += e[g[pv][pr]].cost * addflow;
        }
        flow += addflow;
```

```
    }
    return {flow, cost};
}
};
```

Listing 48: MISC

Listing 49: Disjoint Set

```
//cat dsu.h | ./hash.sh
//9b3c97
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/unionfind
//stress tests: tests/stress_tests/misc/disjoint_set.cpp
struct DSU { //NOLINT(readability-identifier-naming)
    int num_sets;
    vector<int> par;
    DSU(int n) : num_sets(n), par(n, -1) {}
    DSU(const DSU& rhs) : num_sets(rhs.num_sets), par(rhs.par) {}
    int find(int x) {
        return par[x] < 0 ? x : par[x] = find(par[x]);
    }
    int size_of_set(int x) {
        return -par[find(x)];
    }
    bool join(int x, int y) {
        if ((x = find(x)) == (y = find(y))) return false;
        if (par[y] < par[x]) swap(x, y);
        par[x] += par[y];
        par[y] = x;
        num_sets--;
        return true;
    }
};
```

Listing 50: PBDS

```
//cat policy_based_data_structures.h | ./hash.sh
//807de9
#pragma once
//status: not tested
//place these includes *before* the '#define int long long' else compile error
//not using <bits/extc++.h> as it compile errors on codeforces c++20 compiler
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
//BST with extra functions https://codeforces.com/blog/entry/11080
//order_of_key - # of elements *strictly* less than given element
//find_by_order - find kth largest element, k is 0 based so find_by_order(0) returns min
    ↪ element
template<class T>
using indexed_set = tree<T, null_type, less<T>, rb_tree_tag,
    ↪ tree_order_statistics_node_update>;
//example initialization:
indexed_set<pair<long long, int>> is;
//hash table (apparently faster than unordered_map):
    ↪ https://codeforces.com/blog/entry/60737
```

```
//example initialization:
gp_hash_table<string, long long> ht;
```

Listing 51: Monotonic Stack

```
//cat monotonic_stack.h | ./hash.sh
//90f107
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/cartesian_tree
//stress tests: tests/stress_tests/misc/count_rectangles.cpp
//calculates array 'left' with:
//for every index j with left[i] < j < i: arr[j] > arr[i]
//and
//arr[left[i]] <= arr[i] if left[i] != -1
//
//trick: pass in vector<pair<T/*value*/, int/*index*/>> with arr[i].second = i (0<=i<n)
    ↪ to simulate arr[j] >= arr[i]
//
//O(n)
template<class T>
vector<int> monotonic_stack(const vector<T>& arr) {
    int n = arr.size();
    vector<int> left(n);
    for (int i = 0; i < n; i++) {
        int& j = left[i] = i - 1;
        while (j >= 0 && arr[j] > arr[i]) j = left[j];
    }
    return left;
}
```

Listing 52: Count Rectangles

```
//cat count_rectangles.h | ./hash.sh
//69a1b0
#pragma once
#include "monotonic_stack.h"
//stress tests: tests/stress_tests/misc/count_rectangles.cpp
//given a 2D boolean matrix, calculate cnt[i][j]
//cnt[i][j] = the number of times an (i * j) rectangle appears in the matrix such that
    ↪ all i*j cells in the rectangle are true
//Note cnt[0][j] and cnt[i][0] will contain garbage values
//O(n*m)
vector<vector<int>> count_rectangles(const vector<vector<bool>>& grid) {
    const int n = grid.size(), m = grid[0].size();
    vector<vector<int>> cnt(n + 1, vector<int>(m + 1, 0));
    vector<int> arr(m, 0);
    auto rv = [&](int j) -> int { //reverse
        return m - 1 - j;
    };
    for (int i = 0; i < n; i++) {
        vector<pair<int, int>> arr_rev(m);
        for (int j = 0; j < m; j++) {
            arr[j] = grid[i][j] * (arr[j] + 1);
            arr_rev[rv(j)] = {arr[j], j};
        }
        vector<int> left = monotonic_stack(arr);
        vector<int> right = monotonic_stack(arr_rev);
        for (int j = 0; j < m; j++) {
            int l = j - left[j] - 1, r = rv(right[rv(j)]) - j - 1;
```

```
        cnt[arr[j]][l + r + 1]++;
        cnt[arr[j]][l]--;
        cnt[arr[j]][r]--;
    }
}
for (int i = 1; i <= n; i++)
    for (int k = 0; k < 2; k++)
        for (int j = m; j > 1; j--)
            cnt[i][j - 1] += cnt[i][j];
for (int j = 1; j <= m; j++)
    for (int i = n; i > 1; i--)
        cnt[i - 1][j] += cnt[i][j];
return cnt;
}
```

```
    x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
    return x ^ (x >> 31);
}
size_t operator()(uint64_t x) const {
    static const uint64_t fixed_random =
        chrono::steady_clock::now().time_since_epoch().count();
    return splitmix64(x + fixed_random);
}
};
//usage:
unordered_map<long long, int, custom_hash> safe_map;
#include "policy_based_data_structures.h"
gp_hash_table<long long, int, custom_hash> safe_hash_table;
```

Listing 53: Longest Increasing Subsequence

```
//cat lis.h | ./hash.sh
//a243e1
#pragma once
//library checker tests: https://judge.yosupo.jp/problem/static_range_lis_query
//returns array of indexes representing the longest *strictly* increasing subsequence
//for non-decreasing: pass in a vector<pair<T, int>> where second is 0, 1, ..., n-1
//alternatively, there's this https://codeforces.com/blog/entry/13225
template<class T>
vector<int> LIS(const vector<T>& arr) { //NOLINT(readability-identifier-naming)
    if (arr.empty()) return {};
    vector<int> dp{0}/*array of indexes into 'arr'*/, prev(arr.size(), -1);
    for (int i = 1; i < (int)arr.size(); i++) {
        auto it = lower_bound(dp.begin(), dp.end(), i, [&](int x, int y) -> bool {
            return arr[x] < arr[y];
        });
        if (it == dp.end()) {
            prev[i] = dp.back();
            dp.push_back(i);
        } else {
            prev[i] = it == dp.begin() ? -1 : *(it - 1);
            *it = i;
        }
        //here, dp.size() = length of LIS of prefix of arr ending at index i
    }
    vector<int> res(dp.size());
    for (int i = dp.back(), j = dp.size(); i != -1; i = prev[i])
        res[--j] = i;
    return res;
}
```

Listing 54: Safe Hash

```
//cat safe_hash.h | ./hash.sh
//e837ee
#pragma once
//status: not tested
//source: https://codeforces.com/blog/entry/62393
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
```