

<b>Listings</b>		
1	<b>DATA STRUCTURES</b>	2
2	Count Rectangles	2
3	Disjoint Set	2
4	PBDS	2
5	<b>GRAPHS</b>	2
6	Bridges and Cuts	2
7	Centroid	4
8	Count Path Lengths	4
9	Dijkstra	5
10	DSU Tree	5
11	Floyd Warshall	6
12	HLD	6
13	Hopcroft Karp	7
14	LCA	7
15	SCC	8
16	<b>HASH</b>	9
17	Safe Hash	9
18	<b>MATH</b>	9
19	Count Primes	9
20	BIN EXP MOD	9
21	Fibonacci	10
22	Matrix Mult and Pow	10
23	N Choose K MOD	10
24	Partition	10
25	Prime Sieve Mobius	11
26	Solve Linear Equations MOD	11
27	Sum Floors of Arithmetic Series	12
28	Sum of Kth Powers	12
29	Euler's Totient Phi Function	13
30	<b>MAX FLOW</b>	13
31	Dinic	13
32	Hungarian	13
33	Min Cost Max Flow	14
34	<b>RANGE DATA STRUCTURES</b>	15
35	Buckets	15
36	Fenwick Tree	15
37	Merge Sort Tree	16
38	Mos Algorithm	17
39	Persistent Segment Tree	17
40	Segment Tree Beats	18
41	Segment Tree	19
42	Sparse Table	20
43	<b>RANGE DATA STRUCTURES</b>	20
44	KMP	20
45	Rolling Hash	21
46	Rotational Equivalence	21
47	Suffix Array	22
48	Trie	23

Listing 1: DATA STRUCTURES

Listing 2: Count Rectangles

```
#pragma once

//given a 2D boolean matrix, calculate cnt[i][j]
//cnt[i][j] = the number of times an (i * j) rectangle appears in the matrix
//such that all cells in the rectangle are false
//Note cnt[0][j] and cnt[i][0] will contain garbage values
//O(R*C)
//
//status: tested on random inputs
vector<vector<int>> getNumRectangles(const vector<vector<bool>>& grid) {
    vector<vector<int>> cnt;
    const int rows = grid.size(), cols = grid[0].size();
    if (rows == 0 || cols == 0) return cnt;
    cnt.resize(rows + 1, vector<int> (cols + 1, 0));
    vector<vector<int>> arr(rows + 2, vector<int> (cols + 1, 0));
    for (int i = 1; i <= rows; ++i) {
        for (int j = 1; j <= cols; ++j) {
            arr[i][j] = 1 + arr[i][j - 1];
            if (grid[i - 1][j - 1]) arr[i][j] = 0;
        }
    }
    for (int j = 1; j <= cols; ++j) {
        arr[rows + 1][j] = 0;
        stack<pair<int, int>> st;
        st.push({0, 0});
        for (int i = 1; i <= rows + 1; ++i) {
            pair<int, int> curr = {i, arr[i][j]};
            while (arr[i][j] < st.top().second) {
                curr = st.top();
                st.pop();
                cnt[i - curr.first][curr.second]++;
                cnt[i - curr.first][max(arr[i][j], st.top().second)]--;
            }
            st.push({curr.first, arr[i][j]});
        }
    }
    for (int j = 1; j <= cols; ++j) {
        for (int i = rows - 1; i >= 1; --i)
            cnt[i][j] += cnt[i + 1][j];
        for (int i = rows - 1; i >= 1; --i)
            cnt[i][j] += cnt[i + 1][j];
    }
    for (int i = 1; i <= rows; ++i) {
        for (int j = cols - 1; j >= 1; --j)
            cnt[i][j] += cnt[i][j + 1];
    }
    return cnt;
}
```

Listing 3: Disjoint Set

```
#pragma once

//status: tested on random inputs, and on https://judge.yosupo.jp/problem/unionfind
```

```
struct disjointSet {
    int numberOfSets;
    vector<int> parent;
    disjointSet(int n) : numberOfSets(n), parent(n, -1) {}
    disjointSet(const disjointSet& rhs) : numberOfSets(rhs.numberOfSets),
        parent(rhs.parent) {}
    int find(int x) {
        return parent[x] < 0 ? x : parent[x] = find(parent[x]);
    }
    int sizeOfSet(int x) {
        return -parent[find(x)];
    }
    bool merge(int x, int y) {
        if ((x = find(x)) == (y = find(y))) return false;
        if (parent[y] < parent[x]) swap(x, y);
        parent[x] += parent[y];
        parent[y] = x;
        numberOfSets--;
        return true;
    }
};
```

Listing 4: PBDS

```
//status: not tested

//place this include *before* the '#define int long long'
#include <bits/extc++.h>
using namespace __gnu_pbds;

//BST with extra functions https://codeforces.com/blog/entry/11080
//order_of_key - # of elements *strictly* less than given element
//find_by_order - find kth largest element, k is 0 based so find_by_order(0) returns min
//                  element
template<class T>
using indexed_set = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;
//example initialization:
indexed_set<int> is;

//hash table (apparently faster than unordered_map):
//                  https://codeforces.com/blog/entry/60737
//example initialization:
gp_hash_table<int, int> ht;
```

Listing 5: GRAPHS

Listing 6: Bridges and Cuts

```
#pragma once

//modified from
//                  https://github.com/nealwu/competitive-programming/blob/master/graph_theory/biconnect
//
//status: tested on random graphs
struct biconnected_components {
```

```
//don't pass in a graph with multiple edges between the same pair of nodes - it
↳ breaks bridge finding
biconnected_components(const vector<vector<int>>& adj) :
    is_cut(adj.size(), false),
    n(adj.size()),
    tour_start(n),
    low_link(n) {
    int tour = 0;
    vector<bool> visited(n, false);
    vector<int> stack;
    for (int i = 0; i < n; i++)
        if (!visited[i])
            dfs(i, -1, adj, visited, stack, tour);
}

bool is_bridge_edge(int u, int v) const {
    if (u > v) swap(u, v);
    return is_bridge.count(1LL * u * n + v);
}

//vector of all bridge edges
vector<pair<int, int>> bridges;

//vector of all BCCs. Note a node can be in multiple BCCs (iff it's a cut node)
vector<vector<int>> components;

//is_cut['node'] is true iff 'node' is a cut node
vector<bool> is_cut;

//use anything below this at your own risk :)
int n;
vector<int> tour_start, low_link;
unordered_set<ll> is_bridge;

void add_bridge(int u, int v) {
    if (u > v) swap(u, v);
    is_bridge.insert(1LL * u * n + v);
}

void dfs(int node, int parent, const vector<vector<int>>& adj, vector<bool>&
    ↳ visited, vector<int>& stack, int& tour) {
    assert(!visited[node]);
    visited[node] = true;
    tour_start[node] = tour++;
    low_link[node] = tour_start[node];
    is_cut[node] = false;
    int parent_count = 0, children = 0;
    for (int next : adj[node]) {
        // Skip the first edge to the parent, but allow multi-edges.
        if (next == parent && parent_count++ == 0)
            continue;
        if (visited[next]) {
            // next is a candidate for low_link.
            low_link[node] = min(low_link[node], tour_start[next]);
            if (tour_start[next] < tour_start[node])
                stack.push_back(node);
        } else {
            int size = (int) stack.size();
            dfs(next, node, adj, visited, stack, tour);
            children++;
        }
    }
}
```

```
// next is part of our subtree.
low_link[node] = min(low_link[node], low_link[next]);
if (low_link[next] > tour_start[node]) {
    // This is a bridge.
    bridges.push_back({node, next});
    add_bridge(node, next);
    components.push_back({node, next});
} else if (low_link[next] == tour_start[node]) {
    // This is the root of a biconnected component.
    stack.push_back(node);
    vector<int> component(stack.begin() + size, stack.end());
    sort(component.begin(), component.end());
    component.erase(unique(component.begin(), component.end()),
        ↳ component.end());
    components.push_back(component);
    stack.resize(size);
} else
    stack.push_back(node);
// In general, 'node' is a cut vertex iff it has a child whose subtree
↳ cannot reach above 'node'.
if (low_link[next] >= tour_start[node])
    is_cut[node] = true;
}
}
// The root of the tree is a cut vertex iff it has more than one child.
if (parent < 0) {
    is_cut[node] = children > 1;
    if (children == 0) {
        components.push_back({node});
    }
}
}
};

// Note: instead of a block-cut tree this is technically a block-vertex tree, which ends
↳ up being much easier to use.
// block-cut tree:
//     nodes for each BCC, and for each cut node
//     edges between a BCC and cut node iff that cut node is in that BCC (so no edges
↳ between 2 cut nodes, or 2 BCCs)
//
// block-vertex tree:
//     nodes for each BCC, and for each original node in graph
//     edges between an original node and BCC if that node is inside that BCC
struct block_cut_tree {
    block_cut_tree(const biconnected_components& _bi_comps) :
        n(_bi_comps.n),
        BC(_bi_comps.components.size()),
        T(n + BC),
        block_vertex_tree(T),
        parent(T, -1),
        depth(T) {
        auto add_edge = [&](int a, int b) {
            assert((a < n) ^ (b < n));
            block_vertex_tree[a].push_back(b);
            block_vertex_tree[b].push_back(a);
        };
        for (int bc = 0; bc < BC; bc++)
            for (int x : _bi_comps.components[bc])
                add_edge(x, n + bc);
    }
}
```

```
    for (int root = 0; root < T; root++)
        if (parent[root] < 0)
            dfs(root, -1);
}

//If a and b are in the same BCC, this returns the index into
//biconnected_components::components representing which bcc contains both a,b
//else returns -1
//assumes a != b
int which_bcc(int a, int b) const {
    assert(a != b);
    if (depth[a] > depth[b])
        swap(a, b);
    // Two different nodes are in the same biconnected component iff their distance
    // ↪ = 2 in the block-cut tree.
    if ((depth[b] == depth[a] + 2 && parent[parent[b]] == a) || (parent[a] >= 0 &&
        ↪ parent[a] == parent[b]))
        return parent[b] - n;
    return -1;
}

//use anything below this at your own risk :)
int n, BC, T;
vector<vector<int>> block_vertex_tree;//adjacency list of block vertex tree
vector<int> parent;
vector<int> depth;

void dfs(int node, int par) {
    parent[node] = par;
    depth[node] = par < 0 ? 0 : depth[par] + 1;
    for (int neigh : block_vertex_tree[node])
        if (neigh != par)
            dfs(neigh, node);
}

};
```

Listing 7: Centroid

```
#pragma once

//status: not tested

const int Max = 2e5 + 2;
vector<int> adj[Max];
int sizes[Max], parent[Max];
bool removed[Max];

void dfs2(int node, int par) {
    sizes[node] = 1;
    for (int to : adj[node]) {
        if (to != par && !removed[to]) {
            dfs2(to, node);
            sizes[node] += sizes[to];
        }
    }
}

int findCentroid(int node) {
    dfs2(node, node);
    bool found = true;
```

```
    int sizeCap = sizes[node] / 2;
    int par = node;
    while (found) {
        found = false;
        for (int to : adj[node]) {
            if (to != par && !removed[to] && sizes[to] > sizeCap) {
                found = true;
                par = node;
                node = to;
                break;
            }
        }
        return node;
    }
}

void dfs1(int node, int par) {
    removed[node] = true;
    parent[node] = par;
    for (int to : adj[node]) {
        if (!removed[to])
            dfs1(findCentroid(to), node);
    }
}

//dfs1(findCentroid(1), 0);
```

Listing 8: Count Path Lengths

```
#pragma once

//status: not tested

#include "../math/fft.h"

const int Max = 1e6+10;
int n, sizes[Max];
vector<int> adj[Max], cntPathLength[Max];
ll cntTotalPathLengths[Max];
bool removed[Max];

void dfs2(int node, int par, int root, int currDist) {
    while((int)cntPathLength[root].size() <= currDist) {
        cntPathLength[root].push_back(0);
    }
    cntPathLength[root][currDist]++;
    sizes[node] = 1;
    for (int to : adj[node]) {
        if (to != par && !removed[to]) {
            dfs2(to, node, root, currDist+1);
            sizes[node] += sizes[to];
        }
    }
}

int findCentroid(int node) {
    dfs2(node, node, node, 1);
    bool found = true;
    int sizeCap = sizes[node]/2;
    int par = node;
    while(found) {
```

```
        found = false;
        for(int to : adj[node]) {
            if(to != par && !removed[to] && sizes[to] > sizeCap) {
                found = true;
                par = node;
                node = to;
                break;
            }
        }
    }
    return node;
}

void dfs1(int node, int par) {
    removed[node] = true;
    int maxLength = 1;
    for(int to : adj[node]) {
        if(to != par && !removed[to]) {
            cntPathLength[to].clear();
            cntPathLength[to].push_back(0);
            dfs2(to, to, to, 1);
            maxLength = max(maxLength, (int)cntPathLength[to].size());
        }
    }
    vector<int> temp(maxLength, 0);
    temp[0]++;
    for(int to : adj[node]) {
        if(to != par && !removed[to]) {
            vector<ll> prod = multiply(temp, cntPathLength[to]);
            for(int i = 0; i < (int)prod.size(); ++i) {
                cntTotalPathLengths[i] += prod[i];
            }
            for(int i = 0; i < (int)cntPathLength[to].size(); ++i) {
                temp[i] += cntPathLength[to][i];
            }
        }
    }

    for(int to : adj[node]) {
        if(to != par && !removed[to]) {
            dfs1(findCentroid(to), node);
        }
    }
}
```

Listing 9: Dijkstra

```
#pragma once

//returns array 'len' where 'len[i]' = shortest path from node 'startNode' to node i
//For example len[startNode] will always = 0
//
//status: tested on random graphs against floyd warshals, and on
//      ↪ https://judge.yosupo.jp/problem/shortest_path

const ll INF = 1e18;

struct dij {
    vector<ll> len;
    vector<int> par;
};

dij dijkstra(const vector<vector<pair<int, ll>>>& adj /*directed or undirected, weighted
    ↪ graph*/, int startNode) {
    vector<ll> len(adj.size(), INF);
    vector<int> par(adj.size(), -1);
    len[startNode] = 0;
    set<pair<ll, int>> q; //weight, node
    q.insert({0, startNode});
    while (!q.empty()) {
        auto it = q.begin();
        const int node = it->second;
        q.erase(it);
        for (auto [to, weight] : adj[node]) {
            if (len[to] > weight + len[node]) {
                q.erase({len[to], to});
                len[to] = weight + len[node];
                par[to] = node;
                q.insert({len[to], to});
            }
        }
    }
    return dij{len, par};
}
```

```
};

dij dijkstra(const vector<vector<pair<int, ll>>>& adj /*directed or undirected, weighted
    ↪ graph*/, int startNode) {
    vector<ll> len(adj.size(), INF);
    vector<int> par(adj.size(), -1);
    len[startNode] = 0;
    set<pair<ll, int>> q; //weight, node
    q.insert({0, startNode});
    while (!q.empty()) {
        auto it = q.begin();
        const int node = it->second;
        q.erase(it);
        for (auto [to, weight] : adj[node]) {
            if (len[to] > weight + len[node]) {
                q.erase({len[to], to});
                len[to] = weight + len[node];
                par[to] = node;
                q.insert({len[to], to});
            }
        }
    }
    return dij{len, par};
}
```

Listing 10: DSU Tree

```
#pragma once

//status: not tested

const int Max = 1e5 + 3;
int color[Max], Time = 1, timeIn[Max], timeOut[Max], ver[Max], Size[Max], cnt[Max],
    ↪ heavyChild[Max], Depth[Max] = {0}, answer[Max];
vector<int> adj[Max];

void dfs(int node, int prev) {
    timeIn[node] = Time;
    ver[Time] = node;
    Time++;
    Size[node] = 1;
    int largest = heavyChild[node] = -1;
    Depth[node] = 1 + Depth[prev];
    for (int to : adj[node]) {
        if (to == prev) continue;
        dfs(to, node);
        Size[node] += Size[to];
        if (Size[to] > largest) {
            largest = Size[to];
            heavyChild[node] = to;
        }
    }
    timeOut[node] = Time;
}

void dfs1(int node, int prev, bool keep = true) {
    for (int to : adj[node]) {
        if (to == prev || to == heavyChild[node]) continue;
        dfs1(to, node, false);
    }
}
```

```
if (heavyChild[node] != -1)
    dfs1(heavyChild[node], node, true);
cnt[color[node]]++;
for (int to : adj[node]) {
    if (to == prev || to == heavyChild[node]) continue;
    for (int i = timeIn[to]; i < timeOut[to]; ++i)
        cnt[color[ver[i]]]++;
}
if (!keep) {
    for (int i = timeIn[node]; i < timeOut[node]; ++i)
        cnt[color[ver[i]]]--;
}
}
/*
int n;
cin >> n;
dfs(1, 1);
dfs1(1, 1);
for(int i = 1; i <= n; ++i) {
    cout << answer[i] << ' ';
}
cout << '\n';
*/
```

Listing 11: Floyd Warshall

```
#pragma once

//status: tested against output of dijkstras on random graphs

vector<vector<ll>> floydWarshall(const vector<vector<pair<int, ll>>>& adj /*directed or
    ↳ undirected, weighted graph*/) {
    int n = adj.size();
    vector<vector<ll>> len(n, vector<ll> (n, 1e18));
    for (int i = 0; i < n; i++) {
        len[i][i] = 0; //remove this line if you want shortest cycle - len[i][i] will =
            ↳ length of shortest cycle including node i (only for directed graphs)
        for (auto [neighbor, weight] : adj[i])
            len[i][neighbor] = min(len[i][neighbor], weight);
    }
    for (int k = 0; k < n; k++) {
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < n; j++)
                len[i][j] = min(len[i][j], len[i][k] + len[k][j]);
        }
    }
    return len;
}
```

Listing 12: HLD

```
#pragma once

//status: all functions tested on random trees; also 'lca' tested on
    ↳ https://judge.yosupo.jp/problem/lca

struct hld {
    vector<int> Size, par, Depth, timeIn, Next, timeInToNode;
    hld(vector<vector<int>>& adj /*forest of trees*/, int root = -1/*pass in to specify
        ↳ root, usually for a single component*/) :
```

```
Size(adj.size(), 1), par(adj.size(), -1), Depth(adj.size(), 1),
    ↳ timeIn(adj.size()), Next(adj.size(), -1), timeInToNode(adj.size()) {
    int Time = 0;
    auto callDfss = [&](int node) -> void {
        Next[node] = par[node] = node;
        dfs1(node, adj);
        dfs2(node, adj, Time);
    };
    if (root != -1)
        callDfss(root);
    for (int i = 0; i < (int) adj.size(); i++) {
        if (par[i] == -1) //roots each tree by node with min label
            callDfss(i);
    }
}

void dfs1(int node, vector<vector<int>>& adj) {
    for (auto& to : adj[node]) {
        if (to == par[node]) continue;
        Depth[to] = 1 + Depth[node];
        par[to] = node;
        dfs1(to, adj);
        Size[node] += Size[to];
        if (Size[to] > Size[adj[node][0]] || adj[node][0] == par[node])
            swap(to, adj[node][0]);
    }
}

void dfs2(int node, const vector<vector<int>>& adj, int& Time) {
    timeIn[node] = Time;
    timeInToNode[Time] = node;
    Time++;
    for (auto to : adj[node]) {
        if (to == par[node]) continue;
        Next[to] = (Time == timeIn[node] + 1 ? Next[node] : to);
        dfs2(to, adj, Time);
    }
}

// Returns intervals (of timeIn's) corresponding to the path between u and v, not
    ↳ necessarily in order
// This can answer queries for "is some node 'x' on some path" by checking if the
    ↳ timeIn[x] is in any of these intervals
vector<pair<int, int>> path(int u, int v) const {
    vector<pair<int, int>> res;
    for (; v = par[Next[v]]) {
        if (timeIn[v] < timeIn[u]) swap(u, v);
        if (timeIn[Next[v]] <= timeIn[u]) {
            res.push_back({timeIn[u], timeIn[v]});
            return res;
        }
        res.push_back({timeIn[Next[v]], timeIn[v]});
    }
}

// Returns interval (of timeIn's) corresponding to the subtree of node i
// This can answer queries for "is some node 'x' in some other node's subtree" by
    ↳ checking if timeIn[x] is in this interval
pair<int, int> subtree(int i) const {
    return {timeIn[i], timeIn[i] + Size[i] - 1};
}

// Returns lca of nodes u and v
int lca(int u, int v) const {
    for (; v = par[Next[v]]) {
        if (timeIn[v] < timeIn[u]) swap(u, v);
```

```
        if (timeIn[Next[v]] <= timeIn[u]) return u;
    }
}
};
```

Listing 13: Hopcroft Karp

```
#pragma once

//Modified from
//↳ https://github.com/foreverbell/acm-icpc-cheat-sheet/blob/master/src/graph-algorithms/hopcroft-karp.cpp
//Worst case  $O(E\sqrt{V})$  but faster in practice
//status: tested on https://judge.yosupo.jp/problem/bipartitematching with asserts
//↳ checking correctness of min vertex cover

struct match {
    /** of edges in matching (which = size of min vertex cover by öKnig's theorem)
    int sizeOfMatching;
    //an arbitrary max matching is found. For this matching:
    //if ml[nodeLeft] == -1:
    //    'nodeLeft' is not in matching
    //else:
    //    the edge 'nodeLeft' <=> ml[nodeLeft] is in the matching
    //
    //similarly for mr with edge mr[nodeRight] <=> nodeRight in matching if
    ↳ mr[nodeRight] != -1
    //matchings stored in ml and mr are the same matching
    //provides way to check if any node is in matching
    vector<int> ml, mr;
    //an arbitrary min vertex cover is found. For this MVC: leftMVC['left node'] is true
    ↳ iff 'left node' is in the min vertex cover (same for rightMVC)
    //if leftMVC['left node'] is false, then 'left node' is in the corresponding maximal
    ↳ independent set
    vector<bool> leftMVC, rightMVC;
};

//Think of the bipartite graph as having a left side (with size lSz) and a right side
↳ (with size rSz).
//Nodes on left side are indexed 0,1,...,lSz-1
//Nodes on right side are indexed 0,1,...,rSz-1
//
//'adj' is like a directed adjacency list containing edges from left side -> right side:
//To initialize 'adj': For every edge nodeLeft <=> nodeRight, do:
↳ adj[nodeLeft].push_back(nodeRight)
match hopcroftKarp(const vector<vector<int>>& adj /*bipartite graph*/) {
    int sizeOfMatching = 0;
    int lSz = adj.size();
    int rSz = 0;
    /*size of mr = 1 + largest right node****/
    for (const vector<int>& v : adj) for (int rhs : v) rSz = max(rSz, rhs + 1);
    vector<int> level(lSz), ml(lSz, -1), mr(rSz, -1);
    vector<bool> visL(lSz, false);
    while (true) {
        queue<int> q;
        for (int i = 0; i < lSz; i++) {
            if (ml[i] == -1) level[i] = 0, q.push(i);
            else level[i] = -1;
        }
        while (!q.empty()) {
            int u = q.front();
```

```
            q.pop();
            for (int x : adj[u]) {
                int v = mr[x];
                if (v != -1 && level[v] < 0) {
                    level[v] = level[u] + 1;
                    q.push(v);
                }
            }
        }
        auto dfs = [&](auto&& dfs, int u) -> bool {
            visL[u] = true;
            for (int x : adj[u]) {
                int v = mr[x];
                if (v == -1 || (!visL[v] && level[u] < level[v] && dfs(dfs, v))) {
                    ml[u] = x;
                    mr[x] = u;
                    return true;
                }
            }
            return false;
        };
        visL.assign(lSz, false);
        bool found = false;
        for (int i = 0; i < lSz; i++)
            if (ml[i] == -1 && dfs(dfs, i)) {
                found = true;
                sizeOfMatching++;
            }
        if (!found) break;
    }
    //find min vertex cover
    vector<bool> visR(rSz, false);
    auto dfs = [&](auto&& dfs, int node) -> void {
        for (int to : adj[node]) {
            if (!visR[to] && mr[to] != -1) {
                visR[to] = true;
                dfs(dfs, mr[to]);
            }
        }
    };
    for (int i = 0; i < lSz; i++) {
        visL[i] = !visL[i];
        if (ml[i] == -1)
            dfs(dfs, i);
    }
    return {sizeOfMatching, ml, mr, visL, visR};
}
```

Listing 14: LCA

```
#pragma once

/*
 * Description: Lowest Common Ancestor (LCA) implemented with Binary Lifting.
 * Supports functionality like kth Parent, distance between pair of nodes in
 * number of edges, and distance between pair of nodes in sum of edge weight.
 * Time:  $O(n * \log(n))$  for construction and all queries can be answered in
 *  $O(\log(n))$ 
 *
 * status: all functions tested on random trees. 'getLca' also tested on
```

```
↪ https://judge.yosupo.jp/problem/lca
*/

struct lca {
    typedef long long ll;
    vector<vector<int>> memo;
    vector<int> depth;
    vector<ll> dist;
    int Log;

    // use weights of 1 for unweighted tree
    lca(const vector<vector<pair<int, ll>>>& adj /*connected, weighted tree*/, int root)
        ↪ :
        depth(adj.size()), dist(adj.size()), Log(1) {          //0 - based nodes
            int n = adj.size();
            while ((1 << Log) < n) ++Log;
            memo.resize(n, vector<int> (Log));
            dfs(root, root, adj);
        }

    void dfs(int node, int par, const vector<vector<pair<int, ll>>>& adj) {
        memo[node][0] = par;
        for (int i = 1; i < Log; ++i)
            memo[node][i] = memo[memo[node][i - 1]][i - 1];
        for (auto [to, w] : adj[node]) {
            if (to == par) continue;
            depth[to] = 1 + depth[node];
            dist[to] = w + dist[node];
            dfs(to, node, adj);
        }
    }

    //if k > depth of node, then this returns the root
    int kthPar(int node, int k) const {
        for (int bit = 0; bit < Log; ++bit)
            if (k & (1 << bit))
                node = memo[node][bit];
        return node;
    }

    int getLca(int x, int y) const {
        if (depth[x] < depth[y]) swap(x, y);
        x = kthPar(x, depth[x] - depth[y]);
        if (x == y) return x;
        for (int bit = Log - 1; bit >= 0; --bit)
            if (memo[x][bit] != memo[y][bit]) {
                x = memo[x][bit];
                y = memo[y][bit];
            }
        assert(x != y && memo[x][0] == memo[y][0]);
        return memo[x][0];
    }

    int distEdges(int x, int y) const {
        return depth[x] + depth[y] - 2 * depth[getLca(x, y)];
    }

    ll distWeight(int x, int y) const {
        return dist[x] + dist[y] - 2 * dist[getLca(x, y)];
    }
};
```

Listing 15: SCC

```
#pragma once

//status: tested against floyd warshals on random graphs. also tested on
↪ https://judge.yosupo.jp/problem/scc

struct sccInfo {
    //sccId[i] is the id of the scc containing node 'i'
    vector<int> sccId;
    //scc's are labeled 0,1,...,'numberOfSCCs-1'
    int numberOfSCCs;
    //adjacency list of "condensation graph", condensation graph is a dag with topo
    ↪ ordering 0,1,...,'numberOfSCCs-1'
    // - nodes are scc's (labeled by sccId)
    // - edges: if u -> v exists in original graph, then add edge sccId[u] -> sccId[v]
    ↪ (then remove multiple&self edges)
    vector<vector<int>> adj;
};

sccInfo getSCCs(const vector<vector<int>>& adj /*directed, unweighted graph*/) {
    int n = adj.size();
    sccInfo res;
    res.sccId.resize(n);
    res.numberOfSCCs = 0;
    stack<int> seen;
    {
        vector<bool> vis(n, false);
        auto dfs = [&](auto&& dfsPtr, int curr) -> void {
            vis[curr] = true;
            for (int x : adj[curr]) {
                if (!vis[x])
                    dfsPtr(dfsPtr, x);
            }
            seen.push(curr);
        };
        for (int i = 0; i < n; ++i) {
            if (!vis[i])
                dfs(dfs, i);
        }
    }
    vector<vector<int>> adjInv(n);
    for (int i = 0; i < n; ++i) {
        for (int to : adj[i])
            adjInv[to].push_back(i);
    }
    vector<bool> vis(n, false);
    auto dfs = [&](auto&& dfsPtr, int curr) -> void {
        vis[curr] = true;
        res.sccId[curr] = res.numberOfSCCs;
        for (int x : adjInv[curr]) {
            if (!vis[x])
                dfsPtr(dfsPtr, x);
        }
    };
    while (!seen.empty()) {
        int node = seen.top();
        seen.pop();
    }
}
```



```
        if (vis[node])
            continue;
        dfs(dfs, node);
        res.numberOfSCCs++;
    }
    // This condensation graph building part is not tested
    res.adj.resize(res.numberOfSCCs);
    for (int i = 0; i < n; i++) {
        for (int j : adj[i]) {
            int sccI = res.sccId[i], sccJ = res.sccId[j];
            if (sccI != sccJ) {
                assert(sccI < sccJ);    //sanity check for topo order
                res.adj[sccI].push_back(sccJ);
            }
        }
    }
    for (vector<int>& nexts : res.adj) {
        sort(nexts.begin(), nexts.end());
        nexts.erase(unique(nexts.begin(), nexts.end()), nexts.end());
    }
    return res;
}
```

Listing 16: HASH

Listing 17: Safe Hash

```
struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        // http://xorshift.di.unimi.it/splitmix64.c
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(uint64_t x) const {
        static const uint64_t FIXED_RANDOM =
            chrono::steady_clock::now().time_since_epoch().count();
        return splitmix64(x + FIXED_RANDOM);
    }
};
```

Listing 18: MATH

Listing 19: Count Primes

```
#pragma once

//status: not tested

const int MAX = 1000005;
bool prime[MAX];
int prec[MAX];
vector<int> P;
```

```
ll rec(ll N, int K) {
    if (N <= 1 || K < 0) return 0;
    if (N <= P[K]) return N - 1;
    if (N < MAX && ll(P[K]) * P[K] > N) return N - 1 - prec[N] + prec[P[K]];
    const int LIM = 250;
    static int memo[LIM * LIM][LIM];
    bool ok = N < LIM * LIM;
    if (ok && memo[N][K]) return memo[N][K];
    ll ret = N / P[K] - rec(N / P[K], K - 1) + rec(N, K - 1);
    if (ok) memo[N][K] = ret;
    return ret;
}

// init_count_primes();
// count_primes(x);
// Time complexity: Around O(N ^ 0.75)
// Constants to configure:
// - MAX is the maximum value of sqrt(N) + 2
// increase MAX to increase time efficiency
ll count_primes(ll N) {
    if (N < MAX) return prec[N];
    int K = prec[(int) sqrt(N) + 1];
    return N - 1 - rec(N, K) + prec[P[K]];
}

void init_count_primes() {
    prime[2] = true;
    for (int i = 3; i < MAX; i += 2) prime[i] = true;
    for (int i = 3; i * i < MAX; i += 2)
        if (prime[i])
            for (int j = i * i; j < MAX; j += i + i)
                prime[j] = false;
    for (int i = 0; i < MAX; ++i) if (prime[i]) P.push_back(i);
    for (int i = 1; i < MAX; ++i) prec[i] = prec[i - 1] + prime[i];
}
```

Listing 20: BIN EXP MOD

```
#pragma once

//status: tested on random inputs, and used in misc. problems

//returns a^pw % mod in O(log(pw))
ll fastPow(ll a, ll pw, int mod) {
    ll res = 1;
    a %= mod;
    while (pw > 0) {
        if (pw & 1) res = (res * a) % mod;
        a = (a * a) % mod;
        pw >>= 1;
    }
    return res;
}
```

Listing 21: Fibonacci

```
#pragma once

//status: not tested
```

```
const int mod = 1e9 + 7;
unordered_map<ll, ll> table;
int fib(int n) {    /**O(log(n))**
    if (n < 2) return 1;
    if (table.find(n) != table.end()) return table[n];
    table[n] = (fib((n + 1) / 2) * fib(n / 2) + fib((n - 1) / 2) * fib((n - 2) / 2)) %
        ↪ mod;
    return table[n];
}
```

Listing 22: Matrix Mult and Pow

```
#pragma once

//status: not tested, but used on misc. problems

const int mod = 1e9 + 7;

vector<vector<int>> mult(const vector<vector<int>>& a, const vector<vector<int>>& b) {
    if (a.size() == 0) return {};
    if (a[0].size() == 0) return {};
    if (b.size() == 0) return {};
    if (b[0].size() == 0) return {};
    if (a[0].size() != b.size()) return {};
    int resultRow = a.size(), resultCol = b[0].size(), n = a[0].size();
    vector<vector<int>> product(resultRow, vector<int> (resultCol, 0));
    for (int i = 0; i < resultRow; ++i) {
        for (int k = 0; k < n; ++k) {
            for (int j = 0; j < resultCol; ++j)
                product[i][j] = (product[i][j] + 1LL * a[i][k] * b[k][j]) % mod;
        }
    }
    return product;
}

vector<vector<int>> power(vector<vector<int>> matrix, int b) {
    vector<vector<int>> res(matrix.size(), vector<int> (matrix.size(), 0));
    for (int i = 0; i < (int) matrix.size(); i++)
        res[i][i] = 1;
    while (b > 0) {
        if (b % 2 == 1)
            res = mult(res, matrix);
        matrix = mult(matrix, matrix);
        b /= 2;
    }
    return res;
}
```

Listing 23: N Choose K MOD

```
#pragma once

//status: tested on random inputs

#include "exp_mod.h"

// usage:
//      NchooseK nk(n+1, 1e9+7) to use 'choose', 'inv' with inputs <= n
```

```
// or:
//      NchooseK nk(mod, mod) to use 'chooseWithLucasTheorem'
struct NchooseK {
    // 'factSz' is the size of the factorial array, so only call 'choose', 'inv' with n
    ↪ < factSz

    NchooseK(int factSz, int currMod) : mod(currMod), fact(factSz, 1), invFact(factSz) {
        //this implementation of doesn't work if factSz > mod because n! % mod = 0 when
        ↪ n >= mod. So 'invFact' array will be all 0's

        assert(factSz <= mod);
        //assert mod is prime. mod is intended to fit inside an int so that
        //multiplications fit in a longlong before being modded down. So this
        //will take sqrt(2^31) time
        assert(mod >= 2);
        for (int i = 2; i * i <= mod; i++)
            assert(mod % i);
        for (int i = 1; i < factSz; i++)
            fact[i] = 1LL * fact[i - 1] * i % mod;
        invFact.back() = fastPow(fact.back(), mod - 2, mod);
        for (int i = factSz - 2; i >= 0; i--)
            invFact[i] = 1LL * invFact[i + 1] * (i + 1) % mod;
    }

    //classic n choose k
    //fails when n >= mod
    int choose(int n, int k) const {
        if (k < 0 || k > n) return 0;
        //now we know 0 <= k <= n so 0 <= n
        return 1LL * fact[n] * invFact[k] % mod * invFact[n - k] % mod;
    }

    //lucas theorem to calculate n choose k in O(log(k))
    //need to calculate all factorials in range [0,mod), so O(mod) time&space, so need
    ↪ smallish mod (< 1e6 maybe)
    //handles n >= mod correctly
    int chooseWithLucasTheorem(ll n, ll k) const {
        if (k < 0 || k > n) return 0;
        if (k == 0 || k == n) return 1;
        return 1LL * chooseWithLucasTheorem(n / mod, k / mod) * choose(n % mod, k % mod)
            ↪ % mod;
    }

    //returns inverse of n in O(1)
    int inv(int n) const {
        assert(1 <= n);    //don't divide by 0 :)
        return 1LL * fact[n - 1] * invFact[n] % mod;
    }

    int mod;
    vector<int> fact, invFact;
};
```

Listing 24: Partition

```
#pragma once

//status: not tested

struct partitionFunction {
    vector<ll> remember;
    //The number of ways you can add to a number
```

```
ll getPartitionsModM(ll n, ll m) {
    if (n < 0) return 0;
    if (n == 0) return 1;
    if ((int) remember.size() <= n) remember.resize(n + 1, -1);
    if (remember[n] != -1) return remember[n];
    ll sum = 0;
    ll val = 1;
    for (ll i = 1; val <= n; i++) {
        ll multiply = 1;
        if (i % 2 == 0) multiply = -1;
        val = ((3 * i * i) + i) / 2;
        sum += getPartitionsModM(n - val, m) * multiply % m;
        val = ((3 * i * i) - i) / 2;
        sum += getPartitionsModM(n - val, m) * multiply % m;
        sum %= m;
        if (sum < 0) sum += m;
    }
    return remember[n] = sum % m;
}
```

Listing 25: Prime Sieve Mobius

```
#pragma once

//status: not tested, but used on various problems

//mobius[i] = 0 iff there exists a prime p s.t. i%(p^2)=0
//mobius[i] = -1 iff i has an odd number of distinct prime factors
//mobius[i] = 1 iff i has an even number of distinct prime factors
const int N = 2e6 + 10;
int mobius[N];
void calcMobius() {
    mobius[1] = 1;
    for (int i = 1; i < N; ++i) {
        for (int j = i + i; j < N; j += i)
            mobius[j] -= mobius[i];
    }
}

int minPrime[N];
void calcSeive() {
    fill(minPrime, minPrime + N, N);
    for (int i = N - 1; i >= 2; --i) {
        for (int j = i; j < N; j += i)
            minPrime[j] = i;
    }
}
```

Listing 26: Solve Linear Equations MOD

```
#pragma once

#include "exp_mod.h"

struct matrixInfo {
    int rank, det;
    vector<int> x;
};
```

```
//Solves A * x = b under prime mod.
//A is a n (rows) by m (cols) matrix, b is a length n column vector, x is a length m
//column vector.
//assumes n,m >= 1, else RTE
//Returns rank of A, determinant of A, and x (solution vector). x is empty if no
//solution. If multiple solutions, an arbitrary one is returned.
//Leaves A in reduced row echelon form (unlike kactl).
//O(n * m * min(n,m))
//
//status: tested on https://judge.yosupo.jp/problem/system_of_linear_equations and
//https://judge.yosupo.jp/problem/matrix_det
matrixInfo solve_linear_mod(vector<vector<int>>& A, vector<int>& b, const int mod) {
    assert(A.size() == b.size());
    int n = A.size(), m = A[0].size(), rank = 0, det = 1;
    //start of row reduce
    for (int col = 0; col < m && rank < n; ++col) {
        //find arbitrary pivot and swap pivot to current row
        for (int i = rank; i < n; ++i) if (A[i][col] != 0) {
            if (rank != i) det = det == 0 ? det : mod - det;
            swap(A[i], A[rank]);
            swap(b[i], b[rank]);
            break;
        }
        if (A[rank][col] == 0) {
            det = 0;
            continue;
        }
        det = (1LL * det * A[rank][col]) % mod;
        //make pivot 1 by dividing row by inverse of pivot
        const int aInv = fastPow(A[rank][col], mod - 2, mod);
        for (int j = 0; j < m; ++j)
            A[rank][j] = (1LL * A[rank][j] * aInv) % mod;
        b[rank] = (1LL * b[rank] * aInv) % mod;
        //zero-out all numbers above & below pivot
        for (int i = 0; i < n; ++i) if (i != rank && A[i][col] != 0) {
            const int val = A[i][col];
            for (int j = 0; j < m; ++j) {
                A[i][j] -= 1LL * A[rank][j] * val % mod;
                if (A[i][j] < 0) A[i][j] += mod;
            }
            b[i] -= 1LL * b[rank] * val % mod;
            if (b[i] < 0) b[i] += mod;
        }
        ++rank;
    }
    //end of row reduce, start of extracting answer ('x') from 'A' and 'b'
    assert(rank <= min(n, m));
    matrixInfo info{rank, det, vector<int>() };
    //check if solution exists
    for (int i = rank; i < n; ++i) {
        if (b[i] != 0) return info; //no solution exists
    }
    info.x.resize(m, 0);
    //initialize solution vector ('x')
    for (int i = 0, j = 0; i < rank; i++) {
        while (A[i][j] == 0) j++;
        assert(A[i][j] == 1);
        info.x[j] = b[i];
    }
    return info;
}
```

```
}

```

Listing 27: Sum Floors of Arithmetic Series

```
#pragma once

//status: used on https://open.kattis.com/problems/itsamodmodmodmodworld

//computes:
//[p/q] + [2p/q] + [3p/q] + ... + [np/q]
//(p, q, n are natural numbers)
//[x] = floor(x)

ll cnt(ll p, ll q, ll n) {
    ll t = __gcd(p, q);
    p = p / t;
    q = q / t;
    ll s = 0;
    ll z = 1;
    while ((q > 0) && (n > 0)) {
        //(point A)
        t = p / q;
        s += z * t * n * (n + 1) / 2;
        p -= q * t;
        //(point B)
        t = n / q;
        s += z * p * t * (n + 1) - z * t * (p * q * t + p + q - 1) / 2;
        n -= q * t;
        //(point C)
        t = n * p / q;
        s += z * t * n;
        n = t;
        swap(p, q);
        z = -z;
    }
    return s;
}
```

Listing 28: Sum of Kth Powers

```
#pragma once

//status: not tested, but used on misc. problems

#define MAX 1000010
#define MOD 1000000007

//Faulhaber's the sum of the k-th powers of the first n positive integers
//1^k + 2^k + 3^k + 4^k + ... + n^k
//O(k*log(k))

//Usage: lgr::lagrange(n, k)

namespace lgr {
short factor[MAX];
int P[MAX], S[MAX], ar[MAX], inv[MAX];

inline int expo(int a, int b) {
    int res = 1;
```

```
while (b) {
    if (b & 1) res = (long long) res * a % MOD;
    a = (long long) a * a % MOD;
    b >>= 1;
}
return res;
}

int lagrange(long long n, int k) {
    if (!k) return (n % MOD);
    int i, j, x, res = 0;
    if (!inv[0]) {
        for (i = 2, x = 1; i < MAX; i++) x = (long long) x * i % MOD;
        inv[MAX - 1] = expo(x, MOD - 2);
        for (i = MAX - 2; i >= 0; i--) inv[i] = ((long long) inv[i + 1] * (i + 1)) % MOD;
    }
    k++;
    for (i = 0; i <= k; i++) factor[i] = 0;
    for (i = 4; i <= k; i += 2) factor[i] = 2;
    for (i = 3; (i * i) <= k; i += 2) {
        if (!factor[i]) {
            for (j = (i * i), x = i << 1; j <= k; j += x)
                factor[j] = i;
        }
    }
    for (ar[1] = 1, ar[0] = 0, i = 2; i <= k; i++) {
        if (!factor[i]) ar[i] = expo(i, k - 1);
        else ar[i] = ((long long) ar[factor[i]] * ar[i / factor[i]]) % MOD;
    }
    for (i = 1; i <= k; i++) {
        ar[i] += ar[i - 1];
        if (ar[i] >= MOD) ar[i] -= MOD;
    }
    if (n <= k) return ar[n];
    P[0] = 1, S[k] = 1;
    for (i = 1; i <= k; i++) P[i] = ((long long) P[i - 1] * ((n - i + 1) % MOD)) % MOD;
    for (i = k - 1; i >= 0; i--) S[i] = ((long long) S[i + 1] * ((n - i - 1) % MOD)) %
        MOD;
    for (i = 0; i <= k; i++) {
        x = (long long) ar[i] * P[i] % MOD * S[i] % MOD * inv[k - i] % MOD * inv[i] %
            MOD;
        if ((k - i) & 1) {
            res -= x;
            if (res < 0) res += MOD;
        } else {
            res += x;
            if (res >= MOD) res -= MOD;
        }
    }
    return (res % MOD);
}
}
```

Listing 29: Euler's Totient Phi Function

```
#pragma once

//not tested, but used in misc. problems

// Euler's totient function counts the positive integers
```

```
// up to a given integer n that are relatively prime to n.
ll phi(ll n) {
    ll tempN = n;
    ll result = n;
    for (ll i = 2; i * i <= tempN; i++) {
        if (n % i == 0) {
            while (n % i == 0)
                n /= i;
            result -= result / i;
        }
    }
    if (n > 1) result -= result / n;
    return result;
}
```

Listing 30: MAX FLOW

Listing 31: Dinic

```
#pragma once

//status: no tests, but used in various problems

struct maxflow {
public:
    ll n, s, t;
    maxflow(int _n, int _s, int _t) : n(_n), s(_s), t(_t), d(n), ptr(n), q(n), g(n) {}
    void addedge(ll a, ll b, ll cap) {
        edgeMap[a * n + b] = e.size();
        edge e1 = { a, b, cap, 0 };
        edge e2 = { b, a, 0, 0 };
        g[a].push_back((ll) e.size());
        e.push_back(e1);
        g[b].push_back((ll) e.size());
        e.push_back(e2);
    }
    ll getflow() {
        ll flow = 0;
        for (;;) {
            if (!bfs()) break;
            ptr.assign(ptr.size(), 0);
            while (ll pushed = dfs(s, inf))
                flow += pushed;
        }
        return flow;
    }
    ll getFlowForEdge(ll a, ll b) {
        return e[edgeMap[a * n + b]].flow;
    }
private:
    const ll inf = 1e18;
    struct edge {
        ll a, b, cap, flow;
    };
    unordered_map<int, ll> edgeMap;
    vector<ll> d, ptr, q;
    vector<edge> e;
};
```

```
vector<vector<ll>> g;
bool bfs() {
    ll qh = 0, qt = 0;
    q[qt++] = s;
    d.assign(d.size(), -1);
    d[s] = 0;
    while (qh < qt && d[qt] == -1) {
        ll v = q[qh++];
        for (size_t i = 0; i < g[v].size(); ++i) {
            ll id = g[v][i],
                to = e[id].b;
            if (d[to] == -1 && e[id].flow < e[id].cap) {
                q[qt++] = to;
                d[to] = d[v] + 1;
            }
        }
    }
    return d[t] != -1;
}
ll dfs(ll v, ll flow) {
    if (!flow) return 0;
    if (v == t) return flow;
    for (; ptr[v] < (ll) g[v].size(); ++ptr[v]) {
        ll id = g[v][ptr[v]];
        ll to = e[id].b;
        if (d[to] != d[v] + 1) continue;
        ll pushed = dfs(to, min(flow, e[id].cap - e[id].flow));
        if (pushed) {
            e[id].flow += pushed;
            e[id ^ 1].flow -= pushed;
            return pushed;
        }
    }
    return 0;
}
};
```

Listing 32: Hungarian

```
#pragma once

const ll inf = 1e18;

// this is one-indexed
// jobs X workers cost matrix
// cost[i][j] is cost of job i done by worker j
// #jobs must be <= #workers
// Default finds min cost; to find max cost set all costs[i][j] to -costs[i][j], set all
// ↪ unused to positive inf, ***set main diagonal (self edges) to 0***

//status: tested on https://judge.yosupo.jp/problem/assignment

struct match {
    ll cost;
    vector<int> matching;
};

match HungarianMatch(const vector<vector<ll>>& cost) {
    ll n = cost.size() - 1;
    ll m = cost[0].size() - 1;
};
```

```
vector<ll> u(n + 1), v(m + 1), p(m + 1), way(m + 1);
for (ll i = 1; i <= n; ++i) {
    p[0] = i;
    ll j0 = 0;
    vector<ll> minv(m + 1, inf);
    vector<char> used(m + 1, false);
    do {
        used[j0] = true;
        ll i0 = p[j0], delta = inf, j1 = 0;
        for (ll j = 1; j <= m; ++j)
            if (!used[j]) {
                ll cur = cost[i0][j] - u[i0] - v[j];
                if (cur < minv[j])
                    minv[j] = cur, way[j] = j0;
                if (minv[j] < delta)
                    delta = minv[j], j1 = j;
            }
        for (ll j = 0; j <= m; ++j)
            if (used[j])
                u[p[j]] += delta, v[j] -= delta;
            else
                minv[j] -= delta;
        j0 = j1;
    } while (p[j0] != 0);
    do {
        ll j1 = way[j0];
        p[j0] = p[j1];
        j0 = j1;
    } while (j0);
}
// For each N, it contains the M it selected
vector<int> ans(n + 1);
for (ll j = 1; j <= m; ++j)
    ans[p[j]] = j;
return {-v[0], ans};
}
```

Listing 33: Min Cost Max Flow

```
#pragma once

//status: not tested, but used in various problems

const ll inf = 1e18;

struct mincostmaxflow {
    struct edge {
        ll a, b, cap, cost, flow;
        size_t back;
    };

    vector<edge> e;
    vector<vector<ll>> g;
    ll n, s, t;
    ll k = inf; // The maximum amount of flow allowed

    mincostmaxflow(int _n, int _s, int _t) : n(_n), s(_s), t(_t) {
        g.resize(n);
    }
};
```

```
void addedge(ll a, ll b, ll cap, ll cost) {
    edge e1 = {a, b, cap, cost, 0, g[b].size() };
    edge e2 = {b, a, 0, -cost, 0, g[a].size() };
    g[a].push_back((ll) e.size());
    e.push_back(e1);
    g[b].push_back((ll) e.size());
    e.push_back(e2);
}

// Returns {flow, cost}
pair<ll, ll> getflow() {
    ll flow = 0, cost = 0;
    while (flow < k) {
        vector<ll> id(n, 0);
        vector<ll> d(n, inf);
        vector<ll> q(n);
        vector<ll> p(n);
        vector<size_t> p_edge(n);
        ll qh = 0, qt = 0;
        q[qt++] = s;
        d[s] = 0;
        while (qh != qt) {
            ll v = q[qh++];
            id[v] = 2;
            if (qh == n) qh = 0;
            for (size_t i = 0; i < g[v].size(); ++i) {
                edge& r = e[g[v][i]];
                if (r.flow < r.cap && d[v] + r.cost < d[r.b]) {
                    d[r.b] = d[v] + r.cost;
                    if (id[r.b] == 0) {
                        q[qt++] = r.b;
                        if (qt == n) qt = 0;
                    } else if (id[r.b] == 2) {
                        if (--qh == -1) qh = n - 1;
                        q[qh] = r.b;
                    }
                    id[r.b] = 1;
                    p[r.b] = v;
                    p_edge[r.b] = i;
                }
            }
        }
        if (d[t] == inf) break;
        ll addflow = k - flow;
        for (ll v = t; v != s; v = p[v]) {
            ll pv = p[v];
            size_t pr = p_edge[v];
            addflow = min(addflow, e[g[pv][pr]].cap - e[g[pv][pr]].flow);
        }
        for (ll v = t; v != s; v = p[v]) {
            ll pv = p[v];
            size_t pr = p_edge[v], r = e[g[pv][pr]].back;
            e[g[pv][pr]].flow += addflow;
            e[g[v][r]].flow -= addflow;
            cost += e[g[pv][pr]].cost * addflow;
        }
        flow += addflow;
    }
    return {flow, cost};
}
```

Listing 34: RANGE DATA STRUCTURES

Listing 35: Buckets

```
#pragma once

//this code isn't the best. It's meant as a rough start for sqrt-decomposition, and to
    ↪ be (heavily) modified
//doesn't handle overflow

//status: tested on random inputs, also used in various problems
struct buckets {
    const int BUCKET_SIZE = 50; //TODO: change - small value for testing

    struct bucket {
        int sumLazy = 0;
        int sumBucket = 0;
        int l, r; //inclusive range of bucket
        int len() const {
            return r - l + 1;
        }
    };

    vector<int> values;
    vector<bucket> _buckets;

    buckets(const vector<int>& initial) : values(initial) {
        int numBuckets = ((int) values.size() + BUCKET_SIZE - 1) / BUCKET_SIZE;
        _buckets.resize(numBuckets);
        for (int i = 0; i < numBuckets; i++) {
            _buckets[i].sumLazy = 0;
            _buckets[i].sumBucket = 0;
            _buckets[i].l = i * BUCKET_SIZE;
            _buckets[i].r = min((i + 1) * BUCKET_SIZE, (int) values.size()) - 1;
            for (int j = _buckets[i].l; j <= _buckets[i].r; j++)
                _buckets[i].sumBucket += values[j];
        }

        void pushLazy(int bIdx) {
            bucket& b = _buckets[bIdx];
            if (!b.sumLazy) return;
            for (int i = b.l; i <= b.r; i++)
                values[i] += b.sumLazy;
            b.sumLazy = 0;
        }

        //update range [L,R]
        void update(int L, int R, int diff) {
            int startBucket = L / BUCKET_SIZE;
            int endBucket = R / BUCKET_SIZE;
            if (startBucket == endBucket) { //range contained in same bucket case
                for (int i = L; i <= R; i++) {
                    values[i] += diff;
                    _buckets[startBucket].sumBucket += diff;
                }
            }
            return;
        }
    };
};
```

```
    }
    for (int bIdx : {
        startBucket, endBucket
    }) { //handle "endpoint" buckets
        bucket& b = _buckets[bIdx];
        for (int i = max(b.l, L); i <= min(b.r, R); i++) {
            values[i] += diff;
            b.sumBucket += diff;
        }
    }

    for (int i = startBucket + 1; i < endBucket; i++) { //handle all n/B buckets
        ↪ in middle
        bucket& b = _buckets[i];
        b.sumLazy += diff;
        b.sumBucket += b.len() * diff;
    }
}

//sum of range [L,R]
int query(int L, int R) {
    int startBucket = L / BUCKET_SIZE;
    int endBucket = R / BUCKET_SIZE;
    if (startBucket == endBucket) { //range contained in same bucket case
        pushLazy(startBucket);
        int sum = 0;
        for (int i = L; i <= R; i++)
            sum += values[i];
        return sum;
    }
    int sum = 0;
    for (int bIdx : {
        startBucket, endBucket
    }) { //handle "endpoint" buckets
        bucket& b = _buckets[bIdx];
        pushLazy(bIdx);
        for (int i = max(b.l, L); i <= min(b.r, R); i++)
            sum += values[i];
    }
    for (int i = startBucket + 1; i < endBucket; i++) //handle all n/B buckets in
        ↪ middle
        sum += _buckets[i].sumBucket;
    return sum;
}
};
```

Listing 36: Fenwick Tree

```
#pragma once

//status: tested on random inputs; also tested on
    ↪ https://judge.yosupo.jp/problem/point_add_range_sum

template<class T>
struct fenwickTree {
    vector<T> bit;
    fenwickTree(int n) : bit(n, 0) {}
    fenwickTree(const vector<T>& a) : bit(a.size()) {
        if (a.empty()) return;
        bit[0] = a[0];
        for (int i = 1; i < (int) a.size(); i++)
```

```
        bit[i] = bit[i - 1] + a[i];
    for (int i = (int) a.size() - 1; i > 0; i--) {
        int lower_i = (i & (i + 1)) - 1;
        if (lower_i >= 0)
            bit[i] -= bit[lower_i];
    }
    void update(int idx, const T& d) {
        for (; idx < (int) bit.size(); idx = idx | (idx + 1))
            bit[idx] += d;
    }
    T sum(int r) const {
        T ret = 0;
        for (; r >= 0; r = (r & (r + 1)) - 1)
            ret += bit[r];
        return ret;
    }
    T sum(int l, int r) const {
        return sum(r) - sum(l - 1);
    }
};

//status: tested on random inputs

template<class T>
struct rangeUpdatesAndPointQueries {
    fenwickTree<T> ft;
    rangeUpdatesAndPointQueries(int n) : ft(n) {}
    rangeUpdatesAndPointQueries(vector<T> arr) : ft(0) {
        for (int i = (int) arr.size() - 1; i >= 1; i--)
            arr[i] -= arr[i - 1];
        ft = fenwickTree<T> (arr);
    }
    void updateRange(int l, int r, const T& diff) {
        ft.update(l, diff);
        if (r + 1 < (int) ft.bit.size())
            ft.update(r + 1, -diff);
    }
    T queryIdx(int idx) const {
        return ft.sum(idx);
    }
};
```

Listing 37: Merge Sort Tree

```
#pragma once

//status: not tested, but used in various problems

struct MergeSortTree {
    struct Node {
        vector<int> vals;
    };
    vector<Node> tree;
    int n, size;

    /*implement these*/
    Node combine(const Node& L, const Node& R) {
        Node par;
        //merge from merge sort
```

```
int ptrL = 0, ptrR = 0;
while (ptrL < (int) L.vals.size() && ptrR < (int) R.vals.size()) {
    int valL = L.vals[ptrL];
    int valR = R.vals[ptrR];
    if (valL > valR) {
        par.vals.push_back(valR);
        ptrR++;
    } else if (valL < valR) {
        par.vals.push_back(valL);
        ptrL++;
    } else {
        par.vals.push_back(valL);
        par.vals.push_back(valR);
        ptrL++, ptrR++;
    }
}
while (ptrL < (int) L.vals.size())
    par.vals.push_back(L.vals[ptrL++]);
while (ptrR < (int) R.vals.size())
    par.vals.push_back(R.vals[ptrR++]);
return par;
}

MergeSortTree(const vector<int>& arr) : n((int) arr.size()) {
    size = 1;
    while (size < n) size <= 1;
    size <= 1;
    tree.resize(size);
    build(arr, 1, 0, n - 1);
}

void build(const vector<int>& arr, int node, int start, int end) {
    if (start == end)
        tree[node].vals.push_back(arr[start]);
    else {
        int mid = (start + end) / 2;
        build(arr, 2 * node, start, mid);
        build(arr, 2 * node + 1, mid + 1, end);
        tree[node] = combine(tree[2 * node], tree[2 * node + 1]);
    }
}

//returns how many values of arr[l], arr[l+1], ..., arr[r] which are < x
int query(int l, int r, int x) {
    return query(1, 0, n - 1, l, r, x);
}

int query(int node, int start, int end, int l, int r, int x) {
    if (r < start || end < l) return 0;
    if (l <= start && end <= r) {
        auto& v = tree[node].vals;
        return lower_bound(v.begin(), v.end(), x) - v.begin();
    }
    int mid = (start + end) / 2;
    return query(2 * node, start, mid, l, r, x) + query(2 * node + 1, mid + 1, end,
        ↪ l, r, x);
}
};
```

Listing 38: Mos Algorithm

```
//status: not tested, but used in various problems
```



```
#include <bits/stdc++.h>
using namespace std;

const int Max = 1e6+2;
int block, answer[Max], answerToQuery;

struct query {
    int l, r, index;
};

bool cmp(query x, query y) {
    if(x.l/block == y.l/block) return x.r < y.r;
    return x.l < y.l;
}

void add(int pos) {
}

void remove(int pos) {
}

int main() {
    int q;
    cin >> q;
    vector<query> queries(q);
    for(int i = 0; i < q; ++i) {
        cin >> queries[i].l >> queries[i].r;
        queries[i].index = i;
        answer[i] = 0;
    }
    sort(queries.begin(), queries.end(), cmp);
    int left = 0, right = 0; //store inclusive ranges, start at [0,0]
    add(0);
    answerToQuery = 0;
    for(auto& q : queries) {
        while(left > q.l) {
            left--;
            add(left);
        }
        while(right < q.r) {
            right++;
            add(right);
        }
        while(left < q.l) {
            remove(left);
            left++;
        }
        while(right > q.r) {
            remove(right);
            right--;
        }
        answer[q.index] = answerToQuery;
    }
    for(int i = 0; i < q; ++i) cout << answer[i] << '\n';
    return 0;
}
```

Listing 39: Persistent Segment Tree

```
#pragma once

//modified from k-th smallest section of
```

```
↪ https://cp-algorithms.com/data_structures/segment_tree.html
//
//status: tested on random inputs, and used in various problems
struct pst {
public:
    /* Persistent seg tree handle a variety of queries
     * - no updates. For point updates, use either merge sort tree, wavelet tree or
     *   ↪ sqrt-decomp
     * O(nlogn) time and space to build tree
     */
    pst(const vector<int>& arr) : sorted(arr), n(arr.size()) {
        nodes.reserve(4 * n * log(n + 1));
        roots.reserve(n + 1);
        nodes.push_back(Node(Node::Data())); //acts as nullptr
        sort(sorted.begin(), sorted.end());
        sorted.erase(unique(sorted.begin(), sorted.end()), sorted.end());
        tl = 0, tr = (int) sorted.size() - 1;
        roots.push_back(0);
        for (int val : arr) {
            int idx = lower_bound(sorted.begin(), sorted.end(), val) - sorted.begin();
            roots.push_back(update(roots.back(), tl, tr, idx, val));
        }
    }
    /* find kth smallest number among arr[L], arr[L+1], ..., arr[R]
     * k is 1-based, so find_kth(L,R,1) returns the min
     * O(logn)
     */
    int find_kth(int L, int R, int k) const {
        assert(1 <= k && k <= R - L + 1); //note this condition implies L <= R
        assert(0 <= L && R < n);
        return sorted[find_kth(roots[L], roots[R + 1], tl, tr, k)];
    }

    /* Among elements arr[L], arr[L+1], ..., arr[R], this returns:
     * the number of elements which is in range [valueL, valueR]
     */
    int cnt_in_range(int L, int R, int valueL, int valueR) const {
        return calc_in_range(L, R, valueL, valueR).cnt;
    }

    /* Among elements arr[L], arr[L+1], ..., arr[R], this returns:
     * the **sum** of elements which is in range [valueL, valueR]
     */
    ll sum_in_range(int L, int R, int valueL, int valueR) const {
        return calc_in_range(L, R, valueL, valueR).sum;
    }

    /* Returns sum of min(arr[i], X) for i in range [L,R]
     * assumes -1e9 <= arr[i] <= 1e9 for each i
     */
    ll sum_in_range_min(int L, int R, int X) const {
        return calc_in_range(L, R, -1e9, X).sum + 1LL * calc_in_range(L, R, X + 1,
            ↪ 1e9).cnt * X;
    }

    /* Returns sum of max(arr[i], X) for i in range [L,R]
     * assumes -1e9 <= arr[i] <= 1e9 for each i
     */
    ll sum_in_range_max(int L, int R, int X) const {
```

```
        return calc_in_range(L, R, X, 1e9).sum + 1LL * calc_in_range(L, R, -1e9, X -
        ↪ 1).cnt * X;
    }
private:
    struct Node {
        int lCh, rCh;
        struct Data {
            int cnt = 0;
            ll sum = 0;
        } data;
        Node(Data _data) : lCh(0), rCh(0), data(_data) {}
        Node(int _lCh, int _rCh, const vector<Node>& nodes) : lCh(_lCh), rCh(_rCh),
        ↪ data(combine(nodes[_lCh].data, nodes[_rCh].data)) {}
    };
    static Node::Data combine(const Node::Data& L, const Node::Data& R) {
        return Node::Data {
            L.cnt + R.cnt,
            L.sum + R.sum
        };
    }
    vector<Node> nodes;
    vector<int> roots, sorted;
    int allocateNode(const Node& v) {
        nodes.push_back(v);
        return (int) nodes.size() - 1;
    }
    int tl, tr, n;
    int update(int v, int l, int r, int pos, int val) {
        if (l == r) {
            return allocateNode(Node({nodes[v].data.cnt + 1, nodes[v].data.sum + val}));
        }
        int m = (l + r) / 2;
        if (pos <= m)
            return allocateNode(Node(update(nodes[v].lCh, l, m, pos, val), nodes[v].rCh,
            ↪ nodes));
        return allocateNode(Node(nodes[v].lCh, update(nodes[v].rCh, m + 1, r, pos, val),
        ↪ nodes));
    }
    int find_kth(int vl, int vr, int l, int r, int k) const {
        if (l == r)
            return l;
        int m = (l + r) / 2, left_count = nodes[nodes[vr].lCh].data.cnt -
        ↪ nodes[nodes[vl].lCh].data.cnt;
        if (left_count >= k) return find_kth(nodes[vl].lCh, nodes[vr].lCh, l, m, k);
        return find_kth(nodes[vl].rCh, nodes[vr].rCh, m + 1, r, k - left_count);
    }
    Node::Data calc_in_range(int L, int R, int valueL, int valueR) const {
        assert(L <= R && valueL <= valueR);
        int compL = lower_bound(sorted.begin(), sorted.end(), valueL) - sorted.begin();
        int compR = (int)upper_bound(sorted.begin(), sorted.end(), valueR) -
        ↪ sorted.begin() - 1;
        if (compL > compR) return Node::Data();
        return calc_in_range(roots[L], roots[R + 1], tl, tr, compL, compR);
    }
    Node::Data calc_in_range(int vl, int vr, int l, int r, int valueL, int valueR) const
    ↪ {
        if (valueR < l || r < valueL) return Node::Data();
        if (valueL <= l && r <= valueR) return {nodes[vr].data.cnt - nodes[vl].data.cnt,
        ↪ nodes[vr].data.sum - nodes[vl].data.sum};
        int m = (l + r) / 2;
        return combine(
```

```
        calc_in_range(nodes[vl].lCh, nodes[vr].lCh, l, m, valueL, valueR),
        calc_in_range(nodes[vl].rCh, nodes[vr].rCh, m + 1, r, valueL, valueR)
    );
    }
};
```

Listing 40: Segment Tree Beats

```
#pragma once

//status: not tested, used in various problems

struct SegTreeBeats {
    struct Node {
        ll sum;
        ll mx;
        ll secondMx;
        ll cntMx;
    };
    vector<Node> tree;
    vector<int> lazy;
    int n, size;
    const ll inf = 1e18;

    /*implement these*/
    const Node zero = {0, -inf, -inf, 0};
    Node combine(const Node& L, const Node& R) {
        Node par;
        par.sum = L.sum + R.sum;
        if (L.mx == R.mx)
            par.cntMx = L.cntMx + R.cntMx;
        else if (L.mx > R.mx)
            par.cntMx = L.cntMx;
        else
            par.cntMx = R.cntMx;
        par.mx = max(L.mx, R.mx);
        par.secondMx = -inf;
        for (ll val : {
            L.mx, R.mx, L.secondMx, R.secondMx
        }) {
            if (par.mx != val) {
                assert(par.mx > val);
                par.secondMx = max(par.secondMx, val);
            }
        }
        return par;
    }
    void push(int node, int start, int end) {
        if (start == end) return;
        assert(start < end);
        for (int child : {
            2 * node, 2 * node + 1
        }) {
            if (tree[child].mx <= tree[node].mx) continue;
            tree[child].sum -= (tree[child].mx - tree[node].mx) * tree[child].cntMx;
            tree[child].mx = tree[node].mx;
        }
    }
    SegTreeBeats(const vector<int>& arr) : n((int) arr.size()) {
```

```
size = 1;
while (size < n) size <= 1;
size <= 1;
tree.resize(size);
lazy.resize(size, 0);
build(arr, 1, 0, n - 1);
}

void build(const vector<int>& arr, int node, int start, int end) {
    if (start == end) {
        tree[node].sum = arr[start];
        tree[node].mx = arr[start];
        tree[node].secondMx = -inf;
        tree[node].cntMx = 1;
    } else {
        const int mid = (start + end) / 2;
        build(arr, 2 * node, start, mid);
        build(arr, 2 * node + 1, mid + 1, end);
        tree[node] = combine(tree[2 * node], tree[2 * node + 1]);
    }
}

//set a[i] = min(a[i], newMn), for i in range: [l,r]
void update(int l, int r, int newMn) {
    update(1, 0, n - 1, l, r, newMn);
}

void update(int node, int start, int end, int l, int r, int newMn) {
    assert(start <= end);
    push(node, start, end);
    if (start > r || end < l || tree[node].mx <= newMn) return;
    if (start >= l && end <= r && tree[node].secondMx < newMn) {
        tree[node].sum -= (tree[node].mx - newMn) * tree[node].cntMx;
        tree[node].mx = newMn;
        return;
    }
    assert(start < end);
    const int mid = (start + end) / 2;
    update(2 * node, start, mid, l, r, newMn);
    update(2 * node + 1, mid + 1, end, l, r, newMn);
    tree[node] = combine(tree[2 * node], tree[2 * node + 1]);
}

//query for sum/max in range [l,r]
Node query(int l, int r) {
    return query(1, 0, n - 1, l, r);
}

Node query(int node, int start, int end, int l, int r) {
    if (r < start || end < l) return zero;
    push(node, start, end);
    if (l <= start && end <= r) return tree[node];
    const int mid = (start + end) / 2;
    return combine(query(2 * node, start, mid, l, r), query(2 * node + 1, mid + 1,
        ↪ end, l, r));
}
};
```

Listing 41: Segment Tree

```
#pragma once

//status: tested on random inputs

const ll inf = 1e18;
```

```
struct SegmentTree {
    struct Node {
        ll sum = 0;
        ll mx = -inf;
        ll mn = inf;

        int l, r;

        ll lazy = 0;
    };

    //change to unordered_map<int, Node> for implicit seg tree. Although I've TLE'd
    ↪ multiple times doing this
    vector<Node> tree;
    int n;

    /**implement these**/
    Node combineChildren(const Node& L, const Node& R) {
        return Node {
            L.sum + R.sum,
            max(L.mx, R.mx),
            min(L.mn, R.mn),
            L.l,
            R.r
            //Note lazy value initializes to 0 here which is ok since we always push
            ↪ lazy down&reset before combining back up
        };
    }

    //what happens when delta is applied to every index in range [start,end]?
    void applyDeltaOnRange(int node, ll delta) {
        int start = tree[node].l, end = tree[node].r;
        tree[node].sum += (end - start + 1) * delta;
        tree[node].mx += delta;
        tree[node].mn += delta;
        if (start != end) {
            tree[2 * node].lazy += delta;
            tree[2 * node + 1].lazy += delta;
        }
    }

    //apply lazy value to range
    void pushLazy(int node) {
        ll& currLazy = tree[node].lazy;
        if (currLazy) {
            applyDeltaOnRange(node, currLazy);
            currLazy = 0;
        }
    }

    /*******/

    SegmentTree(const vector<ll>& arr) : n((int) arr.size()) {
        auto build = [&](auto&& buildPtr, int node, int start, int end) -> void {
            if (start == end) {
                tree[node] = Node {
                    arr[start],
                    arr[start],
                    arr[start],
                    start,
                    end
                };
            } else {

```

```
int mid = (start + end) / 2;
buildPtr(buildPtr, 2 * node, start, mid);
buildPtr(buildPtr, 2 * node + 1, mid + 1, end);
tree[node] = combineChildren(tree[2 * node], tree[2 * node + 1]);
}
};
int size = 1;
while (size < n) size <= 1;
size <= 1;
tree.resize(size);
build(build, 1, 0, n - 1);
}
//inclusive range: [l,r]
void update(int l, int r, ll diff) {
    auto update = [&](auto&& updatePtr, int node) -> void {
        pushLazy(node);
        int start = tree[node].l, end = tree[node].r;
        if (r < start || end < l) return;
        if (l <= start && end <= r) {
            applyDeltaOnRange(node, diff);
            return;
        }
        updatePtr(updatePtr, 2 * node);
        updatePtr(updatePtr, 2 * node + 1);
        tree[node] = combineChildren(tree[2 * node], tree[2 * node + 1]);
    };
    update(update, 1);
}
//inclusive range: [l,r]
Node query(int l, int r) {
    auto query = [&](auto&& queryPtr, int node) -> Node {
        int start = tree[node].l, end = tree[node].r;
        if (r < start || end < l) return Node(); //l,r is uninitialized -> access
        //means undefined behavior
        pushLazy(node);
        if (l <= start && end <= r) return tree[node];
        return combineChildren(
            queryPtr(queryPtr, 2 * node),
            queryPtr(queryPtr, 2 * node + 1)
        );
    };
    return query(query, 1);
}
};
};
```

Listing 42: Sparse Table

```
#pragma once

//usage:
// sparseTable<ll> st(arr, [](ll x, ll y) { return min(x,y); });
//
//to also get index of min element, do:
// sparseTable<pair<ll,int>> st(arr, [](auto x, auto y) { return min(x,y); });
//and initialize second to index. If there are multiple indexes of min element,
//it'll return the smallest (left-most) one
//
//status: tested on random inputs, also on https://judge.yosupo.jp/problem/staticrmq
template <class T>
struct sparseTable {
```

```
vector<int> log2;
vector<vector<T>> dp;
function<T(const T&, const T&) > func;
sparseTable(const vector<T>& arr, const function<T(const T&, const T&) >& _func) :
    func(_func) {
    const int n = arr.size();
    log2.resize(n + 1, -1);
    for (int i = 1; i <= n; ++i) log2[i] = 1 + log2[i / 2];
    dp.resize(log2[n] + 1, arr);
    for (int i = 1; i <= log2[n]; ++i) {
        for (int j = 0; j + (1 << i) - 1 < n; ++j)
            dp[i][j] = func(dp[i - 1][j], dp[i - 1][j + (1 << (i - 1))]);
    }
}
//returns func of arr[l], arr[l+1], ..., arr[r]
T query(int l, int r) const {
    const int x = log2[r - l + 1];
    return func(dp[x][l], dp[x][r - (1 << x) + 1]);
}
};
```

Listing 43: RANGE DATA STRUCTURES

Listing 44: KMP

```
#pragma once

//usage:
// KMP_Match<string> kmp(needle);
//or
// KMP_Match<vector<int>> kmp(needle);
//
//status: tested on random inputs
template <class T>
struct KMP_Match {
public:
    KMP_Match(const T& needle_) : prefixFunction(needle_.size() + 1, 0), needle(needle_)
        {}
    for (int i = 1, p = 0; i < (int) needle.size(); i++) {
        update(needle[i], p);
        prefixFunction[i + 1] = p;
    }
};

// if haystack = "bananas"
// needle = "ana"
//
// then we find 2 matches:
// bananas
// _ana_
// __ana_
// 0123456 (indexes)
// and KMP_Match::find returns {1,3} - the indexes in haystack where
// each match starts.
//
// You can also pass in false for "all" and KMP_Match::find will only
// return the first match: {1}. Useful for checking if there exists
// some match:
```

```
//
// KMP_Match::find(<haystack>,false).size() > 0
vector<int> find(const T& haystack, bool all = true) const {
    vector<int> matches;
    for (int i = 0, p = 0; i < (int) haystack.size(); i++) {
        update(haystack[i], p);
        if (p == (int) needle.size()) {
            matches.push_back(i - (int) needle.size() + 1);
            if (!all) return matches;
            p = prefixFunction[p];
        }
    }
    return matches;
}

private:
void update(char val, int& p) const {
    while (p && val != needle[p]) p = prefixFunction[p];
    if (val == needle[p]) p++;
}

vector<int> prefixFunction;
T needle;
```

Listing 45: Rolling Hash

```
#pragma once

//usage:
// Hash<string> h(s);
//or
// Hash<vector<int>> h(arr);
// assumes 0 < arr[i] < 1e9+5 = 'base'
// here, for negatives or longlongs, compress values to {1,2,...,n} and make sure
//   ↪ 'base' is > n
//
//status: tested on random inputs, and on https://judge.yosupo.jp/problem/zalgorithms
template <class T>
struct Hash {
    // 'base' should be relatively prime with all mods and *strictly* larger than max
    //   ↪ element
    // larger/smaller 'base' *doesn't* change collision odds
    // ideally 'base' would be random to avoid getting hacked
    const int base = 1e9 + 5;
    // From C.R.T., this is the same as having a single mod = product of 'mods' = n
    // probability of collision is 1/n
    // probability that k unique strings have k unique hashes = (1/n)^k * (n permute k)
    //   ↪ from birthday paradox
    const vector<int> mods = { (int) 1e9 + 7, (int) 1e9 + 9, (int) 1e9 + 21, (int) 1e9 +
        ↪ 33, (int) 1e9 + 87 };
    vector<vector<int>> prefix, powB;

    Hash(const T& s) :
        prefix(mods.size(), vector<int> (s.size() + 1, 0)),
        powB(mods.size(), vector<int> (s.size() + 1, 1)) {
        // negatives may cause trivial collisions, when s[i]%mod = s[j]%mod, but s[i] !=
        //   ↪ s[j]
        // 0's cause trivial collisions: "0" and "00" both hash to 0
        for (auto val : s) assert(0 < val && val < base);
        for (int i = 0; i < (int) mods.size(); i++) {
            for (int j = 0; j < (int) s.size(); j++) {
```

```
                powB[i][j + 1] = 1LL * powB[i][j] * base % mods[i];
                prefix[i][j + 1] = (1LL * base * prefix[i][j] + s[j]) % mods[i];
            }
        }
    }

    // returns hashes of substring/subarray [L,R] inclusive, one hash per mod
    vector<int> getHashes(int L, int R) const {
        assert(0 <= L && L <= R && R + 1 < (int) prefix[0].size());
        vector<int> res(mods.size());
        for (int i = 0; i < (int) mods.size(); i++) {
            res[i] = prefix[i][R + 1] - 1LL * prefix[i][L] * powB[i][R - L + 1] %
                ↪ mods[i];
            if (res[i] < 0) res[i] += mods[i];
        }
        return res;
    }
};
```

Listing 46: Rotational Equivalence

```
#pragma once

// Checks if two arrays are rotationally equivalent
// uses KMP with doubling trick
// usage:
//   rot_eq<string>(s1, s2)
// or
//   rot_eq<vector<int>>(arr1, arr2)
//
//status: tested on random inputs, also on https://open.kattis.com/problems/maze

template <class T>
bool rot_eq(const T& a, const T& b) {
    if (a.size() != b.size()) return false;
    if (a.empty()) return true;
    int n = a.size();
    vector<int> fail(n + 1, 0);
    auto update = [&](int val, int& p) -> void {
        while (p && val != a[p]) p = fail[p];
        if (val == a[p]) p++;
    };
    for (int i = 1, p = 0; i < n; i++) {
        update(a[i], p);
        fail[i + 1] = p;
    }
    for (int i = 0, p = 0; i < 2 * n; i++) {
        update(b[i % n], p);
        if (p == n) return true;
    }
    return false;
}
```

Listing 47: Suffix Array

```
#pragma once

// modified from here: https://judge.yosupo.jp/submission/37410
//
```

```
//status: tested on random inputs, and on
↳ https://open.kattis.com/problems/automatictrading
class suffix_array {
public:
    //computes suffix array, lcp array, and then sparse table over lcp array
    //O(n log n)
    suffix_array(const string& s) {
        int n = (int) s.size();
        vector<int> arr(n);
        for (int i = 0; i < n; i++)
            arr[i] = s[i];
        sa_ = sa_is(arr, 255);
        inv_sa_.resize(n);
        for (int i = 0; i < n; i++)
            inv_sa_[sa_[i]] = i;
        lcp_ = lcp_array(arr, sa_);
        init_min_sparse_table(lcp_);
    }

    //length of longest common prefix of suffixes s[idx1..n], s[idx2..n], 0-based
    ↳ indexing
    //You can check if two substrings s[L1..R1], s[L2..R2] are equal in O(1) by:
    //
    //R2-L2 == R1-L1 ⇔ suffix_array::longest_common_prefix(L1, L2) >= R2-L2+1
    int longest_common_prefix(int idx1, int idx2) const {
        if (idx1 == idx2) return (int) sa_.size() - idx1;
        idx1 = inv_sa_[idx1];
        idx2 = inv_sa_[idx2];
        if (idx1 > idx2) swap(idx1, idx2);
        int lg = log2_[idx2 - idx1];
        return min(dp_[lg][idx1], dp_[lg][idx2 - (1 << lg)]);
    }

    //returns true if suffix s[idx1..n] < s[idx2..n]
    //(so false if idx1 == idx2)
    //O(1)
    bool less(int idx1, int idx2) const {
        return inv_sa_[idx1] < inv_sa_[idx2];
    }

    vector<int> get_suffix_array() const {
        return sa_;
    }

    vector<int> get_lcp_array() const {
        return lcp_;
    }
private:
    vector<int> sa_, lcp_, inv_sa_, log2_;
    vector<vector<int>> dp_;

    // SA-IS, linear-time suffix array construction
    // Reference:
    // G. Nong, S. Zhang, and W. H. Chan,
    // Two Efficient Algorithms for Linear Time Suffix Array Construction
    vector<int> sa_is(const vector<int>& s, int upper) {
        int n = (int) s.size();
        if (n == 0) return {};
        if (n == 1) return {0};
        if (n == 2) {
            if (s[0] < s[1]) {
```

```
                return {0, 1};
            } else {
                return {1, 0};
            }
        }
        vector<int> sa(n);
        vector<bool> ls(n);
        for (int i = n - 2; i >= 0; i--)
            ls[i] = (s[i] == s[i + 1]) ? ls[i + 1] : (s[i] < s[i + 1]);
        vector<int> sum_l(upper + 1), sum_s(upper + 1);
        for (int i = 0; i < n; i++) {
            if (!ls[i])
                sum_s[s[i]]++;
            else
                sum_l[s[i] + 1]++;
        }
        for (int i = 0; i <= upper; i++) {
            sum_s[i] += sum_l[i];
            if (i < upper) sum_l[i + 1] += sum_s[i];
        }
        vector<int> buf(upper + 1);
        auto induce = [&](const vector<int>& lms) {
            fill(sa.begin(), sa.end(), -1);
            fill(buf.begin(), buf.end(), 0);
            copy(sum_s.begin(), sum_s.end(), buf.begin());
            for (auto d : lms) {
                if (d == n) continue;
                sa[buf[s[d]]++] = d;
            }
            copy(sum_l.begin(), sum_l.end(), buf.begin());
            sa[buf[s[n - 1]]++] = n - 1;
            for (int i = 0; i < n; i++) {
                int v = sa[i];
                if (v >= 1 && !ls[v - 1])
                    sa[buf[s[v - 1]]++] = v - 1;
            }
            copy(sum_l.begin(), sum_l.end(), buf.begin());
            for (int i = n - 1; i >= 0; i--) {
                int v = sa[i];
                if (v >= 1 && ls[v - 1])
                    sa[--buf[s[v - 1] + 1]] = v - 1;
            }
        };
        vector<int> lms_map(n + 1, -1);
        int m = 0;
        for (int i = 1; i < n; i++) {
            if (!ls[i - 1] && ls[i])
                lms_map[i] = m++;
        }
        vector<int> lms;
        lms.reserve(m);
        for (int i = 1; i < n; i++) {
            if (!ls[i - 1] && ls[i])
                lms.push_back(i);
        }
        induce(lms);
        if (m) {
            vector<int> sorted_lms;
            sorted_lms.reserve(m);
            for (int v : sa) {
                if (lms_map[v] != -1) sorted_lms.push_back(v);
```

```

}
vector<int> rec_s(m);
int rec_upper = 0;
rec_s[lms_map[sorted_lms[0]]] = 0;
for (int i = 1; i < m; i++) {
    int l = sorted_lms[i - 1], r = sorted_lms[i];
    int end_l = (lms_map[l] + 1 < m) ? lms[lms_map[l] + 1] : n;
    int end_r = (lms_map[r] + 1 < m) ? lms[lms_map[r] + 1] : n;
    bool same = true;
    if (end_l - 1 != end_r - r)
        same = false;
    else {
        while (l < end_l) {
            if (s[l] != s[r])
                break;
            l++;
            r++;
        }
        if (l == n || s[l] != s[r]) same = false;
    }
    if (!same) rec_upper++;
    rec_s[lms_map[sorted_lms[i]]] = rec_upper;
}
auto rec_sa =
    sa_is(rec_s, rec_upper);
for (int i = 0; i < m; i++)
    sorted_lms[i] = lms[rec_sa[i]];
induce(sorted_lms);
}
return sa;
}

// Reference:
// T. Kasai, G. Lee, H. Arimura, S. Arikawa, and K. Park,
// Linear-Time Longest-Common-Prefix Computation in Suffix Arrays and Its
// Applications
vector<int> lcp_array(const vector<int>& s, const vector<int>& sa) {
    int n = s.size(), k = 0;
    vector<int> lcp(n, 0);
    vector<int> rank(n, 0);
    for (int i = 0; i < n; i++) rank[sa[i]] = i;
    for (int i = 0; i < n; i++, k ? k-- : 0) {
        if (rank[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = sa[rank[i] + 1];
        while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
        lcp[rank[i]] = k;
    }
    return lcp;
}

void init_min_sparse_table(const vector<int>& arr) {
    const int n = arr.size();
    log2_.resize(n + 1, -1);
    for (int i = 1; i <= n; ++i) log2_[i] = 1 + log2_[i / 2];
    dp_.resize(log2_[n] + 1, arr);
    for (int i = 1; i <= log2_[n]; ++i) {
        for (int j = 0; j + (1 << i) - 1 < n; ++j)
            dp_[i][j] = min(dp_[i - 1][j], dp_[i - 1][j + (1 << (i - 1))]);
    }
}

```

```

    }
};

```

Listing 48: Trie

```

#pragma once

//status: not tested, but used on various problems

const int K = 26; //character size

struct node {
    bool leaf = 0;
    int next[K], id, p = -1;
    char pch;
    node(int _p = -1, char ch = '#') : p(_p), pch(ch) {
        fill(next, next + K, -1);
    }
};

vector<node> t(1); //adj list

void add_string(const string& s, int id) {
    int c = 0;
    for (char ch : s) {
        int v = ch - 'a';
        if (t[c].next[v] == -1) {
            t[c].next[v] = t.size();
            t.emplace_back(c, ch);
        }
        c = t[c].next[v];
    }
    t[c].leaf = 1;
    t[c].id = id;
}

void remove_string(const string& s) {
    int c = 0;
    for (char ch : s) {
        int v = ch - 'a';
        if (t[c].next[v] == -1)
            return;
        c = t[c].next[v];
    }
    t[c].leaf = 0;
}

int find_string(const string& s) {
    int c = 0;
    for (char ch : s) {
        int v = ch - 'a';
        if (t[c].next[v] == -1)
            return -1;
        c = t[c].next[v];
    }
    if (!t[c].leaf) return -1;
    return t[c].id;
}

```