Detector	Pilatus3 S 6M	Rayonix MX 300 HS	ADSC HF-4M
Mode	Photon Counting PAD	Integrating CCD	Counting or Integrating PAD mode selectable pixel by pixel
Active Area (mm x mm)	423.6 x 434.6	300 x 300	340 x 310
Gaps	8.5 % of active area	50 µm wide (0.1 % of active area)	8.5 % of active area
# Edge Pixels	81,840 (1.3%)	245,760 (1.7%) 2 x 2 binning	81,920 (2.0%)
Nominal Pixel Size (µm x µm)	172 x 172	1 x 1 bin: 39 x 39 2 x 2 bin: 78 x 78 3 x 3 bin: 117 x 117 4 x 4 bin: 156 x 156 etc to 10 x 10 binning	150 x 150
Nominal # Pixels	6,224,001	1 x 1 bin: 58,982,400 2 x 2 bin: 14,745,600 3 x 3 bin: 6,553,600 4 x 4 bin: 3,686,400 etc to 10 x 10 binning	4,194,304
Maximum Readout Rate (Hz)	25	bin High Speed Low Noise 1 x 1 3 1.5 2 x 2 10 6 3 x 3 20 12 4 x 4 35 20 etc. to 10 x 10 binning	200 (50 w/o option)
Deadtime (ms)	2	1	0.001
Sensor	450 µm Si	40 µm Gd2O2S	500 µm Si
QE	0.96	0.8	0.8
Read Noise	0	8 e/pixel (fast) 4 e/pixel (slow)	0 (counting) 0.2 x-ray (integrating)
Point Spread Function FWHM (µm	172	100	150
Max Photons per pixel @ 12 KeV	1,048,576 (20 bits)	50,000 (16 bits, fast mode) 100,000 (18 bits, slow mode)	4,194,304 (22 bits counting) 200,000,000 (integrating)