LS-CAT PGPMAC

Generated by Doxygen 1.8.2

Wed Jan 23 2013 10:19:09

Contents

1	The	LS-CAT	Г pgpmac	Project	1
2	Nam	nespace	Index		5
	2.1	Names	space List		5
3	Data	Struct	ure Index		7
	3.1	Data S	Structures		7
4	File	Index			9
	4.1	File Lis	st		9
5	Nam	nespace	Documer	ntation	11
	5.1	iniPars	er Names	pace Reference	11
		5.1.1	Variable l	Documentation	11
			5.1.1.1	ip	11
	5.2	mk_pg	pmac_redi	is Namespace Reference	11
		5.2.1	Variable l	Documentation	12
			5.2.1.1	b	12
			5.2.1.2	bi_list	12
			5.2.1.3	f	12
			5.2.1.4	fnc	12
			5.2.1.5	hard_ini	12
			5.2.1.6	hard_ini_fields	12
			5.2.1.7	head	12
			5.2.1.8	hi	12
			5.2.1.9	1	13
			5.2.1.10	motor_dict	13
			5.2.1.11	motor_field_lists	13
			5.2.1.12	motor_presets	13
			5.2.1.13	p	13
			5.2.1.14	pi	13
			5.2.1.15	ppos	13
			52116	nref ini	13

ii CONTENTS

			5.2.1.17 v	3
			5.2.1.18 x	3
			5.2.1.19 y	3
			5.2.1.20 zoom_settings	3
6	Data	Structi	re Documentation 15	5
U	6.1		er.iniParser Class Reference	
	0.1	6.1.1	Detailed Description	
		_	•	
		6.1.2	Constructor & Destructor Documentation	
			6.1.2.1init	
		6.1.3	Member Function Documentation	
			6.1.3.1 get	
			6.1.3.2 has_option	
			6.1.3.3 has_section	ô
			6.1.3.4 options	6
			6.1.3.5 read	7
			6.1.3.6 sections	7
		6.1.4	Field Documentation	7
			6.1.4.1 f	7
			6.1.4.2 sd	7
	6.2	Isevent	s_listener_struct Struct Reference	7
		6.2.1	Detailed Description	8
		6.2.2	Field Documentation	8
			6.2.2.1 cb	8
			6.2.2.2 next	8
			6.2.2.3 raw_regexp	8
			6.2.2.4 re	8
	6.3	Isevent	s_queue_struct Struct Reference	8
		6.3.1	Detailed Description	9
		6.3.2	Field Documentation	9
			6.3.2.1 evp	9
	6.4	Isloggir	ng queue struct Struct Reference	9
		6.4.1	Detailed Description	9
		6.4.2	Field Documentation	
		•	6.4.2.1 lmsg	
			6.4.2.2 Itime	
	6.5	Ispa d	emandairrights_struct Struct Reference	
	0.0	6.5.1	Detailed Description	
		6.5.2	Field Documentation	
		0.0.2		
			6.5.2.1 cond	J

CONTENTS

		6.5.2.2	mutex	20
		6.5.2.3	new_value_ready	20
6.6	lspg_g	etcenter_s	struct Struct Reference	20
	6.6.1	Detailed	Description	21
	6.6.2	Field Doo	cumentation	21
		6.6.2.1	cond	21
		6.6.2.2	dax	21
		6.6.2.3	dax_isnull	21
		6.6.2.4	day	22
		6.6.2.5	day_isnull	22
		6.6.2.6	daz	22
		6.6.2.7	daz_isnull	22
		6.6.2.8	dcx	22
		6.6.2.9	dcx_isnull	22
		6.6.2.10	dcy	22
		6.6.2.11	dcy_isnull	22
		6.6.2.12	mutex	22
		6.6.2.13	new_value_ready	22
		6.6.2.14	no_rows_returned	23
		6.6.2.15	zoom	23
		6.6.2.16	zoom_isnull	23
6.7	lspg_g	etcurrents	ampleid_struct Struct Reference	23
	6.7.1	Detailed	Description	23
	6.7.2	Field Doo	cumentation	23
		6.7.2.1	cond	23
		6.7.2.2	getcurrentsampleid	24
		6.7.2.3	getcurrentsampleid_isnull	24
		6.7.2.4	mutex	24
		6.7.2.5	new_value_ready	24
		6.7.2.6	no_rows_returned	24
6.8	lspg_lo	ck_detect	or_struct Struct Reference	24
	6.8.1	Detailed	Description	24
	6.8.2	Field Doo	cumentation	24
		6.8.2.1	cond	24
		6.8.2.2	mutex	25
		6.8.2.3	new_value_ready	25
6.9	lspg_lo	ock_diffract	tometer_struct Struct Reference	25
	6.9.1	Detailed	Description	25
	6.9.2	Field Doo	cumentation	25
		6.9.2.1	cond	25

iv CONTENTS

		6.9.2.2	mutex	25
		6.9.2.3	new_value_ready	25
6.10	lspg_ne	extsample_	_struct Struct Reference	25
	6.10.1	Detailed [Description	26
	6.10.2	Field Doc	sumentation	26
		6.10.2.1	cond	26
		6.10.2.2	mutex	26
		6.10.2.3	new_value_ready	26
		6.10.2.4	nextsample	26
		6.10.2.5	nextsample_isnull	26
		6.10.2.6	no_rows_returned	27
6.11	lspg_ne	extshot_str	ruct Struct Reference	27
	6.11.1	Detailed [Description	29
	6.11.2	Field Doc	cumentation	29
		6.11.2.1	active	29
		6.11.2.2	active2	30
		6.11.2.3	active2_isnull	30
		6.11.2.4	active_isnull	30
		6.11.2.5	ax	30
		6.11.2.6	ax2	30
		6.11.2.7	ax2_isnull	30
		6.11.2.8	ax_isnull	30
		6.11.2.9	ay	30
		6.11.2.10	ay2	30
		6.11.2.11	ay2_isnull	30
		6.11.2.12	ay_isnull	30
		6.11.2.13	az	31
		6.11.2.14	az2	31
		6.11.2.15	az2_isnull	31
		6.11.2.16	az_isnull	31
		6.11.2.17	cond	31
		6.11.2.18	cx	31
		6.11.2.19	cx2	31
		6.11.2.20	cx2_isnull	31
		6.11.2.21	cx_isnull	31
		6.11.2.22	cy	31
		6.11.2.23	cy2	32
		6.11.2.24	cy2_isnull	32
		6.11.2.25	cy_isnull	32
		6.11.2.26	dsdir	32

CONTENTS

6.11.2.27 dsdir_isnull
6.11.2.28 dsdist
6.11.2.29 dsdist2
6.11.2.30 dsdist2_isnull
6.11.2.31 dsdist_isnull
6.11.2.32 dsexp
6.11.2.33 dsexp2
6.11.2.34 dsexp2_isnull
6.11.2.35 dsexp_isnull
6.11.2.36 dshpid
6.11.2.37 dshpid_isnull
6.11.2.38 dskappa
6.11.2.39 dskappa2
6.11.2.40 dskappa2_isnull
6.11.2.41 dskappa_isnull
6.11.2.42 dsnrg
6.11.2.43 dsnrg2
6.11.2.44 dsnrg2_isnull
6.11.2.45 dsnrg_isnull
6.11.2.46 dsomega
6.11.2.47 dsomega2
6.11.2.48 dsomega2_isnull
6.11.2.49 dsomega_isnull
6.11.2.50 dsoscaxis
6.11.2.51 dsoscaxis2
6.11.2.52 dsoscaxis2_isnull
6.11.2.53 dsoscaxis_isnull
6.11.2.54 dsowidth
6.11.2.55 dsowidth2
6.11.2.56 dsowidth2_isnull
6.11.2.57 dsowidth_isnull
6.11.2.58 dsphi
6.11.2.59 dsphi2
6.11.2.60 dsphi2_isnull
6.11.2.61 dsphi_isnull
6.11.2.62 dspid
6.11.2.63 dspid_isnull
6.11.2.64 mutex
6.11.2.65 new_value_ready
6.11.2.66 no_rows_returned

vi CONTENTS

		6.11.2.67 sfn	 . 36
		6.11.2.68 sfn_isnull	 . 36
		6.11.2.69 sindex	 . 36
		6.11.2.70 sindex2	 . 36
		6.11.2.71 sindex2_isnull	 . 36
		6.11.2.72 sindex_isnull	 . 36
		6.11.2.73 skey	 . 36
		6.11.2.74 skey_isnull	 . 37
		6.11.2.75 sstart	 . 37
		6.11.2.76 sstart2	 . 37
		6.11.2.77 sstart2_isnull	 . 37
		6.11.2.78 sstart_isnull	 . 37
		6.11.2.79 stype	 . 37
		6.11.2.80 stype2	 . 37
		6.11.2.81 stype2_isnull	 . 37
		6.11.2.82 stype_isnull	 . 37
6.12	lspg_se	eq_run_prep_struct Struct Reference	 . 37
	6.12.1	Detailed Description	 . 38
	6.12.2	Field Documentation	 . 38
		6.12.2.1 cond	 . 38
		6.12.2.2 mutex	 . 38
		6.12.2.3 new_value_ready	
6.13	lspg_st	arttransfer_struct Struct Reference	 . 38
	6.13.1	Detailed Description	 . 39
	6.13.2	Field Documentation	 . 39
		6.13.2.1 cond	 . 39
		6.13.2.2 mutex	 . 39
		6.13.2.3 new_value_ready	 . 39
		6.13.2.4 no_rows_returned	 . 39
		6.13.2.5 starttransfer	 . 39
6.14	lspg_w	ait_for_detector_struct Struct Reference	 . 39
	6.14.1	Detailed Description	 . 40
	6.14.2	Field Documentation	 . 40
		6.14.2.1 cond	 . 40
		6.14.2.2 mutex	 . 40
		6.14.2.3 new_value_ready	 . 40
6.15		aitcryo_struct Struct Reference	
		Detailed Description	
	6.15.2	Field Documentation	
		6.15.2.1 cond	 . 40

CONTENTS vii

		6.15.2.2	mutex	 41
		6.15.2.3	new_value_ready	 41
6.16	IspgQu	eryQueue	eStruct Struct Reference	 41
	6.16.1	Detailed	Description	 41
	6.16.2	Field Doo	cumentation	 41
		6.16.2.1	onResponse	 41
		6.16.2.2	qs	 41
6.17	Ispmac	_ascii_buf	Iffers_struct Struct Reference	 42
	6.17.1	Detailed	Description	 42
	6.17.2	Field Doo	cumentation	 42
		6.17.2.1	command_buf	 42
		6.17.2.2	command_buf_cc	 42
		6.17.2.3	command_str	 42
		6.17.2.4	response_buf	 42
		6.17.2.5	response_n	 42
		6.17.2.6	response_str	 42
6.18	Ispmac	_bi_struct	t Struct Reference	 42
	6.18.1	Detailed	Description	 43
	6.18.2	Field Doo	cumentation	 43
		6.18.2.1	changeEventOff	 43
		6.18.2.2	changeEventOn	 43
		6.18.2.3	first_time	 43
		6.18.2.4	mask	 43
		6.18.2.5	mutex	 44
		6.18.2.6	position	 44
		6.18.2.7	previous	 44
		6.18.2.8	ptr	 44
6.19	Ispmac	_cmd_que	eue_struct Struct Reference	 44
	6.19.1	Detailed	Description	 44
	6.19.2	Field Doo	cumentation	 45
		6.19.2.1	event	 45
		6.19.2.2	no_reply	 45
		6.19.2.3	onResponse	 45
		6.19.2.4	pcmd	 45
		6.19.2.5	time_sent	 45
6.20	Ispmac	_dpascii_d	queue_struct Struct Reference	 45
	6.20.1	Detailed	Description	 45
	6.20.2	Field Doo	cumentation	 45
		6.20.2.1	event	 45
		6.20.2.2	pl	 46

viii CONTENTS

6.21	Ispmac	c_motor_struct Struct Reference	16
	6.21.1	Detailed Description	18
	6.21.2	Field Documentation	18
		6.21.2.1 active	18
		6.21.2.2 active_init	18
		6.21.2.3 actual_pos_cnts	18
		6.21.2.4 actual_pos_cnts_p	18
		6.21.2.5 axis	18
		6.21.2.6 command_sent	19
		6.21.2.7 cond	19
		6.21.2.8 coord_num	19
		6.21.2.9 dac_mvar	19
		6.21.2.10 home	19
		6.21.2.11 homing	19
		6.21.2.12 inactive_init	19
		6.21.2.13 lut	19
		6.21.2.14 max_accel	19
		6.21.2.15 max_pos	50
		6.21.2.16 max_speed	50
		6.21.2.17 min_pos	50
		6.21.2.18 motion_seen	50
		6.21.2.19 motor_num	50
			50
		6.21.2.21 mutex	50
		6.21.2.22 name	50
		6.21.2.23 neg_limit_hit	50
		6.21.2.24 neutral_pos	51
		6.21.2.25 nlut	51
		6.21.2.26 not_done	51
		6.21.2.27 pos_limit_hit	51
		6.21.2.28 position	51
		6.21.2.29 pq	51
		6.21.2.30 precision	51
		6.21.2.31 printf_fmt	51
		6.21.2.32 read	51
		6.21.2.33 read_mask	52
		6.21.2.34 read_ptr	52
		_	52
		-	52
		6.21.2.37 reported_position	52

CONTENTS

	6.21.2.38	3 requested_pos_cnts	. 52
	6.21.2.39	9 requested_position	. 52
	6.21.2.40) status1	. 52
	6.21.2.41	l status1_p	. 52
	6.21.2.42	2 status2	. 53
	6.21.2.43	3 status2_p	. 53
	6.21.2.44	4 status_str	. 53
	6.21.2.45	5 u2c	. 53
	6.21.2.46	3 unit	. 53
	6.21.2.47	7 update_resolution	. 53
	6.21.2.48	3 win	. 53
	6.21.2.49	9 write_fmt	. 53
6.22 lsr	redis_obj_struct	t Struct Reference	. 53
6.3	22.1 Detailed I	Description	. 54
6.5	22.2 Field Doo	cumentation	. 54
	6.22.2.1	avalue	. 54
	6.22.2.2	bvalue	. 54
	6.22.2.3	cond	. 55
	6.22.2.4	cvalue	. 55
	6.22.2.5	dvalue	. 55
	6.22.2.6	events_name	. 55
	6.22.2.7	hits	. 55
	6.22.2.8	key	. 55
	6.22.2.9	lvalue	. 55
	6.22.2.10	O mutex	. 55
	6.22.2.11	I next	. 55
	6.22.2.12	2 valid	. 56
	6.22.2.13	3 value	. 56
	6.22.2.14	1 value_length	. 56
	6.22.2.15	5 wait_for_me	. 56
6.23 lst	timer_list_struct	t Struct Reference	. 56
6.3	23.1 Detailed I	Description	. 57
6.3	23.2 Field Doo	cumentation	. 57
	6.23.2.1	delay_nsecs	. 57
	6.23.2.2	delay_secs	. 57
	6.23.2.3	event	. 57
	6.23.2.4	init_nsecs	. 57
	6.23.2.5	init_secs	. 57
	6.23.2.6	last_nsecs	. 57
	6.23.2.7	last_secs	. 57

CONTENTS

	6.23.2.8 ncalls	58
	6.23.2.9 next_nsecs	58
	6.23.2.10 next_secs	58
	6.23.2.11 shots	58
6.24 md2St	atusStruct Struct Reference	58
6.24.1	Detailed Description	59
6.24.2	Field Documentation	60
	6.24.2.1 acc11c_1	60
	6.24.2.2 acc11c_2	60
	6.24.2.3 acc11c_3	60
	6.24.2.4 acc11c_5	60
	6.24.2.5 acc11c_6	60
	6.24.2.6 alignx_act_pos	60
	6.24.2.7 alignx_status_1	60
	6.24.2.8 alignx_status_2	60
	6.24.2.9 aligny_act_pos	60
	6.24.2.10 aligny_status_1	60
	6.24.2.11 aligny_status_2	60
	6.24.2.12 alignz_act_pos	60
	6.24.2.13 alignz_status_1	61
	6.24.2.14 alignz_status_2	61
	6.24.2.15 analyzer_act_pos	61
	6.24.2.16 analyzer_status_1	61
	6.24.2.17 analyzer_status_2	61
	6.24.2.18 aperturey_act_pos	61
	6.24.2.19 aperturey_status_1	61
	6.24.2.20 aperturey_status_2	61
	6.24.2.21 aperturez_act_pos	61
	6.24.2.22 aperturez_status_1	61
	6.24.2.23 aperturez_status_2	61
	6.24.2.24 back_dac	61
	6.24.2.25 capy_act_pos	62
	6.24.2.26 capy_status_1	62
	6.24.2.27 capy_status_2	62
	6.24.2.28 capz_act_pos	62
	6.24.2.29 capz_status_1	62
	6.24.2.30 capz_status_2	62
	6.24.2.31 centerx_act_pos	62
	6.24.2.32 centerx_status_1	62
	6.24.2.33 centerx_status_2	62

CONTENTS xi

		6.24.2.34 centery_act_pos	62
		6.24.2.35 centery_status_1	62
		6.24.2.36 centery_status_2	62
		6.24.2.37 dummy1	63
		6.24.2.38 dummy2	63
		6.24.2.39 dummy3	63
		6.24.2.40 dummy4	63
		6.24.2.41 dummy5	63
		6.24.2.42 dummy6	63
		6.24.2.43 dummy7	63
		6.24.2.44 dummy8	63
		6.24.2.45 dummy9	63
		6.24.2.46 dummyA	63
		6.24.2.47 dummyB	63
		6.24.2.48 front_dac	63
		6.24.2.49 fs_has_opened	64
		6.24.2.50 fs_has_opened_globally	64
		6.24.2.51 fs_is_open	64
		6.24.2.52 kappa_act_pos	64
		6.24.2.53 kappa_status_1	64
		6.24.2.54 kappa_status_2	64
		6.24.2.55 moving_flags	64
		6.24.2.56 number_passes	64
		6.24.2.57 omega_act_pos	64
		6.24.2.58 omega_status_1	64
		6.24.2.59 omega_status_2	64
		6.24.2.60 phi_act_pos	64
		6.24.2.61 phi_status_1	65
		6.24.2.62 phi_status_2	65
		6.24.2.63 phiscan	65
		6.24.2.64 scint_act_pos	65
		6.24.2.65 scint_piezo	65
		6.24.2.66 scint_status_1	65
		6.24.2.67 scint_status_2	65
		6.24.2.68 zoom_act_pos	65
		6.24.2.69 zoom_status_1	65
		6.24.2.70 zoom_status_2	65
6.25	tagEthe	ernetCmd Struct Reference	65
	6.25.1	Detailed Description	66
	6.25.2	Field Documentation	66

xii CONTENTS

			6.25.2.1	bData	66
			6.25.2.2	Request	66
			6.25.2.3	RequestType	66
			6.25.2.4	wIndex	66
			6.25.2.5	wLength	66
			6.25.2.6	wValue	67
7	File	Docume	entation		69
	7.1	iniPars	er.py File F	Reference	69
	7.2	kvredis	s.c File Ref	erence	69
		7.2.1	Macro De	efinition Documentation	71
			7.2.1.1	LS_PG_QUERY_QUEUE_LENGTH	71
			7.2.1.2	LS_PG_QUERY_STRING_LENGTH	71
			7.2.1.3	LS_PG_STATE_IDLE	71
			7.2.1.4	LS_PG_STATE_INIT	71
			7.2.1.5	LS_PG_STATE_INIT_POLL	72
			7.2.1.6	LS_PG_STATE_RECV	72
			7.2.1.7	LS_PG_STATE_RESET	72
			7.2.1.8	LS_PG_STATE_RESET_POLL	72
			7.2.1.9	LS_PG_STATE_SEND	72
			7.2.1.10	LS_PG_STATE_SEND_FLUSH	72
		7.2.2	Typedef [Documentation	72
			7.2.2.1	lspg_query_queue_t	72
		7.2.3	Function	Documentation	72
			7.2.3.1	addRead	72
			7.2.3.2	addWrite	72
			7.2.3.3	cleanup	73
			7.2.3.4	debugCB	73
			7.2.3.5	delRead	73
			7.2.3.6	delWrite	74
			7.2.3.7	fd_service	74
			7.2.3.8	lspg_allkvs_cb	74
			7.2.3.9	lspg_flush	75
			7.2.3.10	lspg_next_state	75
			7.2.3.11	lspg_notice_processor	76
			7.2.3.12	lspg_pg_connect	76
			7.2.3.13	lspg_pg_service	77
			7.2.3.14	lspg_query_next	79
			7.2.3.15	lspg_query_push	79
			7.2.3.16	lspg_query_reply_next	79

CONTENTS xiii

		7.2.3.17	lspg_query_reply_peek	80
		7.2.3.18	lspg_receive	80
		7.2.3.19	lspg_send_next_query	81
		7.2.3.20	main	81
		7.2.3.21	redisDisconnectCB	83
	7.2.4	Variable l	Documentation	83
		7.2.4.1	cmdac	83
		7.2.4.2	cmdfd	83
		7.2.4.3	kvseq	83
		7.2.4.4	ls_pg_state	83
		7.2.4.5	lspg_connectPoll_response	84
		7.2.4.6	lspg_query_queue	84
		7.2.4.7	lspg_query_queue_off	84
		7.2.4.8	lspg_query_queue_on	84
		7.2.4.9	lspg_query_queue_reply	84
		7.2.4.10	lspg_resetPoll_response	84
		7.2.4.11	lspgfd	84
		7.2.4.12	now	84
		7.2.4.13	q	85
		7.2.4.14	subac	85
		7.2.4.15	subfd	85
7.3	Isevent	s.c File Re	eference	85
	7.3.1	Detailed	Description	86
	7.3.2	Macro De	efinition Documentation	86
		7.3.2.1	LSEVENTS_QUEUE_LENGTH	86
	7.3.3	Typedef I	Documentation	87
		7.3.3.1	sevents_listener_t	87
		7.3.3.2	lsevents_queue_t	87
	7.3.4	Function	Documentation	87
		7.3.4.1	Isevents_add_listener	87
		7.3.4.2	Isevents_init	88
		7.3.4.3	Isevents_remove_listener	88
		7.3.4.4	Isevents_run	88
		7.3.4.5	Isevents_send_event	89
		7.3.4.6	lsevents_worker	89
	7.3.5	Variable l	Documentation	90
		7.3.5.1	sevents_listener_mutex	90
		7.3.5.2	lsevents_listeners_p	90
		7.3.5.3	Isevents_queue	90
		7.3.5.4	Isevents_queue_cond	90

XIV

		7.3.5.5	lsevents_queue_mutex
		7.3.5.6	lsevents_queue_off
		7.3.5.7	lsevents_queue_on
		7.3.5.8	lsevents_thread
7.4	Isloggii	ng.c File F	Reference
	7.4.1	Detailed	Description
	7.4.2	Macro D	efinition Documentation
		7.4.2.1	LSLOGGING_FILE_NAME
		7.4.2.2	LSLOGGING_MSG_LENGTH
		7.4.2.3	LSLOGGING_QUEUE_LENGTH
	7.4.3	Typedef	Documentation
		7.4.3.1	lslogging_queue_t
	7.4.4	Function	Documentation
		7.4.4.1	lslogging_init
		7.4.4.2	lslogging_log_message
		7.4.4.3	lslogging_run
		7.4.4.4	lslogging_worker
	7.4.5	Variable	Documentation
		7.4.5.1	lslogging_cond
		7.4.5.2	lslogging_file
		7.4.5.3	lslogging_mutex
		7.4.5.4	lslogging_off
		7.4.5.5	lslogging_on
		7.4.5.6	lslogging_queue
		7.4.5.7	lslogging_thread
7.5	lspg.c	File Refere	ence
	7.5.1	Detailed	Description
	7.5.2	Macro D	efinition Documentation
		7.5.2.1	LS_PG_QUERY_QUEUE_LENGTH 100
		7.5.2.2	LS_PG_STATE_IDLE
		7.5.2.3	LS_PG_STATE_INIT
		7.5.2.4	LS_PG_STATE_INIT_POLL
		7.5.2.5	LS_PG_STATE_RECV
		7.5.2.6	LS_PG_STATE_RESET
		7.5.2.7	LS_PG_STATE_RESET_POLL
		7.5.2.8	LS_PG_STATE_SEND
		7.5.2.9	LS_PG_STATE_SEND_FLUSH
	7.5.3	Typedef	Documentation
		7.5.3.1	lspg_lock_detector_t
		7.5.3.2	lspg_lock_diffractometer_t

CONTENTS xv

	7.5.3.3	lspg_seq_run_prep_t	101
	7.5.3.4	lspg_wait_for_detector_t	101
7.5.4	Function	Documentation	102
	7.5.4.1	lspg_array2ptrs	102
	7.5.4.2	lspg_cmd_cb	103
	7.5.4.3	lspg_demandairrights_all	104
	7.5.4.4	lspg_demandairrights_call	104
	7.5.4.5	lspg_demandairrights_cb	104
	7.5.4.6	lspg_demandairrights_init	104
	7.5.4.7	lspg_demandairrights_wait	104
	7.5.4.8	lspg_flush	105
	7.5.4.9	lspg_getcenter_all	105
	7.5.4.10	lspg_getcenter_call	105
	7.5.4.11	lspg_getcenter_cb	105
	7.5.4.12	lspg_getcenter_done	106
	7.5.4.13	lspg_getcenter_init	106
	7.5.4.14	lspg_getcenter_wait	107
	7.5.4.15	lspg_getcurrentsampleid_call	107
	7.5.4.16	lspg_getcurrentsampleid_cb	107
	7.5.4.17	lspg_getcurrentsampleid_init	108
	7.5.4.18	lspg_getcurrentsampleid_read	108
	7.5.4.19	lspg_getcurrentsampleid_wait_for_id	108
	7.5.4.20	lspg_init	108
	7.5.4.21	lspg_lock_detector_all	109
	7.5.4.22	lspg_lock_detector_call	109
	7.5.4.23	lspg_lock_detector_cb	109
	7.5.4.24	lspg_lock_detector_done	109
	7.5.4.25	lspg_lock_detector_init	110
	7.5.4.26	lspg_lock_detector_wait	110
	7.5.4.27	lspg_lock_diffractometer_all	110
	7.5.4.28	lspg_lock_diffractometer_call	110
	7.5.4.29	lspg_lock_diffractometer_cb	110
	7.5.4.30	lspg_lock_diffractometer_done	111
	7.5.4.31	lspg_lock_diffractometer_init	111
	7.5.4.32	lspg_lock_diffractometer_wait	111
	7.5.4.33	lspg_next_state	111
	7.5.4.34	lspg_nextaction_cb	112
	7.5.4.35	lspg_nextsample_all	113
	7.5.4.36	lspg_nextsample_call	113
	7.5.4.37	lspg_nextsample_cb	113

xvi CONTENTS

7.5.4.38	lspg_nextsample_done	114
7.5.4.39	lspg_nextsample_init	114
7.5.4.40	lspg_nextsample_wait	114
7.5.4.41	lspg_nextshot_call	114
7.5.4.42	lspg_nextshot_cb	115
7.5.4.43	lspg_nextshot_done	118
7.5.4.44	lspg_nextshot_init	119
7.5.4.45	lspg_nextshot_wait	119
7.5.4.46	lspg_notice_processor	119
7.5.4.47	lspg_pg_connect	119
7.5.4.48	lspg_pg_service	120
7.5.4.49	lspg_query_next	122
7.5.4.50	lspg_query_push	122
7.5.4.51	lspg_query_reply_next	123
7.5.4.52	lspg_query_reply_peek	123
7.5.4.53	lspg_receive	123
7.5.4.54	lspg_run	124
7.5.4.55	lspg_send_next_query	124
7.5.4.56	lspg_seq_run_prep_all	125
7.5.4.57	lspg_seq_run_prep_call	126
7.5.4.58	lspg_seq_run_prep_cb	126
7.5.4.59	lspg_seq_run_prep_done	126
7.5.4.60	lspg_seq_run_prep_init	126
7.5.4.61	lspg_seq_run_prep_wait	127
7.5.4.62	lspg_sig_service	127
7.5.4.63	lspg_starttransfer_all	127
7.5.4.64	lspg_starttransfer_call	128
7.5.4.65	lspg_starttransfer_cb	128
7.5.4.66	lspg_starttransfer_done	128
7.5.4.67	lspg_starttransfer_init	128
7.5.4.68	lspg_starttransfer_wait	129
7.5.4.69	lspg_wait_for_detector_all	129
7.5.4.70	lspg_wait_for_detector_call	129
7.5.4.71	lspg_wait_for_detector_cb	129
7.5.4.72	lspg_wait_for_detector_done	129
7.5.4.73	lspg_wait_for_detector_init	130
7.5.4.74	lspg_wait_for_detector_wait	130
7.5.4.75	lspg_waitcryo_all	130
7.5.4.76	lspg_waitcryo_cb	130
7.5.4.77	lspg_waitcryo_init	131

CONTENTS xvii

		7.5.4.78	lspg_worker	131
		7.5.4.79	lspmac_sample_detector_cb	132
	7.5.5	Variable I	Documentation	132
		7.5.5.1	ls_pg_state	132
		7.5.5.2	lspg_connectPoll_response	132
		7.5.5.3	lspg_demandairrights	132
		7.5.5.4	lspg_getcenter	132
		7.5.5.5	lspg_getcurrentsampleid	132
		7.5.5.6	lspg_lock_detector	133
		7.5.5.7	lspg_lock_diffractometer	133
		7.5.5.8	lspg_nextsample	133
		7.5.5.9	lspg_nextshot	133
		7.5.5.10	lspg_query_queue	133
		7.5.5.11	lspg_query_queue_off	133
		7.5.5.12	lspg_query_queue_on	133
		7.5.5.13	lspg_query_queue_reply	133
		7.5.5.14	lspg_queue_cond	133
		7.5.5.15	lspg_queue_mutex	134
		7.5.5.16	lspg_resetPoll_response	134
		7.5.5.17	lspg_seq_run_prep	134
		7.5.5.18	lspg_starttransfer	134
		7.5.5.19	lspg_thread	134
		7.5.5.20	lspg_wait_for_detector	134
		7.5.5.21	lspg_waitcryo	134
		7.5.5.22	lspgfd	134
		7.5.5.23	now	134
		7.5.5.24	q	135
7.6	Ispmac	.c File Ref	erence	135
	7.6.1	Detailed	Description	143
	7.6.2	Macro De	efinition Documentation	143
		7.6.2.1	LS_PMAC_STATE_CR	143
		7.6.2.2	LS_PMAC_STATE_DETACHED	144
		7.6.2.3	LS_PMAC_STATE_GB	144
		7.6.2.4	LS_PMAC_STATE_GMR	144
		7.6.2.5	LS_PMAC_STATE_IDLE	144
		7.6.2.6	LS_PMAC_STATE_RESET	144
		7.6.2.7	LS_PMAC_STATE_RR	144
		7.6.2.8	LS_PMAC_STATE_SC	144
		7.6.2.9	LS_PMAC_STATE_WACK	
		7.6.2.10	LS_PMAC_STATE_WACK_CC	144

xviii CONTENTS

	7.6.2.11	LS_PMAC_STATE_WACK_NFR	14
	7.6.2.12	LS_PMAC_STATE_WACK_RR	14
	7.6.2.13	LS_PMAC_STATE_WCR	14
	7.6.2.14	LS_PMAC_STATE_WGB	1 5
	7.6.2.15	LSPMAC_DPASCII_QUEUE_LENGTH	1 5
	7.6.2.16	LSPMAC_PRESET_REGEX	1 5
	7.6.2.17	PMAC_CMD_QUEUE_LENGTH	1 5
	7.6.2.18	pmac_cmd_size	45
	7.6.2.19	PMAC_MIN_CMD_TIME	1 5
	7.6.2.20	PMACPORT	1 5
	7.6.2.21	VR_CTRL_RESPONSE	1 5
	7.6.2.22	VR_DOWNLOAD	1 5
	7.6.2.23	VR_FWDOWNLOAD	1 5
	7.6.2.24	VR_IPADDRESS	1 5
	7.6.2.25	VR_PMAC_FLUSH	16
	7.6.2.26	VR_PMAC_GETBUFFER	16
	7.6.2.27	VR_PMAC_GETLINE	1 6
	7.6.2.28	VR_PMAC_GETMEM	1 6
	7.6.2.29	VR_PMAC_GETRESPONSE	1 6
	7.6.2.30	VR_PMAC_PORT	16
	7.6.2.31	VR_PMAC_READREADY	1 6
	7.6.2.32	VR_PMAC_SENDCTRLCHAR	1 6
	7.6.2.33	VR_PMAC_SENDLINE	1 6
	7.6.2.34	VR_PMAC_SETBIT	1 6
	7.6.2.35	VR_PMAC_SETBITS	1 6
	7.6.2.36	VR_PMAC_SETMEM	1 6
	7.6.2.37	VR_PMAC_WRITEBUFFER	17
	7.6.2.38	VR_PMAC_WRITEERROR	17
	7.6.2.39	VR_UPLOAD	17
7.6.3	Typedef [Documentation	17
	7.6.3.1	lspmac_ascii_buffers_t	17
	7.6.3.2	lspmac_dpascii_queue_t	17
	7.6.3.3	md2_status_t	17
7.6.4	Function	Documentation	17
	7.6.4.1	_lspmac_motor_init	17
	7.6.4.2	cleanstr	18
	7.6.4.3	hex_dump	18
	7.6.4.4	IsConnect	19
	7.6.4.5	Ispmac_abort	50
	7.6.4.6	lspmac_asciicmdCB	50

CONTENTS xix

7.6.4.7	Ispmac_backLight_down_cb	150
7.6.4.8	lspmac_backLight_up_cb	150
7.6.4.9	lspmac_bi_init	151
7.6.4.10	lspmac_blight_lut_setup	151
7.6.4.11	Ispmac_bo_init	151
7.6.4.12	lspmac_bo_read	152
7.6.4.13	lspmac_command_done_cb	152
7.6.4.14	lspmac_cryoSwitchChanged_cb	153
7.6.4.15	lspmac_dac_init	153
7.6.4.16	lspmac_dac_read	153
7.6.4.17	lspmac_Error	154
7.6.4.18	lspmac_est_move_time	154
7.6.4.19	lspmac_flight_lut_setup	155
7.6.4.20	Ispmac_fscint_lut_setup	156
7.6.4.21	lspmac_fshut_init	156
7.6.4.22	lspmac_get_ascii	157
7.6.4.23	lspmac_get_ascii_cb	157
7.6.4.24	lspmac_get_status	158
7.6.4.25	lspmac_get_status_cb	159
7.6.4.26	Ispmac_GetAllIVars	162
7.6.4.27	Ispmac_GetAllIVarsCB	162
7.6.4.28	Ispmac_GetAllMVars	162
7.6.4.29	Ispmac_GetAllMVarsCB	162
7.6.4.30	Ispmac_getBIPosition	163
7.6.4.31	lspmac_Getmem	163
7.6.4.32	Ispmac_GetmemReplyCB	163
7.6.4.33	Ispmac_getPosition	163
7.6.4.34	lspmac_GetShortReplyCB	164
7.6.4.35	lspmac_home1_queue	164
7.6.4.36	lspmac_home2_queue	166
7.6.4.37	lspmac_init	166
7.6.4.38	lspmac_jogabs_queue	169
7.6.4.39	lspmac_light_zoom_cb	170
7.6.4.40	lspmac_lut	170
7.6.4.41	lspmac_more_ascii_cb	171
7.6.4.42	lspmac_motor_init	171
7.6.4.43	lspmac_move_or_jog_abs_queue	172
7.6.4.44	lspmac_move_or_jog_preset_queue	174
7.6.4.45	lspmac_move_preset_queue	175
7.6.4.46	lspmac_moveabs_blight_factor_queue	175

CONTENTS

7.6.4.47	lspmac_moveabs_bo_queue	176
7.6.4.48	lspmac_moveabs_flight_factor_queue	176
7.6.4.49	lspmac_moveabs_frontlight_oo_queue	176
7.6.4.50	lspmac_moveabs_fshut_queue	177
7.6.4.51	lspmac_moveabs_queue	177
7.6.4.52	lspmac_moveabs_timed_queue	178
7.6.4.53	lspmac_moveabs_wait	178
7.6.4.54	lspmac_movedac_queue	180
7.6.4.55	lspmac_movezoom_queue	180
7.6.4.56	lspmac_next_state	181
7.6.4.57	lspmac_pmacmotor_read	182
7.6.4.58	lspmac_pop_queue	186
7.6.4.59	lspmac_pop_reply	186
7.6.4.60	lspmac_push_queue	186
7.6.4.61	lspmac_Reset	187
7.6.4.62	lspmac_reset_queue	187
7.6.4.63	lspmac_rlut	187
7.6.4.64	lspmac_run	188
7.6.4.65	lspmac_scint_dried_cb	189
7.6.4.66	Ispmac_scint_inPosition_cb	190
7.6.4.67	lspmac_send_command	190
7.6.4.68	lspmac_sendcmd	191
7.6.4.69	lspmac_sendcmd_nocb	191
7.6.4.70	Ispmac_SendControlReplyPrintCB	192
7.6.4.71	Ispmac_Service	192
7.6.4.72	lspmac_shutter_read	195
7.6.4.73	lspmac_SockFlush	195
7.6.4.74	lspmac_SockGetmem	195
7.6.4.75	lspmac_SockSendControlCharPrint	196
7.6.4.76	lspmac_SockSendDPControlChar	196
7.6.4.77	lspmac_SockSendDPControlCharCB	196
7.6.4.78	Ispmac_SockSendDPline	196
7.6.4.79	Ispmac_SockSendDPqueue	197
7.6.4.80	lspmac_SockSendline	197
7.6.4.81	lspmac_SockSendline_nr	198
7.6.4.82	lspmac_soft_motor_init	198
7.6.4.83	lspmac_soft_motor_read	198
7.6.4.84	lspmac_test_preset	199
7.6.4.85	lspmac_video_rotate	199
7.6.4.86	lspmac_worker	199

CONTENTS xxi

	7.6.4.87	lspmac_zoom_lut_setup	200
7.6.5	Variable I	Documentation	201
	7.6.5.1	alignx	201
	7.6.5.2	aligny	201
	7.6.5.3	alignz	201
	7.6.5.4	anal	201
	7.6.5.5	apery	201
	7.6.5.6	aperz	201
	7.6.5.7	arm_parked	201
	7.6.5.8	blight	201
	7.6.5.9	blight_down	201
	7.6.5.10	$blight_f \ . \ . \ . \ . \ . \ . \ . \ . \ . \ $	202
	7.6.5.11	blight_ud	202
	7.6.5.12	blight_up	202
	7.6.5.13	сару	202
	7.6.5.14	capz	202
	7.6.5.15	cenx	202
	7.6.5.16	ceny	202
	7.6.5.17	cr_cmd	202
	7.6.5.18	cryo	202
	7.6.5.19	cryo_back	203
	7.6.5.20	cryo_switch	203
	7.6.5.21	dbmem	203
	7.6.5.22	dbmemIn	203
	7.6.5.23	dryer	203
	7.6.5.24	etel_init_ok	203
	7.6.5.25	etel_on	203
	7.6.5.26	etel_ready	203
	7.6.5.27	ethCmdOff	203
	7.6.5.28	ethCmdOn	204
	7.6.5.29	ethCmdQueue	204
	7.6.5.30	ethCmdReply	204
	7.6.5.31	flight	204
	7.6.5.32	$flight_f \ \dots $	204
	7.6.5.33	flight_oo	204
	7.6.5.34	fluo	204
	7.6.5.35	fluor_back	204
	7.6.5.36	fscint	204
	7.6.5.37	fshut	205
	7.6.5.38	gb_cmd	205

xxii CONTENTS

7.6.5.39	getivars	205
7.6.5.40	getmvars	205
7.6.5.41	hp_air	205
7.6.5.42	kappa	205
7.6.5.43	lp_air	205
7.6.5.44	ls_pmac_state	205
7.6.5.45	lspmac_ascii_buffers	205
7.6.5.46	lspmac_ascii_buffers_mutex	205
7.6.5.47	lspmac_ascii_busy	206
7.6.5.48	lspmac_ascii_mutex	206
7.6.5.49	lspmac_bis	206
7.6.5.50	lspmac_dpascii_off	206
7.6.5.51	lspmac_dpascii_on	206
7.6.5.52	lspmac_dpascii_queue	206
7.6.5.53	lspmac_motors	206
7.6.5.54	lspmac_moving_cond	206
7.6.5.55	lspmac_moving_flags	206
7.6.5.56	lspmac_moving_mutex	206
7.6.5.57	lspmac_nbis	207
7.6.5.58	lspmac_nmotors	207
7.6.5.59	lspmac_shutter_cond	207
7.6.5.60	lspmac_shutter_has_opened	207
7.6.5.61	lspmac_shutter_mutex	207
7.6.5.62	lspmac_shutter_state	207
7.6.5.63	lspmac_status_last_time	207
7.6.5.64	lspmac_status_time	207
7.6.5.65	md2_status	207
7.6.5.66	md2_status_mutex	208
7.6.5.67	minikappa_ok	208
7.6.5.68	now	208
7.6.5.69	omega	208
7.6.5.70	omega_zero_search	208
7.6.5.71	omega_zero_time	208
7.6.5.72	omega_zero_velocity	208
7.6.5.73	phi	208
7.6.5.74	pmac_error_strs	208
7.6.5.75	pmac_queue_cond	209
7.6.5.76	pmac_queue_mutex	209
7.6.5.77	pmac_thread	209
7.6.5.78	pmacfd	209

CONTENTS xxiii

		7.6.5.79	rr_cmd	209
		7.6.5.80	sample_detected	209
		7.6.5.81	scint	209
		7.6.5.82	shutter_open	210
		7.6.5.83	smart_mag_err	210
		7.6.5.84	smart_mag_off	210
		7.6.5.85	smart_mag_on	210
		7.6.5.86	smart_mag_oo	210
		7.6.5.87	zoom	210
7.7	Isredis	.c File Refe	erence	210
	7.7.1	Detailed	Description	212
	7.7.2	Function	Documentation	213
		7.7.2.1	_lsredis_get_obj	213
		7.7.2.2	_lsredis_set_value	214
		7.7.2.3	Isredis_addRead	215
		7.7.2.4	Isredis_addWrite	215
		7.7.2.5	lsredis_cleanup	215
		7.7.2.6	Isredis_cmpnstr	216
		7.7.2.7	Isredis_cmpstr	216
		7.7.2.8	lsredis_debugCB	216
		7.7.2.9	Isredis_delRead	217
		7.7.2.10	Isredis_delWrite	217
		7.7.2.11	lsredis_fd_service	217
		7.7.2.12	lsredis_find_preset	218
		7.7.2.13	lsredis_get_obj	219
		7.7.2.14	Isredis_get_string_array	219
		7.7.2.15	Isredis_getb	219
		7.7.2.16	Isredis_getc	220
		7.7.2.17	Isredis_getd	220
		7.7.2.18	Isredis_getl	220
		7.7.2.19	lsredis_getstr	220
		7.7.2.20	lsredis_hgetCB	221
		7.7.2.21	Isredis_init	221
		7.7.2.22	lsredis_keysCB	222
		7.7.2.23	lsredis_maybe_add_key	223
		7.7.2.24	lsredis_regexec	223
		7.7.2.25	lsredis_run	223
		7.7.2.26	lsredis_set_value	223
		7.7.2.27	lsredis_setstr	224
		7.7.2.28	lsredis_sig_service	224

xxiv CONTENTS

		7.7.2.29	Isredis_subCB	25
		7.7.2.30	Isredis_worker	26
		7.7.2.31	redisDisconnectCB	27
	7.7.3	Variable I	Documentation	27
		7.7.3.1	Isredis_cond	27
		7.7.3.2	Isredis_head	27
		7.7.3.3	Isredis_htab	28
		7.7.3.4	lsredis_key_select_regex	28
		7.7.3.5	Isredis_mutex	28
		7.7.3.6	Isredis_objs	28
		7.7.3.7	lsredis_publisher	28
		7.7.3.8	Isredis_running	28
		7.7.3.9	Isredis_thread	28
		7.7.3.10	roac	28
		7.7.3.11	rofd	28
		7.7.3.12	subac	28
		7.7.3.13	subfd	28
		7.7.3.14	wrac	28
		7.7.3.15	wrfd	29
7.8	Istimer.	c File Refe	erence	29
	7.8.1	Detailed	Description	30
	7.8.2	Macro De	efinition Documentation	30
		7.8.2.1	LSTIMER_LIST_LENGTH	30
		7.8.2.2	LSTIMER_RESOLUTION_NSECS	30
	7.8.3	Typedef I	Documentation	30
		7.8.3.1	lstimer_list_t	30
	7.8.4	Function	Documentation	30
		7.8.4.1	handler	30
		7.8.4.2	lstimer_add_timer	31
		7.8.4.3	lstimer_init	32
		7.8.4.4	lstimer_run	32
		7.8.4.5	Istimer_worker	32
		7.8.4.6	service_timers	33
	7.8.5	Variable I	Documentation	34
		7.8.5.1	lstimer_active_timers	34
		7.8.5.2	Istimer_cond	34
		7.8.5.3	lstimer_list	34
		7.8.5.4	lstimer_mutex	34
		7.8.5.5	lstimer_thread	35
		7.8.5.6	lstimer_timerid	35

CONTENTS xxv

	7.8.5.7	new_timer
md2cm	nds.c File F	Reference
7.9.1	Detailed	Description
7.9.2	Function	Documentation
	7.9.2.1	md2cmds_abort
	7.9.2.2	md2cmds_action_queue
	7.9.2.3	md2cmds_action_wait
	7.9.2.4	md2cmds_center
	7.9.2.5	md2cmds_collect
	7.9.2.6	md2cmds_coordsys_1_stopped_cb
	7.9.2.7	md2cmds_coordsys_2_stopped_cb
	7.9.2.8	md2cmds_coordsys_3_stopped_cb
	7.9.2.9	md2cmds_coordsys_4_stopped_cb
	7.9.2.10	md2cmds_coordsys_5_stopped_cb
	7.9.2.11	md2cmds_coordsys_7_stopped_cb
	7.9.2.12	md2cmds_home_prep
	7.9.2.13	md2cmds_home_wait
	7.9.2.14	md2cmds_init
	7.9.2.15	md2cmds_is_moving
	7.9.2.16	md2cmds_kappaphi_move
	7.9.2.17	md2cmds_maybe_done_homing_cb
	7.9.2.18	md2cmds_maybe_done_moving_cb
	7.9.2.19	md2cmds_maybe_rotate_done_cb
	7.9.2.20	md2cmds_move_prep
	7.9.2.21	md2cmds_move_wait
	7.9.2.22	md2cmds_moveAbs
	7.9.2.23	md2cmds_mvcenter_move
	7.9.2.24	md2cmds_organs_move_presets
	7.9.2.25	md2cmds_phase_change
	7.9.2.26	md2cmds_prep_axis
	7.9.2.27	md2cmds_rotate
	7.9.2.28	md2cmds_rotate_cb
	7.9.2.29	md2cmds_run
	7.9.2.30	md2cmds_set_scale_cb
	7.9.2.31	md2cmds_time_capz_cb
	7.9.2.32	md2cmds_transfer
	7.9.2.33	md2cmds_worker
7.9.3	Variable I	Documentation
	7.9.3.1	md2cmds_capz_moving_time
	7.9.3.2	md2cmds_cmd
	7.9.1 7.9.2	md2cmds.c File for File for Function 7.9.2.1 7.9.2.2 7.9.2.3 7.9.2.4 7.9.2.5 7.9.2.6 7.9.2.10 7.9.2.10 7.9.2.11 7.9.2.12 7.9.2.13 7.9.2.14 7.9.2.15 7.9.2.16 7.9.2.17 7.9.2.18 7.9.2.19 7.9.2.20 7.9.2.20 7.9.2.21 7.9.2.22 7.9.2.23 7.9.2.24 7.9.2.25 7.9.2.26 7.9.2.27 7.9.2.28 7.9.2.29 7.9.2.29 7.9.2.30 7.9.2.30 7.9.2.31 7.9.2.32 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33 7.9.2.33

XXVI

		7.9.3.3	$md2cmds_cond \ \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots$	258
		7.9.3.4	md2cmds_homing_cond	259
		7.9.3.5	md2cmds_homing_count	259
		7.9.3.6	md2cmds_homing_mutex	259
		7.9.3.7	md2cmds_md_status_code	259
		7.9.3.8	md2cmds_moving_cond	259
		7.9.3.9	md2cmds_moving_count	259
		7.9.3.10	md2cmds_moving_mutex	259
		7.9.3.11	md2cmds_moving_queue_wait	259
		7.9.3.12	md2cmds_mutex	259
		7.9.3.13	md2cmds_thread	259
		7.9.3.14	rotating	260
7.10	mk_pgp	omac_redi	s.py File Reference	260
7.11	pgpmad	c.c File Re	ference	260
	7.11.1	Detailed I	Description	261
	7.11.2	Function	Documentation	261
		7.11.2.1	main	261
		7.11.2.2	pgpmac_printf	263
		7.11.2.3	stdinService	263
	7.11.3	Variable [Documentation	264
		7.11.3.1	ncurses_mutex	264
		7.11.3.2	$running \ . \ . \ . \ . \ . \ . \ . \ . \ . \ $	265
		7.11.3.3	stdinfda	265
		7.11.3.4	term_input	265
		7.11.3.5	term_output	265
		7.11.3.6	term_status	265
		7.11.3.7	term_status2	265
7.12	pgpmad	c.h File Re	eference	265
	7.12.1	Detailed I	Description	273
	7.12.2	Macro De	efinition Documentation	273
		7.12.2.1	_GNU_SOURCE	273
		7.12.2.2	LS_DISPLAY_WINDOW_HEIGHT	273
		7.12.2.3	LS_DISPLAY_WINDOW_WIDTH	273
		7.12.2.4	LS_PG_QUERY_STRING_LENGTH	273
		7.12.2.5	LSEVENTS_EVENT_LENGTH	273
		7.12.2.6	MD2CMDS_CMD_LENGTH	274
	7.12.3	Typedef D	Documentation	274
		7.12.3.1	lspg_demandairrights_t	274
		7.12.3.2	lspg_getcenter_t	274
		7.12.3.3	$lspg_getcurrentsampleid_t \ . \ . \ . \ . \ . \ . \ . \ . \ . \ $	274

CONTENTS xxvii

	7.12.3.4	lspg_nextsample_t	274
	7.12.3.5	lspg_nextshot_t	274
	7.12.3.6	lspg_query_queue_t	274
	7.12.3.7	lspg_starttransfer_t	274
	7.12.3.8	lspg_waitcryo_t	274
	7.12.3.9	lspmac_bi_t	274
	7.12.3.10	lspmac_motor_t	274
	7.12.3.11	lsredis_obj_t	274
	7.12.3.12	2 pmac_cmd_queue_t	275
	7.12.3.13	pmac_cmd_t	275
7.12.4	Function	Documentation	275
	7.12.4.1	Isevents_add_listener	275
	7.12.4.2	Isevents_init	276
	7.12.4.3	Isevents_remove_listener	276
	7.12.4.4	Isevents_run	276
	7.12.4.5	Isevents_send_event	277
	7.12.4.6	lslogging_init	277
	7.12.4.7	lslogging_log_message	277
	7.12.4.8	lslogging_run	278
	7.12.4.9	lspg_array2ptrs	278
	7.12.4.10	lspg_demandairrights_all	280
	7.12.4.11	lspg_getcenter_call	280
	7.12.4.12	2 lspg_getcenter_done	280
	7.12.4.13	B lspg_getcenter_wait	280
	7.12.4.14	lspg_getcurrentsampleid_wait_for_id	280
	7.12.4.15	ispg_init	281
	7.12.4.16	S lspg_nextsample_all	281
	7.12.4.17	' lspg_nextshot_call	281
	7.12.4.18	B lspg_nextshot_done	281
	7.12.4.19	9 lspg_nextshot_wait	282
	7.12.4.20	lspg_query_push	282
	7.12.4.21	lspg_run	282
	7.12.4.22	Plspg_seq_run_prep_all	283
	7.12.4.23	B lspg_starttransfer_call	283
	7.12.4.24	Ispg_starttransfer_done	283
	7.12.4.25	s lspg_starttransfer_wait	283
	7.12.4.26	S Ispg_waitcryo_all	284
	7.12.4.27	' Ispg_waitcryo_cb	284
	7.12.4.28	B lspg_zoom_lut_call	284
	7.12.4.29	lspmac_abort	284

xxviii CONTENTS

	7.12.4.30 lspmac_getBIPosition	284
	7.12.4.31 lspmac_getPosition	285
	7.12.4.32 lspmac_home1_queue	285
	7.12.4.33 lspmac_init	286
	7.12.4.34 lspmac_jogabs_queue	289
	7.12.4.35 lspmac_move_or_jog_abs_queue	289
	7.12.4.36 lspmac_move_or_jog_preset_queue	292
	7.12.4.37 lspmac_move_or_jog_queue	292
	7.12.4.38 lspmac_move_preset_queue	292
	7.12.4.39 lspmac_moveabs_queue	293
	7.12.4.40 lspmac_moveabs_wait	293
	7.12.4.41 lspmac_run	294
	7.12.4.42 lspmac_SockSendDPline	295
	7.12.4.43 lspmac_SockSendline	296
	7.12.4.44 lspmac_video_rotate	296
	7.12.4.45	297
	7.12.4.46 Isredis_cmpstr	297
	7.12.4.47	297
	7.12.4.48	298
	7.12.4.49 Isredis_get_string_array	298
	7.12.4.50 Isredis_getb	299
	7.12.4.51 Isredis_getd	299
	7.12.4.52	299
	7.12.4.53	299
	7.12.4.54 Isredis_init	300
	7.12.4.55 Isredis_regexec	301
	-	301
	7.12.4.57	301
	7.12.4.58 lstimer_add_timer	302
	7.12.4.59 lstimer_init	303
	7.12.4.60 lstimer_run	303
	7.12.4.61 supdate_init	304
	7.12.4.62 supdate_run	304
	7.12.4.63 md2cmds_init	304
	7.12.4.64 md2cmds_run	304
	7.12.4.65 pgpmac_printf	304
		305
7.12.5	Variable Documentation	305
	5	305
	7.12.5.2 aligny	305

CONTENTS xxix

7.12.5.3 alignz)5
7.12.5.4 anal)5
7.12.5.5 apery)5
7.12.5.6 aperz)5
7.12.5.7 arm_parked)6
7.12.5.8 blight)6
7.12.5.9 blight_down)6
7.12.5.10 blight_f)6
7.12.5.11 blight_ud)6
7.12.5.12 blight_up)6
7.12.5.13 capy)6
7.12.5.14 capz)6
7.12.5.15 cenx	
7.12.5.16 ceny)7
7.12.5.17 cryo)7
7.12.5.18 cryo_back)7
7.12.5.19 cryo_switch)7
7.12.5.20 dryer	
7.12.5.21 etel_init_ok)7
7.12.5.22 etel_on)7
7.12.5.23 etel_ready)7
7.12.5.24 flight)7
7.12.5.25 flight_f)8
7.12.5.26 flight_oo)8
7.12.5.27 fluo)8
7.12.5.28 fluor_back)8
7.12.5.29 fscint)8
7.12.5.30 fshut)8
7.12.5.31 hp_air)8
7.12.5.32 kappa)8
7.12.5.33 lp_air)8
7.12.5.34 lspg_demandairrights)9
7.12.5.35 lspg_getcenter)9
7.12.5.36 lspg_getcurrentsampleid)9
7.12.5.37 lspg_nextsample)9
7.12.5.38 lspg_nextshot)9
7.12.5.39 lspg_starttransfer)9
7.12.5.40 lspg_waitcryo)9
7.12.5.41 lspmac_motors)9
7.12.5.42 lspmac_moving_cond)9

CONTENTS

7.12.5.43 lspmac_moving_flags	10
7.12.5.44 Ispmac_moving_mutex	10
7.12.5.45 lspmac_nmotors	10
7.12.5.46 lspmac_shutter_cond	10
7.12.5.47 Ispmac_shutter_has_opened	10
7.12.5.48 lspmac_shutter_mutex	10
7.12.5.49 lspmac_shutter_state	10
7.12.5.50 md2_status_mutex	10
7.12.5.51 md2cmds_cmd	10
7.12.5.52 md2cmds_cond	11
7.12.5.53 md2cmds_md_status_code	11
7.12.5.54 md2cmds_mutex	11
7.12.5.55 md2cmds_pg_cond	11
7.12.5.56 md2cmds_pg_mutex	11
7.12.5.57 minikappa_ok	11
7.12.5.58 ncurses_mutex	11
7.12.5.59 omega	11
7.12.5.60 omega_zero_time	11
7.12.5.61 phi	11
7.12.5.62 pmac_queue_cond	11
7.12.5.63 pmac_queue_mutex	12
7.12.5.64 sample_detected	12
7.12.5.65 scint	12
7.12.5.66 shutter_open	12
7.12.5.67 smart_mag_err	12
7.12.5.68 smart_mag_off	12
7.12.5.69 smart_mag_on	12
7.12.5.70 smart_mag_oo	12
7.12.5.71 term_input	12
7.12.5.72 term_output	13
7.12.5.73 term_status	13
7.12.5.74 term_status2	13
7.12.5.75 zoom	13

Index 313

Chapter 1

The LS-CAT pgpmac Project

pgpmac.c

Some pmac defines, typedefs, functions suggested by Delta Tau Accessory 54E User Manual, October 23, 2003 (C) 2003 by Delta Tau Data Systems, Inc. All rights reserved.

Original work Copyright (C) 2012 by Keith Brister, Northwestern University, All rights reserved.

This project implements the MD2 communications required for operation at LS-CAT and is intended to replace Windows XP based .NET code provided by MAATEL.

The need to do this is driven by a desire to make the system as effecient and fast as possible by combining various operations. A proof-of-principle version of this code saw frame rates of 23/minute as opposed to the nominal 18/minute we normally quote for 1 second exposures.

Additionally, as we rapidly approach EOL for Windows XP an alternative is urgently needed.

Structure

The project is roughly broken down as follows:

lsevents.c Simple event queue

lsredis.c	Receive key value pair updates from redis databases
lslogging.c	A logging utility to simplify debugging
lspg.c	Handles communications with the controlling posgresql database
lsupdate.c	Periodically update the px.kvs table with new positions.
md2cmds.c	Provides the equivilant (mostly) of the LS-CAT BLUMax code.
pgpmac.c	Main: parses command line and starts up the various threads
pgpmac.h	All includes and defines. The only file included by the .c files in this
pmac_md2_1s-cat.pmc	Code for the PMAC: compile and install with pmac exectutive program.
pmac_md2.sql	Tables and procedures for the posgresql side of the project.

Notes:

- The postgresql and the pmac communications interfaces are asynchronous and rely heavyly on the unix "poll" routine.
- The project is multithreaded and based on "pthreads".
- · Most threads maintain a queue of commands to simplfy communications with each other.
- Note that a MAATEL supported interface for a more recent version of Windows may be available, however, a bit of effort will be required to implement it at LS-CAT as the BLUMax code will likely require some revisions. This is still an option should the present project become intractable.
- An important constraint has been to run the MD2 either from the windows .NET environment or from the pgpmac environment. A consequence is that the pmac "pmc" file has been augmented to include new capabilities without destroying the code that the .NET interface requires.
- Epics support could come by adapting the "e.c" code to work here directly or could come by making use of the existing kv pair mechanism already in place or, as is most likely, a combination of the two.
- Ncurses support could include input lines for SQL queries and direct commands for supporting homing etc.
 Perhaps the F keys could change modes or use of special mode changing text commands. Output is not
 asynchronous. Although this is unlikely to cause a problem I'd hate to have the program hang because
 terminal output is hung up.
- PG queries come back as text instead of binary. We could reduce the numeric errors by using binary and things would run a tad faster, though it is unlikely anyone would notice or care about the speed.

MD2 Motors and Coordinate Systems

CS	Motor	
1	1	X = Omega
2	17 18	<pre>X = Center X Y = Center Y</pre>
3	2 3 4	<pre>X = Alignment X Y = Alignment Y Z = Alignment Z</pre>
	5	Analyzer
4	6	X = Zoom
5	7 8 9 10 11	Y = Aperture Y Z = Aperture Z U = Capillary Y V = Capillary Z W = Scintillator Z
6		(None)
7	19 20	X = Kappa Y = Phi

MD2 Motion Programs

```
before calling, set M4XX = 1: flag to indicate we are running program XX P variables as arguments
```

```
Program
                Description
 1
                home omega
  2
                home alignment table X
  3
                home alignment table Y
  4
                home alignment table Z
  6
                home camera zoom
  7
                home aperture Y
  8
                home aperture Z
  9
                home capillary Y
 10
                home capillary Z
 11
                home scintillator Z
 17
                home center X
 18
                home center Y
 19
                home kappa
 20
                home phi (Home position is not defined for phi ...)
 25
                kappa stress test
 26
                Combined Incremental move of X and Y in selected coordinate system
                        (Does not reset M426)
                        P170 = X increment
                        P171 = Y increment
 31
                scan omega
                        P170 = Start
                        P171 = End
                        P173 = Velocity (float)
P174 = Sample Rate (I5049)
                        P175 = Acceleration time
                        P176
                              = Gathering source
                        P177 = Number of passes
                        P178 = Shutter rising distance (units of omega motion)
                        P179 = Shutter falling distance (units of omega motion)
                        P180 = Exposure Time
 34
                Organ Scan
                        P169 = Motor Number
                        P170 = Start Position
                        P171 = End Position
                        P172 = Step Size
                        P173 = Motor Speed
 35
                Organ Homing
 37
                Organ Move
                             (microdiff_hard.ini says we don't use this anymore)
                        P169 = Capillary Z
                        P170 = Scintillator Z
                        P171 = Aperture Z
 50
                Combined Incremental move of X and Y
                        P170 = X increment
                        P171 = Y increment
 52
                X oscillation (while M320 == 1)
                        (Does not reset M452)
 53
                Center X and Y Synchronized homing
```

```
Combined X, Y, Z absolute move
 54
                      P170 = X
                      P171 = Y
                      P172 = Z
131
               LS-CAT Modified Omega Scan
                      P170 = Shutter open position, in counts
                      P171 = Delta omega, in counts
                      P173 = Omega velocity (counts/msec)
                      P175
                            = Acceleration Time (msec)
                      P177
                            = Number of passes
                      P178
                            = Shutter Rising Distance
                      P179
                            = Shutter Falling Distance
                      P180
                             = Exposure TIme (msec)
140
               LS-CAT Move X Absolute
                           = X Value (cts)
                      Q10
141
               LS-CAT Move Y Absolute
                      Q11 = Y Value (cts)
               LS-CAT Move Z Absolute
142
                      Q12 = Z Value (cts)
               LS-CAT Move X, Y Absolute
150
                      Q20
                           = X Value
                            = Y Value
                      Q21
160
               LS-CAT Move X, Y, Z Absolute
                      Q30 = X Value
                      Q31 = Y Value
                      Q32 = Z Value
```

Chapter 2

Namespace Index

2.1	Names	pace	List
	11411100	1000	

Here is a list of	of all na	ame	esp	ac	es	wit	h k	rie	f c	les	cri	ipti	ion	ıs:												
iniParser															 		 							 		1
mk_pgpm	ac_rec	lis													 									 		1

6 Namespace Index

Chapter 3

Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

iniParser.iniParser	
This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the	
License, or (at your option) any later version	15
lsevents_listener_struct	
Linked list of event listeners	17
lsevents_queue_struct	
Storage definition for the events	18
lslogging_queue_struct	
Our log object: time and message	19
lspg_demandairrights_struct	20
lspg_getcenter_struct	
Storage for getcenter query Used for the md2 ROTATE command that generates the centering	
movies	20
lspg_getcurrentsampleid_struct	23
lspg_lock_detector_struct	
Lock detector object Implements detector lock for exposure control	24
lspg_lock_diffractometer_struct	
Object used to impliment locking the diffractometer Critical to exposure timing	25
lspg_nextsample_struct	
Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)	25
lspg_nextshot_struct	
Storage definition for nextshot query	27
lspg_seq_run_prep_struct	
Data collection running object	37
lspg_starttransfer_struct	
Returns 1 if transfer can continue 0 to abort	38
lspg_wait_for_detector_struct	
Object that implements detector / spindle timing We use database locks for exposure control and	
this implements the md2 portion of this handshake	39
lspg_waitcryo_struct	40
lspgQueryQueueStruct	
Store each query along with it's callback function	41
spmac_ascii_buffers_struct	42
lspmac_bi_struct	
Storage for binary inputs	42
lspmac_cmd_queue_struct	
PMAC command queue item	44

8 Data Structure Index

Ispmac_dpascii_queue_struct	45
Ispmac_motor_struct	
Motor information	46
lsredis_obj_struct	
Redis Object Basic object whose value is sychronized with our redis db	53
lstimer_list_struct	
Everything we need to know about a timer	56
md2StatusStruct	
The block of memory retrieved in a status request	58
tagEthernetCmd	
PMAC ethernet packet definition	65

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

ıParser.py
redis.c
events.c
Event subsystem for inter-pgpmac communication
logging.c
Logs messages to a file
og.c
Postgresql support for the LS-CAT pgpmac project
pmac.c
Routines concerned with communication with PMAC
redis.c
Support redis hash synchronization
timer.c
Support for delayed and periodic events
d2cmds.c
Implements commands to run the md2 diffractometer attached to a PMAC controled by post-
gresql
k_pgpmac_redis.py
gpmac.c
Main for the pgpmac project
gpmac.h
Headers for the entire pgpmac project

10 File Index

Chapter 5

Namespace Documentation

5.1 iniParser Namespace Reference

Data Structures

· class iniParser

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

Variables

• tuple ip iniParser("21-ID-E/microdiff_hard.ini")

5.1.1 Variable Documentation

5.1.1.1 tuple iniParser.ip iniParser("21-ID-E/microdiff_hard.ini")

Definition at line 104 of file iniParser.py.

5.2 mk_pgpmac_redis Namespace Reference

Variables

- list head sys.argv[1]
- list pref_ini sys.argv[2]
- list hard_ini sys.argv[3]
- dictionary motor_dict
- · dictionary hard_ini_fields
- list motor_field_lists
- list bi_list ["CryoSwitch"]
- dictionary motor_presets
- list zoom_settings
- tuple hi iniParser.iniParser(hard_ini)
- · list v motor_dict[m]
- string f "HSETNX"
- tuple pi iniParser.iniParser(pref_ini)
- int i 0

- tuple ppos pi.get(section, option)
- string fnc "HSETNX"
- tuple b pi.get(section, "LightIntensity")
- tuple p pi.get(section, "MotorPosition")
- tuple x pi.get(section, "ScaleX")
- tuple y pi.get(section, "ScaleY")

5.2.1 Variable Documentation

5.2.1.1 tuple mk_pgpmac_redis.b pi.get(section, "LightIntensity")

Definition at line 379 of file mk pgpmac redis.py.

5.2.1.2 list mk_pgpmac_redis.bi_list ["CryoSwitch"]

Definition at line 229 of file mk_pgpmac_redis.py.

5.2.1.3 tuple mk_pgpmac_redis.f "HSETNX"

Definition at line 329 of file mk_pgpmac_redis.py.

5.2.1.4 string mk_pgpmac_redis.fnc "HSETNX"

Definition at line 371 of file mk_pgpmac_redis.py.

5.2.1.5 mk_pgpmac_redis.hard_ini sys.argv[3]

Definition at line 21 of file mk_pgpmac_redis.py.

5.2.1.6 dictionary mk_pgpmac_redis.hard_ini_fields

Initial value:

Definition at line 169 of file mk_pgpmac_redis.py.

5.2.1.7 list mk_pgpmac_redis.head sys.argv[1]

Definition at line 13 of file mk_pgpmac_redis.py.

5.2.1.8 tuple mk_pgpmac_redis.hi iniParser.iniParser(hard_ini)

Definition at line 304 of file mk_pgpmac_redis.py.

5.2.1.9 int mk_pgpmac_redis.i 0

Definition at line 350 of file mk_pgpmac_redis.py.

5.2.1.10 dictionary mk_pgpmac_redis.motor_dict

Definition at line 26 of file mk_pgpmac_redis.py.

5.2.1.11 list mk_pgpmac_redis.motor_field_lists

Definition at line 191 of file mk_pgpmac_redis.py.

5.2.1.12 dictionary mk_pgpmac_redis.motor_presets

Definition at line 231 of file mk_pgpmac_redis.py.

5.2.1.13 tuple mk_pgpmac_redis.p pi.get(section, "MotorPosition")

Definition at line 385 of file mk_pgpmac_redis.py.

5.2.1.14 tuple mk_pgpmac_redis.pi iniParser.iniParser(pref_ini)

Definition at line 347 of file mk_pgpmac_redis.py.

5.2.1.15 tuple mk_pgpmac_redis.ppos pi.get(section, option)

Definition at line 357 of file mk_pgpmac_redis.py.

5.2.1.16 mk_pgpmac_redis.pref_ini sys.argv[2]

Definition at line 16 of file mk_pgpmac_redis.py.

5.2.1.17 tuple mk_pgpmac_redis.v motor_dict[m]

Definition at line 328 of file mk pgpmac redis.py.

5.2.1.18 tuple mk_pgpmac_redis.x pi.get(section, "ScaleX")

Definition at line 391 of file mk_pgpmac_redis.py.

5.2.1.19 tuple mk_pgpmac_redis.y pi.get(section, "ScaleY")

Definition at line 397 of file mk_pgpmac_redis.py.

5.2.1.20 list mk_pgpmac_redis.zoom_settings

Initial value:

```
1 [
                                                                        front back pos scalex scaley section

4.0, 8.0, 34100, 2.7083, 3.3442, "CoaxCam.Zoom1"],
6.0, 8.1, 31440, 2.2487, 2.2776, "CoaxCam.Zoom2"],
6.5, 8.2, 27460, 1.7520, 1.7550, "CoaxCam.Zoom3"],
7.0, 8.3, 23480, 1.3360, 1.3400, "CoaxCam.Zoom4"],
8.0, 10.0, 19500, 1.0140, 1.0110, "CoaxCam.Zoom5"],
9.0, 12.0, 15520, 0.7710, 0.7760, "CoaxCam.Zoom6"],
10.0, 17.0, 11540, 0.5880, 0.5920, "CoaxCam.Zoom6"],
12.0, 25.0, 7560, 0.4460, 0.4480, "CoaxCam.Zoom8"],
15.0, 37.0, 3580, 0.3410, 0.3460, "CoaxCam.Zoom9"],
16.0, 42.0, 0, 0.2700, 0.2690, "CoaxCam.Zoom10"]
                                   #lev
3
 4
                                   [2,
 5
                                    [3,
 6
                                    [4,
                                    [5,
 8
 9
10
11
                                       [9,
 12
                                        [10,
```

Definition at line 280 of file mk_pgpmac_redis.py.

Chapter 6

Data Structure Documentation

6.1 iniParser.iniParser Class Reference

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

Public Member Functions

- def __init__
- def read
- · def sections
- def options
- def has_section
- def has_option
- def get

Data Fields

- f
- sd

6.1.1 Detailed Description

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see http-://www.gnu.org/licenses/.

We assume the sections and options are case insensitive and that, although nested sections are implied by the format used by the md2, that the nesting has no practical importance.

The current version is for READING the files.

TODO: add writing. We'll need to keep track of the preferred case used in the ini file as well as the existing comments. This is mildly tricky since comments apparently can appear on both option lines and non-option lines so

we'll need to track the line number within each section to preserve all the comments. Strictly speaking this is not necessary as we can just spit stuff out all lower case without comments and, presumably, the md2 should be able to deal with it. However, there is enough of a problem with the lack of documentation that willfully removing seems like a bad idea.

Definition at line 42 of file iniParser.py.

6.1.2 Constructor & Destructor Documentation

```
6.1.2.1 def iniParser.iniParser.__init__ ( self, fn )
```

Definition at line 44 of file iniParser.py.

6.1.3 Member Function Documentation

```
6.1.3.1 def iniParser.iniParser.get ( self, section, option )
```

Definition at line 99 of file iniParser.py.

```
99
100 def get(self, section, option):
101 return self.sd[section.lower()][option.lower()]
102
```

6.1.3.2 def iniParser.iniParser.has_option (self, section, option)

Definition at line 94 of file iniParser.py.

6.1.3.3 def iniParser.iniParser.has_section (self, section)

Definition at line 91 of file iniParser.py.

```
91
92 def has_section( self, section):
93 return self.sd.has_key( section.lower())
```

6.1.3.4 def iniParser.iniParser.options (self, section)

Definition at line 87 of file iniParser.py.

```
87
88 def options( self, section):
89 return self.sd[section.lower()].keys()
90
```

6.1.3.5 def iniParser.iniParser.read (self)

Definition at line 49 of file iniParser.py.

```
50
       def read( self):
         self.sd = {}
current_section = "default"
51
52
53
           current_dict
                            = {}
           for 1 in self.f.readlines():
               sl = l.strip()
56
                if len(sl) > 0:
                    if sl[0] == ";":
57
58
59
60
                    if sl[0] == "[" and sl.find("]") > 1:
                        self.sd[current_section] = current_dict
62
                         current_dict = {}
63
                         current_section = (sl[1:sl.find("]")]).lower()
64
65
                        if sl.find(";") > 0:
66
                            s = sl[0:sl.find(";")]
68
69
                             s = s1
70
71
                         if s.find("=") > 0:
                            slist = s.split("=")
73
                             if len(slist) == 2:
                                 k = (slist[0].strip()).lower()
v = slist[1].strip()
75
76
                                 current_dict[k] = v
77
78
           self.sd[current_section] = current_dict
80
81
            self.f.close()
82
```

6.1.3.6 def iniParser.iniParser.sections (self)

Definition at line 83 of file iniParser.py.

```
83
84    def sections( self):
85         ks = set(self.sd.keys())
86         return list(ks.difference( ["default"]))
```

6.1.4 Field Documentation

6.1.4.1 iniParser.iniParser.f

Definition at line 45 of file iniParser.py.

6.1.4.2 iniParser.iniParser.sd

Definition at line 46 of file iniParser.py.

The documentation for this class was generated from the following file:

iniParser.py

6.2 | Isevents_listener_struct Struct Reference

Linked list of event listeners.

Data Fields

• struct |sevents_listener_struct * next

Next listener.

char * raw_regexp

the original string sent to us

regex_t re

regular expression representing listened for events

void(* cb)(char *)

call back function

6.2.1 Detailed Description

Linked list of event listeners.

Definition at line 27 of file Isevents.c.

6.2.2 Field Documentation

6.2.2.1 void(* Isevents_listener_struct::cb)(char *)

call back function

Definition at line 31 of file Isevents.c.

6.2.2.2 struct | sevents_listener_struct | sevents_listener_struct::next

Next listener.

Definition at line 28 of file Isevents.c.

6.2.2.3 char* lsevents_listener_struct::raw_regexp

the original string sent to us

Definition at line 29 of file Isevents.c.

6.2.2.4 regex_t lsevents_listener_struct::re

regular expression representing listened for events

Definition at line 30 of file Isevents.c.

The documentation for this struct was generated from the following file:

· Isevents.c

6.3 | Isevents_queue_struct Struct Reference

Storage definition for the events.

Data Fields

char * evp

name of the event

6.3.1 Detailed Description

Storage definition for the events.

Just a string for now. Perhaps one day we'll succumb to the temptation to add an argument or two.

Definition at line 17 of file Isevents.c.

6.3.2 Field Documentation

6.3.2.1 char* lsevents_queue_struct::evp

name of the event

Definition at line 18 of file Isevents.c.

The documentation for this struct was generated from the following file:

· Isevents.c

6.4 Islogging_queue_struct Struct Reference

Our log object: time and message.

Data Fields

· struct timespec Itime

time stamp: set when queued

char lmsg [LSLOGGING_MSG_LENGTH]

our message, truncated if too long

6.4.1 Detailed Description

Our log object: time and message.

Definition at line 24 of file Islogging.c.

6.4.2 Field Documentation

6.4.2.1 char lslogging_queue_struct::lmsg[LSLOGGING_MSG_LENGTH]

our message, truncated if too long

Definition at line 26 of file Islogging.c.

6.4.2.2 struct timespec Islogging_queue_struct::ltime

time stamp: set when queued

Definition at line 25 of file Islogging.c.

The documentation for this struct was generated from the following file:

• Islogging.c

6.5 lspg_demandairrights_struct Struct Reference

```
#include <pgpmac.h>
```

Data Fields

- pthread_mutex_t mutex
- · pthread cond t cond
- int new_value_ready

6.5.1 Detailed Description

Definition at line 196 of file pgpmac.h.

6.5.2 Field Documentation

6.5.2.1 pthread_cond_t lspg_demandairrights_struct::cond

Definition at line 198 of file pgpmac.h.

6.5.2.2 pthread_mutex_t lspg_demandairrights_struct::mutex

Definition at line 197 of file pgpmac.h.

6.5.2.3 int lspg_demandairrights_struct::new_value_ready

Definition at line 199 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.6 Ispg_getcenter_struct Struct Reference

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies.

```
#include <pgpmac.h>
```

Data Fields

• pthread_mutex_t mutex

don't let the threads collide!

pthread_cond_t cond

provides signaling for when the query is done

• int new_value_ready

used with condition

• int no_rows_returned

flag in case no centering information was forthcoming

• int zoom

the next zoom level to go to before taking the next movie

- int zoom isnull
- double dcx

center x change

- int dcx_isnull
- · double dcy

center y change

- int dcy_isnull
- · double dax

alignment x change

- int dax isnull
- · double day

alignment y change

- int day_isnull
- double daz

alignment z change

• int daz_isnull

6.6.1 Detailed Description

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies. Definition at line 210 of file pgpmac.h.

6.6.2 Field Documentation

6.6.2.1 pthread_cond_t lspg_getcenter_struct::cond

provides signaling for when the query is done

Definition at line 212 of file pgpmac.h.

6.6.2.2 double lspg_getcenter_struct::dax

alignment x change

Definition at line 225 of file pgpmac.h.

6.6.2.3 int lspg_getcenter_struct::dax_isnull

Definition at line 226 of file pgpmac.h.

22 6.6.2.4 double lspg_getcenter_struct::day alignment y change Definition at line 228 of file pgpmac.h. 6.6.2.5 int lspg_getcenter_struct::day_isnull Definition at line 229 of file pgpmac.h. 6.6.2.6 double lspg_getcenter_struct::daz alignment z change Definition at line 231 of file pgpmac.h. 6.6.2.7 int lspg_getcenter_struct::daz_isnull Definition at line 232 of file pgpmac.h. 6.6.2.8 double lspg_getcenter_struct::dcx center x change Definition at line 219 of file pgpmac.h. 6.6.2.9 int lspg_getcenter_struct::dcx_isnull Definition at line 220 of file pgpmac.h. 6.6.2.10 double lspg_getcenter_struct::dcy center y change Definition at line 222 of file pgpmac.h. 6.6.2.11 int lspg_getcenter_struct::dcy_isnull Definition at line 223 of file pgpmac.h. 6.6.2.12 pthread_mutex_t lspg_getcenter_struct::mutex don't let the threads collide! Definition at line 211 of file pgpmac.h.

6.6.2.13 int lspg_getcenter_struct::new_value_ready used with condition Definition at line 213 of file pgpmac.h.

6.6.2.14 int lspg_getcenter_struct::no_rows_returned

flag in case no centering information was forthcoming

Definition at line 214 of file pgpmac.h.

6.6.2.15 int lspg_getcenter_struct::zoom

the next zoom level to go to before taking the next movie

Definition at line 216 of file pgpmac.h.

6.6.2.16 int lspg_getcenter_struct::zoom_isnull

Definition at line 217 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.7 lspg_getcurrentsampleid_struct Struct Reference

#include <pgpmac.h>

Data Fields

- pthread_mutex_t mutex
 - practice safe threading
- pthread_cond_t cond

for signaling

int no_rows_returned

flag for an empty return

· int new_value_ready

OK, there is never a value, we need a variable for the conditional wait and this is what we call it everywhere else.

· unsigned int getcurrentsampleid

the sample we think is mounted on the diffractometer

• int getcurrentsampleid_isnull

the sample we think is mounted on the diffractometer

6.7.1 Detailed Description

Definition at line 184 of file pgpmac.h.

6.7.2 Field Documentation

6.7.2.1 pthread_cond_t lspg_getcurrentsampleid_struct::cond

for signaling

Definition at line 186 of file pgpmac.h.

6.7.2.2 unsigned int lspg_getcurrentsampleid_struct::getcurrentsampleid

the sample we think is mounted on the diffractometer

Definition at line 189 of file pgpmac.h.

6.7.2.3 int lspg_getcurrentsampleid_struct::getcurrentsampleid_isnull

the sample we think is mounted on the diffractometer

Definition at line 190 of file pgpmac.h.

6.7.2.4 pthread_mutex_t lspg_getcurrentsampleid_struct::mutex

practice safe threading

Definition at line 185 of file pgpmac.h.

6.7.2.5 int lspg_getcurrentsampleid_struct::new_value_ready

OK, there is never a value, we need a variable for the conditional wait and this is what we call it everywhere else.

Definition at line 188 of file pgpmac.h.

6.7.2.6 int lspg_getcurrentsampleid_struct::no_rows_returned

flag for an empty return

Definition at line 187 of file pgpmac.h.

The documentation for this struct was generated from the following file:

• pgpmac.h

6.8 lspg_lock_detector_struct Struct Reference

lock detector object Implements detector lock for exposure control

Data Fields

- pthread_mutex_t mutex
- pthread_cond_t cond
- int new_value_ready

6.8.1 Detailed Description

lock detector object Implements detector lock for exposure control Definition at line 974 of file Ispg.c.

6.8.2 Field Documentation

6.8.2.1 pthread_cond_t lspg_lock_detector_struct::cond

Definition at line 976 of file Ispg.c.

6.8.2.2 pthread_mutex_t lspg_lock_detector_struct::mutex

Definition at line 975 of file lspg.c.

6.8.2.3 int lspg_lock_detector_struct::new_value_ready

Definition at line 977 of file lspg.c.

The documentation for this struct was generated from the following file:

· lspg.c

6.9 Ispg_lock_diffractometer_struct Struct Reference

Object used to impliment locking the diffractometer Critical to exposure timing.

Data Fields

- pthread_mutex_t mutex
- · pthread cond t cond
- · int new value ready

6.9.1 Detailed Description

Object used to impliment locking the diffractometer Critical to exposure timing. Definition at line 915 of file lspg.c.

6.9.2 Field Documentation

6.9.2.1 pthread_cond_t lspg_lock_diffractometer_struct::cond

Definition at line 917 of file lspg.c.

6.9.2.2 pthread_mutex_t lspg_lock_diffractometer_struct::mutex

Definition at line 916 of file lspg.c.

6.9.2.3 int lspg_lock_diffractometer_struct::new_value_ready

Definition at line 918 of file lspg.c.

The documentation for this struct was generated from the following file:

· lspg.c

6.10 lspg_nextsample_struct Struct Reference

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

#include <pgpmac.h>

Data Fields

pthread_mutex_t mutex

Our mutex.

pthread_cond_t cond

Our condition.

int new_value_ready

flag for our condition

• int no_rows_returned

just in case, though this query should always return an integer, perhaps 0

· unsigned int nextsample

sample number (4 8-bit segments: station, dewar (lid), puck, and position in the puck)

· int nextsample_isnull

shouldn't ever be set, but if we change the logic of this call in PG then we are ready for it here.

6.10.1 Detailed Description

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

Definition at line 257 of file pgpmac.h.

6.10.2 Field Documentation

6.10.2.1 pthread_cond_t lspg_nextsample_struct::cond

Our condition.

Definition at line 259 of file pgpmac.h.

6.10.2.2 pthread_mutex_t lspg_nextsample_struct::mutex

Our mutex.

Definition at line 258 of file pgpmac.h.

6.10.2.3 int lspg_nextsample_struct::new_value_ready

flag for our condition

Definition at line 260 of file pgpmac.h.

6.10.2.4 unsigned int lspg_nextsample_struct::nextsample

sample number (4 8-bit segments: station, dewar (lid), puck, and position in the puck)

Definition at line 263 of file pgpmac.h.

6.10.2.5 int lspg_nextsample_struct::nextsample_isnull

shouldn't ever be set, but if we change the logic of this call in PG then we are ready for it here.

Definition at line 264 of file pgpmac.h.

6.10.2.6 int lspg_nextsample_struct::no_rows_returned

just in case, though this query should always return an integer, perhaps 0

Definition at line 261 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.11 | Ispg_nextshot_struct Struct Reference

Storage definition for nextshot query.

```
#include <pgpmac.h>
```

Data Fields

• pthread_mutex_t mutex

Our mutex for sanity in the multi-threaded program.

• pthread_cond_t cond

Condition to wait for a response from our postgresql server.

· int new value ready

Our flag for the condition to wait for.

• int no_rows_returned

flag indicating that no rows were returned.

char * dsdir

Directory for data relative to the ESAF home directory.

- · int dsdir isnull
- · char * dspid

ID string identifying this dataset.

- · int dspid_isnull
- · double dsowidth

dataset defined oscillation width

- int dsowidth_isnull
- char * dsoscaxis

dataset defined oscillation axis (always omega)

- · int dsoscaxis_isnull
- · double dsexp

dataset defined exposure time

- int dsexp_isnull
- · long long skey

key identifying a particulary image

- int skey_isnull
- · double sstart

starting angle

- int sstart_isnull
- char * sfn

file name

- · int sfn isnull
- · double dsphi

dataset defined starting phi angle

int dsphi_isnull

· double dsomega

dataset defined starting omega angle

- int dsomega_isnull
- · double dskappa

dataset defined starting kappa angle

- int dskappa_isnull
- double dsdist

dataset defined detector distance

- · int dsdist_isnull
- · double dsnrg

dataset defined energy

- · int dsnrg isnull
- · unsigned int dshpid

sample holder ID

- int dshpid_isnull
- · double cx

centering table x position

- int cx isnull
- double cy

centering table y position

- int cy_isnull
- · double ax

alignment table x position

- · int ax isnull
- double ay

alignment table y position

- int ay_isnull
- double az

alignment table z position

- int az_isnull
- · int active

flag: 1=move to indicated center position, 0=don't move center or alignment tables

- · int active isnull
- int sindex

index of frame (used to generate the file extension)

- int sindex_isnull
- char * stype

"Normal" or "Gridsearch"

- · int stype isnull
- double dsowidth2

next image oscillation width

- int dsowidth2_isnull
- char * dsoscaxis2

next image ascillation axis (always "omega")

- · int dsoscaxis2_isnull
- double dsexp2

next image exposure time

- · int dsexp2_isnull
- double sstart2

next image start angle

- int sstart2_isnull
- double dsphi2

next image phi position

- · int dsphi2 isnull
- · double dsomega2

next image omega position

- · int dsomega2_isnull
- double dskappa2

next image kappa position

- int dskappa2_isnull
- double dsdist2

next image distance

- · int dsdist2 isnull
- double dsnrg2

next image energy

- · int dsnrg2_isnull
- double cx2

next image centering table x position

- · int cx2 isnull
- double cy2

next image centering table y position

- · int cy2_isnull
- double ax2

next image alignment x position

- · int ax2 isnull
- double ay2

next image alignment y position

- · int ay2 isnull
- double az2

next image alignment z position

- int az2 isnull
- int active2

flag: 1 if next image should use the above centering parameters

- int active2_isnull
- int sindex2

next image index number

- int sindex2 isnull
- char * stype2

next image type ("Normal" or "Gridsearch")

int stype2_isnull

6.11.1 Detailed Description

Storage definition for nextshot query.

The next shot query returns all the information needed to collect the next data frame. Since SQL allows for null fields independently from blank strings a separate integer is used as a flag for this case. This adds to the program complexity but allows for some important cases. Suck it up.

Definition at line 277 of file pgpmac.h.

6.11.2 Field Documentation

6.11.2.1 int lspg_nextshot_struct::active

flag: 1=move to indicated center position, 0=don't move center or alignment tables

Definition at line 340 of file pgpmac.h.

6.11.2.2 int lspg_nextshot_struct::active2

flag: 1 if next image should use the above centering parameters

Definition at line 391 of file pgpmac.h.

6.11.2.3 int lspg_nextshot_struct::active2_isnull

Definition at line 392 of file pgpmac.h.

6.11.2.4 int lspg_nextshot_struct::active_isnull

Definition at line 341 of file pgpmac.h.

6.11.2.5 double lspg_nextshot_struct::ax

alignment table x position

Definition at line 331 of file pgpmac.h.

6.11.2.6 double lspg_nextshot_struct::ax2

next image alignment x position

Definition at line 382 of file pgpmac.h.

6.11.2.7 int lspg_nextshot_struct::ax2_isnull

Definition at line 383 of file pgpmac.h.

6.11.2.8 int lspg_nextshot_struct::ax_isnull

Definition at line 332 of file pgpmac.h.

6.11.2.9 double lspg_nextshot_struct::ay

alignment table y position

Definition at line 334 of file pgpmac.h.

6.11.2.10 double lspg_nextshot_struct::ay2

next image alignment y position

Definition at line 385 of file pgpmac.h.

6.11.2.11 int lspg_nextshot_struct::ay2_isnull

Definition at line 386 of file pgpmac.h.

6.11.2.12 int lspg_nextshot_struct::ay_isnull

Definition at line 335 of file pgpmac.h.

6.11.2.13 double lspg_nextshot_struct::az

alignment table z position

Definition at line 337 of file pgpmac.h.

6.11.2.14 double lspg_nextshot_struct::az2

next image alignment z position

Definition at line 388 of file pgpmac.h.

6.11.2.15 int lspg_nextshot_struct::az2_isnull

Definition at line 389 of file pgpmac.h.

6.11.2.16 int lspg_nextshot_struct::az_isnull

Definition at line 338 of file pgpmac.h.

6.11.2.17 pthread_cond_t lspg_nextshot_struct::cond

Condition to wait for a response from our postgresql server.

Definition at line 279 of file pgpmac.h.

6.11.2.18 double lspg_nextshot_struct::cx

centering table x position

Definition at line 325 of file pgpmac.h.

6.11.2.19 double lspg_nextshot_struct::cx2

next image centering table x position

Definition at line 376 of file pgpmac.h.

6.11.2.20 int lspg_nextshot_struct::cx2_isnull

Definition at line 377 of file pgpmac.h.

6.11.2.21 int lspg_nextshot_struct::cx_isnull

Definition at line 326 of file pgpmac.h.

6.11.2.22 double lspg_nextshot_struct::cy

centering table y position

Definition at line 328 of file pgpmac.h.

6.11.2.23 double lspg_nextshot_struct::cy2

next image centering table y position

Definition at line 379 of file pgpmac.h.

6.11.2.24 int lspg_nextshot_struct::cy2_isnull

Definition at line 380 of file pgpmac.h.

6.11.2.25 int lspg_nextshot_struct::cy_isnull

Definition at line 329 of file pgpmac.h.

6.11.2.26 char* lspg_nextshot_struct::dsdir

Directory for data relative to the ESAF home directory.

Definition at line 283 of file pgpmac.h.

6.11.2.27 int lspg_nextshot_struct::dsdir_isnull

Definition at line 284 of file pgpmac.h.

6.11.2.28 double lspg_nextshot_struct::dsdist

dataset defined detector distance

Definition at line 316 of file pgpmac.h.

6.11.2.29 double lspg_nextshot_struct::dsdist2

next image distance

Definition at line 370 of file pgpmac.h.

6.11.2.30 int lspg_nextshot_struct::dsdist2_isnull

Definition at line 371 of file pgpmac.h.

6.11.2.31 int lspg_nextshot_struct::dsdist_isnull

Definition at line 317 of file pgpmac.h.

6.11.2.32 double lspg_nextshot_struct::dsexp

dataset defined exposure time

Definition at line 295 of file pgpmac.h.

6.11.2.33 double lspg_nextshot_struct::dsexp2

next image exposure time

Definition at line 355 of file pgpmac.h.

6.11.2.34 int lspg_nextshot_struct::dsexp2_isnull

Definition at line 356 of file pgpmac.h.

6.11.2.35 int lspg_nextshot_struct::dsexp_isnull

Definition at line 296 of file pgpmac.h.

6.11.2.36 unsigned int lspg_nextshot_struct::dshpid

sample holder ID

Definition at line 322 of file pgpmac.h.

6.11.2.37 int lspg_nextshot_struct::dshpid_isnull

Definition at line 323 of file pgpmac.h.

6.11.2.38 double lspg_nextshot_struct::dskappa

dataset defined starting kappa angle

Definition at line 313 of file pgpmac.h.

6.11.2.39 double lspg_nextshot_struct::dskappa2

next image kappa position

Definition at line 367 of file pgpmac.h.

6.11.2.40 int lspg_nextshot_struct::dskappa2_isnull

Definition at line 368 of file pgpmac.h.

6.11.2.41 int lspg_nextshot_struct::dskappa_isnull

Definition at line 314 of file pgpmac.h.

6.11.2.42 double lspg_nextshot_struct::dsnrg

dataset defined energy

Definition at line 319 of file pgpmac.h.

6.11.2.43 double lspg_nextshot_struct::dsnrg2

next image energy

Definition at line 373 of file pgpmac.h.

6.11.2.44 int lspg_nextshot_struct::dsnrg2_isnull

Definition at line 374 of file pgpmac.h.

6.11.2.45 int lspg_nextshot_struct::dsnrg_isnull

Definition at line 320 of file pgpmac.h.

6.11.2.46 double lspg_nextshot_struct::dsomega

dataset defined starting omega angle

Definition at line 310 of file pgpmac.h.

6.11.2.47 double lspg_nextshot_struct::dsomega2

next image omega position

Definition at line 364 of file pgpmac.h.

6.11.2.48 int lspg_nextshot_struct::dsomega2_isnull

Definition at line 365 of file pgpmac.h.

6.11.2.49 int lspg_nextshot_struct::dsomega_isnull

Definition at line 311 of file pgpmac.h.

6.11.2.50 char* lspg_nextshot_struct::dsoscaxis

dataset defined oscillation axis (always omega)

Definition at line 292 of file pgpmac.h.

6.11.2.51 char* lspg_nextshot_struct::dsoscaxis2

next image ascillation axis (always "omega")

Definition at line 352 of file pgpmac.h.

6.11.2.52 int lspg_nextshot_struct::dsoscaxis2_isnull

Definition at line 353 of file pgpmac.h.

6.11.2.53 int lspg_nextshot_struct::dsoscaxis_isnull

Definition at line 293 of file pgpmac.h.

6.11.2.54 double lspg_nextshot_struct::dsowidth

dataset defined oscillation width

Definition at line 289 of file pgpmac.h.

6.11.2.55 double lspg_nextshot_struct::dsowidth2

next image oscillation width

Definition at line 349 of file pgpmac.h.

6.11.2.56 int lspg_nextshot_struct::dsowidth2_isnull

Definition at line 350 of file pgpmac.h.

6.11.2.57 int lspg_nextshot_struct::dsowidth_isnull

Definition at line 290 of file pgpmac.h.

6.11.2.58 double lspg_nextshot_struct::dsphi

dataset defined starting phi angle

Definition at line 307 of file pgpmac.h.

6.11.2.59 double lspg_nextshot_struct::dsphi2

next image phi position

Definition at line 361 of file pgpmac.h.

6.11.2.60 int lspg_nextshot_struct::dsphi2_isnull

Definition at line 362 of file pgpmac.h.

6.11.2.61 int lspg_nextshot_struct::dsphi_isnull

Definition at line 308 of file pgpmac.h.

6.11.2.62 char* lspg_nextshot_struct::dspid

ID string identifying this dataset.

Definition at line 286 of file pgpmac.h.

6.11.2.63 int lspg_nextshot_struct::dspid_isnull

Definition at line 287 of file pgpmac.h.

6.11.2.64 pthread_mutex_t lspg_nextshot_struct::mutex

Our mutex for sanity in the multi-threaded program.

Definition at line 278 of file pgpmac.h.

6.11.2.65 int lspg_nextshot_struct::new_value_ready

Our flag for the condition to wait for.

Definition at line 280 of file pgpmac.h.

6.11.2.66 int lspg_nextshot_struct::no_rows_returned

flag indicating that no rows were returned.

Definition at line 281 of file pgpmac.h.

6.11.2.67 char* lspg_nextshot_struct::sfn

file name

Definition at line 304 of file pgpmac.h.

6.11.2.68 int lspg_nextshot_struct::sfn_isnull

Definition at line 305 of file pgpmac.h.

6.11.2.69 int lspg_nextshot_struct::sindex

index of frame (used to generate the file extension)

Definition at line 343 of file pgpmac.h.

6.11.2.70 int lspg_nextshot_struct::sindex2

next image index number

Definition at line 394 of file pgpmac.h.

6.11.2.71 int lspg_nextshot_struct::sindex2_isnull

Definition at line 395 of file pgpmac.h.

6.11.2.72 int lspg_nextshot_struct::sindex_isnull

Definition at line 344 of file pgpmac.h.

6.11.2.73 long long lspg_nextshot_struct::skey

key identifying a particulary image

Definition at line 298 of file pgpmac.h.

6.11.2.74 int lspg_nextshot_struct::skey_isnull

Definition at line 299 of file pgpmac.h.

6.11.2.75 double lspg_nextshot_struct::sstart

starting angle

Definition at line 301 of file pgpmac.h.

6.11.2.76 double lspg_nextshot_struct::sstart2

next image start angle

Definition at line 358 of file pgpmac.h.

6.11.2.77 int lspg_nextshot_struct::sstart2_isnull

Definition at line 359 of file pgpmac.h.

6.11.2.78 int lspg_nextshot_struct::sstart_isnull

Definition at line 302 of file pgpmac.h.

6.11.2.79 char* lspg_nextshot_struct::stype

"Normal" or "Gridsearch"

Definition at line 346 of file pgpmac.h.

6.11.2.80 char* lspg_nextshot_struct::stype2

next image type ("Normal" or "Gridsearch")

Definition at line 397 of file pgpmac.h.

6.11.2.81 int lspg_nextshot_struct::stype2_isnull

Definition at line 398 of file pgpmac.h.

6.11.2.82 int lspg_nextshot_struct::stype_isnull

Definition at line 347 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.12 | Ispg_seq_run_prep_struct Struct Reference

Data collection running object.

Data Fields

- pthread_mutex_t mutex
- pthread_cond_t cond
- int new_value_ready

6.12.1 Detailed Description

Data collection running object.

Definition at line 1032 of file lspg.c.

6.12.2 Field Documentation

6.12.2.1 pthread_cond_t lspg_seq_run_prep_struct::cond

Definition at line 1034 of file lspg.c.

6.12.2.2 pthread_mutex_t lspg_seq_run_prep_struct::mutex

Definition at line 1033 of file lspg.c.

6.12.2.3 int lspg_seq_run_prep_struct::new_value_ready

Definition at line 1035 of file lspg.c.

The documentation for this struct was generated from the following file:

• Ispg.c

6.13 lspg_starttransfer_struct Struct Reference

returns 1 if transfer can continue 0 to abort

```
#include <pgpmac.h>
```

Data Fields

• pthread_mutex_t mutex

Our mutex.

pthread_cond_t cond

Our condition.

· int new_value_ready

flag for our condition

• int no_rows_returned

just in case, though this query should always return an integer, perhaps 0

· unsigned int starttransfer

sample number (4 8-bit segments: station, dewar (lid), puck, and position in the puck)

6.13.1 Detailed Description

returns 1 if transfer can continue 0 to abort

Definition at line 243 of file pgpmac.h.

6.13.2 Field Documentation

6.13.2.1 pthread_cond_t lspg_starttransfer_struct::cond

Our condition.

Definition at line 245 of file pgpmac.h.

6.13.2.2 pthread_mutex_t lspg_starttransfer_struct::mutex

Our mutex.

Definition at line 244 of file pgpmac.h.

6.13.2.3 int lspg_starttransfer_struct::new_value_ready

flag for our condition

Definition at line 246 of file pgpmac.h.

6.13.2.4 int lspg_starttransfer_struct::no_rows_returned

just in case, though this query should always return an integer, perhaps 0

Definition at line 247 of file pgpmac.h.

6.13.2.5 unsigned int lspg_starttransfer_struct::starttransfer

sample number (4 8-bit segments: station, dewar (lid), puck, and position in the puck)

Definition at line 249 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.14 lspg_wait_for_detector_struct Struct Reference

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

Data Fields

- pthread_mutex_t mutex
- · pthread cond t cond
- int new_value_ready

6.14.1 Detailed Description

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

Definition at line 850 of file Ispg.c.

6.14.2 Field Documentation

6.14.2.1 pthread_cond_t lspg_wait_for_detector_struct::cond

Definition at line 852 of file lspg.c.

6.14.2.2 pthread_mutex_t lspg_wait_for_detector_struct::mutex

Definition at line 851 of file Ispg.c.

6.14.2.3 int lspg_wait_for_detector_struct::new_value_ready

Definition at line 853 of file Ispg.c.

The documentation for this struct was generated from the following file:

• Ispg.c

6.15 | Ispg_waitcryo_struct Struct Reference

```
#include <pgpmac.h>
```

Data Fields

- pthread_mutex_t mutex
 practice safe threading
- pthread_cond_t cond for signaling
- · int new_value_ready

OK, there is never a value, we need a variable for the conditional wait and this is what we call it everywhere else.

6.15.1 Detailed Description

Definition at line 176 of file pgpmac.h.

6.15.2 Field Documentation

6.15.2.1 pthread_cond_t lspg_waitcryo_struct::cond

for signaling

Definition at line 178 of file pgpmac.h.

6.15.2.2 pthread_mutex_t lspg_waitcryo_struct::mutex

practice safe threading

Definition at line 177 of file pgpmac.h.

6.15.2.3 int lspg_waitcryo_struct::new_value_ready

OK, there is never a value, we need a variable for the conditional wait and this is what we call it everywhere else.

Definition at line 179 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.16 IspgQueryQueueStruct Struct Reference

Store each query along with it's callback function.

```
#include <pgpmac.h>
```

Data Fields

• char qs [LS_PG_QUERY_STRING_LENGTH]

our queries should all be pretty short as we'll just be calling functions: fixed length here simplifies memory management

• void(* onResponse)(struct lspgQueryQueueStruct *qq, PGresult *pgr)

Callback function for when a query returns a result.

6.16.1 Detailed Description

Store each query along with it's callback function.

All calls are asynchronous

Definition at line 31 of file kvredis.c.

6.16.2 Field Documentation

6.16.2.1 void(* IspgQueryQueueStruct::onResponse)(struct IspgQueryQueueStruct *qq, PGresult *pgr)

Callback function for when a query returns a result.

Definition at line 33 of file kvredis.c.

6.16.2.2 char IspgQueryQueueStruct::qs

our queries should all be pretty short as we'll just be calling functions: fixed length here simplifies memory management

Definition at line 32 of file kvredis.c.

The documentation for this struct was generated from the following files:

- · kvredis.c
- · pgpmac.h

6.17 Ispmac_ascii_buffers_struct Struct Reference

Data Fields

- · uint16 t command buf
- uint16_t command_buf_cc
- char command_str [160]
- uint16_t response_buf
- uint16_t response_n
- char response_str [256]

6.17.1 Detailed Description

Definition at line 344 of file Ispmac.c.

6.17.2 Field Documentation

6.17.2.1 uint16_t lspmac_ascii_buffers_struct::command_buf

Definition at line 346 of file Ispmac.c.

6.17.2.2 uint16_t lspmac_ascii_buffers_struct::command_buf_cc

Definition at line 347 of file Ispmac.c.

6.17.2.3 char lspmac_ascii_buffers_struct::command_str[160]

Definition at line 348 of file Ispmac.c.

6.17.2.4 uint16_t lspmac_ascii_buffers_struct::response_buf

Definition at line 349 of file Ispmac.c.

6.17.2.5 uint16_t lspmac_ascii_buffers_struct::response_n

Definition at line 350 of file Ispmac.c.

6.17.2.6 char lspmac_ascii_buffers_struct::response_str[256]

Definition at line 351 of file Ispmac.c.

The documentation for this struct was generated from the following file:

· Ispmac.c

6.18 Ispmac_bi_struct Struct Reference

Storage for binary inputs.

#include <pgpmac.h>

Data Fields

int * ptr

points to the location in the status buffer

pthread_mutex_t mutex

so we don't get confused

· int mask

mask for the bit in the status register

int position

the current value.

· int previous

the previous value

· int first time

flag indicating we've not read the input even once

• char * changeEventOn

Event to send when the value changes to 1.

• char * changeEventOff

Event to send when the value changes to 0.

6.18.1 Detailed Description

Storage for binary inputs.

Definition at line 156 of file pgpmac.h.

6.18.2 Field Documentation

6.18.2.1 char* lspmac_bi_struct::changeEventOff

Event to send when the value changes to 0.

Definition at line 164 of file pgpmac.h.

6.18.2.2 char* lspmac_bi_struct::changeEventOn

Event to send when the value changes to 1.

Definition at line 163 of file pgpmac.h.

6.18.2.3 int lspmac_bi_struct::first_time

flag indicating we've not read the input even once

Definition at line 162 of file pgpmac.h.

6.18.2.4 int lspmac_bi_struct::mask

mask for the bit in the status register

Definition at line 159 of file pgpmac.h.

6.18.2.5 pthread_mutex_t lspmac_bi_struct::mutex

so we don't get confused

Definition at line 158 of file pgpmac.h.

6.18.2.6 int lspmac_bi_struct::position

the current value.

Definition at line 160 of file pgpmac.h.

6.18.2.7 int lspmac_bi_struct::previous

the previous value

Definition at line 161 of file pgpmac.h.

6.18.2.8 int* lspmac_bi_struct::ptr

points to the location in the status buffer

Definition at line 157 of file pgpmac.h.

The documentation for this struct was generated from the following file:

• pgpmac.h

6.19 Ispmac_cmd_queue_struct Struct Reference

PMAC command queue item.

#include <pgpmac.h>

Data Fields

• pmac_cmd_t pcmd

the pmac command to send

· int no_reply

1 = no reply is expected, 0 = expect a reply

• struct timespec time_sent

time this item was dequeued and sent to the pmac

char * event

event name to send

void(* onResponse)(struct lspmac_cmd_queue_struct *, int, char *)

function to call when response is received. args are (int fd, nreturned, buffer)

6.19.1 Detailed Description

PMAC command queue item.

Command queue items are fixed length to simplify memory management.

Definition at line 86 of file pgpmac.h.

6.19.2 Field Documentation

6.19.2.1 char* lspmac_cmd_queue_struct::event

event name to send

Definition at line 90 of file pgpmac.h.

6.19.2.2 int lspmac_cmd_queue_struct::no_reply

1 = no reply is expected, 0 = expect a reply

Definition at line 88 of file pgpmac.h.

6.19.2.3 void(* lspmac_cmd_queue_struct::onResponse)(struct lspmac_cmd_queue_struct *, int, char *)

function to call when response is received. args are (int fd, nreturned, buffer)

Definition at line 91 of file pgpmac.h.

6.19.2.4 pmac_cmd_t lspmac_cmd_queue_struct::pcmd

the pmac command to send

Definition at line 87 of file pgpmac.h.

6.19.2.5 struct timespec lspmac_cmd_queue_struct::time_sent

time this item was dequeued and sent to the pmac

Definition at line 89 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.20 Ispmac_dpascii_queue_struct Struct Reference

Data Fields

- · char * event
- char pl [160]

6.20.1 Detailed Description

Definition at line 358 of file Ispmac.c.

6.20.2 Field Documentation

6.20.2.1 char* lspmac_dpascii_queue_struct::event

Definition at line 359 of file Ispmac.c.

6.20.2.2 char lspmac_dpascii_queue_struct::pl[160]

Definition at line 360 of file Ispmac.c.

The documentation for this struct was generated from the following file:

• Ispmac.c

6.21 Ispmac_motor_struct Struct Reference

```
Motor information.
```

```
#include <pgpmac.h>
```

Data Fields

• pthread_mutex_t mutex

coordinate waiting for motor to be done

pthread_cond_t cond

used to signal when a motor is done moving

· int not done

set to 1 when request is queued, zero after motion has toggled

void(* read)(struct lspmac_motor_struct *)

method to read the motor status and position

int command_sent

Motion command verified sent to pmac.

· int motion_seen

set to 1 when motion has been verified to have started

pmac_cmd_queue_t * pq

the queue item requesting motion. Used to check time request was made

· int homing

Homing routine started.

int requested_pos_cnts

requested position

int * actual_pos_cnts_p

pointer to the md2_status structure to the actual position

• int actual_pos_cnts

local copy of actual counts so only our mutex is needed to read

· double position

scaled position

• double reported_position

previous position reported to the database

· double requested_position

The position as requested by the user.

int * status1_p

First 24 bit PMAC motor status word.

• int status1

local copy of status1

int * status2_p

Sectond 24 bit PMAC motor status word.

• int status2

```
local copy of status2
• char * dac_mvar
     controlling mvariable as a string
• char * name
     Name of motor as refered by Is database kvs table.
Isredis_obj_t * active
     Use the motor ("true") or not ("false")

    Isredis_obj_t * active_init

     pmac commands to make this motor active
lsredis_obj_t * axis
     the axis (X, Y, Z, etc) or null if not in a coordinate system
• Isredis_obj_t * coord_num
     coordinate system this motor belongs to (0 if none)
Isredis_obj_t * home
     pmac commands to home motor

    Isredis_obj_t * inactive_init

     pmac commands to inactivate the motor

    lsredis_obj_t * max_accel

     our maximum acceleration (cts/msec<sup>∧</sup>2)
lsredis_obj_t * max_pos
     our maximum position (soft limit)

    Isredis_obj_t * max_speed

     our maximum speed (cts/msec)
lsredis_obj_t * min_pos
      our minimum position (soft limit)
• Isredis_obj_t * motor_num
     pmac motor number
lsredis_obj_t * neutral_pos
     zero offset

    Isredis_obj_t * pos_limit_hit

     positive limit status

    Isredis_obj_t * neg_limit_hit

     negative limit status
• Isredis_obj_t * precision
     moves of less than this amount may be ignored
Isredis_obj_t * printf_fmt
     printf format
Isredis_obj_t * redis_fmt
      special format string to create text array for putting the position back into redis

    lsredis_obj_t * redis_position

     how we report our position to the world
Isredis_obj_t * status_str
     A talky version of the status.
lsredis_obj_t * u2c
     conversion from counts to units: 0.0 means not loaded yet

    Isredis_obj_t * unit

     string to use as the units
lsredis_obj_t * update_resolution
      Change needs to be at least this big to report as a new position to the database.
char * write fmt
      Format string to write requested position to PMAC used for binary io.
```

int * read_ptr

With read_mask finds bit to read for binary i/o.

· int read mask

With read_ptr find bit to read for binary i/o.

int(* moveAbs)(struct lspmac_motor_struct *, double)

function to move the motor

double * lut

lookup table (instead of u2c)

int nlut

length of lut

• WINDOW * win

our ncurses window

6.21.1 Detailed Description

Motor information.

A catchall for motors and motor like objects. Not all members are used by all objects.

Definition at line 101 of file pgpmac.h.

6.21.2 Field Documentation

6.21.2.1 | Isredis_obj_t* | Ispmac_motor_struct::active

Use the motor ("true") or not ("false")

Definition at line 122 of file pgpmac.h.

6.21.2.2 | Isredis obj t*|spmac_motor_struct::active_init

pmac commands to make this motor active

Definition at line 123 of file pgpmac.h.

6.21.2.3 int lspmac_motor_struct::actual_pos_cnts

local copy of actual counts so only our mutex is needed to read

Definition at line 112 of file pgpmac.h.

6.21.2.4 int* lspmac_motor_struct::actual_pos_cnts_p

pointer to the md2_status structure to the actual position

Definition at line 111 of file pgpmac.h.

6.21.2.5 | Isredis_obj_t* | Ispmac_motor_struct::axis

the axis (X, Y, Z, etc) or null if not in a coordinate system

Definition at line 124 of file pgpmac.h.

6.21.2.6 int lspmac_motor_struct::command_sent

Motion command verified sent to pmac.

Definition at line 106 of file pgpmac.h.

6.21.2.7 pthread_cond_t lspmac_motor_struct::cond

used to signal when a motor is done moving

Definition at line 103 of file pgpmac.h.

6.21.2.8 | Isredis_obj_t* | Ispmac_motor_struct::coord_num

coordinate system this motor belongs to (0 if none)

Definition at line 125 of file pgpmac.h.

6.21.2.9 char* lspmac_motor_struct::dac_mvar

controlling mvariable as a string

Definition at line 120 of file pgpmac.h.

6.21.2.10 Isredis obj t* Ispmac_motor_struct::home

pmac commands to home motor

Definition at line 126 of file pgpmac.h.

6.21.2.11 int lspmac_motor_struct::homing

Homing routine started.

Definition at line 109 of file pgpmac.h.

6.21.2.12 | Isredis_obj_t* | Ispmac_motor_struct::inactive_init

pmac commands to inactivate the motor

Definition at line 127 of file pgpmac.h.

6.21.2.13 double* Ispmac_motor_struct::lut

lookup table (instead of u2c)

Definition at line 148 of file pgpmac.h.

our maximum acceleration (cts/msec^2)

Definition at line 128 of file pgpmac.h.

6.21.2.15 | Isredis_obj_t* | Ispmac_motor_struct::max_pos

our maximum position (soft limit)

Definition at line 129 of file pgpmac.h.

our maximum speed (cts/msec)

Definition at line 130 of file pgpmac.h.

our minimum position (soft limit)

Definition at line 131 of file pgpmac.h.

6.21.2.18 int lspmac_motor_struct::motion_seen

set to 1 when motion has been verified to have started

Definition at line 107 of file pgpmac.h.

6.21.2.19 | Isredis_obj_t* | Ispmac_motor_struct::motor_num

pmac motor number

Definition at line 132 of file pgpmac.h.

6.21.2.20 int(* lspmac_motor_struct::moveAbs)(struct lspmac_motor_struct *, double)

function to move the motor

Definition at line 147 of file pgpmac.h.

6.21.2.21 pthread_mutex_t lspmac_motor_struct::mutex

coordinate waiting for motor to be done

Definition at line 102 of file pgpmac.h.

6.21.2.22 char* lspmac_motor_struct::name

Name of motor as refered by Is database kvs table.

Definition at line 121 of file pgpmac.h.

6.21.2.23 | Isredis_obj_t* | Ispmac_motor_struct::neg_limit_hit

negative limit status

Definition at line 135 of file pgpmac.h.

6.21.2.24 | Isredis_obj_t* | Ispmac_motor_struct::neutral_pos

zero offset

Definition at line 133 of file pgpmac.h.

6.21.2.25 int lspmac_motor_struct::nlut

length of lut

Definition at line 149 of file pgpmac.h.

6.21.2.26 int lspmac_motor_struct::not_done

set to 1 when request is queued, zero after motion has toggled

Definition at line 104 of file pgpmac.h.

positive limit status

Definition at line 134 of file pgpmac.h.

6.21.2.28 double lspmac_motor_struct::position

scaled position

Definition at line 113 of file pgpmac.h.

6.21.2.29 pmac_cmd_queue_t* lspmac_motor_struct::pq

the queue item requesting motion. Used to check time request was made

Definition at line 108 of file pgpmac.h.

moves of less than this amount may be ignored

Definition at line 136 of file pgpmac.h.

6.21.2.31 | Isredis_obj_t* | Ispmac_motor_struct::printf_fmt

printf format

Definition at line 137 of file pgpmac.h.

6.21.2.32 void(* lspmac_motor_struct::read)(struct lspmac_motor_struct *)

method to read the motor status and position

Definition at line 105 of file pgpmac.h.

6.21.2.33 int lspmac_motor_struct::read_mask

With read_ptr find bit to read for binary i/o.

Definition at line 146 of file pgpmac.h.

6.21.2.34 int* Ispmac_motor_struct::read_ptr

With read_mask finds bit to read for binary i/o.

Definition at line 145 of file pgpmac.h.

6.21.2.35 | Isredis_obj_t* | Ispmac_motor_struct::redis_fmt

special format string to create text array for putting the position back into redis

Definition at line 138 of file pgpmac.h.

how we report our position to the world

Definition at line 139 of file pgpmac.h.

6.21.2.37 double lspmac_motor_struct::reported_position

previous position reported to the database

Definition at line 114 of file pgpmac.h.

6.21.2.38 int lspmac_motor_struct::requested_pos_cnts

requested position

Definition at line 110 of file pgpmac.h.

6.21.2.39 double Ispmac_motor_struct::requested_position

The position as requested by the user.

Definition at line 115 of file pgpmac.h.

6.21.2.40 int lspmac_motor_struct::status1

local copy of status1

Definition at line 117 of file pgpmac.h.

6.21.2.41 int* lspmac_motor_struct::status1_p

First 24 bit PMAC motor status word.

Definition at line 116 of file pgpmac.h.

6.21.2.42 int lspmac_motor_struct::status2

local copy of status2

Definition at line 119 of file pgpmac.h.

6.21.2.43 int* Ispmac_motor_struct::status2_p

Sectond 24 bit PMAC motor status word.

Definition at line 118 of file pgpmac.h.

6.21.2.44 Isredis obj t* Ispmac_motor_struct::status_str

A talky version of the status.

Definition at line 140 of file pgpmac.h.

6.21.2.45 | Isredis_obj_t* | Ispmac_motor_struct::u2c

conversion from counts to units: 0.0 means not loaded yet

Definition at line 141 of file pgpmac.h.

string to use as the units

Definition at line 142 of file pgpmac.h.

6.21.2.47 | Isredis_obj_t* | Ispmac_motor_struct::update_resolution

Change needs to be at least this big to report as a new position to the database.

Definition at line 143 of file pgpmac.h.

6.21.2.48 WINDOW* Ispmac_motor_struct::win

our ncurses window

Definition at line 150 of file pgpmac.h.

6.21.2.49 char* lspmac_motor_struct::write_fmt

Format string to write requested position to PMAC used for binary io.

Definition at line 144 of file pgpmac.h.

The documentation for this struct was generated from the following file:

• pgpmac.h

6.22 | Isredis_obj_struct Struct Reference

Redis Object Basic object whose value is sychronized with our redis db.

#include <pgpmac.h>

Data Fields

• pthread_mutex_t mutex

Don't let anyone use an old value.

· pthread cond t cond

wait for a valid value

struct lsredis_obj_struct * next

the next in our list (I guess this is going to be a linked list)

· char valid

1 if we think the value is good, 0 otherwise

• int wait_for_me

Number of times we need to see our publication before we start accepting new values.

char * key

The redis key for this object.

• char * events_name

Name used to generate events (normally key without the station id)

• int value_length

Number of bytes allocated for value (not value's string length)

• char * value

our value

· double dvalue

our value as a double

long int Ivalue

our value as a long

char ** avalue

our value as an array of strings

· int bvalue

our value as a boolean (1 or 0) -1 means we couldn't figure it out

char cvalue

just the first character of our value

• int hits

number of times we've searched for this key

6.22.1 Detailed Description

Redis Object Basic object whose value is sychronized with our redis db.

Definition at line 38 of file pgpmac.h.

6.22.2 Field Documentation

6.22.2.1 char** lsredis_obj_struct::avalue

our value as an array of strings

Definition at line 50 of file pgpmac.h.

6.22.2.2 int lsredis_obj_struct::bvalue

our value as a boolean (1 or 0) -1 means we couldn't figure it out

Definition at line 51 of file pgpmac.h.

6.22.2.3 pthread_cond_t lsredis_obj_struct::cond

wait for a valid value

Definition at line 40 of file pgpmac.h.

6.22.2.4 char lsredis_obj_struct::cvalue

just the first character of our value

Definition at line 52 of file pgpmac.h.

6.22.2.5 double lsredis_obj_struct::dvalue

our value as a double

Definition at line 48 of file pgpmac.h.

6.22.2.6 char* lsredis_obj_struct::events_name

Name used to generate events (normally key without the station id)

Definition at line 45 of file pgpmac.h.

6.22.2.7 int lsredis_obj_struct::hits

number of times we've searched for this key

Definition at line 53 of file pgpmac.h.

6.22.2.8 char* lsredis_obj_struct::key

The redis key for this object.

Definition at line 44 of file pgpmac.h.

6.22.2.9 long int Isredis_obj_struct::lvalue

our value as a long

Definition at line 49 of file pgpmac.h.

6.22.2.10 pthread_mutex_t lsredis_obj_struct::mutex

Don't let anyone use an old value.

Definition at line 39 of file pgpmac.h.

6.22.2.11 struct | st

the next in our list (I guess this is going to be a linked list)

Definition at line 41 of file pgpmac.h.

6.22.2.12 char lsredis_obj_struct::valid

1 if we think the value is good, 0 otherwise

Definition at line 42 of file pgpmac.h.

6.22.2.13 char* lsredis_obj_struct::value

our value

Definition at line 47 of file pgpmac.h.

6.22.2.14 int lsredis_obj_struct::value_length

Number of bytes allocated for value (not value's string length)

Definition at line 46 of file pgpmac.h.

6.22.2.15 int lsredis_obj_struct::wait_for_me

Number of times we need to see our publication before we start accepting new values.

Definition at line 43 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.23 Istimer_list_struct Struct Reference

Everything we need to know about a timer.

Data Fields

• int shots

run this many times: -1 means reload forever, 0 means we are done with this timer and it may be reused

· unsigned long int ncalls

track how many times we triggered a callback (like an unsigned long int is really needed)

• char event [LSEVENTS_EVENT_LENGTH]

the event to send

· long int next secs

epoch (seconds) of next alarm

long int next_nsecs

nano seconds of next alarm

· long int delay_secs

number of seconds for a periodic delay

· long int delay nsecs

nano seconds of delay

long int last_secs

the last time this timer was triggered

long int last_nsecs

the last time this timer was triggered

• long int init_secs

our initialization time

• long int init_nsecs

our initialization time

6.23.1 Detailed Description

Everything we need to know about a timer.

Definition at line 22 of file Istimer.c.

6.23.2 Field Documentation

6.23.2.1 long int lstimer_list_struct::delay_nsecs

nano seconds of delay

Definition at line 29 of file Istimer.c.

6.23.2.2 long int lstimer_list_struct::delay_secs

number of seconds for a periodic delay

Definition at line 28 of file Istimer.c.

6.23.2.3 char lstimer_list_struct::event[LSEVENTS_EVENT_LENGTH]

the event to send

Definition at line 25 of file Istimer.c.

6.23.2.4 long int lstimer_list_struct::init_nsecs

our initialization time

Definition at line 33 of file Istimer.c.

6.23.2.5 long int lstimer_list_struct::init_secs

our initialization time

Definition at line 32 of file Istimer.c.

6.23.2.6 long int lstimer_list_struct::last_nsecs

the last time this timer was triggered

Definition at line 31 of file Istimer.c.

6.23.2.7 long int lstimer_list_struct::last_secs

the last time this timer was triggered

Definition at line 30 of file Istimer.c.

6.23.2.8 unsigned long int lstimer_list_struct::ncalls

track how many times we triggered a callback (like an unsigned long int is really needed)

Definition at line 24 of file Istimer.c.

6.23.2.9 long int lstimer_list_struct::next_nsecs

nano seconds of next alarm

Definition at line 27 of file Istimer.c.

6.23.2.10 long int lstimer_list_struct::next_secs

epoch (seconds) of next alarm

Definition at line 26 of file Istimer.c.

6.23.2.11 int lstimer_list_struct::shots

run this many times: -1 means reload forever, 0 means we are done with this timer and it may be reused Definition at line 23 of file Istimer.c.

The documentation for this struct was generated from the following file:

· Istimer.c

6.24 md2StatusStruct Struct Reference

The block of memory retrieved in a status request.

Data Fields

- int dummy1
- int omega_status_1
- int alignx_status_1
- int aligny_status_1
- int alignz_status_1
- int analyzer_status_1
- int zoom_status_1
- int aperturey_status_1
- int aperturez_status_1
- int capy_status_1
- int capz_status_1
- int scint_status_1
- int centerx_status_1
- int centery_status_1
- int kappa_status_1
- int phi_status_1
- int dummy2
- int omega_status_2
- int alignx_status_2
- int aligny_status_2

- int alignz_status_2
- int analyzer_status_2
- int zoom_status_2
- int aperturey_status_2
- int aperturez_status_2
- int capy_status_2
- int capz_status_2
- int scint_status_2
- int centerx_status_2
- int centery_status_2
- int kappa_status_2
- int phi status 2
- int dummy3
- int omega_act_pos
- int alignx_act_pos
- int aligny_act_pos
- int alignz_act_pos
- int analyzer_act_pos
- int zoom_act_pos
- int aperturey_act_pos
- int aperturez_act_pos
- int capy_act_pos
- int capz_act_pos
- int scint_act_pos
- · int centerx act pos
- int centery_act_pos
- int kappa_act_pos
- int phi_act_pos
- int acc11c_1
- int acc11c_2
- int acc11c_3
- int acc11c_5
- int acc11c_6
- int front_dacint back_dac
- int scint_piezo
- int dummy4
- int dummy5
- int dummy6
- int dummy7
- int dummy8
- int dummy9
- int dummyA
- int dummyB
- int fs_is_open
- int phiscan
- int fs_has_opened
- int fs_has_opened_globally
- int number_passes
- int moving_flags

6.24.1 Detailed Description

The block of memory retrieved in a status request.

Definition at line 245 of file Ispmac.c.

6.24.2 Field Documentation

6.24.2.1 int md2StatusStruct::acc11c_1

Definition at line 312 of file Ispmac.c.

6.24.2.2 int md2StatusStruct::acc11c_2

Definition at line 313 of file Ispmac.c.

6.24.2.3 int md2StatusStruct::acc11c_3

Definition at line 314 of file Ispmac.c.

6.24.2.4 int md2StatusStruct::acc11c_5

Definition at line 315 of file Ispmac.c.

6.24.2.5 int md2StatusStruct::acc11c_6

Definition at line 316 of file Ispmac.c.

6.24.2.6 int md2StatusStruct::alignx_act_pos

Definition at line 296 of file Ispmac.c.

6.24.2.7 int md2StatusStruct::alignx_status_1

Definition at line 262 of file Ispmac.c.

6.24.2.8 int md2StatusStruct::alignx_status_2

Definition at line 279 of file Ispmac.c.

6.24.2.9 int md2StatusStruct::aligny_act_pos

Definition at line 297 of file Ispmac.c.

6.24.2.10 int md2StatusStruct::aligny_status_1

Definition at line 263 of file Ispmac.c.

 $6.24.2.11 \quad int \ md2StatusStruct::aligny_status_2$

Definition at line 280 of file Ispmac.c.

6.24.2.12 int md2StatusStruct::alignz_act_pos

Definition at line 298 of file Ispmac.c.

6.24.2.13 int md2StatusStruct::alignz_status_1

Definition at line 264 of file Ispmac.c.

6.24.2.14 int md2StatusStruct::alignz_status_2

Definition at line 281 of file Ispmac.c.

6.24.2.15 int md2StatusStruct::analyzer_act_pos

Definition at line 299 of file Ispmac.c.

6.24.2.16 int md2StatusStruct::analyzer_status_1

Definition at line 265 of file Ispmac.c.

6.24.2.17 int md2StatusStruct::analyzer_status_2

Definition at line 282 of file Ispmac.c.

6.24.2.18 int md2StatusStruct::aperturey_act_pos

Definition at line 301 of file Ispmac.c.

6.24.2.19 int md2StatusStruct::aperturey_status_1

Definition at line 267 of file Ispmac.c.

6.24.2.20 int md2StatusStruct::aperturey_status_2

Definition at line 284 of file Ispmac.c.

6.24.2.21 int md2StatusStruct::aperturez_act_pos

Definition at line 302 of file Ispmac.c.

6.24.2.22 int md2StatusStruct::aperturez_status_1

Definition at line 268 of file Ispmac.c.

6.24.2.23 int md2StatusStruct::aperturez_status_2

Definition at line 285 of file Ispmac.c.

6.24.2.24 int md2StatusStruct::back_dac

Definition at line 318 of file Ispmac.c.

6.24.2.25 int md2StatusStruct::capy_act_pos

Definition at line 303 of file Ispmac.c.

6.24.2.26 int md2StatusStruct::capy_status_1

Definition at line 269 of file Ispmac.c.

6.24.2.27 int md2StatusStruct::capy_status_2

Definition at line 286 of file Ispmac.c.

6.24.2.28 int md2StatusStruct::capz_act_pos

Definition at line 304 of file Ispmac.c.

6.24.2.29 int md2StatusStruct::capz_status_1

Definition at line 270 of file Ispmac.c.

6.24.2.30 int md2StatusStruct::capz_status_2

Definition at line 287 of file Ispmac.c.

6.24.2.31 int md2StatusStruct::centerx_act_pos

Definition at line 306 of file Ispmac.c.

6.24.2.32 int md2StatusStruct::centerx_status_1

Definition at line 272 of file Ispmac.c.

6.24.2.33 int md2StatusStruct::centerx_status_2

Definition at line 289 of file Ispmac.c.

6.24.2.34 int md2StatusStruct::centery_act_pos

Definition at line 307 of file Ispmac.c.

6.24.2.35 int md2StatusStruct::centery_status_1

Definition at line 273 of file Ispmac.c.

6.24.2.36 int md2StatusStruct::centery_status_2

Definition at line 290 of file Ispmac.c.

6.24.2.37 int md2StatusStruct::dummy1 Definition at line 260 of file Ispmac.c. 6.24.2.38 int md2StatusStruct::dummy2 Definition at line 277 of file Ispmac.c. 6.24.2.39 int md2StatusStruct::dummy3 Definition at line 294 of file Ispmac.c. 6.24.2.40 int md2StatusStruct::dummy4 Definition at line 321 of file Ispmac.c. 6.24.2.41 int md2StatusStruct::dummy5 Definition at line 322 of file Ispmac.c. 6.24.2.42 int md2StatusStruct::dummy6 Definition at line 323 of file Ispmac.c. 6.24.2.43 int md2StatusStruct::dummy7 Definition at line 324 of file Ispmac.c. 6.24.2.44 int md2StatusStruct::dummy8 Definition at line 325 of file Ispmac.c. 6.24.2.45 int md2StatusStruct::dummy9 Definition at line 326 of file Ispmac.c. 6.24.2.46 int md2StatusStruct::dummyA Definition at line 327 of file Ispmac.c. 6.24.2.47 int md2StatusStruct::dummyB Definition at line 328 of file Ispmac.c. 6.24.2.48 int md2StatusStruct::front_dac 6.24.2.49 int md2StatusStruct::fs_has_opened

Definition at line 332 of file Ispmac.c.

6.24.2.50 int md2StatusStruct::fs_has_opened_globally

Definition at line 333 of file Ispmac.c.

6.24.2.51 int md2StatusStruct::fs_is_open

Definition at line 330 of file Ispmac.c.

6.24.2.52 int md2StatusStruct::kappa_act_pos

Definition at line 308 of file Ispmac.c.

6.24.2.53 int md2StatusStruct::kappa_status_1

Definition at line 274 of file Ispmac.c.

6.24.2.54 int md2StatusStruct::kappa_status_2

Definition at line 291 of file Ispmac.c.

6.24.2.55 int md2StatusStruct::moving_flags

Definition at line 336 of file Ispmac.c.

6.24.2.56 int md2StatusStruct::number_passes

Definition at line 334 of file Ispmac.c.

6.24.2.57 int md2StatusStruct::omega_act_pos

Definition at line 295 of file Ispmac.c.

6.24.2.58 int md2StatusStruct::omega_status_1

Definition at line 261 of file Ispmac.c.

6.24.2.59 int md2StatusStruct::omega_status_2

Definition at line 278 of file Ispmac.c.

6.24.2.60 int md2StatusStruct::phi_act_pos

Definition at line 309 of file Ispmac.c.

6.24.2.61 int md2StatusStruct::phi_status_1

Definition at line 275 of file Ispmac.c.

6.24.2.62 int md2StatusStruct::phi_status_2

Definition at line 292 of file Ispmac.c.

6.24.2.63 int md2StatusStruct::phiscan

Definition at line 331 of file Ispmac.c.

6.24.2.64 int md2StatusStruct::scint_act_pos

Definition at line 305 of file Ispmac.c.

6.24.2.65 int md2StatusStruct::scint_piezo

Definition at line 319 of file Ispmac.c.

6.24.2.66 int md2StatusStruct::scint_status_1

Definition at line 271 of file Ispmac.c.

6.24.2.67 int md2StatusStruct::scint_status_2

Definition at line 288 of file Ispmac.c.

6.24.2.68 int md2StatusStruct::zoom_act_pos

Definition at line 300 of file Ispmac.c.

6.24.2.69 int md2StatusStruct::zoom_status_1

Definition at line 266 of file Ispmac.c.

6.24.2.70 int md2StatusStruct::zoom_status_2

Definition at line 283 of file Ispmac.c.

The documentation for this struct was generated from the following file:

• Ispmac.c

6.25 tagEthernetCmd Struct Reference

PMAC ethernet packet definition.

#include <pgpmac.h>

Data Fields

• unsigned char RequestType

VR_UPLOAD or VR_DOWNLOAD.

• unsigned char Request

The command to run (VR_PMAC_GETMEM, etc).

· unsigned short wValue

Command parameter 1.

• unsigned short windex

Command parameter 2.

unsigned short wLength

Number of bytes in bData.

• unsigned char bData [1492]

The data buffer, if required.

6.25.1 Detailed Description

PMAC ethernet packet definition.

Taken directly from the Delta Tau documentation.

Definition at line 73 of file pgpmac.h.

6.25.2 Field Documentation

6.25.2.1 unsigned char tagEthernetCmd::bData[1492]

The data buffer, if required.

Definition at line 79 of file pgpmac.h.

6.25.2.2 unsigned char tagEthernetCmd::Request

The command to run (VR_PMAC_GETMEM, etc).

Definition at line 75 of file pgpmac.h.

6.25.2.3 unsigned char tagEthernetCmd::RequestType

VR_UPLOAD or VR_DOWNLOAD.

Definition at line 74 of file pgpmac.h.

6.25.2.4 unsigned short tagEthernetCmd::wIndex

Command parameter 2.

Definition at line 77 of file pgpmac.h.

6.25.2.5 unsigned short tagEthernetCmd::wLength

Number of bytes in bData.

Definition at line 78 of file pgpmac.h.

6.25.2.6 unsigned short tagEthernetCmd::wValue

Command parameter 1.

Definition at line 76 of file pgpmac.h.

The documentation for this struct was generated from the following file:

• pgpmac.h

Doto	Struc	+	Daai	ıman	tation
vala	อแนน	lure	DUC	amen	lalion

Chapter 7

File Documentation

7.1 iniParser.py File Reference

Data Structures

· class iniParser.iniParser

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

Namespaces

namespace iniParser

Variables

• tuple iniParser.ip iniParser("21-ID-E/microdiff_hard.ini")

7.2 kyredis.c File Reference

```
#include <stdio.h>
#include <stdlib.h>
#include <hiredis/hiredis.h>
#include <hiredis/async.h>
#include <poll.h>
#include <postgresql/libpq-fe.h>
#include <string.h>
```

Data Structures

• struct lspgQueryQueueStruct

Store each query along with it's callback function.

Macros

• #define LS_PG_QUERY_QUEUE_LENGTH 512

70 File Documentation

```
• #define LS_PG_QUERY_STRING_LENGTH 512
```

- #define LS_PG_STATE_INIT -4
- #define LS PG STATE INIT POLL -3
- #define LS PG STATE RESET -2
- #define LS_PG_STATE_RESET_POLL -1
- #define LS_PG_STATE_IDLE 1
- #define LS PG STATE SEND 2
- #define LS PG STATE SEND FLUSH 3
- #define LS_PG_STATE_RECV 4

Typedefs

typedef struct lspgQueryQueueStruct lspg_query_queue_t

Store each query along with it's callback function.

Functions

- void redisDisconnectCB (const redisAsyncContext *ac, int status)
- void debugCB (redisAsyncContext *ac, void *reply, void *privdata)
- void addRead (void *data)
- void delRead (void *data)
- void addWrite (void *data)
- void delWrite (void *data)
- void cleanup (void *data)
- void lspg_allkvs_cb (lspg_query_queue_t *qqp, PGresult *pgr)
- PQnoticeProcessor lspg_notice_processor (void *arg, const char *msg)
- lspg_query_queue_t * lspg_query_next ()

Return the next item in the postgresql queue.

void lspg query reply next ()

Remove the oldest item in the queue.

lspg_query_queue_t * lspg_query_reply_peek ()

Return the next item in the reply queue but don't pop it since we may need it more than once.

void lspg_query_push (void(*cb)(lspg_query_queue_t *, PGresult *), char *fmt,...)

Place a query on the queue.

• void lspg_receive ()

Receive a result of a query.

void lspg_pg_connect ()

Connect to the pg server.

• void lspg_flush ()

Flush psql output buffer (ie, send the query)

void lspg_next_state ()

Implements our state machine Does not strictly only set the next state as it also calls some functions that, perhaps, alters the state mid-function.

void lspg_send_next_query ()

send the next queued query to the DB server

void lspg_pg_service (struct pollfd *evt)

I/O control to/from the postgresql server.

- void fd_service (struct pollfd *evt)
- main ()

Variables

- static redisAsyncContext * subac
- static redisAsyncContext * cmdac
- static int ls_pg_state = LS_PG_STATE_INIT

State of the Ispg state machine.

· static struct timeval

lspg_time_sent now

used to ensure we do not inundate the db server with connection requests

static int kvseq = 0

used to synchronize pg.kvs and redis

• static lspg_query_queue_t lspg_query_queue [LS_PG_QUERY_QUEUE_LENGTH]

Our query queue.

• static unsigned int lspg_query_queue_on = 0

Next position to add something to the queue.

static unsigned int lspg_query_queue_off = 0

The last item still being used (on == off means nothing in queue)

• static unsigned int lspg_query_queue_reply = 0

The current item being digested.

static PGconn * q = NULL

Database connector.

static PostgresPollingStatusType lspg_connectPoll_response

Used to determine state while connecting.

static PostgresPollingStatusType lspg_resetPoll_response

Used to determine state while reconnecting.

static struct pollfd lspgfd

our poll info

· static struct pollfd subfd

poll info for redis subscribe channel

static struct pollfd cmdfd

poll info for redis command channel

7.2.1 Macro Definition Documentation

7.2.1.1 #define LS PG QUERY QUEUE LENGTH 512

Definition at line 12 of file kyredis.c.

7.2.1.2 #define LS_PG_QUERY_STRING_LENGTH 512

Definition at line 13 of file kvredis.c.

7.2.1.3 #define LS_PG_STATE_IDLE 1

Definition at line 19 of file kvredis.c.

7.2.1.4 #define LS_PG_STATE_INIT -4

Definition at line 15 of file kvredis.c.

72 File Documentation

7.2.1.5 #define LS_PG_STATE_INIT_POLL -3

Definition at line 16 of file kvredis.c.

7.2.1.6 #define LS_PG_STATE_RECV 4

Definition at line 22 of file kyredis.c.

7.2.1.7 #define LS_PG_STATE_RESET -2

Definition at line 17 of file kvredis.c.

7.2.1.8 #define LS_PG_STATE_RESET_POLL -1

Definition at line 18 of file kvredis.c.

7.2.1.9 #define LS_PG_STATE_SEND 2

Definition at line 20 of file kvredis.c.

7.2.1.10 #define LS_PG_STATE_SEND_FLUSH 3

Definition at line 21 of file kvredis.c.

7.2.2 Typedef Documentation

7.2.2.1 typedef struct lspgQueryQueueStruct lspg_query_queue_t

Store each query along with it's callback function.

All calls are asynchronous

7.2.3 Function Documentation

7.2.3.1 void addRead (void * data)

Definition at line 111 of file kvredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;
pfd->events |= POLLIN;
```

7.2.3.2 void addWrite (void * data)

Definition at line 121 of file kvredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;
pfd->events |= POLLOUT;
```

7.2.3.3 void cleanup (void * data)

Definition at line 131 of file kvredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;
pfd->events &= ~(POLLOUT | POLLIN);
}
```

7.2.3.4 void debugCB (redisAsyncContext * ac, void * reply, void * privdata)

Definition at line 63 of file kvredis.c.

```
static int indentlevel = 0;
redisReply *r;
int i;
r = (redisReply *)reply;
if( r == NULL) {
 printf( "Null reply. Odd\n");
  return;
switch( r->type) {
case REDIS_REPLY_STATUS:
 printf( "%*sSTATUS: %s\n", indentlevel*4,"", r->str);
  break;
case REDIS_REPLY_ERROR:
    printf( "%*sERROR: %s\n", indentlevel*4, "", r->str);
  break;
case REDIS_REPLY_INTEGER:
 printf( "%*sInteger: %lld\n", indentlevel*4, "", r->integer);
case REDIS_REPLY_NIL:
    printf( "%*s(nil)\n", indentlevel*4, "");
  break;
case REDIS_REPLY_STRING:
 printf( "%*sSTRING: %s\n", indentlevel*4, "", r->str);
  break;
case REDIS_REPLY_ARRAY:
 printf( "%*sARRAY of %d elements\n", indentlevel*4, "", (int)r->elements);
  indentlevel++;
  for( i=0; i<r->elements; i++) {
    debugCB( ac, r->element[i], NULL);
  indentlevel--;
  break;
default:
  printf( "%*sUnknown type %d\n", indentlevel*4,"", r->type);
```

7.2.3.5 void delRead (void * data)

Definition at line 116 of file kvredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;
pfd->events &= ~POLLIN;
}
```

74 File Documentation

7.2.3.6 void delWrite (void * data)

Definition at line 126 of file kvredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;
pfd->events &= ~POLLOUT;
```

7.2.3.7 void fd_service (struct pollfd * evt)

Definition at line 636 of file kvredis.c.

```
if( evt->fd == subac->c.fd) {
   if( evt->revents & POLLIN)
      redisAsyncHandleRead( subac);
   if( evt->revents & POLLOUT)
      redisAsyncHandleWrite( subac);
}
if( evt->fd == cmdac->c.fd) {
   if( evt->revents & POLLIN)
      redisAsyncHandleRead( cmdac);
   if( evt->revents & POLLOUT)
      redisAsyncHandleWrite( cmdac);
}
if( q && evt->fd == PQsocket( q))
   lspg_pg_service( evt);
```

7.2.3.8 void lspg_allkvs_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Definition at line 137 of file kvredis.c.

```
int kvname_col, kvvalue_col, kvseq_col, kvdbrtype_col;
int seq;
char *argv[8];
if( kvname_col == -1 || kvvalue_col == -1 || kvseq_col == -1 || kvdbrtype_col
     == -1) {
  fprintf( stderr, "lspg_allkvs_cb: bad column number(s)\n");
  return;
redisAsyncCommand( cmdac, NULL, NULL, "MULTI");
for( i=0; i<PQntuples( pgr); i++) {</pre>
  seq = atoi( PQgetvalue( pgr, i, kvseq_col));
  kvseq = kvseq < seq ? seq : kvseq;</pre>
  argv[0] = "HMSET";
  argv[1] = PQgetvalue( pgr, i, kvname_col);
argv[2] = "VALUE";
  argv[3] = PQgetvalue( pgr, i, kvvalue_col);
  argv[4] = "SEQ";
  argv[5] = PQgetvalue( pgr, i, kvseq_col);
  argv[6] = "DBRTYPE";
argv[7] = PQgetvalue( pgr, i, kvdbrtype_col);
  redisAsyncCommandArgv( cmdac, NULL, NULL, 8, (const char **)argv, NULL
   );
  argv[0] = "PUBLISH";
  argv[1] = "REDIS_KV_CONNECTOR";
  argv[2] = PQgetvalue( pgr, i, kvname_col);
  \verb|redisAsyncCommandArgv(cmdac, NULL, NULL, 3, (const char **) argv, NULL|\\
    );
```

```
redisAsyncCommand( cmdac, NULL, NULL, "SET redis.kvseq %d", kvseq);
redisAsyncCommand( cmdac, NULL, NULL, "EXEC");
}
```

7.2.3.9 void lspg_flush ()

Flush psql output buffer (ie, send the query)

Definition at line 412 of file kvredis.c.

```
{
int err;
err = PQflush( q);
switch( err) {
case -1:
    // an error occured

    fprintf( stderr, "flush failed: %s\n", PQerrorMessage( q));

    ls_pg_state = LS_PG_STATE_IDLE;
    //
    // We should probably reset the connection and start from scratch.
        Probably the connection died.
    //
    break;

case 0:
    // goodness and joy.
    ls_pg_state = LS_PG_STATE_RECV;
    break;

case 1:
    // more sending to do
    ls_pg_state = LS_PG_STATE_SEND_FLUSH;
    break;
}
```

7.2.3.10 void lspg_next_state ()

}

Implements our state machine Does not strictly only set the next state as it also calls some functions that, perhaps, alters the state mid-function.

Definition at line 444 of file kvredis.c.

```
{
// connect to the database
if( q == NULL ||
    ls_pg_state == LS_PG_STATE_INIT ||
ls_pg_state == LS_PG_STATE_RESET ||
ls_pg_state == LS_PG_STATE_INIT_POLL ||
    ls_pg_state == LS_PG_STATE_RESET_POLL)
  lspg_pg_connect( lspgfd);
if( ls_pg_state == LS_PG_STATE_IDLE &&
    lspg_query_queue_on != lspg_query_queue_off
  ls_pg_state = LS_PG_STATE_SEND;
switch( ls_pg_state) {
case LS_PG_STATE_INIT_POLL:
  if( lspg_connectPoll_response ==
    PGRES_POLLING_WRITING)
    lspgfd.events = POLLOUT;
       if( lspg_connectPoll_response ==
   PGRES_POLLING_READING)
    lspgfd.events = POLLIN;
  else
   lspgfd.events = 0;
  break;
```

76 File Documentation

```
case LS_PG_STATE_RESET_POLL:
  if( lspg_resetPoll_response == PGRES_POLLING_WRITING
    lspgfd.events = POLLOUT;
  else if( lspg_resetPoll_response ==
   PGRES_POLLING_READING)
    lspgfd.events = POLLIN;
   lspgfd.events = 0;
  break:
case LS_PG_STATE_IDLE:
case LS_PG_STATE_RECV:
  lspgfd.events = POLLIN;
case LS_PG_STATE_SEND:
case LS_PG_STATE_SEND_FLUSH:
  lspgfd.events = POLLOUT;
default:
  lspgfd.events = 0;
```

7.2.3.11 PQnoticeProcessor lspg_notice_processor (void * arg, const char * msg)

Definition at line 182 of file kvredis.c.

```
fprintf( stderr, "lspg: %s", msg);
```

7.2.3.12 void lspg_pg_connect()

Connect to the pg server.

Definition at line 325 of file kvredis.c.

```
PGresult *pgr;
int wait_interval = 1;
int connection_init = 0;
int i, err;
if(q == NULL)
 ls_pg_state = LS_PG_STATE_INIT;
switch( ls_pg_state) {
case LS_PG_STATE_INIT:
  if( lspg_time_sent.tv_sec != 0) {
    // Reality check: if it's less the about 10 seconds since the last failed
     attempt
    // the just chill.
    gettimeofday( &now, NULL);
    if( now.tv_sec - lspg_time_sent.tv_sec < 10) {</pre>
      return;
    }
  q = PQconnectStart( "dbname=ls user=lsuser hostaddr=10.1.0.3");
  if(q == NULL) {
    fprintf( stderr, "Out of memory (lspg_pg_connect)");
    exit(-1);
  err = PQstatus( q);
  if( err == CONNECTION_BAD) {
  fprintf( stderr, "Trouble connecting to database");
    gettimeofday( &lspg_time_sent, NULL);
    return;
```

```
err = PQsetnonblocking( q, 1);
  if( err != 0) {
   fprintf( stderr, "Odd, could not set database connection to nonblocking")
  ls_pg_state = LS_PG_STATE_INIT_POLL;
  lspg_connectPoll_response = PGRES_POLLING_WRITING;
  // set up the connection for poll
  lspgfd.fd = PQsocket( q);
  break;
case LS_PG_STATE_INIT_POLL:
  if( lspq_connectPoll_response ==
    PGRES_POLLING_FAILED) {
    PQfinish(q);
    q = NULL;
    ls_pg_state = LS_PG_STATE_INIT;
  } else if( lspg_connectPoll_response ==
    PGRES_POLLING_OK) {
    {\tt PQsetNoticeProcessor(\ q,\ (PQnoticeProcessor)lspg\_notice\_processor)}
    , NULL);
    ls_pg_state = LS_PG_STATE_IDLE;
  break;
case LS_PG_STATE_RESET:
  err = PQresetStart(q);
    PQfinish(q);
    q = NULL;
    ls_pg_state = LS_PG_STATE_INIT;
  } else {
   ls_pg_state = LS_PG_STATE_RESET_POLL;
   lspg_resetPoll_response = PGRES_POLLING_WRITING;
case LS PG STATE RESET POLL:
 if( lspg_resetPoll_response == PGRES_POLLING_FAILED)
    PQfinish(q);
    q = NULL;
   ls_pg_state = LS_PG_STATE_INIT;
  } else if( lspg_resetPoll_response ==
   PGRES_POLLING_OK) {
    ls_pg_state = LS_PG_STATE_IDLE;
  break;
```

7.2.3.13 void $lspg_pg_service$ (struct pollfd * evt)

I/O control to/from the postgresql server.

Parameters

in evt The pollfd object that we are responding to	
--	--

Definition at line 543 of file kvredis.c.

```
{
/// Currently just used to check for notifies
// Other socket communication is done syncronously
//

if( evt->revents & POLLIN) {
  int err;

if( ls_pg_state == LS_PG_STATE_INIT_POLL) {
   lspg_connectPoll_response = PQconnectPoll( q);
   if( lspg_connectPoll_response ==
        PGRES_POLLING_FAILED) {
```

```
ls_pg_state = LS_PG_STATE_RESET;
    return;
  }
  if( ls_pg_state == LS_PG_STATE_RESET_POLL)
    lspg_resetPoll_response = PQresetPoll( q);
    if( lspg_resetPoll_response ==
    -_._.DILING_FAILED) {
  ls_pg_state = LS_PG_STATE_RESET;
}
    return;
  // if in IDLE or RECV we need to call consumeInput first
  if( ls_pg_state == LS_PG_STATE_IDLE) {
    err = PQconsumeInput(q);
    if( err != 1) {
     frpintf( stderr, "consume input failed: %s", PQerrorMessage( q));
ls_pg_state == LS_PG_STATE_RESET;
      return;
   }
  if( ls_pg_state == LS_PG_STATE_RECV) {
    lspg_receive();
  // Check for notifies regardless of our state
  \ensuremath{//} Push as many requests as we have notifies.
    PGnotify *pgn;
    while( 1) {
      pgn = PQnotifies(q);
      if( pgn == NULL)
        break:
     lspg_query_push( lspg_allkvs_cb, "SELECT *
FROM px.redis_kv_update(%d)", kvseq);
      PQfreemem( pgn);
    }
  }
if( evt->revents & POLLOUT) {
  if( ls_pg_state == LS_PG_STATE_INIT_POLL) {
   lspg_connectPoll_response = PQconnectPoll(q);
if(lspg_connectPoll_response ==
    PGRES_POLLING_FAILED) {
     ls_pg_state = LS_PG_STATE_RESET;
    return;
  if( ls_pg_state == LS_PG_STATE_RESET_POLL)
    lspg_resetPoll_response = PQresetPoll( q);
    if( lspg_resetPoll_response ==
    PGRES_POLLING_FAILED) {
     ls_pg_state = LS_PG_STATE_RESET;
    return;
  if( ls_pg_state == LS_PG_STATE_SEND) {
    lspg_send_next_query();
  if( ls_pg_state == LS_PG_STATE_SEND_FLUSH)
    lspg_flush();
  }
```

```
7.2.3.14 lspg_query_queue_t* lspg_query_next( )
```

Return the next item in the postgresql queue.

If there is an item left in the queue then it is returned. Otherwise, NULL is returned.

Definition at line 191 of file kvredis.c.

7.2.3.15 void lspg_query_push (void(*)(lspg_query_queue_t *, PGresult *) cb, char * fmt, ...)

Place a query on the queue.

Parameters

in	cb	Our callback function that deals with the response
in	fmt	Printf style function to generate the query

Definition at line 234 of file kvredis.c.

```
int idx;
 va_list arg_ptr;
  ^{\prime\prime} // Pause the thread while we service the queue
 fprintf( stderr, "lspg_query_push: queue is full. Ignoring query \"%s\"\n"
     , fmt);
   return;
 }
 idx = lspg_query_queue_on % LS_PG_QUERY_QUEUE_LENGTH
 va_start( arg_ptr, fmt);
 vsnprintf( lspg_query_queue[idx].qs,
    LS_PG_QUERY_STRING_LENGTH-1, fmt, arg_ptr);
 va_end( arg_ptr);
 lspg_query_queue[idx].qs[LS_PG_QUERY_STRING_LENGTH
 lspg_query_queue[idx].onResponse = cb;
 lspg_query_queue_on++;
};
```

7.2.3.16 void lspg_query_reply_next ()

Remove the oldest item in the queue.

this is called only when there is nothing else to service the reply: this pop does not return anything. We use the ...reply_peek function to return the next item in the reply queue

Definition at line 211 of file kvredis.c.

```
{
  if( lspg_query_queue_reply != lspg_query_queue_on
    )
  lspg_query_queue_reply++;
}
```

```
7.2.3.17 lspg_query_queue_t* lspg_query_reply_peek( )
```

Return the next item in the reply queue but don't pop it since we may need it more than once.

Call lspg_query_reply_next() when done.

Definition at line 221 of file kvredis.c.

```
lspg_query_queue_t *rtn;

if( lspg_query_queue_reply == lspg_query_queue_on
    )
    rtn = NULL;
else
    rtn = &(lspg_query_queue[(lspg_query_queue_reply
    ) % LS_PG_QUERY_QUEUE_LENGTH]);

return rtn;
```

7.2.3.18 void lspg_receive ()

Receive a result of a query.

Definition at line 266 of file kvredis.c.

```
PGresult *pgr;
lspg_query_queue_t *qqp;
int err:
err = PQconsumeInput( q);
  fprintf( stderr, "consume input failed: %s", PQerrorMessage( q));
  ls_pg_state == LS_PG_STATE_RESET;
  return:
// We must call PQgetResult until it returns NULL before sending the next
     query
// This implies that only one query can ever be active at a time and our
     queue
// management should be simple
// We should be in the LS_PG_STATE_RECV here //
while( !PQisBusy( q)) {
  pgr = PQgetResult(q);
  if ( pgr == NULL) {
    lspg_query_reply_next();
    ^{\prime\prime} // we are now done reading the response from the database
    ls_pg_state = LS_PG_STATE_IDLE;
    break;
  } else {
    ExecStatusType es;
    qqp = lspg_query_reply_peek();
    es = PQresultStatus( pgr);
    if( es != PGRES_COMMAND_OK && es != PGRES_TUPLES_OK) {
```

```
char *emess;
  emess = PQresultErrorMessage( pgr);
  if( emess != NULL && emess[0] != 0) {
    fprintf( stderr, "Error from query '%s':\n%s", qqp->qs, emess);
  }
} else {
  //
  // Deal with the response
  //
  // If the response is likely to take awhile we should probably
  // add a new state and put something in the main look to run the
  onResponse
  // routine in the main loop. For now, though, we only expect very
  brief onResponse routines
  //
  if( qqp != NULL && qqp->onResponse != NULL)
    qqp->onResponse( qqp, pgr);
}
PQclear( pgr);
}
```

7.2.3.19 void lspg_send_next_query ()

send the next queued query to the DB server

Definition at line 496 of file kvredis.c.

```
// Normally we should be in the "send" state
  // but we can also send if we are servicing
  // a reply
  lspg_query_queue_t *qqp;
  int err;
  qqp = lspg_query_next();
  if( qqp == NULL) {
    // A send without a query? Should never happen.
// But at least we shouldn't segfault if it does.
    //
    return;
  if(qqp->qs[0] == 0) {
    // Do we really have to check this case?
    // It would only come up if we stupidly pushed an empty query string // or ran off the end of the queue
    fprintf( stderr, "Popped empty query string. Probably bad things are going on.\n");
    lspg_query_reply_next();
ls_pg_state = LS_PG_STATE_IDLE;
    else {
err = PQsendQuery( q, qqp->qs);
    if( err == 0) {
       fprintf( stderr, "query failed: %s\n", PQerrorMessage( q));
       // Don't wait for a reply, just reset the connection
       lspg_query_reply_next();
ls_pg_state == LS_PG_STATE_RESET;
    } else {
       ls_pg_state = LS_PG_STATE_SEND_FLUSH;
    }
}
```

7.2.3.20 main ()

Definition at line 655 of file kvredis.c.

```
static struct pollfd fda[3];
static int nfda = 0;
int pollrtn;
int poll_timeout_ms;
int i:
subac = redisAsyncConnect("127.0.0.1", 6379);
if( subac->err) {
  fprintf( stderr, "Error: %s\n", subac->errstr);
 exit(-1);
cmdac = redisAsyncConnect("127.0.0.1", 6379);
if( cmdac->err) {
  fprintf( stderr, "Error: %s\n", cmdac->errstr);
  exit(-1);
if( redisAsyncSetDisconnectCallback( subac, redisDisconnectCB
  ) == REDIS_ERR) {
fprintf( stderr, "Error: could not set disconnect callback\n");
 exit(-1);
if( redisAsyncSetDisconnectCallback( cmdac, redisDisconnectCB
      == REDIS_ERR) {
  fprintf( stderr, "Error: could not set disconnect callback\n");
  exit(-1);
// Set up redis events
subfd.fd
                     = subac->c.fd;
subfd.events = 0;
subac->ev.data = &subfd;
subac->ev.addRead = addRead;
subac->ev.delRead = delRead;
subac->ev.addWrite = addWrite;
subac->ev.delWrite = delWrite;
subac->ev.cleanup = cleanup;
cmdfd.fd
                     = cmdac->c.fd:
                   = 0;
= &cmdfd;
cmdfd.events
cmdac->ev.data
cmdac->ev.addRead = addRead;
cmdac->ev.delRead = delRead;
cmdac->ev.addWrite = addWrite;
cmdac->ev.delWrite = delWrite;
cmdac->ev.cleanup = cleanup;
lspgfd.fd = -1;
if( redisAsyncCommand( cmdac, NULL, NULL, "KEYS *") == REDIS_ERR) {
  fprintf( stderr, "Error sending KEYS command\n");
  exit( -1);
if( redisAsyncCommand( subac, debugCB, NULL, "PSUBSCRIBE MD2* UI*
  ") == REDIS_ERR) { fprintf( stderr, "Error sending PSUBSCRIBE command\n");
  exit( -1);
lspg_query_push( lspg_allkvs_cb, "SELECT * FROM
px.redis_kv_init()");
lspg_query_push( NULL, "LISTEN REDIS_KV_CONNECTOR");
while( 1) {
  nfda = 0;
  if( subfd.fd != -1) {
  fda[nfda].fd = subfd.fd;
  fda[nfda].events = subfd.events;
  fda[nfda].revents = 0;
    nfda++;
  if( cmdfd.fd != -1) {
  fda[nfda].fd = cmdfd.fd;
  fda[nfda].events = cmdfd.events;
    fda[nfda].revents = 0;
   nfda++;
  poll_timeout_ms = -1;
```

```
lspg_next_state();
  if( lspgfd.fd == -1) {
     ^{\prime\prime} // Here a connection to the database is not established.
     // Periodicaly try again. Should possibly arrange to reconnect
     // to signalfd but that's unlikely to be nessesary.
     poll_timeout_ms = 10000;
  } else { //
     ^{\prime\prime} // Arrange to peacfully do nothing until either the pg server sends us
     // or someone pushs something onto our queue
     fda[nfda].fd = lspgfd.fd;
fda[nfda].events = lspgfd.events;
fda[nfda].revents = 0;
     nfda++;
    poll_timeout_ms = -1;
  pollrtn = poll( fda, nfda, poll_timeout_ms);
  for( i=0; i<nfda; i++) {</pre>
     if( fda[i].revents)
      fd_service( &(fda[i]));
}
```

7.2.3.21 void redisDisconnectCB (const redisAsyncContext * ac, int status)

Definition at line 54 of file kvredis.c.

```
if( status == REDIS_OK) {
  printf( "OK, that was fun.\n");
  exit( 0);
}
fprintf( stderr, "Opps, Disconnected with status %d\n", status);
exit( -1);
}
```

7.2.4 Variable Documentation

7.2.4.1 redisAsyncContext * cmdac [static]

Definition at line 9 of file kvredis.c.

```
7.2.4.2 struct pollfd cmdfd [static]
```

poll info for redis command channel

Definition at line 50 of file kvredis.c.

```
7.2.4.3 int kvseq = 0 [static]
```

used to synchronize pg.kvs and redis

Definition at line 26 of file kvredis.c.

```
7.2.4.4 int ls_pg_state = LS PG STATE INIT [static]
```

State of the Ispg state machine.

Definition at line 24 of file kvredis.c.

7.2.4.5 PostgresPollingStatusType lspg_connectPoll_response [static]

Used to determine state while connecting.

Definition at line 46 of file kyredis.c.

7.2.4.6 Ispg_query_queue_t Ispg_query_queue[LS_PG_QUERY_QUEUE_LENGTH] [static]

Our query queue.

Definition at line 37 of file kvredis.c.

7.2.4.7 unsigned int lspg_query_queue_off = 0 [static]

The last item still being used (on == off means nothing in queue)

Definition at line 39 of file kvredis.c.

7.2.4.8 unsigned int lspg_query_queue_on = 0 [static]

Next position to add something to the gueue.

Definition at line 38 of file kvredis.c.

7.2.4.9 unsigned int lspg_query_queue_reply = 0 [static]

The current item being digested.

Normally off \leq = reply \leq = on. Corner case of queue wrap arround works because we only increment and compare for equality.

Definition at line 40 of file kvredis.c.

7.2.4.10 PostgresPollingStatusType lspg_resetPoll_response [static]

Used to determine state while reconnecting.

Definition at line 47 of file kvredis.c.

7.2.4.11 struct pollfd lspgfd [static]

our poll info

Definition at line 48 of file kvredis.c.

7.2.4.12 struct timeval lspg_time_sent now [static]

used to ensure we do not inundate the db server with connection requests

Definition at line 25 of file kvredis.c.

```
7.2.4.13  PGconn* q = NULL [static]
Database connector.
Definition at line 45 of file kvredis.c.
7.2.4.14  redisAsyncContext* subac [static]
Definition at line 9 of file kvredis.c.
7.2.4.15  struct pollfd subfd [static]
poll info for redis subscribe channel
```

7.3 Isevents.c File Reference

Definition at line 49 of file kvredis.c.

```
event subsystem for inter-pgpmac communication
```

```
#include "pgpmac.h"
```

Data Structures

• struct lsevents_queue_struct

Storage definition for the events.

• struct lsevents_listener_struct

Linked list of event listeners.

Macros

• #define LSEVENTS QUEUE LENGTH 512

Typedefs

• typedef struct lsevents_queue_struct lsevents_queue_t

Storage definition for the events.

typedef struct

Isevents_listener_struct Isevents_listener_t

Linked list of event listeners.

Functions

• void lsevents_send_event (char *fmt,...)

Call the callback routines for the given event.

void lsevents_add_listener (char *event, void(*cb)(char *))

Add a callback routine to listen for a specific event.

• void listener (char *event, void(*cb)(char *))

Remove a listener previously added with Isevents_add_listener.

```
Our worker.
    void lsevents_init ()
          Initialize this module.
    • void Isevents_run ()
          Start up the thread and get out of the way.
Variables
    • static lsevents_queue_t lsevents_queue [LSEVENTS_QUEUE_LENGTH]
          simple list of events

    static unsigned int lsevents_queue_on = 0

          next queue location to write
    • static unsigned int lsevents_queue_off = 0
          next queue location to read
    • static Isevents listener t * Isevents listeners p = NULL
          Pointer to the first item in the link list of listeners.

    static pthread_t lsevents_thread

          thread to run the event queue

    static pthread_mutex_t lsevents_listener_mutex

          mutex to protect the listener linked list
    • static pthread_mutex_t lsevents_queue_mutex
          mutex to protect the event queue
    • static pthread_cond_t lsevents_queue_cond
          condition to pause the queue if needed
7.3.1 Detailed Description
event subsystem for inter-pgpmac communication
Date
    2012
Author
    Keith Brister
Copyright
    All Rights Reserved
Definition in file Isevents.c.
       Macro Definition Documentation
7.3.2
```

7.3.2.1 #define LSEVENTS_QUEUE_LENGTH 512

Definition at line 10 of file Isevents.c.

void * lsevents_worker (void *dummy)

7.3.3 Typedef Documentation

7.3.3.1 typedef struct Isevents_listener_struct Isevents_listener_t

Linked list of event listeners.

7.3.3.2 typedef struct Isevents queue struct Isevents queue t

Storage definition for the events.

Just a string for now. Perhaps one day we'll succumb to the temptation to add an argument or two.

7.3.4 Function Documentation

7.3.4.1 void | sevents_add_listener (char * event, void(*)(char *) cb)

Add a callback routine to listen for a specific event.

Parameters

event the name of the event to listen for	
cb	the routine to call

Definition at line 75 of file Isevents.c.

```
lsevents_listener_t *new;
int err;
char *errbuf;
int nerrbuf;
new = calloc( 1, sizeof( lsevents_listener_t));
if ( new == NULL) {
  lslogging_log_message( "lsevents_add_listener: out of
  memory");
  exit(-1);
err = regcomp( &new->re, event, REG_EXTENDED | REG_NOSUB);
  nerrbuf = regerror( err, &new->re, NULL, 0);
  errbuf = calloc( nerrbuf, sizeof( char));
  if( errbuf == NULL) {
    lslogging_log_message( "lsevents_add_listener: out
     of memory (re)");
    exit(-1);
  regerror( err, &new->re, errbuf, nerrbuf);
lslogging_log_message( "lsevents_add_listener: %s",
    errbuf);
  free( errbuf);
  free ( new);
new->raw_regexp = strdup( event);
new->cb
          = cb;
pthread_mutex_lock( &lsevents_listener_mutex);
new->next = lsevents_listeners_p;
lsevents_listeners_p = new;
pthread_mutex_unlock( &lsevents_listener_mutex);
lslogging_log_message( "lsevents_add_listener: added
      listener for event %s", event);
```

7.3.4.2 void Isevents_init ()

Initialize this module.

Definition at line 214 of file Isevents.c.

```
pthread_mutex_init( &lsevents_queue_mutex, NULL);
pthread_cond_init( &lsevents_queue_cond, NULL);
pthread_mutex_init( &lsevents_listener_mutex, NULL);
```

7.3.4.3 void lsevents_remove_listener (char * event, void(*)(char *) cb)

Remove a listener previously added with Isevents_add_listener.

Parameters

event The name of the event	
cb	The callback routine to remove

Definition at line 120 of file Isevents.c.

```
lsevents_listener_t *last, *current;
// Find the listener to remove
// and unlink it from the list
pthread_mutex_lock( &lsevents_listener_mutex);
last = NULL;
for( current = lsevents_listeners_p; current != NULL;
    current = current->next) {
  if( strcmp( last->raw_regexp, event) == 0 && last->cb == cb) {
    if( last == NULL) {
      lsevents_listeners_p = current->next;
    } else {
      last->next = current->next;
pthread_mutex_unlock( &lsevents_listener_mutex);
// Now remove it
if( current != NULL) {
   if( current->raw_regexp != NULL)
    free( current->raw_regexp);
  free (current);
```

7.3.4.4 void lsevents_run ()

Start up the thread and get out of the way.

Definition at line 222 of file Isevents.c.

7.3.4.5 void lsevents_send_event (char * fmt, ...)

Call the callback routines for the given event.

Parameters

fmt	a printf style formating string	
	list of arguments specified by the format string	

Definition at line 45 of file Isevents.c.

7.3.4.6 void* lsevents_worker (void * dummy)

Our worker.

Parameters

dummy Unused but needed by pthreads to be happy

Definition at line 155 of file Isevents.c.

```
{
// char *event;
lsevents_queue_t *ep;
lsevents_listener_t *p;

while( 1) {
    pthread_mutex_lock( &lsevents_queue_mutex);

    //
    // wait for someone to send an event
    //
    while( lsevents_queue_off == lsevents_queue_on
    )
        pthread_cond_wait( &lsevents_queue_cond, &
        lsevents_queue_mutex);

//
    // copy event string since the value in the queue may change when
    // we unlock the mutex
    //
    ep = &(lsevents_queue[(lsevents_queue_off++
        ) % LSEVENTS_QUEUE_LENGTH]);
```

```
^{\prime\prime} // let the send event process know there is room on the queue again
pthread_cond_signal( &lsevents_queue_cond);
pthread_mutex_unlock( &lsevents_queue_mutex);
// Find the callbacks and, well, call them back
// TODO:
// Yes, this is O(N).
// Plan to make this O(1):
   track actual event names from send_event
// match listeners for new event names
   store matchs in hash table
// That makes send_event for new events O(N)
// but O(1) otherwise, O(N) for add_listener, and O(1) here.
pthread_mutex_lock( &lsevents_listener_mutex);
for( p = lsevents_listeners_p; p != NULL; p = p->next
  if( regexec( &p->re, ep->evp, 0, NULL, 0) == 0) {
   p->cb( ep->evp);
free( ep->evp);
pthread_mutex_unlock( &lsevents_listener_mutex);
eturn NULL;
```

7.3.5 Variable Documentation

7.3.5.1 pthread_mutex_t lsevents_listener_mutex [static]

mutex to protect the listener linked list

Definition at line 37 of file Isevents.c.

7.3.5.2 | Isevents_listener_t*| Isevents_listeners_p = NULL [static]

Pointer to the first item in the link list of listeners.

Definition at line 34 of file Isevents.c.

7.3.5.3 Isevents_queue_t | Isevents_queue[LSEVENTS_QUEUE_LENGTH] [static]

simple list of events

Definition at line 21 of file Isevents.c.

7.3.5.4 pthread_cond_t | sevents_queue_cond [static]

condition to pause the queue if needed

Definition at line 39 of file Isevents.c.

7.3.5.5 pthread_mutex_t | sevents_queue_mutex [static]

mutex to protect the event queue

Definition at line 38 of file Isevents.c.

7.3.5.6 unsigned int lsevents_queue_off = 0 [static] next queue location to read Definition at line 23 of file Isevents.c. 7.3.5.7 unsigned int lsevents_queue_on = 0 [static] next queue location to write Definition at line 22 of file Isevents.c. 7.3.5.8 pthread_t lsevents_thread [static]

thread to run the event queue

Definition at line 36 of file Isevents.c.

7.4 Islogging.c File Reference

Logs messages to a file.

```
#include "pgpmac.h"
```

Data Structures

• struct lslogging_queue_struct

Our log object: time and message.

Macros

• #define LSLOGGING FILE NAME "/tmp/pgpmac.log" Full name of the log file.

#define LSLOGGING_MSG_LENGTH 2048

Fixed maximum length messages to keep some form of sanity.

• #define LSLOGGING_QUEUE_LENGTH 8192

Modest length queue.

Typedefs

· typedef struct lslogging_queue_struct lslogging_queue_t Our log object: time and message.

Functions

• void Islogging_init ()

Initialize the Islogging objects.

void lslogging_log_message (char *fmt,...)

The routine everyone will be talking about.

void * Islogging_worker (void *dummy)

Service the queue, write to the file.

• void lslogging_run ()

Start up the worker thread.

Variables

• static pthread_t lslogging_thread

our thread

• static pthread_mutex_t lslogging_mutex

mutex to keep the various threads from adding to the queue at the exact same time

· static pthread_cond_t lslogging_cond

We'll spend most of our time waiting for this condition's signal.

static FILE * Islogging_file

our log file object

• static lslogging_queue_t lslogging_queue [LSLOGGING_QUEUE_LENGTH]

Our entire queue. Right here. Every message we'll ever write.

• static unsigned int lslogging_on = 0

next location to add to the queue

• static unsigned int Islogging_off = 0

next location to remove from the queue

7.4.1 Detailed Description

Logs messages to a file.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file Islogging.c.

7.4.2 Macro Definition Documentation

7.4.2.1 #define LSLOGGING_FILE_NAME "/tmp/pgpmac.log"

Full name of the log file.

Probably should be in /var/log/pgpmac.

Definition at line 16 of file Islogging.c.

7.4.2.2 #define LSLOGGING_MSG_LENGTH 2048

Fixed maximum length messages to keep some form of sanity.

Definition at line 20 of file Islogging.c.

7.4.2.3 #define LSLOGGING_QUEUE_LENGTH 8192

Modest length queue.

Definition at line 30 of file Islogging.c.

7.4.3 Typedef Documentation

7.4.3.1 typedef struct Islogging_queue_struct Islogging_queue_t

Our log object: time and message.

7.4.4 Function Documentation

```
7.4.4.1 void Islogging_init ( )
```

Initialize the Islogging objects.

Definition at line 37 of file Islogging.c.

7.4.4.2 void lslogging_log_message (char * fmt, ...)

The routine everyone will be talking about.

Parameters

fmt	t A printf style formating string.	
The arguments specified by fmt		

Definition at line 48 of file Islogging.c.

```
7.4.4.3 void Islogging_run ( )
```

Start up the worker thread.

Definition at line 105 of file Islogging.c.

```
pthread_create( &lslogging_thread, NULL, &lslogging_worker
    , NULL);
lslogging_log_message( "Start up");
```

7.4.4.4 void* Islogging_worker (void * dummy)

Service the queue, write to the file.

Parameters

in	dummy	Required by protocol but unused
----	-------	---------------------------------

Definition at line 76 of file Islogging.c.

```
{
struct tm coarsetime;
char tstr[64];
unsigned int msecs;
unsigned int off;
pthread_mutex_lock( &lslogging_mutex);
  while( lslogging_on == lslogging_off) {
    pthread_cond_wait( &lslogging_cond, &lslogging_mutex
  off = (lslogging_off++) % LSLOGGING_QUEUE_LENGTH
  localtime_r( &(lslogging_queue[off].ltime.tv_sec), &
   coarsetime);
  strftime(tstr, sizeof(tstr)-1, "%Y-%m-%d %H:%M:%S", &coarsetime);
  tstr[sizeof(tstr)-1] = 0;
  msecs = lslogging_queue[off].ltime.tv_nsec / 1000;
  fprintf( lslogging_file, "%s.%.06u %s\n", tstr, msecs,
    lslogging_queue[off].lmsg);
  fflush( lslogging_file);
```

7.4.5 Variable Documentation

7.4.5.1 pthread_cond_t lslogging_cond [static]

We'll spend most of our time waiting for this condition's signal.

Definition at line 12 of file Islogging.c.

```
7.4.5.2 FILE* Islogging_file [static]
```

our log file object

Definition at line 17 of file Islogging.c.

7.4.5.3 pthread_mutex_t lslogging_mutex [static]

mutex to keep the various threads from adding to the queue at the exact same time

Definition at line 11 of file Islogging.c.

7.4.5.4 unsigned int slogging_off = 0 [static]

next location to remove from the queue

Definition at line 34 of file Islogging.c.

7.4.5.5 unsigned int |slogging_on = 0 [static]

next location to add to the queue

Definition at line 33 of file Islogging.c.

7.4.5.6 Islogging_queue_t Islogging_queue[LSLOGGING_QUEUE_LENGTH] [static]

Our entire queue. Right here. Every message we'll ever write.

Definition at line 31 of file Islogging.c.

7.4.5.7 pthread_t lslogging_thread [static]

our thread

Definition at line 10 of file Islogging.c.

7.5 Ispg.c File Reference

Postgresql support for the LS-CAT pgpmac project.

```
#include "pgpmac.h"
```

Data Structures

struct lspg_wait_for_detector_struct

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

struct lspg_lock_diffractometer_struct

Object used to impliment locking the diffractometer Critical to exposure timing.

· struct lspg lock detector struct

lock detector object Implements detector lock for exposure control

struct lspg_seq_run_prep_struct

Data collection running object.

Macros

- #define LS_PG_STATE_INIT -4
- #define LS_PG_STATE_INIT_POLL -3
- #define LS_PG_STATE_RESET -2

- #define LS_PG_STATE_RESET_POLL -1
- #define LS_PG_STATE_IDLE 1
- #define LS PG STATE SEND 2
- #define LS PG STATE SEND FLUSH 3
- #define LS PG STATE RECV 4
- #define LS PG QUERY QUEUE LENGTH 16384

Queue length should be long enough that we do not ordinarly bump into the end We should be safe as long as the thread the adds stuff to the queue is not the one that removes it.

Typedefs

· typedef struct

```
lspg_wait_for_detector_struct lspg_wait_for_detector_t
```

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

· typedef struct

```
lspg lock diffractometer struct lspg lock diffractometer t
```

Object used to impliment locking the diffractometer Critical to exposure timing.

· typedef struct

```
lspg_lock_detector_struct lspg_lock_detector_t
```

lock detector object Implements detector lock for exposure control

· typedef struct

```
lspg_seq_run_prep_struct lspg_seq_run_prep_t
```

Data collection running object.

Functions

• lspg_query_queue_t * lspg_query_next ()

Return the next item in the postgresql queue.

void lspg_query_reply_next ()

Remove the oldest item in the queue.

• lspg_query_queue_t * lspg_query_reply_peek ()

Return the next item in the reply queue but don't pop it since we may need it more than once.

void lspg_query_push (void(*cb)(lspg_query_queue_t *, PGresult *), char *fmt,...)

Place a query on the queue.

char ** lspg_array2ptrs (char *a)

returns a null terminated list of strings parsed from postgresql array

- void lspg_starttransfer_init ()
- void lspg_starttransfer_cb (lspg_query_queue_t *qqp, PGresult *pgr)
- void lspg_starttransfer_call (unsigned int nextsample, int sample_detected, double ax, double ay, double az, double horz, double vert, double esttime)
- void lspg_starttransfer_wait ()
- void lspg_starttransfer_done ()
- int lspg_starttransfer_all (int *err, unsigned int nextsample, int sampledetected, double ax, double ay, double az, double horz, double vert, double esttime)
- void lspg getcurrentsampleid init ()
- void lspg_getcurrentsampleid_cb (lspg_query_queue_t *qqp, PGresult *pgr)

get currentsampleid

- void lspg_getcurrentsampleid_call ()
- unsigned int lspg getcurrentsampleid read ()
- · void lspg getcurrentsampleid wait for id (unsigned int test)
- void lspg_nextsample_cb (lspg_query_queue_t *qqp, PGresult *pgr)

```
Next Sample.
void lspg_nextsample_init ()
      Initialize the nextsample variable, mutex, and condition.

    void lspg_nextsample_call ()

      Queue up a nextsample query.
void lspg_nextsample_wait ()
      Wait for the nextsample query to get processed.

    void lspg_nextsample_done ()

      Called when the next shot query has been processed.

    unsigned int lspg_nextsample_all (int *err)

• void lspg waitcryo init ()

    void lspg_waitcryo_cb (lspg_query_queue_t *qqp, PGresult *pgr)

    void lspg_waitcryo_all ()

      no need to get fancy with the wait cryo command It should not return until the robot is almost ready for air rights

    void lspg_demandairrights_init ()

      initialize the demandairrights structure
• void lspg_demandairrights_cb (lspg_query_queue_t *qqp, PGresult *pgr)
      handle the airrights response

    void lspg_demandairrights_call ()

      call for airrights
void lspg_demandairrights_wait ()
      wait for the air rights request to return

    void lspg_demandairrights_all ()

      do nothing until we get airrights

    void lspg_nextshot_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Next Shot Callback.

    void lspg nextshot init ()

      Initialize the nextshot variable, mutex, and condition.

    void lspg_nextshot_call ()

      Queue up a nextshot query.

    void lspg_nextshot_wait ()

      Wait for the next shot query to get processed.
void lspg_nextshot_done ()
      Called when the next shot query has been processed.

    void lspg_wait_for_detector_init ()

      initialize the detector timing object
void lspg_wait_for_detector_cb (lspg_query_queue_t *qqp, PGresult *pgr)
      Callback for the wait for detector query.

    void lspg_wait_for_detector_call ()

      initiate the wait for detector query

    void lspg_wait_for_detector_wait ()

      Pause the calling thread until the detector is ready Called by the MD2 thread.

    void lspg_wait_for_detector_done ()

      Done waiting for the detector.

    void lspg wait for detector all ()

      Combined call to wait for the detector.

    void lspg_lock_diffractometer_init ()

      initialize the diffractometer locking object

    void lspg_lock_diffractometer_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Callback routine for a lock diffractometer query.

    void lspg_lock_diffractometer_call ()
```

```
Request that the database grab the diffractometer lock.

    void lspg_lock_diffractometer_wait ()

      Wait for the diffractometer lock.

    void lspg_lock_diffractometer_done ()

      Finish up the lock diffractometer call.

    void lspg_lock_diffractometer_all ()

      Convience function that combines lock diffractometer calls.
• void lspg_lock_detector_init ()
     Initialize detector lock object.

    void lspg_lock_detector_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Callback for when the detector lock has be grabbed.

    void lspg_lock_detector_call ()

      Request (demand) a detector lock.

    void lspg_lock_detector_wait ()

      Wait for the detector lock.

    void lspg_lock_detector_done ()

      Finish waiting.
• void lspg_lock_detector_all ()
      Detector lock convinence function.
void lspg_seq_run_prep_init ()
      Initialize the data collection object.
void lspg_seq_run_prep_cb (lspg_query_queue_t *qqp, PGresult *pgr)
      Callback for the seq_run_prep query.
· void lspg seg run prep call (long long skey, double kappa, double phi, double cx, double cy, double ax,
  double ay, double az)
      queue up the seq_run_prep query

    void lspg seg run prep wait ()

      Wait for seq run prep query to return.

    void lspg_seq_run_prep_done ()

      Indicate we are done waiting.
• void lspg_seq_run_prep_all (long long skey, double kappa, double phi, double cx, double cy, double ax,
  double ay, double az)
      Convinence function to call seq run prep.

    void lspg_getcenter_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Retrieve the data to center the crystal.

    void lspg_getcenter_init ()

      Initialize getcenter object.

    void lspg_getcenter_call ()

      Request a getcenter query.
void lspg_getcenter_wait ()
      Wait for a getcenter query to return.
• void lspg_getcenter_done ()
      Done with getcenter query.

    void lspg_getcenter_all ()

      Convenience function to complete synchronous getcenter query.

    void lspg_nextaction_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Queue the next MD2 instruction.

    void lspg_cmd_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Send strings directly to PMAC queue.

    void lspg flush ()

      Flush psql output buffer (ie, send the guery)
```

```
    void lspg_send_next_query ()

          send the next queued query to the DB server

    void lspg_receive ()

          Receive a result of a query.

    void lspg_sig_service (struct pollfd *evt)

          Service a signal Signals here are treated as file descriptors and fits into our poll scheme.

    void lspg pg service (struct pollfd *evt)

          I/O control to/from the postgresql server.

    PQnoticeProcessor lspg_notice_processor (void *arg, const char *msg)

    void lspg_pg_connect ()

          Connect to the pg server.
    void lspg_next_state ()
          Implements our state machine Does not strictly only set the next state as it also calls some functions that, perhaps,
          alters the state mid-function.
    void * lspg_worker (void *dummy)
          The main loop for the Ispg thread.

    void lspmac_sample_detector_cb (char *event)

          log magnet state
    • void lspg_init ()
          Initiallize the Ispg module.
    • void lspg run ()
          Start 'er runnin'.
Variables

    static int ls pg state = LS PG STATE INIT

          State of the Ispg state machine.
    · static struct timeval
      Ispg time sent now
          used to ensure we do not inundate the db server with connection requests
    · static pthread_t lspg_thread
          our worker thread

    static pthread_mutex_t lspg_queue_mutex

          keep the queue from getting tangled

    static pthread_cond_t lspg_queue_cond

          keeps the queue from overflowing
    · static struct pollfd lspgfd
          our poll info
    • static lspg_query_queue_t lspg_query_queue [LS_PG_QUERY_QUEUE_LENGTH]
          Our query queue.
    • static unsigned int lspg_query_queue_on = 0
          Next position to add something to the queue.

    static unsigned int lspg_query_queue_off = 0

          The last item still being used (on == off means nothing in queue)

    static unsigned int lspg_query_queue_reply = 0
```

Generated on Wed Jan 23 2013 10:19:08 for LS-CAT PGPMAC by Doxygen

Used to determine state while connecting.

static PostgresPollingStatusType lspg_connectPoll_response

• static PostgresPollingStatusType lspg_resetPoll_response

The current item being digested.

 static PGconn * q = NULL Database connector.

Used to determine state while reconnecting.

lspg_nextsample_t lspg_nextsample

the very next sample

· lspg_nextshot_t lspg_nextshot

the nextshot object

• lspg_getcenter_t lspg_getcenter

the getcenter object

lspg_demandairrights_t lspg_demandairrights

our demandairrights object

· lspg_getcurrentsampleid_t lspg_getcurrentsampleid

our currentsample id

· lspg_starttransfer_t lspg_starttransfer

start a sample transfer

lspg_waitcryo_t lspg_waitcryo

signal the robot

static lspg_wait_for_detector_t lspg_wait_for_detector

Instance of the detector timing object.

- static lspg_lock_diffractometer_t lspg_lock_diffractometer
- static lspg_lock_detector_t lspg_lock_detector
- static lspg_seq_run_prep_t lspg_seq_run_prep

7.5.1 Detailed Description

Postgresql support for the LS-CAT pgpmac project.

```
\date 2012
\author Keith Brister
\copyright All Rights Reserved
```

Database state machine

State	Description
-4	Initiate connection
-3	Poll until connection initialization is complete
-2	Initiate reset
-1	Poll until connection reset is complete
1	Idle (wait for a notify from the server)
2	Send a query to the server
3	Continue flushing a command to the server
4	Waiting for a reply

Definition in file lspg.c.

7.5.2 Macro Definition Documentation

7.5.2.1 #define LS_PG_QUERY_QUEUE_LENGTH 16384

Queue length should be long enough that we do not ordinarly bump into the end We should be safe as long as the thread the adds stuff to the queue is not the one that removes it.

(And we can tolerate the adding thread being paused.)

Definition at line 51 of file lspg.c.

7.5.2.2 #define LS_PG_STATE_IDLE 1

Definition at line 34 of file lspg.c.

7.5.2.3 #define LS_PG_STATE_INIT -4

Definition at line 30 of file lspg.c.

7.5.2.4 #define LS_PG_STATE_INIT_POLL -3

Definition at line 31 of file lspg.c.

7.5.2.5 #define LS_PG_STATE_RECV 4

Definition at line 37 of file lspg.c.

7.5.2.6 #define LS_PG_STATE_RESET -2

Definition at line 32 of file lspg.c.

7.5.2.7 #define LS_PG_STATE_RESET_POLL -1

Definition at line 33 of file lspg.c.

7.5.2.8 #define LS_PG_STATE_SEND 2

Definition at line 35 of file lspg.c.

7.5.2.9 #define LS_PG_STATE_SEND_FLUSH 3

Definition at line 36 of file lspg.c.

7.5.3 Typedef Documentation

7.5.3.1 typedef struct lspg_lock_detector_struct lspg_lock_detector_t

lock detector object Implements detector lock for exposure control

7.5.3.2 typedef struct lspg_lock_diffractometer_struct lspg_lock_diffractometer_t

Object used to impliment locking the diffractometer Critical to exposure timing.

7.5.3.3 typedef struct lspg_seq_run_prep_struct lspg_seq_run_prep_t

Data collection running object.

7.5.3.4 typedef struct lspg_wait_for_detector_struct lspg_wait_for_detector_t

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

7.5.4 Function Documentation

7.5.4.1 char** lspg_array2ptrs (char * a)

returns a null terminated list of strings parsed from postgresql array

Definition at line 161 of file lspg.c.

```
char **rtn, *sp, *acums;
int i, n, inquote, havebackslash, rtni;;
int mxsz:
inquote
havebackslash = 0;
// Despense with the null input condition before we complicate the code below
if( a == NULL || a[0] != '{' || a[strlen(a)-1] != '}')
 return NULL;
// Count the maximum number of strings
// Actual number will be less if there are quoted commas
11
n = 1;
for( i=0; a[i]; i++) {
 if(a[i] == ',')
   n++;
// The maximum size of any string is the length of a (+1)
mxsz = strlen(a) + 1;
// This is the accumulation string to make up the array elements
acums = (char *)calloc( mxsz, sizeof( char));
if( acums == NULL) {
 lslogging_log_message( "lspg_array2ptrs: out of memory
  (acums)");
 exit(1);
^{\prime\prime} allocate storage for the pointer array and the null terminator
rtn = (char **)calloc( n+1, sizeof( char *));
if( rtn == NULL) {
 lslogging_log_message( "lspg_array2ptrs: out of memory
    (rtn)");
 exit( 1);
rtni = 0;
// Go through and create the individual strings
sp = acums;
*sp = 0;
inquote = 0;
havebackslash = 0;
for( i=1; a[i] != 0; i++) {
  switch( a[i]) {
case '"':
   if( havebackslash) {
     // a quoted quote. Cool
      *(sp++) = a[i];
      *sp = 0;
      havebackslash = 0;
    } else {
  // Toggle the flag
      inquote = 1 - inquote;
    break;
  case '\\':
   if ( havebackslash) {
     *(sp++) = a[i];
*sp = 0;
     havebackslash = 0;
     havebackslash = 1;
    break:
  case ',':
```

```
if( inquote || havebackslash) {
     *(sp++) = a[i];
*sp = 0;
      havebackslash = 0;
    } else {
      rtn[rtni++] = strdup( acums);
      sp = acums;
    break;
  case '}':
   if( inquote || havebackslash) {
     *(sp++) = a[i];
*sp = 0;
      havebackslash = 0;
    } else {
  rtn[rtni++] = strdup( acums);
      rtn[rtni] = NULL;
free( acums);
      return( rtn);
    break;
  default:
    *(sp++) = a[i];
    havebackslash = 0;
// Getting here means the final '}' was missing
// Probably we should throw an error or log it or something.
// Through out the last entry since this there is not resonable expectation
\ensuremath{//} we should be parsing it anyway.
rtn[rtni] = NULL;
free ( acums);
return( rtn);
```

7.5.4.2 void lspg_cmd_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Send strings directly to PMAC queue.

Parameters

in	qqp	Our query
in	pgr	Our result

Definition at line 1238 of file lspg.c.

```
{
//
// Call back funciton assumes query results in zero or more commands to send
    to the PMAC
//
int i;
char *sp;

for( i=0; i<PQntuples( pgr); i++) {
    sp = PQgetvalue( pgr, i, 0);
    if( sp != NULL && *sp != 0) {
        lspmac_SockSendDPline( NULL, sp);
        // lspmac_SockSendline( sp);
        //
        // Keep asking for more until
        // there are no commands left
        //
        // This should solve a potential problem where
        // more than one command is put on the queue for a given notify.
        lspg_query_push( lspg_cmd_cb, "select
        pmac.md2_queue_next()");
    }
}</pre>
```

```
7.5.4.3 void lspg_demandairrights_all ( )
do nothing until we get airrights
Definition at line 556 of file lspg.c.
  lspg_demandairrights_call();
  lspg_demandairrights_wait();
// there is no "done" version
7.5.4.4 void lspg_demandairrights_call ( )
call for airrights
Definition at line 538 of file lspg.c.
  pthread_mutex_lock( &lspg_demandairrights.mutex);
   lspg_demandairrights.new_value_ready = 0;
  pthread_mutex_unlock( &lspg_demandairrights.mutex);
  lspg_query_push( lspg_demandairrights_cb
    , "SELECT px.demandairrights())");
7.5.4.5 void lspg\_demandairrights\_cb ( lspg\_query\_queue\_t*qqp, PGresult*pgr)
handle the airrights response
Definition at line 529 of file Ispg.c.
  pthread_mutex_lock( &lspg_demandairrights.mutex);
  lspg_demandairrights.new_value_ready = 1;
pthread_cond_signal( &lspg_demandairrights.cond);
pthread_mutex_unlock( &lspg_demandairrights.mutex);
7.5.4.6 void lspg_demandairrights_init ( )
initialize the demandairrights structure
Definition at line 521 of file lspg.c.
   lspg_demandairrights.new_value_ready = 0;
  pthread_mutex_init( &lspg_demandairrights.mutex,
       NULL);
  pthread_cond_init( &lspg_demandairrights.cond, NULL);
7.5.4.7 void lspg_demandairrights_wait ( )
wait for the air rights request to return
Definition at line 547 of file Ispg.c.
  pthread_mutex_lock( &lspg_demandairrights.mutex);
while( lspg_demandairrights.new_value_ready
     pthread_cond_wait( &lspg_demandairrights.cond, &
       lspg_demandairrights.mutex);
  pthread_mutex_unlock( &lspg_demandairrights.mutex);
```

```
7.5.4.8 void lspg_flush ( )
```

Flush psql output buffer (ie, send the query)

Definition at line 1268 of file lspg.c.

```
{
int err;
err = PQflush(q);
switch( err) {
case -1:
 // an error occured
  lslogging_log_message( "flush failed: %s",
    PQerrorMessage(q));
  ls_pg_state = LS_PG_STATE_IDLE;
  ^{\prime\prime} // We should probably reset the connection and start from scratch.
     Probably the connection died.
  break:
  // goodness and joy.
  ls_pg_state = LS_PG_STATE_RECV;
  // more sending to do
  ls_pg_state = LS_PG_STATE_SEND_FLUSH;
```

7.5.4.9 void lspg_getcenter_all ()

Convenience function to complete synchronous getcenter query.

Definition at line 1201 of file lspg.c.

```
lspg_getcenter_call();
lspg_getcenter_wait();
lspg_getcenter_done();
```

7.5.4.10 void lspg_getcenter_call ()

Request a getcenter query.

Definition at line 1177 of file Ispg.c.

```
fpthread_mutex_lock( &lspg_getcenter.mutex);
lspg_getcenter.new_value_ready = 0;
pthread_mutex_unlock( &lspg_getcenter.mutex);
lspg_query_push( lspg_getcenter_cb, "SELECT *
    FROM px.getcenter2()");
```

7.5.4.11 void $lspg_getcenter_cb$ ($lspg_query_queue_t*qqp$, PGresult*pgr)

Retrieve the data to center the crystal.

Definition at line 1112 of file Ispg.c.

```
static int
    zoom_c, dcx_c, dcy_c, dax_c, day_c, daz_c;
  pthread_mutex_lock( &(lspg_getcenter.mutex));
  lspg_getcenter.no_rows_returned = PQntuples(
       pgr) <= 0;
  if( lspg_getcenter.no_rows_returned) {
    // No particular reason this path should ever be taken // but if we don't get rows then we had better not move anything.
    lspg_getcenter.new_value_ready = 1;
    pthread_cond_signal( &(lspg_getcenter.cond));
    pthread_mutex_unlock( &(lspg_getcenter.mutex));
     return:
  zoom_c = PQfnumber( pgr, "zoom");
dcx_c = PQfnumber( pgr, "dcx");
dcy_c = PQfnumber( pgr, "dcy");
dax_c = PQfnumber( pgr, "dax");
day_c = PQfnumber( pgr, "day");
daz_c = PQfnumber( pgr, "daz");
  lspg_getcenter.zoom_isnull = PQgetisnull( pgr, 0,
       zoom_c);
  if( lspg_getcenter.zoom_isnull == 0)
    lspg_getcenter.zoom = atoi( PQgetvalue( pgr, 0, zoom_c));
  lspg_getcenter.dcx_isnull = PQgetisnull( pgr, 0,
      dcx_c);
  if( lspg_getcenter.dcx_isnull == 0)
    lspg_getcenter.dcx = atof( PQgetvalue( pgr, 0, dcx_c));
  lspg_getcenter.dcy_isnull = PQgetisnull( pgr, 0,
       dcy_c);
  if( lspg_getcenter.dcy_isnull == 0)
    lspg_getcenter.dcy = atof( PQgetvalue( pgr, 0, dcy_c));
  lspg_getcenter.dax_isnull = PQgetisnull( pgr, 0,
       dax c);
  if( lspg_getcenter.dax_isnull == 0)
    lspg_getcenter.dax = atof( PQgetvalue( pgr, 0, dax_c));
  lspg_getcenter.day_isnull = PQgetisnull( pgr, 0,
       day_c);
  if( lspg_getcenter.day_isnull == 0)
    lspg_getcenter.day = atof( PQgetvalue( pgr, 0, day_c));
  lspg_getcenter.daz_isnull = PQgetisnull( pgr, 0,
       daz_c);
  if( lspg_getcenter.daz_isnull == 0)
    lspg_getcenter.daz = atof( PQgetvalue( pgr, 0, daz_c));
  lspg_getcenter.new_value_ready = 1;
  pthread_cond_signal( &(lspg_getcenter.cond));
  pthread_mutex_unlock( &(lspg_getcenter.mutex));
7.5.4.12 void lspg_getcenter_done ( )
Done with getcenter query.
Definition at line 1195 of file lspg.c.
  pthread_mutex_unlock( &(lspg_getcenter.mutex));
7.5.4.13 void lspg_getcenter_init ( )
Initialize getcenter object.
```

Definition at line 1169 of file Ispg.c.

```
memset( &lspg_getcenter, 0, sizeof( lspg_getcenter
  pthread_mutex_init( &(lspg_getcenter.mutex), NULL);
  pthread_cond_init( &(lspg_getcenter.cond), NULL);
7.5.4.14 void lspg_getcenter_wait ( )
Wait for a getcenter query to return.
Definition at line 1187 of file lspg.c.
  pthread_mutex_lock( &(lspg_getcenter.mutex));
  while( lspg_getcenter.new_value_ready == 0)
  pthread_cond_wait( &(lspg_getcenter.cond), &(
      lspg_getcenter.mutex));
7.5.4.15 void lspg_getcurrentsampleid_call ( )
Definition at line 367 of file lspg.c.
  \verb|pthread_mutex_lock(&lspg_getcurrentsampleid.mutex|\\
  lspg_getcurrentsampleid.new_value_ready
       = 0;
  pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
  lspg\_query\_push (\ lspg\_getcurrentsampleid\_cb
      , "SELECT px.getcurrentsampleid()");
7.5.4.16 void lspg_getcurrentsampleid_cb ( lspg_query_queue_t*qqp, PGresult*pgr)
get currentsampleid
Definition at line 346 of file Ispg.c.
  pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
      );
  lspg_nextsample.new_value_ready = 1;
  lspg_getcurrentsampleid.no_rows_returned
       = PQntuples( pgr) <= 0;
  if( lspg_getcurrentsampleid.no_rows_returned
    pthread_cond_signal( &lspg_getcurrentsampleid.cond
    pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    return;
```

== 0)

);

}

7.5.4.17 void lspg_getcurrentsampleid_init ()

Definition at line 338 of file lspg.c.

7.5.4.18 unsigned int lspg_getcurrentsampleid_read ()

Definition at line 377 of file lspg.c.

```
unsigned int rtn;
pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
    );
while( lspg_getcurrentsampleid.new_value_ready
    == 0)
pthread_cond_wait( &lspg_getcurrentsampleid.cond
    , &lspg_getcurrentsampleid.mutex);

if( lspg_getcurrentsampleid.getcurrentsampleid_isnull
    )
    rtn = -1;
else
    rtn = lspg_getcurrentsampleid.getcurrentsampleid
    ;
pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    );
return rtn;
```

7.5.4.19 void lspg_getcurrentsampleid_wait_for_id (unsigned int test)

Definition at line 393 of file lspg.c.

```
pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
    );
while( lspg_getcurrentsampleid.getcurrentsampleid
    != test)
pthread_cond_wait( &lspg_getcurrentsampleid.cond
    , &lspg_getcurrentsampleid.mutex);
pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    );
```

7.5.4.20 void lspg_init ()

Initiallize the Ispg module.

Definition at line 1758 of file lspg.c.

```
{
pthread_mutex_init( &lspg_queue_mutex, NULL);
pthread_cond_init( &lspg_queue_cond, NULL);

lspg_demandairrights_init();
lspg_getcenter_init();
lspg_getcurrentsampleid_init();
lspg_lock_detector_init();
lspg_lock_diffractometer_init();
lspg_nextsample_init();
```

```
lspg_nextshot_init();
  lspg_seq_run_prep_init();
  lspg_starttransfer_init();
  lspg_wait_for_detector_init();
  lspg_waitcryo_init();
7.5.4.21 void lspg_lock_detector_all ( )
Detector lock convinence function.
Definition at line 1024 of file lspg.c.
  lspg_lock_detector_call();
  lspg_lock_detector_wait();
  lspg_lock_detector_done();
7.5.4.22 void lspg_lock_detector_call ( )
Request (demand) a detector lock.
Definition at line 1000 of file lspg.c.
  pthread_mutex_lock( &(lspg_lock_detector.mutex));
lspg_lock_detector.new_value_ready = 0;
  pthread_mutex_unlock( &(lspg_lock_detector.mutex));
  7.5.4.23 void lspg_lock_detector_cb ( lspg_query_queue_t * qqp, PGresult * pgr )
Callback for when the detector lock has be grabbed.
Definition at line 991 of file lspg.c.
  pthread_mutex_lock( &(lspg_lock_detector.mutex));
  lspg_lock_detector.new_value_ready = 1;
  pthread_cond_signal( &(lspg_lock_detector.cond));
  pthread_mutex_unlock( &(lspg_lock_detector.mutex));
7.5.4.24 void lspg_lock_detector_done ( )
Finish waiting.
Definition at line 1018 of file lspg.c.
 pthread_mutex_unlock( &(lspg_lock_detector.mutex));
```

```
7.5.4.25 void lspg_lock_detector_init ( )
```

Initialize detector lock object.

Definition at line 983 of file lspg.c.

```
lspg_lock_detector.new_value_ready = 0;
pthread_mutex_init( &(lspg_lock_detector.mutex), NULL);
pthread_cond_init( &(lspg_lock_detector.cond), NULL);
```

7.5.4.26 void lspg_lock_detector_wait ()

Wait for the detector lock.

Definition at line 1010 of file lspg.c.

7.5.4.27 void lspg_lock_diffractometer_all ()

Convience function that combines lock diffractometer calls.

Definition at line 965 of file Ispg.c.

```
lspg_lock_diffractometer_call();
lspg_lock_diffractometer_wait();
lspg_lock_diffractometer_all();
}
```

7.5.4.28 void lspg_lock_diffractometer_call ()

Request that the database grab the diffractometer lock.

Definition at line 941 of file lspg.c.

7.5.4.29 void lspg_lock_diffractometer_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Callback routine for a lock diffractometer query.

Definition at line 932 of file Ispg.c.

7.5.4.30 void lspg_lock_diffractometer_done ()

Finish up the lock diffractometer call.

Definition at line 959 of file Ispg.c.

```
pthread_mutex_unlock( &(lspg_lock_diffractometer.
    mutex));
```

7.5.4.31 void lspg_lock_diffractometer_init ()

initialize the diffractometer locking object

Definition at line 924 of file Ispg.c.

7.5.4.32 void lspg_lock_diffractometer_wait ()

Wait for the diffractometer lock.

Definition at line 951 of file lspg.c.

7.5.4.33 void lspg_next_state ()

Implements our state machine Does not strictly only set the next state as it also calls some functions that, perhaps, alters the state mid-function.

Definition at line 1623 of file lspg.c.

```
{
//
// connect to the database
//
if( q == NULL ||
    ls_pg_state == LS_PG_STATE_INIT ||
```

```
ls_pg_state == LS_PG_STATE_RESET ||
    ls_pg_state == LS_PG_STATE_INIT_POLL ||
ls_pg_state == LS_PG_STATE_RESET_POLL)
  lspg_pg_connect( lspgfd);
if( ls_pg_state == LS_PG_STATE_IDLE &&
    lspg_query_queue_on != lspg_query_queue_off
  ls_pg_state = LS_PG_STATE_SEND;
switch( ls_pg_state) {
case LS_PG_STATE_INIT_POLL:
  if( lspg_connectPoll_response ==
    PGRES_POLLING_WRITING)
    lspgfd.events = POLLOUT;
  else if( lspg_connectPoll_response ==
    PGRES_POLLING_READING)
    lspgfd.events = POLLIN;
    lspgfd.events = 0;
  break;
case LS_PG_STATE_RESET_POLL:
  if( lspg_resetPoll_response == PGRES_POLLING_WRITING
    lspgfd.events = POLLOUT;
  else if( lspg_resetPoll_response ==
   PGRES_POLLING_READING)
    lspqfd.events = POLLIN;
  else
    lspgfd.events = 0;
  break;
case LS_PG_STATE_IDLE:
case LS_PG_STATE_RECV:
  lspgfd.events = POLLIN;
case LS_PG_STATE_SEND:
case LS_PG_STATE_SEND_FLUSH:
  lspgfd.events = POLLOUT;
  break:
default:
  lspgfd.events = 0;
```

7.5.4.34 void lspg_nextaction_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Queue the next MD2 instruction.

Parameters

in	qqp	The query that generated this result
in	pgr	The result

Definition at line 1210 of file lspg.c.

```
lslogging_log_message( "MD2 command '%s' ignored.
         Already running '%s'", action, md2cmds_cmd);
}
```

7.5.4.35 unsigned int lspg_nextsample_all (int * err)

Definition at line 468 of file lspg.c.

```
unsigned int rtn;
lspg_nextsample_call();
lspg_nextsample_wait();

if( lspg_nextsample.no_rows_returned) {
   rtn = 0;
   *err = 1;
} else {
   if( lspg_nextsample.nextsample_isnull) {
      rtn = 0;
      *err = 1;
} else {
      rtn = lspg_nextsample.nextsample;
      *err = 0;
}
}lspg_nextsample_done();
return rtn;
```

7.5.4.36 void lspg_nextsample_call ()

Queue up a nextsample query.

Definition at line 445 of file Ispg.c.

7.5.4.37 void lspg_nextsample_cb ($lspg_query_queue_t * qqp$, $pg_query_queue_t * qqp$, pg_qq

Next Sample.

Parameters

in	qqp	Our nextsample query
in	pgr	result of the query

Definition at line 404 of file Ispg.c.

```
{
static int got_columns = 0;
static int nextsample_col;
pthread_mutex_lock( &(lspg_nextsample.mutex));

lspg_nextsample.no_rows_returned = PQntuples(
    pgr) <= 0;
if( lspg_nextsample.no_rows_returned) {
    lslogging_log_message( "lspg_nextsample_cb: no rows
    returned. This should never happen.");</pre>
```

```
lspg_nextsample.new_value_ready = 1;
pthread_cond_signal( & (lspg_nextsample.cond));
pthread_mutex_unlock( & (lspg_nextsample.mutex));
return;
}

if( got_columns == 0) {
    nextsample_col = PQfnumber( pgr, "nextsample");
    got_columns = 1;
}

lspg_nextsample.nextsample_isnull =
    PQgetisnull( pgr, 0, nextsample_col);
if( lspg_nextsample.nextsample_isnull == 0)
    lspg_nextsample.nextsample = strtol( PQgetvalue( pgr, 0, nextsample_col), NULL, 0);

lspg_nextsample.new_value_ready = 1;
pthread_cond_signal( & (lspg_nextsample.cond));
pthread_mutex_unlock( & (lspg_nextsample.mutex));
```

7.5.4.38 void lspg_nextsample_done ()

Called when the next shot query has been processed.

Definition at line 463 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_nextsample.mutex));
}
```

7.5.4.39 void lspg_nextsample_init ()

Initialize the nextsample variable, mutex, and condition.

Definition at line 437 of file lspg.c.

```
memset( &lspg_nextsample, 0, sizeof( lspg_nextsample
    ));
pthread_mutex_init( &(lspg_nextsample.mutex), NULL);
pthread_cond_init( &(lspg_nextsample.cond), NULL);
}
```

7.5.4.40 void lspg_nextsample_wait ()

Wait for the nextsample query to get processed.

Definition at line 455 of file Ispg.c.

7.5.4.41 void lspg_nextshot_call ()

Queue up a nextshot query.

Definition at line 824 of file Ispg.c.

7.5.4.42 void lspg_nextshot_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Next Shot Callback.

This is a long and tedious routine as there are a large number of variables returned. Suck it up. Return with the global object lspg_nextshot set.

Parameters

in	qqp	Our nextshot query
in	pgr	result of the query

Definition at line 569 of file lspg.c.

```
static int got_col_nums=0;
static int
     dsdir_c, dspid_c, dsowidth_c, dsoscaxis_c, dsexp_c, skey_c, sstart_c, sfn_c
             , dsphi_c,
      dsomega_c, dskappa_c, dsdist_c, dsnrg_c, dshpid_c, cx_c, cy_c, ax_c, ay_c,
      active_c, sindex_c, stype_c,
     dsowidth2_c, dsoscaxis2_c, dsexp2_c, sstart2_c, dsphi2_c, dsomega2_c,
   dskappa2_c, dsdist2_c, dsnrg2_c,
      cx2_c, cy2_c, ax2_c, ay2_c, az2_c, active2_c, sindex2_c, stype2_c;
pthread_mutex_lock( &(lspg_nextshot.mutex));
lspg_nextshot.no_rows_returned = PQntuples( pgr)
               <= 0;
if( lspg_nextshot.no_rows_returned) {
      lspg_nextshot.new_value_ready = 1;
      pthread_cond_signal( &(lspg_nextshot.cond));
      pthread_mutex_unlock( &(lspg_nextshot.mutex));
      return;
                                                                                                // I guess there was no shot after all
if( got_col_nums == 0) {
     dsdir_c
dspid_c
dspid_c
dspid_c
dsowidth_c
dsowidth_c
dsoscaxis_c
dsexp_c
dsexp_c
skey_c
skey_c
systart_c
pQfnumber(pgr, "dsoxids");
dsomega_c
dsdist_c
dsdist_c
dsdist_c
dshid_c
dshi
      dspid_c
      dsoscaxis2_c = PQfnumber( pgr, "dsoscaxis2");
      dsexp2_c = PQfnumber(pgr, "dsexp2");

sstart2_c = PQfnumber(pgr, "sstart2");

dsphi2_c = PQfnumber(pgr, "dsphi2");
```

```
cx2_c
               = PQfnumber( pgr, "cx2");
              PQfnumber( pgr, "cx2");
PQfnumber( pgr, "cy2");
PQfnumber( pgr, "ax2");
PQfnumber( pgr, "ay2");
PQfnumber( pgr, "az2");
PQfnumber( pgr, "active2");
PQfnumber( pgr, "sindex2");
PQfnumber( pgr, "stype2");
  cy2_c
  ax2_c
  ay2_c
  az2 c
  active2_c
  sindex2_c
  stype2_c
 got_col_nums = 1;
// NULL string values come back as empty strings
// Mark the null flag but allocate the empty string anyway
lspg_nextshot.dsdir_isnull = PQgetisnull( pgr, 0,
    dsdir_c);
if( lspg_nextshot.dsdir != NULL)
  free( lspg_nextshot.dsdir);
lspg_nextshot.dsdir = strdup( PQgetvalue( pgr, 0, dsdir_c))
lspg_nextshot.dspid_isnull = PQgetisnull( pgr, 0,
if( lspg_nextshot.dspid != NULL)
free( lspg_nextshot.dspid);
lspg_nextshot.dspid = strdup( PQgetvalue( pgr, 0, dspid_c))
lspg_nextshot.dsoscaxis_isnull = PQgetisnull(
    pgr, 0, dsoscaxis_c);
if( lspg_nextshot.dsoscaxis != NULL)
  free( lspg_nextshot.dsoscaxis);
lspg_nextshot.dsoscaxis = strdup( PQgetvalue( pgr, 0,
    dsoscaxis_c));
lspg_nextshot.dsoscaxis2_isnull = PQgetisnull(
    pgr, 0, dsoscaxis2_c);
if( lspg_nextshot.dsoscaxis2 != NULL)
free( lspg_nextshot.dsoscaxis2);
lspg_nextshot.dsoscaxis2 = strdup( PQgetvalue( pgr, 0,
     dsoscaxis2_c));
lspg_nextshot.sfn_isnull = PQgetisnull(pgr, 0, sfn_c);
if( lspg_nextshot.sfn != NULL)
 free( lspg_nextshot.sfn);
lspg_nextshot.sfn = strdup( PQgetvalue( pgr, 0, sfn_c));
lspg_nextshot.stype_isnull = PQgetisnull( pgr, 0,
    stype_c);
if( lspg_nextshot.stype != NULL)
  free( lspg_nextshot.stype);
lspg_nextshot.stype = strdup( PQgetvalue( pgr, 0, stype_c))
lspg_nextshot.stype2_isnull = PQgetisnull( pgr, 0,
    stype2_c);
if( lspg_nextshot.stype2 != NULL)
 free( lspg_nextshot.stype2);
lspg_nextshot.stype2 = strdup( PQgetvalue( pgr, 0,
    stype2_c));
lspg_nextshot.dsowidth_isnull = PQgetisnull( pgr,
     0, dsowidth_c);
if( lspg_nextshot.dsowidth_isnull == 0)
  lspg_nextshot.dsowidth = atof( PQgetvalue( pgr,0,
    dsowidth_c));
lspg nextshot.dsexp isnull = POgetisnull( pgr, 0,
    dsexp_c);
if( lspg_nextshot.dsexp_isnull == 0)
  lspg_nextshot.dsexp = atof( PQgetvalue( pgr,0, dsexp_c
    ));
lspg_nextshot.sstart_isnull = PQgetisnull( pgr, 0,
    sstart_c);
if( lspg_nextshot.sstart_isnull == 0)
  lspg_nextshot.sstart
                          = atof( PQgetvalue( pgr,0,
    sstart_c));
lspg_nextshot.dsphi_isnull = PQgetisnull( pgr, 0,
```

```
dsphi_c);
if( lspg_nextshot.dsphi_isnull == 0)
  lspg_nextshot.dsphi
                       = atof( PQgetvalue( pgr,0, dsphi_c
lspg_nextshot.dsomega_isnull = PQgetisnull( pgr, 0
   , dsomega_c);
if( lspg_nextshot.dsomega_isnull == 0)
  lspg_nextshot.dsomega = atof( PQgetvalue( pgr,0,
    dsomega_c));
lspg_nextshot.dskappa_isnull = PQgetisnull( pgr, 0
, dskappa_c);
if( lspg_nextshot.dskappa_isnull == 0)
  lspg_nextshot.dskappa = atof( PQgetvalue( pgr,0,
    dskappa_c));
lspg_nextshot.dsdist_isnull = PQgetisnull( pgr, 0,
   dsdist_c);
if( lspg_nextshot.dsdist_isnull == 0)
  lspg_nextshot.dsdist = atof( PQgetvalue( pgr, 0,
    dsdist_c));
lspg_nextshot.dsnrg_isnull = PQgetisnull( pgr, 0,
   dsnrg_c);
if( lspg_nextshot.dsnrg_isnull == 0)
  lspg_nextshot.dsnrg
                        = atof( PQgetvalue( pgr,0, dsnrg_c
lspg_nextshot.cx_isnull = PQgetisnull( pgr, 0, cx_c);
if( lspg_nextshot.cx_isnull == 0)
 lspg_nextshot.cx
                        = atof( PQgetvalue( pgr,0, cx_c));
lspg_nextshot.cy_isnull = PQgetisnull( pgr, 0, cy_c);
if( lspg_nextshot.cy_isnull == 0)
                        = atof( PQgetvalue( pgr,0, cy_c));
 lspq_nextshot.cy
lspg_nextshot.ax_isnull = PQgetisnull( pgr, 0, ax_c);
if( lspg_nextshot.ax_isnull == 0)
 lspg_nextshot.ax
                        = atof( PQgetvalue( pgr,0, ax_c));
lspg_nextshot.ay_isnull = POgetisnull( pgr, 0, ay_c);
if( lspg_nextshot.ay_isnull == 0)
  lspg_nextshot.ay
                        = atof( PQgetvalue( pgr,0, ay_c));
lspg_nextshot.az_isnull = PQgetisnull( pgr, 0, az_c);
if( lspg_nextshot.az_isnull == 0)
  lspg_nextshot.az
                        = atof( PQgetvalue( pgr,0, az_c));
lspg_nextshot.active_isnull = PQgetisnull( pgr, 0,
   active_c);
if( lspg_nextshot.active_isnull == 0)
  lspg_nextshot.active = atoi( PQgetvalue( pgr, 0,
    active_c));
lspg nextshot.sindex isnull = POgetisnull( pgr, 0,
   sindex_c);
if( lspg_nextshot.sindex_isnull == 0)
  lspg_nextshot.sindex = atoi( PQgetvalue( pgr, 0,
    sindex_c));
lspg_nextshot.dshpid_isnull = PQgetisnull( pgr, 0,
    dshpid_c);
if( lspg_nextshot.dshpid_isnull == 0)
  lspg_nextshot.dshpid = atoi( PQgetvalue( pgr, 0,
    dshpid_c));
lspg nextshot.skev isnull = POgetisnull( pgr, 0,
   skey_c);
if( lspg_nextshot.skey_isnull == 0)
  lspg_nextshot.skey = atoll( PQgetvalue( pgr, 0, skey_c))
lspg_nextshot.dsowidth2_isnull = PQgetisnull(
   pgr, 0, dsowidth2_c);
if( lspg_nextshot.dsowidth2_isnull == 0)
  lspg_nextshot.dsowidth2 = atof( PQgetvalue( pgr, 0,
    dsowidth2_c));
lspg_nextshot.dsexp2_isnull = PQgetisnull( pgr, 0,
   dsexp2_c);
if( lspg_nextshot.dsexp2_isnull == 0)
  lspg_nextshot.dsexp2
                        = atof( PQgetvalue( pgr,0,
    dsexp2_c));
lspg_nextshot.sstart2_isnull = PQgetisnull( pgr, 0
    , sstart2_c);
```

```
if( lspg_nextshot.sstart2_isnull == 0)
 lspg_nextshot.sstart2 = atof( PQgetvalue( pgr, 0,
    sstart2_c));
lspg_nextshot.dsphi2_isnull = PQgetisnull( pgr, 0,
    dsphi2 c);
if( lspg_nextshot.dsphi2_isnull == 0)
  lspg_nextshot.dsphi2
                           = atof( PQgetvalue( pgr,0,
    dsphi2_c));
lspg_nextshot.dsomega2_isnull = PQgetisnull( pgr,
     0, dsomega2_c);
if( lspg_nextshot.dsomega2_isnull == 0)
  lspg_nextshot.dsomega2 = atof( PQgetvalue( pgr, 0,
    dsomega2_c));
lspg_nextshot.dskappa2_isnull = PQgetisnull( pgr,
     0, dskappa2_c);
if( lspg_nextshot.dskappa2_isnull == 0)
  lspg_nextshot.dskappa2 = atof( PQgetvalue( pgr, 0,
    dskappa2_c));
lspg_nextshot.dsdist2_isnull = PQgetisnull( pgr, 0
    , dsdist2_c);
if( lspg_nextshot.dsdist2_isnull == 0)
  lspg_nextshot.dsdist2 = atof( PQgetvalue( pgr, 0,
    dsdist2_c));
lspg_nextshot.dsnrg2_isnull = PQgetisnull( pgr, 0,
    dsnrg2_c);
if( lspg_nextshot.dsnrg2_isnull == 0)
  lspg_nextshot.dsnrg2
                           = atof( PQgetvalue( pgr,0,
    dsnrg2_c));
lspg_nextshot.cx2_isnull = PQgetisnull( pgr, 0, cx2_c)
if( lspg_nextshot.cx2_isnull == 0)
  lspg_nextshot.cx2
                          = atof( PQgetvalue( pgr,0, cx2_c));
lspg_nextshot.cy2_isnull = PQgetisnull( pgr, 0, cy2_c)
if( lspg_nextshot.cy2_isnull == 0)
                         = atof( PQgetvalue( pgr,0, cy2_c));
  lspg_nextshot.cy2
lspg_nextshot.ax2_isnull = PQgetisnull( pgr, 0, ax2_c)
if( lspg_nextshot.ax2_isnull == 0)
                         = atof( PQgetvalue( pgr,0, ax2_c));
  lspg_nextshot.ax2
lspg_nextshot.ay2_isnull = PQgetisnull( pgr, 0, ay2_c)
if( lspg_nextshot.ay2_isnull == 0)
  lspg_nextshot.ay2
                         = atof( PQgetvalue( pgr,0, ay2_c));
lspg_nextshot.az2_isnull = PQgetisnull( pgr, 0, az2_c)
if( lspg_nextshot.az2_isnull == 0)
                         = atof( PQgetvalue( pgr,0, az2_c));
  lspg_nextshot.az2
lspg_nextshot.active2_isnull = PQgetisnull( pgr, 0
, active2_c);
if( lspg_nextshot.active2_isnull == 0)
  lspg_nextshot.active2 = atoi( PQgetvalue( pgr, 0,
    active2_c));
lspg_nextshot.sindex2_isnull = PQgetisnull( pgr, 0
, sindex2_c);
if( lspg_nextshot.sindex2_isnull == 0)
  lspg_nextshot.sindex2 = atoi( PQgetvalue( pgr, 0,
    sindex2_c));
lspg_nextshot.new_value_ready = 1;
pthread_cond_signal( &(lspg_nextshot.cond));
pthread_mutex_unlock( &(lspg_nextshot.mutex));
```

7.5.4.43 void lspg_nextshot_done ()

Called when the next shot guery has been processed.

Definition at line 842 of file Ispg.c.

```
pthread_mutex_unlock( &(lspg_nextshot.mutex));
}
```

7.5.4.44 void lspg_nextshot_init ()

Initialize the nextshot variable, mutex, and condition.

Definition at line 816 of file lspg.c.

```
memset( &lspg_nextshot, 0, sizeof( lspg_nextshot));
pthread_mutex_init( &(lspg_nextshot.mutex), NULL);
pthread_cond_init( &(lspg_nextshot.cond), NULL);
```

7.5.4.45 void lspg_nextshot_wait ()

Wait for the next shot query to get processed.

Definition at line 834 of file lspg.c.

```
pthread_mutex_lock( &(lspg_nextshot.mutex));
while( lspg_nextshot.new_value_ready == 0)
pthread_cond_wait( &(lspg_nextshot.cond), &(lspg_nextshot.mutex));
```

7.5.4.46 PQnoticeProcessor lspg_notice_processor (void * arg, const char * msg)

Definition at line 1527 of file lspg.c.

```
lslogging_log_message( "lspg: %s", msg);
return NULL;
}
```

7.5.4.47 void lspg_pg_connect ()

Connect to the pg server.

Definition at line 1534 of file lspg.c.

```
fint err;
if( q == NULL)
    ls_pg_state = LS_PG_STATE_INIT;

switch( ls_pg_state) {
    case LS_PG_STATE_INIT:

    if( lspg_time_sent.tv_sec != 0) {
        //
        // Reality check: if it's less the about 10 seconds since the last failed attempt
        // the just chill.
        //
        gettimeofday( &now, NULL);
        if( now.tv_sec - lspg_time_sent.tv_sec < 10) {
            return;
        }
    }
    q = PQconnectStart( "dbname=ls user=lsuser hostaddr=10.1.0.3");</pre>
```

```
if( q == NULL) {
   lslogging_log_message( "Out of memory
     (lspg_pg_connect)");
    exit(-1);
  err = PQstatus( q);
  if( err == CONNECTION_BAD) {
   lslogging_log_message( "Trouble connecting to
     database");
   gettimeofday( &lspg_time_sent, NULL);
    return;
  err = PQsetnonblocking( q, 1);
  if( err != 0) {
    lslogging_log_message( "Odd, could not set database
     connection to nonblocking");
  ls_pg_state = LS_PG_STATE_INIT_POLL;
  lspg_connectPoll_response = PGRES_POLLING_WRITING;
  \ensuremath{//} set up the connection for poll
  lspgfd.fd = PQsocket( q);
case LS_PG_STATE_INIT_POLL:
  if( lspq_connectPoll_response ==
    PGRES_POLLING_FAILED) {
    PQfinish(q);
    q = NULL;
    ls_pg_state = LS_PG_STATE_INIT;
  } else if( lspg_connectPoll_response ==
PGRES_POLLING_OK) {
    PQsetNoticeProcessor( q, (PQnoticeProcessor)lspg_notice_processor
    lspg_query_push( NULL, "select pmac.md2_init()");
ls_pg_state = LS_PG_STATE_IDLE;
  break;
case LS_PG_STATE_RESET:
  err = PQresetStart(q);
  if( err == 0) {
   PQfinish(q);
    q = NULL;
    ls_pg_state = LS_PG_STATE_INIT;
  } else {
    ls_pg_state = LS_PG_STATE_RESET_POLL;
    lspg_resetPoll_response = PGRES_POLLING_WRITING;
 break;
case LS_PG_STATE_RESET_POLL:
 if( lspg_resetPoll_response == PGRES_POLLING_FAILED)
    PQfinish(q);
    q = NULL;
 ls_pg_state = LS_PG_STATE_INIT;
} else if( lspg_resetPoll_response ==
    PGRES_POLLING_OK) {
    lspg_query_push( NULL, "select pmac.md2_init()");
    ls_pg_state = LS_PG_STATE_IDLE;
  break;
}
```

7.5.4.48 void lspg_pg_service (struct pollfd * evt)

I/O control to/from the postgresql server.

Parameters

in	evt The pollfd	bject that we are responding to
----	------------------	---------------------------------

Definition at line 1428 of file lspg.c.

```
{
// Currently just used to check for notifies
// Other socket communication is done syncronously
if( evt->revents & POLLIN) {
  if( ls_pg_state == LS_PG_STATE_INIT_POLL) {
  lspg_connectPoll_response = PQconnectPoll( q);
  if( lspg_connectPoll_response ==
    PGRES_POLLING_FAILED) {
       ls_pg_state = LS_PG_STATE_RESET;
    return;
  if( ls_pg_state == LS_PG_STATE_RESET_POLL)
     lspg_resetPoll_response = PQresetPoll( q);
     if( lspg_resetPoll_response ==
    PGRES_POLLING_FAILED) {
      ls_pg_state = LS_PG_STATE_RESET;
    return;
  // if in IDLE or RECV we need to call consumeInput first
  if( ls_pg_state == LS_PG_STATE_IDLE) {
    err = PQconsumeInput(q);
    if( err != 1) {
       lslogging_log_message( "consume input failed: %s",
     PQerrorMessage(q));
ls_pg_state = LS_PG_STATE_RESET;
       return;
  if( ls_pg_state == LS_PG_STATE_RECV) {
    lspg_receive();
  // Check for notifies regardless of our state
  \ensuremath{//} Push as many requests as we have notifies.
    PGnotify *pgn;
    while( 1) {
       pgn = PQnotifies(q);
       if( pgn == NULL)
      lslogging_log_message( "lspg_pg_service: notify
recieved %s", pgn->relname);
       if( strstr( pgn->relname, "_pmac") != NULL) {
   lspg_query_push( lspg_cmd_cb, "SELECT
      pmac.md2_queue_next()");
     } else if (strstr(pgn->relname, "_diff") != NULL || strstr(pgn->relname, "_run") != NULL) {
      lspg_query_push( lspg_nextaction_cb,
"SELECT action FROM px.nextaction()");
       } else if (strstr( pgn->relname, "_sample") != NULL) {
  lspg_getcurrentsampleid_call();
       PQfreemem( pgn);
    }
  }
if( evt->revents & POLLOUT) {
  if( ls_pg_state == LS_PG_STATE_INIT_POLL) {
   lspg_connectPoll_response = PQconnectPoll( q);
   if( lspg_connectPoll_response ==
     PGRES_POLLING_FAILED) {
      ls_pg_state = LS_PG_STATE_RESET;
    return;
```

7.5.4.49 Ispg query queue t* Ispg_query_next()

Return the next item in the postgresql queue.

If there is an item left in the queue then it is returned. Otherwise, NULL is returned.

Definition at line 75 of file lspg.c.

7.5.4.50 void lspg_query_push (void(*)(lspg_query_queue_t *, PGresult *) cb, char * fmt, ...)

Place a query on the queue.

Parameters

in	cb	Our callback function that deals with the response
in	fmt	Printf style function to generate the query

Definition at line 128 of file Ispg.c.

```
{
int idx;
va_list arg_ptr;

pthread_mutex_lock( &lspg_queue_mutex);

//
// Pause the thread while we service the queue
//
while( (lspg_query_queue_on + 1) %
   LS_PG_QUERY_QUEUE_LENGTH == lspg_query_queue_off %
   LS_PG_QUERY_QUEUE_LENGTH) {
   pthread_cond_wait( &lspg_queue_cond, &lspg_queue_mutex
```

7.5.4.51 void lspg_query_reply_next ()

Remove the oldest item in the queue.

this is called only when there is nothing else to service the reply: this pop does not return anything. We use the ...reply_peek function to return the next item in the reply queue

Definition at line 99 of file lspg.c.

7.5.4.52 lspg_query_queue_t* lspg_query_reply_peek()

Return the next item in the reply queue but don't pop it since we may need it more than once.

Call lspg_query_reply_next() when done.

Definition at line 112 of file Ispg.c.

```
lspg_query_queue_t *rtn;

pthread_mutex_lock( &lspg_queue_mutex);

if( lspg_query_queue_reply == lspg_query_queue_on
    )
    rtn = NULL;

else
    rtn = &(lspg_query_queue[(lspg_query_queue_reply
    ) % LS_PG_QUERY_QUEUE_LENGTH]);

pthread_mutex_unlock( &lspg_queue_mutex);
    return rtn;
```

7.5.4.53 void lspg_receive ()

Receive a result of a query.

Definition at line 1345 of file lspg.c.

```
{
  PGresult *pgr;
  lspg_query_queue_t *qqp;
  int err;
  err = PQconsumeInput( q);
  if( err != 1) {
    lslogging_log_message( "consume input failed: %s",
      PQerrorMessage(q));
    ls_pg_state = LS_PG_STATE_RESET;
    return:
  // We must call PQgetResult until it returns NULL before sending the next
  // This implies that only one query can ever be active at a time and our
       queue
  // management should be simple
  // We should be in the LS_PG_STATE_RECV here
  while( !PQisBusy( q)) {
  pgr = PQgetResult( q);
    if ( pgr == NULL) {
       lspg_query_reply_next();
       ^{\prime\prime} // we are now done reading the response from the database
       ls_pg_state = LS_PG_STATE_IDLE;
      break;
    } else {
       ExecStatusType es;
      qqp = lspg_query_reply_peek();
es = PQresultStatus( pgr);
       if( es != PGRES_COMMAND_OK && es != PGRES_TUPLES_OK) {
        char *emess;
         emess = PQresultErrorMessage( pgr);
         if( emess != NULL && emess[0] != 0) {
  lslogging_log_message( "Error from query '%s':\n
       %s", qqp->qs, emess);
       } else {
         //
// Deal with the response
         // If the response is likely to take awhile we should probably
         // add a new state and put something in the main look to run the
        onResponse
         // routine in the main loop. For now, though, we only expect very
        brief onResponse routines
         if( qqp != NULL && qqp->onResponse != NULL)
           qqp->onResponse( qqp, pgr);
      PQclear( pgr);
  }
7.5.4.54 void lspg_run ( )
Start 'er runnin'.
Definition at line 1777 of file Ispg.c.
  pthread_create( &lspg_thread, NULL, lspg_worker, NULL);
lsevents_add_listener( "Sample(Detected|Absent)",
      lspmac_sample_detector_cb);
7.5.4.55 void lspg_send_next_query ( )
```

send the next queued query to the DB server

Definition at line 1298 of file Ispg.c.

```
// Normally we should be in the "send" state
// but we can also send if we are servicing
// a reply
//
lspg_query_queue_t *qqp;
int err;
qqp = lspg_query_next();
if( qqp == NULL) {
  //
// A send without a query? Should never happen.
// But at least we shouldn't segfault if it does.
  //
  return;
}
if(qqp->qs[0] == 0) {
  // Do we really have to check this case?
  // It would only come up if we stupidly pushed an empty query string
  \ensuremath{//} or ran off the end of the queue
  //
Islogging_log_message( "Popped empty query string.
   Probably bad things are going on.");
  lspg_query_reply_next();
  ls_pg_state = LS_PG_STATE_IDLE;
} else {
  err = PQsendQuery( q, qqp->qs);
  if( err == 0) {
    lslogging_log_message( "query failed: %s\n",
    PQerrorMessage(q));
    //
// Don't wait for a reply, just reset the connection
    lspg_query_reply_next();
    ls_pg_state = LS_PG_STATE_RESET;
    ls_pg_state = LS_PG_STATE_SEND_FLUSH;
  }
```

7.5.4.56 void lspg_seq_run_prep_all (long long *skey*, double *kappa*, double *phi*, double *cx*, double *cy*, double *ax*, double *ax*, double *ax*,

Convinence function to call seq run prep.

Parameters

in	skey	px.shots key for this image
in	kappa	current kappa postion
in	phi	current phi postition
in	СХ	current center table x
in	су	current center table y
in	ax	current alignment table x
in	ay	current alignment table y
in	az	current alignment table z

Definition at line 1095 of file Ispg.c.

7.5.4.57 void lspg_seq_run_prep_call (long long skey, double kappa, double phi, double cx, double cy, double ax, double ax, double ax)

queue up the seq_run_prep query

Parameters

in	skey	px.shots key for this image
in	kappa	current kappa postion
in	phi	current phi postition
in	СХ	current center table x
in	су	current center table y
in	ax	current alignment table x
in	ay	current alignment table y
in	az	current alignment table z

Definition at line 1061 of file lspg.c.

7.5.4.58 void $lspg_seq_run_prep_cb$ ($lspg_query_queue_t*qqp$, PGresult*pgr)

Callback for the seq_run_prep query.

Parameters

in	qqp	The query item that generated this callback
in	pgr	The result of the query

Definition at line 1049 of file Ispg.c.

```
{
pthread_mutex_lock( &(lspg_seq_run_prep.mutex));
lspg_seq_run_prep.new_value_ready = 1;
pthread_cond_signal( &(lspg_seq_run_prep.cond));
pthread_mutex_unlock( &(lspg_seq_run_prep.mutex));
```

7.5.4.59 void lspg_seq_run_prep_done ()

Indicate we are done waiting.

Definition at line 1089 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_seq_run_prep.mutex));
}
```

7.5.4.60 void lspg_seq_run_prep_init ()

Initialize the data collection object.

Definition at line 1041 of file lspg.c.

```
lspg_seq_run_prep.new_value_ready = 0;
pthread_mutex_init( &(lspg_seq_run_prep.mutex), NULL);
pthread_cond_init( &(lspg_seq_run_prep.cond), NULL);
```

7.5.4.61 void lspg_seq_run_prep_wait ()

Wait for seq run prep query to return.

Definition at line 1081 of file Ispg.c.

```
pthread_mutex_lock( &(lspg_seq_run_prep.mutex));
while( lspg_seq_run_prep.new_value_ready == 0
    )
    pthread_cond_wait( &(lspg_seq_run_prep.cond), &(
        lspg_seq_run_prep.mutex));
}
```

7.5.4.62 void lspg_sig_service (struct pollfd * evt)

Service a signal Signals here are treated as file descriptors and fits into our poll scheme.

Parameters

in	evt	The pollfd object that triggered this call
----	-----	--

Definition at line 1406 of file lspg.c.

```
{
struct signalfd_siginfo fdsi;

//
// Really, we don't care about the signal,
// it's just used to drop out of the poll
// function when there is something for us
// to do that didn't invovle something coming
// from our postgresql server.
//
// This is accompished by the query_push function
// to notify us that a new query is ready.
//
read( evt->fd, &fdsi, sizeof( struct signalfd_siginfo));
```

7.5.4.63 int lspg_starttransfer_all (int * err, unsigned int nextsample, int sampledetected, double ax, double ay, double az, double horz, double vert, double esttime)

Definition at line 322 of file lspg.c.

```
int rtn;
lspg_starttransfer_call( nextsample, sampledetected,
    ax, ay, az, horz, vert, esttime);
lspg_starttransfer_wait();
if( lspg_starttransfer.no_rows_returned ||
    lspg_starttransfer.starttransfer != 1) {
    *err = 1;
} else {
    *err = 0;
    rtn = lspg_starttransfer.starttransfer;
}
lspg_starttransfer_done();
```

```
return rtn;
```

7.5.4.64 void lspg_starttransfer_call (unsigned int *nextsample*, int *sample_detected*, double *ax*, double *ay*, double *ay*, double *ax*, double *esttime*)

Definition at line 302 of file lspg.c.

7.5.4.65 void lspg_starttransfer_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Parameters

in	qqp	Our nextsample query
in	pgr	result of the query

Definition at line 281 of file lspg.c.

```
{
pthread_mutex_lock( & (lspg_starttransfer.mutex));

lspg_starttransfer.new_value_ready = 1;
if( PQntuples( pgr) <=0) {
    lspg_starttransfer.no_rows_returned = 0;
    lspg_starttransfer.starttransfer = 0;
} else {
    lspg_starttransfer.no_rows_returned = 1;
    if( PQgetisnull( pgr, 0, 0) || strtol( PQgetvalue( pgr, 0, 0), NULL, 0) != 1)
    lspg_starttransfer.starttransfer = 0;
else
    lspg_starttransfer.starttransfer = 1;
}
pthread_cond_signal( & (lspg_starttransfer.cond));
pthread_mutex_unlock( & (lspg_starttransfer.mutex));</pre>
```

7.5.4.66 void lspg_starttransfer_done ()

Definition at line 317 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_starttransfer.mutex));
}
```

7.5.4.67 void lspg_starttransfer_init ()

Definition at line 275 of file Ispg.c.

```
lspg_starttransfer.new_value_ready = 0;
pthread_mutex_init( &lspg_starttransfer.mutex, NULL);
pthread_cond_init( &lspg_starttransfer.cond, NULL);
```

```
7.5.4.68 void lspg_starttransfer_wait ( )
```

Definition at line 311 of file lspg.c.

7.5.4.69 void lspg_wait_for_detector_all ()

Combined call to wait for the detector.

Definition at line 905 of file lspg.c.

```
lspg_wait_for_detector_call();
lspg_wait_for_detector_wait();
lspg_wait_for_detector_done();
}
```

7.5.4.70 void lspg_wait_for_detector_call ()

initiate the wait for detector query

Definition at line 879 of file Ispg.c.

```
pthread_mutex_lock( &(lspg_wait_for_detector.mutex
    ));
lspg_wait_for_detector.new_value_ready =
    0;
pthread_mutex_unlock( &(lspg_wait_for_detector.mutex
    ));
lspg_query_push( lspg_wait_for_detector_cb
    , "SELECT px.lock_detector_test_block()");
```

7.5.4.71 void $lspg_wait_for_detector_cb$ ($lspg_query_queue_t*qqp$, PGresult*pgr)

Callback for the wait for detector query.

Definition at line 870 of file lspg.c.

```
pthread_mutex_lock( &(lspg_wait_for_detector.mutex
     ));
lspg_wait_for_detector.new_value_ready =
          1;
pthread_cond_signal( &(lspg_wait_for_detector.cond
          ));
pthread_mutex_unlock( &(lspg_wait_for_detector.mutex
          ));
```

7.5.4.72 void lspg_wait_for_detector_done ()

Done waiting for the detector.

Definition at line 898 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_wait_for_detector.mutex
     ));
}
```

7.5.4.73 void lspg_wait_for_detector_init ()

initialize the detector timing object

Definition at line 862 of file Ispg.c.

```
lspg_wait_for_detector.new_value_ready =
    0;
pthread_mutex_init( &(lspg_wait_for_detector.mutex
    ), NULL);
pthread_cond_init( &(lspg_wait_for_detector.cond),
    NULL);
```

7.5.4.74 void lspg_wait_for_detector_wait ()

Pause the calling thread until the detector is ready Called by the MD2 thread.

Definition at line 890 of file Ispg.c.

```
pthread_mutex_lock( &(lspg_wait_for_detector.mutex
    ));
while( lspg_wait_for_detector.new_value_ready
    == 0)
pthread_cond_wait( &(lspg_wait_for_detector.cond)
    , &(lspg_wait_for_detector.mutex));
```

7.5.4.75 void lspg_waitcryo_all()

no need to get fancy with the wait cryo command It should not return until the robot is almost ready for air rights Definition at line 507 of file lspg.c.

7.5.4.76 void lspg_waitcryo_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Definition at line 497 of file Ispg.c.

```
pthread_mutex_lock( &lspg_waitcryo.mutex);
lspg_waitcryo.new_value_ready = 1;
pthread_cond_signal( &lspg_waitcryo.cond);
pthread_mutex_unlock( &lspg_waitcryo.mutex);
```

7.5.4.77 void lspg_waitcryo_init ()

Definition at line 491 of file lspg.c.

```
lspg_waitcryo.new_value_ready = 0;
pthread_mutex_init( &lspg_waitcryo.mutex, NULL);
pthread_cond_init( &lspg_waitcryo.cond, NULL);
}
```

7.5.4.78 void* lspg_worker (void * dummy)

The main loop for the lspg thread.

Parameters

in	dummy	Required by pthreads but unused

Definition at line 1674 of file Ispg.c.

```
static struct pollfd fda[2]; // 0=signal handler, 1=pg socket
static int nfda = 0;
static sigset_t our_sigset;
// block ordinary signal mechanism
sigemptyset( &our_sigset);
sigaddset( &our_sigset, SIGUSR1);
pthread_sigmask(SIG_BLOCK, &our_sigset, NULL);
fda[0].fd = signalfd( -1, &our_sigset, SFD_NONBLOCK);
if( fda[0].fd == -1) {
  char *es;
  es = strerror(errno);
  lslogging_log_message( "Signalfd trouble: %s", es);
fda[0].events = POLLIN;
// make sure file descriptor is not legal until it's been conneceted
lspgfd.fd = -1;
while( 1) {
  int pollrtn;
  int poll_timeout_ms;
 lspg_next_state();
  if( lspgfd.fd == -1) {
     // Here a connection to the database is not established.
     // nete a connector to the database is not established.
// Periodicaly try again. Should possibly arrange to reconnect
// to signalfd but that's unlikely to be nessesary.
     nfda = 1;
     poll_timeout_ms = 10000;
fda[1].revents = 0;
  } else {
     // Arrange to peacfully do nothing until either the pg server sends us
      something
     // or someone pushs something onto our queue //
     nfda = 2;
     fda[1].fd = lspgfd.fd;
fda[1].events = lspgfd.events;
fda[1].revents = 0;
    poll_timeout_ms = -1;
  pollrtn = poll( fda, nfda, poll_timeout_ms);
```

```
if( pollrtn && fda[0].revents) {
    lspg_sig_service( &(fda[0]));
    pollrtn--;
}
if( pollrtn && fda[1].revents) {
    lspg_pg_service( &(fda[1]));
    pollrtn--;
}
}
```

7.5.4.79 void lspmac_sample_detector_cb (char * event)

log magnet state

Definition at line 1746 of file lspg.c.

```
int present;
if( strcmp( event, "SampleDetected") == 0)
   present = 1;
else
   present = 0;

lspg_query_push( NULL, "SELECT px.logmagnetstate(%s)", present
   ? "TRUE" : "FALSE");
}
```

7.5.5 Variable Documentation

```
7.5.5.1 int ls_pg_state = LS_PG_STATE_INIT [static]
```

State of the Ispg state machine.

Definition at line 39 of file lspg.c.

7.5.5.2 PostgresPollingStatusType lspg_connectPoll_response [static]

Used to determine state while connecting.

Definition at line 60 of file lspg.c.

7.5.5.3 Ispg_demandairrights_t lspg_demandairrights

our demandairrights object

Definition at line 66 of file lspg.c.

7.5.5.4 lspg_getcenter_t lspg_getcenter

the getcenter object

Definition at line 65 of file lspg.c.

7.5.5.5 lspg_getcurrentsampleid_t lspg_getcurrentsampleid

our currentsample id

Definition at line 67 of file lspg.c.

7.5.5.6 lspg_lock_detector_t lspg_lock_detector [static] Definition at line 979 of file lspg.c. 7.5.5.7 lspg_lock_diffractometer_t lspg_lock_diffractometer [static] Definition at line 920 of file lspg.c. 7.5.5.8 lspg_nextsample_t lspg_nextsample the very next sample Definition at line 63 of file lspg.c. 7.5.5.9 Ispg_nextshot_t lspg_nextshot the nextshot object Definition at line 64 of file lspg.c. 7.5.5.10 Ispg_query_queue_t Ispg_query_queue[LS_PG_QUERY_QUEUE_LENGTH] [static] Our query queue. Definition at line 52 of file lspg.c. **7.5.5.11** unsigned int lspg_query_queue_off = 0 [static] The last item still being used (on == off means nothing in queue) Definition at line 54 of file lspg.c. **7.5.5.12** unsigned int lspg_query_queue_on = 0 [static] Next position to add something to the queue. Definition at line 53 of file lspg.c. **7.5.5.13** unsigned int lspg_query_queue_reply = 0 [static] The current item being digested. Normally off <= reply <= on. Corner case of queue wrap arround works because we only increment and compare for equality. Definition at line 55 of file lspg.c. 7.5.5.14 pthread_cond_t lspg_queue_cond [static]

keeps the queue from overflowing Definition at line 44 of file lspg.c.

```
7.5.5.15 pthread_mutex_t lspg_queue_mutex [static]
keep the queue from getting tangled
Definition at line 43 of file lspg.c.
7.5.5.16 PostgresPollingStatusType lspg_resetPoll_response [static]
Used to determine state while reconnecting.
Definition at line 61 of file lspg.c.
7.5.5.17 lspg_seq_run_prep_t lspg_seq_run_prep [static]
Definition at line 1037 of file lspg.c.
7.5.5.18 lspg_starttransfer_t lspg_starttransfer
start a sample transfer
Definition at line 68 of file lspg.c.
7.5.5.19 pthread_t lspg_thread [static]
our worker thread
Definition at line 42 of file lspg.c.
7.5.5.20 lspg_wait_for_detector_t lspg_wait_for_detector [static]
Instance of the detector timing object.
Definition at line 858 of file Ispg.c.
7.5.5.21 lspg_waitcryo_t lspg_waitcryo
signal the robot
Definition at line 69 of file lspg.c.
7.5.5.22 struct pollfd lspgfd [static]
our poll info
Definition at line 45 of file lspg.c.
7.5.5.23 struct timeval lspg_time_sent now [static]
used to ensure we do not inundate the db server with connection requests
```

Definition at line 40 of file lspg.c.

7.5.5.24 PGconn*q=NULL [static]

Database connector.

Definition at line 59 of file lspg.c.

7.6 Ispmac.c File Reference

Routines concerned with communication with PMAC.

```
#include "pgpmac.h"
```

Data Structures

struct md2StatusStruct

The block of memory retrieved in a status request.

- struct lspmac_ascii_buffers_struct
- struct lspmac_dpascii_queue_struct

Macros

- #define LS_PMAC_STATE_RESET -1
- #define LS_PMAC_STATE_DETACHED 0
- #define LS PMAC STATE IDLE 1
- #define LS PMAC STATE SC 2
- #define LS PMAC STATE WACK NFR 3
- #define LS_PMAC_STATE_WACK_CC 4
- #define LS PMAC STATE WACK 5
- #define LS_PMAC_STATE_GMR 6
- #define LS PMAC STATE CR 7
- #define LS PMAC STATE RR 8
- #define LS_PMAC_STATE_WACK_RR 9
- #define LS_PMAC_STATE_GB 10
- #define LS_PMAC_STATE_WCR 11
- #define LS_PMAC_STATE_WGB 12
- #define LSPMAC_PRESET_REGEX "(.*\\.%s\\.presets)\\.([0-9]+)\\.(name|position)"

Regex to pick out preset name and corresponding position.

• #define PMACPORT 1025

The PMAC (only) listens on this port.

#define pmac_cmd_size 8

PMAC command size in bytes.

- #define VR_UPLOAD 0xc0
- #define VR DOWNLOAD 0x40
- #define VR PMAC SENDLINE 0xb0
- #define VR_PMAC_GETLINE 0xb1
- #define VR_PMAC_FLUSH 0xb3
- #define VR_PMAC_GETMEM 0xb4
- #define VR_PMAC_SETMEM 0xb5
- #define VR PMAC SENDCTRLCHAR 0xb6
- #define VR_PMAC_SETBIT 0xba
- #define VR PMAC SETBITS 0xbb
- #define VR_PMAC_PORT 0xbe

- #define VR_PMAC_GETRESPONSE 0xbf
- #define VR_PMAC_READREADY 0xc2
- #define VR_CTRL_RESPONSE 0xc4
- #define VR PMAC GETBUFFER 0xc5
- #define VR PMAC WRITEBUFFER 0xc6
- #define VR PMAC WRITEERROR 0xc7
- #define VR FWDOWNLOAD 0xcb
- #define VR_IPADDRESS 0xe0
- #define PMAC_MIN_CMD_TIME 10000.0

Minimum time between commands to the pmac.

#define PMAC CMD QUEUE LENGTH 2048

Size of the PMAC command queue.

• #define LSPMAC DPASCII QUEUE LENGTH 1024

Typedefs

typedef struct md2StatusStruct md2_status_t

The block of memory retrieved in a status request.

· typedef struct

lspmac_ascii_buffers_struct lspmac_ascii_buffers_t

typedef struct

lspmac_dpascii_queue_struct lspmac_dpascii_queue_t

Functions

void lspmac_get_ascii (char *)

Forward declarateion.

double lspmac_lut (int nlut, double *lut, double x)

Look up table support for motor positions (think x=zoom, y=light intensity) use a lookup table to find the "counts" to move the motor to the requested position The look up table is a simple one dimensional array with the x values as even indicies and the y values as odd indices.

- double Ispmac rlut (int nlut, double *lut, double y)
- void hex_dump (int n, unsigned char *s)

Prints a hex dump of the given data.

void cleanstr (char *s)

Replace \r with \n in null terminated string and print result to terminal.

• void IsConnect (char *ipaddr)

Connect to the PMAC socket.

· void Ispmac reset queue ()

Clear the queue as part of PMAC reinitialization.

pmac_cmd_queue_t * lspmac_push_queue (pmac_cmd_queue_t *cmd)

Put a new command on the queue.

pmac_cmd_queue_t * lspmac_pop_queue ()

Remove the oldest queue item.

pmac_cmd_queue_t * lspmac_pop_reply ()

Remove the next command queue item that is waiting for a reply.

 pmac_cmd_queue_t * Ispmac_send_command (int rqType, int rq, int wValue, int wIndex, int wLength, char *data, void(*responseCB)(pmac_cmd_queue_t *, int, char *), int no_reply, char *event)

Compose a packet and send it to the PMAC.

· void Ispmac SockFlush ()

Reset the PMAC socket from the PMAC side.

void lspmac_Reset ()

Clear the queue and put the PMAC into a known state.

void lspmac_Error (char *buff)

The service routing detected an error condition.

void Ispmac Service (struct pollfd *evt)

Service routine for packet coming from the PMAC.

void lspmac_GetShortReplyCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

Receive a reply that does not require multiple buffers.

void lspmac_SendControlReplyPrintCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

Receive a reply to a control character Print a "printable" version of the character to the terminal Followed by a hex dump of the response.

void lspmac_GetmemReplyCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

Service a reply to the getmem command.

pmac_cmd_queue_t * lspmac_SockGetmem (int offset, int nbytes)

Request a chunk of memory to be returned.

pmac_cmd_queue_t * Ispmac_SockSendline (char *event, char *fmt,...)

Send a one line command.

pmac_cmd_queue_t * lspmac_SockSendline_nr (char *event, char *fmt,...)

Send a command and ignore the response.

• pmac_cmd_queue_t * Ispmac_SockSendControlCharPrint (char *event, char c)

Send a control character.

void lspmac_Getmem ()

Request a block of double buffer memory.

void lspmac_bo_read (lspmac_motor_t *mp)

Read the state of a binary i/o motor This is the read method for the binary i/o motor class.

void lspmac_dac_read (lspmac_motor_t *mp)

Read a DAC motor position.

void lspmac shutter read (lspmac motor t *mp)

Fast shutter read routine The shutter is mildly complicated in that we need to take into account the fact that the shutter can open and close again between status updates.

void lspmac_home1_queue (lspmac_motor_t *mp)

Home the motor.

void lspmac_home2_queue (lspmac_motor_t *mp)

Second stage of homing.

double lspmac_getPosition (lspmac_motor_t *mp)

get the motor position (with locking)

void lspmac_pmacmotor_read (lspmac_motor_t *mp)

Read the position and status of a normal PMAC motor.

int lspmac_getBIPosition (lspmac_bi_t *bip)

get binary input value

• void lspmac_get_status_cb (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

Service routing for status upate This updates positions and status information.

void lspmac_get_status ()

Request a status update from the PMAC.

void lspmac_more_ascii_cb (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

we are expecting more characters from the DPRAM ASCII interface

void lspmac_get_ascii_cb (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

service the ascii buffer request response

void lspmac asciicmdCB (pmac cmd queue t *cmd, int nreceived, char *buf)

PMAC has received our ascii command request Now see when it is ready for the next one.

• void Ispmac SockSendDPline (char *event, char *fmt,...)

prepare (queue up) a line to send the dpram ascii command interface

```
    void lspmac_SockSendDPControlCharCB (pmac_cmd_queue_t *cmd, int nreceived, char *buf)

    void lspmac_SockSendDPControlChar (char *event, char c)

     use dpram ascii interface to send a control character

    void Ispmac SockSendDPqueue ()

• void lspmac_abort ()
     abort motion and try to recover

    void lspmac_GetAllIVarsCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

      Receive the values of all the I variables Update our Postgresgl database with the results.

    void lspmac_GetAllIVars ()

      Request the values of all the I variables.

    void lspmac_GetAllMVarsCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

      Receive the values of all the M variables Update our database with the results.

    void lspmac_GetAllMVars ()

      Request the values of all the M variables.

    void lspmac sendcmd nocb (char *fmt,...)

      Send a command that does not need to deal with the reply.

    void <a href="Ispace">Ispace</a> sendcmd (char *event, void(*responseCB)(pmac_cmd_queue_t *, int, char *), char *fmt,...)

     PMAC command with call back.

    void Ispmac next state ()

     State machine logic.

    void * Ispmac_worker (void *dummy)

     Our Ispmac worker thread.

    int lspmac_movedac_queue (lspmac_motor_t *mp, double requested_position)

     Move method for dac motor objects (ie, lights)

    int lspmac_movezoom_queue (lspmac_motor_t *mp, double requested_position)

     Move method for the zoom motor.
• int lspmac_move_preset_queue (lspmac_motor_t *mp, char *preset_name)
     Move a given motor to one of its preset positions.
• int lspmac_test_preset (lspmac_motor_t *mp, char *preset_name, double tolerance)
     see if the motor is within tolerance of the preset 1 means yes, it is 0 mean no it isn't or that the preset was not found
• int lspmac_moveabs_fshut_queue (lspmac_motor_t *mp, double requested_position)
     Move method for the fast shutter.
• int lspmac_moveabs_bo_queue (lspmac_motor_t *mp, double requested_position)
     Move method for binary i/o motor objects.

    void lspmac_moveabs_timed_queue (lspmac_motor_t *mp, double start, double delta, double time)

     timed motor move

    int lspmac moveabs frontlight oo queue (lspmac motor t*mp, double pos)

      "move" frontlight on/off

    int lspmac_moveabs_flight_factor_queue (lspmac_motor_t *mp, double pos)

• int lspmac_moveabs_blight_factor_queue (lspmac_motor_t *mp, double pos)
• void <a href="mailto:lspmac_video_rotate">lspmac_video_rotate</a> (double secs)
      Special motion program to collect centering video.

    double Ispmac est move time (double min time, double delta, Ispmac motor t*mp 1, char*preset 1, dou-

  ble end_point_1,...)
     guess the minimum time it will take to move the motor
• int Ispmac move or jog abs queue (Ispmac motor t *mp, double requested position, int use jog)
     Move method for normal stepper and servo motor objects Returns non-zero on abort, zero if OK.

    int lspmac_move_or_jog_preset_queue (lspmac_motor_t *mp, char *preset, int use_jog)

     move using a preset value returns 0 on success, non-zero on error
```

int lspmac moveabs queue (lspmac motor t *mp, double requested position)

Use coordinate system motion program, if available, to move motor to requested position.

 int lspmac_jogabs_queue (lspmac_motor_t *mp, double requested_position) Use jog to move motor to requested position. int lspmac_moveabs_wait (lspmac_motor_t *mp, double timeout_secs) Wait for motor to finish moving. void Ispmac motor init (Ispmac motor t *d, char *name) Helper funciton for the init calls. • Ispmac_motor_t * Ispmac_motor_init (Ispmac_motor_t *d, int wy, int wx, int *posp, int *stat1p, int *stat2p, char *wtitle, char *name, int(*moveAbs)(Ispmac motor t *, double)) Initialize a pmac stepper or servo motor. lspmac_motor_t * lspmac_fshut_init (lspmac_motor_t *d) Initalize the fast shutter motor. Ispmac_motor_t * Ispmac_bo_init (Ispmac_motor_t *d, char *name, char *write_fmt, int *read_ptr, int read-_mask) Initialize binary i/o motor. Ispmac_motor_t * Ispmac_dac_init (Ispmac_motor_t *d, int *posp, char *mvar, char *name, int(*move-Abs)(Ispmac motor t *, double)) Initialize DAC motor Note that some motors require further initialization from a database query. void lspmac soft motor read (lspmac motor t*p) Dummy routine to read a soft motor. Ispmac_motor_t * Ispmac_soft_motor_init (Ispmac_motor_t *d, char *name, int(*moveAbs)(Ispmac_motor_t *, double)) Ispmac bi t * Ispmac bi init (Ispmac bi t *d, int *ptr, int mask, char *onEvent, char *offEvent) Initialize binary input. void Ispmac init (int ivarsflag, int mvarsflag) Initialize this module. void lspmac cryoSwitchChanged cb (char *event) void lspmac_scint_inPosition_cb (char *event) Maybe start drying off the scintilator. void lspmac_backLight_up_cb (char *event) Turn on the backlight whenever it goes up. void lspmac backLight down cb (char *event) Turn off the backlight whenever it goes down. void lspmac_light_zoom_cb (char *event) Set the backlight intensity whenever the zoom is changed (and the backlight is up) void lspmac_scint_dried_cb (char *event) Turn off the dryer. void lspmac_zoom_lut_setup () Set up lookup table for zoom. void lspmac_flight_lut_setup () Set up lookup table for flight. · void lspmac_blight_lut_setup () Set up lookup table for blight. • void lspmac_fscint_lut_setup ()

void lspmac_command_done_cb (char *event)

Set up lookup table for fscint.

Start up the Ispmac thread.

• void Ispmac run ()

Variables

• static int Is pmac state = LS PMAC STATE DETACHED

Current state of the PMAC communications state machine.

· int lspmac_shutter_state

State of the shutter, used to detect changes.

int lspmac_shutter_has_opened

Indicates that the shutter had opened, perhaps briefly even if the state did not change.

pthread mutex t lspmac shutter mutex

Coordinates threads reading shutter status.

• pthread_cond_t lspmac_shutter_cond

Allows waiting for the shutter status to change.

pthread_mutex_t lspmac_moving_mutex

Coordinate moving motors between threads.

pthread_cond_t lspmac_moving_cond

Wait for motor(s) to finish moving condition.

• int lspmac_moving_flags

Flag used to implement motor moving condition.

static pthread_mutex_t lspmac_ascii_mutex

Keep too many processes from sending commands at once.

• static int lspmac_ascii_busy = 0

flag for condition to wait for

• static int omega zero search = 0

Indicate we'd really like to know when omega crosses zero.

static double omega zero velocity = 0

rate (cnts/sec) that omega was traveling when it crossed zero

· struct timespec omega zero time

Time we believe that omega crossed zero.

static struct timespec lspmac_status_time

Time the status was read.

static struct timespec lspmac_status_last_time

Time the status was read.

· static pthread_t pmac_thread

our thread to manage access and communication to the pmac

• pthread_mutex_t pmac_queue_mutex

manage access to the pmac command queue

pthread_cond_t pmac_queue_cond

wait for a command to be sent to PMAC before continuing

· static struct pollfd pmacfd

our poll structure

• static int getivars = 0

flag set at initialization to send i vars to db

• static int getmvars = 0

flag set at initialization to send m vars to db

· Ispmac bi t Ispmac bis [32]

array of binary inputs

• int lspmac_nbis = 0

number of active binary inputs

· Ispmac motor t Ispmac motors [48]

All our motors.

• int lspmac_nmotors = 0

The number of motors we manage. • lspmac_motor_t * omega MD2 omega axis (the air bearing) • Ispmac motor t * alignx Alignment stage X. lspmac_motor_t * aligny Alignment stage Y. lspmac_motor_t * alignz Alignment stage X. Ispmac_motor_t * anal Polaroid analyzer motor. Ispmac_motor_t * zoom Optical zoom. Ispmac_motor_t * apery Aperture Y. Ispmac_motor_t * aperz Aperture Z. Ispmac_motor_t * capy Capillary Y. Ispmac_motor_t * capz Capillary Z. Ispmac_motor_t * scint Scintillator Z. Ispmac_motor_t * cenx Centering Table X. Ispmac_motor_t * ceny Centering Table Y. Ispmac_motor_t * kappa Карра. • Ispmac motor t * phi Phi (not data collection axis) lspmac_motor_t * fshut Fast shutter. • Ispmac_motor_t * flight Front Light DAC. Ispmac_motor_t * blight Back Light DAC. Ispmac_motor_t * fscint Scintillator Piezo DAC. lspmac_motor_t * smart_mag_oo Smart Magnet on/off. • lspmac_motor_t * blight_ud Back light Up/Down actuator. lspmac_motor_t * cryo Move the cryostream towards or away from the crystal. lspmac_motor_t * dryer blow air on the scintilator to dry it off Ispmac_motor_t * fluo Move the fluorescence detector in/out. • Ispmac_motor_t * flight_oo Turn front light on/off.

```
lspmac_motor_t * blight_f
     Back light scale factor.
lspmac_motor_t * flight_f
     Front light scale factor.
lspmac_bi_t * lp_air
     Low pressure air OK.
• Ispmac_bi_t * hp_air
     High pressure air OK.
lspmac_bi_t * cryo_switch
     that little toggle switch for the cryo
• Ispmac bi t * blight down
     Backlight is down.
lspmac_bi_t * blight_up
     Backlight is up.
Ispmac_bi_t * cryo_back
     cryo is in the back position
lspmac_bi_t * fluor_back
     fluor is in the back position
• lspmac_bi_t * sample_detected
     smart magnet detected sample
lspmac_bi_t * etel_ready
     ETEL is ready.
lspmac_bi_t * etel_on
     ETEL is on.
• lspmac_bi_t * etel_init_ok
     ETEL initialized OK.

    Ispmac bi t * minikappa ok

     Minikappa is OK (whatever that means)
lspmac_bi_t * smart_mag_on
     smart magnet is on
• Ispmac_bi_t * arm_parked
     (whose arm? parked where?)
• Ispmac_bi_t * shutter_open
     shutter is open (note in pmc says this is a slow input)
lspmac_bi_t * smart_mag_err
     smart magnet error (coil broken perhaps)
• Ispmac_bi_t * smart_mag_off
     smart magnet is off

    static unsigned char dbmem [64 *1024]

     double buffered memory

    static int dbmemIn = 0

     next location

    static struct timeval

  pmac time sent now
     used to ensure we do not send commands to the pmac too often. Only needed for non-DB commands.
· static pmac cmd t rr cmd
• static pmac_cmd_t gb_cmd
• static pmac_cmd_t cr_cmd
     commands to send out "readready", "getbuffer", "controlresponse" (initialized in main)

    static pmac cmd queue t ethCmdQueue [PMAC CMD QUEUE LENGTH]

     PMAC command queue.
```

```
• static unsigned int ethCmdOn = 0
```

points to next empty PMAC command queue position

• static unsigned int ethCmdOff = 0

points to current command (or none if == ethCmdOn)

static unsigned int ethCmdReply = 0

Used like ethCmdOff only to deal with the pmac reply to a command.

static char * pmac error strs []

Decode the errors perhaps returned by the PMAC.

• static md2_status_t md2_status

Buffer for MD2 Status.

pthread_mutex_t md2_status_mutex

Synchronize reading/writting status buffer.

- · static Ispmac ascii buffers t Ispmac ascii buffers
- pthread mutex t lspmac ascii buffers mutex
- static Ispmac dpascii queue t Ispmac dpascii queue [LSPMAC DPASCII QUEUE LENGTH]
- static uint32 t Ispmac dpascii on = 0
- static uint32_t lspmac_dpascii_off = 0

7.6.1 Detailed Description

Routines concerned with communication with PMAC.

```
\date 2012
\author Keith Brister
\copyright All Rights Reserved
```

This is a state machine (surprise!) Lacking is support for writingbuffer, control writing and reading, as well as double buffered memory It looks like several different methods of managing PMAC communications are possible. Here is set up a queue of outgoing commands and deal completely with the result before sending the next. A full handshake of acknowledgements and "readready" is expected.

```
State Description
 -1
       Reset the connection
 Ω
       Detached: need to connect to tcp port
 1
        Idle (waiting for a command to send to the pmac)
  2.
        Send command
  3
        Waiting for command acknowledgement (no further response expected)
  4
        Waiting for control character acknowledgement (further response expected)
  5
        Waiting for command acknowledgement (further response expected)
  6
        Waiting for get memory response
  7
        Send controlresponse
  8
         Send readready
  9
        Waiting for acknowledgement of "readready"
 10
        Send readbuffer
 11
        Waiting for control response
 12
        Waiting for readbuffer response
```

Definition in file Ispmac.c.

7.6.2 Macro Definition Documentation

7.6.2.1 #define LS_PMAC_STATE_CR 7

Definition at line 45 of file Ispmac.c.

7.6.2.2 #define LS_PMAC_STATE_DETACHED 0

Definition at line 38 of file Ispmac.c.

7.6.2.3 #define LS_PMAC_STATE_GB 10

Definition at line 48 of file Ispmac.c.

7.6.2.4 #define LS_PMAC_STATE_GMR 6

Definition at line 44 of file Ispmac.c.

7.6.2.5 #define LS_PMAC_STATE_IDLE 1

Definition at line 39 of file Ispmac.c.

7.6.2.6 #define LS_PMAC_STATE_RESET -1

Definition at line 37 of file Ispmac.c.

7.6.2.7 #define LS_PMAC_STATE_RR 8

Definition at line 46 of file Ispmac.c.

7.6.2.8 #define LS_PMAC_STATE_SC 2

Definition at line 40 of file Ispmac.c.

7.6.2.9 #define LS_PMAC_STATE_WACK 5

Definition at line 43 of file Ispmac.c.

7.6.2.10 #define LS_PMAC_STATE_WACK_CC 4

Definition at line 42 of file Ispmac.c.

7.6.2.11 #define LS_PMAC_STATE_WACK_NFR 3

Definition at line 41 of file Ispmac.c.

7.6.2.12 #define LS_PMAC_STATE_WACK_RR 9

Definition at line 47 of file Ispmac.c.

7.6.2.13 #define LS_PMAC_STATE_WCR 11

Definition at line 49 of file Ispmac.c.

7.6.2.14 #define LS_PMAC_STATE_WGB 12

Definition at line 50 of file Ispmac.c.

7.6.2.15 #define LSPMAC_DPASCII_QUEUE_LENGTH 1024

Definition at line 357 of file Ispmac.c.

7.6.2.16 #define LSPMAC_PRESET_REGEX "(.*\\.%s\\.presets)\\.([0-9]+)\\.(name|position)"

Regex to pick out preset name and corresponding position.

Definition at line 140 of file Ispmac.c.

7.6.2.17 #define PMAC_CMD_QUEUE_LENGTH 2048

Size of the PMAC command queue.

Definition at line 184 of file Ispmac.c.

7.6.2.18 #define pmac_cmd_size 8

PMAC command size in bytes.

Definition at line 150 of file Ispmac.c.

7.6.2.19 #define PMAC_MIN_CMD_TIME 10000.0

Minimum time between commands to the pmac.

Definition at line 180 of file Ispmac.c.

7.6.2.20 #define PMACPORT 1025

The PMAC (only) listens on this port.

Definition at line 144 of file Ispmac.c.

7.6.2.21 #define VR_CTRL_RESPONSE 0xc4

Definition at line 166 of file Ispmac.c.

7.6.2.22 #define VR_DOWNLOAD 0x40

Definition at line 153 of file Ispmac.c.

7.6.2.23 #define VR_FWDOWNLOAD 0xcb

Definition at line 170 of file Ispmac.c.

7.6.2.24 #define VR_IPADDRESS 0xe0

Definition at line 171 of file Ispmac.c.

7.6.2.25 #define VR_PMAC_FLUSH 0xb3

Definition at line 157 of file Ispmac.c.

7.6.2.26 #define VR_PMAC_GETBUFFER 0xc5

Definition at line 167 of file Ispmac.c.

7.6.2.27 #define VR_PMAC_GETLINE 0xb1

Definition at line 156 of file Ispmac.c.

7.6.2.28 #define VR_PMAC_GETMEM 0xb4

Definition at line 158 of file Ispmac.c.

7.6.2.29 #define VR_PMAC_GETRESPONSE 0xbf

Definition at line 164 of file Ispmac.c.

7.6.2.30 #define VR_PMAC_PORT 0xbe

Definition at line 163 of file Ispmac.c.

7.6.2.31 #define VR_PMAC_READREADY 0xc2

Definition at line 165 of file Ispmac.c.

7.6.2.32 #define VR_PMAC_SENDCTRLCHAR 0xb6

Definition at line 160 of file Ispmac.c.

7.6.2.33 #define VR_PMAC_SENDLINE 0xb0

Definition at line 155 of file Ispmac.c.

7.6.2.34 #define VR_PMAC_SETBIT 0xba

Definition at line 161 of file Ispmac.c.

7.6.2.35 #define VR_PMAC_SETBITS 0xbb

Definition at line 162 of file Ispmac.c.

7.6.2.36 #define VR_PMAC_SETMEM 0xb5

Definition at line 159 of file Ispmac.c.

7.6.2.37 #define VR_PMAC_WRITEBUFFER 0xc6

Definition at line 168 of file Ispmac.c.

7.6.2.38 #define VR_PMAC_WRITEERROR 0xc7

Definition at line 169 of file Ispmac.c.

7.6.2.39 #define VR_UPLOAD 0xc0

Definition at line 152 of file Ispmac.c.

7.6.3 Typedef Documentation

- 7.6.3.1 typedef struct lspmac_ascii_buffers_struct lspmac_ascii_buffers_t
- 7.6.3.2 typedef struct lspmac_dpascii_queue_struct lspmac_dpascii_queue_t
- 7.6.3.3 typedef struct md2StatusStruct md2_status_t

The block of memory retrieved in a status request.

7.6.4 Function Documentation

7.6.4.1 void _lspmac_motor_init (lspmac_motor_t * d, char * name)

Helper funciton for the init calls.

Definition at line 2961 of file Ispmac.c.

```
lspmac_nmotors++;
pthread_mutex_init( &(d->mutex), NULL);
pthread_cond_init( &(d->cond), NULL);
                  = strdup(name);
                    = lsredis_get_obj( "%s.active",
d->active
     d->active_init
   %s.active_init",
                      d->name);
= lsredis_get_obj( "%s.axis",
= lsredis_get_obj( "%s.home",
   inactive_init
%s.inactive_init", d->name);
-3:c fmt = lsredis_get_obj( "%s.format",
d->redis_fmt
   d->max_accel
d->max speed
   %s.max_pos = lsredis_get_obj( "
%s.maxPosition", d->name);
min_pos = lsredis_get_obj( "
d->max_pos
  d->min_pos
d->motor_num
d->neg_limit_hit
d->neutral_pos
d->redis_position = lsredis_get_obj( "
   %s.position",
                     d->name);
```

```
= lsredis_get_obj( "
d->pos_limit_hit
    %s.posLimitSet",
                         d->name);
                     = lsredis_get_obj( "
d->precision
= lsredis_get_obj( "
    d->status_str
                  = lsredis_get_obj( "%s.unit",
d->unit
      d->name);
d->update_resolution
                     = lsredis_get_obj( "
    %s.update_resolution", d->name);
           = NULL;
= 0;
d->lut
d->nlut
d->homing = 0;
d->dac_mvar = NULL;
d->actual_pos_cnts_p = NULL;
d->statusl_p = NULL;
d->status2_p = NULL;
d->win = NULL;
d->read = NULL;
d->reported_position = INFINITY;
```

7.6.4.2 void cleanstr (char *s)

Replace \r with \n in null terminated string and print result to terminal.

Needed to turn PMAC messages into something printable.

Parameters

in	S	String to print to terminal.
----	---	------------------------------

Definition at line 537 of file Ispmac.c.

```
fint i;

pthread_mutex_lock( &ncurses_mutex);

for( i=0; i<strlen( s); i++) {
   if( s[i] == '\r')
      wprintw( term_output, "\n");
   else
      wprintw( term_output, "%c", s[i]);
}

pthread_mutex_unlock( &ncurses_mutex);</pre>
```

7.6.4.3 void hex_dump (int n, unsigned char *s)

Prints a hex dump of the given data.

Used to debug packet data.

Parameters

in	n	Number of bytes passed in s
in	s	Data to dump

Definition at line 510 of file Ispmac.c.

```
int i; // row counter
int j; // column counter
```

```
unsigned char outs[128], outs1[4];
for( i=0; n > 0; i++) {
    sprintf( (char *)outs, "*04d: ", 16*i);
    for( j=0; j<16 && n > 0; j++) {
        if( j==8)
            strcat( (char *)outs, " ");
        sprintf( (char *)outs1, " *02x", *(s + 16*i + j));
        strcat( (char *)outs, (char *)outs1);
        n--;
    }
    lslogging_log_message( "hex_dump: %s", outs);
}
```

7.6.4.4 void IsConnect (char * ipaddr)

Connect to the PMAC socket.

Establish or reestablish communications.

Parameters

in	ipaddr	String representation of the IP address (dot quad or FQN)
----	--------	---

Definition at line 558 of file Ispmac.c.

```
int psock;
                                   // our socket: value stored in pmacfda.fd
int err;
                                   // error code from some system calls
struct sockaddr_in *addrP; // our address structure to connect to struct addrinfo ai_hints; // required for getaddrinfo struct addrinfo *ai_resultP; // linked list of address structures (we'll
     always pick the first)
pmacfd.fd
              = -1;
pmacfd.events = 0;
// Initial buffer(s)
memset( &ai_hints, 0, sizeof( ai_hints));
ai_hints.ai_family = AF_INET;
ai_hints.ai_socktype = SOCK_STREAM;
// get address
err = getaddrinfo( ipaddr, NULL, &ai_hints, &ai_resultP);
if( err != 0) {
  lslogging_log_message( "Could not find address: %s",
    gai_strerror( err));
  return;
addrP = (struct sockaddr_in *)ai_resultP->ai_addr;
addrP->sin_port = htons( PMACPORT);
psock = socket( PF_INET, SOCK_STREAM, 0);
if(psock == -1) {
 lslogging_log_message( "Could not create socket");
err = connect( psock, (const struct sockaddr *)addrP, sizeof( *addrP));
if ( err != 0) {
  lslogging_log_message( "Could not connect socket: %s",
     strerror( errno));
  return;
ls_pmac_state = LS_PMAC_STATE_IDLE;
pmacfd.fd
              = psock;
pmacfd.events = POLLIN;
```

}

```
7.6.4.5 void Ispmac_abort ( )
```

abort motion and try to recover

Definition at line 2012 of file Ispmac.c.

7.6.4.6 void lspmac_asciicmdCB (pmac_cmd_queue_t * cmd, int nreceived, char * buf)

PMAC has received our ascii command request Now see when it is ready for the next one.

Definition at line 1943 of file Ispmac.c.

```
lspmac_get_ascii( cmd->event);
}
```

7.6.4.7 void lspmac_backLight_down_cb (char * event)

Turn off the backlight whenever it goes down.

Parameters

```
event Name of the event that called us
```

Definition at line 3321 of file Ispmac.c.

```
blight->moveAbs( blight, 0.0);
}
```

7.6.4.8 void lspmac_backLight_up_cb (char * event)

Turn on the backlight whenever it goes up.

Parameters

```
event Name of the event that called us
```

Definition at line 3314 of file Ispmac.c.

7.6.4.9 Ispmac_bi_t* Ispmac_bi_init (Ispmac_bi_t * d, int * ptr, int mask, char * onEvent, char * offEvent)

Initialize binary input.

Definition at line 3116 of file Ispmac.c.

7.6.4.10 void lspmac_blight_lut_setup ()

Set up lookup table for blight.

Definition at line 3423 of file Ispmac.c.

```
{
int i;
lsredis_obj_t *p;
pthread_mutex_lock( &blight->mutex);
blight->nlut = 11;
blight->lut = calloc( 2 * blight->nlut, sizeof( double));
if( blight->lut == NULL) {
  lslogging_log_message( "lspmac_blight_lut_setup: out
      of memory");
  exit(-1);
blight \rightarrow lut[0] = 0;
blight->lut[1] = 0;
for( i=1; i<bli>blight->nlut; i++) {
   p = lsredis_get_obj( "cam.zoom.%d.LightIntensity", i);
  if( p==NULL || strlen( lsredis_getstr(p)) == 0) {
     free( blight->lut);
     blight->lut = NULL;
blight->nlut = 0;
     pthread_mutex_unlock( &blight->mutex);
     {\tt lslogging\_log\_message("lspmac\_blight\_lut\_setup:}
     cannot find MotorPosition element for cam.blight level %d", i);
     return:
  blight->lut[2*i]
  blight->lut[2*i+1] = 20000.0 * lsredis_getd(p) / 100.
for( i=0; i<bli>i<bli>blight->nlut; i++) {
  lslogging_log_message( "lspmac_blight_lut_setup: i:
    %d x: %f y: %f y(lut): %f x(rlut): %f",
                              i, blight->lut[2*i], blight->lut[2
                              lspmac_lut( blight->nlut, blight
     ->lut, blight->lut[2*i]),
                             lspmac_rlut( blight->nlut,
     blight->lut, blight->lut[2*i+1])
pthread_mutex_unlock( &blight->mutex);
```

7.6.4.11 Ispmac_motor_t* Ispmac_bo_init (Ispmac_motor_t * d, char * name, char * write_fmt, int * read_ptr, int read_mask)

Initialize binary i/o motor.

Parameters

in	d	Our uninitialized motor object
in	name	Name of motor to coordinate with DB
in	write_fmt	Format string used to generate PMAC command to move motor
in	read_ptr	Pointer to byte in md2_status to find position
in	read_mask	Bitmask to find position in *read_ptr

Definition at line 3050 of file Ispmac.c.

7.6.4.12 void lspmac_bo_read (lspmac_motor_t * mp)

Read the state of a binary i/o motor This is the read method for the binary i/o motor class.

Parameters

in mp The motor		mp
---------------------	--	----

Definition at line 1121 of file Ispmac.c.

```
int pos, changed;
pthread_mutex_lock( &(mp->mutex));
pos = (*(mp->read_ptr) & mp->read_mask) == 0 ? 0 : 1;
changed = pos != mp->position;
mp->position = pos;
pthread_mutex_unlock( &(mp->mutex));
if( changed)
   lsevents_send_event( "%s %d", mp->name, pos);
```

7.6.4.13 void lspmac_command_done_cb (char * event)

Definition at line 3483 of file Ispmac.c.

```
int i;
lspmac_motor_t *mp;

// O(n). Bad.
//
for( i=0; i<lspmac_nmotors; i++) {
   if( strncmp( lspmac_motors[i].name, event, strlen( lspmac_motors[i].name)) == 0)
   break;
}

if( i >= lspmac_nmotors)
   return;

mp = &(lspmac_motors[i]);
pthread_mutex_lock(&(mp->mutex));
```

```
mp->command_sent = 1;
pthread_cond_signal( &(mp->cond));
pthread_mutex_unlock( &(mp->mutex));
return;
```

7.6.4.14 void lspmac_cryoSwitchChanged_cb (char * event)

Definition at line 3276 of file Ispmac.c.

```
int pos;

pthread_mutex_lock( &(cryo->mutex));
pos = cryo->position;
pthread_mutex_unlock( &(cryo->mutex));

cryo->moveAbs( cryo, pos ? 0.0 : 1.0);
}
```

7.6.4.15 Ispmac_motor_t* Ispmac_motor_t * d, int * posp, char * mvar, char * name, int(*)(Ispmac_motor_t *, double) moveAbs)

Initialize DAC motor Note that some motors require further initialization from a database query.

For this reason this initialzation code must be run before the database queue is allowed to be processed.

Parameters

out	d	Returns the (almost) initialized motor object [in,out] unitintialized motor
in	posp	Location of current position
in	mvar	M variable, ie, "M1200"
in	name	name to coordinate with DB
in	moveAbs	Method to use to move this motor

Definition at line 3076 of file Ispmac.c.

```
_lspmac_motor_init( d, name);
d->moveAbs = moveAbs;
d->read = lspmac_dac_read;
d->actual_pos_cnts_p = posp;
d->dac_mvar = strdup(mvar);
return d;
```

7.6.4.16 void lspmac_dac_read (lspmac_motor_t * mp)

Read a DAC motor position.

Parameters

in mp The motor	
-----------------	--

Definition at line 1141 of file Ispmac.c.

```
double u2c;
```

```
pthread_mutex_lock( & (mp->mutex));
mp->actual_pos_cnts = *mp->actual_pos_cnts_p;
u2c = lsredis_getd( mp->u2c);

if( mp->nlut >0 && mp->lut != NULL) {
   if( u2c == 0.0)
      u2c = 1.0;
   mp->position = lspmac_rlut( mp->nlut, mp->lut, mp
      ->actual_pos_cnts/u2c);
} else {
   if( u2c != 0.0) {
      mp->position = mp->actual_pos_cnts / u2c;
} else {
      mp->position = mp->actual_pos_cnts;
}
}
pthread_mutex_unlock( & (mp->mutex));
```

7.6.4.17 void lspmac_Error (char * buff)

The service routing detected an error condition.

Scan the response buffer for an error code and print it out.

Parameters

in	buff	Buffer returned by PMAC perhaps containing a NULL terminated message.
----	------	---

Definition at line 767 of file Ispmac.c.

7.6.4.18 double lspmac_est_move_time (double *min_time*, double *delta*, lspmac_motor_t * *mp_1*, char * *preset_1*, double end_point_1, ...)

guess the minimum time it will take to move the motor

Parameters

ſ	min_time	Return at least this value. Can be zero if you like.
ľ	delta	Add this fudge factor to the estimate so we always over estimate the time (You do not want to
		under estimate or even be exactly right)
ľ	mp_1	Pointer to first motor
Ī	preset_1	Name of preset we'd like to move to or NULL if end_point_1 should be used instead

end_point_1	End point for the first motor. Ignored if preset_1 is non null and identifies a valid preset for	
	motor	
	Perhaps more pairs of motors and end points MUST END ARG LIST WITH NULL	

Definition at line 2606 of file Ispmac.c.

```
{
va_list arg_ptr;
lspmac_motor_t *mp;
double ep, maybe_ep;
char *ps;
double rtn;
double t;
int err;
rtn = min_time;
mp = mp_1;
ps = preset_1;
ep = end_point_1;
va_start( arg_ptr, end_point_1);
while( 1) {
  t = min_time;
  if ( mp != NULL && mp->max_speed != NULL && mp->max_accel
    != NULL && mp->u2c &&
       lsredis_getd( mp->max_speed) > 0 && lsredis_getd
     (mp->max\_accel) > 0 \&\& lsredis\_getd(mp->u2c) > 0) {
    if( ps != NULL && *ps != 0) {
  err = lsredis_find_preset( mp->name, ps, &
    maybe_ep);
       if( err != 0)
         ep = maybe_ep;
    // time if we went the entire way at constant velocity
    t = fabs(ep - lspmac_getPosition(mp)) / lsredis_getd
( mp->u2c) / lsredis_getd( mp->max_speed);
     \ensuremath{//} Correction for acceleration time
    t += lsredis_getd( mp->max_speed) / lsredis_getd
    ( mp->max_accel);
    \ensuremath{//} Add something for good measure: we always want to overestimate the
     timeout
    t += delta;
  rtn = rtn < t ? t : rtn;
  mp = va_arg( arg_ptr, lspmac_motor_t *);
  if ( mp == NULL)
    break;
  ps = va_arg( arg_ptr, char *);
  ep = va_arg( arg_ptr, double);
va_end( arg_ptr);
return rtn;
```

7.6.4.19 void lspmac_flight_lut_setup ()

Set up lookup table for flight.

Definition at line 3390 of file Ispmac.c.

```
int i;
lsredis_obj_t *p;
```

7.6.4.20 void lspmac_fscint_lut_setup ()

Set up lookup table for fscint.

Definition at line 3464 of file Ispmac.c.

7.6.4.21 | Ispmac_motor_t* | Ispmac_fshut_init (| Ispmac_motor_t * d)

Initalize the fast shutter motor.

Parameters

in	d	Our uninitialized motor object
----	---	--------------------------------

Definition at line 3034 of file Ispmac.c.

```
return d;
7.6.4.22 void lspmac_get_ascii ( char * event )
Forward declarateion.
Request the ascii buffers from the PMAC.
Definition at line 1935 of file Ispmac.c.
  lspmac_send_command( VR_UPLOAD, VR_PMAC_GETMEM
       , 0x0e9c, 0, sizeof(lspmac_ascii_buffers_t), NULL,
       lspmac_get_ascii_cb, 0, event);
7.6.4.23 void lspmac_get_ascii_cb ( pmac_cmd_queue_t * cmd, int nreceived, char * buff )
service the ascii buffer request response
Definition at line 1827 of file Ispmac.c.
  uint32_t clrdata;
  int need_more;
  need\_more = 0;
  pthread_mutex_lock( &lspmac_ascii_mutex);
memcpy( &lspmac_ascii_buffers, buff, sizeof(
       lspmac_ascii_buffers));
  //
// The response is not ready yet
// This will be an infinite loop if we queue a command that does not
  // produce a response.
  // Quoted comments below from Delta Tau "Turbo PMAC User Manual 9/12/2008,
  // "1. Wait for the Host-Input Control Word at 0x0F40 (Y:$063D0) to become
    greater than 0, indicating
// that a response line is ready."
  if( lspmac_ascii_buffers.response_buf == 0) {
    need\_more = 1;
  } else {
  if( (lspmac_ascii_buffers.response_buf & 0
    x8000) != 0) {
       char bcd1, bcd2, bcd3;
       int errcode;
       // Error response
       ^{\prime\prime} // "2. Interpret the value in this register to determine what
       // type of response is present. If Bit 15 is 1, Turbo PMAC is
       // reporting an error in the command, and there is no response
       // other than this word. In this case, Bits 0 - 11 encode the
       // error number for the command as 3 BCD digits."
       need_more = 0;
       bcd1 = lspmac_ascii_buffers.response_buf
        & 0x000f;
       bcd2 = (lspmac_ascii_buffers.response_buf
        & 0x00f0) >> 4;
       errcode = (bcd3 * 10 + bcd2) * 10 + bcd1;
       if( errcode >= sizeof( pmac_error_strs)/sizeof(
        *pmac_error_strs))
         errcode = 0;
       lslogging_log_message( "lspmac_get_ascii_cb: Error returned for %s: %s", lspmac_ascii_buffers.command_str
```

, pmac_error_strs[errcode]);
//

```
// Command not allowed during program execution.
     // Requeue it;
     if( errcode == 1) {
       lspmac_dpascii_off--;
  } else {
     //
// "3. Read the response string starting at 0x0F44
// (Y:$0603D1). Two 8-bit characters are packed into each 16-bit
     // word; the first character is placed into the low
     // byte. Subsequent characters are placed into consecutive
// higher addresses, two per 16-bit word. (In byte addressing,
// each character is read from an address one higher than the
     // preceding character.) Up to 255 characters can be sent in a
     \ensuremath{//} single response line. The string is terminated with the NULL
     \ensuremath{//} character (byte value 0), convenient for C-style string
     // handling. For Pascal-style string handling, the register at // 0x0F42 (X:$0603D0) contains the number of characters in the
     // string (plus one)."
     if( lspmac_ascii_buffers.response_n > 1)
  lslogging_log_message( "lspmac_get_ascii_cb: '%s'
  '%s'", lspmac_ascii_buffers.command_str,
     lspmac_ascii_buffers.response_str);
     else
        lslogging_log_message( "lspmac_get_ascii_cb: '%s'
        responded", lspmac_ascii_buffers.command_str);
     ^{\prime\prime} 5. "If Bits 0 - 7 of the Host-Input Control Word had
     // contained the value $0D (13 decimal, "CR"), this was not the
     // last line in the response, and steps 1 - 4 should be
     // repeated. If they had contained the value $06 (6 decimal,
     // "ACK"), this was the last line in the response."
     if( (lspmac_ascii_buffers.response_buf &
     0x00ff) == 0x0d) {
       need_more = 1;
       else {
       need\_more = 0;
       if( cmd->event != NULL && *(cmd->event) != 0)
  lsevents_send_event( "%s command accepted", cmd->
     event);
  }
pthread mutex unlock( &lspmac ascii mutex);
// Reset the buffer flags and, perhaps, requeue a request
// "4. Clear the Host-Input Control Word at 0x0F40 (Y:$063D0)
// to 0. Turbo PMAC will not send another response line until it sees
// this register set to 0."
clrdata = 0;
                           // set the control word to zero
if( need_more) {
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
  , 0x0f40, 0, 4, (char *)&clrdata, lspmac_more_ascii_cb, 1,
     NULL);
} else {
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
  , 0x0f40, 0, 4, (char *)&clrdata, NULL, 1, NULL); lspmac_ascii_busy = 0;
```

7.6.4.24 void lspmac_get_status ()

}

Request a status update from the PMAC.

Definition at line 1815 of file Ispmac.c.

7.6.4.25 void lspmac_get_status_cb (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Service routing for status upate This updates positions and status information.

Parameters

in	cmd	The command that generated this reply
in	nreceived	Number of bytes received
in	buff	The Big Byte Buffer

Definition at line 1591 of file Ispmac.c.

```
#ifdef SHOW_RATE
static struct timespec ts1;
static struct timespec ts2;
static int cnt = 0;
#endif
int i;
lspmac_bi_t
clock_gettime( CLOCK_REALTIME, &lspmac_status_time);
#ifdef SHOW_RATE
if(cnt == 0) {
 clock_gettime( CLOCK_REALTIME, &ts1);
#endif
pthread_mutex_lock( &md2_status_mutex);
memcpy( &md2_status, buff, sizeof(md2_status));
//
// Note that we are the only thread that writes to md2_status
// so we no longer need the lock to read. Other threads must
// lock the mutex to read md2_status.
pthread_mutex_unlock( &md2_status_mutex);
//  \begin{tabular}{ll} // & track the coordinate system moving flags \end{tabular} 
pthread_mutex_lock( &lspmac_moving_mutex);
if( md2_status.moving_flags != lspmac_moving_flags
  int mask;
  lslogging_log_message( "lspmac_get_status_cb: new
    moving flag: %0x", md2_status.moving_flags);
  for( i=1; i<=16; i++, mask <<= 1) {</pre>
    if( ((lspmac_moving_flags & mask) != 0) && ((
    md2_status.moving_flags & mask) == 0)) {
  // Falling edge: send event
      lsevents_send_event( "Coordsys %d Stopped", i);
  lspmac_moving_flags = md2_status.moving_flags
  pthread_cond_signal( &lspmac_moving_cond);
pthread_mutex_unlock( &lspmac_moving_mutex);
// Read the motor positions //
for( i=0; i<lspmac_nmotors; i++) {</pre>
  lspmac_motors[i].read(&(lspmac_motors[i]));
// Read the binary inputs and perhaps send an event
for( i=0; i<lspmac_nbis; i++) {</pre>
  bp = &(lspmac_bis[i]);
  pthread_mutex_lock( & (bp->mutex));
  bp \rightarrow position = (*(bp \rightarrow ptr) & bp \rightarrow mask) == 0 ? 0 : 1;
```

```
if( bp->first_time) {
    bp->first_time = 0;
    if( bp->position==1 && bp->changeEventOn != NULL &&
    bp->changeEventOn[0] != 0)
      lsevents_send_event( lspmac_bis[i].
    changeEventOn);
    if( bp->position==0 && bp->changeEventOff != NULL
    && bp->changeEventOff[0] != 0)
      lsevents_send_event( lspmac_bis[i].
    changeEventOff);
  } else {
    if( bp->position != bp->previous) {
      if( bp->position==1 && bp->changeEventOn != NULL
    && bp->changeEventOn[0] != 0)
         lsevents_send_event( lspmac_bis[i].
    changeEventOn);
    if(bp->position==0 && bp->changeEventOff != NULL
&& bp->changeEventOff[0] != 0)
   lsevents_send_event( lspmac_bis[i].
    changeEventOff);
  bp->previous = bp->position;
 pthread_mutex_unlock( &(bp->mutex));
pthread_mutex_lock( &ncurses_mutex);
// acc11c_1
              INPUTS
// mask bit
// 0x01 0
              M1000
                      Air pressure OK
Air bearing OK
// 0x02
              M1001
// 0x04
              M1002
                       Cryo switch
// 0x08
              M1003
                       Backlight Down
// 0x10 4
// 0x20 5
              M1004
                      Backlight Up
// 0x40 6
              M1006
                      Crvo is back
// acc11c_2
              INPUTS
// mask bit
// 0x01 0
              M1008
                       Fluor Dector back
                       Sample Detected
// 0x02
              M1009
// 0x04 2
              M1020
                       {SC load request}
              M1021
// 0x08 3
                       {SC move cryo back request}
// 0x10 4
              M1022
                       {SC sample magnet control}
// 0x20 5
              M1013
                       Etel Ready
// 0x40
        6
              M1014
                       Etel On
// 0x80
              M1015
                       Etel Init OK
if( md2_status.acc11c_2 & 0x01)
 mvwprintw( term_status2, 3, 10, "%*s", -8, "Fluor Out");
else
 mvwprintw( term_status2, 3, 10, "%*s", -8, "Fluor In");
if( md2_status.acc11c_5 & 0x08)
 mvwprintw(term_status2, 4, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
    -2), "Dryer On");
 mvwprintw( term_status2, 4, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
    -2), "Dryer Off");
if ( md2_status.acc11c_2 & 0x02)
 mvwprintw( term_status2, 2, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
    -2), "Cap Dectected");
 mvwprintw( term_status2, 2, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
-2), "Cap Not Dectected");
wnoutrefresh( term_status2);
// acc11c_3
              INPUTS
// mask bit
              M1025
// 0x01 0
                       Minikappa OK
// 0x02 1
              M1023
                       {SC unload request}
// 0x04 2
              M1024
                       Smartmagnet is on (note in pmc saying this is not used
     in VB interface)
// 0x08 3
              M1027
                       Arm Parked
// 0x10 4
              M1031
                       Smartmagnet error (coil is broken)
// 0x20
// 0x40
// 0x80
// 0x100 8
              M1048
                       Shutter is open (note in pmc says: slow input !!!)
// acc11c_4
              INPUTS
// mask bit
// 0x01 0
              M1031
                       {laser mirror is back}
```

```
// 0x02 1
               M1032
                       {laser PSS OK}
// 0x04 2
              M1033
                      {laser shutter open}
// acc11c_5
              OUTPUTS
// mask bit
// 0x01 0
              M1100
                       Mag Off
// 0x02
               M1191
                       Condenser Out
// 0x04 2
               M1102
                       Cryo Back
// 0x08 3
              M1103
                       Drver On
// 0x10 4
               M1104
                      FluoDet Out
                      {smartmagnet on/off: note in pmc says this is not used}
1=SmartMag, 0=Permanent Mag
// 0x20 5
               M1105
// 0x40 6
              M1106
if( md2_status.acc11c_5 & 0x04)
 mvwprintw( term_status2, 3, 1, "%*s", -8, "Cryo Out");
 mvwprintw( term_status2, 3, 1, "%*s", -8, "Cryo In ");
// acc11c_6 OUTPUTS
// mask bit
// 0x0001 0
            0 M1040 {SC Sample transfer is on}
// 0x0002
// 0x0004
// 0x0008
             3
// 0x0010
// 0x0020
             5
           6
7 M1115 Etel Enable
8 M1124 Fast Shutter Enable
9 M1125 Fast Shutter Manual
// 0x0040
// 0x0080
// 0x0100
// 0x0200
                       Fast Shutter Manual Enable
// 0x0400 10 M1126 Fast Shutter On
// 0x0800 11
// 0x1000 12 M1128 ADC1 gain bit 0
// 0x2000 13 M1129
                      ADC1 gain bit 1
// 0x4000 14 M1130
                       ADC2 gain bit 0
// 0x8000 15 M1131
                      ADC2 gain bit 1
if ( md2_status.acc11c_5 & 0x02)
 mvwprintw(term_status, 3, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
    -2), "Backlight Up");
else
 mvwprintw( term_status, 3, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
-2), "Backlight Down");
mvwprintw( term_status, 4, 1, "Front: %*u",
    LS_DISPLAY_WINDOW_WIDTH-2-8, (int)flight->position);
mvwprintw( term_status, 5, 1, "Back: %*u", LS_DISPLAY_WINDOW_WIDTH
    -2-7,
           (int)blight->position);
mvwprintw( term_status, 6, 1, "Piezo: %*u",
    LS_DISPLAY_WINDOW_WIDTH-2-8, (int)fscint->position);
wnoutrefresh( term_status);
wnoutrefresh( term_input);
doupdate();
pthread_mutex_unlock( &ncurses_mutex);
#ifdef SHOW_RATE
if( ++cnt % 1000 == 0) {
  long diff_sec;
  long diff_nsec;
  clock_gettime( CLOCK_REALTIME, &ts2);
  diff_sec = ts2.tv_sec - ts1.tv_sec;
  diff_nsec = ts2.tv_nsec - ts1.tv_nsec;
  if( diff_nsec < 0) {</pre>
    diff_nsec += 1000000000;
   diff_sec--;
  lslogging_log_message( "Refresh Rate: %0.1f Hz", (
   double)cnt / (diff_sec + diff_nsec/1000000000.));
 cnt = 0:
#endif
```

```
7.6.4.26 void Ispmac_GetAllIVars ( )
```

Request the values of all the I variables.

Definition at line 2042 of file Ispmac.c.

```
static char *cmds = "IO..8191";
lspmac_send_command( VR_DOWNLOAD,
    VR_PMAC_SENDLINE, 0, 0, strlen( cmds), cmds,
    lspmac_GetAllIVarsCB, 0, NULL);
```

7.6.4.27 void lspmac_GetAllIVarsCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Receive the values of all the I variables Update our Postgresql database with the results.

Parameters

in	cmd	The command that gave this response
in	nreceived	Number of bytes received
in	buff	The byte buffer

Definition at line 2025 of file Ispmac.c.

```
static char qs[LS_PG_QUERY_STRING_LENGTH];
char *sp;
int i;
for( i=0, sp=strtok(buff, "\r"); sp != NULL; sp=strtok( NULL, "\r"), i++) {
    snprintf( qs, sizeof( qs)-1, "SELECT pmac.md2_ivar_set( %d, '%s')", i, sp);
    qs[sizeof( qs)-1]=0;
    lspg_query_push( NULL, qs);
}
```

7.6.4.28 void Ispmac_GetAIIMVars ()

Request the values of all the M variables.

Definition at line 2067 of file Ispmac.c.

7.6.4.29 void $lspmac_GetAllMVarsCB$ ($pmac_cmd_queue_t*cmd$, int nreceived, char*buff)

Receive the values of all the M variables Update our database with the results.

Parameters

in	cmd	The command that started this
in	nreceived	Number of bytes received
in	buff	Our byte buffer

Definition at line 2050 of file Ispmac.c.

{

```
static char qs[LS_PG_QUERY_STRING_LENGTH];
char *sp;
int i;
for( i=0, sp=strtok(buff, "\r"); sp != NULL; sp=strtok( NULL, "\r"), i++) {
    snprintf( qs, sizeof( qs)-1, "SELECT pmac.md2_mvar_set( %d, '%s')", i, sp);
    qs[sizeof( qs)-1]=0;
    lspg_query_push( NULL, qs);
}
```

7.6.4.30 int lspmac_getBIPosition (lspmac_bi_t * bip)

get binary input value

Definition at line 1579 of file Ispmac.c.

```
int rtn;
pthread_mutex_lock( &bip->mutex);
rtn = bip->position;
pthread_mutex_unlock( &bip->mutex);
return rtn;
```

7.6.4.31 void Ispmac_Getmem ()

Request a block of double buffer memory.

Definition at line 1112 of file Ispmac.c.

```
int nbytes;
nbytes = (dbmemIn + 1400 > sizeof( dbmem)) ? sizeof( dbmem)
  - dbmemIn : 1400;
lspmac_SockGetmem( dbmemIn, nbytes);
```

7.6.4.32 void lspmac_GetmemReplyCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Service a reply to the getmem command.

Parameters

cmd	Queue item this is a reply to	
nreceived	Number of bytes received	
buff	buff Buffer of bytes recieved	

Definition at line 1038 of file Ispmac.c.

```
memcpy( &(dbmem[ntohs(cmd->pcmd.wValue)]), buff, nreceived);
dbmemIn += nreceived;
if( dbmemIn >= sizeof( dbmem)) {
   dbmemIn = 0;
}
```

7.6.4.33 double lspmac_getPosition (Ispmac_motor_t * mp)

get the motor position (with locking)

Parameters

mp	the motor object

Definition at line 1339 of file Ispmac.c.

```
double rtn;
pthread_mutex_lock( & (mp->mutex));
rtn = mp->position;
pthread_mutex_unlock( & (mp->mutex));
return rtn;
}
```

7.6.4.34 void lspmac_GetShortReplyCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Receive a reply that does not require multiple buffers.

Parameters

in	cmd	Queue item this is a reply to
in	nreceived	Number of bytes received
in	buff	The buffer of bytes

Definition at line 981 of file Ispmac.c.

```
// pointer to the command this is a reply to
char *sp;
if( nreceived < 1400)</pre>
 buff[nreceived]=0;
sp = (char *) (cmd->pcmd.bData);
if( *buff == 0) {
 pthread_mutex_lock( &ncurses_mutex);
  wprintw( term_output, "%s\n", sp);
  pthread_mutex_unlock( &ncurses_mutex);
  pthread_mutex_lock( &ncurses_mutex);
  wprintw( term_output, "%s: ", sp);
pthread_mutex_unlock( &ncurses_mutex);
  cleanstr( buff);
wnoutrefresh( term_output);
wnoutrefresh( term_input);
doupdate();
memset( cmd->pcmd.bData, 0, sizeof( cmd->pcmd.bData));
```

7.6.4.35 void lspmac_home1_queue (lspmac_motor_t * mp)

Home the motor.

Parameters

in	тр	motor we are concerned about
----	----	------------------------------

Definition at line 1205 of file Ispmac.c.

```
int i;
int motor_num;
int coord_num;
char **home;
```

```
pthread_mutex_lock( & (mp->mutex));
motor_num = lsredis_get1( mp->motor_num);
coord_num = lsredis_get1( mp->coord_num);
          = lsredis_get_string_array( mp->home);
home
// Each of the motors should have this defined
// but let's not seg fault if home is missing
if( home == NULL || *home == NULL) {
  // Note we are already initialized
  // so if we are here there is something wrong.
  lslogging_log_message( "lspmac_home1_queue: null or
    empty home strings for motor %s", mp->name);
  pthread_mutex_unlock( &(mp->mutex));
  return;
// We've already been called. Don't home again until // we're finish with the last time.
if( mp->homing) {
 pthread_mutex_unlock( & (mp->mutex));
  return;
// Don't go on if any other motors in this coordinate system are homing.
// It's possible to write the homing program to home all the motors in the
     coordinate
// system. TODO (hint hint)
if( coord_num > 0) {
  for( i=0; i<lspmac_nmotors; i++) {</pre>
    if( &(lspmac_motors[i]) == mp)
      continue;
    if( lsredis_getl(lspmac_motors[i].coord_num) ==
    coord_num) {
      int nogo;
      nogo = 0:
      pthread_mutex_lock( &(lspmac_motors[i].mutex));
      // Don't go on if
      //
            we are homing
                                 or ( not in position
     while
               in open loop)
      //
       if( lspmac_motors[i].homing || (((lspmac_motors
    [i].status2 & 0x01)==0) && ((lspmac_motors[i].status1 & 0x040000)
    != 0)))
        nogo = 1;
      pthread_mutex_unlock( &(lspmac_motors[i].mutex));
      if ( nogo) {
       pthread_mutex_unlock( & (mp->mutex));
        return;
   }
  }
mp->homing
mp->not_done = 1;
                      // set up waiting for cond
mp->motion_seen = 0;
// This opens the control loop.
// The status routine should notice this and the fact that
// the homing flag is set and call on the home2 routine
^{\prime\prime} // Only send the open loop command if we are not in
// open loop mode already. This test might prevent a race condition
// where we've already moved the home2 routine (and queue the homing program
     motion)
// before the open loop command is dequeued and acted on.
if( ~(mp->status1) & 0x040000) {
  lspmac_SockSendDPline( mp->name, "#%d$*",
    motor_num);
pthread mutex unlock( & (mp->mutex));
lsevents_send_event( "%s Homing", mp->name);
```

7.6.4.36 void lspmac_home2_queue (lspmac_motor_t * mp)

Second stage of homing.

Parameters

in	тр	motor we are concerned about
----	----	------------------------------

Definition at line 1293 of file Ispmac.c.

```
char **spp;
char **home;
// At this point we are in open loop.
// Run the motor specific commands
pthread_mutex_lock( &(mp->mutex));
home = lsredis_get_string_array( mp->home);
// We don't have any motors that have a null home text array so
// there is currently no need to worry about this case other than
// not to seg fault
^{\prime\prime} // Also, Only go on if the first homing phase has been started
if( home == NULL || mp->homing != 1) {
  pthread_mutex_unlock( & (mp->mutex));
for( spp = home; *spp != NULL; spp++) {
  pthread_mutex_lock( &ncurses_mutex);
  wprintw( term_output, "home2 is queuing '%s'\n", *spp);
  wnoutrefresh( term_output);
  doupdate();
  pthread_mutex_unlock( &ncurses_mutex);
  lspmac_SockSendDPline( mp->name, *spp);
mp \rightarrow homing = 2;
pthread_mutex_unlock( & (mp->mutex));
```

7.6.4.37 void Ispmac_init (int ivarsflag, int mvarsflag)

Initialize this module.

Parameters

in	ivarsflag	Set global flag to harvest i variables
in	mvarsflag	Set global flag to harvest m variables

Definition at line 3132 of file Ispmac.c.

```
{
md2_status_t *p;
pthread_mutexattr_t mutex_initializer;

// Set our global harvest flags
getivars = ivarsflag;
getmvars = mvarsflag;

// Use recursive mutexs
//
pthread_mutexattr_init( &mutex_initializer);
pthread_mutexattr_settype( &mutex_initializer, PTHREAD_MUTEX_RECURSIVE);
```

```
// All important status mutex
pthread_mutex_init( &md2_status_mutex, &mutex_initializer);
// Get the MD2 initialization strings
// lspmac_md2_init = lsredis_get_obj( "md2_pmac.init"); // hard coded now.
// Initialize the motor objects
p = &md2_status;
omega = lspmac_motor_init( &(lspmac_motors
     [ 0]), 0, 0, &p->omega_act_pos, &p->omega_status_1, &p->omega_status_2, "Omega #1 &1 X", "omega",
     lspmac_moveabs_queue);
    alignx = lspmac_motor_init( &(lspmac_motors
     lspmac_moveabs_queue);
aligny = lspmac_motor_init( &(lspmac_motors
    [ 2]), 0, 2, &p->aligny_act_pos, &p->aligny_status_1 , &p->aligny_status_2, "Align Y #3 &3 Y", "align.y",
     lspmac_moveabs_queue);
alignz = lspmac_motor_init( &(lspmac_motors
     [ 3]), 0, 3, &p->alignz_act_pos, &p->alignz_status_1 . &p->alignz_status_2, "Align Z #4 &3 Z", "align.z",
     lspmac_moveabs_queue);
         = lspmac_motor_init( &(lspmac_motors
    [ 4]), 0, 4, &p->analyzer_act_pos, &p->analyzer_status_1, &p->analyzer_status_2, "Anal #5", "lightPolar
                                                             "lightPolar",
        &p->analyzer_status_2,
    lspmac_moveabs_queue);
        = lspmac_motor_init( &(lspmac_motors
    [5]), 1, 0, &p->zoom_act_pos, &p->zoom_status_1, &p->zoom_status_2, "Zoom #6 &4 Z", "cam.zoom",
     lspmac_movezoom_queue);
apery = lspmac_motor_init( &(lspmac_motors
    [ 6]), 1, 1, &p->aperturey_act_pos, &p->aperturey_status_1
    , &p->aperturey_status_2, "Aper Y #7 &5 Y", "appy",
     lspmac_moveabs_queue);
aperz = lspmac_motor_init( &(lspmac_motors
    [ 7]), 1, 2, &p->aperturez_act_pos, &p->aperturez_status_1
    , &p->aperturez_status_2, "Aper Z #8 &5 Z", "appz",
        = lspmac_motor_init( &(lspmac_motors
     lspmac_moveabs_queue);
       = lspmac_motor_init( &(lspmac_motors
    [8]), 1, 3, &p->capy_act_pos, &p->capy_status_1, &p->capy_status_2, "Cap Y #9 &5 U", "capy",
    lspmac_moveabs_queue);
        = lspmac_motor_init( &(lspmac_motors
     [ 9]), 1, 4, &p->capz_act_pos, &p->capz_status_1, &p->capz_status_2, "Cap Z #10 &5 V", "capz",
          &p->capz_status_2,
    lspmac_moveabs_queue);
nt = lspmac_motor_init( &(lspmac_motors)
scint
    [10]), 2, 0, &p->scint_act_pos,
                                               &p->scint_status_1
           &p->scint_status_2,
                                         "Scin Z #11 &5 W", "scint",
     lspmac_moveabs_queue);
        = lspmac_motor_init( &(lspmac_motors
    [11]), 2, 1, &p->centerx_act_pos, &p->centerx_status_1
, &p->centerx_status_2, "Cen X #17 &2 X", "centering.x",
     lspmac_moveabs_queue);
         = lspmac_motor_init( &(lspmac_motors
     [12]), 2, 2, &p->centery_act_pos, &p->centery_status_1
, &p->centery_status_2, "Cen Y #18 &2 Y", "centering.y",
     lspmac_moveabs_queue);
        = lspmac_motor_init( &(lspmac_motors
    [13]), 2, 3, &p->kappa_act_pos, &p->kappa_status_1
, &p->kappa_status_2, "Kappa #19 &7 X", "kappa",
     lspmac_moveabs_queue);
        = lspmac_motor_init( &(lspmac_motors[
    lspmac_moveabs_queue);
fshut = lspmac_fshut_init( &(lspmac_motors
     [15]));
lspmac_movedac_queue);
blight = lspmac_dac_init( &(lspmac_motors[1
     7]), &p->back_dac,
                               "M1201", "backLight.intensity",
     lspmac_movedac_queue);
fscint = lspmac_dac_init( &(lspmac_motors[1
   8]), &p->scint_piezo, "M1203", "scint.focus",
     lspmac_movedac_queue);
```

```
smart_mag_oo = lspmac_bo_init( &(lspmac_motors
[19]), "smartMagnet", "M1100=%d", &(md2_status.acc11c_5), 0x01)
    ght_ud = lspmac_bo_init( &(lspmac_motors
[20]), "backLight", "M1101=%d", &(md2_status.acc11c_5), 0x02)
blight ud
                = lspmac_bo_init( &(lspmac_motors
    [21]), "cryo",
                            "M1102=%d", & (md2_status.acc11c_5), 0x04)
               = lspmac_bo_init( &(lspmac_motors aryer", "M1103=%d", &(md2_status.accl1c_5), 0x08)
    [22]), "dryer",
               = lspmac_bo_init( &(lspmac_motors
     [23]), "fluo",
                              "M1104=%d", & (md2_status.acc11c_5), 0x10)
    ,ht_oo = lspmac_soft_motor_init( &(
lspmac_motors[24]), "frontLight",
lspmac_moveabs_frontlight_oo_queue);
flight oo
                = lspmac_soft_motor_init( &(
     lspmac_motors[25]), "backLight.factor",
     lspmac_moveabs_blight_factor_queue);
     ht_f = lspmac_soft_motor_init( &(
lspmac_motors[26]), "frontLight.factor",
flight_f
     lspmac_moveabs_flight_factor_queue);
                   = lspmac_bi_init( &(lspmac_bis[
     0]), &(md2_status.accl1c_1), 0x01, "Low Pressure Air OK", "
     Low Pressure Air Failed");
     hp_air
    High Pressure Air Failed");
cryo_switch
                  = lspmac_bi_init( &(lspmac_bis
     [ 2]), & (md2_status.acc11c_1), 0x04, "CryoSwitchChanged",
    ght_down = lspmac_bi_init( &(lspmac_bis
[ 3]), &(md2_status.accllc_1), 0x08, "Backlight Down",
"Backlight Not Down");
     "CryoSwitchChanged");
blight_down
blight_up
                   = lspmac_bi_init( &(lspmac_bis
     [ 4]), & (md2_status.acc11c_1), 0x10, "Backlight Up",
     "Backlight Not Up");
cryo_back = lspmac_bi_init( &(lspmac_bis
      [ 5]), &(md2_status.accl1c_1), 0x40, "Cryo Back",
     "Cryo Not Back");
fluor_back
               = lspmac_bi_init( &(lspmac_bis
      6]), &(md2_status.acc11c_2), 0x01, "Fluor. Det. Parked",
     "Fluor. Det. Not Parked");
sample_detected = lspmac_bi_init( &(lspmac_bis
        [ 7]), &(md2_status.acc11c_2), 0x02, "SamplePresent",
     "SampleAbsent");
etel_ready
                  = lspmac_bi_init( &(lspmac_bis
     [ 8]), &(md2_status.acc11c_2), 0x20, "ETEL Ready",
     "ETEL Not Ready");
     _on = lspmac_bi_init( &(lspmac_bis [ 9]), &(md2_status.accl1c_2), 0x40, "ETEL On",
etel_on
     "ETEL Off");
etel_init_ok
                   = lspmac_bi_init( &(lspmac_bis
     [10]), & (md2_status.acc11c_2), 0x80, "ETEL Init OK",
     "ETEL Init Not OK");
     .kappa_ok = lspmac_bi_init( &(lspmac_bis
[11]), &(md2_status.accl1c_3), 0x01, "Minikappa OK",
minikappa_ok
     "Minikappa Not OK");
smart_mag_on
                  = lspmac_bi_init( &(lspmac_bis
    [12]), & (md2_status.acc11c_3), 0x04, "Smart Magnet On",
     "Smart Magnet Not On");
     parked = lspmac_bi_init( &(lspmac_bis
[13]), &(md2_status.accl1c_3), 0x08, "Arm Parked",
arm_parked
     "Arm Not Parked");
smart_mag_err = lspmac_bi_init( &(lspmac_bis
     [14]), & (md2_status.acc11c_3), 0x10, "Smart Magnet Error",
     "Smart Magnet OK");
     ter_open = lspmac_bi_init( &(lspmac_bis
[15]), &(md2_status.accl1c_3), 0x100, "Shutter Open",
shutter_open
     "Shutter Not Open");
     tt_mag_off = lspmac_bi_init( &(lspmac_bis
[16]), &(md2_status.acc11c_5), 0x01, "Smart Magnet Off",
smart_mag_off
     "Smart Magnet Not Off");
^{\prime\prime} // Initialize several commands that get called, perhaps, alot
rr_cmd.RequestType = VR_UPLOAD;
rr_cmd.Request = VR_PMAC_READREADY;
rr_cmd.wValue = 0;
```

```
= 0;
= htons(2);
rr_cmd.wIndex
rr_cmd.wLength
memset( rr_cmd.bData, 0, sizeof(rr_cmd.bData));
gb_cmd.RequestType = VR_UPLOAD;
gb_cmd.Requestrype = VR_DFLOAD;
gb_cmd.Request = VR_PMAC_GETBUFFER;
gb_cmd.wValue = 0;
gb_cmd.wIndex = 0;
gb_cmd.wLength = htons(1400);
memset( gb_cmd.bData, 0, sizeof(gb_cmd.bData));
cr_cmd.RequestType = VR_UPLOAD;
cr_cmd.wValue
                   = 0;
= htons(1400);
cr_cmd.wIndex
cr_cmd.wLength
memset( cr_cmd.bData, 0, sizeof(cr_cmd.bData));
// Initialize some mutexs and conditions
pthread_mutex_init( &pmac_queue_mutex, &mutex_initializer);
pthread_cond_init( &pmac_queue_cond, NULL);
lspmac_shutter_state = 0;
      assume the shutter is now closed: not a big deal if we are wrong
pthread_mutex_init( &lspmac_shutter_mutex, &
    mutex_initializer);
pthread_cond_init( &lspmac_shutter_cond, NULL);
pmacfd.fd = -1;
pthread_mutex_init( &lspmac_moving_mutex, &
    mutex_initializer);
pthread_cond_init( &lspmac_moving_cond, NULL);
pthread_mutex_init( &lspmac_ascii_mutex, &mutex_initializer
pthread_mutex_init( &lspmac_ascii_buffers_mutex, &
    mutex_initializer);
// clear the ascii communications buffers
  uint32_t cc;
  cc = 0;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
  , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
lspmac_SockSendDPline( NULL, "I5=0");
lspmac_SockSendDPline( NULL, "ENABLE PLCC 0,2");
lspmac_SockSendDPline( NULL, "DISABLE PLCC 1");
lspmac_SockSendDPline( NULL, "I5=3");
```

 $7.6.4.38 \quad \text{int } lspmac_jogabs_queue \left(\ lspmac_motor_t * \textit{mp, } double \textit{ } \textit{requested_position } \right)$

Use jog to move motor to requested position.

Parameters

in	тр	The motor to move
in	requested	Where to move it
	position	

Definition at line 2871 of file Ispmac.c.

```
return lspmac_move_or_jog_abs_queue( mp,
```

```
requested_position, 1);
}
```

7.6.4.39 void lspmac_light_zoom_cb (char * event)

Set the backlight intensity whenever the zoom is changed (and the backlight is up)

Parameters

```
event Name of the event that calledus
```

Definition at line 3328 of file Ispmac.c.

7.6.4.40 double $lspmac_lut$ (int nlut, double *lut, double x)

Look up table support for motor positions (think x=zoom, y=light intensity) use a lookup table to find the "counts" to move the motor to the requested position The look up table is a simple one dimensional array with the x values as even indicies and the y values as odd indices.

Returns: y value

Parameters

in	nlut	number of entries in lookup table
in	lut	The lookup table: even indicies are the x values, odd are the y's
in	X	The x value we are looking up.

Definition at line 378 of file Ispmac.c.

```
{
int i, foundone;
double m;
double y1, y2, x1, x2, y;

foundone = 0;
if( lut != NULL && nlut > 1) {
   for( i=0; i < 2*nlut; i += 2) {
      x1 = lut[i];
      y1 = lut[i+1];
      if( i < 2*nlut - 2) {
      x2 = lut[i+2];
      y2 = lut[i+3];
   }

//
// First one too big? Use the y value of the first element
//
   if( i == 0 && x1 > x) {
      y = y1;
}
```

```
foundone = 1;
    break;
}

//

// Look for equality
//

if( x1 == x) {
    y = y1;
    foundone = 1;
    break;
}

//

// Maybe interpolate
//

if( (i < 2*nlut-2) && x < x2) {
    m = (y2 - y1) / (x2 - x1);
    y = m*(x - x1) + y1;
    foundone = 1;
    break;
}

if( foundone == 0) {
    // must be bigger than the last entry
    //
    y = lut[2*(nlut-1) + 1];
}
return y;
}
return 0.0;</pre>
```

7.6.4.41 void lspmac_more_ascii_cb (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

we are expecting more characters from the DPRAM ASCII interface

Definition at line 1821 of file Ispmac.c.

```
lspmac_get_ascii( cmd->event);
}
```

7.6.4.42 Ispmac_motor_t* Ispmac_motor_init (Ispmac_motor_t * d, int wy, int wx, int * posp, int * stat1p, int * stat2p, char * wtitle, char * name, int(*)(Ispmac_motor_t *, double) moveAbs)

Initialize a pmac stepper or servo motor.

Parameters

in,out	d	An uninitialize motor object
in	wy	Curses status window row index
in	WX	Curses status window column index
in	posp	Pointer to position status
in	stat1p	Pointer to 1st status word
in	stat2p	Pointer to 2nd status word
in	wtitle	Title for this motor (to display)
in	name	This motor's name
in	moveAbs	Method to use to move this motor

Definition at line 3005 of file Ispmac.c.

7.6.4.43 int lspmac_move_or_jog_abs_queue (lspmac_motor_t * mp, double requested_position, int use_jog)

Move method for normal stepper and servo motor objects Returns non-zero on abort, zero if OK.

- < format string for coordinate system move
- < coordinate system bit
- < the requested position in units of "counts"
- < motor and coordinate system;
- < our axis

Parameters

in	тр	The motor to move
in	requested	Where to move it
	position	
in	use_jog	1 to force jog, 0 for motion prog

Definition at line 2664 of file Ispmac.c.

```
char *fmt;
int q100;
int requested_pos_cnts;
int coord_num, motor_num;
char *axis;
double u2c;
double neutral_pos;
double min pos, max pos;
int pos_limit_hit, neg_limit_hit;
struct timespec timeout, now;
int err;
pthread_mutex_lock( & (mp->mutex));
                = lsredis_getd( mp->u2c);
motor_num = lsredis_get1( mp->motor_num);
coord_num = lsredis_get1( mp->coord_num);
               = lsredis_getstr( mp->axis);
axis
axis = Isredis_getstr( mp>axis);
neutral_pos = lsredis_getd( mp>neutral_pos);
min_pos = lsredis_getd( mp>min_pos);
max_pos = lsredis_getd( mp>max_pos);
pos_limit_hit = lsredis_getd( mp>pos_limit_hit);
neg_limit_hit = lsredis_getd( mp>neg_limit_hit);
if( u2c == 0.0 || requested_position < min_pos || requested_position >
     max_pos) {
   // Shouldn't try moving a motor that's in trouble
  lsevents_send_event( "%s Move Aborted", mp->name);
if( (neg_limit_hit && (requested_position < mp->position)) || (pos_limit_hit
     && (requested_position > mp->position))) {
   pthread_mutex_unlock( & (mp->mutex));
```

```
lslogging_log_message( "lspmac_move_or_jog_abs_queue:
     %s Moving wrong way on limit: requested position=%f current position=%f low
     limit=%d high limit=%d",
                         mp->name, requested_position, mp->position
  , neg_limit_hit, pos_limit_hit);
lsevents_send_event( "%s Move Aborted", mp->name);
 return 2;
mp->requested_position = requested_position;
mp->not_done = 1;
mp->motion_seen = 0;
mp->command_sent = 0;
mp->requested_pos_cnts = u2c * (requested_position +
   neutral_pos);
requested_pos_cnts = mp->requested_pos_cnts;
if( use_jog || axis == NULL || *axis == 0) {
 use_jog = 1;
} else {
 use_jog = 0;
 q100 = 1 << (coord_num -1);
pthread_mutex_unlock( &(mp->mutex));
if(!use_jog) {
  // Make sure the coordinate system is not moving something, wait if it is
  pthread_mutex_lock( &lspmac_moving_mutex);
  clock_gettime( CLOCK_REALTIME, &now);
  // TODO: Have all moves estimate how long they'll take and use that here
  timeout.tv_sec = now.tv_sec + 60.0;
                                                      // a long timeout, but
     we might really be moving something that takes this long (or longer)
  timeout.tv_nsec = now.tv_nsec;
  err = 0:
  while( err == 0 && (lspmac_moving_flags & q100) != 0)
   err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
  pthread_mutex_unlock( &lspmac_moving_mutex);
  if( err == ETIMEDOUT) {
    lslogging_log_message( "
    lspmac_move_or_jog_abs_queue: Done. lspmac_moving_flags = %0x", lspmac_moving_flags);
lsevents_send_event( "%s Move Aborted", mp->name);
    return 1;
  // Set the "we are moving this coordinate system" flag
  lspmac_SockSendDPline( NULL, "M5075=(M5075 | %d)",
    q100);
  switch( *axis) {
  case 'A':
   fmt = "&%d Q16=%d Q100=%d B146R";
  case 'B':
  fmt = "&%d Q17=%d Q100=%d B147R";
    break:
  case 'C':
    fmt = "&%d Q18=%d Q100=%d B148R";
  break;
case 'X':
   fmt = "&%d Q10=%d Q100=%d B140R";
  case 'Y':
   fmt = "&%d Q11=%d Q100=%d B141R";
    break:
  case 'Z':
  fmt = "&%d Q12=%d Q100=%d B142R";
    break;
  case 'U':
    fmt = "&%d Q13=%d Q100=%d B143R";
```

```
break;
  case 'V':
    fmt = "&%d Q14=%d Q100=%d B144R";
    break;
  case 'W':
  fmt = "&%d Q15=%d Q100=%d B145R";
  // Make sure the flag has been seen
  clock_gettime( CLOCK_REALTIME, &now);
timeout.tv_sec = now.tv_sec + 4.0;
                                                      // also a long timeout.
  This should really only take a few milliseconds on a slow day timeout.tv_nsec = now.tv_nsec;
  pthread_mutex_lock( &lspmac_moving_mutex);
  err = 0:
  while( err == 0 && (lspmac_moving_flags & q100) == 0)
   err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
  pthread_mutex_unlock( &lspmac_moving_mutex);
  if( err == ETIMEDOUT) {
    lslogging_log_message( "
    lspmac_move_or_jog_abs_queue: Did not see flag propagate. Move aborted. lspmac_moving_flags = %0x",
    lspmac_moving_flags);
    lsevents_send_event( "%s Move Aborted", mp->name);
  }
pthread_mutex_lock( &(mp->mutex));
if( use_jog) {
  lspmac_SockSendDPline( mp->name, "#%d j=%d",
    motor_num, requested_pos_cnts);
} else {
  lspmac_SockSendDPline( mp->name, fmt, coord_num,
    requested_pos_cnts, q100);
pthread_mutex_unlock( &(mp->mutex));
free ( axis);
return 0:
```

7.6.4.44 int lspmac_move_or_jog_preset_queue (lspmac_motor_t * mp, char * preset, int use_jog)

move using a preset value returns 0 on success, non-zero on error

Parameters

in	тр	Our motor
in	preset	the name of the preset
	use_jog	[in[1 to force jog, 0 to try motion prog

Definition at line 2833 of file Ispmac.c.

```
double pos;
int err;
int rtn;
if( preset == NULL || *preset == 0) {
   lsevents_send_event( "%s Move Aborted", mp->name);
   return 0;
}
err = lsredis_find_preset( mp->name, preset, &pos);
if( err != 0)
   rtn = lspmac_move_or_jog_abs_queue( mp, pos,
```

```
use_jog);
else {
  lsevents_send_event( "%s Move Aborted", mp->name);
  rtn = 1;
}
return rtn;
}
```

7.6.4.45 int lspmac_move_preset_queue (lspmac_motor_t * mp, char * preset_name)

Move a given motor to one of its preset positions.

No movement if the preset is not found.

Parameters

тр	Ispmac motor pointer	
preset_name Name of the preset to use		

Definition at line 2351 of file Ispmac.c.

```
double pos;
int err;

lslogging_log_message( "lspmac_move_preset_queue: Called
    with motor %s and preset named '%s'", mp->name, preset_name);

err = lsredis_find_preset( mp->name, preset_name, &pos
    );
if( err == 0)
    return 1;

err = mp->moveAbs( mp, pos);
if( !err)
    lslogging_log_message( "lspmac_move_preset_queue:
        moving %s to preset '%s' (%f)", mp->name, preset_name, pos);
//
// the abort event should have been sent in moveAbs
//
return err;
```

7.6.4.46 int lspmac_moveabs_blight_factor_queue (lspmac motor t * mp, double pos)

Definition at line 2544 of file Ispmac.c.

```
{
char *fmt;
if( pos >= 60 && pos <= 140) {</pre>
  pthread_mutex_lock( &(mp->mutex));
  *mp->actual_pos_cnts_p = pos;
  mp->position =
                           pos;
  pthread_mutex_unlock( & (mp->mutex));
  pthread_mutex_lock( &(blight->mutex));
  fmt = lsredis_getstr( blight->redis_fmt);
  lsredis_setstr( blight->u2c, fmt, pos / 100.0);
  free (fmt);
  pthread_mutex_unlock( & (blight->mutex));
  blight->moveAbs( blight, lspmac_getPosition
    ( zoom));
return 0;
```

7.6.4.47 int lspmac_moveabs_bo_queue (lspmac_motor_t * mp, double requested_position)

Move method for binary i/o motor objects.

Parameters

in	тр	A binary i/o motor object
in	requested	a 1 or a 0 request to move
	position	

Definition at line 2425 of file Ispmac.c.

```
pthread_mutex_lock( &(mp->mutex));
mp->requested_position = requested_position == 0.0 ? 0.0 :
    1.0;
mp->requested_pos_cnts = requested_position == 0.0 ? 0 : 1;
mp->not_done = 1;
mp->motion_seen = 0;
lspmac_SockSendDPline( mp->name, mp->write_fmt
    , mp->requested_pos_cnts);

pthread_mutex_unlock( &(mp->mutex));
return 0;
```

7.6.4.48 int lspmac_moveabs_flight_factor_queue (lspmac_motor_t * mp, double pos)

Definition at line 2521 of file Ispmac.c.

7.6.4.49 int lspmac_moveabs_frontlight_oo_queue (lspmac_motor_t * mp, double pos)

"move" frontlight on/off

Definition at line 2508 of file Ispmac.c.

```
pthread_mutex_lock( & (mp->mutex));
*mp->actual_pos_cnts_p = pos;
mp->position = pos;
pthread_mutex_unlock( & (mp->mutex));
if( pos == 0.0) {
  flight->moveAbs( flight, 0.0);
```

```
} else {
  flight->moveAbs( flight, lspmac_getPosition
       ( zoom));
}
return 0;
```

7.6.4.50 int lspmac_moveabs_fshut_queue (lspmac_motor_t * mp, double requested_position)

Move method for the fast shutter.

Slightly more complicated than a binary io as some flags need to be set up.

Parameters

тр	The fast shutter motor instance
requested	1 (open) or 0 (close), really
position	

Definition at line 2395 of file Ispmac.c.

```
pthread_mutex_lock( & (mp->mutex));

mp->requested_position = requested_position;
mp->not_done = 1;
mp->motion_seen = 0;
mp->requested_pos_cnts = requested_position;
if( requested_position != 0) {
    //
    // ScanEnable=0, ManualEnable=1, ManualOn=1
    //
    lspmac_SockSendDPline( mp->name, "M1124=0 M1125=1
        M1126=1");
} else {
    //
    // ManualOn=0, ManualEnable=0, ScanEnable=0
    //
    lspmac_SockSendDPline( mp->name, "M1126=0 M1125=0
        M1124=0");
}
pthread_mutex_unlock( & (mp->mutex));
return 0;
```

7.6.4.51 int lspmac_moveabs_queue (lspmac_motor_t * mp, double requested_position)

Use coordinate system motion program, if available, to move motor to requested position.

Parameters

in	тр	The motor to move
in	requested	Where to move it
	position	

Definition at line 2861 of file Ispmac.c.

```
return lspmac_move_or_jog_abs_queue( mp,
    requested_position, 0);
```

7.6.4.52 void lspmac_moveabs_timed_queue (Ispmac_motor_t * mp, double start, double delta, double time)

timed motor move

Parameters

тр	Our motor object	
start	rt Beginning of motion	
delta	Ta Distance to move	
time	to move it in (secs)	

< Flags needed for wait routine

Definition at line 2451 of file Ispmac.c.

```
LS-CAT Timed X move
// 240
                 Q10
                          = Starting X value (cnts)
                 Q11
                         = Delta X value (cnts)
                 Q12
                         = Time to run between the two points (mSec)
                          = Acceleration time (msecs)
                 013
                        = 1 << (coord sys no - 1)
                 0100
               // Starting value (counts)
// Delta (counts)
// Time to run (msecs)
// Acceleration time (msecs)
// 1 << (coord sys no - 1)</pre>
int q10;
int q11;
int q12;
int q13;
int q100;
int coord_num; // our coordinate number
double u2c;
double neutral_pos;
double max_accel;
pthread_mutex_lock( &(mp->mutex));
              = lsredis_getd( mp->u2c);
if( u2c == 0.0 || time <= 0.0 || max_accel <= 0.0) {</pre>
  // Shouldn't try moving a motor that has bad motion parameters
  pthread_mutex_unlock( &(mp->mutex));
  return;
mp->not_done
mp->motion_seen = 0;
mp->requested_position = start + delta;
mp->requested_pos_cnts = u2c * (mp->requested_position
      + neutral_pos);
q10 = mp->requested_pos_cnts;
q11 = u2c * delta;
q12 = 1000 * time;
q13 = q11 / q12 / max_accel;
q100 = 1 << (coord_num - 1);
pthread_mutex_unlock( & (mp->mutex));
pthread_mutex_lock( & (mp->mutex));
lspmac_SockSendDPline( mp->name, "&%d Q10=%d Q11=%d
        Q12=%d Q13=%d Q100=%d B240R", coord_num, q10, q11, q12, q13, q100);
pthread_mutex_unlock( &(mp->mutex));
```

7.6.4.53 int lspmac_moveabs_wait (lspmac_motor_t * mp, double timeout_secs)

Wait for motor to finish moving.

Assume motion already queued, now just wait

Parameters

тр	The motor object to wait for	
timeout_secs		

Definition at line 2886 of file Ispmac.c.

```
struct timespec timeout, now;
 double isecs, fsecs;
 int err;
// % \left( \frac{1}{2}\right) =\frac{1}{2}\left( \frac{1}{2}\right) =\frac{1}{2}\left(
 clock_gettime( CLOCK_REALTIME, &now);
 fsecs = modf( timeout_secs, &isecs);
 timeout.tv_sec = now.tv_sec + (long)floor( isecs);
timeout.tv_nsec = now.tv_nsec + (long)floor( fsecs * 1.0e9);
 timeout.tv_sec += timeout.tv_nsec / 1000000000;
timeout.tv_nsec %= 1000000000;
err = 0:
pthread_mutex_lock( & (mp->mutex));
 while( err == 0 && mp->command_sent == 0)
     err = pthread_cond_timedwait( &mp->cond, &mp->mutex, &timeout);
 pthread_mutex_unlock( & (mp->mutex));
 if( err != 0) {
      if ( err != ETIMEDOUT) {
           lslogging_log_message( "lspmac_moveabs_wait:
               unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
            timeout.tv_nsec);
      return 1;
 \ensuremath{//} wait for the motion to have started
 // This will time out if the motion ends before we can read the status back
 \ensuremath{//} hence the added complication of time stamp of the sent packet.
 err = 0;
pthread_mutex_lock( &(mp->mutex));
 while( err == 0 && mp->motion_seen == 0)
      \verb|err = pthread_cond_timedwait( & (mp->cond), & (mp->mutex), & timeout)|\\
 if ( err != 0) {
     if( err != ETIMEDOUT) {
            lslogging_log_message( "lspmac_moveabs_wait:
              unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
            timeout.tv_nsec);
      pthread_mutex_unlock( &(mp->mutex));
      return 1;
 // wait for the motion that we know has started to finish
err = 0;
 while( err == 0 && mp->not_done)
    err = pthread_cond_timedwait( &(mp->cond), &(mp->mutex), &timeout)
 if( err != 0) {
      if( err != ETIMEDOUT) {
            lslogging_log_message( "lspmac_moveabs_wait:
              unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
            timeout.tv_nsec);
     pthread_mutex_unlock( & (mp->mutex));
      return 1;
 // if return code was not 0 then we know we shouldn't wait for not_done flag.
 // In this case the motion ended before we read the status registers
pthread_mutex_unlock( &(mp->mutex));
```

```
return 0;
```

7.6.4.54 int lspmac_movedac_queue (lspmac_motor_t * mp, double requested_position)

Move method for dac motor objects (ie, lights)

Parameters

ir	n	тр	Our motor
ir	n	requested	Desired x postion (look up and send y position)
		position	

Definition at line 2285 of file Ispmac.c.

```
double u2c;
pthread_mutex_lock( &(mp->mutex));
u2c = lsredis_getd( mp->u2c);
mp->requested_position = requested_position;
if( mp->nlut > 0 && mp->lut != NULL) {
 // // u2c scales the lookup table value
 mp->requested_pos_cnts = u2c * lspmac_lut( mp->
   nlut, mp->lut, requested_position);
 , mp->requested_pos_cnts, u2c);
 mp->not_done
 mp->motion_seen = 0;
 lspmac_SockSendDPline( mp->name, "%s=%d", mp->
   dac_mvar, mp->requested_pos_cnts);
pthread_mutex_unlock( &(mp->mutex));
return 0;
```

7.6.4.55 int lspmac_movezoom_queue (lspmac_motor_t * mp, double requested_position)

Move method for the zoom motor.

Parameters

in	тр	the zoom motor
in	requested	our desired zoom
	position	

Definition at line 2318 of file Ispmac.c.

```
{
double y;
int motor_num;

pthread_mutex_lock( &(mp->mutex));

motor_num = lsredis_getl( mp->motor_num);

mp->requested_position = requested_position;

if( mp->nlut > 0 && mp->lut != NULL) {
```

```
y = lspmac_lut( mp->nlut, mp->lut, requested_position);
mp->requested_pos_cnts = (int)y;
mp->not_done = 1;
mp->motion_seen = 0;

lspmac_SockSendDPline( mp->name, "#%d j=%d",
    motor_num, mp->requested_pos_cnts);
}
pthread_mutex_unlock( &(mp->mutex));
return 0;
```

7.6.4.56 void lspmac_next_state ()

State machine logic.

Given the current state, generate the next one

Definition at line 2116 of file Ispmac.c.

```
// Connect to the pmac and perhaps initialize it. // OK, this is slightly more than just the state
// machine logic...
if( ls_pmac_state == LS_PMAC_STATE_DETACHED
  ) {
//
  // TODO (eventually)
  // This ip address wont change in a single PMAC installation // We'll need to audit the code if we decide to implement
  // multiple PMACs so might as well wait til then.
  lsConnect( "192.6.94.5");
  // If the connect was successful we can proceed with the initialization
  if( ls_pmac_state != LS_PMAC_STATE_DETACHED
    lspmac_SockFlush();
    // Harvest the I and M variables in case we need them
     // one day.
    if( getmvars) {
  lspmac_GetAllMVars();
  getmvars = 0;
     if( getivars) {
       lspmac_GetAllIVars();
       getivars = 0;
    }
  }
}
// Check the command queue and perhaps go to the "Send Command" state.
if( ls_pmac_state == LS_PMAC_STATE_IDLE) {
  int goodtogo;
  goodtogo = 0;
  pthread_mutex_lock( &lspmac_ascii_mutex);
  if( lspmac_ascii_busy==0 && lspmac_dpascii_on
  != lspmac_dpascii_off)
  goodtogo = 1;
  pthread_mutex_unlock( &lspmac_ascii_mutex);
  if ( goodtogo)
    lspmac_SockSendDPqueue();
if( ls_pmac_state == LS_PMAC_STATE_IDLE &&
    ethCmdOn != ethCmdOff)
  ls_pmac_state = LS_PMAC_STATE_SC;
```

```
//
// Set the events flag
// to tell poll what we are waiting for.
...
switch( ls_pmac_state) {
case LS_PMAC_STATE_DETACHED:
  // there shouldn't be a valid fd, so ignore the events
  11
  pmacfd.events = 0;
  break;
case LS_PMAC_STATE_IDLE:
  if( ethCmdOn == ethCmdOff) {
   //
     // Anytime we are idle we want to // get the status of the PMAC
     lspmac_get_status();
// These states require that we listen for packets
case LS_PMAC_STATE_WACK_NFR:
case LS_PMAC_STATE_WACK:
case LS_PMAC_STATE_WACK_CC:
case LS_PMAC_STATE_WACK_RR:
case LS_PMAC_STATE_WCR:
case LS_PMAC_STATE_WGB:
case LS_PMAC_STATE_GMR:
  pmacfd.events = POLLIN;
  break;
,, ^{\prime\prime} // These states require that we send packets out. ^{\prime\prime}
case LS_PMAC_STATE_SC:
case LS_PMAC_STATE_CR:
case LS_PMAC_STATE_RR:
case LS_PMAC_STATE_GB:
  //
// Sad fact: PMAC will fail to process commands if we send them too
  quickly.

// We deal with that by waiting a tad before we let poll tell us the PMAC
      socket is ready to write.
  gettimeofday( &now, NULL);
  if( ((now.tv_sec * 1000000. + now.tv_usec) - (pmac_time_sent.tv_sec
 * 1000000. + pmac_time_sent.tv_usec)) < PMAC_MIN_CMD_TIME) {</pre>
    pmacfd.events = 0;
  } else {
    pmacfd.events = POLLOUT;
  break;
}
```

7.6.4.57 void lspmac_pmacmotor_read (lspmac_motor_t * mp)

Read the position and status of a normal PMAC motor.

Parameters

in	тр	Our motor
----	----	-----------

Definition at line 1350 of file Ispmac.c.

```
char s[512], *sp;
int homing1, homing2;
double u2c;
double neutral_pos;
int motor_num;
```

```
char *fmt;
int status_changed;
pthread_mutex_lock( & (mp->mutex));
// if this time and last time were both "in position"
// and the position changed significantly then log the event
// On E omega has been observed to change by 0x10000 on its own
// with no real motion.
if( mp->status2 & 1 && mp->status2 == *mp->status2_p
    && abs( mp->actual_pos_cnts - *mp->actual_pos_cnts_p
    ) > 256) {
    lslogging_log_message( "Instantaneous change: %s old status1: %0x, new status1: %0x, old status2: %0x, new status2: %0x, old cnts: %0x, new cnts:
                          mp->name, mp->status1, *mp->status1_p, mp->status2,
     *mp->status2_p, mp->actual_pos_cnts, *mp->actual_pos_cnts_p);
  // At this point we'll just log the event and return
  // There is no reason to believe the change is real.
  // There is a non-zero probability that the first value is the bad one and
     any value afterwards will be taken as
  \ensuremath{^{\prime\prime}} wrong. Homing (or moving) the motor should fix this. There is a
     non-zero probably that it can happen
  // two or more times in a row after moving.
  // TODO: account for the case where mp->actual_pos_cnts is the bad value.
  // TODO: Is this a problem when the motor is moving? Can we detect it?
  // TODO: Think of the correct change value here (currently 256) that works
     for all motors
  // or have this value configurable
  pthread_mutex_unlock( &(mp->mutex));
  return;
// Send an event if inPosition has changed
if( (mp->status2 & 0x000001) != (*mp->status2_p & 0x000001))
  lsevents_send_event( "%s %s", mp->name, (*mp->
    status2_p & 0x000001) ? "In Position" : "Moving");
// Get some values we might need later
u2c
            = lsredis getd( mp->u2c);
motor_num = lsredis_get1( mp->motor_num);
neutral_pos = lsredis_getd( mp->neutral_pos);
// maybe look for omega zero crossing
if( motor_num == 1 && omega_zero_search && *mp->
    actual_pos_cnts_p >=0 && mp->actual_pos_cnts <</pre>
    0) {
  int secs, nsecs;
  if( omega_zero_velocity > 0.0) {
    secs = *mp->actual_pos_cnts_p / omega_zero_velocity
    nsecs = (*mp->actual_pos_cnts_p / omega_zero_velocity
     - secs) * 1000000000;
    omega_zero_time.tv_sec = lspmac_status_time
    .tv_sec - secs;
    omega_zero_time.tv_nsec= lspmac_status_time
    if( omega_zero_time.tv_nsec < nsecs) {</pre>
      omega_zero_time.tv_sec -= 1;
omega_zero_time.tv_nsec += 1000000000;
    omega_zero_time.tv_nsec -= nsecs;
    lsevents_send_event( "omega crossed zero");
    {\tt lslogging\_log\_message("lspmac\_pmacmotor\_read: omega}
     zero secs %d nsecs %d ozt.tv_sec %ld ozt.tv_nsec %ld, motor cnts %d",
```

```
secs, nsecs, omega_zero_time.tv_sec,
     omega_zero_time.tv_nsec, *mp->actual_pos_cnts_p
    );
  }
  omega_zero_search = 0;
// Make local copies so we can inspect them in other threads
// without having to grab the status mutex
if( mp->status1 != *mp->status1_p || mp->status2 != *
   mp->status2_p) {
 mp > status1_p;
mp -> status1 = *mp -> status1_p;
mp -> status2 = *mp -> status2_p;
  status_changed = 1;
} else {
  status_changed = 0;
mp->actual_pos_cnts = *mp->actual_pos_cnts_p;
// See if we are done moving, ie, in position
11
if( mp->status2 & 0x000001) {
  if( mp->not_done) {
    mp->not_done = 0;
   pthread_cond_signal( &(mp->cond));
} else if( mp->not_done == 0) {
 mp->not\_done = 1;
// See if the motor is moving
//
                  move timer
                                                homing
                    123456
                                                123456
if( mp->status1 & 0x020000 || mp->status1 & 0x000400) {
  if( mp->motion_seen == 0) {
    mp->motion_seen = 1;
   pthread_cond_signal( &(mp->cond));
 }
mvwprintw( mp->win, 2, 1, "%*d cts", LS_DISPLAY_WINDOW_WIDTH
-6, mp->actual_pos_cnts);
mvwprintw( mp->win, 3, 1, "%*s", LS_DISPLAY_WINDOW_WIDTH
-2, " ");
if( mp->nlut >0 && mp->lut != NULL) {
   mp->position = lspmac_rlut( mp->nlut, mp->lut, mp
    ->actual_pos_cnts);
} else {
  if( u2c != 0.0) {
   mp->position = ((mp->actual_pos_cnts / u2c) -
    neutral_pos);
  } else {
   mp->position = mp->actual_pos_cnts;
  }
if( status_changed || fabs(mp->reported_position - mp->
    position) >= lsredis_getd(mp->update_resolution
  )) {
fmt = lsredis_getstr(mp->redis_fmt);
  lsredis_setstr( mp->redis_position, fmt, mp->
    position);
  free(fmt);
 mp->reported_position = mp->position;
fmt = lsredis_getstr( mp->printf_fmt);
snprintf( s, sizeof(s)-1, fmt, 8, mp->position);
s[sizeof(s)-1] = 0;
free ( fmt);
// indicate limit problems
lsredis_setstr( mp->pos_limit_hit, mp->status1
   & 0x200000 ? "1" : "0");
```

```
// set flag if we are not homed
homing1 = 0;
                           ~(homed flag)
if ( mp \rightarrow homing == 0 && (\sim mp \rightarrow status2 & 0x000400) != 0) {
 homing1 = 1;
// set flag if we are homing and in open loop
homing2 = 0;
homing2 = 1;
// maybe reset homing flag
// homed flag in positif (mp->homing == 2) && ((mp->status2 & 0x000400) != 0) && ((mp->status2 & 0x000001) != 0)) {
                                                                in position flag
  mp \rightarrow homing = 0;
  lsevents_send_event( "%s Homed", mp->name);
s[sizeof(s)-1] = 0;
mvwprintw( mp->win, 3, 1, "%*s", LS_DISPLAY_WINDOW_WIDTH
    -6, s);
if( status_changed) {
 mvwprintw( mp->win, 4, 1, "%*x", LS_DISPLAY_WINDOW_WIDTH
   -2, mp->status1);
  mvwprintw(mp->win, 5, 1, "%*x", LS_DISPLAY_WINDOW_WIDTH
   -2, mp->status2);
  sp = "";
  if ( mp->status2 & 0x000002)
    sp = "Following Warning"
  else if( mp->status2 & 0x000004)
  sp = "Following Error";
  else if( mp->status2 & 0x000020)
sp = "I2T Amp Fault";
  else if( mp->status2 & 0x000008)
  sp = "Amp. Fault";
else if( mp->status2 & 0x000800)
sp = "Stopped on Limit";
  else if( mp->status1 & 0x040000)
   sp = "Open Loop";
  else if( ~(mp->status1) & 0x080000)
    sp = "Motor Disabled";
  else if( mp->status1 & 0x000400)
   sp = "Homing";
  else if( (mp->status1 & 0x600000) == 0x600000)
   sp = "Both Limits Tripped";
  else if( mp->status1 & 0x200000)
   sp = "Positive Limit";
  else if( mp->status1 & 0x400000)
   sp = "Negative Limit";
  else if( ~(mp->status2) & 0x000400)
   sp = "Not Homed";
  else if( mp->status1 & 0x020000)
    sp = "Moving";
  else if( mp->status2 & 0x000001)
sp = "In Position";
 mvwprintw(mp->win, 6, 1, "%*s", LS_DISPLAY_WINDOW_WIDTH
  lsredis_setstr( mp->status_str, sp);
wnoutrefresh( mp->win);
pthread_mutex_unlock( & (mp->mutex));
if( homing1)
  lspmac_home1_queue( mp);
if ( homing2)
 lspmac_home2_queue( mp);
lspmac_status_last_time.tv_sec = lspmac_status_time
   .tv_sec;
lspmac_status_last_time.tv_nsec = lspmac_status_time
.tv_nsec;
```

```
7.6.4.58 pmac_cmd_queue_t* lspmac_pop_queue ( )
```

Remove the oldest queue item.

Used to send command to PMAC. Note that there is a separate reply index to ensure we've know to what command a reply is refering. Returns the item.

Definition at line 652 of file Ispmac.c.

```
pmac_cmd_queue_t *rtn;

pthread_mutex_lock( &pmac_queue_mutex);

if( ethCmdOn == ethCmdOff)
   rtn = NULL;
else {
   rtn = &(ethCmdQueue[(ethCmdOff++) %
        PMAC_CMD_QUEUE_LENGTH]);
   clock_gettime( CLOCK_REALTIME, &(rtn->time_sent));
}
pthread_mutex_unlock( &pmac_queue_mutex);
return rtn;
```

7.6.4.59 pmac_cmd_queue_t* lspmac_pop_reply ()

Remove the next command queue item that is waiting for a reply.

We always need a reply to know we are done with a given command. Returns the item.

Definition at line 672 of file Ispmac.c.

```
pmac_cmd_queue_t *rtn;

pthread_mutex_lock( &pmac_queue_mutex);

if( ethCmdOn == ethCmdReply)
   rtn = NULL;
else
   rtn = &(ethCmdQueue[(ethCmdReply++) %
        PMAC_CMD_QUEUE_LENGTH]);

pthread_mutex_unlock( &pmac_queue_mutex);
return rtn;
```

7.6.4.60 pmac_cmd_queue_t* lspmac_push_queue (pmac_cmd_queue_t * cmd)

Put a new command on the queue.

Pointer is returned so caller can evaluate the time command was actually sent.

Parameters

```
cmd | Command to send to the PMAC
```

Definition at line 628 of file Ispmac.c.

```
pthread_mutex_unlock( &pmac_queue_mutex);
return rtn;
}
```

7.6.4.61 void Ispmac_Reset ()

Clear the queue and put the PMAC into a known state.

Definition at line 751 of file Ispmac.c.

```
{
ls_pmac_state = LS_PMAC_STATE_IDLE;

// clear queue
ethCmdReply = ethCmdOn;
ethCmdOff = ethCmdOn;
lspmac_SockFlush();
```

7.6.4.62 void Ispmac_reset_queue ()

Clear the queue as part of PMAC reinitialization.

Definition at line 615 of file Ispmac.c.

```
pthread_mutex_lock( &pmac_queue_mutex);
ethCmdOn = 0;
ethCmdOff = 0;
ethCmdReply = 0;
pthread_mutex_unlock( &pmac_queue_mutex);
}
```

7.6.4.63 double lspmac_rlut (int *nlut*, double * *lut*, double y)

Parameters

in	nlut	number of entries in lookup table
in	lut	our lookup table
in	у	the y value for which we need an x

Definition at line 436 of file Ispmac.c.

```
int i, foundone, up;
double m;
double y1, y2, x1, x2, x;

foundone = 0;
if( lut != NULL && nlut > 1) {

    //
    // are the table values going up or down?
    //
    if( lut[1] < lut[2*nlut-1])
        up = 1;
    else
        up = 0;

    //
    // Linear search
    //
    for( i=0; i < 2*nlut; i += 2) {
        x1 = lut[i];
        y1 = lut[i+1];
        if( i < 2*nlut - 2) {
            x2 = lut[i+2];
        }
</pre>
```

```
y2 = lut[i+3];
     // see if y is before the beginning of the table
     if ( i==0 && ( up ? y1 > y : y1 < y)) {
      x = x1;
       foundone = 1;
       break;
     // Did we, perhaps, nail it?
     if ( y1 == y) {
       x = x1;
       foundone = 1;
       break;
    // Interpolate between the two values (if we've not bumped our heads on
      the end of the table)
    if( (i < 2*nlut-2) && (up ? y < y2 : y > y2)) {
    m = (x2 - x1) / (y2 - y1);
    x = m * (y - y1) + x1;
    foundone = 1;
      break;
  }
  // y is off the charts: just use the last value
  if (foundone == 0) {
  . _candone == 0 ) {
x = lut[2*(nlut-1)];
}
  return x;
return 0.0;
```

7.6.4.64 void lspmac_run ()

Start up the Ispmac thread.

Definition at line 3511 of file Ispmac.c.

```
char **inits;
lspmac_motor_t *mp;
char evts[64];
int i;
int active;
pthread_create( &pmac_thread, NULL, lspmac_worker,
    NULL);
lsevents_add_listener( "CryoSwitchChanged",
lspmac_cryoSwitchChanged_cb);
lsevents_add_listener( "scint In Position",
    lspmac_scint_inPosition_cb);
lsevents_add_listener( "scintDried",
    lspmac_scint_dried_cb);
lsevents_add_listener( "backLight 1",
lspmac_backLight_up_cb);
lsevents_add_listener( "backLight 0",
    lspmac_backLight_down_cb);
lsevents_add_listener( "cam.zoom In Position",
    lspmac_light_zoom_cb);
for( i=0; i<lspmac_nmotors; i++) {
   snprintf( evts, sizeof( evts)-1, "%s command accepted", lspmac_motors</pre>
    [i].name);
  evts[sizeof(evts)-1] = 0;
  lsevents_add_listener( evts, lspmac_command_done_cb
    );
lspmac_zoom_lut_setup();
lspmac_flight_lut_setup();
```

```
lspmac_blight_lut_setup();
lspmac_fscint_lut_setup();
// Clear the command interfaces
lspmac_SockSendControlCharPrint( NULL, '\x18')
 uint32_t cc;
 cc = 0;
 lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
   , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
 lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
, 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
// Initialize the MD2 pmac (ie, turn on the right plcc's etc)
/*
for( inits = lsredis_get_string_array(lspmac_md2_init); *inits != NULL;
     inits++) {
 lspmac_SockSendDPline( NULL, *inits);
// Initialize the pmac's support for each motor
// (ie, set the various flag for when a motor is active or not)
for( i=0; i<lspmac_nmotors; i++) {</pre>
 mp = &(lspmac_motors[i]);
 active = lsredis_getb( mp->active);
  // if there is a problem with "active" then don't do anything
  // On the other hand, various combinations of yes/no true/fals 1/0 should
  switch( active) {
  case 1:
    inits = lsredis_get_string_array( mp->active_init
    );
    break;
  case 0:
    inits = lsredis_get_string_array( mp->
    inactive_init);
   break;
   lslogging_log_message( "lspmac_run: motor %s is
     neither active nor inactive (!?) ", mp->name);
   inits = NULL;
  if( inits != NULL) {
   while( *inits != NULL) {
     lspmac_SockSendDPline( NULL, *inits);
     inits++;
 }
```

7.6.4.65 void lspmac_scint_dried_cb (char * event)

Turn off the dryer.

Parameters

```
event required by protocol
```

Definition at line 3351 of file Ispmac.c.

```
dryer->moveAbs( dryer, 0.0);
}
```

7.6.4.66 void lspmac_scint_inPosition_cb (char * event)

Maybe start drying off the scintilator.

Parameters

```
event required by protocol
```

Definition at line 3289 of file Ispmac.c.

7.6.4.67 pmac_cmd_queue_t* lspmac_send_command (int rqType, int rq, int wValue, int wIndex, int wLength, char * data, void(*)(pmac_cmd_queue_t *, int, char *) responseCB, int no_reply, char * event)

Compose a packet and send it to the PMAC.

This is the meat of the PMAC communications routines. The queued command is returned.

Parameters

in	rqType	VR_UPLOAD or VR_DOWNLOAD
in	rq	PMAC command (see PMAC User Manual
in	wValue	Command argument 1
in	wIndex	Command argument 2
in	wLength	Length of data array
in	data	Data array (or NULL)
in	responseCB	Function to call when a response is read from the PMAC
in	no_reply	Flag, non-zero means no reply is expected
in	event	base name for events

Definition at line 690 of file Ispmac.c.

```
static pmac_cmd_queue_t cmd;

cmd.pcmd.RequestType = rqType;
cmd.pcmd.Request = rq;
cmd.pcmd.wValue = htons(wValue);
cmd.pcmd.wIndex = htons(wIndex);
```

```
= htons(wLength);
= responseCB;
= no_reply;
= event;
cmd.pcmd.wLength
cmd.onResponse
cmd.no_reply
cmd.event
filling it
// or sending garbage in the unused bytes.
if( wLength > sizeof( cmd.pcmd.bData)) {
  // Bad things happen if we do not catch this case.
  lslogging_log_message( "Message Length %d longer than
  maximum of %ld, aborting", wLength, sizeof( cmd.pcmd.bData));
  exit(-1);
if ( data == NULL) {
 memset( cmd.pcmd.bData, 0, sizeof( cmd.pcmd.bData));
 else {
//
  // This could leave bData non-null terminated. I do not know if this is a
 problem.
  if(wLength > 0)
   memcpy( cmd.pcmd.bData, data, wLength);
  if( wLength < sizeof( cmd.pcmd.bData))</pre>
   memset( cmd.pcmd.bData + wLength, 0, sizeof( cmd.pcmd.bData
   ) - wLength);
return lspmac_push_queue( &cmd);
```

7.6.4.68 void lspmac_sendcmd (char * event, void(*)(pmac_cmd_queue_t *, int, char *) responseCB, char * fmt, ...)

PMAC command with call back.

Parameters

in	event	base name for events
in	responseCB	our callback routine
in	fmt	printf style format string

Definition at line 2095 of file Ispmac.c.

7.6.4.69 void lspmac_sendcmd_nocb (char * fmt, ...)

Send a command that does not need to deal with the reply.

Parameters

}

in	fmt	A printf style format string

Definition at line 2076 of file Ispmac.c.

7.6.4.70 void lspmac_SendControlReplyPrintCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Receive a reply to a control character Print a "printable" version of the character to the terminal Followed by a hex dump of the response.

Parameters

in	cmd	Queue item this is a reply to
in	nreceived	Number of bytes received
in	buff	Buffer of bytes received

Definition at line 1015 of file Ispmac.c.

```
pthread_mutex_lock( &ncurses_mutex);
wprintw( term_output, "control-%c: ", '@'+ ntohs(cmd->pcmd.
    wValue));
pthread_mutex_unlock( &ncurses_mutex);
hex_dump( nreceived, (unsigned char *)buff);
pthread_mutex_lock( &ncurses_mutex);
wnoutrefresh( term_output);
wnoutrefresh( term_input);
doupdate();
pthread_mutex_unlock( &ncurses_mutex);
```

7.6.4.71 void lspmac_Service (struct pollfd * evt)

Service routine for packet coming from the PMAC.

All communications is asynchronous so this is the only place incomming packets are handled

Parameters

in	evt	pollfd object returned by poll
----	-----	--------------------------------

Definition at line 798 of file Ispmac.c.

```
static char *receiveBuffer = NULL;  // the buffer inwhich to stick our
    incomming characters
static int receiveBufferSize = 0;
                                              // size of receiveBuffer
static int receiveBufferIn = 0;
                                              // next location to write to in
    receiveBuffer
pmac_cmd_queue_t *cmd;
                                              // maybe the
    command we are servicing
                                              // nbytes dealt with
ssize_t nsent, nread;
                                              // loop counter
int i;
int foundEOCR;
                                              // end of command response flag
if( evt->revents & (POLLERR | POLLHUP | POLLNVAL)) {
  if ( evt->fd != -1) {
   close( evt->fd);
evt->fd = -1;
  ls_pmac_state = LS_PMAC_STATE_DETACHED;
```

```
return;
if( evt->revents & POLLOUT) {
  switch( ls_pmac_state) {
  case LS_PMAC_STATE_DETACHED:
   break;
  case LS_PMAC_STATE_IDLE:
   break:
  case LS_PMAC_STATE_SC:
    cmd = lspmac_pop_queue();
    if( cmd == NULL)
      return;
    if( cmd->pcmd.Request == VR_PMAC_GETMEM) {
      nsent = send( evt->fd, cmd, pmac_cmd_size, 0);
      if( nsent != pmac_cmd_size) {
     lslogging_log_message( "Could only send %d of %d
bytes....Not good.", (int)nsent, (int)(pmac_cmd_size));
    } else {
      nsent = send( evt->fd, cmd, pmac_cmd_size + ntohs(cmd->
    pcmd.wLength), 0);
      gettimeofday( &pmac_time_sent, NULL);
      if( nsent != pmac_cmd_size + ntohs(cmd->pcmd.wLength
    )) {
        {\tt lslogging\_log\_message(\ "Could\ only\ send\ %d\ of\ %d}
     bytes....Not good.", (int)nsent, (int)(pmac_cmd_size + ntohs(cmd->
    pcmd.wLength)));
    }
    if( cmd->pcmd.Request == VR_PMAC_SENDCTRLCHAR
     ls_pmac_state = LS_PMAC_STATE_WACK_CC
    else if( cmd->pcmd.Request == VR_PMAC_GETMEM)
      ls_pmac_state = LS_PMAC_STATE_GMR;
    else if( cmd->no_reply == 0)
  ls_pmac_state = LS_PMAC_STATE_WACK;
    else
      ls_pmac_state = LS_PMAC_STATE_WACK_NFR
    break:
  case LS PMAC STATE CR:
   nsent = send( evt->fd, &cr_cmd, pmac_cmd_size, 0);
gettimeofday( &pmac_time_sent, NULL);
    ls_pmac_state = LS_PMAC_STATE_WCR;
    break;
  case LS_PMAC_STATE_RR:
   nsent = send( evt->fd, &rr_cmd, pmac_cmd_size, 0);
    gettimeofday( &pmac_time_sent, NULL);
    ls_pmac_state = LS_PMAC_STATE_WACK_RR;
    break;
  case LS PMAC STATE GB:
   nsent = send( evt->fd, &gb_cmd, pmac_cmd_size, 0);
gettimeofday( &pmac_time_sent, NULL);
    ls_pmac_state = LS_PMAC_STATE_WGB;
    break;
 }
if( evt->revents & POLLIN) {
  if( receiveBufferSize - receiveBufferIn < 1400) {</pre>
    char *newbuff;
    receiveBufferSize += 1400:
    newbuff = calloc( receiveBufferSize, sizeof( unsigned char));
    if( newbuff == NULL) {
      lslogging_log_message( "lspmac_Service: Out of
     memory");
      exit(-1);
    if( receiveBuffer != NULL) {
      memcpy( newbuff, receiveBuffer, receiveBufferIn);
      free(receiveBuffer);
    receiveBuffer = newbuff;
```

```
nread = read( evt->fd, receiveBuffer + receiveBufferIn, 1400);
foundEOCR = 0;
if( ls_pmac_state == LS_PMAC_STATE_GMR) {
  // get memory returns binary stuff, don't try to parse it
  receiveBufferIn += nread;
} else {
  // other commands end in 6 if OK, 7 if not
  for( i=receiveBufferIn; i<receiveBufferIn+nread; i++) {</pre>
    if ( receiveBuffer[i] == 7) {
      // Error condition
      lspmac_Error( &(receiveBuffer[i]));
      receiveBufferIn = 0;
      return;
    if( receiveBuffer[i] == 6) {
      // End of command response
      foundEOCR = 1;
      receiveBuffer[i] = 0;
      break;
  receiveBufferIn = i;
cmd = NULL;
switch( ls_pmac_state) {
case LS_PMAC_STATE_WACK_NFR:
 receiveBuffer[--receiveBufferIn] = 0;
  cmd = lspmac_pop_reply();
  ls_pmac_state = LS_PMAC_STATE_IDLE;
  break;
case LS_PMAC_STATE_WACK:
 receiveBuffer[--receiveBufferIn] = 0;
ls_pmac_state = LS_PMAC_STATE_RR;
  break;
case LS_PMAC_STATE_WACK_CC:
 receiveBuffer[--receiveBufferIn] = 0;
ls_pmac_state = LS_PMAC_STATE_CR;
 break:
case LS_PMAC_STATE_WACK_RR:
  receiveBufferIn -= 2;
  if( receiveBuffer[receiveBufferIn])
    ls_pmac_state = LS_PMAC_STATE_GB;
  else
   ls_pmac_state = LS_PMAC_STATE_RR;
  receiveBuffer[receiveBufferIn] = 0;
  break;
case LS_PMAC_STATE_GMR:
  cmd = lspmac_pop_reply();
  ls_pmac_state = LS_PMAC_STATE_IDLE;
  break:
case LS_PMAC_STATE_WCR:
 cmd = lspmac_pop_reply();
  ls_pmac_state = LS_PMAC_STATE_IDLE;
 break;
case LS_PMAC_STATE_WGB:
  if( foundEOCR) {
   cmd = lspmac_pop_reply();
ls_pmac_state = LS_PMAC_STATE_IDLE;
    ls_pmac_state = LS_PMAC_STATE_RR;
  break;
if( cmd != NULL && cmd->onResponse != NULL) {
  cmd->onResponse( cmd, receiveBufferIn, receiveBuffer);
  receiveBufferIn = 0;
```

}

7.6.4.72 void lspmac_shutter_read (lspmac_motor_t * mp)

Fast shutter read routine The shutter is mildly complicated in that we need to take into account the fact that the shutter can open and close again between status updates.

This means that we need to rely on a PCL program running in the PMAC to monitor the shutter state and let us know that this has happened.

Parameters

in	тр	The motor object associated with the fast shutter

Definition at line 1171 of file Ispmac.c.

```
// track the shutter state and signal if it has changed
pthread_mutex_lock( &lspmac_shutter_mutex);
if( md2_status.fs_has_opened && !
     lspmac_shutter_has_opened && !md2_status.
    fs_is_open) {
  ^{\prime\prime} Here the shutter opened and closed again before we got the memo // Treat it as a shutter closed event
  pthread_cond_signal( &lspmac_shutter_cond);
lspmac_shutter_has_opened = md2_status.
     fs_has_opened;
if( lspmac_shutter_state != md2_status.
    fs is open) {
  lspmac_shutter_state = md2_status.fs_is_open
  pthread_cond_signal( &lspmac_shutter_cond);
if( md2_status.fs_is_open) {
   mvwprintw( term_status2, 1, 1, "Shutter Open ");
  mp->position = 1;
  mvwprintw( term_status2, 1, 1, "Shutter Closed");
  mp -> position = 0;
pthread_mutex_unlock( &lspmac_shutter_mutex);
```

7.6.4.73 void lspmac_SockFlush ()

Reset the PMAC socket from the PMAC side.

Puts the PMAC into a known communications state

Definition at line 744 of file Ispmac.c.

7.6.4.74 pmac_cmd_queue_t* lspmac_SockGetmem (int offset, int nbytes)

Request a chunk of memory to be returned.

Parameters

in	offset	Offset in PMAC Double Buffer
in	nbytes	Number of bytes to request

Definition at line 1050 of file Ispmac.c.

7.6.4.75 pmac_cmd_queue_t* lspmac_SockSendControlCharPrint (char * event, char c)

Send a control character.

Parameters

in	event	base name for events
	С	The control character to send

Definition at line 1103 of file Ispmac.c.

7.6.4.76 void lspmac_SockSendDPControlChar (char * event, char c)

use dpram ascii interface to send a control character

Definition at line 1976 of file Ispmac.c.

7.6.4.77 void lspmac_SockSendDPControlCharCB (pmac_cmd_queue_t * cmd, int nreceived, char * buf)

Definition at line 1969 of file Ispmac.c.

```
if( cmd->event != NULL && *(cmd->event))
   lsevents_send_event( "%s accepted", cmd->event);
}
```

7.6.4.78 void lspmac_SockSendDPline (char * event, char * fmt, ...)

prepare (queue up) a line to send the dpram ascii command interface

Definition at line 1949 of file Ispmac.c.

```
va_list arg_ptr;
uint32_t index;
char *pl;
```

```
pthread_mutex_lock( &lspmac_ascii_mutex);
index = lspmac_dpascii_on++ % LSPMAC_DPASCII_QUEUE_LENGTH
;

pl = lspmac_dpascii_queue[index].pl;

va_start( arg_ptr, fmt);
vsnprintf( pl, 159, fmt, arg_ptr);
pl[159] = 0;
va_end( arg_ptr);

lspmac_dpascii_queue[index].event = event;
pthread_mutex_unlock( &lspmac_ascii_mutex);
}
```

7.6.4.79 void Ispmac_SockSendDPqueue ()

Definition at line 1985 of file Ispmac.c.

```
lspmac_dpascii_queue_t *qp;
uint32_t mask;
uint32_t clrdata;
lspmac_ascii_busy = 1;
pthread_mutex_unlock( &lspmac_ascii_mutex);
lslogging_log_message( "lspmac_SockSendDPqueue: %s", qp
    ->pl);
clrdata = 0;
                         // set the control word to zero
lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
, 0x0f40, 0, 4, (char *)&clrdata, NULL, 1, NULL); lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9c, 0, 4, (char *)&clrdata, NULL, 1, NULL);
lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0ea0, 0, strlen(qp->pl)+1, qp->pl, NULL, 1, NULL);
mask = 0x0001;
lspmac_send_command( VR_UPLOAD, VR_PMAC_SETBIT
   , 0x0e9c, 1, sizeof( mask), (char *)&mask,lspmac_asciicmdCB, 1,
     qp->event);
if( qp->event != NULL && *(qp->event) != 0)
  lsevents_send_event( "%s queued", qp->event);
```

7.6.4.80 pmac_cmd_queue_t* lspmac_SockSendline (char * event, char * fmt, ...)

Send a one line command.

Uses printf style arguments.

Parameters

in	event	base name for events
in	fmt	Printf style format string

Definition at line 1060 of file Ispmac.c.

```
va_list arg_ptr;
char payload[1400];

va_start( arg_ptr, fmt);
vsnprintf( payload, sizeof(payload)-1, fmt, arg_ptr);
payload[ sizeof(payload)-1] = 0;
va_end( arg_ptr);
```

7.6.4.81 pmac_cmd_queue_t* lspmac_SockSendline_nr (char * event, char * fmt, ...)

Send a command and ignore the response.

Parameters

Ī	in	event	base name for events
	in	fmt	Printf style format string

Definition at line 1083 of file Ispmac.c.

7.6.4.82 Ispmac_motor_t* Ispmac_soft_motor_init (Ispmac_motor_t * d, char * name, int(*)(Ispmac_motor_t *, double) moveAbs)

Definition at line 3101 of file Ispmac.c.

```
lspmac_motor_init( d, name);
d->moveAbs = moveAbs;
d->read = lspmac_soft_motor_read;
d->actual_pos_cnts_p = calloc( sizeof(int), 1);
*d->actual_pos_cnts_p = 0;
return d;
```

7.6.4.83 void lspmac_soft_motor_read (lspmac_motor_t * p)

Dummy routine to read a soft motor.

Definition at line 3096 of file Ispmac.c.

7.6.4.84 int lspmac_test_preset (lspmac_motor_t * mp, char * preset_name, double tolerance)

see if the motor is within tolerance of the preset 1 means yes, it is 0 mean no it isn't or that the preset was not found Definition at line 2374 of file Ispmac.c.

7.6.4.85 void Ispmac_video_rotate (double secs)

Special motion program to collect centering video.

Definition at line 2568 of file Ispmac.c.

```
// starting position (counts)
// delta counts
double q10;
double q11;
                        // milliseconds to run over delta
double q12;
double u2c;
double neutral_pos;
if( secs <= 0.0)</pre>
 return;
omega_zero_search = 1;
pthread_mutex_lock( &(omega->mutex));
u2c = lsredis_getd( omega->u2c);
neutral_pos = lsredis_getd( omega->neutral_pos);
q10 = neutral_pos * u2c;
q11 = 360.0 * u2c;
q12 = 1000 * secs;
omega_zero_velocity = 360.0 * u2c / secs; //
     counts/second to back calculate zero crossing time
lspmac_SockSendDPline( omega->name, "&1
     Q10=%.1f Q11=%.1f Q12=%.1f Q13=(I117) Q14=(I116) B240R", q10, q11, q12);
pthread_mutex_unlock( &(omega->mutex));
```

7.6.4.86 void* Ispmac_worker (void * dummy)

Our Ispmac worker thread.

Parameters

in	dummy	Unused but required by pthread library

Definition at line 2234 of file Ispmac.c.

```
static int disconnected_notify = 0;
static int old_state;
```

```
old_state = ls_pmac_state;
while(1) {
  int pollrtn;
  lspmac next state():
  if( ls_pmac_state != old_state) {
           lslogging_log_message( "lspmac_worker: state = %d",
     ls_pmac_state);
    old_state = ls_pmac_state;
  if ( pmacfd.fd == -1) {
    if( disconnected_notify == 0)
      lslogging_log_message( "lspmac_worker: PMAC not
     connected"):
    disconnected_notify = 1;
    // At this point we assume we became disconnected due to something like a
     hard boot of the MD2 PMAC
    // and hence the entire system needs reinitialization.
    // It's possible to put in a test here (perhaps using I65) to see if we
     in fact suffered a reset
    // and need to clear the queue, reinitialize, etc. Or if it was just a
     networking glitch and do not
    // need to clear the queue and should instead just charge ahead.
    lspmac_reset_queue();
    sleep( 10);
    // This just puts us into a holding pattern until the pmac becomes
     connected again
    continue;
  disconnected\_notify = 0;
  pollrtn = poll( &pmacfd, 1, 10);
  if( pollrtn) {
    lspmac_Service( &pmacfd);
}
```

7.6.4.87 void lspmac_zoom_lut_setup ()

Set up lookup table for zoom.

Definition at line 3359 of file Ispmac.c.

```
int i:
lsredis_obj_t *p;
pthread_mutex_lock( &zoom->mutex);
zoom->nlut = 10:
zoom->lut = calloc( 2 * zoom->nlut, sizeof( double));
if( zoom->lut == NULL) {
  lslogging_log_message( "lspmac_zoom_lut_setup: out of
      memory");
  exit(-1);
for( i=0; i < zoom->nlut; i++) {
      lsredis_get_obj( "cam.zoom.%d.MotorPosition", i+1);
  p = lsredis_get_obj( "cam.zoom.rot.nocorrot
if( p==NULL || strlen( lsredis_getstr(p)) == 0) {
    free( zoom->lut);
     zoom->lut = NULL;
zoom->nlut = 0;
     pthread_mutex_unlock( &zoom->mutex);
lslogging_log_message( "lspmac_zoom_lut_setup:
      cannot find MotorPosition element for cam.zoom level %d", i+1);
     return;
  zoom->lut[2*i] = i+1;
zoom->lut[2*i+1] = lsredis_getd( p);
pthread_mutex_unlock( &zoom->mutex);
```

7.6.5 Variable Documentation

7.6.5.1 Ispmac_motor_t* alignx

Alignment stage X.

Definition at line 90 of file Ispmac.c.

7.6.5.2 Ispmac_motor_t* aligny

Alignment stage Y.

Definition at line 91 of file Ispmac.c.

7.6.5.3 Ispmac_motor_t* alignz

Alignment stage X.

Definition at line 92 of file Ispmac.c.

7.6.5.4 Ispmac_motor_t* anal

Polaroid analyzer motor.

Definition at line 93 of file Ispmac.c.

7.6.5.5 Ispmac_motor_t* apery

Aperture Y.

Definition at line 95 of file Ispmac.c.

Aperture Z.

Definition at line 96 of file Ispmac.c.

7.6.5.7 | Ispmac_bi_t* arm_parked

(whose arm? parked where?)

Definition at line 133 of file Ispmac.c.

7.6.5.8 Ispmac_motor_t* blight

Back Light DAC.

Definition at line 107 of file Ispmac.c.

7.6.5.9 lspmac_bi_t* blight_down

Backlight is down.

Definition at line 123 of file Ispmac.c.

7.6.5.10 Ispmac_motor_t* blight_f

Back light scale factor.

Definition at line 116 of file Ispmac.c.

7.6.5.11 Ispmac_motor_t* blight_ud

Back light Up/Down actuator.

Definition at line 111 of file Ispmac.c.

7.6.5.12 | Ispmac_bi_t* blight_up

Backlight is up.

Definition at line 124 of file Ispmac.c.

7.6.5.13 Ispmac_motor_t* capy

Capillary Y.

Definition at line 97 of file Ispmac.c.

7.6.5.14 Ispmac motor t* capz

Capillary Z.

Definition at line 98 of file Ispmac.c.

7.6.5.15 | Ispmac_motor_t* cenx

Centering Table X.

Definition at line 100 of file Ispmac.c.

7.6.5.16 Ispmac_motor_t* ceny

Centering Table Y.

Definition at line 101 of file Ispmac.c.

7.6.5.17 pmac_cmd_t cr_cmd [static]

commands to send out "readready", "getbuffer", "controlresponse" (initialized in main)

Definition at line 185 of file Ispmac.c.

7.6.5.18 Ispmac_motor_t* cryo

Move the cryostream towards or away from the crystal.

Definition at line 112 of file Ispmac.c.

7.6.5.19 lspmac_bi_t* cryo_back

cryo is in the back position

Definition at line 125 of file Ispmac.c.

7.6.5.20 lspmac_bi_t* cryo_switch

that little toggle switch for the cryo

Definition at line 122 of file Ispmac.c.

7.6.5.21 unsigned char dbmem[64 *1024] [static]

double buffered memory

Definition at line 174 of file Ispmac.c.

7.6.5.22 int dbmemIn = 0 [static]

next location

Definition at line 175 of file Ispmac.c.

7.6.5.23 Ispmac_motor_t* dryer

blow air on the scintilator to dry it off

Definition at line 113 of file Ispmac.c.

7.6.5.24 | Ispmac_bi_t* etel_init_ok

ETEL initialized OK.

Definition at line 130 of file Ispmac.c.

7.6.5.25 | Ispmac_bi_t* etel_on

ETEL is on.

Definition at line 129 of file Ispmac.c.

ETEL is ready.

Definition at line 128 of file Ispmac.c.

7.6.5.27 unsigned int ethCmdOff = 0 [static]

points to current command (or none if == ethCmdOn)

Definition at line 188 of file Ispmac.c.

7.6.5.28 unsigned int ethCmdOn = 0 [static]

points to next empty PMAC command queue position

Definition at line 187 of file Ispmac.c.

7.6.5.29 pmac_cmd_queue_t ethCmdQueue[PMAC_CMD_QUEUE_LENGTH] [static]

PMAC command queue.

Definition at line 186 of file Ispmac.c.

7.6.5.30 unsigned int ethCmdReply = 0 [static]

Used like ethCmdOff only to deal with the pmac reply to a command.

Definition at line 189 of file Ispmac.c.

7.6.5.31 Ispmac_motor_t* flight

Front Light DAC.

Definition at line 106 of file Ispmac.c.

7.6.5.32 Ispmac_motor_t* flight_f

Front light scale factor.

Definition at line 117 of file Ispmac.c.

7.6.5.33 Ispmac_motor_t* flight_oo

Turn front light on/off.

Definition at line 115 of file Ispmac.c.

7.6.5.34 Ispmac_motor_t* fluo

Move the fluorescence detector in/out.

Definition at line 114 of file Ispmac.c.

7.6.5.35 | Ispmac_bi_t* fluor_back

fluor is in the back position

Definition at line 126 of file Ispmac.c.

Scintillator Piezo DAC.

Definition at line 108 of file Ispmac.c.

7.6.5.37 Ispmac_motor_t* fshut

Fast shutter.

Definition at line 105 of file Ispmac.c.

7.6.5.38 pmac_cmd_t gb_cmd [static]

Definition at line 185 of file Ispmac.c.

7.6.5.39 int getivars = 0 [static]

flag set at initialization to send i vars to db

Definition at line 81 of file Ispmac.c.

7.6.5.40 int getmvars = **0** [static]

flag set at initialization to send m vars to db

Definition at line 82 of file Ispmac.c.

7.6.5.41 Ispmac_bi_t* hp_air

High pressure air OK.

Definition at line 121 of file Ispmac.c.

7.6.5.42 Ispmac_motor_t* kappa

Kappa.

Definition at line 102 of file Ispmac.c.

7.6.5.43 Ispmac_bi_t* lp_air

Low pressure air OK.

Definition at line 120 of file Ispmac.c.

7.6.5.44 int ls_pmac_state = LS_PMAC_STATE_DETACHED [static]

Current state of the PMAC communications state machine.

Definition at line 51 of file Ispmac.c.

7.6.5.45 Ispmac_ascii_buffers_t Ispmac_ascii_buffers [static]

Definition at line 354 of file Ispmac.c.

7.6.5.46 pthread_mutex_t lspmac_ascii_buffers_mutex

Definition at line 355 of file Ispmac.c.

```
7.6.5.47 int lspmac_ascii_busy = 0 [static]
flag for condition to wait for
Definition at line 68 of file Ispmac.c.
7.6.5.48 pthread_mutex_t lspmac_ascii_mutex [static]
Keep too many processes from sending commands at once.
Definition at line 67 of file Ispmac.c.
7.6.5.49 | Ispmac_bi_t | Ispmac_bis[32]
array of binary inputs
Definition at line 84 of file Ispmac.c.
7.6.5.50 uint32_t lspmac_dpascii_off = 0 [static]
Definition at line 365 of file Ispmac.c.
7.6.5.51 uint32_t lspmac_dpascii_on = 0 [static]
Definition at line 364 of file Ispmac.c.
7.6.5.52 Ispmac_dpascii_queue_t Ispmac_dpascii_queue[LSPMAC_DPASCII_QUEUE_LENGTH] [static]
Definition at line 363 of file Ispmac.c.
7.6.5.53 | Ispmac_motor_t | Ispmac_motors[48]
All our motors.
Definition at line 87 of file Ispmac.c.
7.6.5.54 pthread_cond_t lspmac_moving_cond
Wait for motor(s) to finish moving condition.
Definition at line 64 of file Ispmac.c.
7.6.5.55 int lspmac_moving_flags
Flag used to implement motor moving condition.
Definition at line 65 of file Ispmac.c.
7.6.5.56 pthread_mutex_t lspmac_moving_mutex
Coordinate moving motors between threads.
```

Definition at line 63 of file Ispmac.c.

7.6.5.57 int $lspmac_nbis = 0$

number of active binary inputs

Definition at line 85 of file Ispmac.c.

7.6.5.58 int lspmac_nmotors = 0

The number of motors we manage.

Definition at line 88 of file Ispmac.c.

7.6.5.59 pthread_cond_t lspmac_shutter_cond

Allows waiting for the shutter status to change.

Definition at line 62 of file Ispmac.c.

7.6.5.60 int lspmac_shutter_has_opened

Indicates that the shutter had opened, perhaps briefly even if the state did not change.

Definition at line 60 of file Ispmac.c.

7.6.5.61 pthread_mutex_t lspmac_shutter_mutex

Coordinates threads reading shutter status.

Definition at line 61 of file Ispmac.c.

7.6.5.62 int Ispmac_shutter_state

State of the shutter, used to detect changes.

Definition at line 59 of file Ispmac.c.

7.6.5.63 struct timespec lspmac_status_last_time [static]

Time the status was read.

Definition at line 74 of file Ispmac.c.

7.6.5.64 struct timespec lspmac_status_time [static]

Time the status was read.

Definition at line 73 of file Ispmac.c.

7.6.5.65 md2_status_t md2_status [static]

Buffer for MD2 Status.

Definition at line 340 of file Ispmac.c.

7.6.5.66 pthread_mutex_t md2_status_mutex Synchronize reading/writting status buffer. Definition at line 341 of file Ispmac.c. Minikappa is OK (whatever that means) Definition at line 131 of file Ispmac.c. **7.6.5.68 struct timeval pmac_time_sent now** [static] used to ensure we do not send commands to the pmac too often. Only needed for non-DB commands. Definition at line 181 of file Ispmac.c. 7.6.5.69 Ispmac_motor_t* omega MD2 omega axis (the air bearing) Definition at line 89 of file Ispmac.c. 7.6.5.70 int omega_zero_search = 0 [static] Indicate we'd really like to know when omega crosses zero. Definition at line 70 of file Ispmac.c. 7.6.5.71 struct timespec omega_zero_time Time we believe that omega crossed zero. Definition at line 72 of file Ispmac.c. **7.6.5.72** double omega_zero_velocity = **0** [static] rate (cnts/sec) that omega was traveling when it crossed zero Definition at line 71 of file Ispmac.c. 7.6.5.73 Ispmac_motor_t* phi Phi (not data collection axis) Definition at line 103 of file Ispmac.c. 7.6.5.74 char* pmac_error_strs[] [static] Initial value:

```
"ERR000: Unknown error",
"ERR001: Command not allowed during program execution",
"ERR002: Password error",
"ERR003: Data error or unrecognized command",
"ERR004: Illegal character",
```

```
"ERR005: Command not allowed unless buffer is open",
  "ERR006: No room in buffer for command",
  "ERR007: Buffer already in use"
  "ERR008: MACRO auziliary communication error",
  "ERR009: Program structure error (e.g. ENDIF without IF)",
"ERR010: Both overtravel limits set for a motor in the C.S.",
  "ERR011: Previous move not completed",
  "ERR012: A motor in the coordinate system is open-loop",
  "ERR013: A motor in the coordinate system is not activated",
  "ERR014: No motors in the coordinate system",
  "ERR015: Not pointer to valid program buffer",
  "ERR016: Running improperly structure program (e.g. missing ENDWHILE)",
  "ERR017: Trying to resume after H or Q with motors out of stopped position",
  "ERR018: Attempt to perform phase reference during move, move during phase
       reference, or enabling with phase clock error",
  "ERR019: Illegal position-chage command while moves stored in CCBUFFER",
  "ERR020: FSAVE issued on Turbo PMAC with incompatible flash memory",
  "ERR021: FSAVE issued while clearing old flash memory sector", "ERR022: FREAD attempted but the flash memory is bad"
Decode the errors perhaps returned by the PMAC.
Definition at line 192 of file Ispmac.c.
7.6.5.75 pthread_cond_t pmac_queue_cond
wait for a command to be sent to PMAC before continuing
Definition at line 78 of file Ispmac.c.
7.6.5.76 pthread_mutex_t pmac_queue_mutex
manage access to the pmac command queue
Definition at line 77 of file Ispmac.c.
7.6.5.77 pthread_t pmac_thread [static]
our thread to manage access and communication to the pmac
Definition at line 76 of file Ispmac.c.
7.6.5.78 struct pollfd pmacfd [static]
our poll structure
Definition at line 79 of file Ispmac.c.
7.6.5.79 pmac_cmd_t rr_cmd [static]
Definition at line 185 of file Ispmac.c.
7.6.5.80 Ispmac_bi_t* sample_detected
smart magnet detected sample
Definition at line 127 of file Ispmac.c.
7.6.5.81 Ispmac motor t* scint
```

Scintillator Z.

Definition at line 99 of file Ispmac.c.

shutter is open (note in pmc says this is a slow input)

Definition at line 134 of file Ispmac.c.

7.6.5.83 | Ispmac_bi_t* smart_mag_err

smart magnet error (coil broken perhaps)

Definition at line 135 of file Ispmac.c.

7.6.5.84 | Ispmac_bi_t* smart_mag_off

smart magnet is off

Definition at line 136 of file Ispmac.c.

7.6.5.85 | Ispmac_bi_t* smart_mag_on

smart magnet is on

Definition at line 132 of file Ispmac.c.

Smart Magnet on/off.

Definition at line 110 of file Ispmac.c.

Optical zoom.

Definition at line 94 of file Ispmac.c.

7.7 Isredis.c File Reference

Support redis hash synchronization.

```
#include "pgpmac.h"
```

Functions

- void lsredis_debugCB (redisAsyncContext *ac, void *reply, void *privdata)
 Log the reply.
- void _lsredis_set_value (lsredis_obj_t *p, char *v)

set_value and setstr helper funciton p->mutex must be locked before calling

void Isredis set value (Isredis obj t *p, char *fmt,...)

Set the value of a redis object and make it valid.

• int lsredis_cmpstr (lsredis_obj_t *p, char *s)

7.7 Isredis.c File Reference 211

```
    int lsredis_cmpnstr (lsredis_obj_t *p, char *s, int n)

    int lsredis_regexec (const regex_t *preg, lsredis_obj_t *p, size_t nmatch, regmatch_t *pmatch, int eflags)

    char * lsredis_getstr (lsredis_obj_t *p)

      return a copy of the key's string value

    void lsredis_setstr (lsredis_obj_t *p, char *fmt,...)

      Set the value and update redis.

    double lsredis_getd (lsredis_obj_t *p)

    long int Isredis getl (Isredis obj t *p)

    char ** Isredis get string array (Isredis obj t *p)

int lsredis_getb (lsredis_obj_t *p)

    char Isredis getc (Isredis obj t *p)

    void lsredis_hgetCB (redisAsyncContext *ac, void *reply, void *privdata)

    Isredis_obj_t * _Isredis_get_obj (char *key)

      Maybe add a new object Used internally for this module Must be called with Isredis_mutex locked.

    Isredis obj t * Isredis get obj (char *fmt,...)

    void redisDisconnectCB (const redisAsyncContext *ac, int status)

      call back in case a redis server becomes disconnected TODO: reconnect

    void Isredis addRead (void *data)

      hook to mange read events

    void lsredis_delRead (void *data)

      hook to manage "don't need to read" events

    void Isredis_addWrite (void *data)

      hook to manage write events

    void Isredis delWrite (void *data)

      hook to manage "don't need to write anymore" events

    void Isredis cleanup (void *data)

      hook to clean up TODO: figure out what we are supposed to do here and do it

    void lsredis_subCB (redisAsyncContext *ac, void *reply, void *privdata)

      Use the publication to request the new value.

    void lsredis_maybe_add_key (char *k)

    void lsredis_keysCB (redisAsyncContext *ac, void *reply, void *privdata)

      Sift through the keys to find ones we like.
• int Isredis find preset (char *base, char *preset name, double *dval)

    void Isredis init (char *pub, char *re, char *head)

      Initialize this module, that is, set up the connections.

    void lsredis_fd_service (struct pollfd *evt)

      service the socket requests

    void lsredis_sig_service (struct pollfd *evt)

    void * Isredis worker (void *dummy)
```

Variables

· static pthread t Isredis thread

• void Isredis run ()

- static pthread mutex t Isredis mutex = PTHREAD RECURSIVE MUTEX INITIALIZER NP
- static pthread_cond_t lsredis_cond
- static int Isredis_running = 0
- static lsredis_obj_t * lsredis_objs = NULL

subscribe to changes and service sockets

- static struct hsearch_data lsredis_htab
- static redisAsyncContext * subac
- static redisAsyncContext * roac

- static redisAsyncContext * wrac
- static char * Isredis_publisher = NULL
- · static regex t Isredis key select regex
- static char * Isredis head = NULL
- · static struct pollfd subfd
- static struct pollfd rofd
- · static struct pollfd wrfd

7.7.1 Detailed Description

Support redis hash synchronization.

```
\date 2012
\author Keith Brister
\copyright All Rights Reserved
```

Redis support for redis in pgpmac.

Values in redis are assumed to be hashs with at list one field "VALUE". At startup the initialization routine is passed a regular expression to select which keys we'd like to duplicate locally as a Isredis_obj_t. It is assumed that the following construct in redis is used to change a value:

```
MULTI
HSET key VALUE value
PUBLISH publisher key
EXEC
```

Where "publisher" is a unique name in the following format:

```
MD2-*
or UI-*
or REDIS_KV_CONNECTOR
```

(this last value is used to support the now depreciated px.kvs table in the LS-CAT postgresql server). We assume that all publisher that we are listening to ONLY publish key names that have changed.

When someone else changes a value we invalidate our internal copy and issue a "HGET key VALUE" command. Other threads that request the value of our Isredis_obj_t will pause until the new value has been received and processed.

When a value changes locally this module changes it in redis as shown above. At this point we refuse other publishers attempt to change the value until we've seen all of our PUBLISH messages. That is, we ignore changes that in redis happened before our change.

You'll need an Isredis_obj_t to do anything with redis in the pgpmac project:

```
lsredis_obj_t *lsredis_get_obj( char *fmt, ...) where fmt is a printf style formatting string

During initialization a "head" string is passe

For example, "omega.position" might refer to the
```

To set a redis value use

```
void lsredis_setstr( lsredis_obj_t *p, char *fmt, ...) where fmt is a printf style formatting
```

When a new value is seen we immediately parse it and make it available through the following functions:

```
*lsredis_getstr( lsredis_obj_t *p)
                                                         Returns a copy of the VALUE field. Use
char
       lsredis_getd( lsredis_obj_t *p)
                                                         Returns a double. If the value was not
double
long int lsredis_getl( lsredis_obj_t *p)
                                                         Returns a long int. If the value was n
     **lsredis_get_string_array( lsredis_obj_t *p) Returns an array of string pointers. \text{\text{\text{$\text{$V$}}}}
char
                                               or NULL if the value could not be parsed
int
         lsredis_getb( lsredis_obj_t *p)
                                                         Returns 1, 0, or -1 based on the fist of
char
        lsredis_getc( lsredis_obj_t *p)
                                                        Returns the first character of VALUE
```

Definition in file Isredis.c.

7.7.2 Function Documentation

7.7.2.1 Isredis obj t* _lsredis_get_obj (char * key)

Maybe add a new object Used internally for this module Must be called with Isredis mutex locked.

Definition at line 438 of file Isredis.c.

```
{
lsredis_obj_t *p;
regmatch_t pmatch[2];
ENTRY htab_input, *htab_output;
// Dispense with obviously bad keys straight away // unless p->valid == 0 in which case we call HGET first
// TODO: review logic: is there ever a time when valid is zero for a
      preexisting \boldsymbol{p} and \boldsymbol{H}\boldsymbol{G}\boldsymbol{E}\boldsymbol{T} has not been called?
//
          If not then we should just return p without checking for validity.
if( key == NULL || *key == 0 || strchr( key, ' ') != NULL) {
  lslogging_log_message( "_lsredis_get_obj: bad key '%s'
    ", key == NULL ? "<NULL>" : key);
  return NULL;
// If the key is already there then just return it
htab_input.key = key;
htab_input.data = NULL;
errno = 0;
err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab);
if( err == 0)
p = NULL;
else
 p = htab_output->data;
if( p != NULL) {
  return p;
  else {
  // make a new one.
  p = calloc( 1, sizeof( lsredis_obj_t));
  if( p == NULL) {
     lslogging_log_message( "_lsredis_get_obj: Out of
      memory");
     exit( -1);
  err = regexec( &lsredis_key_select_regex, key, 2,
    pmatch, 0);
  if( err == 0 && pmatch[1].rm_so != -1) {
```

```
p->events_name = strndup( key+pmatch[1].rm_so, pmatch[1].rm_eo
     - pmatch[1].rm_so);
  } else {
    p->events_name = strdup( key);
  if( p->events_name == NULL) {
    lslogging_log_message( "_lsredis_get_obj: Out of
     memory (events_name)");
    exit(-1);
  pthread_mutex_init( &p->mutex, NULL);
pthread_cond_init( &p->cond, NULL);
  p->value = NULL;
  p->valid = 0;
  lsevents_send_event( "%s Invalid", p->events_name
  p->wait_for_me = 0;
  p->key = strdup( key);
  p->hits = 0;
  htab_input.key = p->key;
  htab_input.data = p;
  errno = 0;
  err = hsearch_r( htab_input, ENTER, &htab_output, &lsredis_htab
  if( err == 0) {
    lslogging_log_message( "_lsredis_get_obj: hseach
error on enter. errno=%d", errno);
  // Shouldn't need the linked list unless we need to rebuild the hash table
  when, for example, we run out of room. // TODO: resize hash table when needed.
  p->next = lsredis_objs;
  lsredis_objs = p;
\ensuremath{//} We arrive here with the valid flag lowered. Go ahead and request the
     latest value.
redisAsyncCommand( roac, lsredis_hgetCB, p, "HGET %s VALUE"
return p;
```

7.7.2.2 void _lsredis_set_value (lsredis_obj_t * p, char * v)

 ${\tt set_value} \ {\tt and} \ {\tt setstr} \ {\tt helper} \ {\tt funciton} \ {\tt p->mutex} \ {\tt must} \ {\tt be} \ {\tt locked} \ {\tt before} \ {\tt calling}$

Definition at line 146 of file Isredis.c.

```
if( strlen(v) >= (unsigned int) p->value_length) {
  if( p->value != NULL)
    free( p->value);
  p->value_length = strlen(v) + 256;
  p->value = calloc( p->value_length, sizeof( char));
  if( p->value == NULL) {
    lslogging_log_message( "_lsredis_set_value: out of
     memory");
    exit( -1);
  }
strncpy( p->value, v, p->value_length - 1);
p->value[p->value_length-1] = 0;
p->dvalue = strtod( p->value, NULL);
p->lvalue = p->dvalue;
if( p->avalue != NULL) {
  for( i=0; (p->avalue)[i] != NULL; i++)
    free( (p->avalue)[i]);
 free( p->avalue);
p->avalue = NULL;
```

```
p->avalue = lspg_array2ptrs( p->value);
switch( *(p->value)) {
    case 'T':
case 't':
    case 'Y':
    case 'y':
case '1':
      p->bvalue = 1;
    break;
    case 'F':
    case 'f':
case 'N':
    case 'n':
case '0':
     p->bvalue = 0;
    break;
    default:
     p->bvalue = -1;
                             // nil is -1 here in our world
p->cvalue = *(p->value);
if( !(p->valid)) {
  lsevents_send_event( "%s Valid", p->events_name
```

7.7.2.3 void lsredis_addRead (void * data)

hook to mange read events

Definition at line 568 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

if( (pfd->events & POLLIN) == 0) {
   pfd->events |= POLLIN;
   pthread_kill( lsredis_thread, SIGUSR1);
}
}
```

7.7.2.4 void lsredis_addWrite (void * data)

hook to manage write events

Definition at line 592 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

if( (pfd->events & POLLOUT) == 0) {
   pfd->events |= POLLOUT;
   pthread_kill( lsredis_thread, SIGUSR1);
}
```

7.7.2.5 void lsredis_cleanup (void * data)

hook to clean up TODO: figure out what we are supposed to do here and do it Definition at line 617 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

pfd->fd = -1;

if( (pfd->events & (POLLOUT | POLLIN)) != 0) {
    pfd->events &= ~(POLLOUT | POLLIN);
    pthread_kill( lsredis_thread, SIGUSR1);
}
```

7.7.2.6 int lsredis_cmpnstr (lsredis_obj_t * p, char * s, int n)

Definition at line 236 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = strncmp( p->value, s, n);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.7.2.7 int lsredis_cmpstr (lsredis_obj_t * p, char * s)

Definition at line 225 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = strcmp( p->value, s);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.7.2.8 void | sredis_debugCB (redisAsyncContext * ac, void * reply, void * privdata)

Log the reply.

Definition at line 96 of file Isredis.c.

```
case REDIS_REPLY_INTEGER:
 lslogging_log_message( "%*sInteger: %lld", indentlevel
  *4, "", r->integer);
  break;
case REDIS_REPLY_NIL:
  lslogging_log_message( "%*s(nil)", indentlevel*4, "");
case REDIS_REPLY_STRING:
  lslogging_log_message( "%*sSTRING: %s", indentlevel*4,
    "", r->str);
  break;
case REDIS_REPLY_ARRAY:
 lslogging_log_message( "%*sARRAY of %d elements",
  indentlevel*4, "", (int)r->elements);
  indentlevel++;
  for( i=0; i<(int)r->elements; i++)
    lsredis_debugCB( ac, r->element[i], NULL);
  indentlevel--;
  break;
default:
  lslogging_log_message( "%*sUnknown type %d",
    indentlevel*4,"", r->type);
```

7.7.2.9 void Isredis_delRead (void * data)

hook to manage "don't need to read" events

Definition at line 580 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

if( (pfd->events & POLLIN) != 0) {
   pfd->events &= ~POLLIN;
   pthread_kill( lsredis_thread, SIGUSR1);
}
```

7.7.2.10 void Isredis_delWrite (void * data)

hook to manage "don't need to write anymore" events

Definition at line 604 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

if( (pfd->events & POLLOUT) != 0) {
   pfd->events &= ~POLLOUT;
   pthread_kill( lsredis_thread, SIGUSR1);
}
```

7.7.2.11 void lsredis_fd_service (struct pollfd * evt)

service the socket requests

Definition at line 889 of file Isredis.c.

```
pthread_mutex_lock( &lsredis_mutex);
if( evt->fd == subac->c.fd) {
```

```
if( evt->revents & POLLIN)
    redisAsyncHandleRead( subac);
if( evt->revents & POLLOUT)
    redisAsyncHandleWrite( subac);
}
if( evt->fd == roac->c.fd) {
    if( evt->revents & POLLIN)
        redisAsyncHandleRead( roac);
    if( evt->revents & POLLOUT)
        redisAsyncHandleWrite( roac);
}
if( evt->fd == wrac->c.fd) {
    if( evt->revents & POLLIN)
        redisAsyncHandleRead( wrac);
    if( evt->revents & POLLIN)
        redisAsyncHandleRead( wrac);
    if( evt->revents & POLLOUT)
        redisAsyncHandleWrite( wrac);
}
pthread_mutex_unlock( &lsredis_mutex);
```

7.7.2.12 int lsredis_find_preset (char * base, char * preset_name, double * dval)

Definition at line 756 of file Isredis.c.

```
char s[512];
int i;
int err:
ENTRY htab_input, *htab_output;
lsredis_obj_t *p;
for( i=0; i<1024; i++) {</pre>
  snprintf(s, sizeof(s)-1, "%s.%s.presets.%d.name", lsredis_head
    , base, i);
  s[sizeof(s)-1] = 0;
  htab_input.key = s;
htab_input.data = NULL;
  err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab)
  if( err == 0) {
    // We've run out of names to look for: done
    lslogging_log_message( "lsredis_find_preset: no
     preset for motor %s named '%s'", base, preset_name);
    *dval = 0.0;
    return 0:
  // Check if we have a match
  p = htab_output->data;
  if( lsredis_cmpstr( p, preset_name) == 0) {
   // got a match, now look for the position
   snprintf( s, sizeof( s)-1, "%s.%s.presets.%d.position", lsredis_head
    , base, i);
    s[sizeof(s)-1] = 0;
    htab_input.key = s;
htab_input.data = NULL;
    err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab
    if( err == 0) {
       // Name but not position? odd.
      lslogging_log_message( "lsredis_find_preset:
Error, motor %s preset '%s' has no position defined", base, preset_name);
       *dval = 0.0;
      return 0;
    p = htab_output->data;
     *dval = lsredis_getd( p);
    return 1;
  }
// How'd we get here?
// did someone really define that many presets? And then looked for one
      that's not there?
*dval = 0;
return 0;
```

```
7.7.2.13 | Isredis_obj_t* | Isredis_get_obj ( char * fmt, ... )
```

Definition at line 524 of file Isredis.c.

```
lsredis_obj_t *rtn;
va_list arg_ptr;
char k[512];
char *kp;
int nkp;
va_start( arg_ptr, fmt);
vsnprintf( k, sizeof(k)-1, fmt, arg_ptr);
k[sizeof(k)-1] = 0;
va_end( arg_ptr);
nkp = strlen(k) + strlen( lsredis_head) + 16;
                                                                 // 16
is overkill. I know. Get over it.
kp = calloc( nkp, sizeof( char));
if ( kp == NULL) {
 lslogging_log_message( "lsredis_get_obj: Out of memory
  exit( -1);
snprintf( kp, nkp-1, "%s.%s", lsredis_head, k);
kp[nkp-1] = 0;
pthread_mutex_lock( &lsredis_mutex);
while( lsredis_running == 0)
 pthread_cond_wait( &lsredis_cond, &lsredis_mutex);
rtn = _lsredis_get_obj( kp);
pthread_mutex_unlock( &lsredis_mutex);
free( kp);
return rtn;
```

7.7.2.14 char** lsredis_get_string_array (lsredis_obj_t * p)

Definition at line 365 of file Isredis.c.

```
char **rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->avalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.7.2.15 int lsredis_getb (lsredis_obj t * p)

Definition at line 378 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);
rtn = p->bvalue;
pthread_mutex_unlock( &p->mutex);
return rtn;
```

```
7.7.2.16 char lsredis_getc ( lsredis_obj_t * p )
```

Definition at line 391 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->cvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.7.2.17 double lsredis_getd (lsredis_obj_t * p)

Definition at line 339 of file Isredis.c.

```
double rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);
rtn = p->dvalue;
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.7.2.18 long int lsredis_getl (lsredis_obj t * p)

Definition at line 352 of file Isredis.c.

```
long int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->lvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.7.2.19 char* lsredis_getstr (lsredis_obj_t * p)

return a copy of the key's string value

Definition at line 263 of file Isredis.c.

```
char *rtn;

//
// Have to use strdup since we cannot guarantee that p->value won't be freed
    while the caller is still using it
//
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
    pthread_cond_wait( &p->cond, &p->mutex);

rtn = strdup(p->value);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.7 Isredis.c File Reference 221

7.7.2.20 void lsredis_hgetCB (redisAsyncContext * ac, void * reply, void * privdata)

Definition at line 404 of file Isredis.c.

```
{
redisReply *r;
lsredis_obj_t *p;
r = reply;
p = privdata;
// lslogging_log_message( "hgetCB: %s %s", p == NULL ? "<NULL>" : p->key, r->type == REDIS_REPLY_STRING ? r->str : "Non-string value. Why?");
//
// Apparently this item does not exist
^{\prime\prime} // Just set it to an empty string so at least other apps will have the same
      behaviour as us
// TODO: figure out a better way to deal with missing key/values
if( p != NULL && r->type == REDIS_REPLY_NIL) {
   lsredis_setstr( p, "");
  return;
if( p != NULL && r->type == REDIS_REPLY_STRING && r->str != NULL) {
  pthread_mutex_lock( &p->mutex);
  _lsredis_set_value( p, r->str);
  pthread_cond_signal( &p->cond);
  pthread_mutex_unlock( &p->mutex);
```

7.7.2.21 void lsredis_init (char * pub, char * re, char * head)

Initialize this module, that is, set up the connections.

Parameters

pub	Publish under this (unique) name	
re	Regular expression to select keys we want to mirror	
head	Prepend this (+ a dot) to the beginning of requested objects	

Definition at line 810 of file Isredis.c.

```
int err;
int nerrmsq;
char *errmsg;
\ensuremath{//} set up hash map to store redis objects
err = hcreate_r( 8192, &lsredis_htab);
if( err == 0) {
 lslogging_log_message( "lsredis_init: Cannot create
    hash table. Really bad things are going to happen. hcreate_r returned %d", err);
lsredis_head
                = strdup( head);
lsredis_publisher = strdup( pub);
pthread_cond_init( &lsredis_cond, NULL);
subac = redisAsyncConnect("127.0.0.1", 6379);
if( subac->err) {
  lslogging_log_message( "Error: %s", subac->errstr
subfd.fd
                  = subac->c.fd:
subfd.events
                  = 0;
subac->ev.data
                   = &subfd;
```

```
subac->ev.addRead = lsredis_addRead;
subac->ev.delRead = lsredis_delRead;
subac->ev.addWrite = lsredis_addWrite;
subac->ev.delWrite = lsredis_delWrite;
subac->ev.cleanup = lsredis_cleanup;
roac = redisAsyncConnect("127.0.0.1", 6379);
  lslogging_log_message( "Error: %s", roac->errstr);
rofd.fd
                     = roac->c.fd;
                     = 0;
rofd.events
roac->ev.data
                     = &rofd;
roac->ev.addRead = lsredis_addRead;
roac->ev.delRead = lsredis_delRead;
roac->ev.addWrite = lsredis_addWrite;
roac->ev.delWrite = lsredis_delWrite;
roac->ev.cleanup = lsredis_cleanup;
//wrac = redisAsyncConnect("10.1.0.3", 6379);
wrac = redisAsyncConnect("127.0.0.1", 6379);
if( wrac->err) {
  lslogging_log_message( "Error: %s", wrac->errstr);
wrfd.fd
                      = wrac->c.fd;
                    = 0;
wrfd.events
wrac->ev.data
                     = &wrfd;
wrac->ev.addRead = lsredis addRead;
wrac->ev.delRead = lsredis_delRead;
wrac->ev.addWrite = lsredis_addWrite;
wrac->ev.delWrite = lsredis_delWrite;
wrac->ev.cleanup = lsredis_cleanup;
err = regcomp( &lsredis_key_select_regex, re,
    REG_EXTENDED);
if( err != 0) {
  nerrmsg = regerror( err, &lsredis_key_select_regex,
      NULL, 0);
   if( nerrmsg > 0) {
     errmsg = calloc( nerrmsg, sizeof( char));
nerrmsg = regerror( err, &lsredis_key_select_regex
     , errmsg, nerrmsg);
     lslogging_log_message( "lsredis_select: %s", errmsg)
     free ( errmsg);
   }
}
```

7.7.2.22 void | sredis_keysCB (redisAsyncContext * ac, void * reply, void * privdata)

Sift through the keys to find ones we like.

Add them to our list of followed objects

Definition at line 735 of file Isredis.c.

```
{
  redisReply *r;
 int i;
  r = reply;
  if( r->type != REDIS_REPLY_ARRAY) {
   lslogging_log_message( "lsredis_keysCB: exepected
      array...");
    lsredis_debugCB( ac, reply, privdata);
   return;
  for( i=0; i< (int)r->elements; i++) {
   if( r->element[i]->type != REDIS_REPLY_STRING) {
     lslogging_log_message( "lsredis_keysCB: exected
      string...");
     lsredis_debugCB( ac, r->element[i], privdata);
    } else {
     lsredis maybe add kev( r->element[i]->str);
}
```

7.7 Isredis.c File Reference 223

7.7.2.23 void lsredis_maybe_add_key (char * k)

Definition at line 727 of file Isredis.c.

```
if( regexec( &lsredis_key_select_regex, k, 0, NULL, 0
     ) == 0) {
    _lsredis_get_obj( k);
}
```

7.7.2.24 int Isredis_regexec (const regex_t * preg, Isredis_obj_t * p, size_t nmatch, regmatch_t * pmatch, int eflags)

Definition at line 247 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = regexec( preg, p->value, nmatch, pmatch, eflags);
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.7.2.25 void Isredis_run ()

Definition at line 1014 of file Isredis.c.

7.7.2.26 void lsredis_set_value ($lsredis_obj_t * p$, char * fmt, ...)

Set the value of a redis object and make it valid.

Called by mgetCB to set the value as it is in redis Maybe TODO: we've arbitrarily set the maximum size of a value here. Although I cannot imagine needed bigger values it would not be a big deal to enable it.

Definition at line 207 of file Isredis.c.

```
va_list arg_ptr;
char v[512];

va_start( arg_ptr, fmt);
vsnprintf( v, sizeof(v)-1, fmt, arg_ptr);
va_end( arg_ptr);

v[sizeof(v)-1] = 0;

pthread_mutex_lock( &p->mutex);

_lsredis_set_value( p, v);

pthread_cond_signal( &p->cond);
pthread_mutex_unlock( &p->mutex);
```

```
7.7.2.27 void lsredis_setstr ( lsredis_obj_t * p, char * fmt, ... )
```

Set the value and update redis.

Note that Isredis_set_value sets the value based on redis while here we set redis based on the value Arbitray maximum string length set here. TODO: Probably this limit should be removed at some point.

redisAsyncCommandArgv used instead of redisAsyncCommand 'cause it's easier (and possible) to deal with strings that would otherwise cause hiredis to emit a bad command, like those containing spaces. < up the count of times we need to see ourselves published before we start listening to others again

- < Unlock to prevent deadlock in case the service routine needs to set our value
- < redisAsyncCommandArgv shouldn't need to access this after it's made up it's packet (before it returns) so we should be OK with this location disappearing soon.

Definition at line 288 of file Isredis.c.

```
va_list arg_ptr;
char v[512];
char *argv[4];
va_start( arg_ptr, fmt);
vsnprintf( v, sizeof(v)-1, fmt, arg_ptr);
v[sizeof(v)-1] = 0;
va_end( arg_ptr);
pthread_mutex_lock( &p->mutex);
// Don't send an update if a good value has not changed
if( p->valid && strcmp( v, p->value) == 0) {
  // nothing to do
  pthread_mutex_unlock( &p->mutex);
p->wait for me++;
pthread mutex unlock( &p->mutex);
argv[0] = "HSET";
argv[1] = p->key;
argv[2] = "VALUE";
argv[3] = v;
pthread_mutex_lock( &lsredis_mutex);
while( lsredis_running == 0)
 pthread_cond_wait( &lsredis_cond, &lsredis_mutex);
redisAsyncCommand( wrac, NULL, NULL, "MULTI");
redisAsyncCommandArgv( wrac, NULL, NULL, 4, (const char **)argv, NULL);
redisAsyncCommand( wrac, NULL, NULL, "PUBLISH %s %s", lsredis_publisher
     , p->key);
redisAsyncCommand( wrac, NULL, NULL, "EXEC");
pthread_mutex_unlock( &lsredis_mutex);
// Assume redis will take exactly the value we sent it
pthread_mutex_lock( &p->mutex);
_lsredis_set_value(p, v);
pthread_cond_signal(&p->cond);
pthread_mutex_unlock( &p->mutex);
```

7.7.2.28 void Isredis_sig_service (struct pollfd * evt)

Parameters

in	evt	The pollfd object that triggered this call

Definition at line 913 of file Isredis.c.

```
struct signalfd_siginfo fdsi;

//
// Really, we don't care about the signal,
// it's just used to drop out of the poll
// function when there is something for us
// to do.
//

read( evt->fd, &fdsi, sizeof( struct signalfd_siginfo));
}
```

7.7.2.29 void lsredis_subCB (redisAsyncContext * ac, void * reply, void * privdata)

Use the publication to request the new value.

Definition at line 635 of file Isredis.c.

```
{
redisReply *r;
lsredis_obj_t *p;
char *k;
char *publisher;
ENTRY htab_input, *htab_output;
int err;
r = (redisReply *)reply;
// Ignore our psubscribe reply
if( r->type == REDIS_REPLY_ARRAY && r->elements == 3 && r->element[0]->type
    == REDIS_REPLY_STRING && strcmp( r->element[0]->str, "psubscribe")==0)
// But log other stuff we don't understand
if( r->type != REDIS_REPLY_ARRAY ||
    r->elements != 4 ||
r->element[3]->type != REDIS_REPLY_STRING ||
    r->element[2]->type != REDIS_REPLY_STRING) {
  lslogging_log_message( "lsredis_subCB: unexpected
    reply");
  lsredis_debugCB( ac, reply, privdata);
  return;
// Ignore obvious junk
k = r - > element[3] - > str;
if(k == NULL || *k == 0)
 return;
//
// see if we care
if( regexec( &lsredis_key_select_regex, k, 0, NULL, 0
  ) == 0) {
//
  // We should know about this one
 htab_input.key = k;
htab_input.data = NULL;
  errno = 0;
  err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab)
  ;
if( err == 0 && errno == ESRCH)
   p = NULL;
   p = htab_output->data;
  if( p == NULL) {
    _lsredis_get_obj( k);
  } else {
```

```
// Look who's talk'n
     publisher = r->element[2]->str;
     pthread_mutex_lock( &p->mutex);
     if( p->wait_for_me) {
        // see if we are done waiting
        if( strcmp( publisher, lsredis_publisher) == 0)
          p->wait_for_me--;
       pthread_mutex_unlock( &p->mutex);
        ^{\prime\prime} // Don't get a new value, either we set it last or we are still waiting
      for redis to report
       // our publication //
       return;
     // Here we know our value is out of date
     p->valid = 0;
     lsevents_send_event( "%s Invalid", p->events_name
     pthread_mutex_unlock( &p->mutex);
     //
// We shouldn't get here if wait_for_me is zero and we are the publisher.
// '' '' '' '' did an heat with out incrementing wait_for_me
     // If somehow we did (ie we did an hset with out incrementing wait_for_me or if we published too many times), it shouldn't hurt to get the value again.
     redisAsyncCommand( roac, lsredis_hgetCB, p, "HGET %s
      VALUE", k);
}
```

7.7.2.30 void* Isredis_worker (void * dummy)

subscribe to changes and service sockets

- < poll timeout, in millisecs (of course)
- < array of pollfd's for the poll function, one entry per connection
- < number of active elements in fda

Definition at line 932 of file Isredis.c.

```
static int poll_timeout_ms = -1;
static struct pollfd fda[4];
static int nfda = 0;
static sigset_t our_sigset;
int pollrtn;
pthread_mutex_lock( &lsredis_mutex);
// block ordinary signal mechanism
sigemptyset( &our_sigset);
sigaddset( &our_sigset, SIGUSR1);
pthread_sigmask( SIG_BLOCK, &our_sigset, NULL);
// Set up fd mechanism
fda[0].fd = signalfd( -1, &our_sigset, SFD_NONBLOCK);
if ( fda[0].fd == -1) {
  char *es;
  es = strerror( errno);
  lslogging_log_message( "lsredis_worker: Signalfd
     trouble '%s'", es);
fda[0].events = POLLIN;
nfda = 1;
lsredis_running = 1;
```

```
if( redisAsyncCommand( subac, lsredis_subCB, NULL, "
    PSUBSCRIBE REDIS_KV_CONNECTOR UI* MD2-*") == REDIS_ERR) {
    lslogging_log_message( "Error sending PSUBSCRIBE
      command");
redisAsyncCommand( roac, lsredis_keysCB, NULL, "KEYS *");
pthread_cond_signal( &lsredis_cond);
pthread_mutex_unlock( &lsredis_mutex);
while(1) {
  nfda = 1;
   pthread_mutex_lock( &lsredis_mutex);
   if( subfd.fd != -1) {
  fda[nfda].fd =
     fda[nfda].fd = subfd.fd;
fda[nfda].events = subfd.events;
     fda[nfda].revents = 0;
  if( rofd.fd != -1) {
  fda[nfda].fd = rofd.fd;
  fda[nfda].events = rofd.events;
     fda[nfda].revents = 0;
   nfda++;
  if( wrfd.fd != -1) {
  fda[nfda].fd = wrfd.fd;
  fda[nfda].events = wrfd.events;
     fda[nfda].revents = 0;
     nfda++;
   pthread_mutex_unlock( &lsredis_mutex);
  pollrtn = poll( fda, nfda, poll_timeout_ms);
   if( pollrtn && fda[0].revents) {
     lsredis_sig_service( &(fda[0]));
     pollrtn--;
   for( i=1; i<nfda; i++) {</pre>
    if( fda[i].revents) {
        lsredis_fd_service( &(fda[i]));
   }
}
```

7.7.2.31 void redisDisconnectCB (const redisAsyncContext * ac, int status)

call back in case a redis server becomes disconnected TODO: reconnect

Definition at line 560 of file Isredis.c.

7.7.3 Variable Documentation

7.7.3.1 pthread_cond_t | static |

Definition at line 75 of file Isredis.c.

```
7.7.3.2 char* lsredis_head = NULL [static]
```

Definition at line 88 of file Isredis.c.

```
7.7.3.3 struct hsearch_data lsredis_htab [static]
Definition at line 80 of file Isredis.c.
7.7.3.4 regex_t | sredis_key_select_regex [static]
Definition at line 87 of file Isredis.c.
7.7.3.5 pthread_mutex_t | sredis_mutex = PTHREAD_RECURSIVE_MUTEX_INITIALIZER_NP [static]
Definition at line 73 of file Isredis.c.
7.7.3.6 Isredis_obj_t* Isredis_objs = NULL [static]
Definition at line 79 of file Isredis.c.
7.7.3.7 char* lsredis_publisher = NULL [static]
Definition at line 86 of file Isredis.c.
7.7.3.8 int lsredis_running = 0 [static]
Definition at line 76 of file Isredis.c.
7.7.3.9 pthread_t | sredis_thread [static]
Definition at line 71 of file Isredis.c.
7.7.3.10 redisAsyncContext* roac [static]
Definition at line 83 of file Isredis.c.
7.7.3.11 struct pollfd rofd [static]
Definition at line 91 of file Isredis.c.
7.7.3.12 redisAsyncContext* subac [static]
Definition at line 82 of file Isredis.c.
7.7.3.13 struct pollfd subfd [static]
Definition at line 90 of file Isredis.c.
7.7.3.14 redisAsyncContext* wrac [static]
Definition at line 84 of file Isredis.c.
```

7.8 Istimer.c File Reference 229

```
7.7.3.15 struct pollfd wrfd [static]
```

Definition at line 92 of file Isredis.c.

7.8 Istimer.c File Reference

Support for delayed and periodic events.

```
#include "pgpmac.h"
```

Data Structures

· struct lstimer_list_struct

Everything we need to know about a timer.

Macros

• #define LSTIMER_LIST_LENGTH 1024

We'll allow this many timers. This should be way more than enough.

#define LSTIMER_RESOLUTION_NSECS 100000

times within this amount in the future are considered "now" and the events should be called

Typedefs

typedef struct lstimer_list_struct lstimer_list_t

Everything we need to know about a timer.

Functions

· void Istimer_add_timer (char *event, int shots, unsigned long int secs, unsigned long int nsecs)

Create a timer.

• static void service_timers ()

Send events that are past due, due, or just about to be due.

static void handler (int sig, siginfo_t *si, void *dummy)

Service the signal.

static void * Istimer_worker (void *dummy)

Our worker.

• void lstimer_init ()

Initialize the timer list and pthread stuff.

• void lstimer_run ()

Start up our thread.

Variables

• static int lstimer_active_timers = 0

count of the number timers we are tracking

• static Istimer list t Istimer list [LSTIMER LIST LENGTH]

Our timer list.

static pthread_t lstimer_thread

the timer thread

• static pthread_mutex_t lstimer_mutex

protect the timer list

· static pthread cond t Istimer cond

allows us to be idle when there is nothing to do

· static timer_t lstimer_timerid

our real time timer

• static int new timer = 0

indicate that a new timer exists and a call to service_timers is required

7.8.1 Detailed Description

Support for delayed and periodic events.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file Istimer.c.

7.8.2 Macro Definition Documentation

7.8.2.1 #define LSTIMER_LIST_LENGTH 1024

We'll allow this many timers. This should be way more than enough.

Definition at line 11 of file Istimer.c.

7.8.2.2 #define LSTIMER_RESOLUTION_NSECS 100000

times within this amount in the future are considered "now" and the events should be called Definition at line 16 of file Istimer.c.

7.8.3 Typedef Documentation

7.8.3.1 typedef struct Istimer list struct Istimer list t

Everything we need to know about a timer.

7.8.4 Function Documentation

7.8.4.1 static void handler (int sig, $siginfo_t * si$, void * dummy) [static]

Service the signal.

Definition at line 174 of file Istimer.c.

```
pthread_mutex_lock( &lstimer_mutex);
service_timers();
pthread_mutex_unlock( &lstimer_mutex);
```

7.8.4.2 void Istimer_add_timer (char * event, int shots, unsigned long int secs, unsigned long int nsecs)

Create a timer.

Parameters

event	Name of the event to send when the timer goes off	
shots	Number of times to run. 0 means never, -1 means forever	
secs	secs Number of seconds to wait	
nsecs	Number of nano-seconds to run in addition to secs	

Definition at line 50 of file Istimer.c.

```
{
int i:
struct timespec now;
\ensuremath{//} Time we were called. Delay is based on call time, not queued time
clock gettime ( CLOCK REALTIME, &now);
pthread_mutex_lock( &lstimer_mutex);
for( i=0; i<LSTIMER_LIST_LENGTH; i++) {</pre>
 if( lstimer_list[i].shots == 0)
   break;
if( i == LSTIMER_LIST_LENGTH) {
 pthread_mutex_unlock( &lstimer_mutex);
 strncpy( lstimer_list[i].event, event, LSEVENTS_EVENT_LENGTH
    - 1);
lstimer_list[i].event[LSEVENTS_EVENT_LENGTH
    -1] = 0;
lstimer_list[i].shots
                          = shots;
lstimer_list[i].delay_secs = secs;
lstimer_list[i].delay_nsecs = nsecs;
lstimer_list[i].next_secs = secs +
   now.tv_nsec + nsecs) / 1000000000;
                          = secs + now.tv_sec + (
lstimer_list[i].next_nsecs = (now.tv_nsec + nsecs
   ) % 1000000000;
                         = 0;
lstimer_list[i].last_secs
lstimer_list[i].last_nsecs = 0;
lstimer_list[i].init_nsecs = now.tv_nsec;
if ( shots != 0) {
 lstimer_active_timers++;
 new_timer++;
pthread_cond_signal( &lstimer_cond);
pthread_mutex_unlock( &lstimer_mutex);
```

7.8.4.3 void Istimer_init ()

Initialize the timer list and pthread stuff.

Definition at line 259 of file Istimer.c.

```
for( i=0; i<LSTIMER_LIST_LENGTH; i++) {
  lstimer_list[i].shots = 0;
}

pthread_mutex_init( &lstimer_mutex, NULL);
pthread_cond_init( &lstimer_cond, NULL);</pre>
```

7.8.4.4 void lstimer_run ()

Start up our thread.

Definition at line 273 of file Istimer.c.

```
pthread_create( &lstimer_thread, NULL, lstimer_worker
    , NULL);
}
```

7.8.4.5 static void* lstimer_worker (void * dummy) [static]

Our worker.

The main loop runs when a new timer is added. The service routine deals with maintenance.

Parameters

in	dummy	required by protocol
----	-------	----------------------

Definition at line 184 of file Istimer.c.

```
int
 known_timers;
struct sigevent sev;
struct sigaction sa;
sigset_t mask;
// See example at
    http://www.kernel.org/doc/man-pages/online/pages/man2/timer_create.2.html
// Set up hander
sa.sa_flags = SA_SIGINFO;
sa.sa_sigaction = handler;
sigemptyset(&sa.sa_mask);
 failed");
 exit(-1);
// Create the timer
sev.sigev_notify = SIGEV_SIGNAL;
sev.sigev_signo = SIGRTMIN;
sev.sigev_value.sival_ptr = &lstimer_timerid;
timer_create( CLOCK_REALTIME, &sev, &lstimer_timerid);
```

```
// Block timer signal for now since we really
// want to be sure we do not own a lock on the timer mutex
// while servicing the signal
sigemptyset ( &mask);
sigaddset( &mask, SIGRTMIN);
known_timers = 0;
while(1) {
 pthread_mutex_lock( &lstimer_mutex);
  while( new_timer == 0)
    pthread_cond_wait( &lstimer_cond, &lstimer_mutex
  // ignore signals so we don't service the signal while we are already in
    the
  // service routine
  sigprocmask( SIG_SETMASK, &mask, NULL);
  // Setting up the timer interval is in the handler
  // so just call it
  service_timers();
  // Reset our flag
  new_timer = 0;
  pthread_mutex_unlock( &lstimer_mutex);
  // Let the signals rain down
  sigprocmask( SIG_UNBLOCK, &mask, NULL);
```

7.8.4.6 static void service_timers () [static]

Send events that are past due, due, or just about to be due.

Definition at line 102 of file Istimer.c.

```
int
  found_active;
lstimer_list_t *p;
struct timespec now, then, soonest;
struct itimerspec its;
// Did I remind you not to let this thread own the 1stimer mutex outside of
     this
// service routine when SIGRTMIN is active?
// Call with lstimer_mutex locked
clock_gettime( CLOCK_REALTIME, &now);
// Project a tad into the future
then.tv_sec = now.tv_sec + (now.tv_nsec + LSTIMER_RESOLUTION_NSECS
) / 1000000000;
then.tv_nsec = (now.tv_nsec + LSTIMER_RESOLUTION_NSECS
   ) % 1000000000;
found_active = 0;
for( i=0; i<lstimer_active_timers; i++) {</pre>
  p = &(lstimer_list[i]);
  if( p->shots != 0) {
    found_active++;
    if( p->next_secs < then.tv_sec || (p->next_secs ==
    then.tv_sec && p->next_nsecs <= then.tv_nsec)) {</pre>
```

```
lsevents_send_event( p->event);
      // After sending the event, compute the next time we need to do this
      p->last_secs = now.tv_sec;
      p->last_nsecs = now.tv_nsec;
      p->ncalls++;
      // Decrement non-infinite loops
      if( p->shots != -1)
       p->shots--;
      if(p\rightarrow shots == 0) {
        // Take this timer out of the mix
        lstimer_active_timers--;
    p->next_secs = p->init_secs + (p->ncalls+1)
* p->delay_secs + (p->init_nsecs + (p->ncalls+1)*p->
    delay_nsecs)/1000000000;
       p->next_nsecs = (p->init_nsecs + (p->ncalls
    +1)*p->delay_nsecs) % 1000000000;
   }
    if( found_active == 1) {
     soonest.tv_sec = p->next_secs;
      soonest.tv_nsec = p->next_nsecs;
      if( soonest.tv_sec > p->next_secs || (soonest.tv_sec == p->
   next_secs && soonest.tv_nsec > p->next_nsecs)) {
    soonest.tv_sec = p->next_secs;
       soonest.tv_nsec = p->next_nsecs;
   }
 }
if( soonest.tv_sec != 0) {
 its.it_interval.tv_nsec = 0;
 timer_settime( lstimer_timerid, TIMER_ABSTIME, &its, NULL);
```

7.8.5 Variable Documentation

7.8.5.1 int lstimer_active_timers = 0 [static]

count of the number timers we are tracking

Definition at line 18 of file Istimer.c.

7.8.5.2 pthread_cond_t lstimer_cond [static]

allows us to be idle when there is nothing to do

Definition at line 40 of file Istimer.c.

7.8.5.3 Istimer_list_t Istimer_list[LSTIMER_LIST_LENGTH] [static]

Our timer list.

Definition at line 36 of file Istimer.c.

7.8.5.4 pthread_mutex_t lstimer_mutex [static]

protect the timer list

Definition at line 39 of file Istimer.c.

```
7.8.5.5 pthread_t lstimer_thread [static]
the timer thread
Definition at line 38 of file Istimer.c.
7.8.5.6 timer_t lstimer_timerid [static]
our real time timer
Definition at line 41 of file Istimer.c.
7.8.5.7 int new_timer = 0 [static]
```

indicate that a new timer exists and a call to service_timers is required

Definition at line 42 of file Istimer.c.

md2cmds.c File Reference 7.9

Implements commands to run the md2 diffractometer attached to a PMAC controled by postgresql.

```
#include "pgpmac.h"
```

Functions

- void md2cmds_home_prep ()
- int md2cmds_home_wait (double timeout_secs)
- void md2cmds_move_prep ()

prepare for new movements

int md2cmds move wait (double timeout secs)

Wait for all the motions requested to complete.

int md2cmds_is_moving ()

returns non-zero if we think a motor is moving, 0 otherwise

- double md2cmds_prep_axis (lspmac_motor_t *mp, double pos)
- void md2cmds_organs_move_presets (char *pay, char *paz, char *pcy, char *pcz, char *psz)
- void md2cmds_transfer ()

Transfer a sample.

int md2cmds_moveAbs (const char *ccmd)

Move a motor to the position requested.

void md2cmds_phase_change (const char *ccmd)

Move md2 devices to a preconfigured state.

void md2cmds_mvcenter_move (double cx, double cy, double ax, double az)

Move the centering and alignment tables.

void md2cmds_maybe_done_moving_cb (char *event)

Track how many motors are moving.

void md2cmds_maybe_done_homing_cb (char *event)

Track motors homing.

- void md2cmds_kappaphi_move (double kappa_deg, double phi_deg)
- void md2cmds collect ()

Collect some data.

void md2cmds_rotate ()

Spin 360 and make a video (recenter first, maybe)

void md2cmds_rotate_cb (char *event)

Tell the database about the time we went through omega=zero.

void md2cmds_maybe_rotate_done_cb (char *event)

Now that we are done with the 360 rotation lets rehome right quick.

void md2cmds_set_scale_cb (char *event)

Fix up xscale and yscale when zoom changes.

void md2cmds center ()

Move centering and alignment tables as requested TODO: Implement.

void md2cmds_time_capz_cb (char *event)

Time the capillary motion for the transfer routine.

- int md2cmds_action_queue (double timeout, char *action)
- void md2cmds abort ()
- void md2cmds_action_wait ()

pause until md2cmds_worker has finished running the command

void * md2cmds_worker (void *dummy)

Our worker thread.

- void md2cmds coordsys 1 stopped cb (char *event)
- void md2cmds_coordsys_2_stopped_cb (char *event)
- void md2cmds_coordsys_3_stopped_cb (char *event)
- void md2cmds_coordsys_4_stopped_cb (char *event)
- void md2cmds_coordsys_5_stopped_cb (char *event)
- void md2cmds_coordsys_7_stopped_cb (char *event)
- void md2cmds_init ()

Initialize the md2cmds module.

void md2cmds_run ()

Start up the thread.

Variables

• pthread_cond_t md2cmds_cond

condition to signal when it's time to run an md2 command

pthread_mutex_t md2cmds_mutex

mutex for the condition

- int md2cmds_moving_queue_wait = 0
- pthread_cond_t md2cmds_moving_cond

wait for command to have been dequeued and run

• pthread_mutex_t md2cmds_moving_mutex

message passing between md2cmds and pg

• int md2cmds_homing_count = 0

We've asked a motor to home.

pthread_cond_t md2cmds_homing_cond

coordinate homing and homed

pthread_mutex_t md2cmds_homing_mutex

our mutex;

- int md2cmds moving count = 0
- char md2cmds cmd [MD2CMDS CMD LENGTH]

our command:

- Isredis_obj_t * md2cmds_md_status_code
- · static pthread t md2cmds thread
- static int rotating = 0

flag: when omega is in position after a rotate we want to re-home omega

static double md2cmds_capz_moving_time = NAN

7.9.1 Detailed Description

Implements commands to run the md2 diffractometer attached to a PMAC controled by postgresql.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file md2cmds.c.

7.9.2 Function Documentation

7.9.2.1 void md2cmds_abort ()

Definition at line 1270 of file md2cmds.c.

7.9.2.2 int md2cmds_action_queue (double timeout, char * action)

Definition at line 1235 of file md2cmds.c.

```
int rtn;
struct timespec waitforit;

if( timeout < 0.0) {
   rtn = pthread_mutex_lock( &md2cmds_mutex);
} else {
   clock_gettime( CLOCK_REALTIME, &waitforit);
}</pre>
```

```
waitforit.tv_sec += floor(timeout);
  waitforit.tv_nsec += (timeout - waitforit.tv_sec)*1.e9;
  while( waitforit.tv_nsec >= 1000000000) {
    waitforit.tv_sec++;
    waitforit.tv_nsec -= 1000000000;
 rtn = pthread_mutex_timedlock( &md2cmds_mutex, &waitforit);
if( rtn == 0) {
  strncpy( md2cmds_cmd, action, MD2CMDS_CMD_LENGTH
  md2cmds\_cmd[MD2CMDS\_CMD\_LENGTH-1] = 0;
 pthread_cond_signal( &md2cmds_cond);
 pthread_mutex_unlock( &md2cmds_mutex);
 else {
  if( rtn == ETIMEDOUT)
   lslogging_log_message( "md2cmds_action_queue: %s not
queued, operation timed out", action);
   lslogging_log_message( "md2cmds_action_queue: %s not
     queued with error code %d", action, rtn);
return rtn;
```

7.9.2.3 void md2cmds_action_wait ()

pause until md2cmds_worker has finished running the command

Definition at line 1300 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_mutex);
pthread_mutex_unlock( &md2cmds_mutex);
}
```

7.9.2.4 void md2cmds_center ()

Move centering and alignment tables as requested TODO: Implement.

Definition at line 1199 of file md2cmds.c.

```
}
```

7.9.2.5 void md2cmds_collect ()

Collect some data.

- < index of shot to be taken
- < Exposure time (saved to compute shutter timeout)
- < start cnts
- < delta cnts
- < omega velocity cnts/msec
- < acceleration time (msec)
- < exposure time (msec)
- < one of the stages, at least, needs to be moved
- < unit to counts conversion

- < nominal zero offset
- < maximum acceleration allowed for omega
- < current kappa position in case we need to move phi only
- < current phi position in case we need to move kappa only
- < setup timeouts for shutter

Definition at line 779 of file md2cmds.c.

```
long long skey;
double exp_time;
double p170;
double p171;
double p173;
double p175;
double p180;
int center_request;
double u2c;
double neutral_pos;
double max_accel;
double kappa_pos;
double phi_pos;
struct timespec now, timeout;
int err:
u2c
            = lsredis_getd( omega->u2c);
neutral_pos = lsredis_getd( omega->neutral_pos);
max_accel = lsredis_getd( omega->max_accel);
md2cmds_move_prep();
md2cmds_organs_move_presets( "In", "In", "In", "In
    ", "Cover");
if( md2cmds_move_wait( 30.0)) {
  lslogging_log_message( "md2cmds_collect: Timed out
  waiting for organs to move. Aborting data collection.");
lsevents_send_event( "Data Colection Aborted");
  return;
// reset shutter has opened flag
lspmac_SockSendDPline( NULL, "P3001=0 P3002=0");
while(1) {
  lspg_nextshot_call();
  lspg_nextshot_wait();
  exp_time = lspg_nextshot.dsexp;
  if( lspg_nextshot.no_rows_returned) {
    lspg_nextshot_done();
    break;
  skey = lspg_nextshot.skey;
  lspg_query_push( NULL, "SELECT px.shots_set_state(%11d,
    'Preparing')", skey);
  center request = 0;
  if( lspg_nextshot.active) {
    if(
        // \mbox{Don't} move if we are within 0.1 microns of our destination
        (fabs( lspg_nextshot.cx - cenx->position) >
     0.1) ||
        (fabs( lspg_nextshot.cy - ceny->position) >
        (fabs( lspg_nextshot.ax - alignx->position
    ) > 0.1) | |
        (fabs( lspg_nextshot.ay - aligny->position
    ) > 0.1) ||
        (fabs( lspg_nextshot.az - alignz->position
       center_request = 1;
       lslogging_log_message( "md2cmds_collect: moving
     center to cx=%f, cy=%f, ax=%f, ay=%f, az=%f",lspg_nextshot.cx,
    lspg_nextshot.cy, lspg_nextshot.ax, lspg_nextshot
```

```
.ay, lspg_nextshot.az);
    md2cmds_move_prep();
    md2cmds_mvcenter_move( lspg_nextshot.
  cx, lspg_nextshot.cy, lspg_nextshot.ax,
  lspg_nextshot.ay, lspg_nextshot.az);
if( md2cmds_move_wait( 2.0)) {
      lslogging_log_message( "md2cmds_collect: Timed
   out waiting for alignment or centering stage (or both) to stop moving. Aborting
   data collection.");
      lsevents_send_event( "Data Colection Aborted");
      return:
 }
}
// Maybe move kappa and/or phi
if( !lspg_nextshot.dsphi_isnull || !lspg_nextshot
  .dskappa_isnull) {
  kappa_pos = lspg_nextshot.dskappa_isnull ?
  lspmac_getPosition( kappa) : lspg_nextshot.
  dskappa;
             = lspg_nextshot.dsphi_isnull
  phi_pos
  lspmac_getPosition(phi): lspg_nextshot.
  lslogging_log_message( "md2cmds_collect: move
phy/kappa: kappa=%f phi=%f", kappa_pos, phi_pos);
  md2cmds_move_prep();
md2cmds_kappaphi_move( kappa_pos, phi_pos);
  if ( md2cmds_move_wait ( 30.0)) {
       lslogging_log_message( "md2cmds_collect: Timed
   out waiting for kappa or phi (or both) to stop moving. Aborting data collection.
  ");
      lsevents_send_event( "Data Colection Aborted");
      return;
  }
// Calculate the parameters we'll need to run the scan
p180 = lspg_nextshot.dsexp * 1000.0;
p170 = u2c * (lspg_nextshot.sstart + neutral_pos);
p171 = u2c * lspg_nextshot.dsowidth;
p173 = fabs(p180) < 1.e-4 ? 0.0 : u2c * lspg_nextshot.dsowidth
   / p180;
p175 = p173/max_accel;
// free up access to nextshot
lspg_nextshot_done();
// prepare the database and detector to expose
// On exit we own the diffractometer lock and
// have checked that all is OK with the detector
lspg_seq_run_prep_all( skey,
                          kappa->position,
                          phi->position,
                          cenx->position,
                          ceny->position,
                          alignx->position.
                          aligny->position,
                          alignz->position
// make sure our opened flag is down
// wait for the p3001=0 command to be noticed
clock_gettime( CLOCK_REALTIME, &now);
timeout.tv_sec = now.tv_sec + 10;
timeout.tv_nsec = now.tv_nsec;
pthread_mutex_lock( &lspmac_shutter_mutex);
while( err == 0 && lspmac_shutter_has_opened == 1)
  err = pthread_cond_timedwait( &lspmac_shutter_cond, &
lspmac_shutter_mutex, &timeout);
pthread_mutex_unlock( &lspmac_shutter_mutex);
```

```
if( err == ETIMEDOUT) {
  pthread_mutex_unlock( &lspmac_shutter_mutex);
  lslogging_log_message( "md2cmds_collect: Timed out
  waiting for shutter to open. Data collection aborted.");
lsevents_send_event( "Data Collection Aborted");
  return;
// Start the exposure
md2cmds_move_prep();
lspmac_SockSendDPline( "Exposure", "&1 P170=%.1f
   P171=%.1f P173=%.1f P174=0 P175=%.1f P176=0 P177=1 P178=0 P180=%.1f M431=1 &1B131R",
                           p170, p171, p173,
                      p180);
// We could look for the "Exposure command accepted" event at this point.
\ensuremath{//} wait for the shutter to open
clock_gettime( CLOCK_REALTIME, &now);
timeout.tv_sec = now.tv_sec + 10;
timeout.tv_nsec = now.tv_nsec;
err = 0;
pthread_mutex_lock( &lspmac_shutter_mutex);
while( err == 0 && lspmac_shutter_has_opened == 0)
  err = pthread_cond_timedwait( &lspmac_shutter_cond, &
  lspmac_shutter_mutex, &timeout);
if( err == ETIMEDOUT) {
  pthread_mutex_unlock( &lspmac_shutter_mutex);
  lslogging_log_message( "md2cmds_collect: Timed out
   waiting for shutter to open. Data collection aborted.");
  lsevents_send_event( "Data Collection Aborted");
  return;
^{\prime\prime} // wait for the shutter to close
clock_gettime( CLOCK_REALTIME, &now);
timeout.tv_sec = now.tv_sec + 4 + exp_time; // hopefully 4 seconds is long enough to never catch a legitimate shutter close and short enough to
   bail when something is really wrong
timeout.tv_nsec = now.tv_nsec;
while( err == 0 && lspmac_shutter_state == 1)
  err = pthread_cond_timedwait( &lspmac_shutter_cond, &
  lspmac shutter mutex, &timeout);
pthread_mutex_unlock( &lspmac_shutter_mutex);
if( err == ETIMEDOUT) {
  pthread_mutex_unlock( &lspmac_shutter_mutex);
  lslogging_log_message( "md2cmds_collect: Timed out
  waiting for shutter to close. Data collection aborted.");
lsevents_send_event( "Data Collection Aborted");
  return;
// Signal the detector to start reading out
lspg_query_push( NULL, "SELECT px.unlock_diffractometer()");
// Update the shot status
lspg_query_push( NULL, "SELECT px.shots_set_state(%11d,
   'Writing')", skey);
// reset shutter has opened flag
lspmac_SockSendDPline( NULL, "P3001=0");
^{\prime\prime} // Wait for omega to stop moving
```

```
if ( md2cmds_move_wait( 10.0)) {
      lslogging_log_message( "md2cmds_collect: Giving up
      waiting for omega to stop moving. Data collection aborted.");
lsevents_send_event( "Data Colection Aborted");
      return;
    // Move the center/alignment stages to the next position
    // TODO: position omega for the next shot. During data collection the
       motion program
    // makes a good guess but for ortho snaps it is wrong. We should add an
       argument to the motion program
    if( !lspg_nextshot.active2_isnull &&
      lspg_nextshot.active2) {
      if(
          (fabs( lspg_nextshot.cx2 - cenx->position)
       > 0.1) ||
          (fabs( lspg_nextshot.cy2 - ceny->position)
       > 0.1) ||
          (fabs( lspg_nextshot.ax2 - alignx->position
      ) > 0.1) ||
          (fabs( lspg_nextshot.ay2 - aligny->position
      ) > 0.1) ||
          (fabs( lspg_nextshot.az2 - alignz->position
      ) > 0.1)) {
        center request = 1;
        md2cmds_move_prep();
        {\tt md2cmds\_mvcenter\_move(lspg\_nextshot.}
      cx, lspg_nextshot.cy, lspg_nextshot.ax,
      lspg_nextshot.ay, lspg_nextshot.az);
  lsevents_send_event( "Data Collection Done");
7.9.2.6 void md2cmds_coordsys_1_stopped_cb ( char * event )
Definition at line 1340 of file md2cmds.c.
}
7.9.2.7 void md2cmds_coordsys_2_stopped_cb ( char * event )
Definition at line 1342 of file md2cmds.c.
}
7.9.2.8 void md2cmds_coordsys_3_stopped_cb ( char * event )
Definition at line 1344 of file md2cmds.c.
                                                     {
}
7.9.2.9 void md2cmds_coordsys_4_stopped_cb ( char * event )
Definition at line 1346 of file md2cmds.c.
}
```

```
7.9.2.10 void md2cmds_coordsys_5_stopped_cb ( char * event )
```

Definition at line 1348 of file md2cmds.c.

```
}
```

7.9.2.11 void md2cmds_coordsys_7_stopped_cb (char * event)

Definition at line 1350 of file md2cmds.c.

```
}
```

7.9.2.12 void md2cmds_home_prep ()

Definition at line 34 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_homing_mutex);
md2cmds_homing_count = -1;
pthread_mutex_unlock( &md2cmds_homing_mutex);
}
```

7.9.2.13 int md2cmds_home_wait (double timeout_secs)

Definition at line 41 of file md2cmds.c.

```
{
struct timespec timeout, now;
double isecs, fsecs;
int err;
clock_gettime( CLOCK_REALTIME, &now);
fsecs = modf( timeout_secs, &isecs);
timeout.tv_sec = now.tv_sec + (long)floor( isecs);
timeout.tv_nsec = now.tv_nsec + (long)floor( fsecs * 1.0e9);
timeout.tv_sec += timeout.tv_nsec / 1000000000;
timeout.tv_nsec %= 1000000000;
pthread_mutex_lock( &md2cmds_homing_mutex);
while( err == 0 && md2cmds_homing_count == -1)
  err = pthread_cond_timedwait( &md2cmds_homing_cond, &
    md2cmds_homing_mutex, &timeout);
if( err != 0) {
  if( err != ETIMEDOUT) {
    lslogging_log_message( "md2cmds_home_wait:
    unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
  pthread_mutex_unlock( &md2cmds_homing_mutex);
  return 1;
if( err != 0) {
  if( err != ETIMEDOUT)
    lslogging_log_message( "md2cmds_home_wait:
     unexpected error from timedwait: %d", err);
```

```
return 1;
}
return 0;
```

7.9.2.14 void md2cmds_init()

Initialize the md2cmds module.

Definition at line 1356 of file md2cmds.c.

7.9.2.15 int md2cmds_is_moving ()

returns non-zero if we think a motor is moving, 0 otherwise

Definition at line 140 of file md2cmds.c.

```
int rtn;

pthread_mutex_lock( &md2cmds_moving_mutex);
rtn = md2cmds_moving_count != 0;
pthread_mutex_unlock( &md2cmds_moving_mutex);
return rtn;
```

7.9.2.16 void md2cmds_kappaphi_move (double kappa_deg, double phi_deg)

Definition at line 759 of file md2cmds.c.

7.9.2.17 void md2cmds_maybe_done_homing_cb (char * event)

Track motors homing.

Definition at line 735 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_homing_mutex);
if( strstr( event, "Homing") == NULL) {
   if( md2cmds_homing_count != -1)
     md2cmds_homing_count = 1;
   else
     md2cmds_homing_count++;
} else {
   if( md2cmds_homing_count > 0)
     md2cmds_homing_count--;
}

if( md2cmds_homing_count != 0)
   lsredis_setstr( md2cmds_md_status_code,
     "%s", "4");

if( md2cmds_homing_count == 0)
   pthread_cond_signal( &md2cmds_homing_cond);
pthread_mutex_unlock( &md2cmds_homing_mutex);
```

7.9.2.18 void md2cmds_maybe_done_moving_cb (char * event)

Track how many motors are moving.

Definition at line 706 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_moving_mutex);
if( strstr( event, "Moving") != NULL) {
    //
    // -1 is a flag indicating we're expecting some action
    //
    if( md2cmds_moving_count == -1)
        md2cmds_moving_count = 1;
else
    md2cmds_moving_count++;
} else {
    //
    //
    if( md2cmds_moving_count > 0)
        md2cmds_moving_count--;
}
lsredis_setstr( md2cmds_md_status_code, "
        %s", md2cmds_moving_count ? "4" : "3");
if( md2cmds_moving_count == 0)
    pthread_cond_signal( &md2cmds_moving_cond);
pthread_mutex_unlock( &md2cmds_moving_mutex);
```

7.9.2.19 void md2cmds_maybe_rotate_done_cb (char * event)

Now that we are done with the 360 rotation lets rehome right quick.

Definition at line 1163 of file md2cmds.c.

```
if( rotating) {
  rotating = 0;
  lsevents_send_event( "Rotate Done");
}
```

```
7.9.2.20 void md2cmds_move_prep ( )
```

prepare for new movements

Definition at line 86 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_moving_mutex);
md2cmds_moving_count = -1;
pthread_mutex_unlock( &md2cmds_moving_mutex);
```

7.9.2.21 int md2cmds_move_wait (double timeout_secs)

Wait for all the motions requested to complete.

Parameters

```
timeout_secs | Double value of seconds to wait
```

There are two waits involved: First to wait for the first "Moving" to be seen and second to wait for the last "In Position". The timeout specified here is the sum of the two.

returns 0 on success and 1 if we timedout.

Definition at line 103 of file md2cmds.c.

```
double isecs, fsecs;
struct timespec timeout, now;
int err;
clock_gettime( CLOCK_REALTIME, &now);
fsecs = modf( timeout_secs, &isecs);
timeout.tv_sec = now.tv_sec + (long)floor( isecs);
timeout.tv_nsec = now.tv_nsec + (long)floor( fsecs * 1.0e9);
timeout.tv_sec += timeout.tv_nsec / 1000000000;
timeout.tv_nsec %= 1000000000;
err = 0;
pthread_mutex_lock( &md2cmds_moving_mutex);
while( err == 0 && md2cmds_moving_count == -1)
  err = pthread_cond_timedwait( &md2cmds_moving_cond, &
   md2cmds_moving_mutex, &timeout);
if( err == ETIMEDOUT) {
 pthread_mutex_unlock( &md2cmds_moving_mutex);
  return 1;
err = 0;
while( err == 0 && md2cmds_moving_count > 0)
  err = pthread_cond_timedwait( &md2cmds_moving_cond, &
   md2cmds_moving_mutex, &timeout);
pthread_mutex_unlock( &md2cmds_moving_mutex);
if( err == ETIMEDOUT)
  return 1;
return 0;
```

7.9.2.22 int md2cmds_moveAbs (const char * ccmd)

Move a motor to the position requested.

Parameters

in	ccmd The	he full command string to parse, ie, "moveAbs omega 180"
----	----------	--

Definition at line 415 of file md2cmds.c.

```
char *cmd;
char *ignore;
char *ptr;
char *mtr;
char *pos;
double fpos;
char *endptr;
lspmac_motor_t *mp;
int i;
int err;
// ignore nothing
if( ccmd == NULL || *ccmd == 0) {
 return 1;
// operate on a copy of the string since strtok_r will modify its argument
cmd = strdup( ccmd);
// Parse the command string
ignore = strtok_r( cmd, " ", &ptr);
if( ignore == NULL) {
 lslogging_log_message( "md2cmds_moveAbs: ignoring
  blank command '%s'", cmd);
  free ( cmd);
  return 1;
// The first string should be "moveAbs" cause that's how we got here.
// Toss it.
mtr = strtok_r( NULL, " ", &ptr);
if( mtr == NULL) {
  lslogging_log_message( "md2cmds moveAbs error: missing
     motor name");
  free ( cmd);
  return 1;
mp = NULL;
for( i=0; i<lspmac_nmotors; i++) {</pre>
  if( strcmp( lspmac_motors[i].name, mtr) == 0) {
  mp = &(lspmac_motors[i]);
    break;
  }
if ( mp == NULL) {
  lslogging_log_message( "md2cmds moveAbs error: cannot
  find motor %s", mtr);
  free ( cmd);
  return 1;
pos = strtok_r( NULL, " ", &ptr);
if( pos == NULL) {
  lslogging_log_message( "md2cmds moveAbs error: missing
     position");
  free ( cmd);
  return 1;
fpos = strtod( pos, &endptr);
if( pos == endptr) {
  /// Maybe we have a preset. Give it a whirl
// In any case we are done here.
  11
  err = lspmac_move_preset_queue( mp, pos);
  free ( cmd);
  return err;
if( mp != NULL && mp->moveAbs != NULL) {
  wprintw( term_output, "Moving %s to %f\n", mtr, fpos);
  wnoutrefresh( term_output);
  err = mp->moveAbs( mp, fpos);
free ( cmd);
return err;
```

7.9.2.23 void md2cmds_mvcenter_move (double cx, double cy, double ax, double ay, double az)

Move the centering and alignment tables.

Parameters

in	CX	Requested Centering Table X
in	су	Requested Centering Table Y
in	ax	Requested Alignment Table X
in	ay	Requested Alignment Table Y
in	az	Requested Alignment Table Z

Definition at line 679 of file md2cmds.c.

7.9.2.24 void md2cmds_organs_move_presets (char * pay, char * paz, char * pcy, char * pcz, char * psz)

Definition at line 175 of file md2cmds.c.

```
double ay, az, cy, cz, sz; int cay, caz, ccy, ccz, csz;
err = lsredis_find_preset( apery->name, pay, &ay)
if( err == 0) {
  lslogging_log_message( "md2cmds_move_organs_presets:
    no preset '%s' for motor '%s'", pay, apery->name);
}
err = lsredis_find_preset( aperz->name, paz, &az)
if( err == 0) {
  lslogging_log_message( "md2cmds_move_organs_presets:
    no preset '%s' for motor '%s'", paz, aperz->name);
   return;
err = lsredis_find_preset( capy->name, pcy, &cy);
if( err == 0) {
 lslogging_log_message( "md2cmds_organs_move_presets:
    no preset '%s' for motor '%s'", pcy, capy->name);
  return;
err = lsredis_find_preset( capz->name, pcz, &cz);
if( err == 0) {
  lslogging_log_message( "md2cmds_organs_move_presets:
    no preset '%s' for motor '%s'", pcz, capz->name);
   return;
```

```
err = lsredis_find_preset( scint->name, psz, &sz)
if( err == 0) {
  lslogging_log_message( "md2cmds_organs_move_presets:
   no preset '%s' for motor '%s'", psz, scint->name);
  return;
cay = md2cmds_prep_axis( apery, ay);
caz = md2cmds_prep_axis( aperz, az);
ccy = md2cmds_prep_axis( capy, cy);
ccz = md2cmds_prep_axis( capz, cz);
csz = md2cmds_prep_axis( scint, sz);
// 170
//
//
                   LS-CAT Move U, V, W, X, Y, Z Absolute
Q40 = X Value
Q41 = Y Value
                         Q42
                                  = Z Value
                                  = U Value
                         Q43
                         Q44
                                  = V Value
                                  = W Value
                         Q45
lspmac_SockSendDPline( "organs", "&5 Q40=0 Q41=%d Q42=%d
      Q43=%d Q44=%d Q45=%d Q100=16 B170R", cay, caz, ccy, ccz, csz);
```

7.9.2.25 void md2cmds_phase_change (const char * ccmd)

Move md2 devices to a preconfigured state.

EMBL calls these states "phases" and this language is partially retained here

Parameters

ccmd The full text of the command that sent us here

Definition at line 504 of file md2cmds.c.

```
char *cmd;
char *ignore;
char *ptr;
char *mode:
int err;
if( ccmd == NULL || *ccmd == 0)
// use a copy as strtok_r modifies the string it is parsing
cmd = strdup( ccmd);
ignore = strtok_r( cmd, " ", &ptr);
if( ignore == NULL) {
 free( cmd);
 return;
// ignore should point to "mode" cause that's how we got here. Ignore it
mode = strtok_r( NULL, " ", &ptr);
if ( mode == NULL) {
 lslogging_log_message( "md2cmds_phase_change: no mode
    specified");
 free( cmd);
 return;
if( strcmp( mode, "manualMount") == 0) {
 lsevents_send_event( "Mode manualMount Starting");
 // Try all motions, flag errors at the end
```

```
md2cmds_move_prep();
  err = lspmac_move_or_jog_preset_queue(
   kappa, "manualMount", 1);
  err += lspmac_move_or_jog_preset_queue(
  omega, "manualMount", 0);
  err += lspmac_move_or_jog_abs_queue( phi,
   0.0, 0);
  err += lspmac_move_or_jog_preset_queue(
    aperz, "Cover", 1);
  err += lspmac_move_or_jog_preset_queue( capz
   , "Cover", 1);
  err += lspmac_move_or_jog_preset_queue(
  scint, "Cover", 1);
err += md2cmds_moveAbs( "moveAbs backLight 0");
  err += md2cmds_moveAbs( "moveAbs backLight.intensity 0");
err += md2cmds_moveAbs( "moveAbs cryo 1");
  err += md2cmds_moveAbs( "moveAbs fluo 0");
  err += md2cmds_moveAbs( "moveAbs cam.zoom 1");
  if( md2cmds_move_wait( 60.0) || err)
    lsevents_send_event( "Mode manualMount Aborted");
  else
    lsevents_send_event( "Mode manualMount Done");
} else if( strcmp( mode, "robotMount") == 0) {
  lsevents_send_event( "Mode robotMount Starting");
  md2cmds_home_prep();
  md2cmds_move_prep();
  lspmac_home1_queue( kappa);
  lspmac_home1_queue( omega);
  lspmac_move_or_jog_abs_queue( phi, 0.0, 0);
  lspmac_move_or_jog_preset_queue( apery,
     "In", 1);
  lspmac_move_or_jog_preset_queue( aperz,
    "In", 1);
  lspmac_move_or_jog_preset_queue( capz,
    "Cover", 1);
  lspmac_move_or_jog_preset_queue( scint,
     "Cover", 1);
  md2cmds_moveAbs( "moveAbs backLight 0");
md2cmds_moveAbs( "moveAbs backLight.intensity 0");
  md2cmds_moveAbs( "moveAbs cryo 1");
  md2cmds_moveAbs( "moveAbs fluo 0");
  md2cmds_moveAbs( "moveAbs cam.zoom 1");
  if( md2cmds_home_wait( 60.0)) {
    lsevents_send_event( "Mode robotMount Aborted");
  } else {
    if( md2cmds_move_wait( 60.0))
      lsevents_send_event( "Mode robotMount Aborted");
    else
      lsevents_send_event( "Mode robotMount Done");
} else if( strcmp( mode, "center") == 0) {
  lsevents_send_event( "Mode center Starting");
  md2cmds_move_prep();
  md2cmds_moveAbs( "moveAbs kappa 0");
md2cmds_moveAbs( "moveAbs omega 0");
                                       phi,
  lspmac_move_or_jog_abs_queue(
                                                0.0.
     0):
  lspmac_move_or_jog_preset_queue( apery,
     "In", 1);
  lspmac_move_or_jog_preset_queue( aperz,
     "In", 1);
  lspmac_move_or_jog_preset_queue( capy,
    "In", 1);
  lspmac_move_or_jog_preset_queue( capz,
    "In", 1);
  lspmac_move_or_jog_preset_queue( scint,
     "Cover", 1);
  md2cmds_moveAbs( "moveAbs backLight 1");
  md2cmds_moveAbs( "moveAbs cam.zoom 1");
md2cmds_moveAbs( "moveAbs cryo 0");
  md2cmds_moveAbs( "moveAbs fluo 0");
  if( md2cmds_move_wait( 60.0))
    lsevents_send_event( "Mode center Aborted");
  else
    lsevents_send_event( "Mode center Done");
} else if( strcmp( mode, "dataCollection") == 0) {
  lsevents_send_event( "Mode dataCollection Starting");
  md2cmds_move_prep();
  lspmac_move_or_jog_preset_queue( apery,
```

```
"In", 1);
  lspmac_move_or_jog_preset_queue( aperz,
     "In", 1);
  lspmac_move_or_jog_preset_queue( capy,
     "In", 1);
  lspmac_move_or_jog_preset_queue( capz,
    "In", 1);
  lspmac_move_or_jog_preset_queue( scint,
     "Cover", 1);
  md2cmds_moveAbs( "moveAbs backLight 0");
md2cmds_moveAbs( "moveAbs backLight.intensity 0");
md2cmds_moveAbs( "moveAbs cryo 0");
  md2cmds_moveAbs( "moveAbs fluo 0");
  if( md2cmds_move_wait( 60.0))
    lsevents_send_event( "Mode dataCollection Aborted");
  else
    lsevents send event( "Mode dataCollection Done");
} else if( strcmp( mode, "beamLocation") == 0) {
  lsevents_send_event( "Mode beamLocation Starting");
  md2cmds_moveAbs( "moveAbs kappa 0");
  md2cmds_moveAbs( "moveAbs omega 0");
  lspmac_move_or_jog_preset_queue( apery,
     "In", 1);
  lspmac_move_or_jog_preset_queue( aperz,
     "In", 1);
  lspmac_move_or_jog_preset_queue( capy,
     "In", 1);
  lspmac_move_or_jog_preset_queue( capz,
    "In", 1);
  lspmac_move_or_jog_preset_queue( scint,
  "Scintillator", 1);
md2cmds_moveAbs( "moveAbs backLight 0");
  md2cmds_moveAbs( "moveAbs cam.zoom 1");
  md2cmds_moveAbs( "moveAbs cryo 0");
  md2cmds_moveAbs( "moveAbs fluo 0");
  if( md2cmds_move_wait( 60.0))
  lsevents_send_event( "Mode beamLocation Aborted");
  else
    lsevents_send_event( "Mode beamLocation Done");
} else if( strcmp( mode, "safe") == 0) {
  lsevents_send_event( "Mode safe Starting");
  md2cmds_moveAbs( "moveAbs kappa 0");
  md2cmds_moveAbs( "moveAbs omega 0");
  lspmac_move_or_jog_preset_queue( apery,
     "In", 1);
  lspmac_move_or_jog_preset_queue( aperz,
    "Cover", 1);
  lspmac_move_or_jog_preset_queue( capy,
  lspmac_move_or_jog_preset_queue( capz,
    "Cover", 1);
  lspmac_move_or_jog_preset_queue( scint,
      "Cover", 1);
  md2cmds_moveAbs( "moveAbs backLight 0");
  md2cmds_moveAbs ( "moveAbs cam.zoom 1");
  md2cmds_moveAbs( "moveAbs cryo 0");
  md2cmds_moveAbs( "moveAbs fluo 0");
  if( md2cmds_move_wait( 60.0))
  lsevents_send_event( "Mode safe Aborted");
  else
    lsevents_send_event( "Mode safe Done");
free ( cmd);
```

7.9.2.26 double md2cmds_prep_axis (Ispmac_motor_t * mp, double pos)

{

Definition at line 151 of file md2cmds.c.

```
double rtn;
double u2c;
```

7.9.2.27 void md2cmds_rotate ()

Spin 360 and make a video (recenter first, maybe)

Definition at line 1026 of file md2cmds.c.

```
double cx, cy, ax, ay, az;
int mmask;
mmask = 0;
// BLUMax disables scintilator here.
^{\prime\prime} // get the new center information
lspg_getcenter_call();
lspg_getcenter_wait();
// put up the back light
blight_ud->moveAbs( blight_ud, 1);
md2cmds_move_prep();
md2cmds_home_prep();
// make sure omega is homed
lspmac_home1_queue( omega);
if( lspg_getcenter.no_rows_returned) {
  // Always specify zoom even if no other center information is found
  zoom->moveAbs( zoom, 1);  // default zoom is 1
  lslogging_log_message( "md2cmds_rotate: getcenter
   , lspg_getcenter.daz,lspg_getcenter.zoom);
  if( lspg_getcenter.zoom_isnull == 0) {
   zoom->moveAbs( zoom, lspg_getcenter.zoom
   );
  } else {
   zoom->moveAbs( zoom, 1);
  }
  \ensuremath{//} Grab the current positions and perhaps add the tad specified by
    getcenter
  cx = lspmac_getPosition( cenx);
  cy = lspmac_getPosition( ceny);
  ax = lspmac_getPosition( alignx);
  ay = lspmac_getPosition( aligny);
  az = lspmac_getPosition( alignz);
  lslogging_log_message( "md2cmds_rotate: actual
    positions cx %f, cy %f, ax %f, ay %f, az %f", cx, cy, ax, ay, az);
```

```
if( lspg_getcenter.dcx_isnull == 0)
    cx += lspg_getcenter.dcx;
  if( lspg_getcenter.dcy_isnull == 0)
   cy += lspg_getcenter.dcv;
  if( (lspg_getcenter.dcx_isnull == 0 && fabs(
   lspg_getcenter.dcx) >= 0.0) ||
      (lspg_getcenter.dcy_isnull == 0 && fabs(
    lspg\_getcenter.dcy) >= 0.0)) {
    mmask |= 2;
  if( lspg_getcenter.dax_isnull == 0)
    ax += lspg_getcenter.dax;
  if( lspg_getcenter.day_isnull == 0)
    ay += lspg_getcenter.day;
  if( lspg_getcenter.daz_isnull == 0)
    az += lspg_getcenter.daz;
  if( (lspg_getcenter.dax_isnull == 0 && fabs(
    lspg_getcenter.dax) >= lsredis_getd( alignx
    ->precision)) ||
      (lspg_getcenter.day_isnull == 0 && fabs(
    lspg_getcenter.day) >= lsredis_getd( aligny
    ->precision)) ||
      (lspg_getcenter.daz_isnull == 0 && fabs(
    lspg_getcenter.daz) >= lsredis_getd( alignz
    ->precision))) {
  lslogging_log_message( "md2cmds_rotate: requested
     positions cx %f, cy %f, ax %f, ay %f, az %f", cx, cy, ax, ay, az);
  lslogging_log_message( "md2cmds_rotate: moving center"
  md2cmds_mvcenter_move( cx, cy, ax, ay, az);
  lslogging_log_message( "md2cmds_rotate: waiting for
     center move");
  lslogging_log_message( "md2cmds_rotate: done waiting")
    ;
lspg_getcenter_done();
if( md2cmds_home_wait( 20.0)) {
   lslogging_log_message( "md2cmds_rotate: homing motors
  timed out. Rotate aborted");
lsevents_send_event( "Rotate Aborted");
 return;
if( md2cmds move wait( 20.0)) {
 return;
// Report new center positions
cx = lspmac_getPosition( cenx);
cy = lspmac_getPosition( ceny);
ax = lspmac_getPosition( alignx);
ay = lspmac_getPosition( aligny);
az = lspmac_getPosition( alignz);
lspg_query_push( NULL, "SELECT px.applycenter( %.3f, %.3f, %.3f, %.3f, %.3f, %.3f, %.3f, %.3f, %.3f)", cx, cy, ax, ay, az, lspmac_getPosition
    (kappa), lspmac_getPosition( phi));
{\tt lslogging\_log\_message(\ "md2cmds\_rotate: \ done \ with}
     applycenter");
lspmac_video_rotate( 4.0);
lslogging_log_message( "md2cmds_rotate: starting
     rotation");
rotating = 1;
```

```
7.9.2.28 void md2cmds_rotate_cb ( char * event )
```

Tell the database about the time we went through omega=zero.

This should trigger the video feed server to starting making a movie.

Definition at line 1148 of file md2cmds.c.

7.9.2.29 void md2cmds_run ()

Start up the thread.

Definition at line 1378 of file md2cmds.c.

```
pthread_create( &md2cmds_thread, NULL,
    md2cmds_worker, NULL);
lsevents_add_listener( "omega crossed zero",
md2cmds_rotate_cb);
lsevents_add_listener( "omega In Position",
    md2cmds_maybe_rotate_done_cb);
lsevents_add_listener( ".+ (Moving|In Position)",
    md2cmds_maybe_done_moving_cb);
lsevents_add_listener( "(.+) (Homing|Homed)",
    md2cmds_maybe_done_homing_cb);
lsevents_add_listener( "capz (Moving|In Position)",
    md2cmds_time_capz_cb);
lsevents_add_listener( "Coordsys 1 Stopped",
md2cmds_coordsys_1_stopped_cb);
lsevents_add_listener( "Coordsys 2 Stopped",
md2cmds_coordsys_2_stopped_cb);
lsevents_add_listener( "Coordsys 3 Stopped",
md2cmds_coordsys_3_stopped_cb);
lsevents_add_listener( "Coordsys 4 Stopped",
    md2cmds_coordsys_4_stopped_cb);
lsevents_add_listener( "Coordsys 5 Stopped",
md2cmds_coordsys_5_stopped_cb);
lsevents_add_listener( "Coordsys 7 Stopped",
    md2cmds_coordsys_7_stopped_cb);
```

7.9.2.30 void md2cmds_set_scale_cb (char * event)

Fix up xscale and yscale when zoom changes.

Definition at line 1173 of file md2cmds.c.

```
int mag;
lsredis_obj_t *p1, *p2;
char *vp;
mag = lspmac_getPosition( zoom);
p1 = lsredis_get_obj( "cam.xScale");
p2 = lsredis_get_obj( "cam.zoom.%d.ScaleX", mag);
vp = lsredis_getstr( p2);
```

```
lsredis_setstr( p2, vp);
free( vp);

p1 = lsredis_get_obj( "cam.yScale");
p2 = lsredis_get_obj( "cam.zoom.%d.ScaleY", mag);

vp = lsredis_getstr( p2);
lsredis_setstr( p2, vp);
free( vp);
```

7.9.2.31 void md2cmds_time_capz_cb (char * event)

Time the capillary motion for the transfer routine.

< track the time spent moving capz

Definition at line 1205 of file md2cmds.c.

```
static struct timespec capz_timestarted;
struct timespec now;
int nsec, sec;

if( strstr( event, "Moving") != NULL) {
   clock_gettime( CLOCK_REALTIME, &capz_timestarted);
} else {
   clock_gettime( CLOCK_REALTIME, &now);

   sec = now.tv_sec - capz_timestarted.tv_sec;
   nsec = 0;
   if( now.tv_nsec > capz_timestarted.tv_nsec) {
      sec--;
      nsec += 10000000000;
}
   nsec += now.tv_nsec - capz_timestarted.tv_nsec;
   md2cmds_capz_moving_time = sec + nsec / 1000000000.
   ;
}
```

7.9.2.32 void md2cmds_transfer ()

Transfer a sample.

Definition at line 232 of file md2cmds.c.

```
int nextsample, abort_now;
double esttime;
double ax, ay, az, cx, cy, horz, vert, oref;
int err;
nextsample = lspg_nextsample_all( &err);
if (err) {
  lslogging_log_message( "md2cmds_transfer: no sample
     requested to be transfered, false alarm");
// BLUMax sets up an abort dialogbox here. Probably we should figure out how
     we are going to handle that.
// Wait for motors to stop
if( md2cmds_is_moving()) {
 lslogging_log_message( "md2cmds_transfer: Waiting for
     previous motion to finish");
  if( md2cmds_move_wait( 30.0)) {
   lslogging_log_message( "md2cmds_transfer: Timed out
   waiting for previous motion to finish. Aborting transfer");
  }
}
```

```
// get positions we'll be needed to report to postgres
ax = lspmac_getPosition(alignx);
ay = lspmac_getPosition(aligny);
az = lspmac_getPosition(alignz);
cx = lspmac_getPosition(cenx);
cy = lspmac_getPosition(ceny);
oref = lsredis_getd(lsredis_get_obj( "
    omega.reference")) * M_PI/180.;
horz = cx * cos(oref) + cy * sin(oref);
vert = cx * sin(oref) - cy * cos(oref);
if( lsredis_getd( capz->u2c) <= 0.0 || lsredis_getd
  ( capz->max_speed) <= 0.0 || lsredis_getd( capz->
  max_accel) <= 0.0) {</pre>
  esttime = 0.0;
} else {
  \ensuremath{//} Here we assume moving the capilary is the rate limiting step in
    preparing the MD2.
  // TODO: look at factors in which something besides the capilary determines
     the time such as if the scintilator is out.
  // pretend we are going to zero instead of the "Out" position. We should
     probably arrange for
  // neutralPosition such that "Out" is zero.
  // This also treats S curve acceleration as taking the same time as linear
     acceleration.
  esttime = lspmac_getPosition( capz)/lsredis_getd
    ( capz->u2c)/(lsredis_getd( capz->max_speed));
// Time if we moved at constant velocity
  esttime += lsredis_getd( capz->max_speed)/
    lsredis_getd(capz->max_accel);
    // Correction for time spent accelerating
  esttime /= 1000.;
    // convert from milliseconds to seconds
lspg_starttransfer_call( nextsample,
    lspmac_getBIPosition( sample_detected), ax,
    ay, az, horz, vert, esttime);
// put the light down if it's not already
if( lspmac_getBIPosition( blight_down) != 1)
  blight_ud->moveAbs(blight_ud, 0);
// Pull the fluorescence detector out of the way
if( lspmac_getBIPosition( fluor_back) != 1)
 blight_ud->moveAbs( fluo, 0);
//
// Prepare for moving stuff
md2cmds_move_prep();
//
// Put the organs into position
md2cmds_home_prep();
// Home Kappa
lspmac_home1_queue( kappa);
//
// Home omega
lspmac_home1_queue( omega);
//
// wait for kappa cause we can't home phi until kappa's done
lspmac_moveabs_wait( kappa, 60.0);
```

```
//
// Home phi (whatever that means)
lspmac_homel_queue( phi);
// Now let's get back to postresql (remember our query so long ago?)
lspg_starttransfer_wait();
^{\prime\prime} // It's possible that the sample that's mounted is unknown to the robot.
// If so then we need to abort after we're done moving stuff
if( lspg_starttransfer.no_rows_returned ||
    lspg_starttransfer.starttransfer != 1)
  abort_now = 1;
else
 abort now = 0;
lspg_starttransfer_done();
// Wait for the homing routines to finish
if ( md2cmds_home_wait( 30.0)) {
  lslogging_log_message( "md2cmds_transfer: homing
  routines taking too long. Aborting transfer.");
lsevents_send_event( "Transfer Aborted");
 return;
// Wait for all the motors to stop moving
if( md2cmds_move_wait( 30.0)) {
  lslogging_log_message( "md2cmds_transfer: We got bored
     waiting for the motors to stop. Aborting transfer. Later.");
  lsevents_send_event( "Transfer Aborted");
  return;
// TODO: check that all the motors are where we told them to go
if( abort_now) {
 lslogging_log_message( "md2cmds_transfer: Apparently
  there is a sample mounted already but we don't know where it is supposed to go"); lsevents_send_event( "Transfer Aborted");
  return:
// refuse to go on if we do not have positive confirmation that the backlight
     is down and the
// fluorescence detector is back
if( lspmac_getBIPosition( blight_down) != 1 ||
    lspmac_getBIPosition( fluor_back) != 1) {
  lslogging_log_message( "md2cmds_transfer: It looks
  like either the back light is not down or the fluoescence dectector is not back"); lsevents_send_event( "Transfer Aborted");
 return;
// Wait for the robot to unlock the cryo which signals us that we need to
\ensuremath{//} move the cryo back and drop air rights
lspg_waitcryo_all();
// Move the cryo back
cryo->moveAbs( cryo, 1);
lspmac_moveabs_wait( cryo, 10.0);
// simplest query yet!
lspg_query_push( lspg_waitcryo_cb, "SELECT
     px.dropairrights()");
// wait for the result
// TODO: find an easy way out of this in case of error
lspg_getcurrentsampleid_wait_for_id(
    nextsample);
\ensuremath{//} grab the airrights again \ensuremath{//}
```

```
lspg_demandairrights_all();
lsevents_send_event( "Transfer Done");
}
```

7.9.2.33 void* md2cmds_worker (void * dummy)

Our worker thread.

Parameters

dummy						
	[in] Unused but required by protocol					

Definition at line 1307 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_mutex);
while(1) {
  // wait for someone to give us a command (and tell us they did so)
  while( md2cmds_cmd[0] == 0)
    \tt pthread\_cond\_wait(\&md2cmds\_cond,\&md2cmds\_mutex)
  if( strcmp( md2cmds_cmd, "abort") == 0) {
    md2cmds_abort();
  } else if( strcmp( md2cmds_cmd, "transfer") == 0) {
    md2cmds_transfer();
  } else if( strcmp( md2cmds_cmd, "collect") == 0) {
    md2cmds collect();
  } else if( strcmp( md2cmds_cmd, "rotate") == 0) {
    md2cmds_rotate();
  } else if( strcmp( md2cmds_cmd, "center") == 0) {
  md2cmds_center();
} else if( strncmp( md2cmds_cmd, "moveAbs", 7) == 0) {
   md2cmds_moveAbs( md2cmds_cmd);
  } else if( strncmp( md2cmds_cmd, "changeMode", 10) == 0) {
   md2cmds_phase_change( md2cmds_cmd);
  md2cmds\_cmd[0] = 0;
```

7.9.3 Variable Documentation

7.9.3.1 double md2cmds_capz_moving_time = NAN [static]

Definition at line 32 of file md2cmds.c.

7.9.3.2 char md2cmds_cmd[MD2CMDS_CMD_LENGTH]

our command;

Definition at line 24 of file md2cmds.c.

7.9.3.3 pthread_cond_t md2cmds_cond

condition to signal when it's time to run an md2 command

Definition at line 10 of file md2cmds.c.

7.9.3.4 pthread_cond_t md2cmds_homing_cond

coordinate homing and homed

Definition at line 18 of file md2cmds.c.

7.9.3.5 int md2cmds_homing_count = 0

We've asked a motor to home.

Definition at line 17 of file md2cmds.c.

7.9.3.6 pthread_mutex_t md2cmds_homing_mutex

our mutex;

Definition at line 19 of file md2cmds.c.

7.9.3.7 | Isredis_obj_t* md2cmds_md_status_code

Definition at line 26 of file md2cmds.c.

7.9.3.8 pthread_cond_t md2cmds_moving_cond

wait for command to have been dequeued and run coordinate call and response

Definition at line 14 of file md2cmds.c.

7.9.3.9 int md2cmds_moving_count = 0

Definition at line 22 of file md2cmds.c.

7.9.3.10 pthread_mutex_t md2cmds_moving_mutex

message passing between md2cmds and pg Definition at line 15 of file md2cmds.c.

7.9.3.11 int md2cmds_moving_queue_wait = 0

Definition at line 13 of file md2cmds.c.

7.9.3.12 pthread_mutex_t md2cmds_mutex

mutex for the condition

Definition at line 11 of file md2cmds.c.

7.9.3.13 pthread_t md2cmds_thread [static]

Definition at line 28 of file md2cmds.c.

```
7.9.3.14 introtating = 0 [static]
```

flag: when omega is in position after a rotate we want to re-home omega Definition at line 30 of file md2cmds.c.

7.10 mk_pgpmac_redis.py File Reference

Namespaces

· namespace mk pgpmac redis

Variables

- list mk_pgpmac_redis.head sys.argv[1]
- list mk_pgpmac_redis.pref_ini sys.argv[2]
- list mk_pgpmac_redis.hard_ini sys.argv[3]
- · dictionary mk_pgpmac_redis.motor_dict
- · dictionary mk pgpmac redis.hard ini fields
- list mk_pgpmac_redis.motor_field_lists
- list mk_pgpmac_redis.bi_list ["CryoSwitch"]
- dictionary mk_pgpmac_redis.motor_presets
- list mk_pgpmac_redis.zoom_settings
- tuple mk_pgpmac_redis.hi iniParser.iniParser(hard_ini)
- list mk pgpmac redis.v motor dict[m]
- string mk_pgpmac_redis.f "HSETNX"
- tuple mk_pgpmac_redis.pi iniParser.iniParser(pref_ini)
- int mk_pgpmac_redis.i 0
- tuple mk_pgpmac_redis.ppos pi.get(section, option)
- string mk_pgpmac_redis.fnc "HSETNX"
- tuple mk pgpmac redis.b pi.get(section, "LightIntensity")
- tuple mk_pgpmac_redis.p pi.get(section, "MotorPosition")
- tuple mk pgpmac redis.x pi.get(section, "ScaleX")
- tuple mk_pgpmac_redis.y pi.get(section, "ScaleY")

7.11 pgpmac.c File Reference

```
Main for the pgpmac project.
```

```
#include "pgpmac.h"
```

Functions

• void stdinService (struct pollfd *evt)

Handle keyboard input.

void pgpmac_printf (char *fmt,...)

Terminal output routine ala printf.

• int main (int argc, char **argv)

Our main routine.

Variables

```
    WINDOW * term_output
        place to print stuff out
    WINDOW * term_input
```

place to put the cursor

WINDOW * term_status

shutter, lamp, air, etc status

WINDOW * term_status2

shutter, lamp, air, etc status

• pthread_mutex_t ncurses_mutex

allow more than one thread access to the screen

static struct pollfd stdinfda

Handle input from the keyboard.

• static int running = 1

7.11.1 Detailed Description

Main for the pgpmac project.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file pgpmac.c.

7.11.2 Function Documentation

7.11.2.1 int main (int argc, char ** argv)

Our main routine.

Parameters

in	argc	Number of arguments
in	argv	Vector of argument strings

Definition at line 353 of file pgpmac.c.

```
int c;
int ivars, mvars;
mvars=0;
ivars=0;
int i;
                                             // standard loop counter
while(1) {
  c=getopt_long( argc, argv, "im", long_options, NULL);
  if(c == -1)
    break:
  switch(c) {
    ivars=1;
    break;
  case 'm':
    mvars=1;
     break;
  }
}
stdinfda.fd = 0;
stdinfda.events = POLLIN;
                                              // Start ncurses
// Line buffering disabled, control
initscr();
raw();
     chars trapped
keypad( stdscr, TRUE);
                                              // Why is F1 nifty?
refresh();
pthread_mutex_init( &ncurses_mutex, NULL);
                                                        // don't lock
      this mutex yet because we are not multi-threaded until the "_run" functions
// Since the modules reference objects in other modules it is important
// that everyone is initiallized before anyone runs
lslogging_init();
lslogging_run();
lsevents_init();
lsevents_run();
lstimer_init();
lstimer_run();
lsredis_init( "MD2-21-ID-E", "redis\\.kvseq|stns\\.2\\.(.+)", "
    stns.2");
lsredis_run();
lspmac_init( ivars, mvars);
lspg_init();
md2cmds_init();
term_status = newwin( LS_DISPLAY_WINDOW_HEIGHT
    , LS_DISPLAY_WINDOW_WIDTH, 3*LS_DISPLAY_WINDOW_HEIGHT
    , 0*LS_DISPLAY_WINDOW_WIDTH);
box( term_status, 0, 0);
wnoutrefresh( term_status);
term_status2 = newwin( LS_DISPLAY_WINDOW_HEIGHT
    , LS_DISPLAY_WINDOW_WIDTH, 3*LS_DISPLAY_WINDOW_HEIGHT , 1*LS_DISPLAY_WINDOW_WIDTH);
box( term_status2, 0, 0);
wnoutrefresh( term_status2);
term_output = newwin( 20, 5*LS_DISPLAY_WINDOW_WIDTH
    , 4*LS_DISPLAY_WINDOW_HEIGHT, 0);
scrollok(term_output, 1);
wnoutrefresh( term_output);
term_input = newwin(3,5*LS_DISPLAY_WINDOW_WIDTH
term_input = newwin(3, 5*LS_DISPLAY_WI)
, 20+4*LS_DISPLAY_WINDOW_HEIGHT, 0);
box(term_input, 0, 0);
mvwprintw(term_input, 1, 1, "PMAC> ");
nodelay(term_input, TRUE);
keypad(term_input, TRUE);
wnoutrefresh( term_input);
doupdate();
lspmac_run();
lspg_run();
md2cmds_run();
while( running) {
```

```
// Big loop
  nfd = 0;
  //
// keyboard
  memcpy( &(fda[nfd++]), &stdinfda, sizeof( struct pollfd));
  if( nfd == 0) {
    ^{\prime\prime} // No connectons yet. Wait a bit and try again.
    sleep( 10);
    // go try to connect again
    continue;
  pollrtn = poll( fda, nfd, 10);
  for( i=0; pollrtn>0 && i<nfd; i++) {</pre>
    if( fda[i].revents) {
      pollrtn--;
      if( fda[i].fd == 0) {
       stdinService( &fda[i]);
   }
 }
endwin();
return 0;
```

7.11.2.2 void pgpmac_printf (char * fmt, ...)

Terminal output routine ala printf.

Parameters

in	fmt	Printf style formating string

Definition at line 330 of file pgpmac.c.

```
va_list arg_ptr;

pthread_mutex_lock( &ncurses_mutex);

va_start( arg_ptr, fmt);
vwprintw( term_output, fmt, arg_ptr);
va_end( arg_ptr);

wnoutrefresh( term_output);
wnoutrefresh( term_input);
doupdate();

pthread_mutex_unlock( &ncurses_mutex);
}
```

7.11.2.3 void stdinService (struct pollfd * evt)

Handle keyboard input.

Parameters

in	evt The pollfd object that caused this call	
----	---	--

Definition at line 254 of file pgpmac.c.

```
static char cmds[1024];
static char cntrlcmd[2];
static unsigned int cmds_on = 0;
int ch;
for( ch=wgetch(term_input); ch != ERR && running; ch=wgetch(
  // wprintw( term_output, "%04x\n", ch);
  // wnoutrefresh( term_output);
  switch(ch) {
  case KEY_F(1):
  case KEY_F(2):
  case KEY_F(3):
   running = 0;
   break;
                     // Control-A
// Control-B
  case 0x0001:
  case 0x0002:
                       // Control-C
  case 0x0003:
                       // Control-D
// Control-E
  case 0x0004:
  case 0x0005:
                      // Control-E
// Control-F
// Control-G
// Control-K
// Control-O
  case 0x0006:
  case 0x0007:
  case 0x000b:
  case 0x000f:
                       // Control-P
  case 0x0010:
                       // Control-Q
  case 0x0011:
                       // Control-R
  case 0x0012:
                       // Control-Q
  case 0x0013:
  case 0x0016:
                        // Control-V
    cntrlcmd[0] = ch;
    cntrlcmd[1] = 0;
lspmac_SockSendline( NULL, cntrlcmd);
    //
            PmacSockSendControlCharPrint(ch);
    break;
  case KEY_BACKSPACE:
    cmds[cmds_on] = 0;
cmds_on == 0 ? 0 : cmds_on--;
    break;
  case KEY_ENTER:
  case 0x000a:
    if(cmds_on > 0 \&\& strlen(cmds) > 0) {
      lspmac_SockSendline( NULL, cmds);
    memset( cmds, 0, sizeof(cmds));
    cmds_on = 0;
    break;
  default:
    if(ch >= 0x20 \&\& ch <= 0x7e) {
     if ( cmds_on < sizeof( cmds)-1) {
  cmds[cmds_on++] = ch;</pre>
        cmds[cmds_on] = 0;
      }
   break;
  if( running) {
    mvwprintw( term_input, 1, 1, "PMAC> %s", cmds);
    wclrtoeol( term_input);
    box( term_input, 0, 0);
    wnoutrefresh( term_input);
    doupdate();
```

7.11.3 Variable Documentation

7.11.3.1 pthread_mutex_t ncurses_mutex

allow more than one thread access to the screen

Definition at line 242 of file pgpmac.c.

7.11.3.2 intrunning = 1 [static]

Definition at line 249 of file pgpmac.c.

7.11.3.3 struct pollfd stdinfda [static]

Handle input from the keyboard.

Definition at line 248 of file pgpmac.c.

7.11.3.4 WINDOW* term_input

place to put the cursor

Definition at line 238 of file pgpmac.c.

7.11.3.5 WINDOW* term_output

place to print stuff out

Definition at line 237 of file pgpmac.c.

7.11.3.6 WINDOW* term_status

shutter, lamp, air, etc status

Definition at line 239 of file pgpmac.c.

7.11.3.7 WINDOW* term_status2

shutter, lamp, air, etc status

Definition at line 240 of file pgpmac.c.

7.12 pgpmac.h File Reference

Headers for the entire pgpmac project.

```
#include <stdint.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netdb.h>
#include <string.h>
#include <netinet/in.h>
#include <errno.h>
#include <poll.h>
#include <libpq-fe.h>
#include <ncurses.h>
#include <math.h>
#include <pthread.h>
#include <signal.h>
#include <sys/signalfd.h>
#include <sys/time.h>
#include <time.h>
#include <getopt.h>
#include <regex.h>
#include <hiredis/hiredis.h>
#include <hiredis/async.h>
#include <search.h>
```

Data Structures

· struct lsredis_obj_struct

Redis Object Basic object whose value is sychronized with our redis db.

struct tagEthernetCmd

PMAC ethernet packet definition.

struct lspmac_cmd_queue_struct

PMAC command queue item.

· struct lspmac_motor_struct

Motor information.

• struct lspmac_bi_struct

Storage for binary inputs.

• struct lspgQueryQueueStruct

Store each query along with it's callback function.

- struct lspg_waitcryo_struct
- struct lspg_getcurrentsampleid_struct
- · struct lspg_demandairrights_struct
- · struct lspg_getcenter_struct

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies.

• struct lspg_starttransfer_struct

returns 1 if transfer can continue 0 to abort

struct lspg_nextsample_struct

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

· struct lspg_nextshot_struct

Storage definition for nextshot query.

Macros

- #define GNU SOURCE
- #define LS_DISPLAY_WINDOW_HEIGHT 8

Number of status box rows.

#define LS_DISPLAY_WINDOW_WIDTH 24

Number of status box columns.

• #define LS_PG_QUERY_STRING_LENGTH 1024

Fixed length postgresql query strings. Queries should all be function calls so this is not as weird as one might think.

#define LSEVENTS EVENT LENGTH 256

Fixed length for event names: simplifies string handling.

• #define MD2CMDS_CMD_LENGTH 32

Typedefs

typedef struct lsredis_obj_struct lsredis_obj_t

Redis Object Basic object whose value is sychronized with our redis db.

typedef struct tagEthernetCmd pmac_cmd_t

PMAC ethernet packet definition.

· typedef struct

lspmac_cmd_queue_struct pmac_cmd_queue_t

PMAC command queue item.

typedef struct lspmac_motor_struct lspmac_motor_t

Motor information.

typedef struct lspmac_bi_struct lspmac_bi_t

Storage for binary inputs.

typedef struct lspgQueryQueueStruct lspg_query_queue_t

Store each query along with it's callback function.

- typedef struct lspg_waitcryo_struct lspg_waitcryo_t
- · typedef struct

lspg_getcurrentsampleid_struct lspg_getcurrentsampleid_t

· typedef struct

lspg_demandairrights_struct lspg_demandairrights_t

· typedef struct

lspg_getcenter_struct lspg_getcenter_t

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies.

· typedef struct

lspg_starttransfer_struct lspg_starttransfer_t

returns 1 if transfer can continue 0 to abort

· typedef struct

lspg_nextsample_struct lspg_nextsample_t

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

typedef struct lspg_nextshot_struct lspg_nextshot_t

Storage definition for nextshot query.

Functions

double lspmac_getPosition (lspmac_motor_t *)

get the motor position (with locking)

char ** lspg array2ptrs (char *)

returns a null terminated list of strings parsed from postgresql array

char ** Isredis_get_string_array (Isredis_obj_t *p)

```
    void lspmac_SockSendDPline (char *, char *fmt,...)

      prepare (queue up) a line to send the dpram ascii command interface

    pmac cmd queue t * Ispmac SockSendline (char *, char *,...)

      Send a one line command.

    Isredis obj t * Isredis get obj (char *,...)

    char * lsredis_getstr (lsredis_obj_t *p)

      return a copy of the key's string value

    void PmacSockSendline (char *s)

    unsigned int lspg_nextsample_all (int *err)

    long int lsredis_getl (lsredis_obj_t *p)

    void lsevents add listener (char *, void(*cb)(char *))

      Add a callback routine to listen for a specific event.

    void Isevents init ()

      Initialize this module.

    void lsevents remove listener (char *, void(*cb)(char *))

      Remove a listener previously added with Isevents_add_listener.
• void lsevents_run ()
      Start up the thread and get out of the way.
void lsevents_send_event (char *,...)
      Call the callback routines for the given event.
• void Islogging_init ()
      Initialize the Islogging objects.

    void lslogging_log_message (char *fmt,...)

      The routine everyone will be talking about.
void lslogging_run ()
      Start up the worker thread.
• void lspg_demandairrights_all ()
      do nothing until we get airrights

    void lspg_getcenter_call ()

      Request a getcenter query.

    void lspg_getcenter_done ()

      Done with getcenter query.

    void lspg_getcenter_wait ()

      Wait for a getcenter query to return.
· void lspg getcurrentsampleid wait for id (unsigned int test)

    void lspg_init ()

      Initiallize the Ispg module.

    void lspg nextshot call ()

      Queue up a nextshot query.
void lspg_nextshot_done ()
      Called when the next shot query has been processed.

    void lspg nextshot wait ()

      Wait for the next shot query to get processed.
• void lspg_query_push (void(*cb)(lspg_query_queue_t *, PGresult *), char *fmt,...)
      Place a query on the queue.
• void lspg_run ()
      Start 'er runnin'.
• void <a href="seq_run_prep_all">lspg_seq_run_prep_all</a> (long long skey, double kappa, double phi, double cx, double cy, double ax,
  double ay, double az)
```

Convinence function to call seg run prep.

```
    void lspg_starttransfer_call (unsigned int nextsample, int sample_detected, double ax, double ay, double az,

  double horz, double vert, double esttime)

    void lspg_starttransfer_done ()

void lspg_starttransfer_wait ()

    void lspg_waitcryo_all ()

      no need to get fancy with the wait cryo command It should not return until the robot is almost ready for air rights

    void lspg_waitcryo_cb (lspg_query_queue_t *qqp, PGresult *pgr)

void lspg_zoom_lut_call ()

    int lspmac getBIPosition (lspmac bi t*)

      get binary input value

    void lspmac_home1_queue (lspmac_motor_t *mp)

      Home the motor.
void lspmac_abort ()
      abort motion and try to recover

    void lspmac_init (int, int)

      Initialize this module.

    int lspmac_jogabs_queue (lspmac_motor_t *, double)

      Use jog to move motor to requested position.

    int lspmac_move_or_jog_abs_queue (lspmac_motor_t *mp, double requested_position, int use_jo)

      Move method for normal stepper and servo motor objects Returns non-zero on abort, zero if OK.

    int lspmac_move_or_jog_preset_queue (lspmac_motor_t *, char *, int)

      move using a preset value returns 0 on success, non-zero on error

    void lspmac_move_or_jog_queue (lspmac_motor_t *, double, int)

• int lspmac_move_preset_queue (lspmac_motor_t *mp, char *preset_name)
      Move a given motor to one of its preset positions.

    int lspmac_moveabs_queue (lspmac_motor_t *, double)

      Use coordinate system motion program, if available, to move motor to requested position.

    int lspmac_moveabs_wait (lspmac_motor_t *mp, double timeout)

      Wait for motor to finish moving.

    void lspmac_run ()

      Start up the Ispmac thread.

    void Ispmac video rotate (double secs)

      Special motion program to collect centering video.

    int lsredis_cmpnstr (lsredis_obj_t *p, char *s, int n)

• int lsredis_cmpstr (lsredis_obj_t *p, char *s)

    int lsredis_find_preset (char *base, char *preset_name, double *dval)

    int lsredis_getb (lsredis_obj_t *p)

    double Isredis getd (Isredis obj t *p)

    void <u>lsredis_init</u> (char *pub, char *re, char *head)

      Initialize this module, that is, set up the connections.

    int Isredis regexec (const regex t *preg, Isredis obj t *p, size t nmatch, regmatch t *pmatch, int eflags)

• void Isredis run ()

    void Isredis setstr (Isredis obj t *p, char *fmt,...)

      Set the value and update redis.

    void lstimer_add_timer (char *, int, unsigned long int, unsigned long int)

      Create a timer.
void lstimer_init ()
      Initialize the timer list and pthread stuff.
• void lstimer_run ()
      Start up our thread.

    void Isupdate init ()

    void lsupdate_run ()
```

```
void md2cmds_init ()
         Initialize the md2cmds module.
    • void md2cmds_run ()
         Start up the thread.

    void pgpmac_printf (char *fmt,...)

          Terminal output routine ala printf.
Variables
    · lspg_waitcryo_t lspg_waitcryo
         signal the robot
    · lspg_getcurrentsampleid_t lspg_getcurrentsampleid
         our currentsample id

    lspg_demandairrights_t lspg_demandairrights

         our demandairrights object
    · Ispg getcenter t Ispg getcenter
         the getcenter object

    lspg_starttransfer_t lspg_starttransfer

         start a sample transfer
    · Ispg nextsample t Ispg nextsample
         the very next sample

    lspg_nextshot_t lspg_nextshot

         the nextshot object

    lspmac_motor_t lspmac_motors []

         All our motors.
    • Ispmac_motor_t * omega
         MD2 omega axis (the air bearing)

    Ispmac_motor_t * alignx

         Alignment stage X.

    Ispmac motor t * aligny

         Alignment stage Y.
    • Ispmac_motor_t * alignz
         Alignment stage X.
    • Ispmac_motor_t * anal
         Polaroid analyzer motor.
    lspmac_motor_t * zoom
          Optical zoom.
    Ispmac_motor_t * apery
         Aperture Y.
    Ispmac_motor_t * aperz
         Aperture Z.
    Ispmac_motor_t * capy
         Capillary Y.
    Ispmac_motor_t * capz
          Capillary Z.
    lspmac_motor_t * scint
         Scintillator Z.
    Ispmac_motor_t * cenx
          Centering Table X.
```

Ispmac_motor_t * ceny

```
Centering Table Y.
Ispmac_motor_t * kappa
     Карра.
• Ispmac motor t * phi
     Phi (not data collection axis)
lspmac_motor_t * fshut
     Fast shutter.
• Ispmac motor t * flight
     Front Light DAC.
Ispmac_motor_t * blight
     Back Light DAC.
lspmac_motor_t * fscint
     Scintillator Piezo DAC.
• Ispmac_motor_t * smart_mag_oo
     Smart Magnet on/off.
lspmac_motor_t * blight_ud
     Back light Up/Down actuator.
• Ispmac_motor_t * cryo
     Move the cryostream towards or away from the crystal.

    Ispmac motor t * dryer

     blow air on the scintilator to dry it off

    lspmac_motor_t * fluo

     Move the fluorescence detector in/out.
• Ispmac_motor_t * flight_oo
      Turn front light on/off.
lspmac_motor_t * blight_f
     Back light scale factor.
lspmac_motor_t * flight_f
     Front light scale factor.
· int Ispmac nmotors
     The number of motors we manage.
lspmac_bi_t * lp_air
     Low pressure air OK.
• lspmac_bi_t * hp_air
     High pressure air OK.

    Ispmac_bi_t * cryo_switch

     that little toggle switch for the cryo
• lspmac_bi_t * blight_down
     Backlight is down.
lspmac_bi_t * blight_up
     Backlight is up.
lspmac_bi_t * cryo_back
     cryo is in the back position

    Ispmac_bi_t * fluor_back

     fluor is in the back position
• lspmac_bi_t * sample_detected
     smart magnet detected sample
lspmac_bi_t * etel_ready
     ETEL is ready.
lspmac_bi_t * etel_on
```

ETEL is on.

```
lspmac_bi_t * etel_init_ok
     ETEL initialized OK.

    Ispmac bi t * minikappa ok

     Minikappa is OK (whatever that means)
lspmac_bi_t * smart_mag_on
     smart magnet is on
• Ispmac bi t * arm parked
     (whose arm? parked where?)
lspmac_bi_t * shutter_open
     shutter is open (note in pmc says this is a slow input)

    Ispmac bi t * smart mag off

     smart magnet is off

    Ispmac bi t * smart mag err

     smart magnet error (coil broken perhaps)
· struct timespec omega zero time
     Time we believe that omega crossed zero.

    WINDOW * term output

     place to print stuff out
WINDOW * term_input
     place to put the cursor
• WINDOW * term_status
     shutter, lamp, air, etc status

    WINDOW * term status2

     shutter, lamp, air, etc status
• pthread_mutex_t ncurses_mutex
     allow more than one thread access to the screen
· pthread cond t md2cmds cond
     condition to signal when it's time to run an md2 command

    pthread_mutex_t md2cmds_mutex

     mutex for the condition
pthread_cond_t md2cmds_pg_cond
pthread_mutex_t md2cmds_pg_mutex
pthread_mutex_t pmac_queue_mutex
     manage access to the pmac command queue

    pthread_cond_t pmac_queue_cond

     wait for a command to be sent to PMAC before continuing
pthread_mutex_t lspmac_shutter_mutex
     Coordinates threads reading shutter status.

    pthread_cond_t lspmac_shutter_cond

     Allows waiting for the shutter status to change.
• int lspmac_shutter_state
     State of the shutter, used to detect changes.
· int Ispmac shutter has opened
     Indicates that the shutter had opened, perhaps briefly even if the state did not change.

    pthread mutex t lspmac moving mutex

     Coordinate moving motors between threads.

    pthread_cond_t lspmac_moving_cond

     Wait for motor(s) to finish moving condition.
· int Ispmac moving flags
     Flag used to implement motor moving condition.
pthread_mutex_t md2_status_mutex
```

Synchronize reading/writting status buffer.

char md2cmds_cmd []

our command;

lsredis_obj_t * md2cmds_md_status_code

7.12.1 Detailed Description

Headers for the entire pgpmac project.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file pgpmac.h.

7.12.2 Macro Definition Documentation

7.12.2.1 #define _GNU_SOURCE

Definition at line 7 of file pgpmac.h.

7.12.2.2 #define LS_DISPLAY_WINDOW_HEIGHT 8

Number of status box rows.

Definition at line 57 of file pgpmac.h.

7.12.2.3 #define LS_DISPLAY_WINDOW_WIDTH 24

Number of status box columns.

Definition at line 61 of file pgpmac.h.

7.12.2.4 #define LS_PG_QUERY_STRING_LENGTH 1024

Fixed length postgresql query strings. Queries should all be function calls so this is not as weird as one might think. Definition at line 64 of file pgpmac.h.

7.12.2.5 #define LSEVENTS_EVENT_LENGTH 256

Fixed length for event names: simplifies string handling.

Definition at line 67 of file pgpmac.h.

7.12.2.6 #define MD2CMDS_CMD_LENGTH 32

Definition at line 484 of file pgpmac.h.

7.12.3 Typedef Documentation

7.12.3.1 typedef struct lspg_demandairrights_struct lspg_demandairrights_t

7.12.3.2 typedef struct lspg_getcenter_struct lspg_getcenter_t

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies.

7.12.3.3 typedef struct lspg_getcurrentsampleid_struct lspg_getcurrentsampleid_t

7.12.3.4 typedef struct lspg_nextsample_struct lspg_nextsample_t

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

7.12.3.5 typedef struct lspg_nextshot_struct lspg_nextshot_t

Storage definition for nextshot query.

The next shot query returns all the information needed to collect the next data frame. Since SQL allows for null fields independently from blank strings a separate integer is used as a flag for this case. This adds to the program complexity but allows for some important cases. Suck it up.definition of the next image to be taken (and the one after that, too!)

7.12.3.6 typedef struct lspgQueryQueueStruct lspg_query_queue_t

Store each query along with it's callback function.

All calls are asynchronous

7.12.3.7 typedef struct lspg_starttransfer_struct lspg_starttransfer_t

returns 1 if transfer can continue 0 to abort

7.12.3.8 typedef struct lspg_waitcryo_struct lspg_waitcryo_t

7.12.3.9 typedef struct lspmac_bi_struct lspmac_bi_t

Storage for binary inputs.

7.12.3.10 typedef struct lspmac_motor_struct lspmac_motor_t

Motor information.

A catchall for motors and motor like objects. Not all members are used by all objects.

7.12.3.11 typedef struct lsredis_obj_struct lsredis_obj_t

Redis Object Basic object whose value is sychronized with our redis db.

7.12.3.12 typedef struct Ispmac_cmd_queue_struct pmac_cmd_queue_t

PMAC command queue item.

Command queue items are fixed length to simplify memory management.

7.12.3.13 typedef struct tagEthernetCmd pmac_cmd_t

PMAC ethernet packet definition.

Taken directly from the Delta Tau documentation.

7.12.4 Function Documentation

7.12.4.1 void lsevents_add_listener (char * event, void(*)(char *) cb)

Add a callback routine to listen for a specific event.

Parameters

event	the name of the event to listen for
cb	the routine to call

Definition at line 75 of file Isevents.c.

```
lsevents_listener_t *new;
int err;
char *errbuf;
int nerrbuf:
new = calloc( 1, sizeof( lsevents_listener_t));
if ( new == NULL) {
 lslogging_log_message( "lsevents_add_listener: out of
  memory");
 exit( -1);
err = regcomp( &new->re, event, REG_EXTENDED | REG_NOSUB);
if ( err != 0) {
 nerrbuf = regerror( err, &new->re, NULL, 0);
  errbuf = calloc( nerrbuf, sizeof( char));
  if( errbuf == NULL) {
    {\tt lslogging\_log\_message("lsevents\_add\_listener: out}
    of memory (re)");
   exit(-1);
  regerror( err, &new->re, errbuf, nerrbuf);
lslogging_log_message( "lsevents_add_listener: %s",
    errbuf);
  free( errbuf);
  free ( new);
  return:
new->raw_regexp = strdup( event);
new->cb
          = cb;
pthread mutex lock( &lsevents listener mutex);
new->next = lsevents_listeners_p;
lsevents_listeners_p = new;
pthread_mutex_unlock( &lsevents_listener_mutex);
lslogging_log_message( "lsevents_add_listener: added
     listener for event %s", event);
```

```
7.12.4.2 void Isevents_init ( )
```

Initialize this module.

Definition at line 214 of file Isevents.c.

```
pthread_mutex_init( &lsevents_queue_mutex, NULL);
pthread_cond_init( &lsevents_queue_cond, NULL);
pthread_mutex_init( &lsevents_listener_mutex, NULL);
}
```

7.12.4.3 void | sevents_remove_listener (char * event, void(*)(char *) cb)

Remove a listener previously added with Isevents_add_listener.

Parameters

event	The name of the event
cb	The callback routine to remove

Definition at line 120 of file Isevents.c.

```
lsevents_listener_t *last, *current;
// Find the listener to remove
// and unlink it from the list
pthread_mutex_lock( &lsevents_listener_mutex);
last = NULL;
for( current = lsevents_listeners_p; current != NULL;
    current = current->next) {
  if( strcmp( last->raw_regexp, event) == 0 && last->cb == cb) {
    if( last == NULL) {
      lsevents_listeners_p = current->next;
    } else {
      last->next = current->next;
pthread_mutex_unlock( &lsevents_listener_mutex);
// Now remove it
if( current != NULL) {
   if( current->raw_regexp != NULL)
    free( current->raw_regexp);
  free (current);
```

7.12.4.4 void Isevents_run ()

Start up the thread and get out of the way.

Definition at line 222 of file Isevents.c.

7.12.4.5 void lsevents_send_event (char * fmt, ...)

Call the callback routines for the given event.

Parameters

fmt	a printf style formating string
	list of arguments specified by the format string

Definition at line 45 of file Isevents.c.

7.12.4.6 void Islogging_init ()

Initialize the Islogging objects.

Definition at line 37 of file Islogging.c.

```
pthread_mutex_init( &lslogging_mutex, NULL);
pthread_cond_init( &lslogging_cond, NULL);
lslogging_file = fopen( LSLOGGING_FILE_NAME,
    "w");
```

7.12.4.7 void lslogging_log_message (char * fmt, ...)

The routine everyone will be talking about.

Parameters

fmt	A printf style formating string.
	The arguments specified by fmt

Definition at line 48 of file Islogging.c.

```
char msg[LSLOGGING_MSG_LENGTH];
```

```
struct timespec theTime;
va_list arg_ptr;
unsigned int on;

clock_gettime( CLOCK_REALTIME, &theTime);

va_start( arg_ptr, fmt);
vsnprintf( msg, sizeof(msg)-1, fmt, arg_ptr);
va_end( arg_ptr);
msg[sizeof(msg)-1]=0;

pthread_mutex_lock( &lslogging_mutex);

on = (lslogging_on++) % LSLOGGING_QUEUE_LENGTH
    ;
strncpy( lslogging_queue[on].lmsg, msg, LSLOGGING_MSG_LENGTH
    -1);
lslogging_queue[on].lmsg[LSLOGGING_MSG_LENGTH
    -1] = 0;

memcpy( &(lslogging_queue[on].ltime), &theTime, sizeof(theTime
    ));

pthread_cond_signal( &lslogging_cond);
pthread_mutex_unlock( &lslogging_mutex);
```

7.12.4.8 void Islogging_run ()

Start up the worker thread.

Definition at line 105 of file Islogging.c.

```
pthread_create( &lslogging_thread, NULL, &lslogging_worker
    , NULL);
lslogging_log_message( "Start up");
```

7.12.4.9 char** lspg_array2ptrs (char *)

returns a null terminated list of strings parsed from postgresql array

Definition at line 161 of file lspg.c.

```
char **rtn, *sp, *acums;
int i, n, inquote, havebackslash, rtni;;
int mxsz;
havebackslash = 0;
// Despense with the null input condition before we complicate the code below if( a == NULL || a[0] != '\{' || a[strlen(a)-1] != '\}')
// Count the maximum number of strings
// Actual number will be less if there are quoted commas
11
n = 1;
for ( i=0; a[i]; i++) {
  if ( a[i] == ',')
    n++;
^{\prime\prime} // The maximum size of any string is the length of a (+1)
mxsz = strlen(a) + 1;
// This is the accumulation string to make up the array elements
acums = (char *)calloc( mxsz, sizeof( char));
if ( acums == NULL) {
  lslogging_log_message( "lspg_array2ptrs: out of memory
      (acums)");
```

```
exit( 1);
// allocate storage for the pointer array and the null terminator
rtn = (char **)calloc( n+1, sizeof( char *));
if( rtn == NULL) {
lslogging_log_message( "lspg_array2ptrs: out of memory
    (rtn)");
 exit( 1);
rtni = 0;
// Go through and create the individual strings
sp = acums;
*sp = 0;
inquote = 0;
havebackslash = 0;
for( i=1; a[i] != 0; i++) {
  switch( a[i]) {
  case '"':
     , ...vebackslash) {
// a quoted quote. Cool
//
    if( havebackslash) {
      *(sp++) = a[i];
      *sp = 0;
     havebackslash = 0;
    } else {
      // Toggle the flag
      inquote = 1 - inquote;
    break;
  case '\\':
   if( havebackslash) {
     *(sp++) = a[i];
      *sp = 0;
      havebackslash = 0;
    } else {
     havebackslash = 1;
    break;
  case ',':
   if( inquote || havebackslash) {
     *(sp++) = a[i];
*sp = 0;
     havebackslash = 0;
     rtn[rtni++] = strdup( acums);
      sp = acums;
    break:
  case '}':
    if( inquote || havebackslash) {
     *(sp++) = a[i];
*sp = 0;
     havebackslash = 0;
    } else {
     rtn[rtni++] = strdup( acums);
      rtn[rtni] = NULL;
      free( acums);
     return( rtn);
   break:
  default:
   *(sp++) = a[i];
    *sp = 0;
   havebackslash = 0;
}
// Getting here means the final '}' was missing
// Probably we should throw an error or log it or something.
// Through out the last entry since this there is not resonable expectation
    that
// we should be parsing it anyway.
rtn[rtni] = NULL;
free( acums);
return( rtn);
```

```
7.12.4.10 void lspg_demandairrights_all ( )
do nothing until we get airrights
Definition at line 556 of file lspg.c.
  lspg_demandairrights_call();
  lspg_demandairrights_wait();
// there is no "done" version
7.12.4.11 void lspg_getcenter_call ( )
Request a getcenter query.
Definition at line 1177 of file lspg.c.
  pthread_mutex_lock( &lspg_getcenter.mutex);
  lspg_getcenter.new_value_ready = 0;
pthread_mutex_unlock( &lspg_getcenter.mutex);
  lspg_query_push( lspg_getcenter_cb, "SELECT *
        FROM px.getcenter2()");
7.12.4.12 void lspg_getcenter_done ( )
Done with getcenter query.
Definition at line 1195 of file lspg.c.
  pthread_mutex_unlock( &(lspg_getcenter.mutex));
7.12.4.13 void lspg_getcenter_wait ( )
Wait for a getcenter query to return.
Definition at line 1187 of file lspg.c.
  pthread_mutex_lock( &(lspg_getcenter.mutex));
   while( lspg_getcenter.new_value_ready == 0)
    pthread_cond_wait( &(lspg_getcenter.cond), &(
       lspg_getcenter.mutex));
7.12.4.14 void lspg_getcurrentsampleid_wait_for_id ( unsigned int test )
Definition at line 393 of file lspg.c.
  pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
      );
  while( lspg_getcurrentsampleid.getcurrentsampleid
    pthread_cond_wait( &lspg_getcurrentsampleid.cond
       , &lspg_getcurrentsampleid.mutex);
  \verb|pthread_mutex_unlock| ( &lspg_getcurrentsampleid.mutex|
      );
```

```
7.12.4.15 void lspg_init ( )
```

Initiallize the Ispg module.

Definition at line 1758 of file Ispg.c.

```
pthread_mutex_init( &lspg_queue_mutex, NULL);
pthread_cond_init( &lspg_queue_cond, NULL);

lspg_demandairrights_init();
lspg_getcenter_init();
lspg_getcurrentsampleid_init();
lspg_lock_detector_init();
lspg_lock_diffractometer_init();
lspg_nextsample_init();
lspg_nextshot_init();
lspg_nextshot_init();
lspg_seq_run_prep_init();
lspg_starttransfer_init();
lspg_wait_for_detector_init();
lspg_wait_ron_init();
```

7.12.4.16 unsigned int lspg_nextsample_all (int * err)

Definition at line 468 of file lspg.c.

```
unsigned int rtn;
lspg_nextsample_call();
lspg_nextsample_wait();

if( lspg_nextsample.no_rows_returned) {
   rtn = 0;
   *err = 1;
} else {
   if( lspg_nextsample.nextsample_isnull) {
      rtn = 0;
      *err = 1;
} else {
      rtn = lspg_nextsample.nextsample;
      *err = 0;
}
lspg_nextsample_done();

return rtn;
```

7.12.4.17 void lspg_nextshot_call ()

Queue up a nextshot query.

Definition at line 824 of file lspg.c.

7.12.4.18 void lspg_nextshot_done ()

Called when the next shot query has been processed.

Definition at line 842 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_nextshot.mutex));
}
```

7.12.4.19 void lspg_nextshot_wait ()

Wait for the next shot query to get processed.

Definition at line 834 of file lspg.c.

```
pthread_mutex_lock( &(lspg_nextshot.mutex));
while( lspg_nextshot.new_value_ready == 0)
  pthread_cond_wait( &(lspg_nextshot.cond), &(lspg_nextshot.mutex));
```

7.12.4.20 void lspg_query_push (void(*)(lspg_query_queue_t *, PGresult *) cb, char * fmt, ...)

Place a query on the queue.

Parameters

in	cb	Our callback function that deals with the response
in	fmt	Printf style function to generate the query

Definition at line 234 of file kvredis.c.

```
int idx;
 va_list arg_ptr;
 // Pause the thread while we service the queue
 if( (lspg_query_queue_on + 1) % LS_PG_QUERY_QUEUE_LENGTH
      == lspg_query_queue_off % LS_PG_QUERY_QUEUE_LENGTH
   fprintf( stderr, "lspg_query_push: queue is full. Ignoring query \"%s\"\n"
     , fmt);
 idx = lspg_query_queue_on % LS_PG_QUERY_QUEUE_LENGTH
 va_start( arg_ptr, fmt);
 va_end( arg_ptr);
 lspg_query_queue[idx].qs[LS_PG_QUERY_STRING_LENGTH
     -1] = 0;
 lspg_query_queue[idx].onResponse = cb;
 lspg_query_queue_on++;
} ;
```

7.12.4.21 void lspg_run ()

Start 'er runnin'.

Definition at line 1777 of file lspg.c.

```
{
    pthread_create( &lspg_thread, NULL, lspg_worker, NULL);
    lsevents_add_listener( "Sample(Detected|Absent)",
```

```
lspmac_sample_detector_cb);
}
```

7.12.4.22 void lspg_seq_run_prep_all (long long *skey*, double *kappa*, double *phi*, double *cx*, double *cy*, double *ax*, double *ax*, double *ax*

Convinence function to call seq run prep.

Parameters

in	skey	px.shots key for this image
in	kappa	current kappa postion
in	phi	current phi postition
in	CX	current center table x
in	су	current center table y
in	ax	current alignment table x
in	ay	current alignment table y
in	az	current alignment table z

Definition at line 1095 of file lspg.c.

```
lspg_seq_run_prep_call( skey, kappa, phi, cx,
      cy, ax, ay, az);
lspg_seq_run_prep_wait();
lspg_seq_run_prep_done();
}
```

7.12.4.23 void lspg_starttransfer_call (unsigned int *nextsample*, int *sample_detected*, double *ax*, double *ay*, double *az*, double *horz*, double *vert*, double *esttime*)

Definition at line 302 of file lspg.c.

7.12.4.24 void lspg_starttransfer_done ()

Definition at line 317 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_starttransfer.mutex));
```

7.12.4.25 void lspg_starttransfer_wait ()

Definition at line 311 of file lspg.c.

```
pthread_mutex_lock( &(lspg_starttransfer.mutex));
  while( lspg_starttransfer.new_value_ready ==
       0)
    pthread_cond_wait( &(lspg_starttransfer.cond), &(
      lspg_starttransfer.mutex));
7.12.4.26 void lspg_waitcryo_all()
no need to get fancy with the wait cryo command It should not return until the robot is almost ready for air rights
Definition at line 507 of file lspg.c.
  pthread_mutex_lock( &lspg_waitcryo.mutex);
  lspg_waitcryo.new_value_ready = 0;
  lspg_query_push( lspg_waitcryo_cb, "SELECT
    px.waitcryo())");
  while( lspg_waitcryo.new_value_ready == 0)
    pthread_cond_wait( &lspg_waitcryo.cond, &lspg_waitcryo
      .mutex);
 pthread_mutex_unlock( &lspg_waitcryo.mutex);
7.12.4.27 void lspg_waitcryo_cb ( lspg_query_queue_t * qqp, PGresult * pgr )
Definition at line 497 of file lspg.c.
  pthread_mutex_lock( &lspg_waitcryo.mutex);
  lspg_waitcryo.new_value_ready = 1;
pthread_cond_signal(&lspg_waitcryo.cond);
  pthread_mutex_unlock( &lspg_waitcryo.mutex);
7.12.4.28 void lspg_zoom_lut_call ( )
7.12.4.29 void lspmac_abort ( )
abort motion and try to recover
Definition at line 2012 of file Ispmac.c.
  // Stop everything! (consider ^O instead of ^A)
  lspmac_SockSendDPControlChar( "Abort Request", 0
      x01);
7.12.4.30 int lspmac_getBlPosition ( lspmac_bi_t * )
```

Definition at line 1579 of file Ispmac.c.

get binary input value

```
int rtn;
pthread_mutex_lock( &bip->mutex);
rtn = bip->position;
pthread_mutex_unlock( &bip->mutex);
return rtn;
}
```

7.12.4.31 double lspmac_getPosition (Ispmac_motor_t * mp)

get the motor position (with locking)

Parameters

```
mp | the motor object
```

Definition at line 1339 of file Ispmac.c.

```
double rtn;
pthread_mutex_lock( &(mp->mutex));
rtn = mp->position;
pthread_mutex_unlock( &(mp->mutex));
return rtn;
}
```

7.12.4.32 void lspmac_home1_queue (lspmac_motor_t * mp)

Home the motor.

Parameters

```
in mp motor we are concerned about
```

Definition at line 1205 of file Ispmac.c.

```
int i;
int motor_num;
int coord_num;
pthread_mutex_lock( &(mp->mutex));
motor_num = lsredis_get1( mp->motor_num);
coord_num = lsredis_get1( mp->coord_num);
          = lsredis_get_string_array( mp->home);
// Each of the motors should have this defined // but let's not seg fault if home is missing
if ( home == NULL || *home == NULL) {
 //
// Note we are already initialized
  // so if we are here there is something wrong.
  lslogging_log_message( "lspmac_homel_queue: null or
     empty home strings for motor %s", mp->name);
  pthread_mutex_unlock( & (mp->mutex));
// We've already been called. Don't home again until
// we're finish with the last time.
if( mp->homing) {
 pthread_mutex_unlock( & (mp->mutex));
  return;
```

```
// Don't go on if any other motors in this coordinate system are homing.
// It's possible to write the homing program to home all the motors in the
     coordinate
// system. TODO (hint hint)
if( coord_num > 0) {
  for( i=0; i<lspmac_nmotors; i++) {</pre>
    if( &(lspmac_motors[i]) == mp)
       continue;
    if( lsredis_getl(lspmac_motors[i].coord_num) ==
    coord_num) {
      int nogo;
      pthread_mutex_lock( &(lspmac_motors[i].mutex));
      //
// Don't go on if
      11
             we are homing
                                     or
                                             ( not in position
     while
              in open loop)
       if( lspmac_motors[i].homing || (((lspmac_motors
     [i].status2 & 0x01)==0) && ((lspmac_motors[i].status1 & 0x040000)
     ! = 0)))
        nogo = 1;
      pthread_mutex_unlock( &(lspmac_motors[i].mutex));
       if( nogo) {
        pthread_mutex_unlock( & (mp->mutex));
         return;
      }
    }
  }
mp->homing = 1;
mp->not_done = 1;
mp->motion_seen = 0;
                        // set up waiting for cond
// This opens the control loop.
// The status routine should notice this and the fact that
// the homing flag is set and call on the home2 routine
^{\prime\prime} Only send the open loop command if we are not in
// open loop mode already. This test might prevent a race condition // where we've already moved the home2 routine (and queue the homing program
     motion)
// before the open loop command is dequeued and acted on.
if( ~(mp->status1) & 0x040000) {
  lspmac_SockSendDPline( mp->name, "#%d$*",
    motor_num);
pthread_mutex_unlock( &(mp->mutex));
lsevents_send_event( "%s Homing", mp->name);
```

7.12.4.33 void Ispmac_init (int, int)

Initialize this module.

Definition at line 3132 of file Ispmac.c.

```
d2_status_t *p;
pthread_mutexattr_t mutex_initializer;

// Set our global harvest flags
getivars = ivarsflag;
getmvars = mvarsflag;

// Use recursive mutexs

//
pthread_mutexattr_init( &mutex_initializer);
pthread_mutexattr_settype( &mutex_initializer, PTHREAD_MUTEX_RECURSIVE);

// All important status mutex
pthread_mutex_init( &md2_status_mutex, &mutex_initializer);

//
// Get the MD2 initialization strings
//
// lspmac_md2_init = lsredis_get_obj( "md2_pmac.init"); // hard coded now.
```

```
//
// Initialize the motor objects
p = &md2_status;
omega = lspmac_motor_init( &(lspmac_motors
        lspmac_moveabs_queue);
alignx = lspmac_motor_init( &(lspmac_motors
       gnx = lspmac_motor_init( & \text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\texi}\tint{\text{\text{\text{\text{\text{\text{\text{\text{\text{\te\
        lspmac_moveabs_queue);
aligny = lspmac_motor_init( &(lspmac_motors
    [ 2]), 0, 2, &p->aligny_act_pos, &p->aligny_status_1
    , &p->aligny_status_2, "Align Y #3 &3 Y", "align.y",
        lspmac_moveabs_queue);
alignz = lspmac_motor_init( &(lspmac_motors
       lspmac_moveabs_queue);
             = lspmac_motor_init( &(lspmac_motors
        [ 4]), 0, 4, &p->analyzer_act_pos, &p->analyzer_status_1, &p->analyzer_status_2, "Anal #5", "lightPolar
                                                                                                     "lightPolar",
        lspmac_moveabs_queue);
             = lspmac_motor_init( &(lspmac_motors
       [5]), 1, 0, &p->zoom_act_pos, &p->zoom_status_1, &p->zoom_status_2, "Zoom #6 &4 Z", "cam.z
                                                                                    #6 &4 Z", "cam.zoom",
                 &p->zoom_status_2,
        lspmac_movezoom_queue);
apery = lspmac_motor_init( &(lspmac_motors
  [ 6]), 1, 1, &p->aperturey_act_pos, &p->aperturey_status_1
  , &p->aperturey_status_2, "Aper Y #7 &5 Y", "appy",
        lspmac_moveabs_queue);
             = lspmac_motor_init( &(lspmac_motors
        [7]), 1, 2, &p->aperturez_act_pos, &p->aperturez_status_1, &p->aperturez_status_2, "Aper Z #8 &5 Z", "appz",
        lspmac_moveabs_queue);
              = lspmac_motor_init( &(lspmac_motors
        [ 8]), 1, 3, &p->capy_act_pos, &p->capy_status_1, &p->capy_status_2, "Cap Y #9 &5 U", "capy",
                 &p->capy_status_2,
        lspmac_moveabs_queue);
              = lspmac_motor_init( &(lspmac_motors
        &p->capz_status_2,
        lspmac_moveabs_queue);
       lspmac_moveabs_queue);
              = lspmac_motor_init( &(lspmac_motors
        [11]), 2, 1, &p->centerx_act_pos, &p->centerx_status_1
, &p->centerx_status_2, "Cen X #17 &2 X", "centering.x",
        lspmac_moveabs_queue);
// = lspmac_motor_init( &(lspmac_motors)
        [12]), 2, 2, &p->centery_act_pos, &p->centery_status_1
, &p->centery_status_2, "Cen Y #18 &2 Y", "centering.y",
        lspmac_moveabs_queue);
       lspmac_moveabs_queue);
             = lspmac_motor_init( &(lspmac_motors[
        14]), 2, 4, &p->phi_act_pos,
                                                                             &p->phi_status_1,
                                                            os, &p->phi_status_i
"Phi #20 &7 Y", "phi",
            &p->phi_status_2,
        lspmac_moveabs_queue);
fshut = lspmac_fshut_init( &(lspmac_motors
        [15]));
6]), &p->front_dac,
        lspmac_movedac_queue);
Ispmac_movedac_queue,,
blight = lspmac_dac_init( &(lspmac_motors[1
    71). &p->back_dac, "M1201", "backLight.intensity",
        lspmac_movedac_queue);
fscint = lspmac_dac_init( &(lspmac_motors[1
  8]), &p->scint_piezo, "M1203", "scint.focus",
        lspmac_movedac_queue);
smart_mag_oo = lspmac_bo_init( &(lspmac_motors
[19]), "smartMagnet","M1100=%d", &(md2_status.acc11c_5), 0x01)
      ght_ud = lspmac_bo_init( &(lspmac_motors
  [20]), "backLight", "M1101=%d", &(md2_status.acc11c_5), 0x02)
blight_ud
crvo
                           = lspmac_bo_init( &(lspmac_motors
```

```
[21]), "cryo",
                           "M1102=%d", & (md2_status.acc11c_5), 0x04)
             = lspmac_bo_init( &(lspmac_motors dryer", "M1103=%d", &(md2_status.acc11c_5), 0x08)
    [22]), "dryer",
             = lspmac_bo_init( &(lspmac_motors
fluo
                           "M1104=%d", & (md2_status.acc11c_5), 0x10)
    [23]), "fluo",
    ht_oo = lspmac_soft_motor_init( &(
lspmac_motors[24]), "frontLight",
lspmac_moveabs_frontlight_oo_queue);
flight_oo
             = lspmac_soft_motor_init( &(
blight f
    lspmac_motors[25]), "backLight.factor",
    lspmac_moveabs_blight_factor_queue);
              = lspmac_soft_motor_init( &(
    lspmac_motors[26]), "frontLight.factor",
    lspmac_moveabs_flight_factor_queue);
                 = lspmac_bi_init( &(lspmac_bis[
     0]), &(md2_status.acc11c_1), 0x01, "Low Pressure Air OK", "
    Low Pressure Air Failed");
hp_air
                = lspmac_bi_init( &(lspmac_bis[
    1]), & (md2_status.accl1c_1), 0x02, "High Pressure Air OK", "
    High Pressure Air Failed");
                = lspmac_bi_init( &(lspmac_bis
cryo_switch
    [ 2]), & (md2_status.acc11c_1), 0x04, "CryoSwitchChanged",
    "CryoSwitchChanged");
    ht_down = lspmac_bi_init( &(lspmac_bis
[ 3]), &(md2_status.acc1lc_1), 0x08, "Backlight Down",
blight_down
    "Backlight Not Down");
                = lspmac_bi_init( &(lspmac_bis
blight up
    [ 4]), & (md2_status.acc11c_1), 0x10, "Backlight Up",
    "Backlight Not Up");
                = lspmac_bi_init( &(lspmac_bis
cryo_back
    [ 5]), &(md2_status.accl1c_1), 0x40, "Cryo Back", "Cryo Not Back");
              = lspmac bi init( &(lspmac bis
fluor back
      6]), &(md2_status.acc11c_2), 0x01, "Fluor. Det. Parked",
    "Fluor. Det. Not Parked");
sample_detected = lspmac_bi_init( &(lspmac_bis
    [ 7]), & (maz_sec., "SampleAbsent"); = lsr
      7]), & (md2_status.acc11c_2), 0x02, "SamplePresent",
etel_ready = lspmac_bi_init( &(lspmac_bis
      [ 8]), &(md2_status.acc1lc_2), 0x20, "ETEL Ready",
    "ETEL Not Ready");
                 = lspmac_bi_init( &(lspmac_bis
    [ 9]), &(md2_status.acc11c_2), 0x40, "ETEL On",
    "ETEL Off");
                = lspmac bi init( &(lspmac bis
etel_init_ok
    [10]), & (md2_status.acc11c_2), 0x80, "ETEL Init OK",
    "ETEL Init Not OK");
                = lspmac_bi_init( &(lspmac_bis
minikappa_ok
    [11]), &(md2_status.acc11c_3), 0x01, "Minikappa OK",
    "Minikappa Not OK");
    ct_mag_on = lspmac_bi_init( &(lspmac_bis
[12]), &(md2_status.acc11c_3), 0x04, "Smart Magnet On",
smart_mag_on
    "Smart Magnet Not On");
                = lspmac_bi_init( &(lspmac_bis
arm_parked
    [13]), &(md2_status.acc11c_3), 0x08, "Arm Parked",
    "Arm Not Parked");
'Smart Magnet OK");
    ter_open = lspmac_bi_init( &(lspmac_bis [15]), &(md2_status.accl1c_3), 0x100, "Shutter Open",
shutter_open
    "Shutter Not Open");
    t_mag_off = lspmac_bi_init( &(lspmac_bis [16]), &(md2_status.acc11c_5), 0x01, "Smart Magnet Off",
smart_mag_off
    "Smart Magnet Not Off");
^{\prime\prime} // Initialize several commands that get called, perhaps, alot
rr_cmd.RequestType = VR_UPLOAD;
rr_cmd.Request = VR_PMAC_READREADY;
rr_cmd.wValue = 0;
rr_cmd.wValue
                  = 0;
= htons(2);
rr_cmd.wIndex
rr cmd.wLength
memset( rr_cmd.bData, 0, sizeof(rr_cmd.bData));
gb_cmd.RequestType = VR_UPLOAD;
ab cmd.wIndex
                    = 0;
```

```
gb_cmd.wLength
                    = htons(1400);
memset( gb_cmd.bData, 0, sizeof(gb_cmd.bData));
cr_cmd.RequestType = VR_UPLOAD;
cr_cmd.Request = VR_CTRL_RESPONSE;
                    = 0;
cr cmd.wValue
                 = 0;
= htons(1400);
cr_cmd.wIndex
cr_cmd.wLength
memset( cr_cmd.bData, 0, sizeof(cr_cmd.bData));
// Initialize some mutexs and conditions
pthread_mutex_init( &pmac_queue_mutex, &mutex_initializer);
pthread_cond_init( &pmac_queue_cond, NULL);
lspmac_shutter_state = 0;
     assume the shutter is now closed: not a big deal if we are wrong
pthread_mutex_init( &lspmac_shutter_mutex, &
    mutex_initializer);
pthread_cond_init( &lspmac_shutter_cond, NULL);
pmacfd.fd = -1;
pthread_mutex_init( &lspmac_moving_mutex, &
    mutex_initializer);
pthread_cond_init( &lspmac_moving_cond, NULL);
pthread_mutex_init( &lspmac_ascii_mutex, &mutex_initializer
    );
pthread_mutex_init( &lspmac_ascii_buffers_mutex, &
    mutex_initializer);
// clear the ascii communications buffers
  uint32_t cc;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
lspmac_SockSendDPline( NULL, "I5=0");
lspmac_SockSendDPline( NULL, "ENABLE PLCC 0,2");
lspmac_SockSendDPline( NULL, "DISABLE PLCC 1");
lspmac_SockSendDPline( NULL, "I5=3");
```

7.12.4.34 int lspmac_jogabs_queue (lspmac_motor_t * , double)

Use jog to move motor to requested position.

Definition at line 2871 of file Ispmac.c.

7.12.4.35 int lspmac_move_or_jog_abs_queue (lspmac_motor_t * mp, double requested_position, int use_jo)

Move method for normal stepper and servo motor objects Returns non-zero on abort, zero if OK.

- < format string for coordinate system move
- < coordinate system bit
- < the requested position in units of "counts"

< motor and coordinate system;

< our axis

Parameters

in	тр	The motor to move
in	requested	Where to move it
	position	
in	use_jo	1 to force jog, 0 for motion prog

Definition at line 2664 of file Ispmac.c.

```
char *fmt;
int q100;
int requested_pos_cnts;
int coord_num, motor_num;
char *axis;
double u2c;
double neutral_pos;
double min_pos, max_pos;
int pos_limit_hit, neg_limit_hit;
struct timespec timeout, now;
int err;
pthread_mutex_lock( &(mp->mutex));
              = lsredis_getd(
u2c
                                 mp->u2c);
                                mp->motor_num);
mp->coord_num);
              = lsredis_getl(
motor num
            = isredis_get1(
coord_num
axis
              = lsredis_getstr( mp->axis);
axis = isredis_getst( mp->axis),
neutral_pos = lsredis_getd( mp->neutral_pos);
min_pos = lsredis_getd( mp->min_pos);
max_pos = lsredis_getd( mp->max_pos);
pos_limit_hit = lsredis_getd( mp->pos_limit_hit);
neg_limit_hit = lsredis_getd( mp->neg_limit_hit);
if( u2c == 0.0 || requested_position < min_pos || requested_position >
    max_pos) {
  // Shouldn't try moving a motor that's in trouble
  //
  pthread_mutex_unlock( & (mp->mutex));
  , u2c, requested_position, min_pos, max_pos);
lsevents_send_event( "%s Move Aborted", mp->name);
  return 1;
&& (requested_position > mp->position))) {
  limit=%d high limit=%d",
                           mp->name, requested_position, mp->position
  , neg_limit_hit, pos_limit_hit);
lsevents_send_event( "%s Move Aborted", mp->name);
  return 2;
mp->requested_position = requested_position;
mp->not_done = 1;
mp->motion_seen = 0;
mp->command_sent = 0;
mp->requested_pos_cnts = u2c * (requested_position +
    neutral_pos);
requested_pos_cnts = mp->requested_pos_cnts;
if( use_jog || axis == NULL || *axis == 0) {
 use_jog = 1;
} else {
  use_jog = 0;
  q100 = 1 << (coord_num -1);
pthread_mutex_unlock( & (mp->mutex));
if( !use_jog) {
```

```
^{\prime\prime} Make sure the coordinate system is not moving something, wait if it is
pthread_mutex_lock( &lspmac_moving_mutex);
clock_gettime( CLOCK_REALTIME, &now);
// TODO: Have all moves estimate how long they'll take and use that here
                                              // a long timeout, but
timeout.tv_sec = now.tv_sec + 60.0;
  we might really be moving something that takes this long (or longer)
timeout.tv_nsec = now.tv_nsec;
while( err == 0 && (lspmac_moving_flags & q100) != 0)
  err = pthread_cond_timedwait( &lspmac_moving_cond, &
  lspmac_moving_mutex, &timeout);
pthread_mutex_unlock( &lspmac_moving_mutex);
if( err == ETIMEDOUT) {
  lslogging_log_message( "
  lspmac_move_or_jog_abs_queue: Done. lspmac_moving_flags = %0x", lspmac_moving_flags);
lsevents_send_event( "%s Move Aborted", mp->name);
  return 1;
// Set the "we are moving this coordinate system" flag
lspmac_SockSendDPline( NULL, "M5075=(M5075 | %d)",
  q100);
switch( *axis) {
case 'A':
  fmt = "&%d Q16=%d Q100=%d B146R";
 break;
case 'B':
  fmt = "&%d Q17=%d Q100=%d B147R";
  break;
case 'C':
 fmt = "&%d Q18=%d Q100=%d B148R";
  break;
 fmt = "&%d Q10=%d Q100=%d B140R";
 break;
 fmt = "&%d Q11=%d Q100=%d B141R";
case 'Z':
  fmt = "&%d Q12=%d Q100=%d B142R";
 break;
case 'U':
  fmt = "&%d Q13=%d Q100=%d B143R";
 break:
case 'V':
  fmt = "&%d Q14=%d Q100=%d B144R";
 break;
case 'W':
   fmt = "&%d Q15=%d Q100=%d B145R";
 break:
^{\prime\prime} // Make sure the flag has been seen
clock_gettime( CLOCK_REALTIME, &now);
timeout.tv_sec = now.tv_sec + 4.0;
                                                    // also a long timeout.
   This should really only take a few milliseconds on a slow day
timeout.tv_nsec = now.tv_nsec;
pthread_mutex_lock( &lspmac_moving_mutex);
while( err == 0 && (lspmac_moving_flags & q100) == 0)
  err = pthread_cond_timedwait( &lspmac_moving_cond, &
  lspmac_moving_mutex, &timeout);
pthread_mutex_unlock( &lspmac_moving_mutex);
```

```
if( err == ETIMEDOUT) {
    lslogging_log_message( "
    lspmac_move_or_jog_abs_queue: Did not see flag propagate. Move aborted. lspmac_moving_flags = %0x",
    lspmac_moving_flags);
    lsevents_send_event( "%s Move Aborted", mp->name);
    return 1;
}

pthread_mutex_lock( &(mp->mutex));
if( use_jog) {
    lspmac_SockSendDPline( mp->name, "#%d j=%d",
        motor_num, requested_pos_cnts);
} else {
    lspmac_SockSendDPline( mp->name, fmt, coord_num,
        requested_pos_cnts, q100);
}
pthread_mutex_unlock( &(mp->mutex));
free( axis);
return 0;
```

7.12.4.36 int lspmac_move_or_jog_preset_queue (lspmac_motor_t * , char * , int)

move using a preset value returns 0 on success, non-zero on error

Definition at line 2833 of file Ispmac.c.

```
double pos;
int err;
int err;
int rtn;

if( preset == NULL || *preset == 0) {
    lsevents_send_event( "%s Move Aborted", mp->name);
    return 0;
}

err = lsredis_find_preset( mp->name, preset, &pos);

if( err != 0)
    rtn = lspmac_move_or_jog_abs_queue( mp, pos,
        use_jog);

else {
    lsevents_send_event( "%s Move Aborted", mp->name);
    rtn = 1;
}
return rtn;
```

- 7.12.4.37 void lspmac_move_or_jog_queue (lspmac_motor_t * , double , int)
- 7.12.4.38 int lspmac_move_preset_queue (lspmac_motor_t * mp, char * preset_name)

Move a given motor to one of its preset positions.

No movement if the preset is not found.

Parameters

n	p Ispmac motor pointer	
preset_nan	e Name of the preset to use	

Definition at line 2351 of file Ispmac.c.

```
double pos;
int err;
lslogging_log_message( "lspmac_move_preset_queue: Called
```

```
with motor %s and preset named '%s'", mp->name, preset_name);
err = lsredis_find_preset( mp->name, preset_name, &pos
    );
if( err == 0)
  return 1;

err = mp->moveAbs( mp, pos);
if( !err)
  lslogging_log_message( "lspmac_move_preset_queue:
    moving %s to preset '%s' (%f)", mp->name, preset_name, pos);
//
// the abort event should have been sent in moveAbs
//
return err;
```

7.12.4.39 int lspmac_moveabs_queue (lspmac_motor_t * , double)

Use coordinate system motion program, if available, to move motor to requested position.

Definition at line 2861 of file Ispmac.c.

```
return lspmac_move_or_jog_abs_queue( mp,
    requested_position, 0);
}
```

7.12.4.40 int lspmac_moveabs_wait (Ispmac_motor_t * mp, double timeout_secs)

Wait for motor to finish moving.

Assume motion already queued, now just wait

Parameters

тр	The motor object to wait for
timeout_secs	The number of seconds to wait for. Fractional values fine.

Definition at line 2886 of file Ispmac.c.

```
struct timespec timeout, now;
double isecs, fsecs;
int err;
// Copy the queue item for the most recent move request
clock_gettime( CLOCK_REALTIME, &now);
fsecs = modf( timeout_secs, &isecs);
timeout.tv_sec = now.tv_sec + (long)floor( isecs);
timeout.tv_nsec = now.tv_nsec + (long)floor( fsecs * 1.0e9);
timeout.tv_sec += timeout.tv_nsec / 1000000000;
timeout.tv_nsec %= 1000000000;
pthread_mutex_lock( &(mp->mutex));
while( err == 0 && mp->command_sent == 0)
  err = pthread_cond_timedwait( &mp->cond, &mp->mutex, &timeout);
pthread_mutex_unlock( & (mp->mutex));
if( err != 0) {
  if( err != ETIMEDOUT) {
    lslogging_log_message( "lspmac_moveabs_wait:
     unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
  return 1;
```

```
}
// wait for the motion to have started
// This will time out if the motion ends before we can read the status back // hence the added complication of time stamp of the sent packet.
pthread_mutex_lock( &(mp->mutex));
while( err == 0 && mp->motion_seen == 0)
  err = pthread_cond_timedwait( &(mp->cond), &(mp->mutex), &timeout)
if( err != 0) {
  if( err != ETIMEDOUT) {
    lslogging_log_message( "lspmac_moveabs_wait:
     unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
 pthread_mutex_unlock( &(mp->mutex));
// wait for the motion that we know has started to finish
err = 0;
while( err == 0 && mp->not_done)
  err = pthread_cond_timedwait( &(mp->cond), &(mp->mutex), &timeout)
if( err != 0) {
  if( err != ETIMEDOUT) {
    lslogging_log_message( "lspmac_moveabs_wait:
     unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
 pthread_mutex_unlock( &(mp->mutex));
  return 1;
// if return code was not 0 then we know we shouldn't wait for not_done flag.
// In this case the motion ended before we read the status registers
pthread_mutex_unlock( & (mp->mutex));
return 0;
```

7.12.4.41 void Ispmac_run ()

Start up the Ispmac thread.

Definition at line 3511 of file Ispmac.c.

```
char **inits;
lspmac_motor_t *mp;
char evts[64];
int i:
int active;
pthread_create( &pmac_thread, NULL, lspmac_worker,
    NULL);
lsevents_add_listener( "CryoSwitchChanged",
    lspmac_cryoSwitchChanged_cb);
lsevents_add_listener( "scint In Position",
    lspmac_scint_inPosition_cb);
lsevents_add_listener( "scintDried",
lspmac_scint_dried_cb);
lsevents_add_listener( "backLight 1",
    lspmac_backLight_up_cb);
lsevents_add_listener( "backLight 0",
    lspmac_backLight_down_cb);
lsevents_add_listener( "cam.zoom In Position",
    lspmac_light_zoom_cb);
for( i=0; i<lspmac_nmotors; i++) {</pre>
 snprintf( evts, sizeof( evts)-1, "%s command accepted", lspmac_motors
    [i].name);
```

```
evts[sizeof(evts)-1] = 0;
  lsevents_add_listener( evts, lspmac_command_done_cb
lspmac_zoom_lut_setup();
lspmac_flight_lut_setup();
lspmac_blight_lut_setup();
lspmac_fscint_lut_setup();
// Clear the command interfaces
lspmac_SockSendControlCharPrint( NULL, '\x18')
  uint32_t cc;
  cc = 0;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
   , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
// Initialize the MD2 pmac (ie, turn on the right plcc's etc)
for( inits = lsredis_get_string_array(lspmac_md2_init); *inits != NULL;
     inits++) {
  lspmac_SockSendDPline( NULL, *inits);
// Initialize the pmac's support for each motor
// (ie, set the various flag for when a motor is active or not)
for( i=0; i<lspmac_nmotors; i++) {</pre>
 mp = &(lspmac_motors[i]);
  active = lsredis_getb( mp->active);
  // if there is a problem with "active" then don't do anything
  // On the other hand, various combinations of yes/no true/fals 1/0 should
    work
  switch( active) {
  case 1:
    inits = lsredis_get_string_array( mp->active_init
    break:
  case 0:
    inits = lsredis_get_string_array( mp->
    inactive_init);
    break;
  default:
    lslogging_log_message( "lspmac_run: motor %s is
     neither active nor inactive (!?)", mp->name);
    inits = NULL;
  if( inits != NULL) {
    while( *inits != NULL) {
     lspmac_SockSendDPline( NULL, *inits);
      inits++;
  }
}
```

7.12.4.42 void lspmac_SockSendDPline (char * , char * fmt, ...)

prepare (queue up) a line to send the dpram ascii command interface Definition at line 1949 of file Ispmac.c.

{

```
va_list arg_ptr;
uint32_t index;
char *pl;

pthread_mutex_lock( &lspmac_ascii_mutex);
index = lspmac_dpascii_on++ % LSPMAC_DPASCII_QUEUE_LENGTH
;

pl = lspmac_dpascii_queue[index].pl;

va_start( arg_ptr, fmt);
vsnprintf( pl, 159, fmt, arg_ptr);
pl[159] = 0;
va_end( arg_ptr);

lspmac_dpascii_queue[index].event = event;
pthread_mutex_unlock( &lspmac_ascii_mutex);
}
```

7.12.4.43 pmac_cmd_queue_t* lspmac_SockSendline (char * event, char * fmt, ...)

Send a one line command.

Uses printf style arguments.

Parameters

in	event	base name for events
in	fmt	Printf style format string

Definition at line 1060 of file Ispmac.c.

7.12.4.44 void Ispmac_video_rotate (double secs)

Special motion program to collect centering video.

Definition at line 2568 of file Ispmac.c.

7.12.4.45 int lsredis_cmpnstr (lsredis_obj_t * p, char * s, int n)

Definition at line 236 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = strncmp( p->value, s, n);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.12.4.46 int lsredis_cmpstr (lsredis_obj_t * p, char * s)

Definition at line 225 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
  pthread_cond_wait( &p->cond, &p->mutex);

rtn = strcmp( p->value, s);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.12.4.47 int lsredis_find_preset (char * base, char * preset_name, double * dval)

Definition at line 756 of file Isredis.c.

```
char s[512];
int i;
int err;
ENTRY htab_input, *htab_output;
lsredis_obj_t *p;
for( i=0; i<1024; i++) {</pre>
  snprintf(s, sizeof(s)-1, "%s.%s.presets.%d.name", lsredis_head
    , base, i);
  s[sizeof(s)-1] = 0;
  htab_input.key = s;
htab_input.data = NULL;
  err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab)
  if( err == 0) {
   // We've run out of names to look for: done
    lslogging_log_message( "lsredis_find_preset: no
preset for motor %s named '%s'", base, preset_name);
    *dval = 0.0;
    return 0;
  // Check if we have a match
  p = htab_output->data;
```

```
if( lsredis_cmpstr( p, preset_name) == 0) {
   // got a match, now look for the position
   snprintf( s, sizeof( s)-1, "%s.%s.presets.%d.position", lsredis_head
     , base, i);
     s[sizeof(s)-1] = 0;
     htab input.kev = s:
     htab_input.data = NULL;
     err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab
     if( err == 0) {
      lslogging_log_message( "lsredis_find_preset:
Error, motor %s preset '%s' has no position defined", base, preset_name);
**dval = 0.0;
        // Name but not position? odd.
        return 0;
     p = htab_output->data;
     *dval = lsredis_getd(p);
return 1;
// How'd we get here?
\ensuremath{//}\xspace did someone really define that many presets? And then looked for one
      that's not there?
*dval = 0;
return 0;
```

7.12.4.48 | Isredis_obj_t* | Isredis_get_obj (char * , ...)

Definition at line 524 of file Isredis.c.

```
lsredis_obj_t *rtn;
va_list arg_ptr;
char k[512];
char *kp;
int nkp;
va_start( arg_ptr, fmt);
vsnprintf( k, sizeof(k)-1, fmt, arg_ptr);
k[sizeof(k)-1] = 0;
va_end( arg_ptr);
nkp = strlen(k) + strlen(lsredis_head) + 16;
    is overkill. I know. Get over it.
kp = calloc( nkp, sizeof( char));
if( kp == NULL) {
 lslogging_log_message( "lsredis_get_obj: Out of memory
");
  exit( -1);
snprintf( kp, nkp-1, "%s.%s", lsredis_head, k);
kp[nkp-1] = 0;
pthread_mutex_lock( &lsredis_mutex);
while( lsredis_running == 0)
 pthread_cond_wait( &lsredis_cond, &lsredis_mutex);
rtn = _lsredis_get_obj( kp);
pthread_mutex_unlock( &lsredis_mutex);
free( kp);
return rtn;
```

7.12.4.49 char** lsredis_get_string_array (lsredis_obj_t * p)

Definition at line 365 of file Isredis.c.

```
char **rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);
```

```
rtn = p->avalue;
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.12.4.50 int lsredis_getb (lsredis_obj_t * p)

Definition at line 378 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->bvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.12.4.51 double lsredis_getd (lsredis_obj_t * p)

Definition at line 339 of file Isredis.c.

```
double rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->dvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.12.4.52 long int lsredis_getl (lsredis_obj_t * p)

Definition at line 352 of file Isredis.c.

```
long int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->lvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.12.4.53 char* lsredis_getstr (lsredis_obj_t * p)

return a copy of the key's string value

Definition at line 263 of file Isredis.c.

7.12.4.54 void Isredis_init (char * pub, char * re, char * head)

Initialize this module, that is, set up the connections.

Parameters

pub	Publish under this (unique) name
re	Regular expression to select keys we want to mirror
head	Prepend this (+ a dot) to the beginning of requested objects

Definition at line 810 of file Isredis.c.

```
int err;
int nerrmsg;
char *errmsg;
// set up hash map to store redis objects
err = hcreate_r( 8192, &lsredis_htab);
if( err == 0) {
 lslogging_log_message( "lsredis_init: Cannot create
    hash table. Really bad things are going to happen. hcreate_r returned %d", err);
lsredis_head
                  = strdup( head);
lsredis_publisher = strdup( pub);
pthread_cond_init( &lsredis_cond, NULL);
subac = redisAsyncConnect("127.0.0.1", 6379);
if( subac->err) {
 lslogging_log_message( "Error: %s", subac->errstr
    );
subfd.fd
                    = subac->c.fd;
subfd.events
                    = 0;
                  = &subfd;
subac->ev.data
subac->ev.addRead = lsredis_addRead;
subac->ev.delRead = lsredis_delRead;
subac->ev.addWrite = lsredis_addWrite;
subac->ev.delWrite = lsredis_delWrite;
subac->ev.cleanup = lsredis_cleanup;
roac = redisAsyncConnect("127.0.0.1", 6379);
if( roac->err) {
  lslogging_log_message( "Error: %s", roac->errstr);
rofd.fd
                   = roac->c.fd;
                  = 0;
= &rofd;
rofd.events
roac->ev.data
roac->ev.addRead = lsredis_addRead;
roac->ev.delRead = lsredis_delRead;
roac->ev.addWrite = lsredis_addWrite;
roac->ev.delWrite = lsredis_delWrite;
roac->ev.cleanup = lsredis_cleanup;
//wrac = redisAsyncConnect("10.1.0.3", 6379);
```

```
wrac = redisAsyncConnect("127.0.0.1", 6379);
if( wrac->err) {
  lslogging_log_message( "Error: %s", wrac->errstr);
wrfd.fd
                  = wrac->c.fd:
                = 0;
= &wrfd;
wrfd.events
wrac->ev.data
wrac->ev.addRead = lsredis_addRead;
wrac->ev.delRead = lsredis_delRead;
wrac->ev.addWrite = lsredis_addWrite;
wrac->ev.delWrite = lsredis_delWrite;
wrac->ev.cleanup = lsredis_cleanup;
err = regcomp( &lsredis_key_select_regex, re,
    REG_EXTENDED);
if( err != 0) {
  nerrmsg = regerror( err, &lsredis_key_select_regex,
    NULL, 0);
  if( nerrmsg > 0) {
    errmsg = calloc( nerrmsg, sizeof( char));
    nerrmsg = regerror( err, &lsredis_key_select_regex
    , errmsg, nerrmsg);
    lslogging_log_message( "lsredis_select: %s", errmsg)
    free ( errmsg);
```

7.12.4.55 int Isredis_regexec (const regex_t * preg, Isredis_obj_t * p, size_t nmatch, regmatch_t * pmatch, int eflags)

Definition at line 247 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = regexec( preg, p->value, nmatch, pmatch, eflags);
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.12.4.56 void Isredis_run ()

Definition at line 1014 of file Isredis.c.

7.12.4.57 void Isredis_setstr (Isredis_obj_t * p, char * fmt, ...)

Set the value and update redis.

Note that Isredis_set_value sets the value based on redis while here we set redis based on the value Arbitray maximum string length set here. TODO: Probably this limit should be removed at some point.

redisAsyncCommandArgv used instead of redisAsyncCommand 'cause it's easier (and possible) to deal with strings that would otherwise cause hiredis to emit a bad command, like those containing spaces. < up the count of times we need to see ourselves published before we start listening to others again

< Unlock to prevent deadlock in case the service routine needs to set our value

< redisAsyncCommandArgv shouldn't need to access this after it's made up it's packet (before it returns) so we should be OK with this location disappearing soon.

Definition at line 288 of file Isredis.c.

```
va_list arg_ptr;
char v[512];
char *argv[4];
va_start( arg_ptr, fmt);
vsnprintf( v, sizeof(v)-1, fmt, arg_ptr);
v[sizeof(v)-1] = 0;
va_end( arg_ptr);
pthread_mutex_lock( &p->mutex);
// Don't send an update if a good value has not changed
if( p->valid && strcmp( v, p->value) == 0) {
  // nothing to do
  pthread_mutex_unlock( &p->mutex);
  return;
p->wait_for_me++;
pthread_mutex_unlock( &p->mutex);
argv[0] = "HSET";
argv[1] = p->key;
argv[2] = "VALUE";
argv[3] = v;
pthread_mutex_lock( &lsredis_mutex);
while( lsredis_running == 0)
  pthread_cond_wait( &lsredis_cond, &lsredis_mutex);
redisAsyncCommand( wrac, NULL, NULL, "MULTI");
redisAsyncCommandArgv( wrac, NULL, NULL, 4, (const char **)argv, NULL);
redisAsyncCommand( wrac, NULL, NULL, "PUBLISH %s %s", lsredis_publisher
redisAsyncCommand( wrac, NULL, NULL, "EXEC");
pthread_mutex_unlock( &lsredis_mutex);
// Assume redis will take exactly the value we sent it
pthread_mutex_lock( &p->mutex);
 _lsredis_set_value( p, v);
pthread_cond_signal( &p->cond);
pthread_mutex_unlock( &p->mutex);
```

7.12.4.58 void lstimer_add_timer (char * event, int shots, unsigned long int secs, unsigned long int nsecs)

Create a timer.

Parameters

event	Name of the event to send when the timer goes off
shots	Number of times to run. 0 means never, -1 means forever
secs	Number of seconds to wait
nsecs	Number of nano-seconds to run in addition to secs

Definition at line 50 of file Istimer.c.

```
int i;
struct timespec now;

// Time we were called. Delay is based on call time, not queued time
```

```
clock_gettime( CLOCK_REALTIME, &now);
pthread mutex lock( &lstimer mutex);
for( i=0; i<LSTIMER_LIST_LENGTH; i++) {</pre>
  if( lstimer_list[i].shots == 0)
   break;
if( i == LSTIMER_LIST_LENGTH) {
  pthread_mutex_unlock( &lstimer_mutex);
  lslogging_log_message( "lstimer_add_timer: out of
    timers for event: %s, shots: %d, secs: %u, nsecs: %u",
                        event, shots, secs, nsecs);
  return;
strncpy( lstimer_list[i].event, event, LSEVENTS_EVENT_LENGTH
      1);
lstimer_list[i].event[LSEVENTS_EVENT_LENGTH
    -1] = 0;
lstimer_list[i].shots
                             = shots;
lstimer_list[i].delay_secs = secs;
lstimer_list[i].delay_nsecs = nsecs;
= secs + now.tv_sec + (
lstimer_list[i].last_secs = 0;
lstimer_list[i].last_nsecs = 0;
lstimer_list[i].ncalls
                            = 0;
lstimer_list[i].init_secs = now.tv_sec;
lstimer_list[i].init_nsecs = now.tv_nsec;
if( shots != 0) {
  lstimer_active_timers++;
  new_timer++;
pthread_cond_signal( &lstimer_cond);
pthread_mutex_unlock( &lstimer_mutex);
```

7.12.4.59 void Istimer_init ()

Initialize the timer list and pthread stuff.

Definition at line 259 of file Istimer.c.

```
for( i=0; i<LSTIMER_LIST_LENGTH; i++) {
   lstimer_list[i].shots = 0;
}

pthread_mutex_init( &lstimer_mutex, NULL);
pthread_cond_init( &lstimer_cond, NULL);</pre>
```

7.12.4.60 void lstimer_run ()

Start up our thread.

Definition at line 273 of file Istimer.c.

```
7.12.4.61 void lsupdate_init ( )
7.12.4.62 void lsupdate_run ( )
7.12.4.63 void md2cmds_init ( )
```

Initialize the md2cmds module.

Definition at line 1356 of file md2cmds.c.

```
pthread_mutexattr_t mutex_initializer;

pthread_mutexattr_init( &mutex_initializer);
pthread_mutexattr_settype( &mutex_initializer, PTHREAD_MUTEX_RECURSIVE);

pthread_mutex_init( &md2cmds_mutex, &mutex_initializer);
pthread_cond_init( &md2cmds_cond, NULL);

pthread_mutex_init( &md2cmds_moving_mutex, &
    mutex_initializer);
pthread_cond_init( &md2cmds_moving_cond, NULL);

pthread_mutex_init( &md2cmds_homing_mutex, &
    mutex_initializer);
pthread_cond_init( &md2cmds_homing_cond, NULL);

md2cmds_md_status_code = lsredis_get_obj
    ( "md2_status_code");
lsredis_setstr( md2cmds_md_status_code, "
    7");
```

7.12.4.64 void md2cmds_run ()

Start up the thread.

Definition at line 1378 of file md2cmds.c.

```
pthread_create( &md2cmds_thread, NULL,
     md2cmds_worker, NULL);
lsevents_add_listener( "omega crossed zero",
md2cmds_rotate_cb);
lsevents_add_listener( "omega In Position",
    md2cmds_maybe_rotate_done_cb);
lsevents_add_listener( ".+ (Moving|In Position)",
md2cmds_maybe_done_moving_cb);
lsevents_add_listener( "(.+) (Homing|Homed)",
    md2cmds_maybe_done_homing_cb);
lsevents_add_listener( "capz (Moving|In Position)",
     md2cmds_time_capz_cb);
lsevents_add_listener( "Coordsys 1 Stopped",
     md2cmds_coordsys_1_stopped_cb);
lsevents_add_listener( "Coordsys 2 Stopped",
md2cmds_coordsys_2_stopped_cb);
lsevents_add_listener( "Coordsys 3 Stopped",
md2cmds_coordsys_3_stopped_cb);
lsevents_add_listener( "Coordsys 4 Stopped",
     md2cmds_coordsys_4_stopped_cb);
lsevents_add_listener( "Coordsys 5 Stopped",
md2cmds_coordsys_5_stopped_cb);
lsevents_add_listener( "Coordsys 7 Stopped",
     md2cmds_coordsys_7_stopped_cb);
```

7.12.4.65 void pgpmac_printf (char * fmt, ...)

Terminal output routine ala printf.

Parameters

Γ	in	fmt	Printf style formating string
П	T11	1111	i find style formating string

Definition at line 330 of file pgpmac.c.

```
va_list arg_ptr;

pthread_mutex_lock( &ncurses_mutex);

va_start( arg_ptr, fmt);
vwprintw( term_output, fmt, arg_ptr);
va_end( arg_ptr);

wnoutrefresh( term_output);
wnoutrefresh( term_input);
doupdate();

pthread_mutex_unlock( &ncurses_mutex);
```

7.12.4.66 void PmacSockSendline (char * s)

7.12.5 Variable Documentation

```
7.12.5.1 Ispmac_motor_t* alignx
```

Alignment stage X.

Definition at line 90 of file Ispmac.c.

```
7.12.5.2 Ispmac_motor_t* aligny
```

Alignment stage Y.

Definition at line 91 of file Ispmac.c.

```
7.12.5.3 Ispmac_motor_t* alignz
```

Alignment stage X.

Definition at line 92 of file Ispmac.c.

```
7.12.5.4 Ispmac_motor_t* anal
```

Polaroid analyzer motor.

Definition at line 93 of file Ispmac.c.

```
7.12.5.5 Ispmac_motor_t* apery
```

Aperture Y.

Definition at line 95 of file Ispmac.c.

Aperture Z.

Definition at line 96 of file Ispmac.c.

7.12.5.7 Ispmac_bi_t* arm_parked

(whose arm? parked where?)

Definition at line 133 of file Ispmac.c.

7.12.5.8 Ispmac_motor_t* blight

Back Light DAC.

Definition at line 107 of file Ispmac.c.

Backlight is down.

Definition at line 123 of file Ispmac.c.

7.12.5.10 Ispmac_motor_t* blight_f

Back light scale factor.

Definition at line 116 of file Ispmac.c.

Back light Up/Down actuator.

Definition at line 111 of file Ispmac.c.

Backlight is up.

Definition at line 124 of file Ispmac.c.

Capillary Y.

Definition at line 97 of file Ispmac.c.

Capillary Z.

Definition at line 98 of file Ispmac.c.

Centering Table X.

Definition at line 100 of file Ispmac.c.

Centering Table Y.

Definition at line 101 of file Ispmac.c.

7.12.5.17 Ispmac_motor_t* cryo

Move the cryostream towards or away from the crystal.

Definition at line 112 of file Ispmac.c.

7.12.5.18 Ispmac_bi_t* cryo_back

cryo is in the back position

Definition at line 125 of file Ispmac.c.

that little toggle switch for the cryo

Definition at line 122 of file Ispmac.c.

7.12.5.20 Ispmac_motor_t* dryer

blow air on the scintilator to dry it off

Definition at line 113 of file Ispmac.c.

7.12.5.21 | Ispmac_bi_t* etel_init_ok

ETEL initialized OK.

Definition at line 130 of file Ispmac.c.

7.12.5.22 lspmac_bi_t* etel_on

ETEL is on.

Definition at line 129 of file Ispmac.c.

7.12.5.23 Ispmac_bi_t* etel_ready

ETEL is ready.

Definition at line 128 of file Ispmac.c.

Front Light DAC.

Definition at line 106 of file Ispmac.c.

7.12.5.25 Ispmac_motor_t* flight_f

Front light scale factor.

Definition at line 117 of file Ispmac.c.

Turn front light on/off.

Definition at line 115 of file Ispmac.c.

7.12.5.27 Ispmac_motor_t* fluo

Move the fluorescence detector in/out.

Definition at line 114 of file Ispmac.c.

fluor is in the back position

Definition at line 126 of file Ispmac.c.

7.12.5.29 Ispmac motor t* fscint

Scintillator Piezo DAC.

Definition at line 108 of file Ispmac.c.

Fast shutter.

Definition at line 105 of file Ispmac.c.

High pressure air OK.

Definition at line 121 of file Ispmac.c.

Kappa.

Definition at line 102 of file Ispmac.c.

Low pressure air OK.

Definition at line 120 of file Ispmac.c.

our demandairrights object

Definition at line 66 of file lspg.c.

7.12.5.35 lspg_getcenter_t lspg_getcenter

the getcenter object

Definition at line 65 of file lspg.c.

7.12.5.36 lspg_getcurrentsampleid_t lspg_getcurrentsampleid

our currentsample id

Definition at line 67 of file lspg.c.

the very next sample

Definition at line 63 of file lspg.c.

7.12.5.38 lspg_nextshot_t lspg_nextshot

the nextshot object

Definition at line 64 of file lspg.c.

7.12.5.39 | Ispg_starttransfer_t | Ispg_starttransfer

start a sample transfer

Definition at line 68 of file lspg.c.

7.12.5.40 lspg_waitcryo_t lspg_waitcryo

signal the robot

Definition at line 69 of file lspg.c.

All our motors.

Definition at line 87 of file Ispmac.c.

7.12.5.42 pthread_cond_t lspmac_moving_cond

Wait for motor(s) to finish moving condition.

Definition at line 64 of file Ispmac.c.

7.12.5.43 int lspmac_moving_flags

Flag used to implement motor moving condition.

Definition at line 65 of file Ispmac.c.

7.12.5.44 pthread_mutex_t lspmac_moving_mutex

Coordinate moving motors between threads.

Definition at line 63 of file Ispmac.c.

7.12.5.45 int Ispmac_nmotors

The number of motors we manage.

Definition at line 88 of file Ispmac.c.

7.12.5.46 pthread_cond_t lspmac_shutter_cond

Allows waiting for the shutter status to change.

Definition at line 62 of file Ispmac.c.

7.12.5.47 int lspmac_shutter_has_opened

Indicates that the shutter had opened, perhaps briefly even if the state did not change.

Definition at line 60 of file Ispmac.c.

7.12.5.48 pthread_mutex_t lspmac_shutter_mutex

Coordinates threads reading shutter status.

Definition at line 61 of file Ispmac.c.

7.12.5.49 int lspmac_shutter_state

State of the shutter, used to detect changes.

Definition at line 59 of file Ispmac.c.

7.12.5.50 pthread_mutex_t md2_status_mutex

Synchronize reading/writting status buffer.

Definition at line 341 of file Ispmac.c.

7.12.5.51 char md2cmds_cmd[]

our command;

Definition at line 24 of file md2cmds.c.

7.12.5.52 pthread_cond_t md2cmds_cond

condition to signal when it's time to run an md2 command

Definition at line 10 of file md2cmds.c.

7.12.5.53 | Isredis_obj_t* md2cmds_md_status_code

Definition at line 26 of file md2cmds.c.

7.12.5.54 pthread_mutex_t md2cmds_mutex

mutex for the condition

Definition at line 11 of file md2cmds.c.

7.12.5.55 pthread_cond_t md2cmds_pg_cond

7.12.5.56 pthread_mutex_t md2cmds_pg_mutex

Minikappa is OK (whatever that means)

Definition at line 131 of file Ispmac.c.

7.12.5.58 pthread_mutex_t ncurses_mutex

allow more than one thread access to the screen

Definition at line 242 of file pgpmac.c.

7.12.5.59 Ispmac_motor_t* omega

MD2 omega axis (the air bearing)

Definition at line 89 of file Ispmac.c.

7.12.5.60 struct timespec omega_zero_time

Time we believe that omega crossed zero.

Definition at line 72 of file Ispmac.c.

7.12.5.61 Ispmac_motor_t* phi

Phi (not data collection axis)

Definition at line 103 of file Ispmac.c.

7.12.5.62 pthread_cond_t pmac_queue_cond

wait for a command to be sent to PMAC before continuing

Definition at line 78 of file Ispmac.c.

7.12.5.63 pthread_mutex_t pmac_queue_mutex

manage access to the pmac command queue

Definition at line 77 of file Ispmac.c.

smart magnet detected sample

Definition at line 127 of file Ispmac.c.

Scintillator Z.

Definition at line 99 of file Ispmac.c.

shutter is open (note in pmc says this is a slow input)

Definition at line 134 of file Ispmac.c.

7.12.5.67 Ispmac bi t* smart_mag_err

smart magnet error (coil broken perhaps)

Definition at line 135 of file Ispmac.c.

smart magnet is off

Definition at line 136 of file Ispmac.c.

smart magnet is on

Definition at line 132 of file Ispmac.c.

Smart Magnet on/off.

Definition at line 110 of file Ispmac.c.

7.12.5.71 WINDOW* term_input

place to put the cursor

Definition at line 238 of file pgpmac.c.

7.12.5.72 WINDOW* term_output

place to print stuff out

Definition at line 237 of file pgpmac.c.

7.12.5.73 WINDOW* term_status

shutter, lamp, air, etc status

Definition at line 239 of file pgpmac.c.

7.12.5.74 WINDOW* term_status2

shutter, lamp, air, etc status

Definition at line 240 of file pgpmac.c.

Optical zoom.

Definition at line 94 of file Ispmac.c.

Index

_GNU_SOURCE	Ispmac.c, 201
pgpmac.h, 273	pgpmac.h, 305
init	aligny_act_pos
iniParser::iniParser, 16	md2StatusStruct, 60
_lspmac_motor_init	aligny_status_1
Ispmac.c, 147	md2StatusStruct, 60
_lsredis_get_obj	
Isredis.c, 213	aligny_status_2 md2StatusStruct, 60
_lsredis_set_value	
Isredis.c, 214	alignz
1310013.0, 214	Ispmac.c, 201
acc11c_1	pgpmac.h, 305
md2StatusStruct, 60	alignz_act_pos
acc11c_2	md2StatusStruct, 60
md2StatusStruct, 60	alignz_status_1
acc11c_3	md2StatusStruct, 60
md2StatusStruct, 60	alignz_status_2
acc11c_5	md2StatusStruct, 61
md2StatusStruct, 60	anal
acc11c_6	Ispmac.c, 201
md2StatusStruct, 60	pgpmac.h, 305
active	analyzer_act_pos
lspg_nextshot_struct, 29	md2StatusStruct, 61
	analyzer_status_1
lspmac_motor_struct, 48 active2	md2StatusStruct, 61
	analyzer_status_2
lspg_nextshot_struct, 29 active2_isnull	md2StatusStruct, 61
	aperturey_act_pos
lspg_nextshot_struct, 30	md2StatusStruct, 61
active_init	aperturey_status_1
Ispmac_motor_struct, 48	md2StatusStruct, 61
active_isnull	aperturey_status_2
lspg_nextshot_struct, 30	md2StatusStruct, 61
actual_pos_cnts	aperturez_act_pos
lspmac_motor_struct, 48	md2StatusStruct, 61
actual_pos_cnts_p	aperturez_status_1
Ispmac_motor_struct, 48	md2StatusStruct, 61
addRead	
kvredis.c, 72	aperturez_status_2
addWrite	md2StatusStruct, 61
kvredis.c, 72	apery
alignx	Ispmac.c, 201
Ispmac.c, 201	pgpmac.h, 305
pgpmac.h, 305	aperz
alignx_act_pos	Ispmac.c, 201
md2StatusStruct, 60	pgpmac.h, 305
alignx_status_1	arm_parked
md2StatusStruct, 60	Ispmac.c, 201
alignx_status_2	pgpmac.h, 305
md2StatusStruct, 60	avalue
aligny	Isredis_obj_struct, 54

ax	md2StatusStruct, 62
lspg_nextshot_struct, 30	capy_status_2
ax2	md2StatusStruct, 62
lspg_nextshot_struct, 30	capz
ax2_isnull	Ispmac.c, 202
lspg_nextshot_struct, 30	pgpmac.h, 306
ax_isnull	capz_act_pos
lspg_nextshot_struct, 30	md2StatusStruct, 62
axis	capz_status_1
Ispmac_motor_struct, 48	md2StatusStruct, 62
ay	capz_status_2
lspg_nextshot_struct, 30	md2StatusStruct, 62
ay2	cb
lspg_nextshot_struct, 30	Isevents_listener_struct, 18
ay2_isnull	centerx act pos
lspg_nextshot_struct, 30	md2StatusStruct, 62
ay_isnull	centerx_status_1
lspg_nextshot_struct, 30	md2StatusStruct, 62
az	centerx_status_2
lspg_nextshot_struct, 30	md2StatusStruct, 62
az2	centery act pos
lspg_nextshot_struct, 31	md2StatusStruct, 62
az2_isnull	centery_status_1
lspg_nextshot_struct, 31	md2StatusStruct, 62
az_isnull	centery_status_2
lspg_nextshot_struct, 31	md2StatusStruct, 62
	cenx
b	Ispmac.c, 202
mk_pgpmac_redis, 12	pgpmac.h, 306
h Data	pgp
bData	cenv
tagEthernetCmd, 66	lspmac c. 202
tagEthernetCmd, 66 back_dac	Ispmac.c, 202
tagEthernetCmd, 66 back_dac md2StatusStruct, 61	lspmac.c, 202 pgpmac.h, 306
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list	lspmac.c, 202 pgpmac.h, 306 changeEventOff
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_tdeltage	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 bvalue	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent Ispmac_motor_struct, 48
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent Ispmac_motor_struct, 48 command_str
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 bvalue lsredis_obj_struct, 54	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent Ispmac_motor_struct, 48 command_str Ispmac_ascii_buffers_struct, 42
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 bvalue lsredis_obj_struct, 54 capy	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent Ispmac_motor_struct, 48 command_str Ispmac_ascii_buffers_struct, 42 cond
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 bvalue lsredis_obj_struct, 54 capy lspmac.c, 202	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent Ispmac_motor_struct, 48 command_str Ispmac_ascii_buffers_struct, 42 cond Ispg_demandairrights_struct, 20
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 bvalue lsredis_obj_struct, 54 capy lspmac.c, 202 pgpmac.h, 306	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent Ispmac_motor_struct, 48 command_str Ispmac_ascii_buffers_struct, 42 cond Ispg_demandairrights_struct, 20 Ispg_getcenter_struct, 21
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 bvalue lsredis_obj_struct, 54 capy lspmac.c, 202 pgpmac.h, 306 capy_act_pos	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent Ispmac_ascii_buffers_struct, 42 command_str Ispmac_ascii_buffers_struct, 42 cond Ispg_demandairrights_struct, 20 Ispg_getcenter_struct, 21 Ispg_getcurrentsampleid_struct, 23
tagEthernetCmd, 66 back_dac md2StatusStruct, 61 bi_list mk_pgpmac_redis, 12 blight lspmac.c, 201 pgpmac.h, 306 blight_down lspmac.c, 201 pgpmac.h, 306 blight_f lspmac.c, 201 pgpmac.h, 306 blight_ud lspmac.c, 202 pgpmac.h, 306 blight_up lspmac.c, 202 pgpmac.h, 306 bvalue lsredis_obj_struct, 54 capy lspmac.c, 202 pgpmac.h, 306	Ispmac.c, 202 pgpmac.h, 306 changeEventOff Ispmac_bi_struct, 43 changeEventOn Ispmac_bi_struct, 43 cleanstr Ispmac.c, 148 cleanup kvredis.c, 72 cmdac kvredis.c, 83 cmdfd kvredis.c, 83 command_buf Ispmac_ascii_buffers_struct, 42 command_buf_cc Ispmac_ascii_buffers_struct, 42 command_sent Ispmac_motor_struct, 48 command_str Ispmac_ascii_buffers_struct, 42 cond Ispg_demandairrights_struct, 20 Ispg_getcenter_struct, 21

	xtsample_struct, 26	-1	lspg_getcenter_struct, 22
	xtshot_struct, 31	acx	_isnull
	q_run_prep_struct, 38	مام	lspg_getcenter_struct, 22
	rttransfer_struct, 39 it_for_detector_struct, 40	dcy	long gotooptor atrust 00
	itcryo_struct, 40	day	Ispg_getcenter_struct, 22
	_motor_struct, 49	ucy_	_isnull _lspg_getcenter_struct, <mark>22</mark>
	obj_struct, 54	dah	ugCB
coord_num	55 <u>J_</u> 5ti dot, 0 i	deb	kvredis.c, 73
	motor struct, 49	delF	Read
cr_cmd	,	33	kvredis.c, 73
Ispmac.o	c, <mark>202</mark>	del\	Vrite
cryo			kvredis.c, 73
Ispmac.	o, 202	dela	ay_nsecs
pgpmac	.h, 307		Istimer_list_struct, 57
cryo_back		dela	ay_secs
Ispmac.			Istimer_list_struct, 57
pgpmac	.h, 307	drye	er
cryo_switch	000		Ispmac.c, 203
Ispmac.			pgpmac.h, 307
pgpmac	.n, 307	dsd	
cvalue	obi struct 55		lspg_nextshot_struct, 32
CX	obj_struct, 55	dsd	ir_isnull
	xtshot_struct, 31		lspg_nextshot_struct, 32
cx2	ktsnot_struct, or	dsd	
	xtshot_struct, 31		lspg_nextshot_struct, 32
cx2 isnull	Kishot_struct, or	dsd	
_	xtshot_struct, 31		lspg_nextshot_struct, 32
cx_isnull		asa	ist2_isnull
	xtshot_struct, 31	-11	lspg_nextshot_struct, 32
cy C	_ ,	asa	ist_isnull
-	xtshot_struct, 31	dso	Ispg_nextshot_struct, 32
cy2		dse	lspg_nextshot_struct, 32
lspg_ne	xtshot_struct, 31	dse	
cy2_isnull		430	lspg_nextshot_struct, 32
	xtshot_struct, 32	dse	xp2 isnull
cy_isnull		400	lspg_nextshot_struct, 33
lspg_ne	xtshot_struct, 32	dse	xp isnull
dac mvar			lspg_nextshot_struct, 33
_	motor struct, 49	dsh	
dax	inotor_struct, 40		lspg_nextshot_struct, 33
	tcenter_struct, 21	dsh	pid_isnull
dax_isnull			lspg_nextshot_struct, 33
	tcenter_struct, 21	dsk	арра
day	_ ,		lspg_nextshot_struct, 33
•	tcenter_struct, 21	dsk	appa2
day_isnull	_ ,		lspg_nextshot_struct, 33
lspg_get	tcenter_struct, 22	dsk	appa2_isnull
daz			lspg_nextshot_struct, 33
lspg_get	tcenter_struct, 22	dsk	appa_isnull
daz_isnull			lspg_nextshot_struct, 33
lspg_get	tcenter_struct, 22	dsn	-
dbmem			lspg_nextshot_struct, 33
Ispmac.	o, 203	dsn	-
dbmemIn			lspg_nextshot_struct, 33
Ispmac.	o, 203	dsn	rg2_isnull
dcx			lspg_nextshot_struct, 34

dsnrg_isnull	dummyB
lspg_nextshot_struct, 34	md2StatusStruct, 63
dsomega	dvalue
lspg_nextshot_struct, 34	lsredis_obj_struct, 55
dsomega2	
lspg_nextshot_struct, 34	etel_init_ok
dsomega2_isnull	Ispmac.c, 203
lspg_nextshot_struct, 34	pgpmac.h, 307
dsomega_isnull	etel_on
lspg_nextshot_struct, 34	Ispmac.c, 203
dsoscaxis	pgpmac.h, 307
lspg_nextshot_struct, 34	etel_ready
dsoscaxis2	Ispmac.c, 203
lspg_nextshot_struct, 34	pgpmac.h, 307
dsoscaxis2_isnull	ethCmdOff
Ispg_nextshot_struct, 34	Ispmac.c, 203
dsoscaxis isnull	ethCmdOn
lspg_nextshot_struct, 34	Ispmac.c, 203
dsowidth	ethCmdQueue
lspg nextshot struct, 34	Ispmac.c, 204
dsowidth2	ethCmdReply
lspg_nextshot_struct, 35	Ispmac.c, 204
dsowidth2 isnull	event
Ispg_nextshot_struct, 35	lspmac_cmd_queue_struct, 45
dsowidth isnull	Ispmac_dpascii_queue_struct, 45
Ispg_nextshot_struct, 35	Istimer_list_struct, 57
	events_name
dsphi	Isredis_obj_struct, 55
lspg_nextshot_struct, 35	evp
dsphi2	Isevents_queue_struct, 19
lspg_nextshot_struct, 35	
dsphi2_isnull	f
lspg_nextshot_struct, 35	iniParser::iniParser, 17
dsphi_isnull	mk_pgpmac_redis, 12
lspg_nextshot_struct, 35	fd_service
dspid	kvredis.c, 74
lspg_nextshot_struct, 35	first_time
dspid_isnull	Ispmac_bi_struct, 43
lspg_nextshot_struct, 35	flight
dummy1	Ispmac.c, 204
md2StatusStruct, 62	pgpmac.h, 307
dummy2	flight_f
md2StatusStruct, 63	Ispmac.c, 204
dummy3	pgpmac.h, 307
md2StatusStruct, 63	flight_oo
dummy4	Ispmac.c, 204
md2StatusStruct, 63	pgpmac.h, 308
dummy5	fluo
md2StatusStruct, 63	Ispmac.c, 204
dummy6	pgpmac.h, 308
md2StatusStruct, 63	fluor_back
dummy7	Ispmac.c, 204
md2StatusStruct, 63	pgpmac.h, 308
dummy8	fnc
md2StatusStruct, 63	mk_pgpmac_redis, 12
dummy9	front_dac
md2StatusStruct, 63	md2StatusStruct, 63
dummyA	fs_has_opened
md2StatusStruct, 63	md2StatusStruct, 63
<i>,</i>	, =

fs has opened globally md2StatusStruct, 64 init16 fs_is_open md2StatusStruct, 64 f. 1,7 fscirt get, 16 lspmac.c, 204 options, 16 pgpmac.h, 308 read, 16 fshut sd, 17 lspmac.c, 204 sections, 17 pgpmac.h, 308 sections, 17 gb_cmd sittime_list_struct, 57 gb_cmd lspmac.c, 205 get iniParser:iniParser, 16 getcurrentsampleid_struct, 23 getcurrentsampleid_struct, 23 getwars lspmac.c, 205 getmvars lspmac.c, 205 getmvars lspmac.c, 205 getmvars lspmac.c, 205 getmvars lspmac.c, 205 handler lstimer.c, 230 hard_ini_fleids mk_pgpmac_redis, 12 hard_ini_fleids mk_pgpmac_redis, 12 has_section, 16 ppmac_sective, 55 kappa_status_2 lsredis_obj_struct, 64 kappa_status_3 mk_pgpmac_redis, 12 hard_ini_fleids mk_pgmac_redis, 12 hix mk_pgmac_redi		
fs_is_open get, 16 md2StatusStruct, 64 has_option, 16 fscint has_option, 16 lspmac.c, 204 options, 16 pgpmac.h, 308 read, 16 fshut sd, 17 lspmac.c, 204 sections, 17 pgpmac.h, 308 init_nescs lstimer_list_struct, 57 ip iniParser.iniParser, 16 kappa_status_2 pgmac, 205 pgmach, 308 kappa_status_2 md2StatusStruct, 64 kappa_status_2 <td>fs_has_opened_globally</td> <td>init, 16</td>	fs_has_opened_globally	init, 16
mid2StatusStruct, 64	md2StatusStruct, 64	f, 17
fscint has_section, 16 options, 17 init_nsecs lstimer_list_struct, 57 init_nsecs lstimer_list_struct, 58 lspp_a.stalus_1 lsppmac., 205 lsppmac., 205 lsppmac., 205 lsppmac., 205 lsppmac., 205 lsppmac., 205 lsppmac_stalus_2 lspmac_stalus_2 lspmac_s	fs_is_open	get, 16
Ispmac.c, 204 options, 16 read, 16 st, 17 sections, 18 sections, 19	md2StatusStruct, 64	_ ·
pspmac.h, 308 fshut sd, 17 lspmac.c, 204 pgpmac.h, 308 lsimer_list_struct, 57 gb_cmd lspmac.c, 205 get iniParser::iniParser, 16 getcurrentsampleid_struct, 23 getcurrentsampleid_struct, 24 getivars lspmac.c, 205 getmvars lspmac.c, 205 lspmac.redis, 12 lspmac.redis, 12 lspmac.c, 206 lspmac.redis, 12 lspmac.motor_struct, 49 lspmac.m	fscint	has_section, 16
fshut sd, 17 lspmac.c, 204 sections, 17 pgpmac.h, 308 lstimer_list_struct, 57 gb_cmd init_nsecs lstimer_list_struct, 57 init_nsecs lstimer_list_struct, 57 init_nsecs lstimer_list_struct, 57 ip inil_arser::iniParser, 16 ip getcurrentsampleid struct, 23 getcurrentsampleid_struct, 23 kappa getwars lspmac.c, 205 lspmac.c, 205 mc2StatusStruct, 64 getmvars lspmac.c, 205 getmvars mc2StatusStruct, 64 lspmac.c, 205 md2StatusStruct, 64 kappa_status_2 md2statusStruct, 64 kappa_	Ispmac.c, 204	options, 16
Ispmac.c, 204 pgpmac.h, 308 gd.cmd Ispmac.c, 205 get iniParser::iniParser, 16 getcurrentsampleid_ispmac.c, 205 getwars Ispmac.c, 205 getwars Ispmac.c, 205 getmars Ispmac.c, 206 getmars Ispmac.c, 206 getmars Ispmac.c, 207 IniParser::iniParser, 16 IniParser::iniParser, 16 Inas_section Ispmac_redis, 12 Inas_getmars Ispmac.c, 148 Ini Ispmac.c, 148 Ini Ispmac_motor_struct, 49 Inoming Ispmac_motor_struct, 49 Inp_air Ispmac_motor_struct, 49 Inp_air Ispmac_motor_struct, 49 Inp_air Ispmac_motor_struct, 49 Inp_air Ispmac_motor_struct, 49 IniParser.iniParser, 11 Ini IniParser.iniParser, 15 Ispn_query_queue_on, 84 Ispn_query_queue	pgpmac.h, 308	read, 16
pgpmac.h, 308 gb_cmd lspmac.c, 205 get iniParser:iniParser, 16 getcurrentsampleid lspg_getcurrentsampleid struct, 23 getwars lspmac.c, 205 getmars lspmac.c, 206 hard_ini mk_pgpmac_redis, 12 hard_ini_fields mk_pgpmac_redis, 12 has_potion iniParser:iniParser, 16 head minParser:iniParser, 16 head minParser:iniParser, 16 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 hp_air lspmac_motor_struct, 49 hp_air lspmac_notor_struct, 49 hp_air lspmac_notor_struct, 49 hp_air lspmac_notor_struct, 49 hp_air lspmac_motor_struct, 49 iniParser.iniParser, 15 iniParser.iniParser, 1	fshut	sd, 17
gb_cmd lspmac.c, 205 lstimer_list_struct, 57 int_secs lstimer_list_struct, 57 int_secs lstimer_list_struct, 57 int_secs lstimer_list_struct, 57 ip int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 57 ip int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 57 ip int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 57 ip int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 57 ip int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struct, 57 ip int_secs lstimer_list_struct, 58 is int_secs lstimer_list_struc	Ispmac.c, 204	sections, 17
gbc milparser::iniParser, 16 geturrentsampleid struct, 23 getcurrentsampleid_struct, 23 getcurrentsampleid_struct, 24 getivars lspmac.c, 205 getmars lspmac.c, 205 handler md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md	pgpmac.h, 308	init_nsecs
Ispmac.c, 205 get iniParser::iniParser, 16 getcurrentsampleid lspg_getcurrentsampleid_struct, 23 getcurrentsampleid_struct, 24 getivars Ispmac.c, 205 getmars Ispmac.c, 205 getmars Ispmac.c, 205 getmars Ispmac.c, 205 handler Istimer.c, 230 hard_ini mk_pgpmac_redis, 12 has_petion iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump Ispmac.c, 148 hi mk_pgpmac_redis, 12 hex_dump Ispmac.c, 148 hi mk_pgpmac_redis, 12 hits Isredis_obj_struct, 55 home Ispmac_motor_struct, 49 hp_air Ispmac.c, 205 pgpmac.h, 308 kappa lspmac_redis, 12 hex_dump Ispmac_motor_struct, 49 hp_air Ispmac_notor_struct, 49 hp_air Ispmac_notor_struct, 49 hp_air Ispmac_notor_struct, 49 hp_air Ispmac_motor_struct, 49 hp_air Ispmac_notor_struct, 49 hp_air Ispmac_notor_		Istimer_list_struct, 57
get iniParser::iniParser, 16 getcurrentsampleid struct, 23 getcurrentsampleid struct, 23 getcurrentsampleid_struct, 24 getivars lspmac.c, 205 getmars lspmac.c, 205 getmars lspmac.c, 205 getmars lspmac.c, 205 getmars lspmac.c, 205 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 key lsredis_obj_struct, 55 kvredis_c, 69 addRead, 72 addWrite, 72 cleanup, 73 delRead, 73 delWrite, 73 delRead, 73 delWrite, 73 delWrite, 73 delWrite, 73 delWrite, 73 fd_service, 74 kvseq, 83 ls_PG_STATE_IDLE, 71 LS_PG_STATE_IDLE, 71 LS_PG_STATE_IDLE, 71 LS_PG_STATE_INIT, 71 hts lspmac_motor_struct, 49	gb_cmd	init_secs
iniParser::iniParser, 16 getcurrentsampleid lspg_getcurrentsampleid_struct, 23 getcurrentsampleid_struct, 24 getivars lspmac.c, 205 getmvars lspmac.c, 205 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 65 key lsredis_obj_struct, 55 kvredis.c, 69 addRead, 72 addWrite, 72 cleanup, 72 cileanup, 72 cileanup, 72 cileanup, 72 cileanup, 72 delRead, 73 delRead, 73 delWrite, 73 delRead, 73 delWrite, 73 delRead, 73 delWrite, 73 delRead, 73 delWrite, 73 delSpmac.c, 148 kvseq, 83 LS_PG_STATE_IDLE, 71 LS_PG_STATE_IDLE, 71 LS_PG_STATE_ESED, 72 LS_PG_STATE_SEND, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_SEND, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_SEND, 72 LS_PG_STATE_RESET, 72 L	Ispmac.c, 205	Istimer list struct, 57
iniParser::iniParser, 16 getcurrentsampleid lspa_getcurrentsampleid_struct, 23 getcurrentsampleid_struct, 24 getivars lspmac.c, 205 getmvars lspmac.c, 205 getmvars lspmac.c, 205 handler lstimer.c, 230 hard_ini mk_pgpmac_redis, 12 has_potton iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 49 hp_air lspmac_motor_struct, 49 hp_air mk_pgpmac_redis, 12 hits lspmac_motor_struct, 49 hp_air mk_pgpmac_redis, 12 inactive_init lspmac_motor_struct, 49 iniParser, 11 ip, 11 ip, 11 iniParser, 16 lspg_query_queue_on, 84 lspg_query_queue_on, 84 lspg_query_queue_en, 84 lspg_query_queue_on, 84 lspg_query_queue_on, 84 lspg_query_queue_on, 84 lspg_query_queue_on, 84 lspg_query_queue_on, 84 lspg_query_queue_on, 84 lspg_query_queue_en, 84	get	ip
getcurrentsampleid spg_ getcurrentsampleid_struct, 23 spg_ getcurrentsampleid_struct, 24 getivars spmac.c, 205 ggmac.h, 308 kappa_act_pos md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2statusStruct, 64 kappa_atus_2 md2status_truct_status_1 md2status_truct_status_1 md2status	iniParser::iniParser, 16	•
lspg_getcurrentsampleid_struct, 23 getcurrentsampleid_isnull lspg_getcurrentsampleid_struct, 24 getivars lspmac.c, 205 getmvars lspmac.c, 205 getmvars lspmac.c, 205 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2status_2 md2StatusStruct, 64 kappa_status_2 md2status_2 md2status_2md2s status_2 md2status_2md2s status_2 md2status_2md2s status_2 md2status_2md2s status_2 md2status_2md2s status_2md2s status_2md2s status_2md2s status_2md2s status_2	getcurrentsampleid	,
getcurrentsampleid_isnull Ispmac.c, 205 pgpmac.h, 308 kappa_act_pos md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 65 key md2StatusStruct, 65 md2StatusStruct, 72 md2StatusStruct, 72 md2StatusStruct, 72 md2StatusStruct, 72 md2StatusStruct, 73 md2StatusStruct, 73 md2StatusStruct, 74 md2StatusStruct, 74 md2StatusStruct, 74 md2StatusStruct, 74 md2StatusStruct, 74 md2StatusStruct, 75 md2StatusStr	- ·	kappa
Ispg_getcurrentsampleid_struct, 24 getivars Ispmac.c, 205 getmvars Ispmac.c, 205 getmvars Ispmac.c, 205 getmvars Ispmac.c, 205 kappa_act_pos md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 key md2Status_1 md2StatusStruct, 64 key md2Status_1 md2StatusStruct, 64 key md2StatusCtruct, 64 key md2StatusCtruc		Ispmac.c, 205
getivars Ispmac.c, 205 getwars spmac.c, 205 getwars spmac.c, 205 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 key lsredis_obj_struct, 55 kvredis_c, 69 addRead, 72 addWrite, 73 adelRead, 73 adelRead, 73 adelRead, 73 adelRead, 73 adelRead, 73 adelRead, 73 adelWrite, 74 adelWrite	. –	pgpmac.h, 308
Ispmac.c, 205 getmvars Ispmac.c, 205 getmvars Ispmac.c, 205 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 kappa_status_1 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 65 kappa_status_2 md2StatusStruct, 65 kappa_status_2 md2StatusStruct, 55 kvredis_c, 69 addRead, 72 addWrite, 72 cleanup, 72 cleanup, 72 cleanup, 72 cleanup, 73 dellWrite, 72 delanup, 74 kvseq, 83 LS_PG_STATE_IDLE, 71 LS_PG_STATE_IDLE, 71 LS_PG_STATE_IDLE, 71 LS_PG_STATE_INIT, 71 LS_PG_STATE_INIT, 71 LS_PG_STATE_RESET, 72 LS_PG_STATE_IDLE, 71 md_spg_duen, 35 lspg_allkvs_cb, 74 lspg_onnectPoll_response, 84 lspg_plexy_push, 75 lspg_notice_processor, 76 lspg_pg_connect, 78 lspg_query_queue_ed,		kappa act pos
getmvars Ispmac.c, 205 handler Istimer.c, 230 hard_ini mk_pgpmac_redis, 12 has_option iniParser::iniParser, 16 has_section iniParser::iniParser, 16 has_pgpmac_redis, 12 has_pgpmac_redis, 12 has_pgpmac_redis, 12 has_psetion iniParser::iniParser, 16 head mk_pgpmac_redis, 12 has_pgpmac_redis, 12 has_psetion iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump Ispmac.c, 148 hi mk_pgpmac_redis, 12 his Isredis_obj_struct, 55 home Ispmac_motor_struct, 49 homing Ispmac_motor_struct, 49 hp_air Ispg_query_queue, 75 Ispg_notice_processor, 76 Ispg_pg_service, 77 Ispg_query_push, 79 Ispg_query_push, 79 Ispg_query_queue_off, 84 Ispg_query_queue_off, 84 Ispg_query_queue_ereply, 84 IniParser.py, 69 Ispg_query_queue_ereply, 84 Ispg_query_queue_reply, 84 Ispg_query_queue_reply, 84	_	
Ispmac.c, 205 md2StatusStruct, 64 kappa_status_2 md2StatusStruct, 64 key lsredis_obj_struct, 55 kvredis.c, 69 kvredis.c, 69 kvredis.c, 69 addRead, 72 addWrite, 72 cleanup, 73 cleanup, 72 cleanup, 73 cleanup, 72 cleanup, 73 cleanup, 72 cleanup, 73 cleanup, 72 cleanup, 73 cleanup, 72 cl	·	
handler lstimer.c, 230 key lstimer.c, 230 key lsredis_obj_struct, 55 kvredis.c, 69 addRead, 72 addWrite, 72 cleanup, 72 cleanup, 72 cleanup, 72 cleanup, 72 cleanup, 73 debugCB, 73 debugCB, 73 delWrite, 73 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac.h, 308 lspg_allkvs_cb, 74 lspmac_motor_struct, 49 iniParser, 11 ink_pgpmac_redis, 12 ink_pgpmac_redis, 12 ink_pgpmac_redis, 13 ink_pagrac_redis, 14 iniParser, 15 ink_pagrac_redis, 15 ink_pagrac_redis, 16 ink_pagrac_redis, 16 ink_pagrac_redis, 17 ink_pagrac_redis, 18 iniParser, 19 iniParser, 11 iniParser, 11 iniParser, 11 iniParser, 15 iniParser, 16 key iniParser, 15 key iniParser, 15 ispedis_obj_struct, 55 kvredis_obj_struct, 55 kvredis_obj_struct, 55 kvredis_obj_struct, 55 cleanup, 72 addRead, 72 addRead, 72 addRead, 72 addRead, 72 addWrite, 73 addWrite, 72 addWrit	_	• • – –
handler stimer.c, 230 key struct, 64 key struct, 64 key struct, 65 key struct, 65 kvredis.c, 69 addRead, 72 addWrite, 72 cleanup, 73 delRead, 73 delRe	13pmac.0, 200	
Istimer.c, 230 hard_ini mk_pgpmac_redis, 12 hard_ini_fields mk_pgpmac_redis, 12 has_option iniParser::iniParser, 16 has_section iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac_nedis, 12 inactive_init lspmac_motor_struct, 49 iniParser, 10 iniParser, 11 iniParser, 11 iniParser, 16 kvredis.c, 69 addRead, 72 addWrite, 72 cleanup, 73 cleanup, 72 cleanup, 72 cleanup, 72 cleanup, 72 cleanup, 73 cleanup, 72 cleanup, 72 cleanup, 72 cleanup, 73 cleanup, 72	handler	– –
hard_ini mk_pgpmac_redis, 12 hard_ini_fields mk_pgpmac_redis, 12 hard_ini_fields mk_pgpmac_redis, 12 has_option iniParser::iniParser, 16 has_section iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 homing lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac_redis, 12 inactive_init lspmac_motor_struct, 49 iniParser, 11 iniParser, 11 iniParser, 15 iniParser, 15 iniParser, 15 iniParser, 16 kvredis.c, 69 addRead, 72 addWrite, 72 addWrite, 72 addWrite, 73 delNrac, 28 adelRead, 73 delRead, 73 del		
mk_pgpmac_redis, 12 hard_ini_fields mk_pgpmac_redis, 12 has_option iniParser::iniParser, 16 has_section iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac.h, 308 iniParser, 11 ip, 11 iniParser, 15 mk_pgpmac_redis, 12 kvredis.c, 69 addRead, 72 addWrite, 72 cleanup, 72 cleanup, 72 cleanup, 72 cleanup, 72 delWrite, 73 delWrite, 74 lspg_state, 83 lspg_state, 83 lspg_state, 83 lspg_state, 83 lspg_guery_next, 75 lspg_next_state, 75 lspg_next_st	•	-
hard_ini_fields mk_pgpmac_redis, 12 has_option iniParser::iniParser, 16 has_section iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 homing lspmac.c, 205 pgpmac.h, 308 liParser, 11 ip, 11 iniParser, 16 cleanup, 72 addWrite, 72 addWrite, 73 addWrite, 73 addWrite, 73 delRead, 73 adelRead, 73 adelRead, 73 adelRead, 73 adelRead, 73 adelRead, 72 addWrite, 73 adelRead, 72 addWrite, 73 adelRead, 72 addWrite, 72 delBary addWrite, 72 cleanup, 72 delBary adelWrite, 73 adelRead, 72 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 73 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 73 addWrite, 72 addWrite, 72 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 72 addWrite, 73 addWrite, 72 addWrite, 72 addWrite, 73 addWrite, 73 addWrite, 72 addWrite,		
mk_pgpmac_redis, 12 has_option iniParser::iniParser, 16 has_section iniParser::iniParser, 16 has_section iniParser::iniParser, 16 head delRead, 73 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 homing lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac.h, 308 pgpmac_redis, 12 inactive_init lspmac_motor_struct, 49 liniParser, 11 liniParser, 11 liniParser, 15 lspg_query_queue_on, 84 liniParser, pg lspg_query_queue_t, 72	_, , , _	
has_option iniParser::iniParser, 16 has_section iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac.h, 308 iniParser, 11 lspmac_motor_struct, 49 lspmac_motor_struct, 49 lspmac.notor_struct, 49 lspg_notice_processor, 76 lspg_notice_processor, 76 lspg_notice_processor, 76 lspg_not_state, 75 lspg_query_next, 78 lspg_query_next, 78 lspg_query_next, 78 lspg_query_next, 78 lspg_query_queue, 84 iniParser, 11 lspg_query_queue_off, 84 lspg_query_queue_on, 84 iniParser.py, 69 lspg_query_queue_reply, 84 iniParser.py, 69		
iniParser::iniParser, 16 has_section iniParser::iniParser, 16 head delRead, 73 mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac.h, 308 lspg_mac.c, 205 pgpmac.h, 308 limiParser, 11 limk_pgpmac_redis, 12 liniParser, 11 liniParser, 11 liniParser.iniParser, 15 lespd_query_queue_ft, 84 ledis_odd, 73 delRead, 73 delR	— - -	
has_section iniParser::iniParser, 16 head debugCB, 73 delRead, 73 delRead, 73 delRead, 73 delWrite, 73 hex_dump lspmac.c, 148 hi LS_PG_STATE_IDLE, 71 mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 homing lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac.h, 308 lspg_mac.c, 205 pgpmac.h, 308 lspg_mac_redis, 12 inactive_init lspmac_motor_struct, 49 iniParser, 11 ip, 11 lspg_query_queue_ft, 84 iniParser.py, 69 ldelWrite, 73 delWrad, 83 delRead, 73 delRea	— ·	•
iniParser::iniParser, 16 head mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 homing lspmac.c, 205 pgpmac.h, 308 lspmac.c, 205 pgpmac.h, 308 iniParser, 11 lspmac_motor_struct, 49 lspmac_motor_struct, 49 lspmac_motor_struct, 49 lspmac_motor_struct, 49 lspmac.d, 308 lspmac_motor_struct, 49 lspmac_motor_struct, 49 lspmac.d, 308 lspmac_motor_struct, 49 lspmac_motor_struct, 49 lspmac_motor_struct, 49 lspmac_onnectPoll_response, 84 lspg_next_state, 75 lspg_next_state, 75 lspg_next_state, 75 lspg_next_state, 75 lspg_query_next, 78 lspg_query_push, 79 lspmac_motor_struct, 49 lspg_query_queue_off, 84 iiiParser, 11 lspg_query_queue_reply, 84 iniParser.py, 69		
head delRead, 73 mk_pgpmac_redis, 12 hex_dump fd_service, 74 lspmac.c, 148 hi LS_PG_STATE_IDLE, 71 mk_pgpmac_redis, 12 hits LS_PG_STATE_INIT, 71 hits LS_PG_STATE_RECV, 72 lsredis_obj_struct, 55 home LS_PG_STATE_SEND, 72 lspmac_motor_struct, 49 homing lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac.h, 308 lspmac.c, 205 pgpmac.h, 308 lspmac_motor_struct, 49 lspmac_motor_struct, 49 lspmac_motor_struct, 49 hp_air lspmac.c, 205 pgpmac.h, 308 lspmac.c, 205 pgpmac.h, 308 lspg_next_state, 75 lspg_next_state, 75 lspg_pg_service, 77 mk_pgpmac_redis, 12 inactive_init lspg_query_next, 78 inactive_init lspg_query_next, 78 lspg_query_queue_off, 84 iniParser, 11 lspg_query_queue_off, 84 iniParser.iniParser, 15 lspg_query_queue_reply, 84 iniParser.py, 69		
mk_pgpmac_redis, 12 hex_dump lspmac.c, 148 hi mk_pgpmac_redis, 12 hits lsredis_obj_struct, 55 home lspmac_motor_struct, 49 homing lspmac.c, 205 pgpmac.h, 308 lspmac_redis, 12 inactive_init lspmac_motor_struct, 49 iniParser, 11 lspmacsed, 12 ldelWrite, 73 fd_service, 74 kvseq, 83 LS_PG_STATE_IDLE, 71 LS_PG_STATE_INIT, 71 LS_PG_STATE_RECV, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_RESET, 72 LS_PG_STATE_SEND, 72 lspmac_motor_struct, 49 lspg_state, 83 lspg_allkvs_cb, 74 lspg_connectPoll_response, 84 lspg_flush, 75 lspg_next_state, 75 lspg_next_state, 75 lspg_next_state, 75 lspg_pg_connect, 76 lspg_pg_connect, 76 lspg_pg_connect, 76 lspg_query_next, 78 lspg_query_next, 78 lspg_query_queue, 84 iniParser, 11 lspg_query_queue_off, 84 iniParser.py, 69 lspg_query_queue_t, 72		-
hex_dump lspmac.c, 148 kvseq, 83 hi		•
Ispmac.c, 148 hi		
hi	- ·	
mk_pgpmac_redis, 12 hits	•	•
hits	hi	
Isredis_obj_struct, 55 home Ispmac_motor_struct, 49 Ispmac_motor_struct, 49 Ispmac_motor_struct, 49 Ispmac_motor_struct, 49 Ispmac_motor_struct, 49 Ispmac.c, 205 Ispmac.c, 205 Ispmac.h, 308 Ispg_notice_processor, 76 Ispg_pg_connect, 76 Ispg_pg_service, 77 Ispg_query_next, 78 Inactive_init Ispmac_motor_struct, 49 IniParser, 11 Ispg_query_queue, 84 IniParser.iniParser, 15 Ispg_query_queue_on, 84 Ispg_query_queue_reply, 84 IniParser.py, 69 Ispg_query_queue_t, 72	mk_pgpmac_redis, 12	
home	hits	
Ispmac_motor_struct, 49 homing Ispmac_motor_struct, 49 Ispmac_motor_struct, 49 Ispmac_motor_struct, 49 Ispg_connectPoll_response, 84 Ispg_flush, 75 Ispmac.c, 205 Ispg_next_state, 75 Ispg_notice_processor, 76 Ispg_pg_connect, 76 Ispg_pg_connect, 76 Ispg_pg_connect, 76 Ispg_pg_service, 77 Ispg_query_next, 78 Ispg_query_next, 78 Ispg_query_push, 79 Ispmac_motor_struct, 49 Ispg_query_queue, 84 IniParser, 11 Ispg_query_queue_off, 84 Ispg_query_queue_on, 84 IniParser.iniParser, 15 Ispg_query_queue_reply, 84 IniParser.py, 69 Ispg_query_queue_t, 72	Isredis_obj_struct, 55	
homing lspg_allkvs_cb, 74 lspmac_motor_struct, 49 lspg_connectPoll_response, 84 hp_air lspg_flush, 75 lspmac.c, 205 pgpmac.h, 308 lspg_next_state, 75 pgpmac_h, 308 lspg_p_connect, 76 i lspg_pg_connect, 76 i lspg_pg_service, 77 mk_pgpmac_redis, 12 lspg_query_next, 78 inactive_init lspg_query_push, 79 lspmac_motor_struct, 49 lspg_query_queue, 84 iniParser, 11 lspg_query_queue_off, 84 ip, 11 lspg_query_queue_on, 84 iniParser.iniParser, 15 lspg_query_queue_reply, 84 iniParser.py, 69 lspg_query_queue_t, 72	home	LS_PG_STATE_SEND, 72
Ispmac_motor_struct, 49 hp_air	lspmac_motor_struct, 49	
hp_air lspmac.c, 205 lspmac.h, 308 lspg_next_state, 75 lspg_pg_connect, 76 lspg_pg_connect, 76 lspg_pg_service, 77 mk_pgpmac_redis, 12 lspg_query_next, 78 inactive_init lspmac_motor_struct, 49 iniParser, 11 lspg_query_queue, 84 iniParser.iniParser, 15 lspg_query_queue_off, 84 iniParser.py, 69 lspg_query_queue_t, 72	homing	lspg_allkvs_cb, 74
hp_air lspg_flush, 75 lspmac.c, 205 pgpmac.h, 308 lspg_notice_processor, 76 lspg_pg_connect, 76 lspg_pg_service, 77 mk_pgpmac_redis, 12 lspg_query_next, 78 inactive_init lspmac_motor_struct, 49 iniParser, 11 lspg_query_queue, 84 iniParser, 11 lspg_query_queue_off, 84 ip, 11 lspg_query_queue_on, 84 iniParser.iniParser, 15 lspg_query_queue_reply, 84 iniParser.py, 69 lspg_query_queue_t, 72	Ispmac motor struct, 49	<pre>lspg_connectPoll_response, 84</pre>
Ispmac.c, 205 pgpmac.h, 308 Ispg_next_state, 75 Ispg_notice_processor, 76 Ispg_pg_connect, 76 Ispg_pg_service, 77 mk_pgpmac_redis, 12 Ispg_query_next, 78 Inactive_init Ispg_query_push, 79 Ispmac_motor_struct, 49 Ispg_query_queue, 84 IniParser, 11 Ispg_query_queue_off, 84 Ipp, 11 Ispg_query_queue_on, 84 IniParser.iniParser, 15 Ispg_query_queue_reply, 84 IniParser.py, 69 Ispg_query_queue_t, 72	· — —	lspg_flush, 75
pgpmac.h, 308 lspg_notice_processor, 76 lspg_pg_connect, 76 i lspg_pg_service, 77 mk_pgpmac_redis, 12 lspg_query_next, 78 inactive_init lspg_query_push, 79 lspmac_motor_struct, 49 lspg_query_queue, 84 iniParser, 11 lspg_query_queue_off, 84 ip, 11 lspg_query_queue_on, 84 iniParser.iniParser, 15 lspg_query_queue_reply, 84 iniParser.py, 69 lspg_query_queue_t, 72	· -	lspg_next_state, 75
Ispg_pg_connect, 76 i Ispg_pg_service, 77 mk_pgpmac_redis, 12 Ispg_query_next, 78 inactive_init Ispg_query_push, 79 Ispmac_motor_struct, 49 Ispg_query_queue, 84 iniParser, 11 Ispg_query_queue_off, 84 ip, 11 Ispg_query_queue_on, 84 iniParser.iniParser, 15 Ispg_query_queue_reply, 84 iniParser.py, 69 Ispg_query_queue_t, 72	•	
i lspg_pg_service, 77 mk_pgpmac_redis, 12 lspg_query_next, 78 inactive_init lspg_query_push, 79 lspmac_motor_struct, 49 lspg_query_queue, 84 iniParser, 11 lspg_query_queue_off, 84 ip, 11 lspg_query_queue_on, 84 iniParser.iniParser, 15 lspg_query_queue_reply, 84 iniParser.py, 69 lspg_query_queue_t, 72	1-31)	Ispg pg connect, 76
mk_pgpmac_redis, 12 inactive_init lspg_query_next, 78 inactive_init lspg_query_push, 79 lspmac_motor_struct, 49 iniParser, 11 lspg_query_queue_off, 84 ip, 11 lspg_query_queue_on, 84 iniParser.iniParser, 15 lspg_query_queue_reply, 84 iniParser.py, 69 lspg_query_queue_t, 72	i	
inactive_init lspg_query_push, 79 lspmac_motor_struct, 49 lspg_query_queue, 84 lspg_query_queue_off, 84 lspg_query_queue_off, 84 lspg_query_queue_on, 84 lspg_query_queue_reply, 84 iniParser.py, 69 lspg_query_queue_t, 72	mk pgpmac redis, 12	
Ispmac_motor_struct, 49 iniParser, 11 ip, 11 Ispg_query_queue_off, 84 iniParser.iniParser, 15 Ispg_query_queue_on, 84 iniParser.py, 69 Ispg_query_queue_t, 72	_, ·, _	
iniParser, 11	-	
ip, 11 lspg_query_queue_on, 84 iniParser.iniParser, 15 lspg_query_queue_reply, 84 iniParser.py, 69 lspg_query_queue_t, 72	· — —	
iniParser.iniParser, 15 lspg_query_queue_reply, 84 iniParser.py, 69 lspg_query_queue_t, 72		
iniParser.py, 69 lspg_query_queue_t, 72	•	
ini arsonanii arson	··	
	iiii aisoi.iiiii aisoi	iopg_query_repry_rext, 70

lspg_query_reply_peek, 80	Imsg
Ispg_receive, 80	Islogging_queue_struct, 19
lspg_resetPoll_response, 84	lp_air
lspg_send_next_query, 81	Ispmac.c, 205
Ispgfd, 84	pgpmac.h, 308
main, 81	. 5.
	ls_pg_state
now, 84	kvredis.c, 83
q, 84	lspg.c, 132
redisDisconnectCB, 83	ls_pmac_state
subac, 85	Ispmac.c, 205
subfd, 85	IsConnect
kvseq	Ispmac.c, 149
kvredis.c, 83	Isevents.c, 85
LO DO OTATE IDLE	lsevents_add_listener, 87
LS_PG_STATE_IDLE	Isevents_init, 87
kvredis.c, 71	Isevents_listener_mutex, 90
lspg.c, 100	Isevents listener t, 87
LS_PG_STATE_INIT	lsevents_listeners_p, 90
kvredis.c, 71	Isevents queue, 90
lspg.c, 101	lsevents_queue_cond, 90
LS_PG_STATE_RECV	Isevents queue mutex, 90
kvredis.c, 72	—· —
lspg.c, 101	lsevents_queue_off, 90
LS_PG_STATE_RESET	lsevents_queue_on, 91
kvredis.c, 72	lsevents_queue_t, 87
lspg.c, 101	lsevents_remove_listener, 88
LS_PG_STATE_SEND	lsevents_run, 88
kvredis.c, 72	Isevents_send_event, 88
Ispg.c, 101	lsevents_thread, 91
LS_PMAC_STATE_CR	lsevents_worker, 89
Ispmac.c, 143	lsevents_add_listener
LS_PMAC_STATE_GB	Isevents.c, 87
	pgpmac.h, 275
Ispmac.c, 144	Isevents init
LS_PMAC_STATE_GMR	Isevents.c, 87
Ispmac.c, 144	pgpmac.h, 275
LS_PMAC_STATE_IDLE	Isevents_listener_mutex
Ispmac.c, 144	Isevents.c, 90
LS_PMAC_STATE_RESET	Isevents listener struct, 17
Ispmac.c, 144	cb, 18
LS_PMAC_STATE_RR	•
Ispmac.c, 144	next, 18
LS_PMAC_STATE_SC	raw_regexp, 18
Ispmac.c, 144	re, 18
LS_PMAC_STATE_WACK	lsevents_listener_t
Ispmac.c, 144	Isevents.c, 87
LS_PMAC_STATE_WCR	lsevents_listeners_p
Ispmac.c, 144	Isevents.c, 90
LS_PMAC_STATE_WGB	lsevents_queue
Ispmac.c, 144	Isevents.c, 90
LSLOGGING FILE NAME	lsevents_queue_cond
Islogging.c, 92	Isevents.c, 90
LSPMAC PRESET REGEX	lsevents_queue_mutex
Ispmac.c, 145	Isevents.c, 90
LSTIMER_LIST_LENGTH	Isevents_queue_off
Istimer.c, 230	Isevents.c, 90
last_nsecs	lsevents_queue_on
Istimer_list_struct, 57	Isevents.c, 91
last_secs	lsevents_queue_struct, 18
Istimer_list_struct, 57	evp, 19

lsevents_queue_t	Islogging.c, 94
Isevents.c, 87	lspg.c, 95
lsevents_remove_listener	LS_PG_STATE_IDLE, 100
Isevents.c, 88	LS_PG_STATE_INIT, 101
pgpmac.h, 276	LS_PG_STATE_RECV, 101
lsevents_run	LS_PG_STATE_RESET, 101
Isevents.c, 88	LS_PG_STATE_SEND, 101
pgpmac.h, 276	ls_pg_state, 132
lsevents_send_event	lspg_array2ptrs, 102
Isevents.c, 88	lspg_cmd_cb, 103
pgpmac.h, 276	lspg_connectPoll_response, 132
Isevents_thread	lspg_demandairrights, 132
Isevents.c, 91	lspg_demandairrights_all, 103
lsevents_worker	lspg_demandairrights_call, 104
Isevents.c, 89	lspg_demandairrights_cb, 104
Islogging.c, 91	lspg_demandairrights_init, 104
LSLOGGING_FILE_NAME, 92	lspg_demandairrights_wait, 104
Islogging_cond, 94	lspg_flush, 104
Islogging_file, 94	lspg_getcenter, 132
Islogging_init, 93	lspg_getcenter_all, 105
Islogging_log_message, 93	lspg_getcenter_call, 105
Islogging_mutex, 94	lspg_getcenter_cb, 105
Islogging_off, 95	lspg_getcenter_done, 106
Islogging_on, 95	lspg_getcenter_init, 106
Islogging_queue, 95	lspg_getcenter_wait, 107
Islogging_queue_t, 93	lspg_getcurrentsampleid, 132
Islogging_run, 94	lspg_getcurrentsampleid_call, 107
Islogging_thread, 95	lspg_getcurrentsampleid_cb, 107
Islogging_worker, 94	lspg_getcurrentsampleid_init, 107
Islogging_cond	lspg_getcurrentsampleid_read, 108
Islogging.c, 94	lspg_getcurrentsampleid_wait_for_id, 108
Islogging_file	lspg_init, 108
Islogging.c, 94	lspg_lock_detector, 132
Islogging_init	lspg_lock_detector_all, 109
Islogging.c, 93	lspg_lock_detector_call, 109
pgpmac.h, 277	lspg_lock_detector_cb, 109
Islogging_log_message	lspg_lock_detector_done, 109
Islogging.c, 93	lspg_lock_detector_init, 109
pgpmac.h, 277	lspg_lock_detector_t, 101
Islogging_mutex	lspg_lock_detector_wait, 110
Islogging.c, 94	lspg_lock_diffractometer, 133
Islogging_off	lspg_lock_diffractometer_all, 110
Islogging.c, 95	Ispg_lock_diffractometer_call, 110
Islogging_on	lspg_lock_diffractometer_cb, 110
Islogging.c, 95	Ispg_lock_diffractometer_done, 111
Islogging_queue	Ispg_lock_diffractometer_init, 111
Islogging.c, 95	lspg_lock_diffractometer_t, 101
Islogging_queue_struct, 19	Ispg_lock_diffractometer_wait, 111
Imsg, 19	Ispg_next_state, 111
Itime, 19	Ispg_nextaction_cb, 112
Islogging_queue_t	Ispg_nextsample, 133
Islogging.c, 93	lspg_nextsample_all, 113
Islogging_run	lspg_nextsample_call, 113
Islogging.c, 94	lspg_nextsample_cb, 113
pgpmac.h, 278	lspg_nextsample_done, 114
Islogging_thread	Ispg_nextsample_init, 114
Islogging.c, 95	Ispg_nextsample_wait, 114
lslogging_worker	lspg_nextshot, 133

lspg_nextshot_call, 114	lspg_array2ptrs
lspg_nextshot_cb, 115	lspg.c, 102
lspg_nextshot_done, 118	pgpmac.h, 278
lspg_nextshot_init, 119	lspg_cmd_cb
lspg_nextshot_wait, 119	lspg.c, 103
lspg_notice_processor, 119	Ispg_connectPoll_response
lspg_pg_connect, 119	kvredis.c, 84
lspg_pg_service, 120	lspg.c, 132
lspg_query_next, 122	lspg_demandairrights
lspg_query_push, 122	lspg.c, 132
lspg_query_queue, 133	pgpmac.h, 308
lspg_query_queue_off, 133	lspg_demandairrights_all
lspg_query_queue_on, 133	lspg.c, 103
lspg_query_queue_reply, 133	pgpmac.h, 279
lspg_query_reply_next, 123	lspg_demandairrights_call
lspg_query_reply_peek, 123	lspg.c, 104
lspg_queue_cond, 133	lspg_demandairrights_cb
lspg_queue_mutex, 133	lspg.c, 104
lspg_receive, 123	lspg_demandairrights_init
lspg_resetPoll_response, 134	lspg.c, 104
lspg_run, 124	lspg_demandairrights_struct, 20
lspg_send_next_query, 124	cond, 20
lspg_seq_run_prep, 134	mutex, 20
lspg_seq_run_prep_all, 125	new_value_ready, 20
lspg_seq_run_prep_call, 125	lspg_demandairrights_t
lspg_seq_run_prep_cb, 126	pgpmac.h, 274
lspg_seq_run_prep_done, 126	lspg_demandairrights_wait
lspg_seq_run_prep_init, 126	lspg.c, 104
lspg_seq_run_prep_t, 101	lspg_flush
lspg_seq_run_prep_wait, 127	kvredis.c, 75
lspg_sig_service, 127	lspg.c, 104
lspg_starttransfer, 134	lspg_getcenter
lspg_starttransfer_all, 127	lspg.c, 132
lspg_starttransfer_call, 128	pgpmac.h, 309
lspg_starttransfer_cb, 128	lspg_getcenter_all
lspg_starttransfer_done, 128	lspg.c, 105
lspg_starttransfer_init, 128	lspg_getcenter_call
Ispg_starttransfer_wait, 128	lspg.c, 105
Ispg_thread, 134	pgpmac.h, 280
Ispg_wait_for_detector, 134	lspg_getcenter_cb
Ispg wait for detector all, 129	lspg.c, 105
Ispg wait for detector call, 129	Ispg getcenter done
lspg_wait_for_detector_cb, 129	Ispg.c, 106
Ispg wait for detector done, 129	pgpmac.h, 280
lspg_wait_for_detector_init, 130	lspg_getcenter_init
lspg_wait_for_detector_t, 101	Ispg.c, 106
Ispg wait for detector wait, 130	lspg_getcenter_struct, 20
Ispg_waitcryo, 134	cond, 21
lspg_waitcryo_all, 130	dax, 21
lspg_waitcryo_cb, 130	dax_isnull, 21
lspg_waitcryo_init, 130	day, 21
lspg_worker, 131	day_isnull, 22
Ispgfd, 134	daz, 22
lspmac_sample_detector_cb, 132	daz isnull, 22
now, 134	dcx, 22
q, 134	dox, 22 dcx_isnull, 22
lspg_allkvs_cb	dcy, 22
kvredis.c, 74	dcy_isnull, 22
	30 <u>, 1</u> 0.13, 22

	mutex, 22	Ispg	_lock_diffractometer_all
	new_value_ready, 22		lspg.c, 110
	no_rows_returned, 22	Ispg	_lock_diffractometer_call
	zoom, 23		Ispg.c, 110
	zoom_isnull, 23	Ispg	_lock_diffractometer_cb
lspg_	_getcenter_t		lspg.c, 110
	pgpmac.h, 274	Ispg	_lock_diffractometer_done
lspg_	_getcenter_wait		lspg.c, 111
	lspg.c, 107	Ispg	_lock_diffractometer_init
	pgpmac.h, 280		Ispg.c, 111
lspg_	_getcurrentsampleid	Ispg	_lock_diffractometer_struct, 25
	lspg.c, 132		cond, 25
	pgpmac.h, 309		mutex, 25
lspg_	_getcurrentsampleid_call		new_value_ready, 25
	lspg.c, 107	Ispg	_lock_diffractometer_t
lspg_	_getcurrentsampleid_cb		lspg.c, 101
	lspg.c, 107	Ispg	_lock_diffractometer_wait
lspg_	_getcurrentsampleid_init		Ispg.c, 111
	lspg.c, 107	Ispg	_next_state
lspg_	_getcurrentsampleid_read		kvredis.c, 75
	Ispg.c, 108		Ispg.c, 111
lspg_	_getcurrentsampleid_struct, 23	lspg_	_nextaction_cb
	cond, 23		Ispg.c, 112
	getcurrentsampleid, 23	lspg_	_nextsample
	getcurrentsampleid_isnull, 24		Ispg.c, 133
	mutex, 24		pgpmac.h, 309
	new_value_ready, 24	lspg_	_nextsample_all
	no_rows_returned, 24		Ispg.c, 113
lspg_	_getcurrentsampleid_t		pgpmac.h, 281
	pgpmac.h, 274	Ispg	_nextsample_call
lspg_	_getcurrentsampleid_wait_for_id		lspg.c, 113
	Ispg.c, 108	lspg_	_nextsample_cb
	pgpmac.h, 280		lspg.c, 113
lspg_		lspg_	_nextsample_done
	lspg.c, 108		Ispg.c, 114
	pgpmac.h, 280	lspg_	_nextsample_init
lspg_	_lock_detector		Ispg.c, 114
	lspg.c, 132	lspg_	_nextsample_struct, 25
lspg_	_lock_detector_all		cond, 26
	lspg.c, 109		mutex, 26
lspg_	_lock_detector_call		new_value_ready, 26
	lspg.c, 109		nextsample, 26
lspg_	_lock_detector_cb		nextsample_isnull, 26
	lspg.c, 109		no_rows_returned, 26
lspg_	_lock_detector_done	Ispg	_nextsample_t
	lspg.c, 109		pgpmac.h, 274
lspg_	_lock_detector_init	Ispg	_nextsample_wait
	lspg.c, 109		Ispg.c, 114
Ispg_	_lock_detector_struct, 24	Ispg	_nextshot
	cond, 24		lspg.c, 133
	mutex, 24		pgpmac.h, 309
l=:-	new_value_ready, 25	ıspg	_nextshot_call
ıspg	_lock_detector_t		lspg.c, 114
l=:-	Ispg.c, 101	la :-	pgpmac.h, 281
ıspg_	_lock_detector_wait	ıspg	_nextshot_cb
1	lspg.c, 110	1	Ispg.c, 115
ıspg	_lock_diffractometer	ıspg	_nextshot_done
	lspg.c, 133		lspg.c, 118

1.004	
pgpmac.h, 281	dsowidth2, 35
lspg_nextshot_init	dsowidth2_isnull, 35
Ispg.c, 119	dsowidth_isnull, 35
lspg_nextshot_struct, 27	dsphi, 35
active, 29	dsphi2, 35
active2, 29	dsphi2_isnull, 35
active2_isnull, 30	dsphi_isnull, 35
active_isnull, 30	dspid, 35
ax, 30	dspid_isnull, 35
ax2, 30	mutex, 35
ax2_isnull, 30	new_value_ready, 36
ax_isnull, 30	no_rows_returned, 36
ay, 30	sfn, 36
ay2, 30	sfn_isnull, 36
ay2_isnull, 30	sindex, 36
ay_isnull, 30	sindex2, 36
az, 30	sindex2_isnull, 36
az2, 31	sindex_isnull, 36
az2_isnull, 31	skey, 36
az_isnull, 31	skey_isnull, 36
cond, 31	sstart, 37
cx, 31	sstart2, 37
cx2, 31	sstart2_isnull, 37
cx2_isnull, 31	sstart_isnull, 37
cx_isnull, 31	stype, 37
cy, 31	stype2, 37
cy2, 31	stype2_isnull, 37
cy2_isnull, 32	stype_isnull, 37
cy_isnull, 32	lspg_nextshot_t
dsdir, 32	pgpmac.h, 274
dsdir_isnull, 32	lspg_nextshot_wait
dsdist, 32	Ispg.c, 119
dsdist2, ianull, 32	pgpmac.h, 282
dsdist2_isnull, 32	lspg_notice_processor
dsdist_isnull, 32	kvredis.c, 76
dsexp, 32	Ispg.c, 119
dsexp2, 32 dsexp2_isnull, 33	lspg_pg_connect kvredis.c, 76
dsexp_isnull, 33	Ispg.c, 119
dsexp_ishdii, 33 dshpid, 33	Ispg_pg_service
dshpid_isnull, 33	kvredis.c, 77
dshipid_ishdii, 33 dskappa, 33	Ispg.c, 120
dskappa2, 33	Ispg_query_next
dskappa2_isnull, 33	kvredis.c, 78
dskappa_isnull, 33	Ispg.c, 122
dsnrg, 33	. 5
dsnrg2, 33	lspg_query_push kvredis.c, 79
dsnrg2_isnull, 34	
dsnrg_isnull, 34 dsnrg_isnull, 34	Ispg.c, 122
-	pgpmac.h, 282
dsomega, 34	lspg_query_queue
dsomega2, 34	kvredis.c, 84
dsomega2_isnull, 34	lspg.c, 133
dsomega_isnull, 34	lspg_query_queue_off
dsoscaxis, 34	kvredis.c, 84
dsoscaxis2, 34	Ispg.c, 133
dsoscaxis2_isnull, 34	lspg_query_queue_on
dsoscaxis_isnull, 34	kvredis.c, 84
dsowidth, 34	lspg.c, 133

lspg_query_queue_reply	pgpmac.h, 283
kvredis.c, 84	lspg_starttransfer_cb
lspg.c, 133	Ispg.c, 128
lspg_query_queue_t	lspg_starttransfer_done
kvredis.c, 72	lspg.c, 128
pgpmac.h, 274	pgpmac.h, 283
lspg_query_reply_next	lspg_starttransfer_init
kvredis.c, 79	lspg.c, 128
lspg.c, 123	lspg_starttransfer_struct, 38
lspg_query_reply_peek	cond, 39
kvredis.c, 80	mutex, 39
lspg.c, 123	new_value_ready, 39
lspg_queue_cond	no_rows_returned, 39
lspg.c, 133	starttransfer, 39
lspg_queue_mutex	lspg_starttransfer_t
lspg.c, 133	pgpmac.h, 274
Ispg_receive	lspg_starttransfer_wait
kvredis.c, 80	lspg.c, 128
lspg.c, 123	pgpmac.h, 283
lspg_resetPoll_response	lspg_thread
kvredis.c, 84	lspg.c, 134
Ispg.c, 134	lspg_wait_for_detector
lspg_run	Ispg.c, 134
lspg.c, 124	lspg_wait_for_detector_all
pgpmac.h, 282	lspg.c, 129
lspg_send_next_query	lspg_wait_for_detector_call
kvredis.c, 81	lspg.c, 129
Ispg.c, 124	lspg_wait_for_detector_cb
lspg_seq_run_prep	lspg.c, 129
Ispg.c, 134	lspg_wait_for_detector_done
lspg_seq_run_prep_all	lspg.c, 129
lspg.c, 125	lspg_wait_for_detector_init
pgpmac.h, 283	lspg.c, 130
lspg_seq_run_prep_call	lspg_wait_for_detector_struct, 39
Ispg.c, 125	cond, 40
lspg_seq_run_prep_cb	mutex, 40
Ispg.c, 126	new_value_ready, 40
lspg_seq_run_prep_done	lspg_wait_for_detector_t
lspg.c, 126	Ispg.c, 101
lspg_seq_run_prep_init	lspg_wait_for_detector_wait
lspg.c, 126	lspg.c, 130
lspg_seq_run_prep_struct, 37	lspg_waitcryo
cond, 38	lspg.c, 134
mutex, 38	pgpmac.h, 309
new_value_ready, 38	lspg_waitcryo_all
lspg_seq_run_prep_t	lspg.c, 130
Ispg.c, 101	pgpmac.h, 284
lspg_seq_run_prep_wait	lspg_waitcryo_cb
Ispg.c, 127	lspg.c, 130
lspg_sig_service	pgpmac.h, 284
Ispg.c, 127	lspg_waitcryo_init
lspg_starttransfer	lspg.c, 130
lspg.c, 134	lspg_waitcryo_struct, 40
pgpmac.h, 309	cond, 40
lspg_starttransfer_all	mutex, 40
lspg.c, 127	new_value_ready, 41
lspg_starttransfer_call	lspg_waitcryo_t
lspg.c, 128	pgpmac.h, 274

lspg_worker	LS_PMAC_STATE_GMR, 144
lspg.c, 131	LS_PMAC_STATE_IDLE, 144
lspg_zoom_lut_call	LS_PMAC_STATE_RR, 144
pgpmac.h, 284	LS_PMAC_STATE_SC, 144
IspgQueryQueueStruct, 41	LS_PMAC_STATE_WACK, 144
onResponse, 41	LS_PMAC_STATE_WCR, 144
qs, 41	LS_PMAC_STATE_WGB, 144
Ispgfd	LSPMAC_PRESET_REGEX, 145
kvredis.c, 84	lp_air, 205
lspg.c, 134	ls_pmac_state, 205
Ispmac.c, 135	IsConnect, 149
_lspmac_motor_init, 147	Ispmac_Error, 154
alignx, 201	Ispmac_GetAllIVars, 161
aligny, 201	lspmac_GetAllIVarsCB, 162
alignz, 201	Ispmac_GetAllMVars, 162
anal, 201	Ispmac_GetAllMVarsCB, 162
apery, 201	Ispmac_GetShortReplyCB, 164
aperz, 201	Ispmac_Getmem, 163
arm_parked, 201	Ispmac_GetmemReplyCB, 163
blight, 201	Ispmac_Reset, 187
blight_down, 201	Ispmac_SendControlReplyPrintCB, 192
blight_f, 201	Ispmac_Service, 192
blight_ud, 202	Ispmac_SockFlush, 195
blight_up, 202	Ispmac_SockGetmem, 195
capy, 202	Ispmac_SockSendControlCharPrint, 196
capz, 202	Ispmac_SockSendDPControlChar, 196
cenx, 202	Ispmac_SockSendDPControlCharCB, 196
ceny, 202	Ispmac_SockSendDPline, 196
cleanstr, 148	Ispmac_SockSendDPqueue, 197
cr_cmd, 202	Ispmac_SockSendline, 197
cryo, 202	lspmac_SockSendline_nr, 198
cryo_back, 202	Ispmac_abort, 150
cryo_switch, 203	Ispmac ascii buffers, 205
dbmem, 203	Ispmac_ascii_buffers_mutex, 205
dbmemIn, 203	Ispmac_ascii_buffers_t, 147
dryer, 203	Ispmac_ascii_busy, 205
etel_init_ok, 203	Ispmac_ascii_mutex, 206
etel_on, 203	Ispmac asciicmdCB, 150
etel_ready, 203	Ispmac_backLight_down_cb, 150
ethCmdOff, 203	Ispmac_backLight_up_cb, 150
ethCmdOn, 203	Ispmac_bi_init, 150
ethCmdQueue, 204	Ispmac_bis, 206
ethCmdReply, 204	Ispmac_blight_lut_setup, 151
flight, 204	Ispmac_bo_init, 151
flight_f, 204	Ispmac bo read, 152
flight oo, 204	Ispmac_command_done_cb, 152
fluo, 204	Ispmac_cryoSwitchChanged_cb, 153
fluor_back, 204	Ispmac_dac_init, 153
fscint, 204	Ispmac_dac_read, 153
fshut, 204	Ispmac_dpascii_off, 206 Ispmac_dpascii_on, 206
gb_cmd, 205	Ispmac_dpascii_queue, 206
getivars, 205	. – . – .
getmvars, 205	Ispmac_dpascii_queue_t, 147
hex_dump, 148	Ispmac_est_move_time, 154
hp_air, 205	Ispmac_flight_lut_setup, 155
kappa, 205	Ispmac_fscint_lut_setup, 156
LS_PMAC_STATE_CR, 143	Ispmac_fshut_init, 156
LS_PMAC_STATE_GB, 144	Ispmac_get_ascii, 157

James and and de 457	
Ispmac_get_ascii_cb, 157	md2_status, 207
Ispmac_get_status, 158	md2_status_mutex, 207
Ispmac_get_status_cb, 158	md2_status_t, 147
Ispmac_getBIPosition, 163	minikappa_ok, 208
Ispmac_getPosition, 163	now, 208
Ispmac_home1_queue, 164	omega, 208
lspmac_home2_queue, 165	omega_zero_search, 208
Ispmac_init, 166	omega_zero_time, 208
lspmac_jogabs_queue, 169	omega_zero_velocity, 208
lspmac_light_zoom_cb, 170	PMAC_MIN_CMD_TIME, 145
Ispmac_lut, 170	PMACPORT, 145
Ispmac_more_ascii_cb, 171	phi, 208
Ispmac_motor_init, 171	pmac_cmd_size, 145
Ispmac_motors, 206	pmac_error_strs, 208
lspmac_move_or_jog_abs_queue, 172	pmac_queue_cond, 209
lspmac_move_or_jog_preset_queue, 174	pmac_queue_mutex, 209
Ispmac_move_preset_queue, 175	pmac_thread, 209
lspmac_moveabs_blight_factor_queue, 175	pmacfd, 209
lspmac_moveabs_bo_queue, 175	rr_cmd, 209
lspmac_moveabs_flight_factor_queue, 176	sample_detected, 209
lspmac_moveabs_frontlight_oo_queue, 176	scint, 209
lspmac_moveabs_fshut_queue, 177	shutter_open, 210
lspmac_moveabs_queue, 177	smart_mag_err, 210
lspmac_moveabs_timed_queue, 177	smart_mag_off, 210
Ispmac_moveabs_wait, 178	smart_mag_on, 210
Ispmac_movedac_queue, 180	smart_mag_oo, 210
lspmac_movezoom_queue, 180	VR_CTRL_RESPONSE, 145
Ispmac_moving_cond, 206	VR_DOWNLOAD, 145
lspmac_moving_flags, 206	VR_FWDOWNLOAD, 145
Ispmac_moving_mutex, 206	VR_IPADDRESS, 145
Ispmac_nbis, 206	VR_PMAC_FLUSH, 145
Ispmac_next_state, 181	VR_PMAC_GETBUFFER, 146
Ispmac_nmotors, 207	VR_PMAC_GETLINE, 146
Ispmac_pmacmotor_read, 182	VR_PMAC_GETMEM, 146
Ispmac_pop_queue, 185	VR_PMAC_GETRESPONSE, 146
Ispmac_pop_reply, 186	VR_PMAC_PORT, 146
lspmac_push_queue, 186	VR_PMAC_READREADY, 146
Ispmac_reset_queue, 187	VR_PMAC_SENDLINE, 146
Ispmac_rlut, 187	VR_PMAC_SETBIT, 146
Ispmac_run, 188	VR_PMAC_SETBITS, 146
Ispmac_scint_dried_cb, 189	VR_PMAC_SETMEM, 146
Ispmac_scint_inPosition_cb, 190	VR_PMAC_WRITEBUFFER, 146
Ispmac_send_command, 190	VR_PMAC_WRITEERROR, 147
Ispmac_sendcmd, 191	VR_UPLOAD, 147
lspmac_sendcmd_nocb, 191	zoom, 210
lspmac_shutter_cond, 207	lspmac_Error
lspmac_shutter_has_opened, 207	Ispmac.c, 154
lspmac_shutter_mutex, 207	Ispmac_GetAllIVars
lspmac_shutter_read, 194	Ispmac.c, 161
lspmac_shutter_state, 207	Ispmac_GetAllIVarsCB
Ispmac_soft_motor_init, 198	Ispmac.c, 162
Ispmac_soft_motor_read, 198	Ispmac_GetAllMVars
Ispmac_status_last_time, 207	Ispmac.c, 162
lspmac_status_time, 207	Ispmac_GetAllMVarsCB
Ispmac_test_preset, 198	Ispmac.c, 162
lspmac_video_rotate, 199	lspmac_GetShortReplyCB
lspmac_worker, 199	Ispmac.c, 164
lspmac_zoom_lut_setup, 200	lspmac_Getmem

Ispmac.c, 163	changeEventOff, 43
Ispmac_GetmemReplyCB	changeEventOn, 43
Ispmac.c, 163	first_time, 43
Ispmac_Reset	mask, 43
Ispmac.c, 187	mutex, 43
Ispmac_SendControlReplyPrintCB	position, 44
Ispmac.c, 192	previous, 44
Ispmac_Service	ptr, 44
lspmac.c, 192	Ispmac_bi_t
Ispmac SockFlush	pgpmac.h, 274
Ispmac.c, 195	Ispmac_bis
Ispmac SockGetmem	Ispmac.c, 206
Ispmac.c, 195	lspmac_blight_lut_setup
Ispmac_SockSendControlCharPrint	Ispmac.c, 151
Ispmac.c, 196	Ispmac_bo_init
Ispmac_SockSendDPControlChar	Ispmac.c, 151
Ispmac.c, 196	Ispmac_bo_read
lspmac_SockSendDPControlCharCB	Ispmac.c, 152
Ispmac.c, 196	Ispmac_cmd_queue_struct, 44
Ispmac SockSendDPline	event, 45
Ispmac.c, 196	no_reply, 45
pgpmac.h, 295	onResponse, 45
Ispmac_SockSendDPqueue	pcmd, 45
Ispmac.c, 197	time_sent, 45
Ispmac_SockSendline	lspmac_command_done_cb
Ispmac.c, 197	Ispmac.c, 152
pgpmac.h, 296	lspmac_cryoSwitchChanged_cb
Ispmac_SockSendline_nr	Ispmac.c, 153
Ispmac.c, 198	lspmac_dac_init
lspmac_abort	Ispmac.c, 153
Ispmac.c, 150	lspmac_dac_read
pgpmac.h, 284	Ispmac.c, 153
lspmac_ascii_buffers	lspmac_dpascii_off
Ispmac.c, 205	Ispmac.c, 206
lspmac_ascii_buffers_mutex	lspmac_dpascii_on
Ispmac.c, 205	Ispmac.c, 206
lspmac_ascii_buffers_struct, 42	lspmac_dpascii_queue
command_buf, 42	Ispmac.c, 206
command_buf_cc, 42	Ispmac_dpascii_queue_struct, 45
command_str, 42	event, 45
response_buf, 42	pl, 45
response_n, 42	lspmac_dpascii_queue_t
response_str, 42	Ispmac.c, 147
lspmac_ascii_buffers_t	lspmac_est_move_time
Ispmac.c, 147	Ispmac.c, 154
lspmac_ascii_busy	lspmac_flight_lut_setup
Ispmac.c, 205	Ispmac.c, 155
Ispmac_ascii_mutex	lspmac_fscint_lut_setup
Ispmac.c, 206	Ispmac.c, 156
Ispmac_asciicmdCB	lspmac_fshut_init
Ispmac.c, 150	Ispmac.c, 156
lspmac_backLight_down_cb	lspmac_get_ascii
Ispmac.c, 150	Ispmac.c, 157
lspmac_backLight_up_cb	lspmac_get_ascii_cb
Ispmac.c, 150	Ispmac.c, 157
lspmac_bi_init	lspmac_get_status
Ispmac.c, 150	Ispmac.c, 158
lspmac_bi_struct, 42	lspmac_get_status_cb

Ispmac.c, 158	read, 51
Ispmac_getBIPosition	read_mask, 51
Ispmac.c, 163	read_ptr, 52
pgpmac.h, 284	redis_fmt, 52
Ispmac_getPosition	redis_position, 52
Ispmac.c, 163	reported_position, 52
pgpmac.h, 285	requested_pos_cnts, 52
Ispmac_home1_queue	requested_position, 52
Ispmac.c, 164	status1, 52
pgpmac.h, 285	status1_p, 52
lspmac_home2_queue	status2, 52
Ispmac.c, 165	status2_p, 53
lspmac_init	status_str, 53
Ispmac.c, 166	u2c, 53
pgpmac.h, 286	unit, 53
lspmac_jogabs_queue	update_resolution, 53
Ispmac.c, 169	win, 53
pgpmac.h, 289	write_fmt, 53
lspmac_light_zoom_cb	lspmac_motor_t
Ispmac.c, 170	pgpmac.h, 274
Ispmac_lut	lspmac_motors
Ispmac.c, 170	Ispmac.c, 206
lspmac_more_ascii_cb	pgpmac.h, 309
Ispmac.c, 171	lspmac_move_or_jog_abs_queue
Ispmac_motor_init	Ispmac.c, 172
Ispmac.c, 171	pgpmac.h, 289
Ispmac_motor_struct, 46	lspmac_move_or_jog_preset_queue
active, 48	Ispmac.c, 174
active_init, 48	pgpmac.h, 292
actual_pos_cnts, 48	lspmac_move_or_jog_queue
actual_pos_cnts_p, 48	pgpmac.h, 292
axis, 48	lspmac_move_preset_queue
command_sent, 48	Ispmac.c, 175
cond, 49	pgpmac.h, 292
coord_num, 49	lspmac_moveabs_blight_factor_queue
dac_mvar, 49	Ispmac.c, 175
home, 49	lspmac_moveabs_bo_queue
homing, 49	Ispmac.c, 175
inactive_init, 49	Ispmac_moveabs_flight_factor_queue
lut, 49	Ispmac.c, 176
max_accel, 49	lspmac_moveabs_frontlight_oo_queue
max_pos, 49	Ispmac.c, 176
max_speed, 50	lspmac_moveabs_fshut_queue
min_pos, 50	Ispmac.c, 177
motion_seen, 50	lspmac_moveabs_queue
motor_num, 50	Ispmac.c, 177
moveAbs, 50	pgpmac.h, 293
mutex, 50	lspmac_moveabs_timed_queue
name, 50	Ispmac.c, 177
neg_limit_hit, 50	Ispmac_moveabs_wait
neutral_pos, 50	Ispmac.c, 178
nlut, 51	pgpmac.h, 293
not_done, 51	lspmac_movedac_queue
pos_limit_hit, 51	Ispmac.c, 180
position, 51	lspmac_movezoom_queue
pq, 51	Ispmac.c, 180
precision, 51	lspmac_moving_cond
printf_fmt, 51	Ispmac.c, 206

1,000	100
pgpmac.h, 309	Ispmac.c, 198
Ispmac_moving_flags	lspmac_status_last_time
Ispmac.c, 206	Ispmac.c, 207
pgpmac.h, 309	Ispmac_status_time Ispmac.c, 207
Ispmac_moving_mutex Ispmac.c, 206	•
pgpmac.h, 310	lspmac_test_preset lspmac.c, 198
Ispmac_nbis	Ispmac video rotate
Ispmac.c, 206	Ispmac.c, 199
Ispmac_next_state	pgpmac.h, 296
Ispmac.c, 181	Ispmac worker
Ispmac_nmotors	Ispmac.c, 199
Ispmac.c, 207	lspmac_zoom_lut_setup
pgpmac.h, 310	Ispmac.c, 200
Ispmac_pmacmotor_read	Isredis.c, 210
Ispmac.c, 182	_lsredis_get_obj, 213
Ispmac_pop_queue	_lsredis_set_value, 214
Ispmac.c, 185	Isredis addRead, 215
Ispmac_pop_reply	Isredis_addWrite, 215
Ispmac.c, 186	Isredis_cleanup, 215
Ispmac_push_queue	Isredis_cmpnstr, 216
Ispmac.c, 186	Isredis cmpstr, 216
Ispmac_reset_queue	Isredis_cond, 227
Ispmac.c, 187	Isredis_debugCB, 216
lspmac_rlut	Isredis_delRead, 217
Ispmac.c, 187	Isredis_delWrite, 217
lspmac_run	Isredis_fd_service, 217
Ispmac.c, 188	Isredis_find_preset, 218
pgpmac.h, 294	Isredis_get_obj, 218
lspmac_sample_detector_cb	Isredis_get_string_array, 219
Ispg.c, 132	Isredis_getb, 219
Ispmac_scint_dried_cb	Isredis getc, 219
Ispmac.c, 189	Isredis_getd, 220
Ispmac_scint_inPosition_cb	Isredis_getl, 220
Ispmac.c, 190	Isredis_getstr, 220
Ispmac_send_command	Isredis_head, 227
Ispmac.c, 190	Isredis_hgetCB, 220
lspmac_sendcmd	Isredis_htab, 227
Ispmac.c, 191	Isredis_init, 221
lspmac_sendcmd_nocb	lsredis_key_select_regex, 228
Ispmac.c, 191	Isredis_keysCB, 222
lspmac_shutter_cond	lsredis_maybe_add_key, 222
Ispmac.c, 207	Isredis_mutex, 228
pgpmac.h, 310	Isredis_objs, 228
lspmac_shutter_has_opened	Isredis_publisher, 228
Ispmac.c, 207	Isredis_regexec, 223
pgpmac.h, 310	Isredis_run, 223
lspmac_shutter_mutex	Isredis_running, 228
Ispmac.c, 207	Isredis_set_value, 223
pgpmac.h, 310	Isredis_setstr, 223
lspmac_shutter_read	Isredis_sig_service, 224
Ispmac.c, 194	Isredis_subCB, 225
lspmac_shutter_state	Isredis_thread, 228
Ispmac.c, 207	Isredis_worker, 226
pgpmac.h, 310	redisDisconnectCB, 227
lspmac_soft_motor_init	roac, 228
Ispmac.c, 198	rofd, 228
lspmac_soft_motor_read	subac, 228

subfd, 228	Isredis.c, 228
wrac, 228	Isredis_keysCB
wrfd, 228	Isredis.c, 222
Isredis_addRead	Isredis_maybe_add_key
Isredis.c, 215	Isredis.c, 222
Isredis_addWrite	Isredis_mutex
Isredis.c, 215	Isredis.c, 228
Isredis_cleanup	Isredis_obj_struct, 53
Isredis.c, 215	avalue, 54
Isredis_cmpnstr	bvalue, 54
Isredis.c, 216	cond, 54
pgpmac.h, 297	cvalue, 55
Isredis_cmpstr	dvalue, 55
Isredis.c, 216	events_name, 55
pgpmac.h, 297	hits, 55
Isredis_cond	key, 55
Isredis.c, 227	Ivalue, 55
Isredis_debugCB	mutex, 55
Isredis.c, 216	next, 55 valid, 55
Isredis_delRead	•
Isredis.c, 217 Isredis delWrite	value, 56
Isredis.c, 217	value_length, 56
•	wait_for_me, 56
Isredis_fd_service	lsredis_obj_t
Isredis.c, 217	pgpmac.h, 274 Isredis_objs
Isredis_find_preset	
Isredis.c, 218	Isredis.c, 228
pgpmac.h, 297	Isredis_publisher Isredis.c, 228
Isredis_get_obj Isredis.c, 218	Isredis_regexec
	_ -
pgpmac.h, 298 Isredis_get_string_array	Isredis.c, 223 pgpmac.h, 301
Isredis.c, 219	Isredis_run
pgpmac.h, 298	Isredis_ruii
Isredis_getb	pgpmac.h, 301
Isredis.c, 219	Isredis_running
pgpmac.h, 299	Isredis_ruming
Isredis_getc	Isredis_set_value
Isredis.c, 219	Isredis.c, 223
Isredis getd	Isredis setstr
Isredis.c, 220	Isredis.c, 223
pgpmac.h, 299	pgpmac.h, 301
Isredis getl	Isredis_sig_service
Isredis.c, 220	lsredis.c, 224
pgpmac.h, 299	Isredis subCB
Isredis getstr	Isredis.c, 225
Isredis.c, 220	Isredis thread
pgpmac.h, 299	Isredis.c, 228
Isredis head	Isredis worker
Isredis.c, 227	Isredis.c, 226
Isredis_hgetCB	Istimer.c, 229
Isredis.c, 220	handler, 230
Isredis htab	LSTIMER_LIST_LENGTH, 230
Isredis.c, 227	Istimer_active_timers, 234
Isredis init	Istimer_add_timer, 231
Isredis.c, 221	Istimer_cond, 234
pgpmac.h, 300	Istimer init, 231
Isredis_key_select_regex	Istimer_list, 234
.5.55.5_7.67_561661_10867	10th 10th 10th 10th 10th 10th 10th 10th

Istimer_list_t, 230	kvredis.c, 81
Istimer_mutex, 234	pgpmac.c, 261
Istimer_run, 232	mask
Istimer_thread, 234	Ispmac_bi_struct, 43
Istimer_timerid, 235	max_accel
Istimer_worker, 232	Ispmac_motor_struct, 49
new_timer, 235	max_pos
service_timers, 233	Ispmac_motor_struct, 49
Istimer_active_timers	max_speed
Istimer.c, 234	Ispmac_motor_struct, 50
Istimer_add_timer	md2_status
Istimer.c, 231	Ispmac.c, 207
pgpmac.h, 302	md2_status_mutex
Istimer_cond	Ispmac.c, 207
Istimer.c, 234	pgpmac.h, 310
Istimer_init	md2_status_t
Istimer.c, 231	Ispmac.c, 147
pgpmac.h, 303	md2StatusStruct, 58
Istimer_list	acc11c_1, 60
Istimer.c, 234	acc11c_2, 60
Istimer_list_struct, 56	acc11c_3, 60
delay_nsecs, 57	acc11c_5, 60
delay_secs, 57	acc11c_6, 60
event, 57	alignx_act_pos, 60
init_nsecs, 57	alignx_status_1, 60
init_secs, 57	alignx_status_2, 60
last_nsecs, 57	aligny_act_pos, 60
last_secs, 57	aligny_status_1, 60
ncalls, 57	aligny_status_2, 60
next_nsecs, 58	alignz_act_pos, 60
next_secs, 58	alignz_status_1, 60
shots, 58	alignz_status_2, 61
Istimer_list_t	analyzer_act_pos, 61
Istimer.c, 230	analyzer_status_1, 61
Istimer_mutex	analyzer_status_2, 61
Istimer.c, 234	aperturey_act_pos, 61
lstimer_run	aperturey_status_1, 61
Istimer.c, 232	aperturey_status_2, 61
pgpmac.h, 303	aperturez_act_pos, 61
Istimer_thread	aperturez_status_1, 61
Istimer.c, 234	aperturez_status_2, 61
Istimer_timerid	back_dac, 61
Istimer.c, 235	capy_act_pos, 61
Istimer_worker	capy_status_1, 62
Istimer.c, 232	capy_status_2, 62
Isupdate_init	capz_act_pos, 62
pgpmac.h, 303	capz_status_1, 62
lsupdate_run	capz_status_2, 62
pgpmac.h, 304 Itime	centerx_act_pos, 62
	centerx_status_1, 62
Islogging_queue_struct, 19	centerx_status_2, 62
langua matar etruat 40	centery_act_pos, 62
Ispmac_motor_struct, 49	centery_status_1, 62
loradia ahi atruat EE	centery_status_2, 62
Isredis_obj_struct, 55	dummy1, 62
MD2CMDS CMD LENGTH	dummy2, 63
pgpmac.h, 273	dummy3, 63
main	dummy4, 63
	33y 1, 00

dummy5, 63	md2cmds_move_wait, 246
dummy6, 63	md2cmds_moveAbs, 246
dummy7, 63	md2cmds moving cond, 259
	md2cmds moving count, 259
dummy8, 63	
dummy9, 63	md2cmds_moving_mutex, 259
dummyA, 63	md2cmds_moving_queue_wait, 259
dummyB, 63	md2cmds_mutex, 259
front_dac, 63	md2cmds_mvcenter_move, 247
fs_has_opened, 63	md2cmds_organs_move_presets, 248
fs_has_opened_globally, 64	md2cmds_phase_change, 249
fs_is_open, 64	md2cmds_prep_axis, 251
kappa_act_pos, 64	md2cmds_rotate, 252
kappa_status_1, 64	md2cmds_rotate_cb, 253
kappa_status_2, 64	md2cmds run, 254
moving_flags, 64	md2cmds_set_scale_cb, 254
number_passes, 64	md2cmds_thread, 259
omega act pos, 64	md2cmds_time_capz_cb, 255
omega_status_1, 64	md2cmds transfer, 255
omega status 2, 64	md2cmds_worker, 258
phi_act_pos, 64	rotating, 259
	-
phi_status_1, 64	md2cmds_abort
phi_status_2, 65	md2cmds.c, 237
phiscan, 65	md2cmds_action_queue
scint_act_pos, 65	md2cmds.c, 237
scint_piezo, 65	md2cmds_action_wait
scint_status_1, 65	md2cmds.c, 238
scint_status_2, 65	md2cmds_capz_moving_time
zoom_act_pos, 65	md2cmds.c, 258
zoom_status_1, 65	md2cmds_center
zoom_status_2, 65	md2cmds.c, 238
md2cmds.c, 235	md2cmds cmd
md2cmds_abort, 237	md2cmds.c, 258
md2cmds_action_queue, 237	pgpmac.h, 310
md2cmds action wait, 238	md2cmds collect
md2cmds capz moving time, 258	md2cmds.c, 238
md2cmds center, 238	md2cmds cond
md2cmds cmd, 258	md2cmds.c, 258
md2cmds_cillect, 238	pgpmac.h, 310
md2cmds_cond, 258	md2cmds_coordsys_1_stopped_cb
md2cmds_coordsys_1_stopped_cb, 242	md2cmds.c, 242
md2cmds_coordsys_2_stopped_cb, 242	md2cmds_coordsys_2_stopped_cb
md2cmds_coordsys_3_stopped_cb, 242	md2cmds.c, 242
md2cmds_coordsys_4_stopped_cb, 242	md2cmds_coordsys_3_stopped_cb
md2cmds_coordsys_5_stopped_cb, 242	md2cmds.c, 242
md2cmds_coordsys_7_stopped_cb, 243	md2cmds_coordsys_4_stopped_cb
md2cmds_home_prep, 243	md2cmds.c, 242
md2cmds_home_wait, 243	md2cmds_coordsys_5_stopped_cb
md2cmds_homing_cond, 258	md2cmds.c, 242
md2cmds_homing_count, 259	md2cmds_coordsys_7_stopped_cb
md2cmds_homing_mutex, 259	md2cmds.c, 243
md2cmds_init, 244	md2cmds_home_prep
md2cmds_is_moving, 244	md2cmds.c, 243
md2cmds_kappaphi_move, 244	md2cmds_home_wait
md2cmds_maybe_done_homing_cb, 244	md2cmds.c, 243
md2cmds_maybe_done_moving_cb, 245	md2cmds_homing_cond
md2cmds_maybe_done_moving_cb, 245 md2cmds_maybe_rotate_done_cb, 245	md2cmds.c, 258
md2cmds_md_status_code, 259	md2cmds_homing_count
md2cmds_move_prep, 245	md2cmds.c, 259

md2cmds_homing_mutex	md2cmds_time_capz_cb
md2cmds.c, 259	md2cmds.c, 255
md2cmds_init	md2cmds_transfer
md2cmds.c, 244	md2cmds.c, 255
pgpmac.h, 304	md2cmds_worker
md2cmds_is_moving	md2cmds.c, 258
md2cmds.c, 244	min_pos
md2cmds_kappaphi_move	lspmac_motor_struct, 50
md2cmds.c, 244	minikappa_ok
md2cmds_maybe_done_homing_cb	Ispmac.c, 208
md2cmds.c, 244	pgpmac.h, 311
md2cmds_maybe_done_moving_cb	mk_pgpmac_redis, 11
md2cmds.c, 245	b, 12
md2cmds_maybe_rotate_done_cb	bi_list, 12
md2cmds.c, 245	f, 12
md2cmds_md_status_code	fnc, 12
md2cmds.c, 259	hard_ini, 12
pgpmac.h, 311	hard_ini_fields, 12
md2cmds_move_prep	head, 12
md2cmds.c, 245	hi, 12
md2cmds_move_wait	i, 12
md2cmds.c, 246	motor_dict, 13
md2cmds_moveAbs	motor_field_lists, 13
md2cmds.c, 246	motor_presets, 13
md2cmds_moving_cond	p, 13
md2cmds.c, 259	pi, 13
md2cmds_moving_count	ppos, 13
md2cmds.c, 259	pref_ini, 13
md2cmds_moving_mutex	v, 13
md2cmds.c, 259	x, 13
md2cmds_moving_queue_wait	y, 13
md2cmds_rioving_quede_wait	zoom_settings, 13
md2cmds_mutex	mk_pgpmac_redis.py, 260
md2cmds.c, 259	motion_seen
pgpmac.h, 311	Ispmac_motor_struct, 50
md2cmds_mvcenter_move	motor dict
md2cmds.c, 247	-
md2cmds_organs_move_presets	mk_pgpmac_redis, 13 motor_field_lists
md2cmds.c, 248	mk_pgpmac_redis, 13
md2cmds_pg_cond	— · · · —
pgpmac.h, 311	motor_num
md2cmds_pg_mutex	Ispmac_motor_struct, 50 motor presets
	_ ,
pgpmac.h, 311	mk_pgpmac_redis, 13 moveAbs
md2cmds_phase_change md2cmds.c, 249	
	Ispmac_motor_struct, 50
md2cmds_prep_axis	moving_flags
md2cmds.c, 251	md2StatusStruct, 64
md2cmds_rotate	mutex
md2cmds.c, 252	lspg_demandairrights_struct, 20
md2cmds_rotate_cb	lspg_getcenter_struct, 22
md2cmds.c, 253	lspg_getcurrentsampleid_struct, 24
md2cmds_run	lspg_lock_detector_struct, 24
md2cmds.c, 254	lspg_lock_diffractometer_struct, 25
pgpmac.h, 304	lspg_nextsample_struct, 26
md2cmds_set_scale_cb	lspg_nextshot_struct, 35
md2cmds.c, 254	lspg_seq_run_prep_struct, 38
md2cmds_thread	lspg_starttransfer_struct, 39
md2cmds.c, 259	lspg_wait_for_detector_struct, 40

lspg_waitcryo_struct, 40	omega
Ispmac_bi_struct, 43	Ispmac.c, 208
Ispmac_motor_struct, 50	pgpmac.h, 311
Isredis_obj_struct, 55	omega_act_pos
name	md2StatusStruct, 64
Ispmac_motor_struct, 50	omega_status_1
ncalls	md2StatusStruct, 64
	omega_status_2
Istimer_list_struct, 57	md2StatusStruct, 64
ncurses_mutex	omega_zero_search
pgpmac.c, 264	Ispmac.c, 208
pgpmac.h, 311	omega_zero_time
neg_limit_hit	Ispmac.c, 208
Ispmac_motor_struct, 50	pgpmac.h, 311
neutral_pos	omega_zero_velocity
Ispmac_motor_struct, 50	Ispmac.c, 208
new_timer	onResponse
Istimer.c, 235	IspgQueryQueueStruct, 41
new_value_ready	lspmac_cmd_queue_struct, 45
lspg_demandairrights_struct, 20	options
lspg_getcenter_struct, 22	iniParser::iniParser, 16
lspg_getcurrentsampleid_struct, 24	
lspg_lock_detector_struct, 25	p
lspg_lock_diffractometer_struct, 25	mk_pgpmac_redis, 13
lspg_nextsample_struct, 26	PMAC_MIN_CMD_TIME
lspg_nextshot_struct, 36	Ispmac.c, 145
lspg_seq_run_prep_struct, 38	PMACPORT
lspg_starttransfer_struct, 39	Ispmac.c, 145
lspg_wait_for_detector_struct, 40	pcmd
lspg_waitcryo_struct, 41	lspmac_cmd_queue_struct, 45
next	pgpmac.c, 260
Isevents_listener_struct, 18	main, 261
Isredis_obj_struct, 55	ncurses_mutex, 264
next_nsecs	pgpmac_printf, 263
Istimer_list_struct, 58	running, 264
next_secs	stdinService, 263
Istimer_list_struct, 58	stdinfda, 265
nextsample	term_input, 265
lspg_nextsample_struct, 26	term_output, 265
nextsample_isnull	term_status, 265
lspg_nextsample_struct, 26	term_status2, 265
nlut	pgpmac.h, 265
lspmac_motor_struct, 51	_GNU_SOURCE, 273
no_reply	alignx, 305
lspmac_cmd_queue_struct, 45	aligny, 305
no rows returned	alignz, 305
Ispg getcenter struct, 22	anal, 305
lspg_getcurrentsampleid_struct, 24	apery, 305
lspg_nextsample_struct, 26	aperz, 305
Ispg_nextshot_struct, 36	arm_parked, 305
lspg_starttransfer_struct, 39	blight, 306
not done	blight_down, 306
Ispmac_motor_struct, 51	blight_f, 306
now	blight_ud, 306
kvredis.c, 84	blight_up, 306
lspg.c, 134	capy, 306
Ispmac.c, 208	capz, 306
number_passes	cenx, 306
md2StatusStruct, 64	ceny, 306

cryo, 307	lspg_waitcryo_t, 274
cryo_back, 307	lspg_zoom_lut_call, 284
cryo_switch, 307	Ispmac_SockSendDPline, 295
dryer, 307	Ispmac_SockSendline, 296
etel_init_ok, 307	Ispmac_abort, 284
etel_on, 307	lspmac_bi_t, 274
etel_ready, 307	Ispmac_getBIPosition, 284
flight, 307	Ispmac_getPosition, 285
flight_f, 307	lspmac_home1_queue, 285
flight_oo, 308	Ispmac_init, 286
fluo, 308	lspmac_jogabs_queue, 289
fluor_back, 308	Ispmac_motor_t, 274
fscint, 308	Ispmac_motors, 309
fshut, 308	lspmac_move_or_jog_abs_queue, 289
hp_air, 308	lspmac_move_or_jog_preset_queue, 292
kappa, 308	lspmac_move_or_jog_queue, 292
lp_air, 308	lspmac_move_preset_queue, 292
lsevents_add_listener, 275	lspmac_moveabs_queue, 293
Isevents_init, 275	Ispmac_moveabs_wait, 293
Isevents_remove_listener, 276	Ispmac_moving_cond, 309
Isevents_run, 276	lspmac_moving_flags, 309
Isevents_send_event, 276	Ispmac_moving_mutex, 310
Islogging_init, 277	Ispmac_nmotors, 310
Islogging_log_message, 277	lspmac_run, 294
Islogging_run, 278	Ispmac_shutter_cond, 310
lspg_array2ptrs, 278	Ispmac_shutter_has_opened, 310
lspg_demandairrights, 308	Ispmac_shutter_mutex, 310
lspg_demandairrights_all, 279	Ispmac_shutter_state, 310
lspg_demandairrights_t, 274	Ispmac_video_rotate, 296
lspg_getcenter, 309	Isredis_cmpnstr, 297
lspg_getcenter_call, 280	Isredis_cmpstr, 297
lspg_getcenter_done, 280	Isredis_find_preset, 297
lspg_getcenter_t, 274	Isredis_get_obj, 298
lspg_getcenter_wait, 280	Isredis_get_string_array, 298
lspg_getcurrentsampleid, 309	Isredis_getb, 299
lspg_getcurrentsampleid_t, 274	Isredis_getd, 299
lspg_getcurrentsampleid_wait_for_id, 280	Isredis_getl, 299
lspg_init, 280	Isredis_getstr, 299
lspg_nextsample, 309	Isredis_init, 300
lspg_nextsample_all, 281	lsredis_obj_t, 274
lspg_nextsample_t, 274	Isredis_regexec, 301
lspg_nextshot, 309	Isredis_run, 301
lspg_nextshot_call, 281	Isredis_setstr, 301
lspg_nextshot_done, 281	Istimer_add_timer, 302
lspg_nextshot_t, 274	Istimer_init, 303
lspg_nextshot_wait, 282	Istimer_run, 303
lspg_query_push, 282	Isupdate_init, 303
lspg_query_queue_t, 274	Isupdate_run, 304
lspg_run, 282	MD2CMDS_CMD_LENGTH, 273
lspg_seq_run_prep_all, 283	md2_status_mutex, 310
lspg_starttransfer, 309	md2cmds_cmd, 310
lspg_starttransfer_call, 283	md2cmds_cond, 310
lspg_starttransfer_done, 283	md2cmds_init, 304
lspg_starttransfer_t, 274	md2cmds_md_status_code, 311
lspg_starttransfer_wait, 283	md2cmds_mutex, 311
lspg_waitcryo, 309	md2cmds_pg_cond, 311
lspg_waitcryo_all, 284	md2cmds_pg_mutex, 311
lspg_waitcryo_cb, 284	md2cmds_run, 304

minikappa_ok, 311		pgpmac.h, 305
ncurses_mutex, 311		pmacfd
omega, 311		Ispmac.c, 209
omega_zero_time, 31	1	pos_limit_hit
pgpmac_printf, 304		lspmac_motor_struct, 51
phi, 311		position
pmac_cmd_queue_t,	274	lspmac_bi_struct, 44
pmac_cmd_t, 275		lspmac_motor_struct, 51
pmac queue cond, 3	11	ppos
pmac_queue_mutex,		mk pgpmac redis, 13
PmacSockSendline, 3		pq
sample_detected, 312		lspmac_motor_struct, 51
scint, 312	•	precision
,		lspmac_motor_struct, 51
shutter_open, 312		pref_ini
smart_mag_err, 312		mk_pgpmac_redis, 13
smart_mag_off, 312		
smart_mag_on, 312		previous
smart_mag_oo, 312		lspmac_bi_struct, 44
term_input, 312		printf_fmt
term_output, 312		lspmac_motor_struct, 51
term_status, 313		ptr
term_status2, 313		lspmac_bi_struct, 44
zoom, 313		
pgpmac_printf		q
pgpmac.c, 263		kvredis.c, 84
pgpmac.h, 304		lspg.c, 134
phi		qs
•		lspgQueryQueueStruct, 41
Ispmac.c, 208		
pgpmac.h, 311		raw_regexp
phi_act_pos		lsevents_listener_struct, 18
md2StatusStruct, 64		re
phi_status_1		Isevents_listener_struct, 18
md2StatusStruct, 64		read
phi_status_2		iniParser::iniParser, 16
md2StatusStruct, 65		lspmac_motor_struct, 51
phiscan		read_mask
md2StatusStruct, 65		Ispmac_motor_struct, 51
pi		read ptr
mk_pgpmac_redis, 13	3	Ispmac motor struct, 52
pl		redis fmt
Ispmac_dpascii_queu	e struct 45	_
pmac_cmd_queue_t	<u> </u>	Ispmac_motor_struct, 52
pgpmac.h, 274		redis_position
		lspmac_motor_struct, 52
pmac_cmd_size		redisDisconnectCB
Ispmac.c, 145		kvredis.c, 83
pmac_cmd_t		Isredis.c, 227
pgpmac.h, 275		reported_position
pmac_error_strs		lspmac_motor_struct, 52
Ispmac.c, 208		Request
pmac_queue_cond		tagEthernetCmd, 66
Ispmac.c, 209		RequestType
pgpmac.h, 311		tagEthernetCmd, 66
pmac_queue_mutex		requested_pos_cnts
Ispmac.c, 209		Ispmac_motor_struct, 52
pgpmac.h, 311		requested_position
pmac_thread		Ispmac_motor_struct, 52
•		• — —
Ispmac.c, 209		response_buf
PmacSockSendline		lspmac_ascii_buffers_struct, 42

response_n	smart_mag_off
lspmac_ascii_buffers_struct, 42	Ispmac.c, 210
response_str	pgpmac.h, 312
lspmac_ascii_buffers_struct, 42	smart_mag_on
roac	lspmac.c, 210
Isredis.c, 228	pgpmac.h, 312
rofd	smart_mag_oo
Isredis.c, 228	Ispmac.c, 210
rotating	pgpmac.h, 312
md2cmds.c, 259	sstart
rr cmd	lspg_nextshot_struct, 37
Ispmac.c, 209	sstart2
running	<pre>lspg_nextshot_struct, 37</pre>
pgpmac.c, 264	sstart2_isnull
pgp	lspg_nextshot_struct, 37
sample_detected	sstart_isnull
Ispmac.c, 209	lspg_nextshot_struct, 37
pgpmac.h, 312	starttransfer
scint	
Ispmac.c, 209	lspg_starttransfer_struct, 39
pgpmac.h, 312	status1
scint_act_pos	Ispmac_motor_struct, 52
md2StatusStruct, 65	status1_p
	Ispmac_motor_struct, 52
scint_piezo	status2
md2StatusStruct, 65	lspmac_motor_struct, 52
scint_status_1	status2_p
md2StatusStruct, 65	lspmac_motor_struct, 53
scint_status_2	status_str
md2StatusStruct, 65	lspmac_motor_struct, 53
sd	stdinService
iniParser::iniParser, 17	pgpmac.c, 263
sections	stdinfda
iniParser::iniParser, 17	pgpmac.c, 265
service_timers	stype
Istimer.c, 233	lspg_nextshot_struct, 37
sfn	stype2
lspg_nextshot_struct, 36	lspg_nextshot_struct, 37
sfn_isnull	stype2_isnull
lspg_nextshot_struct, 36	lspg_nextshot_struct, 37
shots	stype_isnull
Istimer_list_struct, 58	
shutter_open	lspg_nextshot_struct, 37
Ispmac.c, 210	subac
pgpmac.h, 312	kvredis.c, 85
sindex	Isredis.c, 228
	subfd
lspg_nextshot_struct, 36 sindex2	kvredis.c, 85
	Isredis.c, 228
lspg_nextshot_struct, 36	togEthornotCard CE
sindex2_isnull	tagEthernetCmd, 65
lspg_nextshot_struct, 36	bData, 66
sindex_isnull	Request, 66
lspg_nextshot_struct, 36	RequestType, 66
skey	wIndex, 66
lspg_nextshot_struct, 36	wLength, 66
skey_isnull	wValue, 66
lspg_nextshot_struct, 36	term_input
smart_mag_err	pgpmac.c, 265
Ispmac.c, 210	pgpmac.h, 312
pgpmac.h, 312	term_output
	·

pgpmac.c, 265	lsredis_obj_struct, 55
pgpmac.h, 312	value
term_status	Isredis_obj_struct, 56
pgpmac.c, 265	value_length
pgpmac.h, 313	Isredis_obj_struct, 56
term_status2	– ,–
pgpmac.c, 265	wIndex
pgpmac.h, 313	tagEthernetCmd, 66
time_sent	wLength
Ispmac_cmd_queue_struct, 45	tagEthernetCmd, 66
ispinac_cina_queue_struct, 45	wValue
u2c	tagEthernetCmd, 66
Ispmac_motor_struct, 53	wait_for_me
unit	Isredis_obj_struct, 56
lspmac_motor_struct, 53	win
update_resolution	lspmac_motor_struct, 53
Ispmac_motor_struct, 53	wrac
	Isredis.c, 228
V	wrfd
mk_pgpmac_redis, 13	Isredis.c, 228
VR_CTRL_RESPONSE	write_fmt
Ispmac.c, 145	<pre>lspmac_motor_struct, 53</pre>
VR_DOWNLOAD	, – –
Ispmac.c, 145	X
VR FWDOWNLOAD	mk_pgpmac_redis, 13
Ispmac.c, 145	
VR IPADDRESS	у
Ispmac.c, 145	mk_pgpmac_redis, 13
VR_PMAC_FLUSH	_ 51 7
Ispmac.c, 145	zoom
•	lspg_getcenter_struct, 23
VR_PMAC_GETBUFFER	Ispmac.c, 210
Ispmac.c, 146	pgpmac.h, 313
VR_PMAC_GETLINE	zoom_act_pos
Ispmac.c, 146	md2StatusStruct, 65
VR_PMAC_GETMEM	zoom isnull
Ispmac.c, 146	
VR_PMAC_GETRESPONSE	lspg_getcenter_struct, 23
Ispmac.c, 146	zoom_settings
VR_PMAC_PORT	mk_pgpmac_redis, 13
Ispmac.c, 146	zoom_status_1
VR PMAC READREADY	md2StatusStruct, 65
Ispmac.c, 146	zoom_status_2
VR_PMAC_SENDCTRLCHAR	md2StatusStruct, 65
Ispmac.c, 146	
VR_PMAC_SENDLINE	
Ispmac.c, 146	
•	
VR_PMAC_SETBIT	
Ispmac.c, 146	
VR_PMAC_SETBITS	
Ispmac.c, 146	
VR_PMAC_SETMEM	
Ispmac.c, 146	
VR_PMAC_WRITEBUFFER	
Ispmac.c, 146	
VR_PMAC_WRITEERROR	
Ispmac.c, 147	
VR_UPLOAD	
Ispmac.c, 147	
valid	