LS-CAT PGPMAC

Generated by Doxygen 1.8.2

Thu Feb 7 2013 10:09:49

Contents

1	The	The LS-CAT pgpmac Project					
2	Nam	nespace	Index		5		
	2.1	Names	pace List		5		
3	Data	Structi	ıre Index		7		
	3.1	Data S	tructures		7		
4	File	Index			9		
	4.1	File Lis	st		9		
5	Nam	espace	Documer	ntation	11		
	5.1	iniPars	er Names	pace Reference	11		
		5.1.1	Variable I	Documentation	11		
			5.1.1.1	$ip \ldots \ldots \ldots \ldots \ldots$	11		
	5.2	mk_pg	pmac_redi	s Namespace Reference	11		
		5.2.1	Function	Documentation	12		
			5.2.1.1	active_simulation	12		
			5.2.1.2	asis	12		
		5.2.2	Variable l	Documentation	12		
			5.2.2.1	b	12		
			5.2.2.2	bi_list	12		
			5.2.2.3	f	12		
			5.2.2.4	fnc	12		
			5.2.2.5	hard_ini	13		
			5.2.2.6	hard_ini_fields	13		
			5.2.2.7	head	13		
			5.2.2.8	hi	13		
			5.2.2.9	1	13		
			5.2.2.10	motor_dict	13		
			5.2.2.11	motor_field_lists	13		
			5.2.2.12	motor_presets	13		
			52213	n	13		

ii CONTENTS

			5.2.2.14 pi	13
			5.2.2.15 ppos	14
			5.2.2.16 pref_ini	14
			5.2.2.17 v	14
			5.2.2.18 x	14
			5.2.2.19 xlate	14
			5.2.2.20 y	14
			5.2.2.21 zoom_settings	14
6	Data	Structi	ire Documentation	15
	6.1	iniPars	er.iniParser Class Reference	15
		6.1.1	Detailed Description	15
		6.1.2	Constructor & Destructor Documentation	16
			6.1.2.1init	16
		6.1.3	Member Function Documentation	16
			6.1.3.1 get	16
			6.1.3.2 has_option	16
			6.1.3.3 has_section	16
			6.1.3.4 options	16
			6.1.3.5 read	17
			6.1.3.6 sections	17
		6.1.4	Field Documentation	17
			6.1.4.1 f	17
			6.1.4.2 sd	17
	6.2	Isevent	s_listener_struct Struct Reference	17
		6.2.1	Detailed Description	18
		6.2.2	Field Documentation	18
			6.2.2.1 cb	18
			6.2.2.2 next	18
			6.2.2.3 raw_regexp	18
			6.2.2.4 re	18
	6.3	Isevent	s_queue_struct Struct Reference	18
		6.3.1	Detailed Description	19
		6.3.2	Field Documentation	19
			6.3.2.1 evp	19
	6.4	Isloggii	g_queue_struct Struct Reference	19
		6.4.1	Detailed Description	19
		6.4.2	Field Documentation	19
			6.4.2.1 lmsg	19
			6.4.2.2 Itime	20

CONTENTS

6.5	lspg_d	emandairr	ights_struct Struct Reference	20
	6.5.1	Detailed	Description	20
	6.5.2	Field Doo	cumentation	20
		6.5.2.1	cond	20
		6.5.2.2	mutex	20
		6.5.2.3	new_value_ready	20
6.6	lspg_g	etcenter_s	struct Struct Reference	20
	6.6.1	Detailed	Description	21
	6.6.2	Field Doo	cumentation	21
		6.6.2.1	cond	21
		6.6.2.2	dax	21
		6.6.2.3	dax_isnull	21
		6.6.2.4	day	22
		6.6.2.5	day_isnull	22
		6.6.2.6	daz	22
		6.6.2.7	daz_isnull	22
		6.6.2.8	dcx	22
		6.6.2.9	dcx_isnull	22
		6.6.2.10	dcy	22
		6.6.2.11	dcy_isnull	22
		6.6.2.12	mutex	22
		6.6.2.13	new_value_ready	22
		6.6.2.14	no_rows_returned	23
		6.6.2.15	zoom	23
		6.6.2.16	zoom_isnull	23
6.7	lspg_g	etcurrents	ampleid_struct Struct Reference	23
	6.7.1	Detailed	Description	23
	6.7.2	Field Doo	cumentation	23
		6.7.2.1	cond	23
		6.7.2.2	getcurrentsampleid	24
		6.7.2.3	getcurrentsampleid_isnull	24
		6.7.2.4	mutex	24
		6.7.2.5	new_value_ready	24
		6.7.2.6	no_rows_returned	24
6.8	lspg_lc	ock_detect	or_struct Struct Reference	24
	6.8.1	Detailed	Description	24
	6.8.2	Field Doo	cumentation	24
		6.8.2.1	cond	24
		6.8.2.2	mutex	25
		6.8.2.3	new_value_ready	25

iv CONTENTS

6.9	lspg_lo	ck_diffract	tometer_struct Struct Reference	25
	6.9.1	Detailed	Description	25
	6.9.2	Field Doo	cumentation	25
		6.9.2.1	cond	25
		6.9.2.2	mutex	25
		6.9.2.3	new_value_ready	25
6.10	lspg_ne	extsample _.	_struct Struct Reference	25
	6.10.1	Detailed	Description	26
	6.10.2	Field Doo	cumentation	26
		6.10.2.1	cond	26
		6.10.2.2	mutex	26
		6.10.2.3	new_value_ready	26
		6.10.2.4	nextsample	26
		6.10.2.5	nextsample_isnull	26
		6.10.2.6	no_rows_returned	27
6.11	lspg_ne	extshot_st	ruct Struct Reference	27
	6.11.1	Detailed	Description	29
	6.11.2	Field Doo	cumentation	29
		6.11.2.1	active	29
		6.11.2.2	active2	30
		6.11.2.3	active2_isnull	30
		6.11.2.4	active_isnull	30
		6.11.2.5	ax	30
		6.11.2.6	ax2	30
		6.11.2.7	ax2_isnull	30
		6.11.2.8	ax_isnull	30
		6.11.2.9	ay	30
		6.11.2.10) ay2	30
		6.11.2.11	ay2_isnull	30
		6.11.2.12	2 ay_isnull	30
		6.11.2.13	Baz	31
		6.11.2.14	4 az2	31
		6.11.2.15	5 az2_isnull	31
		6.11.2.16	az_isnull	31
		6.11.2.17	7 cond	31
		6.11.2.18	3 cx	31
		6.11.2.19	9 cx2	31
		6.11.2.20	cx2_isnull	31
		6.11.2.21	cx_isnull	31
		6.11.2.22	² cy	31

CONTENTS

6.11.2.23 cy2
6.11.2.24 cy2_isnull
6.11.2.25 cy_isnull
6.11.2.26 dsdir
6.11.2.27 dsdir_isnull
6.11.2.28 dsdist
6.11.2.29 dsdist2
6.11.2.30 dsdist2_isnull
6.11.2.31 dsdist_isnull
6.11.2.32 dsexp
6.11.2.33 dsexp2
6.11.2.34 dsexp2_isnull
6.11.2.35 dsexp_isnull
6.11.2.36 dshpid
6.11.2.37 dshpid_isnull
6.11.2.38 dskappa
6.11.2.39 dskappa2
6.11.2.40 dskappa2_isnull
6.11.2.41 dskappa_isnull
6.11.2.42 dsnrg
6.11.2.43 dsnrg2
6.11.2.44 dsnrg2_isnull
6.11.2.45 dsnrg_isnull
6.11.2.46 dsomega
6.11.2.47 dsomega2
6.11.2.48 dsomega2_isnull
6.11.2.49 dsomega_isnull
6.11.2.50 dsoscaxis
6.11.2.51 dsoscaxis2
6.11.2.52 dsoscaxis2_isnull
6.11.2.53 dsoscaxis_isnull
6.11.2.54 dsowidth
6.11.2.55 dsowidth2
6.11.2.56 dsowidth2_isnull
6.11.2.57 dsowidth_isnull
6.11.2.58 dsphi
6.11.2.59 dsphi2
6.11.2.60 dsphi2_isnull
6.11.2.61 dsphi_isnull
6.11.2.62 dspid

vi CONTENTS

		6.11.2.63	B dspid_isnull	35
		6.11.2.64	I mutex	36
		6.11.2.65	new_value_ready	36
		6.11.2.66	no_rows_returned	36
		6.11.2.67	⁷ sfn	36
		6.11.2.68	3 sfn_isnull	36
		6.11.2.69	sindex	36
		6.11.2.70) sindex2	36
		6.11.2.71	sindex2_isnull	36
		6.11.2.72	2 sindex_isnull	36
		6.11.2.73	Biskey	36
		6.11.2.74	skey_isnull	37
		6.11.2.75	sstart	37
		6.11.2.76	S sstart2	37
		6.11.2.77	sstart2_isnull	37
		6.11.2.78	B sstart_isnull	37
		6.11.2.79	9 stype	37
		6.11.2.80	stype2	37
		6.11.2.81	stype2_isnull	37
		6.11.2.82	2 stype_isnull	37
6.12	lspg_se	eq_run_pro	ep_struct Struct Reference	37
	6.12.1	Detailed	Description	38
	6.12.2	Field Doo	cumentation	38
		6.12.2.1	cond	38
		6.12.2.2	mutex	38
		6.12.2.3	new_value_ready	38
6.13			r_struct Struct Reference	38
	6.13.1	Detailed	Description	39
	6.13.2	Field Doo	cumentation	39
		6.13.2.1	cond	39
		6.13.2.2	mutex	39
		6.13.2.3	new_value_ready	39
		6.13.2.4	no_rows_returned	39
		6.13.2.5	starttransfer	39
6.14			tector_struct Struct Reference	39
			Description	40
	6.14.2		cumentation	40
			cond	40
		6.14.2.2	mutex	40
		6.14.2.3	new_value_ready	40

CONTENTS vii

6.15	lspg_w	aitcryo_str	ruct Struct Reference	40
	6.15.1	Detailed I	Description	40
	6.15.2	Field Doo	cumentation	40
		6.15.2.1	cond	40
		6.15.2.2	mutex	41
		6.15.2.3	new_value_ready	41
6.16	IspgQu	eryQueue	Struct Struct Reference	41
	6.16.1	Detailed I	Description	41
	6.16.2	Field Doo	cumentation	41
		6.16.2.1	onResponse	41
		6.16.2.2	qs	41
6.17	Ispmac	_ascii_buf	fers_struct Struct Reference	42
	6.17.1	Detailed I	Description	42
	6.17.2	Field Doo	cumentation	42
		6.17.2.1	command_buf	42
		6.17.2.2	command_buf_cc	42
		6.17.2.3	command_str	42
		6.17.2.4	response_buf	42
		6.17.2.5	response_n	42
		6.17.2.6	response_str	42
6.18	Ispmac	_bi_struct	Struct Reference	42
	6.18.1	Detailed I	Description	43
	6.18.2	Field Doo	cumentation	43
		6.18.2.1	changeEventOff	43
			changeEventOn	43
		6.18.2.3	first_time	43
		6.18.2.4	mask	43
		6.18.2.5	mutex	44
		6.18.2.6	position	44
		6.18.2.7	previous	44
		6.18.2.8	ptr	44
6.19	Ispmac	_cmd_que	eue_struct Struct Reference	44
	6.19.1	Detailed I	Description	44
	6.19.2	Field Doo	cumentation	45
		6.19.2.1	event	45
		6.19.2.2	no_reply	45
		6.19.2.3	onResponse	45
		6.19.2.4	pcmd	45
		6.19.2.5	time_sent	45
6.20	Ispmac	_combined	d_move_struct Struct Reference	45

viii CONTENTS

	6.20.1	Detailed Description	15
	6.20.2	Field Documentation	15
		6.20.2.1 axis	1 5
		6.20.2.2 coord_num	16
		6.20.2.3 Delta	16
		6.20.2.4 moveme	16
6.21	Ispmac	_dpascii_queue_struct Struct Reference	1 6
	6.21.1	Detailed Description	16
	6.21.2	Field Documentation	l 6
		6.21.2.1 event	16
		6.21.2.2 pl	16
6.22	Ispmac	_motor_struct Struct Reference	16
	6.22.1	Detailed Description	19
	6.22.2	Field Documentation	19
		6.22.2.1 active	19
		6.22.2.2 active_init	19
		6.22.2.3 actual_pos_cnts	19
		6.22.2.4 actual_pos_cnts_p	19
		6.22.2.5 axis	19
		6.22.2.6 command_sent	19
		6.22.2.7 cond	19
		6.22.2.8 coord_num	19
		6.22.2.9 dac_mvar	50
		6.22.2.10 home	50
		6.22.2.11 homing	50
		6.22.2.12 in_position_band	50
		6.22.2.13 inactive_init	50
		6.22.2.14 jogAbs	50
		6.22.2.15 lut	50
		6.22.2.16 max_accel	50
		6.22.2.17 max_pos	50
		6.22.2.18 max_speed	51
		6.22.2.19 min_pos	51
		6.22.2.20 motion_seen	51
		6.22.2.21 motor_num	51
		6.22.2.22 moveAbs	51
		6.22.2.23 mutex	51
		6.22.2.24 name	51
		6.22.2.25 neg_limit_hit	51
		6.22.2.26 neutral_pos	51

CONTENTS

		6.22.2.27 nlut	52
		6.22.2.28 not_done	52
		6.22.2.29 pos_limit_hit	52
		6.22.2.30 position	52
		6.22.2.31 pq	52
		6.22.2.32 precision	52
		6.22.2.33 printf_fmt	52
		6.22.2.34 read	52
		6.22.2.35 read_mask	52
		6.22.2.36 read_ptr	53
		6.22.2.37 redis_fmt	53
		6.22.2.38 redis_position	53
		6.22.2.39 reported_pg_position	53
		6.22.2.40 reported_position	53
		6.22.2.41 requested_pos_cnts	53
		6.22.2.42 requested_position	53
		6.22.2.43 status1	53
		6.22.2.44 status1_p	53
		6.22.2.45 status2	54
		6.22.2.46 status2_p	54
		6.22.2.47 status_str	54
		6.22.2.48 u2c	54
		6.22.2.49 unit	54
		6.22.2.50 update_resolution	54
		6.22.2.51 win	54
		6.22.2.52 write_fmt	54
6.23	Isredis_	_obj_struct Struct Reference	54
	6.23.1	Detailed Description	55
	6.23.2	Field Documentation	55
		6.23.2.1 avalue	55
		6.23.2.2 bvalue	55
		6.23.2.3 cond	56
		6.23.2.4 cvalue	56
		6.23.2.5 dvalue	56
		6.23.2.6 events_name	56
		6.23.2.7 hits	56
		6.23.2.8 key	56
		6.23.2.9 Ivalue	56
		6.23.2.10 mutex	56
		6.23.2.11 next	56

X CONTENTS

	6.23.2.12 valid	57
	6.23.2.13 value	57
	6.23.2.14 value_length	57
	6.23.2.15 wait_for_me	57
6.24 Istim	er_list_struct Struct Reference	57
6.24	.1 Detailed Description	58
6.24	.2 Field Documentation	58
	6.24.2.1 delay_nsecs	58
	6.24.2.2 delay_secs	58
	6.24.2.3 event	58
	6.24.2.4 init_nsecs	58
	6.24.2.5 init_secs	58
	6.24.2.6 last_nsecs	58
	6.24.2.7 last_secs	58
	6.24.2.8 ncalls	59
	6.24.2.9 next_nsecs	59
	6.24.2.10 next_secs	59
	6.24.2.11 shots	59
6.25 md2	cmds_cmd_kv_struct Struct Reference	59
6.25	.1 Detailed Description	59
6.25	.2 Field Documentation	59
	6.25.2.1 k	59
	6.25.2.2 v	59
6.26 md2	StatusStruct Struct Reference	60
6.26	.1 Detailed Description	31
6.26	.2 Field Documentation	31
	6.26.2.1 acc11c_1	31
	6.26.2.2 acc11c_2	31
	6.26.2.3 acc11c_3	31
	6.26.2.4 acc11c_5	31
	6.26.2.5 acc11c_6	31
	6.26.2.6 alignx_act_pos	32
	6.26.2.7 alignx_status_1	32
	6.26.2.8 alignx_status_2	62
	6.26.2.9 aligny_act_pos	32
	6.26.2.10 aligny_status_1	32
	6.26.2.11 aligny_status_2	62
	6.26.2.12 alignz_act_pos	62
	6.26.2.13 alignz_status_1	62
	6.26.2.14 alignz_status_2	32

CONTENTS xi

6.26.2.15 analyzer_act_pos
6.26.2.16 analyzer_status_1
6.26.2.17 analyzer_status_2
6.26.2.18 aperturey_act_pos
6.26.2.19 aperturey_status_1
6.26.2.20 aperturey_status_2
6.26.2.21 aperturez_act_pos
6.26.2.22 aperturez_status_1
6.26.2.23 aperturez_status_2
6.26.2.24 back_dac
6.26.2.25 capy_act_pos
6.26.2.26 capy_status_1
6.26.2.27 capy_status_2
6.26.2.28 capz_act_pos
6.26.2.29 capz_status_1
6.26.2.30 capz_status_2
6.26.2.31 centerx_act_pos
6.26.2.32 centerx_status_1
6.26.2.33 centerx_status_2
6.26.2.34 centery_act_pos
6.26.2.35 centery_status_1
6.26.2.36 centery_status_2
6.26.2.37 dummy1
6.26.2.38 dummy2
6.26.2.39 dummy3
6.26.2.40 dummy4
6.26.2.41 dummy5
6.26.2.42 dummy6
6.26.2.43 dummy7
6.26.2.44 dummy8
6.26.2.45 dummy9
6.26.2.46 dummyA
6.26.2.47 dummyB
6.26.2.48 front_dac
6.26.2.49 fs_has_opened
6.26.2.50 fs_has_opened_globally
6.26.2.51 fs_is_open
6.26.2.52 kappa_act_pos
6.26.2.53 kappa_status_1
6.26.2.54 kappa_status_2

xii CONTENTS

			6.26.2.55 moving_flags	6
			6.26.2.56 number_passes	6
			6.26.2.57 omega_act_pos	6
			6.26.2.58 omega_status_1	6
			6.26.2.59 omega_status_2	6
			6.26.2.60 phi_act_pos	6
			6.26.2.61 phi_status_1	6
			6.26.2.62 phi_status_2	6
			6.26.2.63 phiscan	6
			6.26.2.64 scint_act_pos	6
			6.26.2.65 scint_piezo	6
			6.26.2.66 scint_status_1	7
			6.26.2.67 scint_status_2	7
			6.26.2.68 zoom_act_pos	7
			6.26.2.69 zoom_status_1	7
			6.26.2.70 zoom_status_2	7
	6.27	tagEthe	ernetCmd Struct Reference	7
		6.27.1	Detailed Description	7
		6.27.2	Field Documentation	8
			6.27.2.1 bData	8
			6.27.2.2 Request	8
			6.27.2.3 RequestType	8
			6.27.2.4 windex	8
			6.27.2.5 wLength	8
			6.27.2.6 wValue	8
7	File	Docume	entation 69	9
	7.1		er.py File Reference	
	7.2		s.c File Reference	
		7.2.1	Detailed Description	0
		7.2.2	Macro Definition Documentation	1
			7.2.2.1 LSEVENTS_QUEUE_LENGTH	1
		7.2.3	Typedef Documentation	1
			7.2.3.1	1
			7.2.3.2	1
		7.2.4	Function Documentation	1
			7.2.4.1	1
			7.2.4.2	2
			7.2.4.3	2
			7.2.4.4	3

CONTENTS xiii

		7.2.4.5	lsevents_send_event
		7.2.4.6	lsevents_worker
	7.2.5	Variable	Documentation
		7.2.5.1	lsevents_listener_mutex
		7.2.5.2	lsevents_listeners_p
		7.2.5.3	lsevents_queue
		7.2.5.4	lsevents_queue_cond
		7.2.5.5	lsevents_queue_mutex
		7.2.5.6	Isevents_queue_off
		7.2.5.7	lsevents_queue_on
		7.2.5.8	lsevents_thread
7.3	Isloggii	ng.c File F	Reference
	7.3.1	Detailed	Description
	7.3.2	Macro D	efinition Documentation
		7.3.2.1	LSLOGGING_FILE_NAME
		7.3.2.2	LSLOGGING_MSG_LENGTH
		7.3.2.3	LSLOGGING_QUEUE_LENGTH
	7.3.3	Typedef	Documentation
		7.3.3.1	Islogging_queue_t
	7.3.4	Function	Documentation
		7.3.4.1	Islogging_event_cb
		7.3.4.2	Islogging_init
		7.3.4.3	Islogging_log_message
		7.3.4.4	Islogging_run
		7.3.4.5	Islogging_worker
	7.3.5	Variable	Documentation
		7.3.5.1	Islogging_cond
		7.3.5.2	Islogging_file
		7.3.5.3	Islogging_mutex
		7.3.5.4	Islogging_off
		7.3.5.5	Islogging_on
		7.3.5.6	Islogging_queue
		7.3.5.7	Islogging_thread
7.4	lspg.c	File Refere	ence
	7.4.1	Detailed	Description
	7.4.2	Macro D	efinition Documentation
		7.4.2.1	LS_PG_QUERY_QUEUE_LENGTH 85
		7.4.2.2	LS_PG_STATE_IDLE
		7.4.2.3	LS_PG_STATE_INIT 85
		7.4.2.4	LS_PG_STATE_INIT_POLL

XIV

	7.4.2.5	LS_PG_STATE_RECV	85
	7.4.2.6	LS_PG_STATE_RESET	86
	7.4.2.7	LS_PG_STATE_RESET_POLL	86
	7.4.2.8	LS_PG_STATE_SEND	86
	7.4.2.9	LS_PG_STATE_SEND_FLUSH	86
7.4.3	Typedef I	Documentation	86
	7.4.3.1	lspg_lock_detector_t	86
	7.4.3.2	lspg_lock_diffractometer_t	86
	7.4.3.3	lspg_seq_run_prep_t	86
	7.4.3.4	lspg_wait_for_detector_t	86
7.4.4	Function	Documentation	86
	7.4.4.1	lspg_allkvs_cb	86
	7.4.4.2	lspg_array2ptrs	87
	7.4.4.3	lspg_check_preset_in_position_cb	88
	7.4.4.4	lspg_cmd_cb	89
	7.4.4.5	lspg_demandairrights_all	89
	7.4.4.6	lspg_demandairrights_call	90
	7.4.4.7	lspg_demandairrights_cb	90
	7.4.4.8	lspg_demandairrights_init	90
	7.4.4.9	lspg_demandairrights_wait	90
	7.4.4.10	lspg_flush	90
	7.4.4.11	lspg_getcenter_all	91
	7.4.4.12	lspg_getcenter_call	91
	7.4.4.13	lspg_getcenter_cb	91
	7.4.4.14	lspg_getcenter_done	92
	7.4.4.15	lspg_getcenter_init	92
	7.4.4.16	lspg_getcenter_wait	93
	7.4.4.17	lspg_getcurrentsampleid_call	93
	7.4.4.18	lspg_getcurrentsampleid_cb	93
	7.4.4.19	lspg_getcurrentsampleid_init	93
	7.4.4.20	lspg_getcurrentsampleid_read	94
	7.4.4.21	lspg_getcurrentsampleid_wait_for_id	94
	7.4.4.22	lspg_init	94
	7.4.4.23	lspg_lock_detector_all	95
	7.4.4.24	lspg_lock_detector_call	95
	7.4.4.25	lspg_lock_detector_cb	95
	7.4.4.26	lspg_lock_detector_done	95
	7.4.4.27	lspg_lock_detector_init	95
	7.4.4.28	lspg_lock_detector_wait	96
	7.4.4.29	lspg_lock_diffractometer_all	96

CONTENTS xv

7.4.4.30	lspg_lock_diffractometer_call	96
7.4.4.31	lspg_lock_diffractometer_cb	96
7.4.4.32	lspg_lock_diffractometer_done	97
7.4.4.33	lspg_lock_diffractometer_init	97
7.4.4.34	lspg_lock_diffractometer_wait	97
7.4.4.35	lspg_next_state	97
7.4.4.36	lspg_nextaction_cb	98
7.4.4.37	lspg_nextsample_all	98
7.4.4.38	lspg_nextsample_call	99
7.4.4.39	lspg_nextsample_cb	99
7.4.4.40	lspg_nextsample_done	100
7.4.4.41	lspg_nextsample_init	100
7.4.4.42	lspg_nextsample_wait	100
7.4.4.43	lspg_nextshot_call	100
7.4.4.44	lspg_nextshot_cb	101
7.4.4.45	lspg_nextshot_done	104
7.4.4.46	lspg_nextshot_init	104
7.4.4.47	lspg_nextshot_wait	105
7.4.4.48	lspg_notice_processor	105
7.4.4.49	lspg_pg_connect	105
7.4.4.50	lspg_pg_service	106
7.4.4.51	lspg_preset_changed_cb	108
7.4.4.52	lspg_query_next	108
7.4.4.53	lspg_query_push	108
7.4.4.54	lspg_query_reply_next	109
7.4.4.55	lspg_query_reply_peek	109
7.4.4.56	lspg_receive	110
7.4.4.57	lspg_run	111
7.4.4.58	lspg_sample_detector_cb	111
7.4.4.59	lspg_send_next_query	111
7.4.4.60	lspg_seq_run_prep_all	112
7.4.4.61	lspg_seq_run_prep_call	112
7.4.4.62	lspg_seq_run_prep_cb	113
7.4.4.63	lspg_seq_run_prep_done	113
7.4.4.64	lspg_seq_run_prep_init	113
7.4.4.65	lspg_seq_run_prep_wait	113
7.4.4.66	lspg_set_scale_cb	114
7.4.4.67	lspg_sig_service	114
7.4.4.68	lspg_starttransfer_all	114
7.4.4.69	lspg_starttransfer_call	115

xvi CONTENTS

	7.4.4.70	lspg_starttransfer_cb	115
	7.4.4.71	lspg_starttransfer_done	115
	7.4.4.72	lspg_starttransfer_init	115
	7.4.4.73	lspg_starttransfer_wait	116
	7.4.4.74	lspg_unset_current_preset_moving_cb	116
	7.4.4.75	lspg_update_kvs_cb	116
	7.4.4.76	lspg_wait_for_detector_all	117
	7.4.4.77	lspg_wait_for_detector_call	117
	7.4.4.78	lspg_wait_for_detector_cb	117
	7.4.4.79	lspg_wait_for_detector_done	118
	7.4.4.80	lspg_wait_for_detector_init	118
	7.4.4.81	lspg_wait_for_detector_wait	118
	7.4.4.82	lspg_waitcryo_all	118
	7.4.4.83	lspg_waitcryo_cb	119
	7.4.4.84	lspg_waitcryo_init	119
	7.4.4.85	lspg_worker	119
7.4.5	Variable I	Documentation	120
	7.4.5.1	ls_pg_state	120
	7.4.5.2	lspg_connectPoll_response	120
	7.4.5.3	lspg_demandairrights	120
	7.4.5.4	lspg_getcenter	120
	7.4.5.5	lspg_getcurrentsampleid	120
	7.4.5.6	lspg_lock_detector	121
	7.4.5.7	lspg_lock_diffractometer	121
	7.4.5.8	lspg_nextsample	121
	7.4.5.9	lspg_nextshot	121
	7.4.5.10	lspg_query_queue	121
	7.4.5.11	lspg_query_queue_off	121
	7.4.5.12	lspg_query_queue_on	121
	7.4.5.13	lspg_query_queue_reply	121
	7.4.5.14	lspg_queue_cond	121
	7.4.5.15	lspg_queue_mutex	122
	7.4.5.16	lspg_resetPoll_response	122
	7.4.5.17	lspg_seq_run_prep	122
	7.4.5.18	lspg_starttransfer	122
	7.4.5.19	lspg_thread	122
	7.4.5.20	lspg_wait_for_detector	122
	7.4.5.21	lspg_waitcryo	122
	7.4.5.22	lspgfd	122
	7.4.5.23	now	122

CONTENTS xvii

		7.4.5.24	q	123
7.5	Ispmad	c.c File Ref	ference	123
	7.5.1	Detailed	Description	131
	7.5.2	Macro De	efinition Documentation	132
		7.5.2.1	LS_PMAC_STATE_CR	132
		7.5.2.2	LS_PMAC_STATE_DETACHED	132
		7.5.2.3	LS_PMAC_STATE_GB	132
		7.5.2.4	LS_PMAC_STATE_GMR	132
		7.5.2.5	LS_PMAC_STATE_IDLE	132
		7.5.2.6	LS_PMAC_STATE_RESET	132
		7.5.2.7	LS_PMAC_STATE_RR	133
		7.5.2.8	LS_PMAC_STATE_SC	133
		7.5.2.9	LS_PMAC_STATE_WACK	133
		7.5.2.10	LS_PMAC_STATE_WACK_CC	133
		7.5.2.11	LS_PMAC_STATE_WACK_NFR	133
		7.5.2.12	LS_PMAC_STATE_WACK_RR	133
		7.5.2.13	LS_PMAC_STATE_WCR	133
		7.5.2.14	LS_PMAC_STATE_WGB	133
		7.5.2.15	LSPMAC_DPASCII_QUEUE_LENGTH	133
		7.5.2.16	LSPMAC_MAX_MOTORS	133
		7.5.2.17	LSPMAC_PRESET_REGEX	133
		7.5.2.18	PMAC_CMD_QUEUE_LENGTH	133
		7.5.2.19	pmac_cmd_size	134
		7.5.2.20	PMAC_MIN_CMD_TIME	134
		7.5.2.21	PMACPORT	134
		7.5.2.22	VR_CTRL_RESPONSE	134
		7.5.2.23	VR_DOWNLOAD	134
		7.5.2.24	VR_FWDOWNLOAD	134
		7.5.2.25	VR_IPADDRESS	134
		7.5.2.26	VR_PMAC_FLUSH	134
		7.5.2.27	VR_PMAC_GETBUFFER	134
		7.5.2.28	VR_PMAC_GETLINE	134
		7.5.2.29	VR_PMAC_GETMEM	134
		7.5.2.30	VR_PMAC_GETRESPONSE	135
		7.5.2.31	VR_PMAC_PORT	135
		7.5.2.32	VR_PMAC_READREADY	135
		7.5.2.33	VR_PMAC_SENDCTRLCHAR	135
		7.5.2.34	VR_PMAC_SENDLINE	135
		7.5.2.35	VR_PMAC_SETBIT	135
		7.5.2.36	VR_PMAC_SETBITS	135

xviii CONTENTS

	7.5.2.37	VR_PMAC_SETMEM
	7.5.2.38	VR_PMAC_WRITEBUFFER
	7.5.2.39	VR_PMAC_WRITEERROR
	7.5.2.40	VR_UPLOAD
7.5.3	Typedef I	Documentation
	7.5.3.1	lspmac_ascii_buffers_t
	7.5.3.2	lspmac_combined_move_t
	7.5.3.3	lspmac_dpascii_queue_t
	7.5.3.4	md2_status_t
7.5.4	Function	Documentation
	7.5.4.1	_lspmac_motor_init
	7.5.4.2	cleanstr
	7.5.4.3	hex_dump
	7.5.4.4	IsConnect
	7.5.4.5	Ispmac_abort
	7.5.4.6	lspmac_asciicmdCB
	7.5.4.7	lspmac_backLight_down_cb
	7.5.4.8	lspmac_backLight_up_cb
	7.5.4.9	lspmac_bi_init
	7.5.4.10	lspmac_blight_lut_setup
	7.5.4.11	Ispmac_bo_init 140
	7.5.4.12	lspmac_bo_read
	7.5.4.13	lspmac_command_done_cb
	7.5.4.14	lspmac_cryoSwitchChanged_cb
	7.5.4.15	lspmac_dac_init
	7.5.4.16	
	7.5.4.17	Ispmac_Error
	7.5.4.18	lspmac_est_move_time
	7.5.4.19	lspmac_est_move_time_wait
	7.5.4.20	Ispmac_find_motor_by_name
	7.5.4.21	Ispmac_flight_lut_setup
	7.5.4.22	Ispmac_fscint_lut_setup
	7.5.4.23	Ispmac_fshut_init
	7.5.4.24	Ispmac_get_ascii
	7.5.4.25	Ispmac_get_ascii_cb
	7.5.4.26	Ispmac_get_status
	7.5.4.27	lspmac_get_status_cb
	7.5.4.28	Ispmac_GetAllIVars
	7.5.4.29	Ispmac_GetAllIVarsCB
	7.5.4.30	Ispmac_GetAllMVars

CONTENTS xix

Ispmac_GetAllMVarsCB
Ispmac_getBIPosition
lspmac_Getmem
Ispmac_GetmemReplyCB
Ispmac_getPosition
lspmac_GetShortReplyCB
lspmac_home1_queue
lspmac_home2_queue
lspmac_init
lspmac_jogabs_queue
lspmac_light_zoom_cb
lspmac_lut
lspmac_more_ascii_cb
Ispmac_motor_init
lspmac_move_or_jog_abs_queue
Ispmac_move_or_jog_preset_queue
Ispmac_move_preset_queue
lspmac_moveabs_blight_factor_queue
lspmac_moveabs_bo_queue
lspmac_moveabs_flight_factor_queue
lspmac_moveabs_frontlight_oo_queue
lspmac_moveabs_fshut_queue
lspmac_moveabs_queue
lspmac_moveabs_timed_queue
Ispmac_moveabs_wait
lspmac_movedac_queue
lspmac_movezoom_queue
lspmac_next_state
lspmac_pmacmotor_read
lspmac_pop_queue
lspmac_pop_reply
lspmac_push_queue
Ispmac_Reset
Ispmac_reset_queue
lspmac_rlut
lspmac_run
lspmac_scint_dried_cb
Ispmac_scint_inPosition_cb
lspmac_scint_maybe_move_sample_cb
lspmac_scint_maybe_return_sample_cb

CONTENTS

	7.5.4.71	lspmac_send_command	186
	7.5.4.72	lspmac_sendcmd	187
	7.5.4.73	lspmac_sendcmd_nocb	187
	7.5.4.74	lspmac_SendControlReplyPrintCB	187
	7.5.4.75	Ispmac_Service	188
	7.5.4.76	lspmac_shutter_read	190
	7.5.4.77	lspmac_SockFlush	191
	7.5.4.78	lspmac_SockGetmem	191
	7.5.4.79	Ispmac_SockSendControlCharPrint	191
	7.5.4.80	lspmac_SockSendDPControlChar	192
	7.5.4.81	lspmac_SockSendDPControlCharCB	192
	7.5.4.82	lspmac_SockSendDPline	192
	7.5.4.83	lspmac_SockSendDPqueue	192
	7.5.4.84	lspmac_SockSendline	193
	7.5.4.85	lspmac_SockSendline_nr	193
	7.5.4.86	lspmac_soft_motor_init	194
	7.5.4.87	lspmac_soft_motor_read	194
	7.5.4.88	lspmac_test_preset	194
	7.5.4.89	lspmac_video_rotate	194
	7.5.4.90	lspmac_worker	195
	7.5.4.91	lspmac_zoom_lut_setup	196
7.5.5	Variable I	Documentation	196
	7.5.5.1	alignx	196
	7.5.5.2	aligny	196
	7.5.5.3	alignz	196
	7.5.5.4	anal	197
	7.5.5.5	apery	197
	7.5.5.6	aperz	197
	7.5.5.7	arm_parked	197
	7.5.5.8	blight	197
	7.5.5.9	blight_down	197
	7.5.5.10	$blight_f \ . \ . \ . \ . \ . \ . \ . \ . \ . \ $	197
	7.5.5.11	blight_ud	197
	7.5.5.12	blight_up	197
	7.5.5.13	сару	198
	7.5.5.14	capz	198
	7.5.5.15	cenx	198
	7.5.5.16	ceny	198
	7.5.5.17	cr_cmd	198
	7.5.5.18	cryo	198

CONTENTS xxi

7.5.5.19	cryo_back
7.5.5.20	cryo_switch
7.5.5.21	dbmem
7.5.5.22	dbmemIn
7.5.5.23	dryer
7.5.5.24	etel_init_ok
7.5.5.25	etel_on
7.5.5.26	etel_ready
7.5.5.27	ethCmdOff
7.5.5.28	ethCmdOn
7.5.5.29	ethCmdQueue
7.5.5.30	ethCmdReply
7.5.5.31	flight
7.5.5.32	flight_f
7.5.5.33	flight_oo
7.5.5.34	fluo
7.5.5.35	fluor_back
7.5.5.36	fscint
7.5.5.37	fshut
7.5.5.38	gb_cmd
7.5.5.39	getivars
7.5.5.40	getmvars
7.5.5.41	hp_air
7.5.5.42	kappa
7.5.5.43	lp_air
7.5.5.44	ls_pmac_state
7.5.5.45	Ispmac_ascii_buffers
7.5.5.46	Ispmac_ascii_buffers_mutex
7.5.5.47	Ispmac_ascii_busy
7.5.5.48	Ispmac_ascii_mutex
7.5.5.49	lspmac_bis
7.5.5.50	lspmac_dpascii_off
7.5.5.51	lspmac_dpascii_on
7.5.5.52	Ispmac_dpascii_queue
7.5.5.53	lspmac_motors
7.5.5.54	lspmac_moving_cond
7.5.5.55	lspmac_moving_flags
7.5.5.56	Ispmac_moving_mutex
7.5.5.57	Ispmac_nbis
7.5.5.58	lspmac_nmotors

xxii CONTENTS

		7.5.5.59	lspmac_shutter_cond)2
		7.5.5.60	lspmac_shutter_has_opened)3
		7.5.5.61	lspmac_shutter_mutex)3
		7.5.5.62	lspmac_shutter_state	23
		7.5.5.63	lspmac_status_last_time	23
		7.5.5.64	lspmac_status_time)3
		7.5.5.65	md2_status	23
		7.5.5.66	md2_status_mutex)3
		7.5.5.67	minikappa_ok	23
		7.5.5.68	motors_ht	23
		7.5.5.69	now)4
		7.5.5.70	omega)4
		7.5.5.71	omega_zero_search)4
		7.5.5.72	omega_zero_time)4
		7.5.5.73	omega_zero_velocity)4
		7.5.5.74	phi)4
		7.5.5.75	pmac_error_strs)4
		7.5.5.76	pmac_queue_cond)5
		7.5.5.77	pmac_queue_mutex)5
		7.5.5.78	pmac_thread)5
		7.5.5.79	pmacfd)5
		7.5.5.80	rr_cmd)5
		7.5.5.81	sample_detected)5
		7.5.5.82	scint)5
		7.5.5.83	shutter_open)5
		7.5.5.84	smart_mag_err	05
		7.5.5.85	smart_mag_off	06
		7.5.5.86	smart_mag_on	06
		7.5.5.87	smart_mag_oo	06
		7.5.5.88	zoom	06
7.6	Isredis	.c File Refe	erence	06
	7.6.1	Detailed I	Description	80
	7.6.2	Function	Documentation	09
		7.6.2.1	_lsredis_get_obj	09
		7.6.2.2	_lsredis_set_value	10
		7.6.2.3	Isredis_addRead	11
		7.6.2.4	Isredis_addWrite	11
		7.6.2.5	Isredis_cleanup	11
		7.6.2.6	Isredis_cmpnstr	12
		7.6.2.7	Isredis_cmpstr	12

CONTENTS xxiii

	7.6.2.8	lsredis_debugCB	212
	7.6.2.9	Isredis_delRead	213
	7.6.2.10	Isredis_delWrite	213
	7.6.2.11	lsredis_fd_service	213
	7.6.2.12	Isredis_find_preset	214
	7.6.2.13	lsredis_find_preset_index_by_position	214
	7.6.2.14	lsredis_get_obj	215
	7.6.2.15	lsredis_get_or_set_d	215
	7.6.2.16	lsredis_get_or_set_l	216
	7.6.2.17	Isredis_get_string_array	216
	7.6.2.18	lsredis_getb	216
	7.6.2.19	Isredis_getc	216
	7.6.2.20	lsredis_getd	217
	7.6.2.21	Isredis_getl	217
	7.6.2.22	lsredis_getstr	217
	7.6.2.23	lsredis_hgetCB	218
	7.6.2.24	Isredis_init	218
	7.6.2.25	lsredis_keysCB	219
	7.6.2.26	lsredis_maybe_add_key	220
	7.6.2.27	Isredis_regexec	220
	7.6.2.28	lsredis_run	220
	7.6.2.29	Isredis_set_preset	220
	7.6.2.30	Isredis_set_value	221
	7.6.2.31	Isredis_setstr	221
	7.6.2.32	lsredis_sig_service	222
	7.6.2.33	lsredis_subCB	223
	7.6.2.34	lsredis_worker	224
	7.6.2.35	redisDisconnectCB	225
7.6.3	Variable I	Documentation	225
	7.6.3.1	lsredis_cond	225
	7.6.3.2	Isredis_head	225
	7.6.3.3	lsredis_htab	225
	7.6.3.4	lsredis_key_select_regex	226
	7.6.3.5	Isredis_mutex	226
	7.6.3.6	Isredis_objs	226
	7.6.3.7	lsredis_publisher	226
	7.6.3.8	Isredis_running	226
	7.6.3.9	Isredis_thread	226
	7.6.3.10	roac	226
	7.6.3.11	rofd	226

xxiv CONTENTS

		7.6.3.12	subac	226
		7.6.3.13	subfd	226
		7.6.3.14	wrac	226
		7.6.3.15	wrfd	226
7.7	Istest.c	File Refer	rence	227
	7.7.1	Function	Documentation	227
		7.7.1.1	stest_lspmac_est_move_time	227
		7.7.1.2	lstest_main	228
7.8	lstimer.	.c File Refe	erence	228
	7.8.1	Detailed	Description	230
	7.8.2	Macro De	efinition Documentation	230
		7.8.2.1	LSTIMER_LIST_LENGTH	230
		7.8.2.2	LSTIMER_RESOLUTION_NSECS	230
	7.8.3	Typedef [Documentation	230
		7.8.3.1	lstimer_list_t	230
	7.8.4	Function	Documentation	230
		7.8.4.1	handler	230
		7.8.4.2	lstimer_add_timer	231
		7.8.4.3	Istimer_init	231
		7.8.4.4	lstimer_run	232
		7.8.4.5	lstimer_worker	232
		7.8.4.6	service_timers	233
	7.8.5	Variable I	Documentation	234
		7.8.5.1	Istimer_active_timers	234
		7.8.5.2	lstimer_cond	234
		7.8.5.3	lstimer_list	234
		7.8.5.4	lstimer_mutex	234
		7.8.5.5	Istimer_thread	234
		7.8.5.6	lstimer_timerid	234
		7.8.5.7	new_timer	235
7.9	md2cm	nds.c File F	Reference	235
	7.9.1	Detailed	Description	237
	7.9.2	Typedef [Documentation	238
		7.9.2.1	md2cmds_cmd_kv_t	238
	7.9.3	Function	Documentation	238
		7.9.3.1	md2cmds_abort	238
		7.9.3.2	md2cmds_action_queue	238
		7.9.3.3	md2cmds_action_wait	239
		7.9.3.4	md2cmds_center	239
		7.9.3.5	md2cmds_collect	239

CONTENTS xxv

7.9.3.6	md2cmds_coordsys_1_stopped_cb	243
7.9.3.7	md2cmds_coordsys_2_stopped_cb	243
7.9.3.8	md2cmds_coordsys_3_stopped_cb	243
7.9.3.9	md2cmds_coordsys_4_stopped_cb	243
7.9.3.10	md2cmds_coordsys_5_stopped_cb	243
7.9.3.11	md2cmds_coordsys_7_stopped_cb	244
7.9.3.12	md2cmds_home_prep	244
7.9.3.13	md2cmds_home_wait	244
7.9.3.14	md2cmds_init	244
7.9.3.15	md2cmds_is_moving	245
7.9.3.16	md2cmds_kappaphi_move	245
7.9.3.17	md2cmds_maybe_done_homing_cb	246
7.9.3.18	md2cmds_maybe_done_moving_cb	246
7.9.3.19	md2cmds_maybe_rotate_done_cb	247
7.9.3.20	md2cmds_move_prep	247
7.9.3.21	md2cmds_move_wait	247
7.9.3.22	md2cmds_moveAbs	248
7.9.3.23	md2cmds_moveRel	249
7.9.3.24	md2cmds_mvcenter_move	250
7.9.3.25	md2cmds_organs_move_presets	250
7.9.3.26	md2cmds_phase_beamLocation	251
7.9.3.27	md2cmds_phase_center	252
7.9.3.28	md2cmds_phase_change	253
7.9.3.29	md2cmds_phase_dataCollection	254
7.9.3.30	md2cmds_phase_manualMount	255
7.9.3.31	md2cmds_phase_robotMount	257
7.9.3.32	md2cmds_phase_safe	258
7.9.3.33	md2cmds_prep_axis	259
7.9.3.34	md2cmds_rotate	259
7.9.3.35	md2cmds_rotate_cb	261
7.9.3.36	md2cmds_run	262
7.9.3.37	md2cmds_run_cmd	262
7.9.3.38	md2cmds_set	263
7.9.3.39	md2cmds_set_scale_cb	264
7.9.3.40	md2cmds_test	264
7.9.3.41	md2cmds_time_capz_cb	264
7.9.3.42	md2cmds_transfer	265
7.9.3.43	md2cmds_worker	267
Variable [Documentation	268
7.9.4.1	md2cmds_capz_moving_time	268

7.9.4

xxvi CONTENTS

	7.9.4.2	md2cmds_cmd	268
	7.9.4.3	md2cmds_cmd_kvs	269
	7.9.4.4	md2cmds_cmd_regex	269
	7.9.4.5	md2cmds_cond	269
	7.9.4.6	md2cmds_hmap	269
	7.9.4.7	md2cmds_homing_cond	269
	7.9.4.8	md2cmds_homing_count	269
	7.9.4.9	md2cmds_homing_mutex	269
	7.9.4.10	md2cmds_md_status_code	269
	7.9.4.11	md2cmds_moving_cond	270
	7.9.4.12	md2cmds_moving_count	270
	7.9.4.13	md2cmds_moving_mutex	270
	7.9.4.14	md2cmds_moving_queue_wait	270
	7.9.4.15	md2cmds_mutex	270
	7.9.4.16	md2cmds_thread	270
	7.9.4.17	rotating	270
7.10 mk_pgp	pmac_redi	is.py File Reference	270
7.11 pgpma	c.c File Re	eference	271
7.11.1	Detailed	Description	272
7.11.2	Function	Documentation	272
	7.11.2.1	main	272
	7.11.2.2	pgpmac_printf	274
	7.11.2.3	stdinService	274
7.11.3	Variable I	Documentation	275
	7.11.3.1	ncurses_mutex	275
	7.11.3.2	running	275
	7.11.3.3	stdinfda	275
	7.11.3.4	term_input	276
	7.11.3.5	term_output	276
		term_status	
	7.11.3.7	term_status2	276
7.12 pgpma	c.h File Re	eference	276
7.12.1	Detailed	Description	284
7.12.2	Macro De	efinition Documentation	284
	7.12.2.1	_GNU_SOURCE	284
	7.12.2.2	LS_DISPLAY_WINDOW_HEIGHT	284
	7.12.2.3	LS_DISPLAY_WINDOW_WIDTH	284
	7.12.2.4	LS_PG_QUERY_STRING_LENGTH	284
	7.12.2.5	LSEVENTS_EVENT_LENGTH	284
	7.12.2.6	MD2CMDS_CMD_LENGTH	284

CONTENTS xxvii

7.12.3	Typedef D	Documentation	 . 285
	7.12.3.1	lspg_demandairrights_t	 . 285
	7.12.3.2	lspg_getcenter_t	 . 285
	7.12.3.3	$lspg_getcurrentsampleid_t \ . \ . \ . \ . \ . \ . \ . \ . \ . \ $. 285
	7.12.3.4	lspg_nextsample_t	 . 285
	7.12.3.5	lspg_nextshot_t	 . 285
	7.12.3.6	$lspg_query_queue_t \ . \ . \ . \ . \ . \ . \ . \ . \ . \ $. 285
	7.12.3.7	lspg_starttransfer_t	 . 285
	7.12.3.8	lspg_waitcryo_t	 . 285
	7.12.3.9	$lspmac_bi_t \ \ldots \ldots \ldots \ldots \ldots \ldots \ldots$. 285
	7.12.3.10	lspmac_motor_t	 . 285
	7.12.3.11	${\sf lsredis_obj_t} \ \dots $. 285
	7.12.3.12	pmac_cmd_queue_t	 . 285
	7.12.3.13	$pmac_cmd_t \ \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots$. 286
7.12.4	Function [Documentation	 . 286
	7.12.4.1	_lsredis_get_obj	 . 286
	7.12.4.2	Isevents_add_listener	 . 287
	7.12.4.3	Isevents_init	 . 288
	7.12.4.4	lsevents_remove_listener	 . 288
	7.12.4.5	lsevents_run	 . 288
	7.12.4.6	Isevents_send_event	 . 289
	7.12.4.7	lslogging_init	 . 289
	7.12.4.8	lslogging_log_message	 . 289
	7.12.4.9	lslogging_run	 . 290
	7.12.4.10	lspg_array2ptrs	 . 290
	7.12.4.11	lspg_demandairrights_all	 . 292
	7.12.4.12	lspg_getcenter_call	 . 292
	7.12.4.13	lspg_getcenter_done	 . 292
	7.12.4.14	lspg_getcenter_wait	 . 292
	7.12.4.15	lspg_getcurrentsampleid_wait_for_id	 . 293
	7.12.4.16	lspg_init	 . 293
	7.12.4.17	lspg_nextsample_all	 . 293
	7.12.4.18	lspg_nextshot_call	 . 293
	7.12.4.19	lspg_nextshot_done	 . 294
	7.12.4.20	lspg_nextshot_wait	 . 294
	7.12.4.21	lspg_query_push	 . 294
	7.12.4.22	lspg_run	 . 295
	7.12.4.23	lspg_seq_run_prep_all	 . 295
	7.12.4.24	lspg_starttransfer_call	 . 295
	7.12.4.25	lspg_starttransfer_done	 . 296

xxviii CONTENTS

7.12.4.26 lspg_starttransfer_wait
7.12.4.27 lspg_waitcryo_all
7.12.4.28 lspg_waitcryo_cb
7.12.4.29 lspg_zoom_lut_call
7.12.4.30 lspmac_abort
7.12.4.31 lspmac_est_move_time
7.12.4.32 lspmac_est_move_time_wait
7.12.4.33 lspmac_find_motor_by_name
7.12.4.34 Ispmac_getBIPosition
7.12.4.35 Ispmac_getPosition
7.12.4.36 Ispmac_home1_queue
7.12.4.37 Ispmac_home2_queue
7.12.4.38 spmac_init
7.12.4.39 Ispmac_jogabs_queue
7.12.4.40 lspmac_move_or_jog_abs_queue
7.12.4.41 lspmac_move_or_jog_preset_queue
7.12.4.42 lspmac_move_or_jog_queue
7.12.4.43 lspmac_move_preset_queue
7.12.4.44 spmac_moveabs_queue
7.12.4.45 Ispmac_moveabs_wait
7.12.4.46 lspmac_run
7.12.4.47 Ispmac_SockSendDPControlChar
7.12.4.48
7.12.4.49 lspmac_SockSendline
7.12.4.50 lspmac_video_rotate
7.12.4.51 Isredis_cmpnstr
7.12.4.52
7.12.4.53
7.12.4.54 Isredis_find_preset_index_by_position
7.12.4.55
7.12.4.56
7.12.4.57
7.12.4.58
7.12.4.59
7.12.4.60
7.12.4.61
7.12.4.62
7.12.4.63
7.12.4.64
7.12.4.65

CONTENTS xxix

| | 7.12.4.66 ls | sredis_set | str |
 | 323 |
|--------|--------------|----------------------|----------|------|------|------|------|------|------|------|-----|
| | 7.12.4.67 ls | stest_main | 1 |
 | 324 |
| | 7.12.4.68 ls | stimer_ado | d_timer |
 | 324 |
| | 7.12.4.69 ls | stimer_init | |
 | 325 |
| | 7.12.4.70 ls | stimer_run | |
 | 325 |
| | 7.12.4.71 | supdate_ir | nit |
 | 325 |
| | 7.12.4.72 | supdate_ru | ın |
 | 325 |
| | 7.12.4.73 n | nd2cmds_ | init |
 | 325 |
| | 7.12.4.74 n | nd2cmds_ | run |
 | 326 |
| | 7.12.4.75 p | ogpmac_pr | intf |
 | 327 |
| | 7.12.4.76 F | ² macSock | Sendline |
 | 327 |
| 7.12.5 | Variable Do | ocumentati | on |
 | 327 |
| | 7.12.5.1 a | alignx | |
 | 327 |
| | 7.12.5.2 a | aligny | |
 | 327 |
| | 7.12.5.3 a | alignz | |
 | 327 |
| | 7.12.5.4 a | anal | |
 | 327 |
| | 7.12.5.5 a | apery | |
 | 328 |
| | 7.12.5.6 a | aperz | |
 | 328 |
| | 7.12.5.7 a | arm_parke | d |
 | 328 |
| | 7.12.5.8 b | olight | |
 | 328 |
| | 7.12.5.9 b | olight_dow | n |
 | 328 |
| | 7.12.5.10 b | olight_f | |
 | 328 |
| | 7.12.5.11 b | olight_ud . | |
 | 328 |
| | 7.12.5.12 b | olight_up . | |
 | 328 |
| | 7.12.5.13 c | рару | |
 | 328 |
| | 7.12.5.14 | capz | |
 | 329 |
| | 7.12.5.15 d | enx | |
 | 329 |
| | 7.12.5.16 d | eny | |
 | 329 |
| | 7.12.5.17 d | oryo | |
 | 329 |
| | 7.12.5.18 | cryo_back | |
 | 329 |
| | 7.12.5.19 d | cryo_switch | 1 |
 | 329 |
| | 7.12.5.20 c | dryer | |
 | 329 |
| | 7.12.5.21 e | etel_init_ok | · |
 | 329 |
| | 7.12.5.22 e | etel_on | |
 | 329 |
| | 7.12.5.23 e | etel_ready | |
 | 330 |
| | 7.12.5.24 f | light | |
 | 330 |
| | 7.12.5.25 f | light_f | |
 | 330 |
| | 7.12.5.26 f | light_oo . | |
 | 330 |
| | 7.12.5.27 f | luo | |
 | 330 |
| | 7.12.5.28 f | luor_back | |
 | 330 |

CONTENTS

7.12.5.29 fscint
7.12.5.30 fshut
7.12.5.31 hp_air
7.12.5.32 kappa
7.12.5.33 lp_air
7.12.5.34 lspg_demandairrights
7.12.5.35 lspg_getcenter
7.12.5.36 lspg_getcurrentsampleid
7.12.5.37 lspg_nextsample
7.12.5.38 lspg_nextshot
7.12.5.39 lspg_starttransfer
7.12.5.40 lspg_waitcryo
7.12.5.41 lspmac_motors
7.12.5.42 lspmac_moving_cond
7.12.5.43 lspmac_moving_flags
7.12.5.44 lspmac_moving_mutex
7.12.5.45 lspmac_nmotors
7.12.5.46 lspmac_shutter_cond
7.12.5.47 lspmac_shutter_has_opened
7.12.5.48 lspmac_shutter_mutex
7.12.5.49 lspmac_shutter_state
7.12.5.50 lsredis_cond
7.12.5.51
7.12.5.52
7.12.5.53 md2_status_mutex
7.12.5.54 md2cmds_cmd
7.12.5.55 md2cmds_cond
7.12.5.56 md2cmds_md_status_code
7.12.5.57 md2cmds_mutex
7.12.5.58 md2cmds_pg_cond
7.12.5.59 md2cmds_pg_mutex
7.12.5.60 minikappa_ok
7.12.5.61 ncurses_mutex
7.12.5.62 omega
7.12.5.63 omega_zero_time
7.12.5.64 phi
7.12.5.65 pmac_queue_cond
7.12.5.66 pmac_queue_mutex
7.12.5.67 sample_detected
7.12.5.68 scint

CONTENTS	XX
CONTENTS	XX

Index		335
	7.12.5.78 zoom	 . 335
	7.12.5.77 term_status2	
	7.12.5.76 term_status	 . 335
	7.12.5.75 term_output	 . 335
	7.12.5.74 term_input	 . 335
	7.12.5.73 smart_mag_oo	 . 335
	7.12.5.72 smart_mag_on	 . 335
	7.12.5.71 smart_mag_off	 . 335
	7.12.5.70 smart_mag_err	 . 334
	7.12.5.69 shutter_open	 . 334

Chapter 1

The LS-CAT pgpmac Project

pgpmac.c

Some pmac defines, typedefs, functions suggested by Delta Tau Accessory 54E User Manual, October 23, 2003 (C) 2003 by Delta Tau Data Systems, Inc. All rights reserved.

Original work Copyright (C) 2012 by Keith Brister, Northwestern University, All rights reserved.

This project implements the MD2 communications required for operation at LS-CAT and is intended to replace Windows XP based .NET code provided by MAATEL.

The need to do this is driven by a desire to make the system as effecient and fast as possible by combining various operations. A proof-of-principle version of this code saw frame rates of 23/minute as opposed to the nominal 18/minute we normally quote for 1 second exposures.

Additionally, as we rapidly approach EOL for Windows XP an alternative is urgently needed.

Structure

The project is roughly broken down as follows:

lsevents.c Simple event queue

lsredis.c	Receive key value pair updates from redis databases
lslogging.c	A logging utility to simplify debugging
lspg.c	Handles communications with the controlling posgresql database
lsupdate.c	Periodically update the px.kvs table with new positions.
md2cmds.c	Provides the equivilant (mostly) of the LS-CAT BLUMax code.
pgpmac.c	Main: parses command line and starts up the various threads
pgpmac.h	All includes and defines. The only file included by the .c files in this
pmac_md2_ls-cat.pmc	Code for the PMAC: compile and install with pmac exectutive program.
pmac_md2.sql	Tables and procedures for the posgresql side of the project.

Notes:

- The postgresql and the pmac communications interfaces are asynchronous and rely heavyly on the unix "poll" routine.
- The project is multithreaded and based on "pthreads".
- · Most threads maintain a queue of commands to simpify communications with each other.
- Note that a MAATEL supported interface for a more recent version of Windows may be available, however, a bit of effort will be required to implement it at LS-CAT as the BLUMax code will likely require some revisions. This is still an option should the present project become intractable.
- An important constraint has been to run the MD2 either from the windows .NET environment or from the pgpmac environment. A consequence is that the pmac "pmc" file has been augmented to include new capabilities without destroying the code that the .NET interface requires.
- Epics support could come by adapting the "e.c" code to work here directly or could come by making use of the existing kv pair mechanism already in place or, as is most likely, a combination of the two.
- Ncurses support could include input lines for SQL queries and direct commands for supporting homing etc.
 Perhaps the F keys could change modes or use of special mode changing text commands. Output is not
 asynchronous. Although this is unlikely to cause a problem I'd hate to have the program hang because
 terminal output is hung up.
- PG queries come back as text instead of binary. We could reduce the numeric errors by using binary and things would run a tad faster, though it is unlikely anyone would notice or care about the speed.

MD2 Motors and Coordinate Systems

CS	Motor	
1	1	X = Omega
2	17 18	<pre>X = Center X Y = Center Y</pre>
3	2 3 4	<pre>X = Alignment X Y = Alignment Y Z = Alignment Z</pre>
	5	Analyzer
4	6	X = Zoom
5	7 8 9 10 11	Y = Aperture Y Z = Aperture Z U = Capillary Y V = Capillary Z W = Scintillator Z
6		(None)
7	19 20	X = Kappa Y = Phi

MD2 Motion Programs

```
before calling, set M4XX = 1: flag to indicate we are running program XX P variables as arguments
```

```
Program
                Description
 1
                home omega
  2
                home alignment table X
  3
                home alignment table Y
  4
                home alignment table Z
  6
                home camera zoom
  7
                home aperture Y
  8
                home aperture Z
  9
                home capillary Y
 10
                home capillary Z
 11
                home scintillator Z
 17
                home center X
 18
                home center Y
 19
                home kappa
                home phi (Home position is not defined for phi ...)
 20
 25
                kappa stress test
 26
                Combined Incremental move of X and Y in selected coordinate system
                        (Does not reset M426)
                        P170 = X increment
                        P171 = Y increment
 31
                scan omega
                        P170 = Start
                        P171 = End
                        P173 = Velocity (float)
P174 = Sample Rate (I5049)
                        P175 = Acceleration time
                        P176
                              = Gathering source
                        P177 = Number of passes
                        P178 = Shutter rising distance (units of omega motion)
                        P179 = Shutter falling distance (units of omega motion)
                        P180 = Exposure Time
 34
                Organ Scan
                        P169 = Motor Number
                        P170 = Start Position
                        P171 = End Position
                        P172 = Step Size
                        P173 = Motor Speed
 35
                Organ Homing
 37
                Organ Move
                             (microdiff_hard.ini says we don't use this anymore)
                        P169 = Capillary Z
                        P170 = Scintillator Z
                        P171 = Aperture Z
 50
                Combined Incremental move of X and Y
                        P170 = X increment
                        P171 = Y increment
 52
                X oscillation (while M320 == 1)
                        (Does not reset M452)
 53
                Center X and Y Synchronized homing
```

```
Combined X, Y, Z absolute move
 54
                      P170 = X
                      P171 = Y
                      P172 = Z
131
               LS-CAT Modified Omega Scan
                      P170 = Shutter open position, in counts
                      P171 = Delta omega, in counts
                      P173 = Omega velocity (counts/msec)
                      P175
                           = Acceleration Time (msec)
                      P177
                            = Number of passes
                      P178
                            = Shutter Rising Distance
                      P179
                            = Shutter Falling Distance
                      P180
                            = Exposure TIme (msec)
140
               LS-CAT Move X Absolute
                           = X Value (cts)
                      Q10
141
               LS-CAT Move Y Absolute
                      Q11 = Y Value (cts)
               LS-CAT Move Z Absolute
142
                      Q12 = Z Value (cts)
               LS-CAT Move X, Y Absolute
150
                      Q20
                           = X Value
                            = Y Value
                      Q21
160
               LS-CAT Move X, Y, Z Absolute
                      Q30 = X Value
                      Q31 = Y Value
                      Q32 = Z Value
```

Chapter 2

Namespace Index

2.1	Names	pace	List
	11411100	1000	

Here is a list of	of all na	ame	esp	ac	es	wit	h k	rie	f c	les	cri	ipti	ion	ıs:												
iniParser															 		 							 		1
mk_pgpm	ac_rec	lis													 									 		1

6 Namespace Index

Chapter 3

Data Structure Index

3.1 Data Structures

Here are the data structures with brief descriptions:

iniParser.iniParser	
This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the	
License, or (at your option) any later version	15
lsevents_listener_struct	
Linked list of event listeners	17
lsevents_queue_struct	
Storage definition for the events	18
lslogging_queue_struct	
Our log object: time and message	19
lspg_demandairrights_struct	20
lspg_getcenter_struct	
Storage for getcenter query Used for the md2 ROTATE command that generates the centering	
movies	20
lspg_getcurrentsampleid_struct	23
lspg_lock_detector_struct	
Lock detector object Implements detector lock for exposure control	24
lspg_lock_diffractometer_struct	
Object used to impliment locking the diffractometer Critical to exposure timing	25
lspg_nextsample_struct	
Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)	25
lspg_nextshot_struct	
Storage definition for nextshot query	27
lspg_seq_run_prep_struct	
Data collection running object	37
lspg_starttransfer_struct	
Returns 1 if transfer can continue 0 to abort	38
lspg_wait_for_detector_struct	
Object that implements detector / spindle timing We use database locks for exposure control and	
this implements the md2 portion of this handshake	39
lspg_waitcryo_struct	40
lspgQueryQueueStruct	
Store each query along with it's callback function	41
spmac_ascii_buffers_struct	42
lspmac_bi_struct	
Storage for binary inputs	42
lspmac_cmd_queue_struct	
PMAC command queue item	44

8 Data Structure Index

spmac_combined_move_struct	. 45
spmac_dpascii_queue_struct	. 46
spmac_motor_struct	
Motor information	. 46
sredis_obj_struct	
Redis Object Basic object whose value is sychronized with our redis db	. 54
stimer_list_struct	
Everything we need to know about a timer	. 57
md2cmds_cmd_kv_struct	. 59
md2StatusStruct	
The block of memory retrieved in a status request	. 60
tagEthernetCmd	
PMAC ethernet packet definition	. 67

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

iniParser. Isevents.c	py	69
	Event subsystem for inter-pgpmac communication	69
Islogging.	C	
	Logs messages to a file	75
lspg.c		
	Postgresql support for the LS-CAT pgpmac project	80
Ispmac.c		
	Routines concerned with communication with PMAC	123
Isredis.c		
	Support redis hash synchronization	206
lstest.c		227
lstimer.c		
	Support for delayed and periodic events	228
md2cmds	5.C	
	Implements commands to run the md2 diffractometer attached to a PMAC controlled by post-	
	gresql	
mk_pgpm	nac_redis.py	270
pgpmac.c		
	Main for the pgpmac project	271
pgpmac.h		
	Headers for the entire pgpmac project	276

10 File Index

Chapter 5

Namespace Documentation

5.1 iniParser Namespace Reference

Data Structures

· class iniParser

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

Variables

• tuple ip iniParser("21-ID-E/microdiff_hard.ini")

5.1.1 Variable Documentation

5.1.1.1 tuple iniParser.ip iniParser("21-ID-E/microdiff_hard.ini")

Definition at line 104 of file iniParser.py.

5.2 mk_pgpmac_redis Namespace Reference

Functions

- · def active_simulation
- def asis

Variables

- list head sys.argv[1]
- list pref_ini sys.argv[2]
- list hard_ini sys.argv[3]
- · dictionary motor_dict
- dictionary hard_ini_fields
- list motor_field_lists
- list bi_list ["CryoSwitch"]
- dictionary motor_presets

- · list zoom_settings
- tuple hi iniParser.iniParser(hard_ini)
- list v motor_dict[m]
- · string f "HSETNX"
- list xlate hard_ini_fields[k]
- tuple pi iniParser.iniParser(pref_ini)
- int i 0
- tuple ppos pi.get(section, option)
- string fnc "HSETNX"
- tuple b pi.get(section, "LightIntensity")
- tuple p pi.get(section, "MotorPosition")
- tuple x pi.get(section, "ScaleX")
- tuple y pi.get(section, "ScaleY")

5.2.1 Function Documentation

5.2.1.1 def mk_pgpmac_redis.active_simulation (sim)

Definition at line 172 of file mk_pgpmac_redis.py.

5.2.1.2 def mk_pgpmac_redis.asis (arg)

Definition at line 179 of file mk_pgpmac_redis.py.

```
179
180 def asis(arg):
181 return arg
```

5.2.2 Variable Documentation

5.2.2.1 tuple mk_pgpmac_redis.b pi.get(section, "LightIntensity")

Definition at line 425 of file mk_pgpmac_redis.py.

5.2.2.2 list mk_pgpmac_redis.bi_list ["CryoSwitch"]

Definition at line 243 of file mk_pgpmac_redis.py.

5.2.2.3 tuple mk_pgpmac_redis.f "HSETNX"

Definition at line 366 of file mk_pgpmac_redis.py.

5.2.2.4 string mk_pgpmac_redis.fnc "HSETNX"

Definition at line 416 of file mk_pgpmac_redis.py.

5.2.2.5 mk_pgpmac_redis.hard_ini sys.argv[3]

Definition at line 21 of file mk_pgpmac_redis.py.

5.2.2.6 dictionary mk_pgpmac_redis.hard_ini_fields

Initial value:

Definition at line 182 of file mk_pgpmac_redis.py.

5.2.2.7 list mk_pgpmac_redis.head sys.argv[1]

Definition at line 13 of file mk_pgpmac_redis.py.

5.2.2.8 tuple mk_pgpmac_redis.hi iniParser.iniParser(hard_ini)

Definition at line 336 of file mk_pgpmac_redis.py.

5.2.2.9 int mk_pgpmac_redis.i 0

Definition at line 390 of file mk_pgpmac_redis.py.

5.2.2.10 dictionary mk_pgpmac_redis.motor_dict

Definition at line 29 of file mk_pgpmac_redis.py.

5.2.2.11 list mk_pgpmac_redis.motor_field_lists

Definition at line 204 of file mk_pgpmac_redis.py.

5.2.2.12 dictionary mk_pgpmac_redis.motor_presets

Definition at line 245 of file mk_pgpmac_redis.py.

5.2.2.13 tuple mk_pgpmac_redis.p pi.get(section, "MotorPosition")

Definition at line 432 of file mk_pgpmac_redis.py.

5.2.2.14 tuple mk_pgpmac_redis.pi iniParser.iniParser(pref_ini)

Definition at line 387 of file mk_pgpmac_redis.py.

5.2.2.15 tuple mk_pgpmac_redis.ppos pi.get(section, option)

Definition at line 398 of file mk_pgpmac_redis.py.

5.2.2.16 mk_pgpmac_redis.pref_ini sys.argv[2]

Definition at line 16 of file mk pgpmac redis.py.

5.2.2.17 tuple mk_pgpmac_redis.v motor_dict[m]

Definition at line 365 of file mk_pgpmac_redis.py.

5.2.2.18 tuple mk_pgpmac_redis.x pi.get(section, "ScaleX")

Definition at line 439 of file mk_pgpmac_redis.py.

5.2.2.19 list mk_pgpmac_redis.xlate hard_ini_fields[k]

Definition at line 370 of file mk_pgpmac_redis.py.

5.2.2.20 tuple mk_pgpmac_redis.y pi.get(section, "ScaleY")

Definition at line 446 of file mk pgpmac redis.py.

5.2.2.21 list mk_pgpmac_redis.zoom_settings

Initial value:

```
front back pos
                                                         scalex scaley
                                                                                        section
                                  8.0, 34100, 2.7083, 3.3442, "CoaxCam.Zoom1"], 8.1, 31440, 2.2487, 2.2776, "CoaxCam.Zoom2"], 8.2, 27460, 1.7520, 1.7550, "CoaxCam.Zoom3"], 8.3, 23480, 1.3360, 1.3400, "CoaxCam.Zoom4"],
                       4.0,
          [2,
                       6.0,
          [3,
                       6.5,
          [4,
                       7.0,
                       8.0, 10.0, 19500, 1.0140, 1.0110, "CoaxCam.Zooms"], 9.0, 12.0, 15520, 0.7710, 0.7760, "CoaxCam.Zooms"],
          [5,
          [6,
                      10.0, 17.0, 11540, 0.5880, 0.5920, "CoaxCam.Zoom7"],
                                                 7560, 0.4460, 0.4480, "CoaxCam.Zoom8"],
3580, 0.3410, 0.3460, "CoaxCam.Zoom9"],
0, 0.2700, 0.2690, "CoaxCam.Zoom10"]
10
                      12.0, 25.0,
11
            [9,
                       15.0, 37.0,
                                                3580, 0.3410,
                      16.0,
12
            [10,
                                  42.0,
```

Definition at line 312 of file mk_pgpmac_redis.py.

Chapter 6

Data Structure Documentation

6.1 iniParser.iniParser Class Reference

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

Public Member Functions

- def __init__
- def read
- · def sections
- def options
- def has_section
- def has_option
- def get

Data Fields

- f
- sd

6.1.1 Detailed Description

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program. If not, see http-://www.gnu.org/licenses/.

We assume the sections and options are case insensitive and that, although nested sections are implied by the format used by the md2, that the nesting has no practical importance.

The current version is for READING the files.

TODO: add writing. We'll need to keep track of the preferred case used in the ini file as well as the existing comments. This is mildly tricky since comments apparently can appear on both option lines and non-option lines so

we'll need to track the line number within each section to preserve all the comments. Strictly speaking this is not necessary as we can just spit stuff out all lower case without comments and, presumably, the md2 should be able to deal with it. However, there is enough of a problem with the lack of documentation that willfully removing seems like a bad idea.

Definition at line 42 of file iniParser.py.

6.1.2 Constructor & Destructor Documentation

```
6.1.2.1 def iniParser.iniParser.__init__ ( self, fn )
```

Definition at line 44 of file iniParser.py.

6.1.3 Member Function Documentation

6.1.3.1 def iniParser.iniParser.get (self, section, option)

Definition at line 99 of file iniParser.py.

```
99
100    def get( self, section, option):
101        return self.sd[section.lower()][option.lower()]
102
```

6.1.3.2 def iniParser.iniParser.has_option (self, section, option)

Definition at line 94 of file iniParser.py.

6.1.3.3 def iniParser.iniParser.has_section (self, section)

Definition at line 91 of file iniParser.py.

```
91

92 def has_section( self, section):

93 return self.sd.has_key( section.lower())
```

6.1.3.4 def iniParser.iniParser.options (self, section)

Definition at line 87 of file iniParser.py.

```
87
88 def options( self, section):
89 return self.sd[section.lower()].keys()
90
```

6.1.3.5 def iniParser.iniParser.read (self)

Definition at line 49 of file iniParser.py.

```
50
       def read( self):
        self.sd = {}
current_section = "default"
51
52
53
           current_dict
                            = {}
           for 1 in self.f.readlines():
               sl = l.strip()
56
                if len(sl) > 0:
                    if sl[0] == ";":
57
58
59
60
                    if sl[0] == "[" and sl.find("]") > 1:
                        self.sd[current_section] = current_dict
62
                        current_dict = {}
63
                        current_section = (sl[1:sl.find("]")]).lower()
64
65
                        if sl.find(";") > 0:
66
                            s = sl[0:sl.find(";")]
68
69
                             s = s1
70
71
                        if s.find("=") > 0:
                            slist = s.split("=")
73
                             if len(slist) == 2:
                                 k = (slist[0].strip()).lower()
v = slist[1].strip()
75
76
                                 current_dict[k] = v
78
           self.sd[current_section] = current_dict
80
81
           self.f.close()
```

6.1.3.6 def iniParser.iniParser.sections (self)

Definition at line 83 of file iniParser.py.

```
83
84     def sections( self):
85         ks = set(self.sd.keys())
86         return list(ks.difference( ["default"]))
```

6.1.4 Field Documentation

6.1.4.1 iniParser.iniParser.f

Definition at line 45 of file iniParser.py.

6.1.4.2 iniParser.iniParser.sd

Definition at line 46 of file iniParser.py.

The documentation for this class was generated from the following file:

• iniParser.py

6.2 | Isevents_listener_struct Struct Reference

Linked list of event listeners.

Data Fields

• struct |sevents_listener_struct * next

Next listener.

char * raw_regexp

the original string sent to us

regex_t re

regular expression representing listened for events

void(* cb)(char *)

call back function

6.2.1 Detailed Description

Linked list of event listeners.

Definition at line 27 of file Isevents.c.

6.2.2 Field Documentation

6.2.2.1 void(* Isevents_listener_struct::cb)(char *)

call back function

Definition at line 31 of file Isevents.c.

6.2.2.2 struct | sevents_listener_struct | sevents_listener_struct::next

Next listener.

Definition at line 28 of file Isevents.c.

6.2.2.3 char* lsevents_listener_struct::raw_regexp

the original string sent to us

Definition at line 29 of file Isevents.c.

6.2.2.4 regex_t lsevents_listener_struct::re

regular expression representing listened for events

Definition at line 30 of file Isevents.c.

The documentation for this struct was generated from the following file:

· Isevents.c

6.3 | Isevents_queue_struct Struct Reference

Storage definition for the events.

Data Fields

char * evp

name of the event

6.3.1 Detailed Description

Storage definition for the events.

Just a string for now. Perhaps one day we'll succumb to the temptation to add an argument or two.

Definition at line 17 of file Isevents.c.

6.3.2 Field Documentation

6.3.2.1 char* lsevents_queue_struct::evp

name of the event

Definition at line 18 of file Isevents.c.

The documentation for this struct was generated from the following file:

· Isevents.c

6.4 Islogging_queue_struct Struct Reference

Our log object: time and message.

Data Fields

· struct timespec Itime

time stamp: set when queued

char lmsg [LSLOGGING_MSG_LENGTH]

our message, truncated if too long

6.4.1 Detailed Description

Our log object: time and message.

Definition at line 24 of file Islogging.c.

6.4.2 Field Documentation

 $6.4.2.1 \quad char \ lslogging_queue_struct::lmsg[LSLOGGING_MSG_LENGTH]$

our message, truncated if too long

Definition at line 26 of file Islogging.c.

6.4.2.2 struct timespec Islogging_queue_struct::ltime

time stamp: set when queued

Definition at line 25 of file Islogging.c.

The documentation for this struct was generated from the following file:

• Islogging.c

6.5 lspg_demandairrights_struct Struct Reference

```
#include <pgpmac.h>
```

Data Fields

- pthread_mutex_t mutex
- · pthread cond t cond
- · int new_value_ready

6.5.1 Detailed Description

Definition at line 199 of file pgpmac.h.

6.5.2 Field Documentation

6.5.2.1 pthread_cond_t lspg_demandairrights_struct::cond

Definition at line 201 of file pgpmac.h.

6.5.2.2 pthread_mutex_t lspg_demandairrights_struct::mutex

Definition at line 200 of file pgpmac.h.

6.5.2.3 int lspg_demandairrights_struct::new_value_ready

Definition at line 202 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.6 Ispg_getcenter_struct Struct Reference

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies.

```
#include <pgpmac.h>
```

Data Fields

• pthread_mutex_t mutex

don't let the threads collide!

pthread_cond_t cond

provides signaling for when the query is done

• int new_value_ready

used with condition

• int no_rows_returned

flag in case no centering information was forthcoming

• int zoom

the next zoom level to go to before taking the next movie

- int zoom isnull
- double dcx

center x change

- int dcx_isnull
- · double dcy

center y change

- int dcy_isnull
- · double dax

alignment x change

- int dax isnull
- · double day

alignment y change

- int day_isnull
- double daz

alignment z change

• int daz_isnull

6.6.1 Detailed Description

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies. Definition at line 213 of file pgpmac.h.

6.6.2 Field Documentation

6.6.2.1 pthread_cond_t lspg_getcenter_struct::cond

provides signaling for when the query is done

Definition at line 215 of file pgpmac.h.

6.6.2.2 double lspg_getcenter_struct::dax

alignment x change

Definition at line 228 of file pgpmac.h.

6.6.2.3 int lspg_getcenter_struct::dax_isnull

Definition at line 229 of file pgpmac.h.

6.6.2.4 double lspg_getcenter_struct::day alignment y change Definition at line 231 of file pgpmac.h. 6.6.2.5 int lspg_getcenter_struct::day_isnull Definition at line 232 of file pgpmac.h. 6.6.2.6 double lspg_getcenter_struct::daz alignment z change Definition at line 234 of file pgpmac.h. 6.6.2.7 int lspg_getcenter_struct::daz_isnull Definition at line 235 of file pgpmac.h. 6.6.2.8 double lspg_getcenter_struct::dcx center x change Definition at line 222 of file pgpmac.h. 6.6.2.9 int lspg_getcenter_struct::dcx_isnull Definition at line 223 of file pgpmac.h. 6.6.2.10 double lspg_getcenter_struct::dcy center y change Definition at line 225 of file pgpmac.h. 6.6.2.11 int lspg_getcenter_struct::dcy_isnull Definition at line 226 of file pgpmac.h. 6.6.2.12 pthread_mutex_t lspg_getcenter_struct::mutex don't let the threads collide! Definition at line 214 of file pgpmac.h.

6.6.2.13 int lspg_getcenter_struct::new_value_ready used with condition Definition at line 216 of file pgpmac.h.

6.6.2.14 int lspg_getcenter_struct::no_rows_returned

flag in case no centering information was forthcoming

Definition at line 217 of file pgpmac.h.

6.6.2.15 int lspg_getcenter_struct::zoom

the next zoom level to go to before taking the next movie

Definition at line 219 of file pgpmac.h.

6.6.2.16 int lspg_getcenter_struct::zoom_isnull

Definition at line 220 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.7 lspg_getcurrentsampleid_struct Struct Reference

#include <pgpmac.h>

Data Fields

• pthread_mutex_t mutex

practice safe threading

pthread_cond_t cond

for signaling

int no_rows_returned

flag for an empty return

· int new_value_ready

OK, there is never a value, we need a variable for the conditional wait and this is what we call it everywhere else.

· unsigned int getcurrentsampleid

the sample we think is mounted on the diffractometer

• int getcurrentsampleid_isnull

the sample we think is mounted on the diffractometer

6.7.1 Detailed Description

Definition at line 187 of file pgpmac.h.

6.7.2 Field Documentation

6.7.2.1 pthread_cond_t lspg_getcurrentsampleid_struct::cond

for signaling

Definition at line 189 of file pgpmac.h.

6.7.2.2 unsigned int lspg_getcurrentsampleid_struct::getcurrentsampleid

the sample we think is mounted on the diffractometer

Definition at line 192 of file pgpmac.h.

6.7.2.3 int lspg_getcurrentsampleid_struct::getcurrentsampleid_isnull

the sample we think is mounted on the diffractometer

Definition at line 193 of file pgpmac.h.

6.7.2.4 pthread_mutex_t lspg_getcurrentsampleid_struct::mutex

practice safe threading

Definition at line 188 of file pgpmac.h.

6.7.2.5 int lspg_getcurrentsampleid_struct::new_value_ready

OK, there is never a value, we need a variable for the conditional wait and this is what we call it everywhere else.

Definition at line 191 of file pgpmac.h.

6.7.2.6 int lspg_getcurrentsampleid_struct::no_rows_returned

flag for an empty return

Definition at line 190 of file pgpmac.h.

The documentation for this struct was generated from the following file:

• pgpmac.h

6.8 lspg_lock_detector_struct Struct Reference

lock detector object Implements detector lock for exposure control

Data Fields

- pthread_mutex_t mutex
- pthread_cond_t cond
- int new_value_ready

6.8.1 Detailed Description

lock detector object Implements detector lock for exposure control Definition at line 1073 of file Ispg.c.

6.8.2 Field Documentation

6.8.2.1 pthread_cond_t lspg_lock_detector_struct::cond

Definition at line 1075 of file lspg.c.

6.8.2.2 pthread_mutex_t lspg_lock_detector_struct::mutex

Definition at line 1074 of file Ispg.c.

6.8.2.3 int lspg_lock_detector_struct::new_value_ready

Definition at line 1076 of file lspg.c.

The documentation for this struct was generated from the following file:

· lspg.c

6.9 Ispg_lock_diffractometer_struct Struct Reference

Object used to impliment locking the diffractometer Critical to exposure timing.

Data Fields

- pthread_mutex_t mutex
- · pthread cond t cond
- · int new value ready

6.9.1 Detailed Description

Object used to impliment locking the diffractometer Critical to exposure timing. Definition at line 1014 of file lspg.c.

6.9.2 Field Documentation

6.9.2.1 pthread_cond_t lspg_lock_diffractometer_struct::cond

Definition at line 1016 of file lspg.c.

6.9.2.2 pthread_mutex_t lspg_lock_diffractometer_struct::mutex

Definition at line 1015 of file lspg.c.

6.9.2.3 int lspg_lock_diffractometer_struct::new_value_ready

Definition at line 1017 of file lspg.c.

The documentation for this struct was generated from the following file:

· lspg.c

6.10 lspg_nextsample_struct Struct Reference

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

#include <pgpmac.h>

Data Fields

pthread_mutex_t mutex

Our mutex.

pthread_cond_t cond

Our condition.

int new_value_ready

flag for our condition

• int no_rows_returned

just in case, though this query should always return an integer, perhaps 0

· unsigned int nextsample

sample number (4 8-bit segments: station, dewar (lid), puck, and position in the puck)

· int nextsample_isnull

shouldn't ever be set, but if we change the logic of this call in PG then we are ready for it here.

6.10.1 Detailed Description

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

Definition at line 260 of file pgpmac.h.

6.10.2 Field Documentation

6.10.2.1 pthread_cond_t lspg_nextsample_struct::cond

Our condition.

Definition at line 262 of file pgpmac.h.

6.10.2.2 pthread_mutex_t lspg_nextsample_struct::mutex

Our mutex.

Definition at line 261 of file pgpmac.h.

6.10.2.3 int lspg_nextsample_struct::new_value_ready

flag for our condition

Definition at line 263 of file pgpmac.h.

6.10.2.4 unsigned int lspg_nextsample_struct::nextsample

sample number (4 8-bit segments: station, dewar (lid), puck, and position in the puck)

Definition at line 266 of file pgpmac.h.

6.10.2.5 int lspg_nextsample_struct::nextsample_isnull

shouldn't ever be set, but if we change the logic of this call in PG then we are ready for it here.

Definition at line 267 of file pgpmac.h.

6.10.2.6 int lspg_nextsample_struct::no_rows_returned

just in case, though this query should always return an integer, perhaps 0

Definition at line 264 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.11 | Ispg_nextshot_struct Struct Reference

Storage definition for nextshot query.

```
#include <pgpmac.h>
```

Data Fields

• pthread_mutex_t mutex

Our mutex for sanity in the multi-threaded program.

• pthread_cond_t cond

Condition to wait for a response from our postgresql server.

· int new value ready

Our flag for the condition to wait for.

• int no_rows_returned

flag indicating that no rows were returned.

· char * dsdir

Directory for data relative to the ESAF home directory.

- · int dsdir isnull
- · char * dspid

ID string identifying this dataset.

- · int dspid_isnull
- · double dsowidth

dataset defined oscillation width

- int dsowidth_isnull
- char * dsoscaxis

dataset defined oscillation axis (always omega)

- · int dsoscaxis_isnull
- · double dsexp

dataset defined exposure time

- int dsexp_isnull
- · long long skey

key identifying a particulary image

- int skey_isnull
- · double sstart

starting angle

- int sstart_isnull
- char * sfn

file name

- · int sfn isnull
- · double dsphi

dataset defined starting phi angle

int dsphi_isnull

· double dsomega

dataset defined starting omega angle

- int dsomega_isnull
- · double dskappa

dataset defined starting kappa angle

- int dskappa_isnull
- · double dsdist

dataset defined detector distance

- · int dsdist_isnull
- · double dsnrg

dataset defined energy

- · int dsnrg isnull
- · unsigned int dshpid

sample holder ID

- int dshpid_isnull
- · double cx

centering table x position

- int cx isnull
- double cy

centering table y position

- int cy_isnull
- · double ax

alignment table x position

- · int ax isnull
- double ay

alignment table y position

- int ay_isnull
- double az

alignment table z position

- int az_isnull
- · int active

flag: 1=move to indicated center position, 0=don't move center or alignment tables

- · int active isnull
- int sindex

index of frame (used to generate the file extension)

- int sindex_isnull
- char * stype

"Normal" or "Gridsearch"

- · int stype isnull
- double dsowidth2

next image oscillation width

- int dsowidth2_isnull
- char * dsoscaxis2

next image ascillation axis (always "omega")

- · int dsoscaxis2_isnull
- double dsexp2

next image exposure time

- · int dsexp2_isnull
- double sstart2

next image start angle

- int sstart2_isnull
- double dsphi2

next image phi position

- · int dsphi2 isnull
- · double dsomega2

next image omega position

- · int dsomega2_isnull
- double dskappa2

next image kappa position

- int dskappa2_isnull
- double dsdist2

next image distance

- · int dsdist2 isnull
- double dsnrg2

next image energy

- · int dsnrg2_isnull
- double cx2

next image centering table x position

- · int cx2 isnull
- double cy2

next image centering table y position

- · int cy2_isnull
- double ax2

next image alignment x position

- · int ax2 isnull
- double ay2

next image alignment y position

- int ay2 isnull
- double az2

next image alignment z position

- · int az2 isnull
- int active2

flag: 1 if next image should use the above centering parameters

- int active2_isnull
- int sindex2

next image index number

- int sindex2 isnull
- char * stype2

next image type ("Normal" or "Gridsearch")

int stype2_isnull

6.11.1 Detailed Description

Storage definition for nextshot query.

The next shot query returns all the information needed to collect the next data frame. Since SQL allows for null fields independently from blank strings a separate integer is used as a flag for this case. This adds to the program complexity but allows for some important cases. Suck it up.

Definition at line 280 of file pgpmac.h.

6.11.2 Field Documentation

6.11.2.1 int lspg_nextshot_struct::active

flag: 1=move to indicated center position, 0=don't move center or alignment tables

Definition at line 343 of file pgpmac.h.

6.11.2.2 int lspg_nextshot_struct::active2

flag: 1 if next image should use the above centering parameters

Definition at line 394 of file pgpmac.h.

6.11.2.3 int lspg_nextshot_struct::active2_isnull

Definition at line 395 of file pgpmac.h.

6.11.2.4 int lspg_nextshot_struct::active_isnull

Definition at line 344 of file pgpmac.h.

6.11.2.5 double lspg_nextshot_struct::ax

alignment table x position

Definition at line 334 of file pgpmac.h.

6.11.2.6 double lspg_nextshot_struct::ax2

next image alignment x position

Definition at line 385 of file pgpmac.h.

6.11.2.7 int lspg_nextshot_struct::ax2_isnull

Definition at line 386 of file pgpmac.h.

6.11.2.8 int lspg_nextshot_struct::ax_isnull

Definition at line 335 of file pgpmac.h.

6.11.2.9 double lspg_nextshot_struct::ay

alignment table y position

Definition at line 337 of file pgpmac.h.

6.11.2.10 double lspg_nextshot_struct::ay2

next image alignment y position

Definition at line 388 of file pgpmac.h.

6.11.2.11 int lspg_nextshot_struct::ay2_isnull

Definition at line 389 of file pgpmac.h.

6.11.2.12 int lspg_nextshot_struct::ay_isnull

Definition at line 338 of file pgpmac.h.

6.11.2.13 double lspg_nextshot_struct::az

alignment table z position

Definition at line 340 of file pgpmac.h.

6.11.2.14 double lspg_nextshot_struct::az2

next image alignment z position

Definition at line 391 of file pgpmac.h.

6.11.2.15 int lspg_nextshot_struct::az2_isnull

Definition at line 392 of file pgpmac.h.

6.11.2.16 int lspg_nextshot_struct::az_isnull

Definition at line 341 of file pgpmac.h.

6.11.2.17 pthread_cond_t lspg_nextshot_struct::cond

Condition to wait for a response from our postgresql server.

Definition at line 282 of file pgpmac.h.

6.11.2.18 double lspg_nextshot_struct::cx

centering table x position

Definition at line 328 of file pgpmac.h.

6.11.2.19 double lspg_nextshot_struct::cx2

next image centering table x position

Definition at line 379 of file pgpmac.h.

6.11.2.20 int lspg_nextshot_struct::cx2_isnull

Definition at line 380 of file pgpmac.h.

6.11.2.21 int lspg_nextshot_struct::cx_isnull

Definition at line 329 of file pgpmac.h.

6.11.2.22 double lspg_nextshot_struct::cy

centering table y position

Definition at line 331 of file pgpmac.h.

6.11.2.23 double lspg_nextshot_struct::cy2

next image centering table y position

Definition at line 382 of file pgpmac.h.

6.11.2.24 int lspg_nextshot_struct::cy2_isnull

Definition at line 383 of file pgpmac.h.

6.11.2.25 int lspg_nextshot_struct::cy_isnull

Definition at line 332 of file pgpmac.h.

6.11.2.26 char* lspg_nextshot_struct::dsdir

Directory for data relative to the ESAF home directory.

Definition at line 286 of file pgpmac.h.

6.11.2.27 int lspg_nextshot_struct::dsdir_isnull

Definition at line 287 of file pgpmac.h.

6.11.2.28 double lspg_nextshot_struct::dsdist

dataset defined detector distance

Definition at line 319 of file pgpmac.h.

6.11.2.29 double lspg_nextshot_struct::dsdist2

next image distance

Definition at line 373 of file pgpmac.h.

 $6.11.2.30 \quad int \ lspg_nextshot_struct::dsdist2_isnull$

Definition at line 374 of file pgpmac.h.

6.11.2.31 int lspg_nextshot_struct::dsdist_isnull

Definition at line 320 of file pgpmac.h.

6.11.2.32 double lspg_nextshot_struct::dsexp

dataset defined exposure time

Definition at line 298 of file pgpmac.h.

6.11.2.33 double lspg_nextshot_struct::dsexp2

next image exposure time

Definition at line 358 of file pgpmac.h.

6.11.2.34 int lspg_nextshot_struct::dsexp2_isnull

Definition at line 359 of file pgpmac.h.

6.11.2.35 int lspg_nextshot_struct::dsexp_isnull

Definition at line 299 of file pgpmac.h.

6.11.2.36 unsigned int lspg_nextshot_struct::dshpid

sample holder ID

Definition at line 325 of file pgpmac.h.

6.11.2.37 int lspg_nextshot_struct::dshpid_isnull

Definition at line 326 of file pgpmac.h.

6.11.2.38 double lspg_nextshot_struct::dskappa

dataset defined starting kappa angle

Definition at line 316 of file pgpmac.h.

6.11.2.39 double lspg_nextshot_struct::dskappa2

next image kappa position

Definition at line 370 of file pgpmac.h.

6.11.2.40 int lspg_nextshot_struct::dskappa2_isnull

Definition at line 371 of file pgpmac.h.

6.11.2.41 int lspg_nextshot_struct::dskappa_isnull

Definition at line 317 of file pgpmac.h.

6.11.2.42 double lspg_nextshot_struct::dsnrg

dataset defined energy

Definition at line 322 of file pgpmac.h.

6.11.2.43 double lspg_nextshot_struct::dsnrg2

next image energy

Definition at line 376 of file pgpmac.h.

6.11.2.44 int lspg_nextshot_struct::dsnrg2_isnull

Definition at line 377 of file pgpmac.h.

6.11.2.45 int lspg_nextshot_struct::dsnrg_isnull

Definition at line 323 of file pgpmac.h.

6.11.2.46 double lspg_nextshot_struct::dsomega

dataset defined starting omega angle

Definition at line 313 of file pgpmac.h.

6.11.2.47 double lspg_nextshot_struct::dsomega2

next image omega position

Definition at line 367 of file pgpmac.h.

6.11.2.48 int lspg_nextshot_struct::dsomega2_isnull

Definition at line 368 of file pgpmac.h.

6.11.2.49 int lspg_nextshot_struct::dsomega_isnull

Definition at line 314 of file pgpmac.h.

6.11.2.50 char* lspg_nextshot_struct::dsoscaxis

dataset defined oscillation axis (always omega)

Definition at line 295 of file pgpmac.h.

6.11.2.51 char* lspg_nextshot_struct::dsoscaxis2

next image ascillation axis (always "omega")

Definition at line 355 of file pgpmac.h.

6.11.2.52 int lspg_nextshot_struct::dsoscaxis2_isnull

Definition at line 356 of file pgpmac.h.

6.11.2.53 int lspg_nextshot_struct::dsoscaxis_isnull

Definition at line 296 of file pgpmac.h.

6.11.2.54 double lspg_nextshot_struct::dsowidth

dataset defined oscillation width

Definition at line 292 of file pgpmac.h.

6.11.2.55 double lspg_nextshot_struct::dsowidth2

next image oscillation width

Definition at line 352 of file pgpmac.h.

6.11.2.56 int lspg_nextshot_struct::dsowidth2_isnull

Definition at line 353 of file pgpmac.h.

6.11.2.57 int lspg_nextshot_struct::dsowidth_isnull

Definition at line 293 of file pgpmac.h.

6.11.2.58 double lspg_nextshot_struct::dsphi

dataset defined starting phi angle

Definition at line 310 of file pgpmac.h.

6.11.2.59 double lspg_nextshot_struct::dsphi2

next image phi position

Definition at line 364 of file pgpmac.h.

6.11.2.60 int lspg_nextshot_struct::dsphi2_isnull

Definition at line 365 of file pgpmac.h.

6.11.2.61 int lspg_nextshot_struct::dsphi_isnull

Definition at line 311 of file pgpmac.h.

6.11.2.62 char* lspg_nextshot_struct::dspid

ID string identifying this dataset.

Definition at line 289 of file pgpmac.h.

6.11.2.63 int lspg_nextshot_struct::dspid_isnull

Definition at line 290 of file pgpmac.h.

6.11.2.64 pthread_mutex_t lspg_nextshot_struct::mutex

Our mutex for sanity in the multi-threaded program.

Definition at line 281 of file pgpmac.h.

6.11.2.65 int lspg_nextshot_struct::new_value_ready

Our flag for the condition to wait for.

Definition at line 283 of file pgpmac.h.

6.11.2.66 int lspg_nextshot_struct::no_rows_returned

flag indicating that no rows were returned.

Definition at line 284 of file pgpmac.h.

6.11.2.67 char* lspg_nextshot_struct::sfn

file name

Definition at line 307 of file pgpmac.h.

6.11.2.68 int lspg_nextshot_struct::sfn_isnull

Definition at line 308 of file pgpmac.h.

6.11.2.69 int lspg_nextshot_struct::sindex

index of frame (used to generate the file extension)

Definition at line 346 of file pgpmac.h.

6.11.2.70 int lspg_nextshot_struct::sindex2

next image index number

Definition at line 397 of file pgpmac.h.

6.11.2.71 int lspg_nextshot_struct::sindex2_isnull

Definition at line 398 of file pgpmac.h.

6.11.2.72 int lspg_nextshot_struct::sindex_isnull

Definition at line 347 of file pgpmac.h.

6.11.2.73 long long lspg_nextshot_struct::skey

key identifying a particulary image

Definition at line 301 of file pgpmac.h.

6.11.2.74 int lspg_nextshot_struct::skey_isnull

Definition at line 302 of file pgpmac.h.

6.11.2.75 double lspg_nextshot_struct::sstart

starting angle

Definition at line 304 of file pgpmac.h.

6.11.2.76 double lspg_nextshot_struct::sstart2

next image start angle

Definition at line 361 of file pgpmac.h.

6.11.2.77 int lspg_nextshot_struct::sstart2_isnull

Definition at line 362 of file pgpmac.h.

6.11.2.78 int lspg_nextshot_struct::sstart_isnull

Definition at line 305 of file pgpmac.h.

6.11.2.79 char* lspg_nextshot_struct::stype

"Normal" or "Gridsearch"

Definition at line 349 of file pgpmac.h.

6.11.2.80 char* lspg_nextshot_struct::stype2

next image type ("Normal" or "Gridsearch")

Definition at line 400 of file pgpmac.h.

6.11.2.81 int lspg_nextshot_struct::stype2_isnull

Definition at line 401 of file pgpmac.h.

6.11.2.82 int lspg_nextshot_struct::stype_isnull

Definition at line 350 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.12 | Ispg_seq_run_prep_struct Struct Reference

Data collection running object.

Data Fields

- pthread_mutex_t mutex
- pthread_cond_t cond
- · int new_value_ready

6.12.1 Detailed Description

Data collection running object.

Definition at line 1131 of file lspg.c.

6.12.2 Field Documentation

6.12.2.1 pthread_cond_t lspg_seq_run_prep_struct::cond

Definition at line 1133 of file lspg.c.

6.12.2.2 pthread_mutex_t lspg_seq_run_prep_struct::mutex

Definition at line 1132 of file lspg.c.

6.12.2.3 int lspg_seq_run_prep_struct::new_value_ready

Definition at line 1134 of file lspg.c.

The documentation for this struct was generated from the following file:

• Ispg.c

6.13 lspg_starttransfer_struct Struct Reference

returns 1 if transfer can continue 0 to abort

```
#include <pgpmac.h>
```

Data Fields

• pthread_mutex_t mutex

Our mutex.

pthread_cond_t cond

Our condition.

· int new_value_ready

flag for our condition

• int no_rows_returned

just in case, though this query should always return an integer, perhaps 0

• unsigned int starttransfer

sample number (4 8-bit segments: station, dewar (lid), puck, and position in the puck)

6.13.1 Detailed Description

returns 1 if transfer can continue 0 to abort

Definition at line 246 of file pgpmac.h.

6.13.2 Field Documentation

6.13.2.1 pthread_cond_t lspg_starttransfer_struct::cond

Our condition.

Definition at line 248 of file pgpmac.h.

6.13.2.2 pthread_mutex_t lspg_starttransfer_struct::mutex

Our mutex.

Definition at line 247 of file pgpmac.h.

6.13.2.3 int lspg_starttransfer_struct::new_value_ready

flag for our condition

Definition at line 249 of file pgpmac.h.

6.13.2.4 int lspg_starttransfer_struct::no_rows_returned

just in case, though this query should always return an integer, perhaps 0

Definition at line 250 of file pgpmac.h.

6.13.2.5 unsigned int lspg_starttransfer_struct::starttransfer

sample number (4 8-bit segments: station, dewar (lid), puck, and position in the puck)

Definition at line 252 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.14 lspg_wait_for_detector_struct Struct Reference

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

Data Fields

- pthread_mutex_t mutex
- · pthread cond t cond
- · int new_value_ready

6.14.1 Detailed Description

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

Definition at line 949 of file lspg.c.

6.14.2 Field Documentation

6.14.2.1 pthread_cond_t lspg_wait_for_detector_struct::cond

Definition at line 951 of file lspg.c.

6.14.2.2 pthread_mutex_t lspg_wait_for_detector_struct::mutex

Definition at line 950 of file Ispg.c.

6.14.2.3 int lspg_wait_for_detector_struct::new_value_ready

Definition at line 952 of file Ispg.c.

The documentation for this struct was generated from the following file:

• Ispg.c

6.15 | Ispg_waitcryo_struct Struct Reference

```
#include <pgpmac.h>
```

Data Fields

- pthread_mutex_t mutex
 practice safe threading
- pthread_cond_t cond for signaling
- · int new_value_ready

OK, there is never a value, we need a variable for the conditional wait and this is what we call it everywhere else.

6.15.1 Detailed Description

Definition at line 179 of file pgpmac.h.

6.15.2 Field Documentation

6.15.2.1 pthread_cond_t lspg_waitcryo_struct::cond

for signaling

Definition at line 181 of file pgpmac.h.

6.15.2.2 pthread_mutex_t lspg_waitcryo_struct::mutex

practice safe threading

Definition at line 180 of file pgpmac.h.

6.15.2.3 int lspg_waitcryo_struct::new_value_ready

OK, there is never a value, we need a variable for the conditional wait and this is what we call it everywhere else.

Definition at line 182 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.16 IspgQueryQueueStruct Struct Reference

Store each query along with it's callback function.

```
#include <pgpmac.h>
```

Data Fields

• char qs [LS_PG_QUERY_STRING_LENGTH]

our queries should all be pretty short as we'll just be calling functions: fixed length here simplifies memory management

void(* onResponse)(struct lspgQueryQueueStruct *qq, PGresult *pgr)

Callback function for when a guery returns a result.

6.16.1 Detailed Description

Store each query along with it's callback function.

All calls are asynchronous

Definition at line 174 of file pgpmac.h.

6.16.2 Field Documentation

6.16.2.1 void(* IspgQueryQueueStruct::onResponse)(struct IspgQueryQueueStruct *qq, PGresult *pgr)

Callback function for when a query returns a result.

Definition at line 176 of file pgpmac.h.

6.16.2.2 char lspgQueryQueueStruct::qs[LS PG QUERY STRING LENGTH]

our queries should all be pretty short as we'll just be calling functions: fixed length here simplifies memory management

Definition at line 175 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.17 Ispmac_ascii_buffers_struct Struct Reference

Data Fields

- · uint16 t command buf
- uint16_t command_buf_cc
- char command_str [160]
- uint16_t response_buf
- uint16_t response_n
- char response_str [256]

6.17.1 Detailed Description

Definition at line 354 of file Ispmac.c.

6.17.2 Field Documentation

6.17.2.1 uint16_t lspmac_ascii_buffers_struct::command_buf

Definition at line 356 of file Ispmac.c.

6.17.2.2 uint16_t lspmac_ascii_buffers_struct::command_buf_cc

Definition at line 357 of file Ispmac.c.

6.17.2.3 char lspmac_ascii_buffers_struct::command_str[160]

Definition at line 358 of file Ispmac.c.

6.17.2.4 uint16_t lspmac_ascii_buffers_struct::response_buf

Definition at line 359 of file Ispmac.c.

6.17.2.5 uint16_t lspmac_ascii_buffers_struct::response_n

Definition at line 360 of file Ispmac.c.

6.17.2.6 char lspmac_ascii_buffers_struct::response_str[256]

Definition at line 361 of file Ispmac.c.

The documentation for this struct was generated from the following file:

• Ispmac.c

6.18 Ispmac_bi_struct Struct Reference

Storage for binary inputs.

#include <pgpmac.h>

Data Fields

int * ptr

points to the location in the status buffer

pthread_mutex_t mutex

so we don't get confused

· int mask

mask for the bit in the status register

int position

the current value.

· int previous

the previous value

· int first time

flag indicating we've not read the input even once

• char * changeEventOn

Event to send when the value changes to 1.

• char * changeEventOff

Event to send when the value changes to 0.

6.18.1 Detailed Description

Storage for binary inputs.

Definition at line 159 of file pgpmac.h.

6.18.2 Field Documentation

6.18.2.1 char* lspmac_bi_struct::changeEventOff

Event to send when the value changes to 0.

Definition at line 167 of file pgpmac.h.

6.18.2.2 char* lspmac_bi_struct::changeEventOn

Event to send when the value changes to 1.

Definition at line 166 of file pgpmac.h.

6.18.2.3 int lspmac_bi_struct::first_time

flag indicating we've not read the input even once

Definition at line 165 of file pgpmac.h.

6.18.2.4 int lspmac_bi_struct::mask

mask for the bit in the status register

Definition at line 162 of file pgpmac.h.

6.18.2.5 pthread_mutex_t lspmac_bi_struct::mutex

so we don't get confused

Definition at line 161 of file pgpmac.h.

6.18.2.6 int lspmac_bi_struct::position

the current value.

Definition at line 163 of file pgpmac.h.

6.18.2.7 int lspmac_bi_struct::previous

the previous value

Definition at line 164 of file pgpmac.h.

6.18.2.8 int* lspmac_bi_struct::ptr

points to the location in the status buffer

Definition at line 160 of file pgpmac.h.

The documentation for this struct was generated from the following file:

• pgpmac.h

6.19 Ispmac_cmd_queue_struct Struct Reference

PMAC command queue item.

```
#include <pgpmac.h>
```

Data Fields

• pmac_cmd_t pcmd

the pmac command to send

· int no_reply

1 = no reply is expected, 0 = expect a reply

• struct timespec time_sent

time this item was dequeued and sent to the pmac

char * event

event name to send

• void(* onResponse)(struct lspmac_cmd_queue_struct *, int, char *)

function to call when response is received. args are (int fd, nreturned, buffer)

6.19.1 Detailed Description

PMAC command queue item.

Command queue items are fixed length to simplify memory management.

Definition at line 86 of file pgpmac.h.

6.19.2 Field Documentation

6.19.2.1 char* lspmac_cmd_queue_struct::event

event name to send

Definition at line 90 of file pgpmac.h.

6.19.2.2 int lspmac_cmd_queue_struct::no_reply

1 = no reply is expected, 0 = expect a reply

Definition at line 88 of file pgpmac.h.

6.19.2.3 void(* Ispmac_cmd_queue_struct::onResponse)(struct Ispmac_cmd_queue_struct *, int, char *)

function to call when response is received. args are (int fd, nreturned, buffer)

Definition at line 91 of file pgpmac.h.

6.19.2.4 pmac_cmd_t lspmac_cmd_queue_struct::pcmd

the pmac command to send

Definition at line 87 of file pgpmac.h.

6.19.2.5 struct timespec lspmac_cmd_queue_struct::time_sent

time this item was dequeued and sent to the pmac

Definition at line 89 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.20 Ispmac_combined_move_struct Struct Reference

Data Fields

- int Delta
- int moveme
- int coord_num
- char axis

6.20.1 Detailed Description

Definition at line 377 of file Ispmac.c.

6.20.2 Field Documentation

6.20.2.1 char lspmac_combined_move_struct::axis

Definition at line 381 of file Ispmac.c.

6.20.2.2 int lspmac_combined_move_struct::coord_num

Definition at line 380 of file Ispmac.c.

6.20.2.3 int lspmac_combined_move_struct::Delta

Definition at line 378 of file Ispmac.c.

6.20.2.4 int lspmac_combined_move_struct::moveme

Definition at line 379 of file Ispmac.c.

The documentation for this struct was generated from the following file:

· Ispmac.c

6.21 | Ispmac_dpascii_queue_struct Struct Reference

Data Fields

- · char * event
- char pl [160]

6.21.1 Detailed Description

Definition at line 368 of file Ispmac.c.

6.21.2 Field Documentation

6.21.2.1 char* lspmac_dpascii_queue_struct::event

Definition at line 369 of file Ispmac.c.

6.21.2.2 char lspmac_dpascii_queue_struct::pl[160]

Definition at line 370 of file Ispmac.c.

The documentation for this struct was generated from the following file:

• Ispmac.c

6.22 Ispmac_motor_struct Struct Reference

Motor information.

```
#include <pgpmac.h>
```

Data Fields

pthread_mutex_t mutex
 coordinate waiting for motor to be done

```
    pthread_cond_t cond

     used to signal when a motor is done moving
· int not done
     set to 1 when request is queued, zero after motion has toggled
void(* read )(struct lspmac_motor_struct *)
     method to read the motor status and position
· int command sent
     Motion command verified sent to pmac.
· int motion seen
     set to 1 when motion has been verified to have started
• pmac cmd queue t*pq
      the queue item requesting motion. Used to check time request was made

    int homing

     Homing routine started.
int requested_pos_cnts
     requested position
int * actual_pos_cnts_p
     pointer to the md2_status structure to the actual position
int actual_pos_cnts
     local copy of actual counts so only our mutex is needed to read
· double position
     scaled position
• double reported_pg_position
     previous position reported to postgresql
· double reported_position
     previous position reported to redis

    double requested_position

      The position as requested by the user.
int * status1_p
      First 24 bit PMAC motor status word.

    int status1

     local copy of status1
int * status2_p
     Sectond 24 bit PMAC motor status word.
• int status2
     local copy of status2

    char * dac mvar

     controlling mvariable as a string
char * name
     Name of motor as refered by Is database kvs table.

    Isredis_obj_t * active

      Use the motor ("true") or not ("false")
Isredis_obj_t * active_init
      pmac commands to make this motor active
lsredis_obj_t * axis
     the axis (X, Y, Z, etc) or null if not in a coordinate system

    Isredis_obj_t * coord_num

     coordinate system this motor belongs to (0 if none)

    Isredis obj t * home

     pmac commands to home motor

    Isredis_obj_t * inactive_init
```

```
pmac commands to inactivate the motor

    lsredis_obj_t * in_position_band

     moves within this amount are ignored UNITS ARE 1/16 COUNT
• Isredis obj t * max accel
     our maximum acceleration (cts/msec<sup>∧</sup>2)
lsredis_obj_t * max_pos
     our maximum position (soft limit)

    Isredis obj t * max speed

     our maximum speed (cts/msec)
Isredis_obj_t * min_pos
     our minimum position (soft limit)
• Isredis_obj_t * motor_num
     pmac motor number
lsredis_obj_t * neutral_pos
     zero offset

    Isredis_obj_t * pos_limit_hit

     positive limit status
• Isredis_obj_t * neg_limit_hit
     negative limit status

    Isredis obj t * precision

     moves of less than this amount may be ignored
Isredis_obj_t * printf_fmt
     printf format
Isredis_obj_t * redis_fmt
      special format string to create text array for putting the position back into redis
• Isredis_obj_t * redis_position
     how we report our position to the world
Isredis_obj_t * status_str
      A talky version of the status.

    Isredis obj t * u2c

     conversion from counts to units: 0.0 means not loaded yet
lsredis_obj_t * unit
     string to use as the units
• lsredis_obj_t * update_resolution
      Change needs to be at least this big to report as a new position to the database.
char * write_fmt
      Format string to write requested position to PMAC used for binary io.
int * read ptr
      With read_mask finds bit to read for binary i/o.
· int read mask
      With read_ptr find bit to read for binary i/o.

    int(* moveAbs )(struct lspmac motor struct *, double)

      function to move the motor

    int(* jogAbs )(struct lspmac_motor_struct *, double)

      function to move the motor

    double * lut

     lookup table (instead of u2c)
· int nlut
     length of lut
• WINDOW * win
```

our ncurses window

6.22.1 Detailed Description

Motor information.

A catchall for motors and motor like objects. Not all members are used by all objects.

Definition at line 101 of file pgpmac.h.

6.22.2 Field Documentation

6.22.2.1 | Isredis_obj_t* | Ispmac_motor_struct::active

Use the motor ("true") or not ("false")

Definition at line 123 of file pgpmac.h.

6.22.2.2 | Isredis_obj_t* | Ispmac_motor_struct::active_init

pmac commands to make this motor active

Definition at line 124 of file pgpmac.h.

6.22.2.3 int lspmac_motor_struct::actual_pos_cnts

local copy of actual counts so only our mutex is needed to read

Definition at line 112 of file pgpmac.h.

6.22.2.4 int* Ispmac_motor_struct::actual_pos_cnts_p

pointer to the md2 status structure to the actual position

Definition at line 111 of file pgpmac.h.

6.22.2.5 | Isredis_obj_t* | Ispmac_motor_struct::axis

the axis (X, Y, Z, etc) or null if not in a coordinate system

Definition at line 125 of file pgpmac.h.

6.22.2.6 int lspmac_motor_struct::command_sent

Motion command verified sent to pmac.

Definition at line 106 of file pgpmac.h.

6.22.2.7 pthread_cond_t lspmac_motor_struct::cond

used to signal when a motor is done moving

Definition at line 103 of file pgpmac.h.

6.22.2.8 Isredis_obj_t* Ispmac_motor_struct::coord_num

coordinate system this motor belongs to (0 if none)

Definition at line 126 of file pgpmac.h.

6.22.2.9 char* lspmac_motor_struct::dac_mvar

controlling mvariable as a string

Definition at line 121 of file pgpmac.h.

pmac commands to home motor

Definition at line 127 of file pgpmac.h.

6.22.2.11 int lspmac_motor_struct::homing

Homing routine started.

Definition at line 109 of file pgpmac.h.

moves within this amount are ignored UNITS ARE 1/16 COUNT

Definition at line 129 of file pgpmac.h.

6.22.2.13 | Isredis_obj_t* | Ispmac_motor_struct::inactive_init

pmac commands to inactivate the motor

Definition at line 128 of file pgpmac.h.

6.22.2.14 int(* lspmac_motor_struct::jogAbs)(struct lspmac_motor_struct *, double)

function to move the motor

Definition at line 150 of file pgpmac.h.

6.22.2.15 double* Ispmac_motor_struct::lut

lookup table (instead of u2c)

Definition at line 151 of file pgpmac.h.

our maximum acceleration (cts/msec^2)

Definition at line 130 of file pgpmac.h.

our maximum position (soft limit)

Definition at line 131 of file pgpmac.h.

6.22.2.18 | Isredis_obj_t* | Ispmac_motor_struct::max_speed

our maximum speed (cts/msec)

Definition at line 132 of file pgpmac.h.

our minimum position (soft limit)

Definition at line 133 of file pgpmac.h.

6.22.2.20 int lspmac_motor_struct::motion_seen

set to 1 when motion has been verified to have started

Definition at line 107 of file pgpmac.h.

6.22.2.21 | Isredis_obj_t* | Ispmac_motor_struct::motor_num

pmac motor number

Definition at line 134 of file pgpmac.h.

6.22.2.22 int(* lspmac_motor_struct::moveAbs)(struct lspmac_motor_struct *, double)

function to move the motor

Definition at line 149 of file pgpmac.h.

6.22.2.23 pthread_mutex_t lspmac_motor_struct::mutex

coordinate waiting for motor to be done

Definition at line 102 of file pgpmac.h.

6.22.2.24 char* lspmac_motor_struct::name

Name of motor as refered by Is database kvs table.

Definition at line 122 of file pgpmac.h.

6.22.2.25 | Isredis_obj_t* | Ispmac_motor_struct::neg_limit_hit

negative limit status

Definition at line 137 of file pgpmac.h.

zero offset

Definition at line 135 of file pgpmac.h.

6.22.2.27 int lspmac_motor_struct::nlut

length of lut

Definition at line 152 of file pgpmac.h.

6.22.2.28 int lspmac_motor_struct::not_done

set to 1 when request is queued, zero after motion has toggled

Definition at line 104 of file pgpmac.h.

positive limit status

Definition at line 136 of file pgpmac.h.

6.22.2.30 double lspmac_motor_struct::position

scaled position

Definition at line 113 of file pgpmac.h.

6.22.2.31 pmac cmd queue t* lspmac_motor_struct::pq

the queue item requesting motion. Used to check time request was made

Definition at line 108 of file pgpmac.h.

moves of less than this amount may be ignored

Definition at line 138 of file pgpmac.h.

6.22.2.33 | Isredis_obj_t* | Ispmac_motor_struct::printf_fmt

printf format

Definition at line 139 of file pgpmac.h.

6.22.2.34 void(* lspmac_motor_struct::read)(struct lspmac_motor_struct *)

method to read the motor status and position

Definition at line 105 of file pgpmac.h.

6.22.2.35 int lspmac_motor_struct::read_mask

With read_ptr find bit to read for binary i/o.

Definition at line 148 of file pgpmac.h.

6.22.2.36 int* lspmac_motor_struct::read_ptr

With read_mask finds bit to read for binary i/o.

Definition at line 147 of file pgpmac.h.

6.22.2.37 | Isredis_obj_t* | Ispmac_motor_struct::redis_fmt

special format string to create text array for putting the position back into redis

Definition at line 140 of file pgpmac.h.

how we report our position to the world

Definition at line 141 of file pgpmac.h.

6.22.2.39 double Ispmac_motor_struct::reported_pg_position

previous position reported to postgresql

Definition at line 114 of file pgpmac.h.

6.22.2.40 double lspmac_motor_struct::reported_position

previous position reported to redis

Definition at line 115 of file pgpmac.h.

6.22.2.41 int lspmac_motor_struct::requested_pos_cnts

requested position

Definition at line 110 of file pgpmac.h.

6.22.2.42 double Ispmac_motor_struct::requested_position

The position as requested by the user.

Definition at line 116 of file pgpmac.h.

6.22.2.43 int lspmac_motor_struct::status1

local copy of status1

Definition at line 118 of file pgpmac.h.

6.22.2.44 int* lspmac_motor_struct::status1_p

First 24 bit PMAC motor status word.

Definition at line 117 of file pgpmac.h.

6.22.2.45 int lspmac_motor_struct::status2

local copy of status2

Definition at line 120 of file pgpmac.h.

6.22.2.46 int* Ispmac_motor_struct::status2_p

Sectond 24 bit PMAC motor status word.

Definition at line 119 of file pgpmac.h.

6.22.2.47 | Isredis_obj_t* | Ispmac_motor_struct::status_str

A talky version of the status.

Definition at line 142 of file pgpmac.h.

6.22.2.48 | Isredis_obj_t* | Ispmac_motor_struct::u2c

conversion from counts to units: 0.0 means not loaded yet

Definition at line 143 of file pgpmac.h.

string to use as the units

Definition at line 144 of file pgpmac.h.

6.22.2.50 | Isredis_obj_t* | Ispmac_motor_struct::update_resolution

Change needs to be at least this big to report as a new position to the database.

Definition at line 145 of file pgpmac.h.

6.22.2.51 WINDOW* Ispmac_motor_struct::win

our ncurses window

Definition at line 153 of file pgpmac.h.

6.22.2.52 char* lspmac_motor_struct::write_fmt

Format string to write requested position to PMAC used for binary io.

Definition at line 146 of file pgpmac.h.

The documentation for this struct was generated from the following file:

• pgpmac.h

6.23 | Isredis_obj_struct Struct Reference

Redis Object Basic object whose value is sychronized with our redis db.

#include <pgpmac.h>

Data Fields

• pthread_mutex_t mutex

Don't let anyone use an old value.

· pthread cond t cond

wait for a valid value

struct lsredis_obj_struct * next

the next in our list (I guess this is going to be a linked list)

· char valid

1 if we think the value is good, 0 otherwise

· int wait_for_me

Number of times we need to see our publication before we start accepting new values.

char * key

The redis key for this object.

• char * events_name

Name used to generate events (normally key without the station id)

• int value_length

Number of bytes allocated for value (not value's string length)

• char * value

our value

· double dvalue

our value as a double

long int Ivalue

our value as a long

• char ** avalue

our value as an array of strings

· int bvalue

our value as a boolean (1 or 0) -1 means we couldn't figure it out

char cvalue

just the first character of our value

• int hits

number of times we've searched for this key

6.23.1 Detailed Description

Redis Object Basic object whose value is sychronized with our redis db.

Definition at line 38 of file pgpmac.h.

6.23.2 Field Documentation

6.23.2.1 char** lsredis_obj_struct::avalue

our value as an array of strings

Definition at line 50 of file pgpmac.h.

6.23.2.2 int Isredis_obj_struct::bvalue

our value as a boolean (1 or 0) -1 means we couldn't figure it out

Definition at line 51 of file pgpmac.h.

6.23.2.3 pthread_cond_t lsredis_obj_struct::cond

wait for a valid value

Definition at line 40 of file pgpmac.h.

6.23.2.4 char lsredis_obj_struct::cvalue

just the first character of our value

Definition at line 52 of file pgpmac.h.

6.23.2.5 double lsredis_obj_struct::dvalue

our value as a double

Definition at line 48 of file pgpmac.h.

6.23.2.6 char* lsredis_obj_struct::events_name

Name used to generate events (normally key without the station id)

Definition at line 45 of file pgpmac.h.

6.23.2.7 int lsredis_obj_struct::hits

number of times we've searched for this key

Definition at line 53 of file pgpmac.h.

6.23.2.8 char* lsredis_obj_struct::key

The redis key for this object.

Definition at line 44 of file pgpmac.h.

6.23.2.9 long int lsredis_obj_struct::lvalue

our value as a long

Definition at line 49 of file pgpmac.h.

6.23.2.10 pthread_mutex_t lsredis_obj_struct::mutex

Don't let anyone use an old value.

Definition at line 39 of file pgpmac.h.

6.23.2.11 struct | st

the next in our list (I guess this is going to be a linked list)

Definition at line 41 of file pgpmac.h.

6.23.2.12 char lsredis_obj_struct::valid

1 if we think the value is good, 0 otherwise

Definition at line 42 of file pgpmac.h.

6.23.2.13 char* lsredis_obj_struct::value

our value

Definition at line 47 of file pgpmac.h.

6.23.2.14 int lsredis_obj_struct::value_length

Number of bytes allocated for value (not value's string length)

Definition at line 46 of file pgpmac.h.

6.23.2.15 int lsredis_obj_struct::wait_for_me

Number of times we need to see our publication before we start accepting new values.

Definition at line 43 of file pgpmac.h.

The documentation for this struct was generated from the following file:

· pgpmac.h

6.24 Istimer_list_struct Struct Reference

Everything we need to know about a timer.

Data Fields

• int shots

run this many times: -1 means reload forever, 0 means we are done with this timer and it may be reused

· unsigned long int ncalls

track how many times we triggered a callback (like an unsigned long int is really needed)

char event [LSEVENTS_EVENT_LENGTH]

the event to send

· long int next secs

epoch (seconds) of next alarm

long int next_nsecs

nano seconds of next alarm

long int delay_secs

number of seconds for a periodic delay

· long int delay nsecs

nano seconds of delay

long int last_secs

the last time this timer was triggered

· long int last_nsecs

the last time this timer was triggered

long int init_secs

our initialization time

• long int init_nsecs

our initialization time

6.24.1 Detailed Description

Everything we need to know about a timer.

Definition at line 22 of file Istimer.c.

6.24.2 Field Documentation

6.24.2.1 long int lstimer_list_struct::delay_nsecs

nano seconds of delay

Definition at line 29 of file Istimer.c.

6.24.2.2 long int lstimer_list_struct::delay_secs

number of seconds for a periodic delay

Definition at line 28 of file Istimer.c.

6.24.2.3 char lstimer_list_struct::event[LSEVENTS_EVENT_LENGTH]

the event to send

Definition at line 25 of file Istimer.c.

6.24.2.4 long int lstimer_list_struct::init_nsecs

our initialization time

Definition at line 33 of file Istimer.c.

6.24.2.5 long int lstimer_list_struct::init_secs

our initialization time

Definition at line 32 of file Istimer.c.

6.24.2.6 long int lstimer_list_struct::last_nsecs

the last time this timer was triggered

Definition at line 31 of file Istimer.c.

6.24.2.7 long int lstimer_list_struct::last_secs

the last time this timer was triggered

Definition at line 30 of file Istimer.c.

6.24.2.8 unsigned long int lstimer_list_struct::ncalls

track how many times we triggered a callback (like an unsigned long int is really needed)

Definition at line 24 of file Istimer.c.

6.24.2.9 long int lstimer_list_struct::next_nsecs

nano seconds of next alarm

Definition at line 27 of file Istimer.c.

6.24.2.10 long int lstimer_list_struct::next_secs

epoch (seconds) of next alarm

Definition at line 26 of file Istimer.c.

6.24.2.11 int lstimer_list_struct::shots

run this many times: -1 means reload forever, 0 means we are done with this timer and it may be reused Definition at line 23 of file Istimer.c.

The documentation for this struct was generated from the following file:

· Istimer.c

6.25 md2cmds_cmd_kv_struct Struct Reference

Data Fields

- char * k
- int(* v)(const char *)

6.25.1 Detailed Description

Definition at line 39 of file md2cmds.c.

6.25.2 Field Documentation

6.25.2.1 char* md2cmds_cmd_kv_struct::k

Definition at line 40 of file md2cmds.c.

6.25.2.2 int(* md2cmds_cmd_kv_struct::v)(const char *)

Definition at line 41 of file md2cmds.c.

The documentation for this struct was generated from the following file:

• md2cmds.c

6.26 md2StatusStruct Struct Reference

The block of memory retrieved in a status request.

Data Fields

- int dummy1
- int omega_status_1
- int alignx_status_1
- int aligny_status_1
- int alignz_status_1
- int analyzer_status_1
- int zoom_status_1
- int aperturey_status_1
- int aperturez_status_1
- int capy_status_1
- · int capz_status_1
- · int scint_status_1
- int centerx_status_1
- int centery_status_1
- int kappa_status_1
- int phi_status_1
- int dummy2
- int omega_status_2
- int alignx_status_2
- int aligny_status_2
- int alignz_status_2
- int analyzer_status_2
- int zoom_status_2
- int aperturey_status_2
- int aperturez_status_2
- int capy_status_2
- int capz_status_2
- int scint_status_2
- int centerx_status_2
- int centery_status_2
- int kappa_status_2
- int phi_status_2
- int dummy3
- int omega_act_pos
- int alignx_act_pos
- int aligny_act_pos
- int alignz_act_pos
- int analyzer_act_pos
- int zoom_act_pos
- int aperturey_act_pos
- int aperturez_act_pos
- int capy_act_pos
- int capz_act_pos
- int scint_act_pos
- int centerx_act_pos
- int centery_act_pos
- int kappa_act_pos
- int phi_act_pos

- int acc11c_1
- int acc11c_2
- int acc11c_3
- int acc11c_5
- int acc11c_6
- int front_dac
- int back_dac
- · int scint piezo
- int dummy4
- int dummy5
- int dummy6
- int dummy7
- int dummy8
- int dummy9
- · int dummyA
- · int dummyB
- int fs_is_open
- int phiscan
- int fs_has_opened
- int fs_has_opened_globally
- int number_passes
- int moving_flags

6.26.1 Detailed Description

The block of memory retrieved in a status request.

Definition at line 255 of file Ispmac.c.

6.26.2 Field Documentation

6.26.2.1 int md2StatusStruct::acc11c_1

Definition at line 322 of file Ispmac.c.

6.26.2.2 int md2StatusStruct::acc11c_2

Definition at line 323 of file Ispmac.c.

6.26.2.3 int md2StatusStruct::acc11c_3

Definition at line 324 of file Ispmac.c.

6.26.2.4 int md2StatusStruct::acc11c_5

Definition at line 325 of file Ispmac.c.

6.26.2.5 int md2StatusStruct::acc11c_6

Definition at line 326 of file Ispmac.c.

6.26.2.6 int md2StatusStruct::alignx_act_pos

Definition at line 306 of file Ispmac.c.

6.26.2.7 int md2StatusStruct::alignx_status_1

Definition at line 272 of file Ispmac.c.

6.26.2.8 int md2StatusStruct::alignx_status_2

Definition at line 289 of file Ispmac.c.

6.26.2.9 int md2StatusStruct::aligny_act_pos

Definition at line 307 of file Ispmac.c.

6.26.2.10 int md2StatusStruct::aligny_status_1

Definition at line 273 of file Ispmac.c.

6.26.2.11 int md2StatusStruct::aligny_status_2

Definition at line 290 of file Ispmac.c.

6.26.2.12 int md2StatusStruct::alignz_act_pos

Definition at line 308 of file Ispmac.c.

6.26.2.13 int md2StatusStruct::alignz_status_1

Definition at line 274 of file Ispmac.c.

6.26.2.14 int md2StatusStruct::alignz_status_2

Definition at line 291 of file Ispmac.c.

6.26.2.15 int md2StatusStruct::analyzer_act_pos

Definition at line 309 of file Ispmac.c.

6.26.2.16 int md2StatusStruct::analyzer_status_1

Definition at line 275 of file Ispmac.c.

6.26.2.17 int md2StatusStruct::analyzer_status_2

Definition at line 292 of file Ispmac.c.

6.26.2.18 int md2StatusStruct::aperturey_act_pos

Definition at line 311 of file Ispmac.c.

6.26.2.19 int md2StatusStruct::aperturey_status_1

Definition at line 277 of file Ispmac.c.

6.26.2.20 int md2StatusStruct::aperturey_status_2

Definition at line 294 of file Ispmac.c.

6.26.2.21 int md2StatusStruct::aperturez_act_pos

Definition at line 312 of file Ispmac.c.

6.26.2.22 int md2StatusStruct::aperturez_status_1

Definition at line 278 of file Ispmac.c.

6.26.2.23 int md2StatusStruct::aperturez_status_2

Definition at line 295 of file Ispmac.c.

6.26.2.24 int md2StatusStruct::back_dac

Definition at line 328 of file Ispmac.c.

6.26.2.25 int md2StatusStruct::capy_act_pos

Definition at line 313 of file Ispmac.c.

6.26.2.26 int md2StatusStruct::capy_status_1

Definition at line 279 of file Ispmac.c.

6.26.2.27 int md2StatusStruct::capy_status_2

Definition at line 296 of file Ispmac.c.

6.26.2.28 int md2StatusStruct::capz_act_pos

Definition at line 314 of file Ispmac.c.

6.26.2.29 int md2StatusStruct::capz_status_1

Definition at line 280 of file Ispmac.c.

6.26.2.30 int md2StatusStruct::capz_status_2 Definition at line 297 of file Ispmac.c. 6.26.2.31 int md2StatusStruct::centerx_act_pos Definition at line 316 of file Ispmac.c. 6.26.2.32 int md2StatusStruct::centerx_status_1 Definition at line 282 of file Ispmac.c. 6.26.2.33 int md2StatusStruct::centerx_status_2 Definition at line 299 of file Ispmac.c. 6.26.2.34 int md2StatusStruct::centery_act_pos Definition at line 317 of file Ispmac.c. 6.26.2.35 int md2StatusStruct::centery_status_1 Definition at line 283 of file Ispmac.c. 6.26.2.36 int md2StatusStruct::centery_status_2 Definition at line 300 of file Ispmac.c. 6.26.2.37 int md2StatusStruct::dummy1 Definition at line 270 of file Ispmac.c. 6.26.2.38 int md2StatusStruct::dummy2 Definition at line 287 of file Ispmac.c. 6.26.2.39 int md2StatusStruct::dummy3 Definition at line 304 of file Ispmac.c. 6.26.2.40 int md2StatusStruct::dummy4 Definition at line 331 of file Ispmac.c. 6.26.2.41 int md2StatusStruct::dummy5

Definition at line 332 of file Ispmac.c.

6.26.2.42 int md2StatusStruct::dummy6 Definition at line 333 of file Ispmac.c. 6.26.2.43 int md2StatusStruct::dummy7 Definition at line 334 of file Ispmac.c. 6.26.2.44 int md2StatusStruct::dummy8 Definition at line 335 of file Ispmac.c. 6.26.2.45 int md2StatusStruct::dummy9 Definition at line 336 of file Ispmac.c. 6.26.2.46 int md2StatusStruct::dummyA Definition at line 337 of file Ispmac.c. 6.26.2.47 int md2StatusStruct::dummyB Definition at line 338 of file Ispmac.c. 6.26.2.48 int md2StatusStruct::front_dac Definition at line 327 of file Ispmac.c. 6.26.2.49 int md2StatusStruct::fs_has_opened Definition at line 342 of file Ispmac.c. 6.26.2.50 int md2StatusStruct::fs_has_opened_globally Definition at line 343 of file Ispmac.c. 6.26.2.51 int md2StatusStruct::fs_is_open Definition at line 340 of file Ispmac.c.

6.26.2.52 int md2StatusStruct::kappa_act_pos Definition at line 318 of file Ispmac.c.

6.26.2.53 int md2StatusStruct::kappa_status_1

Definition at line 284 of file Ispmac.c.

6.26.2.54 int md2StatusStruct::kappa_status_2

Definition at line 301 of file Ispmac.c.

6.26.2.55 int md2StatusStruct::moving_flags

Definition at line 346 of file Ispmac.c.

6.26.2.56 int md2StatusStruct::number_passes

Definition at line 344 of file Ispmac.c.

6.26.2.57 int md2StatusStruct::omega_act_pos

Definition at line 305 of file Ispmac.c.

6.26.2.58 int md2StatusStruct::omega_status_1

Definition at line 271 of file Ispmac.c.

6.26.2.59 int md2StatusStruct::omega_status_2

Definition at line 288 of file Ispmac.c.

6.26.2.60 int md2StatusStruct::phi_act_pos

Definition at line 319 of file Ispmac.c.

6.26.2.61 int md2StatusStruct::phi_status_1

Definition at line 285 of file Ispmac.c.

6.26.2.62 int md2StatusStruct::phi_status_2

Definition at line 302 of file Ispmac.c.

6.26.2.63 int md2StatusStruct::phiscan

Definition at line 341 of file Ispmac.c.

6.26.2.64 int md2StatusStruct::scint_act_pos

Definition at line 315 of file Ispmac.c.

6.26.2.65 int md2StatusStruct::scint_piezo

Definition at line 329 of file Ispmac.c.

6.26.2.66 int md2StatusStruct::scint_status_1

Definition at line 281 of file Ispmac.c.

6.26.2.67 int md2StatusStruct::scint_status_2

Definition at line 298 of file Ispmac.c.

6.26.2.68 int md2StatusStruct::zoom_act_pos

Definition at line 310 of file Ispmac.c.

6.26.2.69 int md2StatusStruct::zoom_status_1

Definition at line 276 of file Ispmac.c.

6.26.2.70 int md2StatusStruct::zoom_status_2

Definition at line 293 of file Ispmac.c.

The documentation for this struct was generated from the following file:

· Ispmac.c

6.27 tagEthernetCmd Struct Reference

PMAC ethernet packet definition.

#include <pgpmac.h>

Data Fields

• unsigned char RequestType

VR_UPLOAD or VR_DOWNLOAD.

unsigned char Request

The command to run (VR_PMAC_GETMEM, etc).

• unsigned short wValue

Command parameter 1.

· unsigned short windex

Command parameter 2.

unsigned short wLength

Number of bytes in bData.

• unsigned char bData [1492]

The data buffer, if required.

6.27.1 Detailed Description

PMAC ethernet packet definition.

Taken directly from the Delta Tau documentation.

Definition at line 73 of file pgpmac.h.

6.27.2 Field Documentation

6.27.2.1 unsigned char tagEthernetCmd::bData[1492]

The data buffer, if required.

Definition at line 79 of file pgpmac.h.

6.27.2.2 unsigned char tagEthernetCmd::Request

The command to run (VR_PMAC_GETMEM, etc).

Definition at line 75 of file pgpmac.h.

6.27.2.3 unsigned char tagEthernetCmd::RequestType

VR_UPLOAD or VR_DOWNLOAD.

Definition at line 74 of file pgpmac.h.

6.27.2.4 unsigned short tagEthernetCmd::wIndex

Command parameter 2.

Definition at line 77 of file pgpmac.h.

6.27.2.5 unsigned short tagEthernetCmd::wLength

Number of bytes in bData.

Definition at line 78 of file pgpmac.h.

6.27.2.6 unsigned short tagEthernetCmd::wValue

Command parameter 1.

Definition at line 76 of file pgpmac.h.

The documentation for this struct was generated from the following file:

• pgpmac.h

Chapter 7

File Documentation

7.1 iniParser.py File Reference

Data Structures

· class iniParser.iniParser

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

Namespaces

• namespace iniParser

Variables

• tuple iniParser.ip iniParser("21-ID-E/microdiff_hard.ini")

7.2 Isevents.c File Reference

event subsystem for inter-pgpmac communication

```
#include "pgpmac.h"
```

Data Structures

• struct lsevents_queue_struct

Storage definition for the events.

• struct lsevents_listener_struct

Linked list of event listeners.

Macros

• #define LSEVENTS_QUEUE_LENGTH 512

70 File Documentation

Typedefs

```
· typedef struct
```

Isevents_queue_struct Isevents_queue_t

Storage definition for the events.

· typedef struct

Isevents_listener_struct Isevents_listener_t

Linked list of event listeners.

Functions

void lsevents_send_event (char *fmt,...)

Call the callback routines for the given event.

void lsevents_add_listener (char *event, void(*cb)(char *))

Add a callback routine to listen for a specific event.

void lsevents_remove_listener (char *event, void(*cb)(char *))

Remove a listener previously added with Isevents_add_listener.

void * Isevents_worker (void *dummy)

Our worker.

· void Isevents_init ()

Initialize this module.

• void Isevents run ()

Start up the thread and get out of the way.

Variables

static lsevents_queue_t lsevents_queue [LSEVENTS_QUEUE_LENGTH]

simple list of events

• static unsigned int Isevents queue on = 0

next queue location to write

• static unsigned int lsevents_queue_off = 0

next queue location to read

• static Isevents listener t * Isevents listeners p = NULL

Pointer to the first item in the link list of listeners.

static pthread_t lsevents_thread

thread to run the event queue

static pthread_mutex_t lsevents_listener_mutex

mutex to protect the listener linked list

static pthread_mutex_t lsevents_queue_mutex

mutex to protect the event queue

static pthread_cond_t lsevents_queue_cond

condition to pause the queue if needed

7.2.1 Detailed Description

event subsystem for inter-pgpmac communication

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file Isevents.c.

7.2.2 Macro Definition Documentation

7.2.2.1 #define LSEVENTS_QUEUE_LENGTH 512

Definition at line 10 of file Isevents.c.

7.2.3 Typedef Documentation

7.2.3.1 typedef struct Isevents_listener_struct Isevents_listener_t

Linked list of event listeners.

7.2.3.2 typedef struct Isevents_queue_struct Isevents_queue_t

Storage definition for the events.

Just a string for now. Perhaps one day we'll succumb to the temptation to add an argument or two.

7.2.4 Function Documentation

7.2.4.1 void | sevents_add_listener (char * event, void(*)(char *) cb)

Add a callback routine to listen for a specific event.

Parameters

event	the name of the event to listen for
cb	the routine to call

Definition at line 72 of file Isevents.c.

```
lsevents_listener_t *new;
int err;
char *errbuf;
int nerrbuf;

new = calloc( 1, sizeof( lsevents_listener_t));
if( new == NULL) {
    lslogging_log_message( "lsevents_add_listener: out of memory");
    exit( -1);
}

err = regcomp( &new->re, event, REG_EXTENDED | REG_NOSUB);
if( err != 0) {
    nerrbuf = regerror( err, &new->re, NULL, 0);
    errbuf = calloc( nerrbuf, sizeof( char));
    if( errbuf == NULL) {
        lslogging_log_message( "lsevents_add_listener: out
```

72 File Documentation

```
of memory (re)");
    exit( -1);
}
regerror( err, &new->re, errbuf, nerrbuf);
lslogging_log_message( "lsevents_add_listener: %s",
    errbuf);
free( errbuf);
free( new);
return;
}

new->raw_regexp = strdup( event);
new->cb = cb;

pthread_mutex_lock( &lsevents_listener_mutex);
new->next = lsevents_listeners_p;
lsevents_listeners_p = new;
pthread_mutex_unlock( &lsevents_listener_mutex);

lslogging_log_message( "lsevents_add_listener: added
    listener for event %s", event);
```

7.2.4.2 void Isevents_init ()

Initialize this module.

Definition at line 211 of file Isevents.c.

```
pthread_mutex_init( &lsevents_queue_mutex, NULL);
pthread_cond_init( &lsevents_queue_cond, NULL);
pthread_mutex_init( &lsevents_listener_mutex, NULL);
}
```

7.2.4.3 void lsevents_remove_listener (char * event, void(*)(char *) cb)

Remove a listener previously added with Isevents_add_listener.

Parameters

event	The name of the event
cb	The callback routine to remove

Definition at line 117 of file Isevents.c.

```
lsevents_listener_t *last, *current;
// Find the listener to remove
// and unlink it from the list
pthread_mutex_lock( &lsevents_listener_mutex);
last = NULL;
for( current = lsevents_listeners_p; current != NULL;
    current = current->next) {
  if( strcmp( last->raw_regexp, event) == 0 && last->cb == cb) {
    if ( last == NULL) {
     lsevents_listeners_p = current->next;
    } else {
     last->next = current->next;
    break;
  }
pthread_mutex_unlock( &lsevents_listener_mutex);
// Now remove it
```

```
if( current != NULL) {
   if( current->raw_regexp != NULL)
     free( current->raw_regexp);
   free(current);
}
```

7.2.4.4 void lsevents_run ()

Start up the thread and get out of the way.

Definition at line 219 of file Isevents.c.

```
pthread_create( &lsevents_thread, NULL, lsevents_worker
    , NULL);
}
```

7.2.4.5 void lsevents_send_event (char * fmt, ...)

Call the callback routines for the given event.

Parameters

fmt	a printf style formating string
	list of arguments specified by the format string

Definition at line 45 of file Isevents.c.

7.2.4.6 void* lsevents_worker (void * dummy)

Our worker.

Parameters

|--|

Definition at line 152 of file Isevents.c.

{

74 File Documentation

```
// char *event;
lsevents_queue_t *ep;
lsevents_listener_t *p;
while(1) {
 pthread_mutex_lock( &lsevents_queue_mutex);
  while( lsevents_queue_off == lsevents_queue_on
   pthread_cond_wait( &lsevents_queue_cond, &
    lsevents_queue_mutex);
  ^{\prime\prime} // copy event string since the value in the queue may change when
  // we unlock the mutex
  ep = &(lsevents_queue[(lsevents_queue_off++
   ) % LSEVENTS_QUEUE_LENGTH]);
  // let the send event process know there is room on the queue again
  pthread_cond_signal( &lsevents_queue_cond);
 pthread_mutex_unlock( &lsevents_queue_mutex);
  // Find the callbacks and, well, call them back
  // TODO:
  // Yes, this is O(N).
  // Plan to make this O(1):
  // track actual event names from send_event
  // match listeners for new event names
  // store matchs in hash table
  // That makes send_event for new events O(N) // but O(1) otherwise, O(N) for add_listener, and O(1) here.
  pthread_mutex_lock( &lsevents_listener_mutex);
  for( p = lsevents_listeners_p; p != NULL; p = p->next
    if( regexec( &p->re, ep->evp, 0, NULL, 0) == 0) {
     p->cb (ep->evp);
  free ( ep->evp);
  pthread_mutex_unlock( &lsevents_listener_mutex);
return NULL;
```

7.2.5 Variable Documentation

7.2.5.1 pthread_mutex_t | sevents_listener_mutex [static]

mutex to protect the listener linked list

Definition at line 37 of file Isevents.c.

7.2.5.2 | Isevents_listener_t*| Isevents_listeners_p = NULL [static]

Pointer to the first item in the link list of listeners.

Definition at line 34 of file Isevents.c.

7.2.5.3 | Isevents_queue_t | Isevents_queue[LSEVENTS_QUEUE_LENGTH] [static]

simple list of events

Definition at line 21 of file Isevents.c.

7.2.5.4 pthread_cond_t lsevents_queue_cond [static]

condition to pause the queue if needed

Definition at line 39 of file Isevents.c.

7.2.5.5 pthread_mutex_t | sevents_queue_mutex [static]

mutex to protect the event queue

Definition at line 38 of file Isevents.c.

7.2.5.6 unsigned int lsevents_queue_off = 0 [static]

next queue location to read

Definition at line 23 of file Isevents.c.

7.2.5.7 unsigned int lsevents_queue_on = 0 [static]

next queue location to write

Definition at line 22 of file Isevents.c.

7.2.5.8 pthread_t | sevents_thread [static]

thread to run the event queue

Definition at line 36 of file Isevents.c.

7.3 Islogging.c File Reference

Logs messages to a file.

#include "pgpmac.h"

Data Structures

• struct Islogging_queue_struct

Our log object: time and message.

Macros

- #define LSLOGGING_FILE_NAME "/tmp/pgpmac.log"
 Full name of the log file.
- #define LSLOGGING_MSG_LENGTH 2048

Fixed maximum length messages to keep some form of sanity.

• #define LSLOGGING_QUEUE_LENGTH 8192

Modest length queue.

Typedefs

 typedef struct lslogging_queue_struct lslogging_queue_t
 Our log object: time and message.

Functions

• void Islogging_init ()

Initialize the Islogging objects.

• void lslogging_log_message (char *fmt,...)

The routine everyone will be talking about.

void Islogging_event_cb (char *event)

Log most events.

void * Islogging_worker (void *dummy)

Service the queue, write to the file.

• void lslogging_run ()

Start up the worker thread.

Variables

static pthread_t lslogging_thread

our thread

static pthread_mutex_t lslogging_mutex

mutex to keep the various threads from adding to the queue at the exact same time

• static pthread_cond_t lslogging_cond

We'll spend most of our time waiting for this condition's signal.

• static FILE * Islogging_file

our log file object

• static Islogging_queue_t Islogging_queue [LSLOGGING_QUEUE_LENGTH]

Our entire queue. Right here. Every message we'll ever write.

• static unsigned int Islogging_on = 0

next location to add to the queue

• static unsigned int Islogging_off = 0

next location to remove from the queue

7.3.1 Detailed Description

Logs messages to a file.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file Islogging.c.

7.3.2 Macro Definition Documentation

7.3.2.1 #define LSLOGGING_FILE_NAME "/tmp/pgpmac.log"

Full name of the log file.

Probably should be in /var/log/pgpmac.

Definition at line 16 of file Islogging.c.

7.3.2.2 #define LSLOGGING_MSG_LENGTH 2048

Fixed maximum length messages to keep some form of sanity.

Definition at line 20 of file Islogging.c.

7.3.2.3 #define LSLOGGING_QUEUE_LENGTH 8192

Modest length queue.

Definition at line 30 of file Islogging.c.

7.3.3 Typedef Documentation

7.3.3.1 typedef struct Islogging_queue_struct Islogging_queue_t

Our log object: time and message.

7.3.4 Function Documentation

```
7.3.4.1 void lslogging_event_cb ( char * event )
```

Log most events.

Definition at line 76 of file Islogging.c.

```
if( strcmp( event, "Timer Update KVs") != 0) {
  lslogging_log_message( "EVENT: %s", event);
}
```

7.3.4.2 void Islogging_init()

Initialize the Islogging objects.

Definition at line 37 of file Islogging.c.

7.3.4.3 void Islogging_log_message (char * fmt, ...)

The routine everyone will be talking about.

Parameters

fmt	A printf style formating string.	
	The arguments specified by fmt	

Definition at line 48 of file Islogging.c.

7.3.4.4 void Islogging_run ()

Start up the worker thread.

Definition at line 114 of file Islogging.c.

```
fpthread_create( &lslogging_thread, NULL, &lslogging_worker
    , NULL);
lslogging_log_message( "Start up");
lsevents_add_listener( ".+", lslogging_event_cb
    );
```

7.3.4.5 void* Islogging_worker (void * dummy)

Service the queue, write to the file.

Parameters

in	dummy	Required by protocol but unused

Definition at line 85 of file Islogging.c.

{

```
struct tm coarsetime;
char tstr[64];
unsigned int msecs;
unsigned int off;
pthread_mutex_lock( &lslogging_mutex);
while(1) {
  while( lslogging_on == lslogging_off) {
   pthread_cond_wait( &lslogging_cond, &lslogging_mutex
  off = (lslogging_off++) % LSLOGGING_QUEUE_LENGTH
  localtime_r( &(lslogging_queue[off].ltime.tv_sec), &
   coarsetime);
  strftime( tstr, sizeof(tstr)-1, "%Y-%m-%d %H:%M:%S", &coarsetime);
  tstr[sizeof(tstr)-1] = 0;
 msecs = lslogging_queue[off].ltime.tv_nsec / 1000;
 fprintf( lslogging_file, "%s.%.06u %s\n", tstr, msecs,
    lslogging_queue[off].lmsg);
 fflush( lslogging_file);
```

7.3.5 Variable Documentation

```
7.3.5.1 pthread_cond_t lslogging_cond [static]
```

We'll spend most of our time waiting for this condition's signal.

Definition at line 12 of file Islogging.c.

```
7.3.5.2 FILE* Islogging_file [static]
```

our log file object

Definition at line 17 of file Islogging.c.

```
7.3.5.3 pthread_mutex_t lslogging_mutex [static]
```

mutex to keep the various threads from adding to the queue at the exact same time Definition at line 11 of file Islogging.c.

```
7.3.5.4 unsigned int |slogging_off = 0 [static]
```

next location to remove from the queue

Definition at line 34 of file Islogging.c.

```
7.3.5.5 unsigned int slogging_on = 0 [static]
```

next location to add to the queue

Definition at line 33 of file Islogging.c.

7.3.5.6 Islogging_queue_t Islogging_queue[LSLOGGING_QUEUE_LENGTH] [static]

Our entire queue. Right here. Every message we'll ever write.

Definition at line 31 of file Islogging.c.

7.3.5.7 pthread_t lslogging_thread [static]

our thread

Definition at line 10 of file Islogging.c.

7.4 Ispg.c File Reference

Postgresql support for the LS-CAT pgpmac project.

```
#include "pgpmac.h"
```

Data Structures

• struct lspg_wait_for_detector_struct

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

struct lspg_lock_diffractometer_struct

Object used to impliment locking the diffractometer Critical to exposure timing.

struct lspg_lock_detector_struct

lock detector object Implements detector lock for exposure control

struct lspg_seq_run_prep_struct

Data collection running object.

Macros

- #define LS PG STATE INIT -4
- #define LS_PG_STATE_INIT_POLL -3
- #define LS PG STATE RESET -2
- #define LS PG STATE RESET POLL -1
- #define LS_PG_STATE_IDLE 1
- #define LS_PG_STATE_SEND 2
- #define LS PG STATE SEND FLUSH 3
- #define LS_PG_STATE_RECV 4
- #define LS_PG_QUERY_QUEUE_LENGTH 16384

Queue length should be long enough that we do not ordinarly bump into the end We should be safe as long as the thread the adds stuff to the queue is not the one that removes it.

Typedefs

· typedef struct

```
lspg_wait_for_detector_struct lspg_wait_for_detector_t
```

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

· typedef struct

```
lspg lock diffractometer struct lspg lock diffractometer t
```

Object used to impliment locking the diffractometer Critical to exposure timing.

· typedef struct

```
lspg_lock_detector_struct lspg_lock_detector_t
```

lock detector object Implements detector lock for exposure control

· typedef struct

```
lspg_seq_run_prep_struct lspg_seq_run_prep_t
```

Data collection running object.

Functions

```
    lspg_query_queue_t * lspg_query_next ()

      Return the next item in the postgresql queue.

    void lspg query reply next ()

      Remove the oldest item in the queue.

    lspg_query_queue_t * lspg_query_reply_peek ()

      Return the next item in the reply queue but don't pop it since we may need it more than once.
void lspg_query_push (void(*cb)(lspg_query_queue_t *, PGresult *), char *fmt,...)
      Place a query on the queue.
char ** lspg_array2ptrs (char *a)
      returns a null terminated list of strings parsed from postgresql array

    void lspg_allkvs_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      set a redis variable based on an updated kv pair

    void lspg_update_kvs_cb (char *event)

      Perhaps update the px.kvs table in postgresql Should be triggered by a timer event.

    void lspg_starttransfer_init ()

    void lspg_starttransfer_cb (lspg_query_queue_t *qqp, PGresult *pgr)

• void lspg_starttransfer_call (unsigned int nextsample, int sample_detected, double ax, double ay, double az,
  double horz, double vert, double esttime)

    void lspg_starttransfer_wait ()

• void lspg starttransfer done ()
• int lspg_starttransfer_all (int *err, unsigned int nextsample, int sampledetected, double ax, double ay, double
  az, double horz, double vert, double esttime)

    void lspg_getcurrentsampleid_init ()

    void lspg_getcurrentsampleid_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      get currentsampleid

    void lspg_getcurrentsampleid_call ()

    unsigned int lspg getcurrentsampleid read ()

    void lspg_getcurrentsampleid_wait_for_id (unsigned int test)

void lspg_nextsample_cb (lspg_query_queue_t *qqp, PGresult *pgr)
      Next Sample.

    void lspg_nextsample_init ()

      Initialize the nextsample variable, mutex, and condition.

    void lspg_nextsample_call ()

      Queue up a nextsample query.
void lspg_nextsample_wait ()
      Wait for the nextsample query to get processed.

    void lspg nextsample done ()

      Called when the next shot query has been processed.
• unsigned int lspg_nextsample_all (int *err)

    void lspg waiteryo init ()

    void lspg_waitcryo_cb (lspg_query_queue_t *qqp, PGresult *pgr)

    void lspg waiteryo all ()

      no need to get fancy with the wait cryo command It should not return until the robot is almost ready for air rights

    void lspg_demandairrights_init()

      initialize the demandairrights structure

    void lspg_demandairrights_cb (lspg_query_queue_t *qqp, PGresult *pgr)

     handle the airrights response
· void lspg_demandairrights_call ()
      call for airrights

    void lspg_demandairrights_wait ()
```

```
wait for the air rights request to return
void lspg_demandairrights_all ()
      do nothing until we get airrights
• void lspg_nextshot_cb (lspg_query_queue_t *qqp, PGresult *pgr)
      Next Shot Callback.
void lspg_nextshot_init ()
      Initialize the nextshot variable, mutex, and condition.

    void lspg nextshot call ()

      Queue up a nextshot query.
void lspg_nextshot_wait ()
      Wait for the next shot query to get processed.
void lspg_nextshot_done ()
      Called when the next shot query has been processed.
void lspg_wait_for_detector_init ()
      initialize the detector timing object

    void lspg_wait_for_detector_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Callback for the wait for detector query.

    void lspg_wait_for_detector_call ()

      initiate the wait for detector query

    void lspg wait for detector wait ()

      Pause the calling thread until the detector is ready Called by the MD2 thread.

    void lspg_wait_for_detector_done ()

      Done waiting for the detector.

    void lspg_wait_for_detector_all ()

      Combined call to wait for the detector.

    void lspg_lock_diffractometer_init ()

      initialize the diffractometer locking object

    void lspg_lock_diffractometer_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Callback routine for a lock diffractometer query.
· void lspg lock diffractometer call ()
      Request that the database grab the diffractometer lock.

    void lspg lock diffractometer wait ()

      Wait for the diffractometer lock.

    void lspg_lock_diffractometer_done ()

      Finish up the lock diffractometer call.

    void lspg_lock_diffractometer_all ()

      Convience function that combines lock diffractometer calls.

    void lspg_lock_detector_init ()

      Initialize detector lock object.

    void lspg_lock_detector_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Callback for when the detector lock has be grabbed.

    void lspg_lock_detector_call ()

      Request (demand) a detector lock.

    void lspg_lock_detector_wait ()

      Wait for the detector lock.

    void lspg_lock_detector_done ()

      Finish waiting.
void lspg_lock_detector_all ()
      Detector lock convinence function.
void lspg_seq_run_prep_init ()
      Initialize the data collection object.
```

```
    void lspg_seq_run_prep_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Callback for the seq_run_prep query.
• void lspg_seq_run_prep_call (long long skey, double kappa, double phi, double cx, double cy, double ax,
  double ay, double az)
      queue up the seq_run_prep query
void lspg_seq_run_prep_wait ()
      Wait for seq run prep query to return.

    void lspg seq run prep done ()

      Indicate we are done waiting.
• void lspg_seq_run_prep_all (long long skey, double kappa, double phi, double cx, double cy, double ax,
  double ay, double az)
      Convinence function to call seq run prep.

    void lspg_getcenter_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Retrieve the data to center the crystal.

    void lspg_getcenter_init ()

      Initialize getcenter object.

    void lspg_getcenter_call ()

      Request a getcenter query.

    void lspg_getcenter_wait()

      Wait for a getcenter query to return.

    void lspg_getcenter_done ()

     Done with getcenter query.

    void lspg getcenter all ()

      Convenience function to complete synchronous getcenter query.

    void lspg_nextaction_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Queue the next MD2 instruction.

    void lspg_cmd_cb (lspg_query_queue_t *qqp, PGresult *pgr)

      Send strings directly to PMAC queue.
void lspg_flush ()
      Flush psql output buffer (ie, send the query)

    void lspg_send_next_query ()

      send the next queued query to the DB server

    void lspg receive ()

      Receive a result of a query.

    void lspg_sig_service (struct pollfd *evt)

      Service a signal Signals here are treated as file descriptors and fits into our poll scheme.

    void lspg_pg_service (struct pollfd *evt)

      I/O control to/from the postgresql server.

    PQnoticeProcessor lspg_notice_processor (void *arg, const char *msg)

void lspg_pg_connect ()
      Connect to the pg server.
void lspg_next_state ()
      Implements our state machine Does not strictly only set the next state as it also calls some functions that, perhaps,
      alters the state mid-function.

    void * lspg worker (void *dummy)

      The main loop for the lspg thread.

    void lspg_preset_changed_cb (char *event)

    void lspg_check_preset_in_position_cb (char *event)

    void lspg_unset_current_preset_moving_cb (char *event)

    void lspg_set_scale_cb (char *event)

      Fix up xscale and yscale when zoom changes.
```

```
    void lspg_sample_detector_cb (char *event)

          log magnet state

    void lspg_init ()

          Initiallize the Ispg module.
    void lspg_run ()
          Start 'er runnin'.
Variables
    • static int Is_pg_state = LS_PG_STATE_INIT
          State of the Ispg state machine.
    · static struct timeval
      Ispg time sent now
          used to ensure we do not inundate the db server with connection requests

    static pthread_t lspg_thread

          our worker thread

    static pthread_mutex_t lspg_queue_mutex

          keep the queue from getting tangled

    static pthread_cond_t lspg_queue_cond

          keeps the queue from overflowing
    · static struct pollfd lspgfd
          our poll info

    static lspg_query_queue_t lspg_query_queue [LS_PG_QUERY_QUEUE_LENGTH]

          Our query queue.

    static unsigned int lspg_query_queue_on = 0

          Next position to add something to the queue.
    • static unsigned int lspg_query_queue_off = 0
          The last item still being used (on == off means nothing in queue)

    static unsigned int lspg_query_queue_reply = 0

          The current item being digested.

    static PGconn * q = NULL

          Database connector.

    static PostgresPollingStatusType lspg_connectPoll_response

          Used to determine state while connecting.

    static PostgresPollingStatusType lspg_resetPoll_response

          Used to determine state while reconnecting.
    · lspg_nextsample_t lspg_nextsample
          the very next sample
    · lspg_nextshot_t lspg_nextshot
          the nextshot object

    lspg_getcenter_t lspg_getcenter

          the getcenter object

    lspg_demandairrights_t lspg_demandairrights

          our demandairrights object
    · Ispg getcurrentsampleid t Ispg getcurrentsampleid
          our currentsample id

    lspg_starttransfer_t lspg_starttransfer

          start a sample transfer
    · lspg_waitcryo_t lspg_waitcryo
          signal the robot
```

- static lspg_wait_for_detector_t lspg_wait_for_detector Instance of the detector timing object.
- static lspg_lock_diffractometer_t lspg_lock_diffractometer
- static lspg_lock_detector_t lspg_lock_detector
- static lspg_seq_run_prep_t lspg_seq_run_prep

7.4.1 Detailed Description

Postgresql support for the LS-CAT pgpmac project.

```
\date 2012
\author Keith Brister
\copyright All Rights Reserved
```

Database state machine

State	Description
-4	Initiate connection
-3	Poll until connection initialization is complete
-2	Initiate reset
-1	Poll until connection reset is complete
1	Idle (wait for a notify from the server)
2	Send a query to the server
3	Continue flushing a command to the server
4	Waiting for a reply

Definition in file Ispg.c.

7.4.2 Macro Definition Documentation

7.4.2.1 #define LS_PG_QUERY_QUEUE_LENGTH 16384

Queue length should be long enough that we do not ordinarly bump into the end We should be safe as long as the thread the adds stuff to the queue is not the one that removes it.

(And we can tolerate the adding thread being paused.)

Definition at line 50 of file lspg.c.

7.4.2.2 #define LS_PG_STATE_IDLE 1

Definition at line 33 of file lspg.c.

7.4.2.3 #define LS_PG_STATE_INIT -4

Definition at line 29 of file lspg.c.

7.4.2.4 #define LS_PG_STATE_INIT_POLL -3

Definition at line 30 of file lspg.c.

7.4.2.5 #define LS_PG_STATE_RECV 4

Definition at line 36 of file lspg.c.

7.4.2.6 #define LS_PG_STATE_RESET -2

Definition at line 31 of file lspg.c.

7.4.2.7 #define LS_PG_STATE_RESET_POLL -1

Definition at line 32 of file lspg.c.

7.4.2.8 #define LS_PG_STATE_SEND 2

Definition at line 34 of file lspg.c.

7.4.2.9 #define LS_PG_STATE_SEND_FLUSH 3

Definition at line 35 of file lspg.c.

7.4.3 Typedef Documentation

7.4.3.1 typedef struct lspg_lock_detector_struct lspg_lock_detector_t

lock detector object Implements detector lock for exposure control

7.4.3.2 typedef struct lspg_lock_diffractometer_struct lspg_lock_diffractometer_t

Object used to impliment locking the diffractometer Critical to exposure timing.

7.4.3.3 typedef struct lspg_seq_run_prep_struct lspg_seq_run_prep_t

Data collection running object.

7.4.3.4 typedef struct lspg_wait_for_detector_struct lspg_wait_for_detector_t

Object that implements detector / spindle timing We use database locks for exposure control and this implements the md2 portion of this handshake.

7.4.4 Function Documentation

7.4.4.1 void lspg_allkvs_cb (lspg_query_queue_t * qqp, PGresult * pgr)

set a redis variable based on an updated kv pair

Parameters

qqp	The query that elicited this response
pgr	The resonse from postgresql

Definition at line 279 of file lspg.c.

```
int kvname_col, kvvalue_col, kvseq_col, kvdbrtype_col;
int i;
lsredis_obj_t *robj;
```

7.4.4.2 char** $lspg_array2ptrs(char*a)$

returns a null terminated list of strings parsed from postgresql array

Definition at line 160 of file lspg.c.

```
char **rtn, *sp, *acums;
int i, n, inquote, havebackslash, rtni;;
int mxsz;
inquote
             = 0;
havebackslash = 0;
// Despense with the null input condition before we complicate the code below if( a == NULL || a[0] != '{' || a[strlen(a)-1] != '}')
 return NULL;
// Count the maximum number of strings \,
// Actual number will be less if there are quoted commas // \,
n = 1;
for( i=0; a[i]; i++) {
  if( a[i] == ',')
    n++;
// The maximum size of any string is the length of a (+1)
mxsz = strlen(a) + 1;
\ensuremath{//} This is the accumulation string to make up the array elements
acums = (char *)calloc( mxsz, sizeof( char));
if( acums == NULL) {
 lslogging_log_message( "lspg_array2ptrs: out of memory
     (acums)");
  exit( 1);
// allocate storage for the pointer array and the null terminator
rtn = (char **)calloc( n+1, sizeof( char *));
if( rtn == NULL) {
 exit( 1);
```

```
rtni = 0;
// Go through and create the individual strings
sp = acums;
*sp = 0;
inquote = 0;
havebackslash = 0;
for( i=1; a[i] != 0; i++) {
  switch( a[i]) {
case '"':
     ...vebackslash) {
// a quoted quote. Cool
//
    if( havebackslash) {
      *(sp++) = a[i];
      *sp = 0;
      havebackslash = 0;
    } else {
  // Toggle the flag
      inquote = 1 - inquote;
    break;
  case '\\':
    if( havebackslash) {
     *(sp++) = a[i];
      *sp = 0;
     havebackslash = 0;
    } else {
     havebackslash = 1;
    break;
  case ',':
    if ( inquote || havebackslash) {
     *(sp++) = a[i];
*sp = 0;
      havebackslash = 0;
     rtn[rtni++] = strdup( acums);
      sp = acums;
    break:
    if( inquote || havebackslash) {
     *(sp++) = a[i];
*sp = 0;
      havebackslash = 0;
    } else {
     rtn[rtni++] = strdup(acums);
rtn[rtni] = NULL;
      free( acums);
      return( rtn);
    break;
   *(sp++) = a[i];
    *sp = 0;
   havebackslash = 0;
// Getting here means the final '}' was missing
// Probably we should throw an error or \log it or something.
\ensuremath{//} Through out the last entry since this there is not resonable expectation
    that
// we should be parsing it anyway.
rtn[rtni] = NULL;
free( acums);
return( rtn);
```

7.4.4.3 void lspg_check_preset_in_position_cb (char * event)

Definition at line 1868 of file lspg.c.

```
lspmac_motor_t *mp;
char cp[64];
```

{

```
int i;

for( i=0; i<strlen( event); i++) {
    cp[i] = 0;
    if( event[i] == ' ')
        break;
    cp[i] = event[i];
}

mp = lspmac_find_motor_by_name( cp);
    if( mp == NULL) {
        return;
}
i = lsredis_find_preset_index_by_position
        ( mp);
lspg_query_push( NULL, "EXECUTE kvupdate(
        ' (%s.currentPreset,%d)')", cp, i);</pre>
```

7.4.4.4 void lspg_cmd_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Send strings directly to PMAC queue.

Parameters

in	qqp	Our query
in	pgr	Our result

Definition at line 1338 of file lspg.c.

7.4.4.5 void lspg_demandairrights_all ()

do nothing until we get airrights

Definition at line 655 of file Ispg.c.

```
lspg_demandairrights_call();
lspg_demandairrights_wait();
// there is no "done" version
```

```
7.4.4.6 void lspg_demandairrights_call ( )
call for airrights
Definition at line 637 of file lspg.c.
  pthread_mutex_lock( &lspg_demandairrights.mutex);
  lspg_demandairrights.new_value_ready = 0;
pthread_mutex_unlock( &lspg_demandairrights.mutex);
  lspg_query_push( lspg_demandairrights_cb
    , "SELECT px.demandairrights())");
7.4.4.7 void lspg_demandairrights_cb ( lspg_query_queue_t * qqp, PGresult * pgr )
handle the airrights response
Definition at line 628 of file Ispg.c.
  pthread_mutex_lock( &lspg_demandairrights.mutex);
  lspg_demandairrights.new_value_ready = 1;
pthread_cond_signal( &lspg_demandairrights.cond);
  pthread_mutex_unlock( &lspg_demandairrights.mutex);
7.4.4.8 void lspg_demandairrights_init ( )
initialize the demandairrights structure
Definition at line 620 of file lspg.c.
  lspg_demandairrights.new_value_ready = 0;
  pthread_mutex_init( &lspg_demandairrights.mutex,
  pthread_cond_init( &lspg_demandairrights.cond, NULL);
7.4.4.9 void lspg_demandairrights_wait ( )
wait for the air rights request to return
Definition at line 646 of file Ispg.c.
  pthread_mutex_lock( &lspg_demandairrights.mutex);
  while( lspg_demandairrights.new_value_ready
        == 0)
     pthread_cond_wait( &lspg_demandairrights.cond, &
       lspg_demandairrights.mutex);
  pthread_mutex_unlock( &lspg_demandairrights.mutex);
7.4.4.10 void lspg_flush ( )
Flush psql output buffer (ie, send the query)
```

Definition at line 1368 of file lspg.c.

```
{
int err;
err = PQflush(q);
switch( err) {
case -1:
 // an error occured
  lslogging_log_message( "flush failed: %s",
    PQerrorMessage( q));
  ls_pg_state = LS_PG_STATE_IDLE;
  // We should probably reset the connection and start from scratch.
     Probably the connection died.
  break:
case 0:
  // goodness and joy.
  ls_pg_state = LS_PG_STATE_RECV;
  // more sending to do
  ls_pg_state = LS_PG_STATE_SEND_FLUSH;
```

7.4.4.11 void lspg_getcenter_all ()

Convenience function to complete synchronous getcenter query.

Definition at line 1300 of file lspg.c.

```
lspg_getcenter_call();
lspg_getcenter_wait();
lspg_getcenter_done();
```

7.4.4.12 void lspg_getcenter_call ()

Request a getcenter query.

Definition at line 1276 of file lspg.c.

```
pthread_mutex_lock( &lspg_getcenter.mutex);
lspg_getcenter.new_value_ready = 0;
pthread_mutex_unlock( &lspg_getcenter.mutex);
lspg_query_push( lspg_getcenter_cb, "SELECT *
    FROM px.getcenter2()");
```

7.4.4.13 void lspg_getcenter_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Retrieve the data to center the crystal.

Definition at line 1211 of file lspg.c.

```
static int
zoom_c, dcx_c, dcy_c, dax_c, day_c, daz_c;
pthread_mutex_lock( &(lspg_getcenter.mutex));
lspg_getcenter.no_rows_returned = PQntuples(
    pgr) <= 0;</pre>
```

```
if( lspg_getcenter.no_rows_returned) {
    ^{\prime\prime} // No particular reason this path should ever be taken
    // but if we don't get rows then we had better not move anything.
    lspg_getcenter.new_value_ready = 1;
    pthread_cond_signal(&(lspg_getcenter.cond));
    pthread_mutex_unlock( &(lspg_getcenter.mutex));
  zoom_c = PQfnumber( pgr, "zoom");
dcx_c = PQfnumber( pgr, "dcx");
dcy_c = PQfnumber( pgr, "dcy");
  dax_c = PQfnumber( pgr, "dax");
day_c = PQfnumber( pgr, "day");
daz_c = PQfnumber( pgr, "daz");
  lspg_getcenter.zoom_isnull = PQgetisnull( pgr, 0,
      zoom_c);
  if( lspg_getcenter.zoom_isnull == 0)
    lspg_getcenter.zoom = atoi( PQgetvalue( pgr, 0, zoom_c));
  lspg_getcenter.dcx_isnull = PQgetisnull( pgr, 0,
      dcx_c);
  if( lspg_getcenter.dcx_isnull == 0)
    lspg_getcenter.dcx = atof( PQgetvalue( pgr, 0, dcx_c));
  lspg_getcenter.dcy_isnull = PQgetisnull( pgr, 0,
      dcy_c);
  if( lspg_getcenter.dcy_isnull == 0)
    lspg_getcenter.dcy = atof( PQgetvalue( pgr, 0, dcy_c));
  lspg_getcenter.dax_isnull = PQgetisnull( pgr, 0,
  if( lspg_getcenter.dax_isnull == 0)
    lspg_getcenter.dax = atof( PQgetvalue( pgr, 0, dax_c));
  lspg_getcenter.day_isnull = PQgetisnull( pgr, 0,
     day_c);
  if( lspg_getcenter.day_isnull == 0)
    lspg_getcenter.day = atof( PQgetvalue( pgr, 0, day_c));
  lspg_getcenter.daz_isnull = PQgetisnull( pgr, 0,
      daz_c);
  if( lspg_getcenter.daz_isnull == 0)
    lspg_getcenter.daz = atof( PQgetvalue( pgr, 0, daz_c));
  lspq_getcenter.new_value_ready = 1;
  pthread_cond_signal( &(lspg_getcenter.cond));
  pthread_mutex_unlock( &(lspg_getcenter.mutex));
7.4.4.14 void lspg_getcenter_done ( )
Done with getcenter query.
Definition at line 1294 of file lspg.c.
 pthread_mutex_unlock( &(lspg_getcenter.mutex));
7.4.4.15 void lspg_getcenter_init ( )
Initialize getcenter object.
Definition at line 1268 of file lspg.c.
  memset( &lspg_getcenter, 0, sizeof( lspg_getcenter
  pthread_mutex_init( &(lspg_getcenter.mutex), NULL);
  pthread_cond_init( &(lspg_getcenter.cond), NULL);
```

```
7.4.4.16 void lspg_getcenter_wait ( )
```

Wait for a getcenter query to return.

Definition at line 1286 of file Ispg.c.

```
pthread_mutex_lock( &(lspg_getcenter.mutex));
while( lspg_getcenter.new_value_ready == 0)
pthread_cond_wait( &(lspg_getcenter.cond), &(
    lspg_getcenter.mutex));
```

7.4.4.17 void lspg_getcurrentsampleid_call ()

Definition at line 466 of file lspg.c.

```
pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
    );
lspg_getcurrentsampleid.new_value_ready
    = 0;
pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    );
lspg_query_push( lspg_getcurrentsampleid_cb
    , "SELECT px.getcurrentsampleid()");
```

7.4.4.18 void lspg_getcurrentsampleid_cb (lspg_query_queue_t * qqp, PGresult * pgr)

get currentsampleid

Definition at line 445 of file Ispg.c.

```
pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
    );
lspg_nextsample.new_value_ready = 1;
lspg_getcurrentsampleid.no_rows_returned
= POntuples( pgr) <= 0;
if( lspg_getcurrentsampleid.no_rows_returned
  pthread_cond_signal( &lspg_getcurrentsampleid.cond
  pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    );
  return;
lspg_getcurrentsampleid.getcurrentsampleid_isnull
= PQgetisnull( pgr, 0, 0);
if( lspg_getcurrentsampleid.getcurrentsampleid_isnull
== 0)
  lspg_getcurrentsampleid.getcurrentsampleid
      strtol( PQgetvalue( pgr, 0, 0), NULL, 0);
pthread_cond_signal( &lspg_getcurrentsampleid.cond
pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    );
```

7.4.4.19 void lspg_getcurrentsampleid_init ()

Definition at line 437 of file Ispg.c.

7.4.4.20 unsigned int lspg_getcurrentsampleid_read ()

Definition at line 476 of file lspg.c.

```
unsigned int rtn;
pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
    );
while( lspg_getcurrentsampleid.new_value_ready
    == 0)
pthread_cond_wait( &lspg_getcurrentsampleid.cond
    , &lspg_getcurrentsampleid.mutex);

if( lspg_getcurrentsampleid.getcurrentsampleid_isnull
    )
    rtn = -1;
else
    rtn = lspg_getcurrentsampleid.getcurrentsampleid
    ;
pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    );
return rtn;
```

7.4.4.21 void lspg_getcurrentsampleid_wait_for_id (unsigned int test)

Definition at line 492 of file Ispg.c.

```
pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
    );
while( lspg_getcurrentsampleid.getcurrentsampleid
    != test)
pthread_cond_wait( &lspg_getcurrentsampleid.cond
    , &lspg_getcurrentsampleid.mutex);
pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    );
```

7.4.4.22 void lspg_init ()

Initiallize the Ispg module.

Definition at line 1951 of file lspg.c.

```
{
pthread_mutex_init( &lspg_queue_mutex, NULL);
pthread_cond_init( &lspg_queue_cond, NULL);

lspg_demandairrights_init();
lspg_getcenter_init();
lspg_lock_detector_init();
lspg_lock_detector_init();
lspg_lock_diffractometer_init();
lspg_nextsample_init();
lspg_nextshot_init();
lspg_seq_run_prep_init();
lspg_starttransfer_init();
lspg_wait_for_detector_init();
lspg_waitcryo_init();
```

```
7.4.4.23 void lspg_lock_detector_all ( )
Detector lock convinence function.
Definition at line 1123 of file lspg.c.
  lspg_lock_detector_call();
  lspg_lock_detector_wait();
  lspg_lock_detector_done();
7.4.4.24 void lspg_lock_detector_call ( )
Request (demand) a detector lock.
Definition at line 1099 of file Ispg.c.
  pthread_mutex_lock( &(lspg_lock_detector.mutex));
  lspg_lock_detector.new_value_ready = 0;
  pthread_mutex_unlock( &(lspg_lock_detector.mutex));
  7.4.4.25 void lspg_lock_detector_cb ( lspg_query_queue_t * qqp, PGresult * pgr )
Callback for when the detector lock has be grabbed.
Definition at line 1090 of file lspg.c.
  pthread_mutex_lock( &(lspg_lock_detector.mutex));
  lspg_lock_detector.new_value_ready = 1;
  pthread_cond_signal( &(lspg_lock_detector.cond));
  pthread_mutex_unlock( &(lspg_lock_detector.mutex));
7.4.4.26 void lspg_lock_detector_done ( )
Finish waiting.
Definition at line 1117 of file lspg.c.
 pthread_mutex_unlock( &(lspg_lock_detector.mutex));
7.4.4.27 void lspg_lock_detector_init ( )
Initialize detector lock object.
Definition at line 1082 of file lspg.c.
  lspg_lock_detector.new_value_ready = 0;
  pthread_mutex_init( &(lspg_lock_detector.mutex), NULL)
  pthread_cond_init( &(lspg_lock_detector.cond), NULL);
```

```
7.4.4.28 void lspg_lock_detector_wait ( )
```

Wait for the detector lock.

Definition at line 1109 of file lspg.c.

7.4.4.29 void lspg_lock_diffractometer_all ()

Convience function that combines lock diffractometer calls.

Definition at line 1064 of file lspg.c.

```
lspg_lock_diffractometer_call();
lspg_lock_diffractometer_wait();
lspg_lock_diffractometer_all();
}
```

7.4.4.30 void lspg_lock_diffractometer_call ()

Request that the database grab the diffractometer lock.

Definition at line 1040 of file lspg.c.

7.4.4.31 void lspg_lock_diffractometer_cb ($lspg_query_queue_t*qqp$, $pg_result*pg_r$)

Callback routine for a lock diffractometer query.

Definition at line 1031 of file lspg.c.

```
7.4.4.32 void lspg_lock_diffractometer_done ( )
```

Finish up the lock diffractometer call.

Definition at line 1058 of file Ispg.c.

7.4.4.33 void lspg_lock_diffractometer_init ()

initialize the diffractometer locking object

Definition at line 1023 of file Ispg.c.

7.4.4.34 void lspg_lock_diffractometer_wait ()

Wait for the diffractometer lock.

Definition at line 1050 of file lspg.c.

7.4.4.35 void lspg_next_state ()

Implements our state machine Does not strictly only set the next state as it also calls some functions that, perhaps, alters the state mid-function.

Definition at line 1725 of file Ispg.c.

```
{
//
// connect to the database
//
if( q == NULL ||
    ls_pg_state == LS_PG_STATE_INIT ||
    ls_pg_state == LS_PG_STATE_RESET ||
    ls_pg_state == LS_PG_STATE_INIT_POLL ||
    ls_pg_state == LS_PG_STATE_INIT_POLL ||
    lspg_pg_connect( lspgfd);

if( ls_pg_state == LS_PG_STATE_IDLE &&
    lspg_query_queue_on != lspg_query_queue_off
    )
    ls_pg_state = LS_PG_STATE_SEND;

switch( ls_pg_state) {
    case LS_PG_STATE_INIT_POLL:
    if( lspg_connectPoll_response ==
```

```
PGRES_POLLING_WRITING)
    lspgfd.events = POLLOUT;
  else if( lspg_connectPoll_response ==
    PGRES_POLLING_READING)
    lspgfd.events = POLLIN;
    lspgfd.events = 0;
case LS_PG_STATE_RESET_POLL:
  if( lspg_resetPoll_response == PGRES_POLLING_WRITING
  lspgfd.events = POLLOUT;
else if( lspg_resetPoll_response ==
   PGRES_POLLING_READING)
    lspgfd.events = POLLIN;
    lspgfd.events = 0;
  break;
case LS_PG_STATE_IDLE:
case LS_PG_STATE_RECV:
 lspgfd.events = POLLIN;
  break;
case LS_PG_STATE_SEND:
case LS_PG_STATE_SEND_FLUSH:
  lspgfd.events = POLLOUT;
default:
  lspgfd.events = 0;
```

7.4.4.36 void lspg_nextaction_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Queue the next MD2 instruction.

Parameters

in	qqp	The query that generated this result
in	pgr	The result

Definition at line 1309 of file Ispg.c.

7.4.4.37 unsigned int lspg_nextsample_all (int * err)

Definition at line 567 of file lspg.c.

```
unsigned int rtn;
lspg_nextsample_call();
lspg_nextsample_wait();

if( lspg_nextsample.no_rows_returned) {
  rtn = 0;
  *err = 1;
} else {
  if( lspg_nextsample.nextsample_isnull) {
    rtn = 0;
    *err = 1;
} else {
    rtn = 1spg_nextsample.nextsample;
    *err = 0;
}
}
lspg_nextsample_done();
return rtn;
```

7.4.4.38 void lspg_nextsample_call ()

Queue up a nextsample query.

Definition at line 544 of file Ispg.c.

7.4.4.39 void $lspg_nextsample_cb (lspg_query_queue_t * qqp, PGresult * pgr)$

Next Sample.

Parameters

in	qqp	Our nextsample query
in	pgr	result of the query

Definition at line 503 of file Ispg.c.

```
{
static int got_columns = 0;
static int nextsample_col;
pthread_mutex_lock( & (lspg_nextsample.mutex));

lspg_nextsample.no_rows_returned = PQntuples(
    pgr) <= 0;
if( lspg_nextsample.no_rows_returned) {
    lslogging_log_message( "lspg_nextsample_cb: no rows
        returned. This should never happen.");
    lspg_nextsample.new_value_ready = 1;
    pthread_cond_signal( & (lspg_nextsample.cond));
    pthread_mutex_unlock( & (lspg_nextsample.mutex));
    return;
}

if( got_columns == 0) {
    nextsample_col = PQfnumber( pgr, "nextsample");
    got_columns = 1;
}

lspg_nextsample.nextsample_isnull =
    PQgetisnull( pgr, 0, nextsample_col);
if( lspg_nextsample.nextsample_isnull == 0)</pre>
```

```
lspg_nextsample.nextsample = strtol( PQgetvalue(
    pgr, 0, nextsample_col), NULL, 0);

lspg_nextsample.new_value_ready = 1;
pthread_cond_signal( &(lspg_nextsample.cond));
pthread_mutex_unlock( &(lspg_nextsample.mutex));
```

7.4.4.40 void lspg_nextsample_done ()

Called when the next shot query has been processed.

Definition at line 562 of file Ispg.c.

```
pthread_mutex_unlock( &(lspg_nextsample.mutex));
}
```

7.4.4.41 void lspg_nextsample_init ()

Initialize the nextsample variable, mutex, and condition.

Definition at line 536 of file lspg.c.

```
memset( &lspg_nextsample, 0, sizeof( lspg_nextsample
    ));
pthread_mutex_init( &(lspg_nextsample.mutex), NULL);
pthread_cond_init( &(lspg_nextsample.cond), NULL);
}
```

7.4.4.42 void lspg_nextsample_wait ()

Wait for the nextsample query to get processed.

Definition at line 554 of file lspg.c.

```
pthread_mutex_lock( &(lspg_nextsample.mutex));
while( lspg_nextsample.new_value_ready == 0)
pthread_cond_wait( &(lspg_nextsample.cond), &(
    lspg_nextsample.mutex));
```

7.4.4.43 void lspg_nextshot_call ()

Queue up a nextshot query.

Definition at line 923 of file lspg.c.

7.4.4.44 void lspg_nextshot_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Next Shot Callback.

This is a long and tedious routine as there are a large number of variables returned. Suck it up. Return with the global object lspg_nextshot set.

Parameters

in	qqp	Our nextshot query
in	pgr	result of the query

Definition at line 668 of file lspg.c.

```
static int got_col_nums=0;
static int
      dsdir_c, dspid_c, dsowidth_c, dsoscaxis_c, dsexp_c, skey_c, sstart_c, sfn_c
             , dsphi_c,
      dsomega_c, dskappa_c, dsdist_c, dsnrg_c, dshpid_c, cx_c, cy_c, ax_c, ay_c,
      active_c, sindex_c, stype_c,
      dsowidth2_c, dsoscaxis2_c, dsexp2_c, sstart2_c, dsphi2_c, dsomega2_c,
            dskappa2_c, dsdist2_c, dsnrg2_c,
      cx2_c, cy2_c, ax2_c, ay2_c, az2_c, active2_c, sindex2_c, stype2_c;
pthread_mutex_lock( &(lspg_nextshot.mutex));
lspg_nextshot.no_rows_returned = PQntuples( pgr)
                 <= 0;
if( lspg_nextshot.no_rows_returned) {
       lspg_nextshot.new_value_ready = 1;
      pthread_cond_signal( &(lspg_nextshot.cond));
      pthread_mutex_unlock( &(lspg_nextshot.mutex));
                                                                                                      // I guess there was no shot after all
if( got_col_nums == 0) {
                                      = PQfnumber( pgr, "dsdir");
      dspid_c
                                                 = PQfnumber( pgr, "dspid");
      dsowidth_c = PQfnumber(pgr, "dsowidth");
    dsoscaxis_c
dsexp_c
dsexp_c
skey_c
sstart_c
sfn_c
dsphi_c
dsomega_c
dskappa_c
dshiz_c

      dsoscaxis_c = PQfnumber( pgr, "dsoscaxis");
    cx_c = PQfnumber( pgr, "cx");
cy_c = PQfnumber( pgr, "cy");
ax_c = PQfnumber( pgr, "ax");
ay_c = PQfnumber( pgr, "ay");
az_c = PQfnumber( pgr, "az");
active_c = PQfnumber( pgr, "active");
sindex_c = PQfnumber( pgr, "sindex");
stype_c = PQfnumber( pgr, "stype");
dsowidth2_c = PQfnumber( pgr, "dsowidth2");
dsoxcaxis2_c = PQfnumber( pgr, "dsoscaxis2");
dsexp2_c = PQfnumber( pgr, "dsoxcaxis2");
     dsoscaxis2_c = PQfnumber( pgr, "dsoscaxis2"
dsexp2_c = PQfnumber( pgr, "dsexp2");
sstart2_c = PQfnumber( pgr, "dsphi2");
dsphi2_c = PQfnumber( pgr, "dsphi2");
dsomega2_c = PQfnumber( pgr, "dsomega2");
dsdist2_c = PQfnumber( pgr, "dsdist2");
dsnrg2_c = PQfnumber( pgr, "dsdist2");
dsnrg2_c = PQfnumber( pgr, "dsrg2");
cx2_c = PQfnumber( pgr, "cx2");
                                             = PQfnumber( pgr, "cx2");
= PQfnumber( pgr, "ax2");
= PQfnumber( pgr, "ax2");
= PQfnumber( pgr, "ay2");
= PQfnumber( pgr, "az2");
      cy2_c
      ax2_c
      ay2_c
      az2 c
                                              = PQfnumber( pgr, "active2");
= PQfnumber( pgr, "sindex2");
      active2_c
                                                 = PQfnumber( pgr, "stype2");
      stype2_c
      got_col_nums = 1;
```

```
// NULL string values come back as empty strings
// Mark the null flag but allocate the empty string anyway
lspg_nextshot.dsdir_isnull = PQgetisnull( pgr, 0,
   dsdir_c);
if( lspg_nextshot.dsdir != NULL)
  free( lspg_nextshot.dsdir);
lspg_nextshot.dsdir = strdup( PQgetvalue( pgr, 0, dsdir_c))
lspg_nextshot.dspid_isnull = PQgetisnull( pgr, 0,
   dspid_c);
if( lspg_nextshot.dspid != NULL)
free( lspg_nextshot.dspid);
lspg_nextshot.dspid = strdup( PQgetvalue( pgr, 0, dspid_c))
lspg_nextshot.dsoscaxis_isnull = PQgetisnull(
   pgr, 0, dsoscaxis_c);
if( lspg_nextshot.dsoscaxis != NULL)
  free( lspg_nextshot.dsoscaxis);
lspg_nextshot.dsoscaxis = strdup( PQgetvalue( pgr, 0,
   dsoscaxis_c));
lspg_nextshot.dsoscaxis2_isnull = PQgetisnull(
   pgr, 0, dsoscaxis2_c);
if( lspg_nextshot.dsoscaxis2 != NULL)
  free( lspg_nextshot.dsoscaxis2);
lspg_nextshot.dsoscaxis2 = strdup( PQgetvalue( pgr, 0,
     dsoscaxis2_c));
lspg_nextshot.sfn_isnull = PQgetisnull(pgr, 0, sfn_c);
if( lspg_nextshot.sfn != NULL)
  free( lspg_nextshot.sfn);
lspg_nextshot.sfn = strdup( PQgetvalue( pgr, 0, sfn_c));
lspg_nextshot.stype_isnull = PQgetisnull( pgr, 0,
   stype_c);
if( lspg_nextshot.stype != NULL)
  free( lspg_nextshot.stype);
lspg_nextshot.stype = strdup( PQgetvalue( pgr, 0, stype_c))
lspg_nextshot.stype2_isnull = PQgetisnull( pgr, 0,
   stype2_c);
if( lspg_nextshot.stype2 != NULL)
free( lspg_nextshot.stype2);
lspg_nextshot.stype2 = strdup( PQgetvalue( pgr, 0,
    stype2_c));
// Probably shouldn't try to convert null number values
lspg_nextshot.dsowidth_isnull = PQgetisnull( pgr,
     0, dsowidth_c);
if( lspg_nextshot.dsowidth_isnull == 0)
  lspg_nextshot.dsowidth = atof( PQgetvalue( pgr,0,
    dsowidth_c));
lspg_nextshot.dsexp_isnull = PQgetisnull( pgr, 0,
   dsexp_c);
if( lspg_nextshot.dsexp_isnull == 0)
  lspg_nextshot.dsexp
                        = atof( PQgetvalue( pgr,0, dsexp_c
lspg nextshot.sstart isnull = POgetisnull( pgr. 0.
   sstart c);
if( lspg_nextshot.sstart_isnull == 0)
  lspg_nextshot.sstart = atof( PQgetvalue( pgr,0,
    sstart_c));
lspg_nextshot.dsphi_isnull = PQgetisnull( pgr, 0,
   dsphi c);
if( lspg_nextshot.dsphi_isnull == 0)
  lspg_nextshot.dsphi
                        = atof( PQgetvalue( pgr,0, dsphi_c
lspg_nextshot.dsomega_isnull = PQgetisnull( pgr, 0
   , dsomega_c);
if( lspg_nextshot.dsomega_isnull == 0)
  lspg_nextshot.dsomega = atof( PQgetvalue( pgr,0,
    dsomega_c));
lspg_nextshot.dskappa_isnull = PQgetisnull( pgr, 0
    , dskappa_c);
```

```
if( lspg_nextshot.dskappa_isnull == 0)
  lspg_nextshot.dskappa = atof( PQgetvalue( pgr,0,
    dskappa_c));
lspg_nextshot.dsdist_isnull = PQgetisnull( pgr, 0,
    dsdist c);
if( lspg_nextshot.dsdist_isnull == 0)
  lspg_nextshot.dsdist = atof( PQgetvalue( pgr,0,
    dsdist_c));
lspg_nextshot.dsnrg_isnull = PQgetisnull( pgr, 0,
    dsnrg_c);
if( lspg_nextshot.dsnrg_isnull == 0)
                        = atof( PQgetvalue( pgr,0, dsnrg_c
  lspg_nextshot dsnrg
lspg_nextshot.cx_isnull = PQgetisnull( pgr, 0, cx_c);
if( lspg_nextshot.cx_isnull == 0)
                        = atof( PQgetvalue( pgr,0, cx_c));
  lspg_nextshot.cx
lspg_nextshot.cy_isnull = PQgetisnull( pgr, 0, cy_c);
if( lspg_nextshot.cy_isnull == 0)
                        = atof( PQgetvalue( pgr,0, cy_c));
  lspg_nextshot.cy
lspg_nextshot.ax_isnull = PQgetisnull( pgr, 0, ax_c);
if( lspg_nextshot.ax_isnull == 0)
  lspg_nextshot.ax
                         = atof( PQgetvalue( pgr,0, ax_c));
lspg_nextshot.ay_isnull = POgetisnull( pgr, 0, ay_c);
if(lspg_nextshot.ay_isnull == 0)
  lspg_nextshot.ay
                         = atof( PQgetvalue( pgr,0, ay_c));
lspg_nextshot.az_isnull = PQgetisnull( pgr, 0, az_c);
if( lspg_nextshot.az_isnull == 0)
 lspg_nextshot.az
                         = atof( PQgetvalue( pgr,0, az_c));
lspg_nextshot.active_isnull = PQgetisnull( pgr, 0,
    active_c);
if( lspg_nextshot.active_isnull == 0)
 lspg_nextshot.active = atoi( PQgetvalue( pgr, 0,
    active_c));
lspg_nextshot.sindex_isnull = PQgetisnull( pgr, 0,
    sindex_c);
if( lspg_nextshot.sindex_isnull == 0)
  lspg_nextshot.sindex = atoi( PQgetvalue( pgr, 0,
    sindex_c));
lspg_nextshot.dshpid_isnull = PQgetisnull( pgr, 0,
   dshpid c);
if( lspg_nextshot.dshpid_isnull == 0)
  lspg_nextshot.dshpid = atoi( PQgetvalue( pgr, 0,
    dshpid_c));
lspg_nextshot.skey_isnull = PQgetisnull( pgr, 0,
    skey_c);
if( lspg_nextshot.skey_isnull == 0)
  lspg_nextshot.skey = atoll( PQgetvalue( pgr, 0, skey_c))
lspg nextshot.dsowidth2 isnull = POgetisnull(
    pgr, 0, dsowidth2_c);
if( lspg_nextshot.dsowidth2_isnull == 0)
  lspg_nextshot.dsowidth2 = atof( PQgetvalue( pgr, 0,
    dsowidth2_c));
lspg_nextshot.dsexp2_isnull = PQgetisnull( pgr, 0,
    dsexp2_c);
if( lspg_nextshot.dsexp2_isnull == 0)
  lspg_nextshot.dsexp2
                        = atof( PQgetvalue( pgr,0,
    dsexp2_c));
lspg_nextshot.sstart2_isnull = PQgetisnull( pgr, 0
    , sstart2_c);
if( lspg_nextshot.sstart2_isnull == 0)
  lspg_nextshot.sstart2 = atof( PQgetvalue( pgr, 0,
    sstart2_c));
lspg_nextshot.dsphi2_isnull = PQgetisnull( pgr, 0,
    dsphi2 c):
if( lspg_nextshot.dsphi2_isnull == 0)
  lspg_nextshot.dsphi2
                          = atof( PQgetvalue( pgr,0,
    dsphi2 c));
lspg_nextshot.dsomega2_isnull = PQgetisnull( pgr,
     0, dsomega2 c);
if( lspg_nextshot.dsomega2_isnull == 0)
```

```
lspg_nextshot.dsomega2 = atof( PQgetvalue( pgr, 0,
    dsomega2_c));
lspg_nextshot.dskappa2_isnull = PQgetisnull( pgr,
0, dskappa2_c);
if( lspq_nextshot.dskappa2_isnull == 0)
  lspg_nextshot.dskappa2 = atof( PQgetvalue( pgr, 0,
    dskappa2_c));
lspg_nextshot.dsdist2_isnull = PQgetisnull( pgr, 0
, dsdist2_c);
if( lspg_nextshot.dsdist2_isnull == 0)
  lspg_nextshot.dsdist2 = atof( PQgetvalue( pgr,0,
    dsdist2_c));
lspg_nextshot.dsnrg2_isnull = PQgetisnull( pgr, 0,
    dsnrg2_c);
if( lspg_nextshot.dsnrg2_isnull == 0)
  lspg_nextshot.dsnrg2 = atof( PQgetvalue( pgr,0,
    dsnrg2_c));
lspg_nextshot.cx2_isnull = PQgetisnull( pgr, 0, cx2_c)
if( lspg_nextshot.cx2_isnull == 0)
  lspg_nextshot.cx2
                         = atof( PQgetvalue( pgr,0, cx2_c));
lspg_nextshot.cy2_isnull = PQgetisnull( pgr, 0, cy2_c)
if( lspg_nextshot.cy2_isnull == 0)
                         = atof( PQgetvalue( pgr,0, cy2_c));
  lspg_nextshot.cy2
lspg_nextshot.ax2_isnull = PQgetisnull( pgr, 0, ax2_c)
if( lspg_nextshot.ax2_isnull == 0)
  lspg_nextshot.ax2
                           = atof( PQgetvalue( pgr,0, ax2_c));
lspg_nextshot.ay2_isnull = PQgetisnull( pgr, 0, ay2_c)
if( lspg_nextshot.ay2_isnull == 0)
  lspg_nextshot.ay2
                        = atof( PQgetvalue( pgr,0, ay2_c));
lspg_nextshot.az2_isnull = PQgetisnull( pgr, 0, az2_c)
if( lspg_nextshot.az2_isnull == 0)
                         = atof( PQgetvalue( pgr,0, az2_c));
  lspg_nextshot.az2
lspg_nextshot.active2_isnull = PQgetisnull( pgr, 0
, active2_c);
if( lspg_nextshot.active2_isnull == 0)
  lspg_nextshot.active2 = atoi( PQgetvalue( pgr, 0,
    active2_c));
lspg_nextshot.sindex2_isnull = PQgetisnull( pgr, 0
, sindex2_c);
if( lspg_nextshot.sindex2_isnull == 0)
  lspg_nextshot.sindex2 = atoi( PQgetvalue( pgr, 0,
    sindex2_c));
lspg_nextshot.new_value_ready = 1;
pthread_cond_signal( &(lspg_nextshot.cond));
pthread_mutex_unlock( &(lspg_nextshot.mutex));
```

7.4.4.45 void lspg_nextshot_done ()

Called when the next shot query has been processed.

Definition at line 941 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_nextshot.mutex));
}
```

7.4.4.46 void lspg_nextshot_init ()

Initialize the nextshot variable, mutex, and condition.

Definition at line 915 of file lspg.c.

```
memset( &lspg_nextshot, 0, sizeof( lspg_nextshot));
pthread_mutex_init( &(lspg_nextshot.mutex), NULL);
pthread_cond_init( &(lspg_nextshot.cond), NULL);
}
```

7.4.4.47 void lspg_nextshot_wait ()

Wait for the next shot query to get processed.

Definition at line 933 of file Ispg.c.

```
pthread_mutex_lock( &(lspg_nextshot.mutex));
while( lspg_nextshot.new_value_ready == 0)
pthread_cond_wait( &(lspg_nextshot.cond), &(lspg_nextshot.mutex));
```

7.4.4.48 PQnoticeProcessor lspg_notice_processor (void * arg, const char * msg)

Definition at line 1629 of file lspg.c.

```
lslogging_log_message( "lspg: %s", msg);
return NULL;
}
```

7.4.4.49 void lspg_pg_connect ()

Connect to the pg server.

Definition at line 1636 of file lspg.c.

```
{
int err;
if(q == NULL)
  ls_pg_state = LS_PG_STATE_INIT;
switch( ls_pg_state) {
case LS_PG_STATE_INIT:
  if( lspg_time_sent.tv_sec != 0) {
    //
// Reality check: if it's less the about 10 seconds since the last failed
     {\tt attempt}
    // the just chill.
    gettimeofday( &now, NULL);
    if( now.tv_sec - lspg_time_sent.tv_sec < 10) {</pre>
      return;
  }
  q = PQconnectStart( "dbname=1s user=1suser hostaddr=10.1.0.3");
  if(q == NULL) {
    lslogging_log_message( "Out of memory
    (lspg_pg_connect)");
exit( -1);
  err = PQstatus( q);
  if( err == CONNECTION_BAD) {
   lslogging_log_message( "Trouble connecting to
   database");
    gettimeofday( &lspg_time_sent, NULL);
```

```
return;
  err = PQsetnonblocking( q, 1);
  if( err != 0) {
    lslogging_log_message( "Odd, could not set database
    connection to nonblocking");
  ls_pg_state = LS_PG_STATE_INIT_POLL;
  lspg_connectPoll_response = PGRES_POLLING_WRITING;
  // set up the connection for poll
  lspgfd.fd = PQsocket( q);
case LS_PG_STATE_INIT_POLL:
  if( lspg_connectPoll_response ==
    PGRES_POLLING_FAILED) {
    PQfinish(q);
    q = NULL;
    ls_pg_state = LS_PG_STATE_INIT;
  } else if( lspg_connectPoll_response ==
    PGRES POLLING OK) {
    PQsetNoticeProcessor(q, (PQnoticeProcessor)lspq_notice_processor
    lspg_query_push( NULL, "select pmac.md2_init()");
    ls_pg_state = LS_PG_STATE_IDLE;
  break:
case LS_PG_STATE_RESET:
  err = PQresetStart(q);
  if( err == 0) {
    PQfinish(q);
    q = NULL;
    ls_pg_state = LS_PG_STATE_INIT;
  } else {
    ls_pg_state = LS_PG_STATE_RESET_POLL;
    lspg_resetPoll_response = PGRES_POLLING_WRITING;
  break;
case LS_PG_STATE_RESET_POLL:
  if( lspg_resetPoll_response == PGRES_POLLING_FAILED)
    PQfinish(q);
    q = NULL;
    is_pg_state = LS_PG_STATE_INIT;
  } else if( lspg_resetPoll_response ==
    PGRES_POLLING_OK)
    lspg_query_push( NULL, "select pmac.md2_init()");
    ls_pg_state = LS_PG_STATE_IDLE;
  break:
}
```

7.4.4.50 void lspg_pg_service (struct pollfd * evt)

I/O control to/from the postgresql server.

Parameters

Definition at line 1528 of file lspg.c.

```
{
//
Currently just used to check for notifies
// Other socket communication is done syncronously
//
if( evt->revents & POLLIN) {
  int err;

if( ls_pg_state == LS_PG_STATE_INIT_POLL) {
   lspg_connectPoll_response = PQconnectPoll( q);
```

```
if( lspg_connectPoll_response ==
    PGRES_POLLING_FAILED) {
      ls_pg_state = LS_PG_STATE_RESET;
    return;
  if( ls_pg_state == LS_PG_STATE_RESET_POLL)
    lspg_resetPoll_response = PQresetPoll( q);
    if( lspq_resetPoll_response ==
    PGRES_POLLING_FAILED) {
      ls_pg_state = LS_PG_STATE_RESET;
    return;
  // if in IDLE or RECV we need to call consumeInput first
  if( ls_pg_state == LS_PG_STATE_IDLE) {
    err = PQconsumeInput(q);
    if( err != 1) {
       lslogging_log_message( "consume input failed: %s",
     PQerrorMessage(q));
       ls_pg_state = LS_PG_STATE_RESET;
  }
  if( ls_pg_state == LS_PG_STATE_RECV) {
    lspg_receive();
  // Check for notifies regardless of our state
  // Push as many requests as we have notifies.
    PGnotify *pgn;
    while( 1) {
      pgn = PQnotifies(q);
      if( pgn == NULL)
     lslogging_log_message( "lspg_pg_service: notify
recieved %s", pgn->relname);
      if( strstr( pgn->relname, "_pmac") != NULL) {
         lspg_query_push( lspg_cmd_cb, "EXEVUTE
     md2_queue_next");
    } else if( strstr( pgn->relname, "_diff") != NULL || strstr( pgn->
relname, "_run") != NULL) {
     lspg_query_push( lspg_nextaction_cb,
"EXECUTE nextaction");
      } else if( strstr( pgn->relname, "_sample") != NULL) {
    , case if scisu( pgn->reiname, "_sample") != NULL
lspg_getcurrentsampleid_call();
} else if( strstr( pgn->reiname, "_kvs") != NULL) {
lspg_query_push( lspg_allkvs_cb, "

EXECUTE getkvs");
      PQfreemem( pgn);
  }
if( evt->revents & POLLOUT) {
  if( ls_pg_state == LS_PG_STATE_INIT_POLL) {
    lspg_connectPoll_response = PQconnectPoll( q);
    if( lspg_connectPoll_response ==
PGRES_POLLING_FAILED) {
      ls_pg_state = LS_PG_STATE_RESET;
    return;
  if( ls_pg_state == LS_PG_STATE_RESET_POLL)
    lspg_resetPoll_response = PQresetPoll( q);
    if( lspg_resetPoll_response ==
    PGRES_POLLING_FAILED) {
     ls_pg_state = LS_PG_STATE_RESET;
    return;
```

```
if( ls_pg_state == LS_PG_STATE_SEND) {
    lspg_send_next_query();
}
if( ls_pg_state == LS_PG_STATE_SEND_FLUSH)
    {
    lspg_flush();
}
}
```

7.4.4.51 void lspg_preset_changed_cb (char * event)

Definition at line 1846 of file lspg.c.

```
static char base[] = "Preset Changed ";
char *pn;
lsredis_obj_t *p;
char *v;

pn = strstr( event, base);
if( pn == NULL) {
    lslogging_log_message( "lspg_preset_changed_cb: Could
    not parse '%s'", event);
    return;
}
pn += strlen( base);

p = lsredis_get_obj( "%s", pn);
if( p == NULL) {
    lslogging_log_message( "lspg_preset_changed_cb: Could
    not find variable '%s'", pn);
    return;
}
v = lsredis_getstr( p);
lspg_query_push( NULL, "EXECUTE kvupdate('{%s,%s}'::text[])",
    pn, v);
```

7.4.4.52 lspg_query_queue_t* lspg_query_next()

Return the next item in the postgresql queue.

If there is an item left in the queue then it is returned. Otherwise, NULL is returned.

Definition at line 74 of file lspg.c.

7.4.4.53 void lspg_query_push (void(*)(lspg_query_queue_t *, PGresult *) cb, char * fmt, ...)

Place a query on the queue.

Parameters

in	cb	Our callback function that deals with the response
in	fmt	Printf style function to generate the query

Definition at line 127 of file lspg.c.

```
int idx;
va_list arg_ptr;
pthread_mutex_lock( &lspg_queue_mutex);
// Pause the thread while we service the queue
while( (lspg_query_queue_on + 1) %
    LS_PG_QUERY_QUEUE_LENGTH == lspg_query_queue_off %
    LS_PG_QUERY_QUEUE_LENGTH) {
  pthread_cond_wait( &lspg_queue_cond, &lspg_queue_mutex
idx = lspg_query_queue_on % LS_PG_QUERY_QUEUE_LENGTH
va_end( arg_ptr);
lspg\_query\_queue[idx].qs[LS\_PG\_QUERY\_STRING\_LENGTH
     -1] = 0;
lspg_query_queue[idx].onResponse = cb;
lspg_query_queue_on++;
pthread_kill( lspg_thread, SIGUSR1);
pthread_mutex_unlock( &lspg_queue_mutex);
```

7.4.4.54 void lspg_query_reply_next ()

Remove the oldest item in the queue.

this is called only when there is nothing else to service the reply: this pop does not return anything. We use the ...reply_peek function to return the next item in the reply queue

Definition at line 98 of file lspg.c.

```
f
pthread_mutex_lock( &lspg_queue_mutex);
if( lspg_query_queue_reply != lspg_query_queue_on
    )
    lspg_query_queue_reply++;
pthread_mutex_unlock( &lspg_queue_mutex);
```

7.4.4.55 lspg_query_queue_t* lspg_query_reply_peek()

Return the next item in the reply queue but don't pop it since we may need it more than once.

Call lspg_query_reply_next() when done.

Definition at line 111 of file lspg.c.

```
lspg_query_queue_t *rtn;
pthread_mutex_lock( &lspg_queue_mutex);
```

```
if( lspg_query_queue_reply == lspg_query_queue_on
    )
    rtn = NULL;
else
    rtn = &(lspg_query_queue[(lspg_query_queue_reply
        ) % LS_PG_QUERY_QUEUE_LENGTH]);

pthread_mutex_unlock( &lspg_queue_mutex);
return rtn;
}
```

7.4.4.56 void lspg_receive ()

Receive a result of a query.

Definition at line 1445 of file lspg.c.

```
PGresult *pgr;
lspg_query_queue_t *qqp;
int err:
err = PQconsumeInput( q);
if( err != 1) {
  lslogging_log_message( "consume input failed: %s",
    PQerrorMessage( q));
  ls_pg_state = LS_PG_STATE_RESET;
  return;
// We must call PQgetResult until it returns NULL before sending the next
     query
// This implies that only one query can ever be active at a time and our
     queue
// management should be simple
// We should be in the LS_PG_STATE_RECV here
while( !PQisBusy( q)) {
  pgr = PQgetResult(q);
  if ( pgr == NULL) {
    lspg_query_reply_next();
    // we are now done reading the response from the database
     ls_pg_state = LS_PG_STATE_IDLE;
    break;
  } else {
    ExecStatusType es;
    qqp = lspg_query_reply_peek();
    es = PQresultStatus( pgr);
     if( es != PGRES_COMMAND_OK && es != PGRES_TUPLES_OK) {
      char *emess;
       emess = PQresultErrorMessage( pgr);
if( emess != NULL && emess[0] != 0) {
   lslogging_log_message( "Error from query '%s':\n
     %s", qqp->qs, emess);
     } else {
       // Deal with the response
       // If the response is likely to take awhile we should probably
       // add a new state and put something in the main look to run the
       \ensuremath{//} routine in the main loop. For now, though, we only expect very
      brief onResponse routines
       if( qqp != NULL && qqp->onResponse != NULL)
        qqp->onResponse( qqp, pgr);
    PQclear( pgr);
}
```

```
7.4.4.57 void lspg_run ( )
```

Start 'er runnin'.

Definition at line 1970 of file Ispg.c.

```
pthread_create( &lspg_thread, NULL, lspg_worker, NULL);
lsevents_add_listener( "(appy|appz|capy|capz|scint) In
    Position", lspg_check_preset_in_position_cb
    );
lsevents_add_listener( "(appy|appz|capy|capz|scint)
        Moving", lspg_unset_current_preset_moving_cb
    );
lsevents_add_listener( "Preset Changed (.+)",
    lspg_preset_changed_cb);
lsevents_add_listener( "Sample(Detected|Absent)",
    lspg_sample_detector_cb);
lsevents_add_listener( "Timer Update KVs",
    lspg_update_kvs_cb);
lsevents_add_listener( "cam.zoom In Position",
    lspg_set_scale_cb);
lstimer_add_timer( "Timer Update KVs", -1, 0, 500000000)
    ;
```

7.4.4.58 void lspg_sample_detector_cb (char * event)

log magnet state

Definition at line 1939 of file lspg.c.

```
int present;
if( strcmp( event, "SampleDetected") == 0)
  present = 1;
else
  present = 0;
lspg_query_push( NULL, "SELECT px.logmagnetstate(%s)", present
     ? "TRUE" : "FALSE");
```

7.4.4.59 void lspg_send_next_query ()

send the next queued query to the DB server

Definition at line 1398 of file Ispg.c.

```
//
// Normally we should be in the "send" state
// but we can also send if we are servicing
// a reply
//

lspg_query_queue_t *qqp;
int err;

qqp = lspg_query_next();
if( qqp == NULL) {
    //
    // A send without a query? Should never happen.
    // But at least we shouldn't segfault if it does.
    //
    return;
}

if( qqp->qs[0] == 0) {
    //
    // Do we really have to check this case?
    // It would only come up if we stupidly pushed an empty query string
    // or ran off the end of the queue
    //
```

```
lslogging_log_message( "Popped empty query string.
    Probably bad things are going on.");

lspg_query_reply_next();
ls_pg_state = LS_PG_STATE_IDLE;
} else {
    err = PQsendQuery( q, qqp->qs);
    if( err == 0) {
        lslogging_log_message( "query failed: %s\n",
        PQerrorMessage( q));

    //
    // Don't wait for a reply, just reset the connection
    //
    lspg_query_reply_next();
    ls_pg_state = LS_PG_STATE_RESET;
} else {
    ls_pg_state = LS_PG_STATE_SEND_FLUSH;
}
```

7.4.4.60 void lspg_seq_run_prep_all (long long *skey*, double *kappa*, double *phi*, double *cx*, double *cy*, double *ax*, double *ax*, double *ax*

Convinence function to call seq run prep.

Parameters

in	skey	px.shots key for this image
in	kappa	current kappa postion
in	phi	current phi postition
in	CX	current center table x
in	су	current center table y
in	ax	current alignment table x
in	ay	current alignment table y
in	az	current alignment table z

Definition at line 1194 of file lspg.c.

7.4.4.61 void lspg_seq_run_prep_call (long long *skey*, double *kappa*, double *phi*, double *cx*, double *cy*, double *ax*, double *ax*, double *ax*,

queue up the seq_run_prep query

Parameters

in	skey	px.shots key for this image
in	kappa	current kappa postion
in	phi	current phi postition
in	СХ	current center table x
in	су	current center table y
in	ax	current alignment table x
in	ay	current alignment table y
in	az	current alignment table z

Definition at line 1160 of file lspg.c.

7.4.4.62 void lspg_seq_run_prep_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Callback for the seq_run_prep query.

Parameters

in	qqp	The query item that generated this callback
in	pgr	The result of the query

Definition at line 1148 of file lspg.c.

```
pthread_mutex_lock( &(lspg_seq_run_prep.mutex));
lspg_seq_run_prep.new_value_ready = 1;
pthread_cond_signal( &(lspg_seq_run_prep.cond));
pthread_mutex_unlock( &(lspg_seq_run_prep.mutex));
```

7.4.4.63 void lspg_seq_run_prep_done ()

Indicate we are done waiting.

Definition at line 1188 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_seq_run_prep.mutex));
```

7.4.4.64 void lspg_seq_run_prep_init ()

Initialize the data collection object.

Definition at line 1140 of file lspg.c.

```
lspg_seq_run_prep.new_value_ready = 0;
pthread_mutex_init( &(lspg_seq_run_prep.mutex), NULL);
pthread_cond_init( &(lspg_seq_run_prep.cond), NULL);
}
```

7.4.4.65 void lspg_seq_run_prep_wait ()

Wait for seq run prep query to return.

Definition at line 1180 of file lspg.c.

```
pthread_mutex_lock( &(lspg_seq_run_prep.mutex));
while( lspg_seq_run_prep.new_value_ready == 0
    )
pthread_cond_wait( &(lspg_seq_run_prep.cond), &(
    lspg_seq_run_prep.mutex));
```

7.4.4.66 void lspg_set_scale_cb (char * event)

Fix up xscale and yscale when zoom changes.

Definition at line 1912 of file lspg.c.

7.4.4.67 void lspg_sig_service (struct pollfd * evt)

Service a signal Signals here are treated as file descriptors and fits into our poll scheme.

Parameters

in	evt	The pollfd object that triggered this call

Definition at line 1506 of file lspg.c.

```
{
struct signalfd_siginfo fdsi;

//
// Really, we don't care about the signal,
// it's just used to drop out of the poll
// function when there is something for us
// to do that didn't invovle something coming
// from our postgresql server.
//
// This is accompished by the query_push function
// to notify us that a new query is ready.
//
read( evt->fd, &fdsi, sizeof( struct signalfd_siginfo));
```

7.4.4.68 int lspg_starttransfer_all (int * err, unsigned int nextsample, int sampledetected, double ax, double ay, double az, double horz, double vert, double esttime)

Definition at line 421 of file Ispg.c.

```
lspg_starttransfer.starttransfer != 1) {
  *err = 1;
} else {
  *err = 0;
  rtn = lspg_starttransfer.starttransfer;
}
lspg_starttransfer_done();
return rtn;
}
```

7.4.4.69 void lspg_starttransfer_call (unsigned int *nextsample*, int *sample_detected*, double *ax*, double *ay*, double *az*, double *horz*, double *vert*, double *esttime*)

Definition at line 401 of file lspg.c.

7.4.4.70 void lspg_starttransfer_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Parameters

in	qqp	Our nextsample query
in	pgr	result of the query

Definition at line 380 of file Ispg.c.

```
{
pthread_mutex_lock( &(lspg_starttransfer.mutex));

lspg_starttransfer.new_value_ready = 1;
if( PQntuples( pgr) <=0) {
    lspg_starttransfer.no_rows_returned = 0;
    lspg_starttransfer.starttransfer = 0;
} else {
    lspg_starttransfer.no_rows_returned = 1;
    if( PQgetisnull( pgr, 0, 0) || strtol( PQgetvalue( pgr, 0, 0), NULL, 0) !=
        1)
    lspg_starttransfer.starttransfer = 0;
else
    lspg_starttransfer.starttransfer = 1;
} pthread_cond_signal( &(lspg_starttransfer.cond));
pthread_mutex_unlock( &(lspg_starttransfer.mutex));</pre>
```

7.4.4.71 void lspg_starttransfer_done ()

Definition at line 416 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_starttransfer.mutex));
}
```

7.4.4.72 void lspg_starttransfer_init ()

Definition at line 374 of file lspg.c.

```
lspg_starttransfer.new_value_ready = 0;
pthread_mutex_init( &lspg_starttransfer.mutex, NULL);
pthread_cond_init( &lspg_starttransfer.cond, NULL);
}
```

7.4.4.73 void lspg_starttransfer_wait ()

Definition at line 410 of file lspg.c.

7.4.4.74 void lspg_unset_current_preset_moving_cb (char * event)

Definition at line 1889 of file Ispg.c.

```
lspmac_motor_t *mp;
char cp[64];
int i;

for( i=0; i<strlen( event); i++) {
    cp[i] = 0;
    if( event[i] == ' ')
        break;
    cp[i] = event[i];
}

mp = lspmac_find_motor_by_name( cp);
if( mp == NULL) {
    lslogging_log_message( "
        lspg_unset_current_reset_moving_cb: Could not find motor '%s'", cp);
    return;
}
lspg_query_push( NULL, "EXECUTE kvupdate(
        '{%s.currentPreset, -1}')", cp);</pre>
```

7.4.4.75 void lspg_update_kvs_cb (char * event)

Perhaps update the px.kvs table in postgresql Should be triggered by a timer event.

Definition at line 317 of file Ispg.c.

```
static char s[LS_PG_QUERY_STRING_LENGTH - 64], *fmt;
int i, need_comma, n;
lspmac_motor_t *mp;
int updateme;
double new_value;
s[0] = 0;
need_comma = 0;
for( i=0; i<lspmac_nmotors; i++ ) {</pre>
 mp = &(lspmac_motors[i]);
  pthread_mutex_lock( &mp->mutex);
if( fabs(mp->reported_pg_position - mp->position
    ) >= lsredis_getd(mp->update_resolution)) {
    new_value = mp->position;
    mp->reported_pg_position = mp->position;
    fmt = lsredis_getstr( mp->redis_fmt);
     borrow the redis format
    updateme = 1;
  } else {
```

```
updateme = 0;
 pthread_mutex_unlock( &mp->mutex);
  if( !updateme)
   continue;
 n = strlen(s);
 snprintf(\ \&(s[n])\ ,\ sizeof(s)-n-1,\ "\$s\$s.position,",\ need\_comma++\ ?\ ","\ :\ ""
 n = strlen(s);
  snprintf( &(s[n]), sizeof(s)-n-1, fmt, new_value);
  \ensuremath{//} And again for the original remote interface
  // We'll be able to remove this, someday \,
  n = strlen(s);
 snprintf(\&(s[n]), sizeof(s)-n-1, ",%s,", mp->name);
  snprintf( &(s[n]), sizeof(s)-n-1, fmt, new_value);
 free (fmt);
 n = strlen(s);
 if(n >= sizeof(s) - 64) {
    lspg_query_push( NULL, "EXECUTE kvupdate('{%s}')", s);
    s[0] = 0;
    need\_comma = 0;
 }
if( strlen(s)) {
  lspg\_query\_push ( \ \mbox{NULL, "EXECUTE kvupdate('\{\$s\}')", s);}
```

7.4.4.76 void lspg_wait_for_detector_all ()

Combined call to wait for the detector.

Definition at line 1004 of file lspg.c.

```
lspg_wait_for_detector_call();
lspg_wait_for_detector_wait();
lspg_wait_for_detector_done();
}
```

7.4.4.77 void lspg_wait_for_detector_call ()

initiate the wait for detector query

Definition at line 978 of file Ispg.c.

```
pthread_mutex_lock( &(lspg_wait_for_detector.mutex
    ));
lspg_wait_for_detector.new_value_ready =
    0;
pthread_mutex_unlock( &(lspg_wait_for_detector.mutex
    ));
lspg_query_push( lspg_wait_for_detector_cb
    , "SELECT px.lock_detector_test_block()");
```

7.4.4.78 void lspg_wait_for_detector_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Callback for the wait for detector query.

Definition at line 969 of file lspg.c.

```
pthread_mutex_lock( &(lspg_wait_for_detector.mutex
     ));
lspg_wait_for_detector.new_value_ready =
         1;
pthread_cond_signal( &(lspg_wait_for_detector.cond
         ));
pthread_mutex_unlock( &(lspg_wait_for_detector.mutex
         ));
}
```

7.4.4.79 void lspg_wait_for_detector_done ()

Done waiting for the detector.

Definition at line 997 of file Ispg.c.

7.4.4.80 void lspg_wait_for_detector_init ()

initialize the detector timing object

Definition at line 961 of file lspg.c.

```
lspg_wait_for_detector.new_value_ready =
    0;
pthread_mutex_init( &(lspg_wait_for_detector.mutex
    ), NULL);
pthread_cond_init( &(lspg_wait_for_detector.cond),
    NULL);
```

7.4.4.81 void lspg_wait_for_detector_wait ()

Pause the calling thread until the detector is ready Called by the MD2 thread.

Definition at line 989 of file Ispg.c.

```
pthread_mutex_lock( &(lspg_wait_for_detector.mutex
    ));
while( lspg_wait_for_detector.new_value_ready
    == 0)
    pthread_cond_wait( &(lspg_wait_for_detector.cond)
    , &(lspg_wait_for_detector.mutex));
}
```

7.4.4.82 void lspg_waitcryo_all()

no need to get fancy with the wait cryo command It should not return until the robot is almost ready for air rights Definition at line 606 of file lspg.c.

```
pthread_mutex_lock( &lspg_waitcryo.mutex);
lspg_waitcryo.new_value_ready = 0;
lspg_query_push( lspg_waitcryo_cb, "SELECT px.waitcryo())");
```

7.4.4.83 void lspg_waitcryo_cb (lspg_query_queue_t * qqp, PGresult * pgr)

Definition at line 596 of file lspg.c.

```
pthread_mutex_lock( &lspg_waitcryo.mutex);
lspg_waitcryo.new_value_ready = 1;
pthread_cond_signal( &lspg_waitcryo.cond);
pthread_mutex_unlock( &lspg_waitcryo.mutex);
```

7.4.4.84 void lspg_waitcryo_init ()

Definition at line 590 of file lspg.c.

```
lspg_waitcryo.new_value_ready = 0;
pthread_mutex_init( &lspg_waitcryo.mutex, NULL);
pthread_cond_init( &lspg_waitcryo.cond, NULL);
```

7.4.4.85 void* lspg_worker (void * dummy)

The main loop for the lspg thread.

Parameters

in	dummy	Required by pthreads but unused

Definition at line 1776 of file Ispg.c.

```
static struct pollfd fda[2]; // 0=signal handler, 1=pg socket
static int nfda = 0;
static sigset_t our_sigset;
// block ordinary signal mechanism
sigemptyset( &our_sigset);
sigaddset( &our_sigset, SIGUSR1);
pthread_sigmask(SIG_BLOCK, &our_sigset, NULL);
fda[0].fd = signalfd( -1, &our_sigset, SFD_NONBLOCK);
if( fda[0].fd == -1) {
  char *es;
  es = strerror( errno);
  lslogging_log_message( "Signalfd trouble: %s", es);
fda[0].events = POLLIN;
   make sure file descriptor is not legal until it's been conneceted
lspgfd.fd
while( 1) {
 int pollrtn;
  int poll_timeout_ms;
```

```
lspg_next_state();
if( lspgfd.fd == -1) {
   // Here a connection to the database is not established.
   // Periodicaly try again. Should possibly arrange to reconnect
   // to signalfd but that's unlikely to be nessesary.
  nfda = 1;
  poll_timeout_ms = 10000;
  fda[1].revents = 0;
} else {
   // Arrange to peacfully do nothing until either the pg server sends us
   \ensuremath{//} or someone pushs something onto our queue
  nfda = 2;
   fda[1].fd
                  = lspgfd.fd;
  fda[1].events = lspgfd.events;
fda[1].revents = 0;
  poll\_timeout\_ms = -1;
pollrtn = poll( fda, nfda, poll_timeout_ms);
if( pollrtn && fda[0].revents) {
  lspg_sig_service( &(fda[0]));
  pollrtn--;
if( pollrtn && fda[1].revents) {
   lspg_pg_service( &(fda[1]));
  pollrtn--;
```

7.4.5 Variable Documentation

7.4.5.1 int ls_pg_state = LS_PG_STATE_INIT [static]

State of the Ispg state machine.

Definition at line 38 of file lspg.c.

7.4.5.2 PostgresPollingStatusType lspg_connectPoll_response [static]

Used to determine state while connecting.

Definition at line 59 of file lspg.c.

7.4.5.3 Ispg_demandairrights_t lspg_demandairrights

our demandairrights object

Definition at line 65 of file lspg.c.

7.4.5.4 lspg_getcenter_t lspg_getcenter

the getcenter object

Definition at line 64 of file lspg.c.

7.4.5.5 lspg_getcurrentsampleid_t lspg_getcurrentsampleid

our currentsample id

Definition at line 66 of file lspg.c.

7.4.5.6 lspg_lock_detector_t lspg_lock_detector [static] Definition at line 1078 of file lspg.c. Definition at line 1019 of file lspg.c. 7.4.5.8 lspg_nextsample_t lspg_nextsample the very next sample Definition at line 62 of file lspg.c. 7.4.5.9 lspg_nextshot_t lspg_nextshot the nextshot object Definition at line 63 of file lspg.c. 7.4.5.10 Ispg_query_queue_t Ispg_query_queue[LS_PG_QUERY_QUEUE_LENGTH] [static] Our query queue. Definition at line 51 of file lspg.c. **7.4.5.11** unsigned int lspg_query_queue_off = 0 [static] The last item still being used (on == off means nothing in queue) Definition at line 53 of file lspg.c. **7.4.5.12** unsigned int lspg_query_queue_on = 0 [static] Next position to add something to the queue. Definition at line 52 of file lspg.c. **7.4.5.13** unsigned int lspg_query_queue_reply = 0 [static] The current item being digested. Normally off <= reply <= on. Corner case of queue wrap arround works because we only increment and compare for equality. Definition at line 54 of file lspg.c. 7.4.5.14 pthread_cond_t lspg_queue_cond [static]

keeps the queue from overflowing Definition at line 43 of file lspg.c.

```
7.4.5.15 pthread_mutex_t lspg_queue_mutex [static]
keep the queue from getting tangled
Definition at line 42 of file lspg.c.
7.4.5.16 PostgresPollingStatusType lspg_resetPoll_response [static]
Used to determine state while reconnecting.
Definition at line 60 of file lspg.c.
7.4.5.17 lspg_seq_run_prep_t lspg_seq_run_prep [static]
Definition at line 1136 of file lspg.c.
7.4.5.18 lspg_starttransfer_t lspg_starttransfer
start a sample transfer
Definition at line 67 of file lspg.c.
7.4.5.19 pthread_t lspg_thread [static]
our worker thread
Definition at line 41 of file lspg.c.
7.4.5.20 lspg_wait_for_detector_t lspg_wait_for_detector [static]
Instance of the detector timing object.
Definition at line 957 of file Ispg.c.
7.4.5.21 lspg_waitcryo_t lspg_waitcryo
signal the robot
Definition at line 68 of file lspg.c.
7.4.5.22 struct pollfd lspgfd [static]
our poll info
Definition at line 44 of file lspg.c.
7.4.5.23 struct timeval lspg_time_sent now [static]
used to ensure we do not inundate the db server with connection requests
Definition at line 39 of file lspg.c.
```

7.4.5.24 PGconn*q=NULL [static]

Database connector.

Definition at line 58 of file lspg.c.

7.5 Ispmac.c File Reference

Routines concerned with communication with PMAC.

```
#include "pgpmac.h"
```

Data Structures

· struct md2StatusStruct

The block of memory retrieved in a status request.

- · struct Ispmac ascii buffers struct
- · struct Ispmac dpascii queue struct
- struct lspmac_combined_move_struct

Macros

- #define LS PMAC STATE RESET -1
- #define LS PMAC STATE DETACHED 0
- #define LS PMAC STATE IDLE 1
- #define LS PMAC STATE SC 2
- #define LS_PMAC_STATE_WACK_NFR 3
- #define LS PMAC STATE WACK CC 4
- #define LS_PMAC_STATE_WACK 5
- #define LS PMAC STATE GMR 6
- #define LS PMAC STATE CR 7
- #define LS_PMAC_STATE_RR 8
- #define LS_PMAC_STATE_WACK_RR 9
- #define LS_PMAC_STATE_GB 10
- #define LS_PMAC_STATE_WCR 11
- #define LS_PMAC_STATE_WGB 12
- #define LSPMAC_MAX_MOTORS 48
- #define LSPMAC_PRESET_REGEX "(.*\\.%s\\.presets)\\.([0-9]+)\\.(name|position)"

Regex to pick out preset name and corresponding position.

• #define PMACPORT 1025

The PMAC (only) listens on this port.

#define pmac_cmd_size 8

PMAC command size in bytes.

- #define VR_UPLOAD 0xc0
- #define VR_DOWNLOAD 0x40
- #define VR_PMAC_SENDLINE 0xb0
- #define VR_PMAC_GETLINE 0xb1
- #define VR_PMAC_FLUSH 0xb3
- #define VR_PMAC_GETMEM 0xb4
- #define VR_PMAC_SETMEM 0xb5
- #define VR_PMAC_SENDCTRLCHAR 0xb6
- #define VR_PMAC_SETBIT 0xba

- #define VR_PMAC_SETBITS 0xbb
- #define VR_PMAC_PORT 0xbe
- #define VR PMAC GETRESPONSE 0xbf
- #define VR PMAC READREADY 0xc2
- #define VR CTRL RESPONSE 0xc4
- #define VR PMAC GETBUFFER 0xc5
- #define VR_PMAC_WRITEBUFFER 0xc6
- #define VR_PMAC_WRITEERROR 0xc7
- #define VR FWDOWNLOAD 0xcb
- #define VR IPADDRESS 0xe0
- #define PMAC MIN CMD TIME 10000.0

Minimum time between commands to the pmac.

• #define PMAC CMD QUEUE LENGTH 2048

Size of the PMAC command queue.

#define LSPMAC DPASCII QUEUE LENGTH 1024

Typedefs

typedef struct md2StatusStruct md2_status_t

The block of memory retrieved in a status request.

· typedef struct

lspmac_ascii_buffers_struct lspmac_ascii_buffers_t

· typedef struct

lspmac_dpascii_queue_struct lspmac_dpascii_queue_t

· typedef struct

lspmac_combined_move_struct lspmac_combined_move_t

Functions

void lspmac_get_ascii (char *)

Forward declarateion.

• double lspmac_lut (int nlut, double *lut, double x)

Look up table support for motor positions (think x=zoom, y=light intensity) use a lookup table to find the "counts" to move the motor to the requested position The look up table is a simple one dimensional array with the x values as even indicies and the y values as odd indices.

- double lspmac_rlut (int nlut, double *lut, double y)
- void hex_dump (int n, unsigned char *s)

Prints a hex dump of the given data.

void cleanstr (char *s)

Replace \r with \n in null terminated string and print result to terminal.

void IsConnect (char *ipaddr)

Connect to the PMAC socket.

void lspmac_reset_queue ()

Clear the queue as part of PMAC reinitialization.

pmac_cmd_queue_t * lspmac_push_queue (pmac_cmd_queue_t *cmd)

Put a new command on the queue.

pmac_cmd_queue_t * lspmac_pop_queue ()

Remove the oldest queue item.

pmac_cmd_queue_t * lspmac_pop_reply ()

Remove the next command queue item that is waiting for a reply.

 pmac_cmd_queue_t * lspmac_send_command (int rqType, int rq, int wValue, int wIndex, int wLength, char *data, void(*responseCB)(pmac_cmd_queue_t *, int, char *), int no_reply, char *event) Compose a packet and send it to the PMAC.

void lspmac_SockFlush ()

Reset the PMAC socket from the PMAC side.

void Ispmac Reset ()

Clear the queue and put the PMAC into a known state.

void lspmac_Error (char *buff)

The service routing detected an error condition.

void Ispmac Service (struct pollfd *evt)

Service routine for packet coming from the PMAC.

void lspmac_GetShortReplyCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

Receive a reply that does not require multiple buffers.

void lspmac_SendControlReplyPrintCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

Receive a reply to a control character Print a "printable" version of the character to the terminal Followed by a hex dump of the response.

void lspmac_GetmemReplyCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

Service a reply to the getmem command.

pmac_cmd_queue_t * lspmac_SockGetmem (int offset, int nbytes)

Request a chunk of memory to be returned.

pmac_cmd_queue_t * Ispmac_SockSendline (char *event, char *fmt,...)

Send a one line command.

• pmac_cmd_queue_t * lspmac_SockSendline_nr (char *event, char *fmt,...)

Send a command and ignore the response.

pmac_cmd_queue_t * Ispmac_SockSendControlCharPrint (char *event, char c)

Send a control character.

void lspmac_Getmem ()

Request a block of double buffer memory.

void lspmac bo read (lspmac motor t *mp)

Read the state of a binary i/o motor This is the read method for the binary i/o motor class.

void lspmac_dac_read (lspmac_motor_t *mp)

Read a DAC motor position.

void lspmac shutter read (lspmac motor t *mp)

Fast shutter read routine The shutter is mildly complicated in that we need to take into account the fact that the shutter can open and close again between status updates.

void lspmac_home1_queue (lspmac_motor_t *mp)

Home the motor.

void lspmac_home2_queue (lspmac_motor_t *mp)

Second stage of homing.

double lspmac_getPosition (lspmac_motor_t *mp)

get the motor position (with locking)

void lspmac_pmacmotor_read (lspmac_motor_t *mp)

Read the position and status of a normal PMAC motor.

int lspmac_getBIPosition (lspmac_bi_t *bip)

get binary input value

void lspmac_get_status_cb (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

Service routing for status upate This updates positions and status information.

void lspmac_get_status ()

Request a status update from the PMAC.

• void lspmac_more_ascii_cb (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

we are expecting more characters from the DPRAM ASCII interface

void lspmac_get_ascii_cb (pmac_cmd_queue_t *cmd, int nreceived, char *buff)

service the ascii buffer request response

 void lspmac_asciicmdCB (pmac_cmd_queue_t *cmd, int nreceived, char *buf) PMAC has received our ascii command request Now see when it is ready for the next one. void lspmac SockSendDPline (char *event, char *fmt,...) prepare (queue up) a line to send the dpram ascii command interface void lspmac_SockSendDPControlCharCB (pmac_cmd_queue_t *cmd, int nreceived, char *buf) • void lspmac_SockSendDPControlChar (char *event, char c) use dpram ascii interface to send a control character void Ispmac SockSendDPqueue () void lspmac_abort () abort motion and try to recover void lspmac_GetAllIVarsCB (pmac_cmd_queue_t *cmd, int nreceived, char *buff) Receive the values of all the I variables Update our Postgresql database with the results. • void lspmac_GetAllIVars () Request the values of all the I variables. void Ispmac GetAllMVarsCB (pmac cmd queue t *cmd, int nreceived, char *buff) Receive the values of all the M variables Update our database with the results. void lspmac_GetAllMVars () Request the values of all the M variables. void lspmac sendcmd nocb (char *fmt,...) Send a command that does not need to deal with the reply. void lspmac_sendcmd (char *event, void(*responseCB)(pmac_cmd_queue_t *, int, char *), char *fmt,...) PMAC command with call back. void lspmac_next_state () State machine logic. void * Ispmac_worker (void *dummy) Our Ispmac worker thread. int lspmac_movedac_queue (lspmac_motor_t *mp, double requested_position) Move method for dac motor objects (ie, lights) • int lspmac_movezoom_queue (lspmac_motor_t *mp, double requested_position) Move method for the zoom motor. • int lspmac_move_preset_queue (lspmac_motor_t *mp, char *preset_name) Move a given motor to one of its preset positions. • int lspmac_test_preset (lspmac_motor_t *mp, char *preset_name, double tolerance) see if the motor is within tolerance of the preset 1 means yes, it is 0 mean no it isn't or that the preset was not found int lspmac_moveabs_fshut_queue (lspmac_motor_t *mp, double requested_position) Move method for the fast shutter. int lspmac moveabs bo queue (lspmac motor t *mp, double requested position) Move method for binary i/o motor objects. void lspmac_moveabs_timed_queue (lspmac_motor_t *mp, double start, double delta, double time) timed motor move int lspmac_moveabs_frontlight_oo_queue (lspmac_motor_t *mp, double pos) "move" frontlight on/off int lspmac_moveabs_flight_factor_queue (lspmac_motor_t *mp, double pos) • int lspmac_moveabs_blight_factor_queue (lspmac_motor_t *mp, double pos) void Ispmac video rotate (double secs) Special motion program to collect centering video. int lspmac_est_move_time (double *est_time, int *mmask, lspmac_motor_t *mp_1, int jog_1, char *preset-_1, double end_point_1,...) Move the motors and estimate the time it'll take to finish the job. int Ispmac est move time wait (double move time, int mmask)

wait for motion to stop returns non-zero if the wait timed out

• int lspmac_move_or_jog_abs_queue (lspmac_motor_t *mp, double requested_position, int use_jog)

Move method for normal stepper and servo motor objects Returns non-zero on abort, zero if OK.

• int lspmac_move_or_jog_preset_queue (lspmac_motor_t *mp, char *preset, int use_jog)

move using a preset value returns 0 on success, non-zero on error

int lspmac_moveabs_queue (lspmac_motor_t *mp, double requested_position)

Use coordinate system motion program, if available, to move motor to requested position.

int lspmac_jogabs_queue (lspmac_motor_t *mp, double requested_position)

Use jog to move motor to requested position.

int lspmac_moveabs_wait (lspmac_motor_t *mp, double timeout_secs)

Wait for motor to finish moving.

void Ispmac motor init (Ispmac motor t *d, char *name)

Helper funciton for the init calls.

• Ispmac_motor_t * Ispmac_motor_init (Ispmac_motor_t *d, int wy, int wx, int *posp, int *stat1p, int *stat2p, char *wtitle, char *name, int(*moveAbs)(Ispmac_motor_t *, double), int(*jogAbs)(Ispmac_motor_t *, double))

Initialize a pmac stepper or servo motor.

lspmac_motor_t * lspmac_fshut_init (lspmac_motor_t *d)

Initalize the fast shutter motor.

Ispmac_motor_t * Ispmac_bo_init (Ispmac_motor_t *d, char *name, char *write_fmt, int *read_ptr, int read_mask)

Initialize binary i/o motor.

Ispmac_motor_t * Ispmac_dac_init (Ispmac_motor_t *d, int *posp, char *mvar, char *name, int(*move-Abs)(Ispmac_motor_t *, double))

Initialize DAC motor Note that some motors require further initialization from a database query.

void lspmac_soft_motor_read (lspmac_motor_t *p)

Dummy routine to read a soft motor.

- Ispmac_motor_t * Ispmac_soft_motor_init (Ispmac_motor_t *d, char *name, int(*moveAbs)(Ispmac_motor_t *, double))
- $\bullet \ \ \mathsf{lspmac_bi_t} \ * \ \mathsf{lspmac_bi_init} \ (\mathsf{lspmac_bi_t} \ * \mathsf{d}, \ \mathsf{int} \ * \mathsf{ptr}, \ \mathsf{int} \ \mathsf{mask}, \ \mathsf{char} \ * \mathsf{onEvent}, \ \mathsf{char} \ * \mathsf{offEvent})$

Initialize binary input.

• void lspmac_init (int ivarsflag, int mvarsflag)

Initialize this module.

- void lspmac_cryoSwitchChanged_cb (char *event)
- void Ispmac scint inPosition cb (char *event)

Maybe start drying off the scintilator.

void lspmac_backLight_up_cb (char *event)

Turn on the backlight whenever it goes up.

void lspmac_backLight_down_cb (char *event)

Turn off the backlight whenever it goes down.

void lspmac_light_zoom_cb (char *event)

Set the backlight intensity whenever the zoom is changed (and the backlight is up)

void lspmac_scint_maybe_move_sample_cb (char *event)

Perhaps we need to move the sample out of the way.

void lspmac_scint_maybe_return_sample_cb (char *event)

Perhaps we need to return the sample to the beam.

• void Ispmac scint dried cb (char *event)

Turn off the dryer.

void lspmac_zoom_lut_setup ()

Set up lookup table for zoom.

void lspmac_flight_lut_setup ()

Set up lookup table for flight.

· void lspmac_blight_lut_setup ()

Set up lookup table for blight.

void Ispmac fscint lut setup ()

Set up lookup table for fscint.

- Ispmac_motor_t * Ispmac_find_motor_by_name (char *name)
- void lspmac_command_done_cb (char *event)
- void Ispmac run ()

Start up the Ispmac thread.

Variables

static int ls_pmac_state = LS_PMAC_STATE_DETACHED

Current state of the PMAC communications state machine.

· int Ispmac shutter state

State of the shutter, used to detect changes.

• int lspmac_shutter_has_opened

Indicates that the shutter had opened, perhaps briefly even if the state did not change.

pthread_mutex_t lspmac_shutter_mutex

Coordinates threads reading shutter status.

• pthread_cond_t lspmac_shutter_cond

Allows waiting for the shutter status to change.

pthread_mutex_t lspmac_moving_mutex

Coordinate moving motors between threads.

pthread_cond_t lspmac_moving_cond

Wait for motor(s) to finish moving condition.

int lspmac_moving_flags

Flag used to implement motor moving condition.

• static pthread_mutex_t lspmac_ascii_mutex

Keep too many processes from sending commands at once.

• static int lspmac_ascii_busy = 0

flag for condition to wait for

static int omega_zero_search = 0

Indicate we'd really like to know when omega crosses zero.

• static double omega zero velocity = 0

rate (cnts/sec) that omega was traveling when it crossed zero

struct timespec omega_zero_time

Time we believe that omega crossed zero.

• static struct timespec lspmac_status_time

Time the status was read.

• static struct timespec lspmac_status_last_time

Time the status was read.

static pthread_t pmac_thread

our thread to manage access and communication to the pmac

• pthread_mutex_t pmac_queue_mutex

manage access to the pmac command queue

pthread_cond_t pmac_queue_cond

wait for a command to be sent to PMAC before continuing

· static struct pollfd pmacfd

our poll structure

• static int getivars = 0

```
flag set at initialization to send i vars to db
• static int getmvars = 0
     flag set at initialization to send m vars to db
• Ispmac_bi_t Ispmac_bis [32]
     array of binary inputs
• int lspmac_nbis = 0
     number of active binary inputs
• Ispmac_motor_t Ispmac_motors [LSPMAC_MAX_MOTORS]
     All our motors.
• int lspmac_nmotors = 0
     The number of motors we manage.
· struct hsearch_data motors_ht
     A hash table to find motors by name.
• lspmac_motor_t * omega
     MD2 omega axis (the air bearing)
lspmac_motor_t * alignx
     Alignment stage X.
Ispmac_motor_t * aligny
     Alignment stage Y.
lspmac_motor_t * alignz
     Alignment stage X.
• Ispmac_motor_t * anal
     Polaroid analyzer motor.
Ispmac_motor_t * zoom
     Optical zoom.
Ispmac_motor_t * apery
     Aperture Y.
Ispmac_motor_t * aperz
     Aperture Z.
Ispmac_motor_t * capy
     Capillary Y.
lspmac_motor_t * capz
     Capillary Z.
Ispmac_motor_t * scint
     Scintillator Z.
Ispmac_motor_t * cenx
     Centering Table X.
Ispmac_motor_t * ceny
     Centering Table Y.

    Ispmac_motor_t * kappa

     Карра.
Ispmac_motor_t * phi
     Phi (not data collection axis)

    lspmac_motor_t * fshut

     Fast shutter.
• Ispmac_motor_t * flight
     Front Light DAC.

    Ispmac_motor_t * blight

     Back Light DAC.
lspmac_motor_t * fscint
```

Scintillator Piezo DAC.

```
lspmac_motor_t * smart_mag_oo
     Smart Magnet on/off.
• lspmac_motor_t * blight_ud
     Back light Up/Down actuator.
lspmac_motor_t * cryo
     Move the cryostream towards or away from the crystal.
• Ispmac_motor_t * dryer
     blow air on the scintilator to dry it off

    lspmac_motor_t * fluo

     Move the fluorescence detector in/out.
• Ispmac motor t * flight oo
      Turn front light on/off.
lspmac_motor_t * blight_f
     Back light scale factor.
lspmac_motor_t * flight_f
     Front light scale factor.
lspmac_bi_t * lp_air
     Low pressure air OK.
• Ispmac_bi_t * hp_air
     High pressure air OK.
• Ispmac_bi_t * cryo_switch
     that little toggle switch for the cryo
• Ispmac_bi_t * blight_down
     Backlight is down.
• Ispmac_bi_t * blight_up
     Backlight is up.
lspmac_bi_t * cryo_back
     cryo is in the back position
• Ispmac_bi_t * fluor_back
     fluor is in the back position
• lspmac_bi_t * sample_detected
     smart magnet detected sample
lspmac_bi_t * etel_ready
     ETEL is ready.
• lspmac_bi_t * etel_on
     ETEL is on.

    Ispmac bi t * etel init ok

     ETEL initialized OK.
lspmac_bi_t * minikappa_ok
     Minikappa is OK (whatever that means)
lspmac_bi_t * smart_mag_on
     smart magnet is on
lspmac_bi_t * arm_parked
     (whose arm? parked where?)
• Ispmac_bi_t * shutter_open
     shutter is open (note in pmc says this is a slow input)
· Ispmac_bi_t * smart_mag_err
     smart magnet error (coil broken perhaps)

    Ispmac bi t * smart mag off

     smart magnet is off
```

static unsigned char dbmem [64 *1024]

double buffered memory

• static int dbmemIn = 0

next location

 static struct timeval pmac_time_sent now

used to ensure we do not send commands to the pmac too often. Only needed for non-DB commands.

- · static pmac_cmd_t rr_cmd
- · static pmac cmd t gb cmd
- static pmac_cmd_t cr_cmd

commands to send out "readready", "getbuffer", "controlresponse" (initialized in main)

static pmac_cmd_queue_t ethCmdQueue [PMAC_CMD_QUEUE_LENGTH]

PMAC command queue.

• static unsigned int ethCmdOn = 0

points to next empty PMAC command queue position

• static unsigned int ethCmdOff = 0

points to current command (or none if == ethCmdOn)

• static unsigned int ethCmdReply = 0

Used like ethCmdOff only to deal with the pmac reply to a command.

static char * pmac_error_strs []

Decode the errors perhaps returned by the PMAC.

static md2 status t md2 status

Buffer for MD2 Status.

• pthread mutex t md2 status mutex

Synchronize reading/writting status buffer.

- static lspmac_ascii_buffers_t lspmac_ascii_buffers
- pthread_mutex_t lspmac_ascii_buffers_mutex
- static lspmac_dpascii_queue_t lspmac_dpascii_queue [LSPMAC_DPASCII_QUEUE_LENGTH]
- static uint32 t Ispmac dpascii on = 0
- static uint32_t lspmac_dpascii_off = 0

7.5.1 Detailed Description

Routines concerned with communication with PMAC. Test suite for the pgpmac routines.

```
\date 2012 - 2013
\author Keith Brister
\copyright All Rights Reserved
```

This is a state machine (surprise!)

Lacking is support for writingbuffer, control writing and reading, as well as double buffered memory It looks like several different methods of managing PMAC communications are possible. Here is set up a queue of outgoing commands and deal completely with the result before sending the next. A full handshake of acknowledgements and "readready" is expected.

Most of these states are to deal with the "serial-port" style of communications. Things are surprisingly simple for the double buffer ascii and control character methods.

```
State Description

-1 Reset the connection

0 Detached: need to connect to tcp port

1 Idle (waiting for a command to send to the pmac)

2 Send command
```

```
3
        Waiting for command acknowledgement (no further response expected)
 4
       Waiting for control character acknowledgement (further response expected)
 5
       Waiting for command acknowledgement (further response expected)
 6
       Waiting for get memory response
7
       Send controlresponse
8
       Send readready
9
       Waiting for acknowledgement of "readready"
10
       Send readbuffer
11
       Waiting for control response
12
       Waiting for readbuffer response
```

Date

2013

Author

Keith Brister

Copyright

All Rights Reserved

A place to put unit tests.

Definition in file Ispmac.c.

7.5.2 Macro Definition Documentation

7.5.2.1 #define LS_PMAC_STATE_CR 7

Definition at line 52 of file Ispmac.c.

7.5.2.2 #define LS_PMAC_STATE_DETACHED 0

Definition at line 45 of file Ispmac.c.

7.5.2.3 #define LS_PMAC_STATE_GB 10

Definition at line 55 of file Ispmac.c.

7.5.2.4 #define LS_PMAC_STATE_GMR 6

Definition at line 51 of file Ispmac.c.

7.5.2.5 #define LS_PMAC_STATE_IDLE 1

Definition at line 46 of file Ispmac.c.

7.5.2.6 #define LS_PMAC_STATE_RESET -1

Definition at line 44 of file Ispmac.c.

7.5.2.7 #define LS_PMAC_STATE_RR 8

Definition at line 53 of file Ispmac.c.

7.5.2.8 #define LS_PMAC_STATE_SC 2

Definition at line 47 of file Ispmac.c.

7.5.2.9 #define LS_PMAC_STATE_WACK 5

Definition at line 50 of file Ispmac.c.

7.5.2.10 #define LS_PMAC_STATE_WACK_CC 4

Definition at line 49 of file Ispmac.c.

7.5.2.11 #define LS_PMAC_STATE_WACK_NFR 3

Definition at line 48 of file Ispmac.c.

7.5.2.12 #define LS_PMAC_STATE_WACK_RR 9

Definition at line 54 of file Ispmac.c.

7.5.2.13 #define LS_PMAC_STATE_WCR 11

Definition at line 56 of file Ispmac.c.

7.5.2.14 #define LS_PMAC_STATE_WGB 12

Definition at line 57 of file Ispmac.c.

7.5.2.15 #define LSPMAC_DPASCII_QUEUE_LENGTH 1024

Definition at line 367 of file Ispmac.c.

7.5.2.16 #define LSPMAC_MAX_MOTORS 48

Definition at line 94 of file Ispmac.c.

7.5.2.17 #define LSPMAC_PRESET_REGEX " $(.*\\.\%s\\.presets)\\.([0-9]+)\\.(name|position)$ "

Regex to pick out preset name and corresponding position.

Definition at line 150 of file Ispmac.c.

7.5.2.18 #define PMAC_CMD_QUEUE_LENGTH 2048

Size of the PMAC command queue.

Definition at line 194 of file Ispmac.c.

7.5.2.19 #define pmac_cmd_size 8

PMAC command size in bytes.

Definition at line 160 of file Ispmac.c.

7.5.2.20 #define PMAC_MIN_CMD_TIME 10000.0

Minimum time between commands to the pmac.

Definition at line 190 of file Ispmac.c.

7.5.2.21 #define PMACPORT 1025

The PMAC (only) listens on this port.

Definition at line 154 of file Ispmac.c.

7.5.2.22 #define VR_CTRL_RESPONSE 0xc4

Definition at line 176 of file Ispmac.c.

7.5.2.23 #define VR_DOWNLOAD 0x40

Definition at line 163 of file Ispmac.c.

7.5.2.24 #define VR_FWDOWNLOAD 0xcb

Definition at line 180 of file lspmac.c.

7.5.2.25 #define VR_IPADDRESS 0xe0

Definition at line 181 of file Ispmac.c.

7.5.2.26 #define VR_PMAC_FLUSH 0xb3

Definition at line 167 of file Ispmac.c.

7.5.2.27 #define VR_PMAC_GETBUFFER 0xc5

Definition at line 177 of file Ispmac.c.

7.5.2.28 #define VR_PMAC_GETLINE 0xb1

Definition at line 166 of file Ispmac.c.

7.5.2.29 #define VR_PMAC_GETMEM 0xb4

Definition at line 168 of file Ispmac.c.

7.5.2.30 #define VR_PMAC_GETRESPONSE 0xbf

Definition at line 174 of file Ispmac.c.

7.5.2.31 #define VR_PMAC_PORT 0xbe

Definition at line 173 of file Ispmac.c.

7.5.2.32 #define VR_PMAC_READREADY 0xc2

Definition at line 175 of file Ispmac.c.

7.5.2.33 #define VR_PMAC_SENDCTRLCHAR 0xb6

Definition at line 170 of file Ispmac.c.

7.5.2.34 #define VR_PMAC_SENDLINE 0xb0

Definition at line 165 of file Ispmac.c.

7.5.2.35 #define VR_PMAC_SETBIT 0xba

Definition at line 171 of file Ispmac.c.

7.5.2.36 #define VR_PMAC_SETBITS 0xbb

Definition at line 172 of file Ispmac.c.

7.5.2.37 #define VR_PMAC_SETMEM 0xb5

Definition at line 169 of file Ispmac.c.

7.5.2.38 #define VR_PMAC_WRITEBUFFER 0xc6

Definition at line 178 of file Ispmac.c.

7.5.2.39 #define VR_PMAC_WRITEERROR 0xc7

Definition at line 179 of file Ispmac.c.

7.5.2.40 #define VR_UPLOAD 0xc0

Definition at line 162 of file Ispmac.c.

7.5.3 Typedef Documentation

7.5.3.1 typedef struct lspmac_ascii_buffers_struct lspmac_ascii_buffers_t

7.5.3.2 typedef struct lspmac_combined_move_struct lspmac_combined_move_t

7.5.3.3 typedef struct lspmac_dpascii_queue_struct lspmac_dpascii_queue_t

7.5.3.4 typedef struct md2StatusStruct md2_status_t

The block of memory retrieved in a status request.

7.5.4 Function Documentation

7.5.4.1 void _lspmac_motor_init (lspmac_motor_t * d, char * name)

Helper funciton for the init calls.

Definition at line 3355 of file Ispmac.c.

```
lspmac_nmotors++;
pthread_mutex_init( &(d->mutex), NULL);
{\tt pthread\_cond\_init(~\&(d->cond),~NULL);}
d->name
                  = strdup(name);
d->active
                     = lsredis_get_obj( "%s.active",
      d->active_init
  %s.active_init", d->name);
eaxis = lsredis_get_obj( "%s.axis",
coord_num
%s.coord_num", d->name);
pome = lsredis_get_obj( "%s.home",
%s.inactive_init", d->name);
d->in_position_band = lsredis_get_obj( "
   %s.in_position_band", d->name);
                 = lsredis_get_obj( "%s.format",
d->redis_fmt
            d->name);
  d->max_accel
d->max speed
d->min_pos
   d->motor num
d->neg_limit_hit
d->neutral_pos
                        = lsredis_get_obj( "
   d->status_str
d->u2c
        d->name);
= lsredis_get_obj( "%s.unit",
d->unit
      d->name);
                   = lsredis_get_obj( "
d->update_resolution
   %s.update_resolution", d->name);
        = NULL;
d->lut
                   = 0;
d->nlut
                 = 0;
= NULL;
d->homing
d->dac_mvar
d->actual_pos_cnts_p = NULL;
d->actual_pos_cnts_p = NULL;
d->status1_p = NULL;
d->win = NULL;
d->read
                   = NULL;
d->reported_position = INFINITY;
d->reported_pg_position= INFINITY;
```

7.5.4.2 void cleanstr (char *s)

Replace $\$ with $\$ in null terminated string and print result to terminal.

Needed to turn PMAC messages into something printable.

Parameters

in	s	String to print to terminal.
----	---	------------------------------

Definition at line 553 of file Ispmac.c.

```
{
int i;

pthread_mutex_lock( &ncurses_mutex);

for( i=0; i<strlen( s); i++) {
   if( s[i] == '\r')
     wprintw( term_output, "\n");
   else
     wprintw( term_output, "%c", s[i]);
}

pthread_mutex_unlock( &ncurses_mutex);</pre>
```

7.5.4.3 void hex_dump (int n, unsigned char *s)

Prints a hex dump of the given data.

Used to debug packet data.

Parameters

in	n	Number of bytes passed in s
in	s	Data to dump

Definition at line 526 of file Ispmac.c.

7.5.4.4 void IsConnect (char * ipaddr)

Connect to the PMAC socket.

Establish or reestablish communications.

Parameters

in ipaddr String representation of the IP address (dot quad or FQN)

Definition at line 574 of file Ispmac.c.

```
int psock;
                                   // our socket: value stored in pmacfda.fd
int err;
                                   // error code from some system calls \,
struct sockaddr_in *addrP; // our address structure to connect to struct addrinfo ai_hints; // required for getaddrinfo struct addrinfo *ai_resultP; // linked list of address structures (we'll
     always pick the first)
pmacfd.fd
pmacfd.events = 0;
// Initial buffer(s)
memset( &ai_hints, 0, sizeof( ai_hints));
ai_hints.ai_family = AF_INET;
ai_hints.ai_socktype = SOCK_STREAM;
// get address
err = getaddrinfo( ipaddr, NULL, &ai_hints, &ai_resultP);
if( err != 0) {
  lslogging_log_message( "Could not find address: %s",
    gai_strerror( err));
  return;
addrP = (struct sockaddr_in *)ai_resultP->ai_addr;
addrP->sin_port = htons( PMACPORT);
psock = socket( PF_INET, SOCK_STREAM, 0);
if ( psock == -1) {
  lslogging_log_message( "Could not create socket");
  return;
err = connect( psock, (const struct sockaddr *)addrP, sizeof( *addrP));
if( err != 0) {
  lslogging_log_message( "Could not connect socket: %s",
     strerror(errno));
ls_pmac_state = LS_PMAC_STATE_IDLE;
pmacfd.fd = psock;
pmacfd.events = POLLIN;
```

7.5.4.5 void lspmac_abort ()

abort motion and try to recover

Definition at line 2031 of file Ispmac.c.

7.5.4.6 void lspmac_asciicmdCB (pmac_cmd_queue_t * cmd, int nreceived, char * buf)

PMAC has received our ascii command request Now see when it is ready for the next one.

Definition at line 1962 of file Ispmac.c.

```
lspmac_get_ascii( cmd->event);
}
```

7.5.4.7 void lspmac_backLight_down_cb (char * event)

Turn off the backlight whenever it goes down.

Parameters

```
event | Name of the event that called us
```

Definition at line 3744 of file Ispmac.c.

```
blight->moveAbs( blight, 0.0);
}
```

7.5.4.8 void lspmac_backLight_up_cb (char * event)

Turn on the backlight whenever it goes up.

Parameters

```
event Name of the event that called us
```

Definition at line 3737 of file Ispmac.c.

7.5.4.9 Ispmac_bi_t* Ispmac_bi_init (Ispmac_bi_t * d, int * ptr, int mask, char * onEvent, char * offEvent)

Initialize binary input.

Definition at line 3518 of file Ispmac.c.

7.5.4.10 void lspmac_blight_lut_setup ()

Set up lookup table for blight.

Definition at line 3902 of file Ispmac.c.

```
int i:
lsredis_obj_t *p;
pthread_mutex_lock( &blight->mutex);
blight->nlut = 11;
blight->lut = calloc( 2 * blight->nlut, sizeof( double));
if( blight->lut == NULL) {
   lslogging_log_message( "lspmac_blight_lut_setup: out
     of memory");
  exit(-1);
blight->lut[0] = 0;
blight->lut[1] = 0;
for( i=1; i<bli>blight->nlut; i++) {
   p = lsredis_get_obj( "cam.zoom.%d.LightIntensity", i);
  if( p==NULL || strlen( lsredis_getstr(p)) == 0) {
  free( blight->lut);
    blight->lut = NULL;
blight->nlut = 0;
    pthread_mutex_unlock( &blight->mutex);
    lslogging_log_message( "lspmac_blight_lut_setup:
     cannot find MotorPosition element for cam.blight level %d", i);
    return;
  blight->lut[2*i]
  blight->lut[2*i+1] = 20000.0 * lsredis_getd( p) / 100.
    0;
*i+1],
                           lspmac_lut( blight->nlut, blight
    ->lut, blight->lut[2*i]),
                          lspmac_rlut( blight->nlut,
    blight->lut, blight->lut[2*i+1])
pthread_mutex_unlock( &blight->mutex);
```

7.5.4.11 Ispmac_motor_t* Ispmac_bo_init (Ispmac_motor_t * d, char * name, char * write_fmt, int * read_ptr, int read_mask)

Initialize binary i/o motor.

Parameters

in	d	Our uninitialized motor object
in	name	Name of motor to coordinate with DB
in	write_fmt	Format string used to generate PMAC command to move motor
in	read_ptr	Pointer to byte in md2_status to find position
in	read_mask	Bitmask to find position in *read_ptr

Definition at line 3449 of file Ispmac.c.

7.5.4.12 void lspmac_bo_read (lspmac_motor_t * mp)

Read the state of a binary i/o motor This is the read method for the binary i/o motor class.

Parameters

in	тр	The motor

Definition at line 1137 of file Ispmac.c.

```
int pos, changed;
pthread_mutex_lock( &(mp->mutex));
pos = (*(mp->read_ptr) & mp->read_mask) == 0 ? 0 : 1;
changed = pos != mp->position;
mp->position = pos;
pthread_mutex_unlock( &(mp->mutex));
if( changed)
   lsevents_send_event( "%s %d", mp->name, pos);
}
```

7.5.4.13 void lspmac_command_done_cb (char * event)

Definition at line 3979 of file Ispmac.c.

```
int i;
char s[32];
lspmac_motor_t *mp;
for( i=0; i<sizeof(s)-1 && event[i]; i++) {</pre>
  s[i] = 0;
  if( event[i] == ' ')
    break;
  s[i] = event[i];
mp = lspmac_find_motor_by_name( s);
if ( mp == NULL)
  return;
pthread_mutex_lock( &(mp->mutex));
mp->command_sent = 1;
pthread_cond_signal( &(mp->cond));
pthread_mutex_unlock( & (mp->mutex));
return;
```

7.5.4.14 void lspmac_cryoSwitchChanged_cb (char * event)

Definition at line 3699 of file Ispmac.c.

```
int pos;

pthread_mutex_lock( &(cryo->mutex));
pos = cryo->position;
pthread_mutex_unlock( &(cryo->mutex));

cryo->moveAbs( cryo, pos ? 0.0 : 1.0);
}
```

7.5.4.15 Ispmac_motor_t* Ispmac_dac_init (Ispmac_motor_t * d, int * posp, char * mvar, char * name, int(*)(Ispmac_motor_t *, double) moveAbs)

Initialize DAC motor Note that some motors require further initialization from a database query.

For this reason this initialzation code must be run before the database queue is allowed to be processed.

Parameters

out	d	Returns the (almost) initialized motor object [in,out] unitintialized motor
in	posp	Location of current position
in	mvar	M variable, ie, "M1200"
in	name	name to coordinate with DB
in	moveAbs	Method to use to move this motor

Definition at line 3476 of file Ispmac.c.

```
_lspmac_motor_init( d, name);
d->moveAbs = moveAbs;
d->jogAbs = moveAbs;
d->read = lspmac_dac_read;
d->actual_pos_cnts_p = posp;
d->dac_mvar = strdup(mvar);
return d;
}
```

7.5.4.16 void lspmac_dac_read (lspmac_motor_t * mp)

Read a DAC motor position.

Parameters

in	тр	The motor

Definition at line 1157 of file Ispmac.c.

```
double u2c;

pthread_mutex_lock( & (mp->mutex));
mp->actual_pos_cnts = *mp->actual_pos_cnts_p;
u2c = lsredis_getd( mp->u2c);

if( mp->nlut >0 && mp->lut != NULL) {
   if( u2c == 0.0)
       u2c = 1.0;
   mp->position = lspmac_rlut( mp->nlut, mp->lut, mp
       ->actual_pos_cnts/u2c);
} else {
   if( u2c != 0.0) {
       mp->position = mp->actual_pos_cnts / u2c;
} else {
   mp->position = mp->actual_pos_cnts;
}
}
pthread_mutex_unlock( & (mp->mutex));
```

7.5.4.17 void lspmac_Error (char * buff)

The service routing detected an error condition.

Scan the response buffer for an error code and print it out.

Parameters

in	buff	Buffer returned by PMAC perhaps containing a NULL terminated message.
----	------	---

Definition at line 783 of file Ispmac.c.

```
int err;
//
// assume buff points to a 1400 byte array of stuff read from the pmac
//

if( buff[0] == 7 && buff[1] == 'E' && buff[2] == 'R' && buff[3] == 'R') {
   buff[7] = 0; // For null termination
   err = atoi( &(buff[4]));
   if( err > 0 && err < 20) {
      lslogging_log_message( pmac_error_strs
      [err]);
      pthread_mutex_lock( &ncurses_mutex);
      wprintw( term_output, "\n%s\n", pmac_error_strs
      [err]);
      wnoutrefresh( term_output);
      wnoutrefresh( term_input);
      doupdate();
      pthread_mutex_unlock( &ncurses_mutex);
   }
}
lspmac_Reset();
}</pre>
```

7.5.4.18 int lspmac_est_move_time (double * est_time, int * mmask, lspmac_motor_t * mp_1, int jog_1, char * preset_1, double end_point_1, ...)

Move the motors and estimate the time it'll take to finish the job.

Returns the estimate time and the coordinate system mask to waite for

Parameters

est_time	Returns number of seconds we estimate the move(s) will take
mmask	Mask of coordinate systems we are trying to move, excluding jogs. Used to wait for motions to
	complete
mp_1	Pointer to first motor
jog_1	1 to force a jog, 0 to try a motion program DO NOT MIX JOGS AND MOTION PROGRAMS IN
	THE SAME COORDINATE SYSTEM!
preset_1	Name of preset we'd like to move to or NULL if end_point_1 should be used instead
end_point_1	End point for the first motor. Ignored if preset_1 is non null and identifies a valid preset for this
	motor
	Perhaps more quads of motors, jog flags, preset names, and end points. End is a NULL motor
	pointer MUST END ARG LIST WITH NULL

{

- < units to counts
- < The total distance we need to go
- < Our maximum velocity
- < Our maximum acceleration
- < Total time for this motor
- < coordinate system motion flags

Definition at line 2650 of file Ispmac.c.

```
static char axes[] = "XYZUVWABC";
static int qs[9];
```

```
static lspmac_combined_move_t motions[32];
int j;
va_list arg_ptr;
lspmac_motor_t *mp;
double ep, maybe_ep;
char *ps;
double
 min_pos,
 max_pos,
  neutral_pos,
  u2c.
  D,
  v,
  Α,
 Tt;
int err;
int jog;
int i;
int m5075;
// reset our coordinate flags and command strings
for( i=0; i<32; i++) {
  motions[i].moveme = 0;</pre>
m5075 = 0;
// Initialze first iteration
//
*est_time = 0.0;
mp = mp_1;
ps = preset_1;
ep = end_point_1;
jog = jog_1;
va_start( arg_ptr, end_point_1);
while(1) {
  /*
                                      Constant
                                      Velocity
                                      Time (Ct.)
      V
      e :
      o :
      с:
      i :
      t :
      у:_
                                        Time
                              |<-- Acceleration Time (At)</pre>
                                  Total Time (Tt) ---->|
           Assumption 1: We can replace S curve acceleration with linear
     acceleration
           for the purposes of distance and time calculations for the timeout
           period that we are attempting to calculate here.
           Ct = Constant Velocity Time. The time spent at constant velocity.
          At = Acceleration Time. Time spent accelerating at either end of
         ramp, that is,
1/2 the total time spent accelerating and decelerating.
     the
              = the total distance we need to travel
          V = constant velocity. Here we use the motor's maximum velocity.
          A = the motor acceleration, Here it's the maximum acceleration.
          V = A * At
          or At = V/A
           The Total Time (Tt) is
           Tt = Ct + 2 * At
          If we had infinite acceleration the total time would be \ensuremath{\text{D/V}}. To
     account for finite acceleration we just need to
```

```
adjust this for the average velocity while accelerating (0.5\ \text{V}).
   This neatly adds a single V/A term:
               Tt = D/V + V/A
        (1)
        When the distance is short, we need a different calculation:
        D = 0.5 * A * T1^2 + 0.5 * A * T2^2 (T1 = acceleration time and
   T2 = deceleration time)
        or, since total time Tt = T1 + T2 and T1 = T2,
        D = A * (0.5*Tt)^2
        or
       (2) Tt = 2 * sqrt(D/A)
        When we accelerate to the maximum speed the time it takes is V/A so
   the distance we travel (Da) is
       Da = 0.5 * A * (V/A)^2
        or
       Da = 0.5 * V^2 / A
       So when D > 2 * Da, or
       D > V^2 / A
        we need to use equation (1) otherwise we need to use equation (2)
Tt = 0.0;
if( mp != NULL && mp->max_speed != NULL && mp->max_accel
  != NULL && mp->u2c != NULL) {
 \ensuremath{//} // get the real endpoint if a preset was mentioned
  if ( ps != NULL && *ps != 0) {
   err = lsredis_find_preset( mp->name, ps, &
  maybe_ep);
   if( err != 0)
     ep = maybe_ep;
 u2c = lsredis_getd( mp->u2c);
  if( u2c <= 0.0)</pre>
   continue;
  // For look up tables user units are (or should be) counts and u2c should
   be 1
  if ( mp->nlut > 0 \&\& mp->lut != NULL) {
  u2c = 1.0;
D = lspmac_lut( mp->nlut, mp->lut, ep) - lspmac_lut
( mp->nlut, mp->lut, lspmac_getPosition( mp));
  } else {
   D = ep - lspmac_getPosition( mp);
  // User units
  V = lsredis_getd( mp->max_speed) / u2c * 1000.;
  // User units per second
  A = lsredis_getd( mp->max_accel) / u2c * 1000. *
  1000;
              // User units per second per second
 neutral_pos = lsredis_getd( mp->neutral_pos);
min_pos = lsredis_getd( mp->min_pos) - neutral_pos
  max_pos
              = lsredis_getd( mp->max_pos) - neutral_pos
  if( ep < min_pos || ep > max_pos) {
    lslogging_log_message( "lspmac_est_move_time:
   Motor %s Requested position %f out of range: min=%f, max=%f", mp->name, ep,
  min_pos, max_pos);
   lsevents_send_event( "%s Move Aborted", mp->name
 );
    return 1;
```

```
}
// Don't bother with motors without velocity or acceleration defined
if( V > 0.0 && A > 0.0) {
  if ( fabs(D) > V*V/A) {
    // Normal ramp up, constant velocity, and ramp down
    Tt = fabs(D)/V + V/A;
  } else {
    // Never reach constantant velocity, just ramp up a bit and back down
    Tt = 2.0 * sqrt(fabs(D)/A);
  lslogging_log_message( "lspmac_est_move_time:
 Motor: %s D: %f VV/A: %f Tt: %f", mp->name, D, V*V/A, Tt);
  // TODO: insert move time based for DAC or BO motor like objects;
  // For now assume 100 msec;
  Tt = 0.1;
// Perhaps flag a coordinate system
// We can move a motor that's not in a coordinate system but we cannot
 move a motor that is but does not
// have an axis defined if we are also moving one that does. It's a
 limitation, I guess.
if ( jog != 1 &&
   mp->coord_num != NULL && lsredis_getl( mp->
coord_num) > 0 && lsredis_getl( mp->coord_num) <=</pre>
mp->motor_num != NULL && lsredis_get1( mp->
motor_num) > 0 && mp->axis != NULL && lsredis_getc( mp
->axis) != 0) {
  int axis:
  int motor_num;
  motor_num = lsredis_getl( mp->motor_num);
  axis = lsredis_getc( mp->axis);
  for( j=0; j<sizeof(axes); j++) {</pre>
   if( axis == axes[j])
      break;
  if( j < sizeof( axes)) {</pre>
    // Store the motion request for a normal PMAC motor
    int in_position_band;
    cn = lsredis getl( mp->coord num);
    in_position_band = lsredis_getl( mp->in_position_band
);
    motions[motor_num - 1].coord_num = cn;
    motions[motor_num - 1].axis
    motions[motor_num - 1].Delta
                                       = D * 112c:
    // Don't ask to run a motion program if we are already where we want
 to be
    // Deadband is 10 counts except for zoom which is 100.
    // We use Ixx28 In-Position Band which has units of 1/16 count
    if( abs(motions[motor_num - 1].Delta)*16 >= in_position_band) {
      m5075 |= 1 << (cn - 1);
motions[motor_num - 1].moveme
} else {
  // Here we are dealling with a DAC or BO motor or just want to jog.
 if( mp->jogAbs( mp, ep)) {
   lslogging_log_message( "lspmac_est_move_time:
motor %s failed to queue move of distance %f from %f", mp->name, D,
```

```
lspmac_getPosition(mp));
        lsevents_send_event( "Move Aborted");
         return 1;
    // Update the estimated time
    *est_time = *est_time < Tt ? Tt : *est_time;
    lslogging_log_message( "lspmac_est_move_time:
    est_time=%f", *est_time);
  mp = va_arg( arg_ptr, lspmac_motor_t *);
  if ( mp == NULL)
   break;
  jog = va_arg( arg_ptr, int);
ps = va_arg( arg_ptr, char *);
  ep = va_arg( arg_ptr, double);
va_end( arg_ptr);
// Call the motion program(s)
  char s[256];
  int foundone:
  int err;
  int moving_flags;
  struct timespec timeout;
  if ( m5075 != 0) {
    *mmask |= m5075; // Tell the caller about our new mask
    pthread_mutex_lock( &lspmac_moving_mutex);
    if( (lspmac_moving_flags & m5075) != m5075)
      lspmac_SockSendDPline( NULL, "M5075=(M5075 | %d)",
     m5075);
    clock_gettime( CLOCK_REALTIME, &timeout);
    timeout.tv_sec += 2;
                                 // 2 seconds should be more than enough time to
     set the flags
    err = 0;
    while( err == 0 && (lspmac_moving_flags & m5075) !=
    m5075)
      err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
moving_flags = lspmac_moving_flags;
    pthread_mutex_unlock( &lspmac_moving_mutex);
    if( err == ETIMEDOUT) {
       lslogging_log_message( "lspmac_est_move_time:
     Timed out waiting for moving flags. lspmac_moving_flags = %0x", moving_flags); lsevents_send_event( "%s Move Aborted Combined
     Motors");
      return 1;
  for( i=1; i<=16; i++) {</pre>
    // Loop over coordinate systems
    foundone = 0;
    for( j=0; j<9; j++)</pre>
      qs[j] = 0;
    for( j=0; j<31; j++) {</pre>
      // Loop over motors
      if( motions[j].moveme && motions[j].coord_num == i) {
   if( abs(motions[j].Delta) > 0) {
          qs[(int) (motions[j].axis)] = motions[j].Delta;
           foundone=1;
      }
    }
    if (foundone) {
```

7.5.4.19 int lspmac_est_move_time_wait (double move_time, int mmask)

wait for motion to stop returns non-zero if the wait timed out

Parameters

move_time	The time out in seconds
mmask	A coordinate system mask to wait for

Both values are returned from lspmac_est_move_time

Definition at line 2983 of file Ispmac.c.

```
int err;
double isecs, fsecs;
struct timespec timeout;
clock_gettime( CLOCK_REALTIME, &timeout);
fsecs = modf( move_time, &isecs);
timeout.tv_sec += (long)floor(isecs);
timeout.tv_nsec += (long)floor(fsecs * 1.e9);
timeout.tv_sec += timeout.tv_nsec / 1000000000;
timeout.tv_nsec %= 1000000000;
err = 0;
pthread_mutex_lock( &lspmac_moving_mutex);
while( err == 0 && (lspmac_moving_flags & mmask) != 0)
  err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
pthread_mutex_unlock( &lspmac_moving_mutex);
if( err != 0) {
   if( err == ETIMEDOUT) {
     lslogging_log_message( "lstest_lspmac_est_move_time:
       timed out waiting %f seconds", move_time);
   return 1;
return 0;
```


Definition at line 3962 of file Ispmac.c.

```
lspmac_motor_t *rtn;
ENTRY entry_in, *entry_outp;
int err;

entry_in.key = name;
entry_in.data = NULL;
err = hsearch_r( entry_in, FIND, &entry_outp, &motors_ht);
if( err == 0) {
   lslogging_log_message( "lspmac_find_motor_by_name:
        hsearch_r failed for motor '%s': %s", name, strerror( errno));
   return NULL;
}
rtn = entry_outp->data;
```

```
return rtn;
```

7.5.4.21 void lspmac_flight_lut_setup ()

Set up lookup table for flight.

Definition at line 3869 of file Ispmac.c.

```
int i;
lsredis_obj_t *p;
pthread_mutex_lock( &flight->mutex);
flight->nlut = 11;
flight->lut = calloc( 2 * flight->nlut, sizeof( double));
if( flight->lut == NULL) {
  lslogging_log_message( "lspmac_flight_lut_setup: out
     of memory");
  exit(-1);
flight->lut[0] = 0;
flight \rightarrow lut[1] = 0;
for( i=1; i < flight->nlut; i++) {
  p = lsredis_get_obj( "cam.zoom.%d.FrontLightIntensity", i);
   if( p==NULL || strlen( lsredis_getstr(p)) == 0) {
     free( flight->lut);
     flight->lut = NULL;
flight->nlut = 0;
     pthread_mutex_unlock( &flight->mutex);
lslogging_log_message( "lspmac_flight_lut_setup:
      cannot find MotorPosition element for cam.flight level %d", i);
     return;
   flight->lut[2*i]
   flight->lut[2*i+1] = 32767.0 * lsredis_getd(p) / 100.
     0;
pthread_mutex_unlock( &flight->mutex);
```

7.5.4.22 void lspmac_fscint_lut_setup ()

Set up lookup table for fscint.

Definition at line 3943 of file Ispmac.c.

```
int i;

pthread_mutex_lock( &fscint->mutex);

fscint->nlut = 101;
fscint->lut = calloc( 2 * fscint->nlut, sizeof( double));
if( fscint->lut == NULL) {
   lslogging_log_message( "lspmac_fscint_lut_setup: out
        of memory");
   exit( -1);
}

for( i=0; i<fscint->nlut; i++) {
   fscint->lut[2*i] = i;
   fscint->lut[2*i+1] = 320.0 * i;
}
pthread_mutex_unlock( &fscint->mutex);
```

7.5.4.23 | Ispmac motor t* Ispmac_fshut_init (Ispmac motor t * d)

Initalize the fast shutter motor.

Parameters

	-1	Our unitable de la casa de la casa
ın	а	Our uninitialized motor object

Definition at line 3432 of file Ispmac.c.

7.5.4.24 void lspmac_get_ascii (char * event)

Forward declarateion.

Request the ascii buffers from the PMAC.

Definition at line 1954 of file Ispmac.c.

```
lspmac_send_command( VR_UPLOAD, VR_PMAC_GETMEM
   , 0x0e9c, 0, sizeof(lspmac_ascii_buffers_t), NULL,
   lspmac_get_ascii_cb, 0, event);
}
```

7.5.4.25 void lspmac_get_ascii_cb (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

service the ascii buffer request response

Definition at line 1846 of file Ispmac.c.

```
uint32_t clrdata;
int need_more;
need\_more = 0;
pthread_mutex_lock( &lspmac_ascii_mutex);
memcpy( &lspmac_ascii_buffers, buff, sizeof(
    lspmac_ascii_buffers));
// The response is not ready yet
\ensuremath{//} This will be an infinite loop if we queue a command that does not
// produce a response.
// Quoted comments below from Delta Tau "Turbo PMAC User Manual 9/12/2008,
     page 422"
// "1. Wait for the Host-Input Control Word at 0x0F40 (Y:$063D0) to become
greater than 0, indicating
// that a response line is ready."
if( lspmac_ascii_buffers.response_buf == 0) {
  need\_more = 1;
} else {
  if( (lspmac_ascii_buffers.response_buf & 0
     x8000) != 0) {
     char bcd1, bcd2, bcd3;
     int errcode;
     // Error response
     // "2. Interpret the value in this register to determine what // type of response is present. If Bit 15 is 1, Turbo PMAC is // reporting an error in the command, and there is no response
     // other than this word. In this case, Bits 0 - 11 encode the
```

```
// error number for the command as 3 BCD digits."
    need_more = 0;
    bcd1 = lspmac_ascii_buffers.response_buf
     & 0x000f;
    bcd2 = (lspmac_ascii_buffers.response_buf
     & 0x00f0) >> 4;
    bcd3 = (lspmac_ascii_buffers.response_buf
     & 0x0f00) >> 8;
    errcode = (bcd3 * 10 + bcd2) * 10 + bcd1;
    if( errcode >= sizeof( pmac_error_strs)/sizeof(
     *pmac_error_strs))
      errcode = 0;
    lslogging_log_message( "lspmac_get_ascii_cb: Error
    , pmac_error_strs[errcode]);
//
     returned for %s: %s", lspmac_ascii_buffers.command_str
    // Command not allowed during program execution.
    // Requeue it;
    if ( errcode == 1) {
      lspmac_dpascii_off--;
  } else {
    /// // "3. Read the response string starting at 0 \times 0 F44
    // (Y:$0603D1). Two 8-bit characters are packed into each 16-bit
    // word; the first character is placed into the low
    // byte. Subsequent characters are placed into consecutive
// higher addresses, two per 16-bit word. (In byte addressing,
    // each character is read from an address one higher than the
    // preceding character.) Up to 255 characters can be sent in a
    // single response line. The string is terminated with the NULL
    // character (byte value 0), convenient for C-style string
    // handling. For Pascal-style string handling, the register at // 0x0F42 (X:$0603D0) contains the number of characters in the // string (plus one)."
    if( lspmac_ascii_buffers.response_n > 1)
  lslogging_log_message( "lspmac_get_ascii_cb: '%s'
  '%s'", lspmac_ascii_buffers.command_str,
    lspmac ascii buffers.response_str);
    else
      lslogging_log_message( "lspmac_get_ascii_cb: '%s'
       responded", lspmac_ascii_buffers.command_str);
    // contained the value $0D (13 decimal, "CR"), this was not the // last line in the response, and steps 1 - 4 should be
    // repeated. If they had contained the value $06 (6 decimal,
    // "ACK"), this was the last line in the response."
    if( (lspmac_ascii_buffers.response_buf &
    0x00ff) == 0x0d) {
      need_more = 1;
      need_more = 0;
      if( cmd->event != NULL && *(cmd->event) != 0)
  lsevents_send_event( "%s command accepted", cmd->
    event);
 }
pthread mutex unlock( &lspmac ascii mutex);
// Reset the buffer flags and, perhaps, requeue a request
// "4.
        Clear the Host-Input Control Word at 0x0F40 (Y:$063D0)
// to 0. Turbo PMAC will not send another response line until it sees
// this register set to 0."
                        // set the control word to zero
if( need_more) {
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0f40, 0, 4, (char *)&clrdata, lspmac_more_ascii_cb, 1,
    NULL);
} else {
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
     , 0x0f40, 0, 4, (char *)&clrdata, NULL, 1, NULL);
  lspmac_ascii_busy = 0;
```

}

```
7.5.4.26 void lspmac_get_status ( )
```

Request a status update from the PMAC.

Definition at line 1834 of file Ispmac.c.

7.5.4.27 void lspmac_get_status_cb (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Service routing for status upate This updates positions and status information.

Parameters

in	cmd	The command that generated this reply
in	nreceived	Number of bytes received
in	buff	The Big Byte Buffer

Definition at line 1610 of file Ispmac.c.

```
#ifdef SHOW_RATE
static struct timespec ts1;
static struct timespec ts2;
static int cnt = 0;
#endif
int i;
lspmac_bi_t
                *bp;
clock_gettime( CLOCK_REALTIME, &lspmac_status_time);
#ifdef SHOW_RATE
if(cnt == 0) {
 clock_gettime( CLOCK_REALTIME, &ts1);
pthread_mutex_lock( &md2_status_mutex);
memcpy( &md2_status, buff, sizeof(md2_status));
// Note that we are the only thread that writes to md2_status
// so we no longer need the lock to read. Other threads must
// lock the mutex to read md2_status.
pthread_mutex_unlock( &md2_status_mutex);
// \ensuremath{//} track the coordinate system moving flags
pthread_mutex_lock( &lspmac_moving_mutex);
if( md2_status.moving_flags != lspmac_moving_flags
  int mask;
  lslogging_log_message( "lspmac_get_status_cb: new
  moving flag: %0x", md2_status.moving_flags);
  mask = 1;
  for( i=1; i<=16; i++, mask <<= 1) {</pre>
    if( ((lspmac_moving_flags & mask) != 0) && ((
    md2_status.moving_flags & mask) == 0)) {
      // Falling edge: send event
lsevents_send_event( "Coordsys %d Stopped", i);
    }
  lspmac_moving_flags = md2_status.moving_flags
```

```
pthread_cond_signal( &lspmac_moving_cond);
pthread_mutex_unlock( &lspmac_moving_mutex);
// Read the motor positions
for( i=0; i<lspmac_nmotors; i++) {</pre>
  lspmac_motors[i].read(&(lspmac_motors[i]));
// Read the binary inputs and perhaps send an event
for( i=0; i<lspmac_nbis; i++) {</pre>
  bp = &(lspmac_bis[i]);
  pthread_mutex_lock( & (bp->mutex));
  bp->position = (*(bp->ptr) & bp->mask) == 0 ? 0 : 1;
  if( bp->first time) {
    bp->first_time = 0;
     if ( bp->position==1 && bp->changeEventOn != NULL &&
    bp->changeEventOn[0] != 0)
      lsevents_send_event( lspmac_bis[i].
    changeEventOn);
    if( bp->position==0 && bp->changeEventOff != NULL
    && bp->changeEventOff[0] != 0)
      lsevents_send_event( lspmac_bis[i].
    changeEventOff);
    if( bp->position != bp->previous) {
  if( bp->position==1 && bp->changeEventOn != NULL
&& bp->changeEventOn[0] != 0)
        lsevents_send_event( lspmac_bis[i].
    changeEventOn);
    if(bp->position==0 && bp->changeEventOff != NULL
&& bp->changeEventOff[0] != 0)
   lsevents_send_event( lspmac_bis[i].
    changeEventOff);
  bp->previous = bp->position;
  pthread_mutex_unlock( & (bp->mutex));
pthread_mutex_lock( &ncurses_mutex);
// acc11c_1
               INPUTS
// mask bit
                        Air pressure OK
Air bearing OK
// 0x01 0
               M1000
// 0x02
               M1001
// 0x04
               M1002
                        Cryo switch
// 0x08
               M1003
                        Backlight Down
// 0x10
               M1004
                       Backlight Up
// 0x20
// 0x40 6
               M1006 Cryo is back
// acc11c_2
               INPUTS
// mask bit
// 0x01
               M1008 Fluor Dector back
// 0x02 1
// 0x04 2
               M1009
                        Sample Detected
               M1020
                        {SC load request}
{SC move cryo back request}
// 0x08
               M1021
// 0x10 4
               M1022
                        {SC sample magnet control}
// 0x20
               M1013
                        Etel Ready
// 0x40 6
// 0x80 7
               M1014
                        Etel On
               M1015
                        Etel Init OK
if ( md2_status.acc11c_2 & 0x01)
 mvwprintw( term_status2, 3, 10, "%*s", -8, "Fluor Out");
  mvwprintw( term_status2, 3, 10, "%*s", -8, "Fluor In");
if( md2_status.acc11c_5 & 0x08)
  mvwprintw( term_status2, 4, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
    -2), "Dryer On");
  mvwprintw( term_status2, 4, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
    -2), "Dryer Off");
if( md2_status.acc11c_2 & 0x02)
  mvwprintw( term_status2, 2, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
```

```
-2), "Cap Dectected");
else
 mvwprintw( term_status2, 2, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
   -2), "Cap Not Dectected");
wnoutrefresh( term_status2);
// acc11c_3
             INPUTS
// mask bit
// 0x01 0
             M1025
                     Minikappa OK
// 0x02 1
             M1023
                      {SC unload request}
// 0x04 2
             M1024
                      Smartmagnet is on (note in pmc saying this is not used
    in VB interface)
// 0x08 3
             M1027
                      Arm Parked
// 0x10 4
              M1031
                      Smartmagnet error (coil is broken)
// 0x20 5
// 0x40
// 0x80
// 0x100 8
             M1048 Shutter is open (note in pmc says: slow input !!!)
// acc11c_4
             INPUTS
// mask bit
// 0x01 0
             M1031
                      {laser mirror is back}
// 0x02
              M1032
                      {laser PSS OK}
        1
// 0x04
              M1033
                      {laser shutter open}
// acc11c 5
             OUTPUTS
// mask bit
// 0x01 0
              M1100
                     Mag Off
// 0x02 1
              M1191
                      Condenser Out
// 0x04 2
              M1102
                      Cryo Back
// 0x08 3
              M1103
                      Dryer On
// 0x10 4
              M1104
                     FluoDet Out
// 0x20
              M1105
                      {smartmagnet on/off: note in pmc says this is not used}
                     1=SmartMag, 0=Permanent Mag
// 0x40 6
             M1106
if ( md2\_status.acc11c\_5 \& 0x04)
 mvwprintw( term_status2, 3, 1, "%*s", -8, "Cryo Out");
else.
 mvwprintw( term_status2, 3, 1, "%*s", -8, "Cryo In ");
// accl1c_6 OUTPUTS
// mask bit
// 0x0001 0 M1040 {SC Sample transfer is on}
// 0x0002
// 0x0004
// 0x0008
// 0x0010
            4
// 0x0020
            5
           6
7 M1115 Etel Enable
// 0x0040
// 0x0080
          8 M1124 Fast Shutter Enable
9 M1125 Fast Shutter Manual Enable
10 M1126 Fast Shutter On
// 0x0100
// 0x0200
// 0x0400
// 0x0800 11
// 0x1000 12 M1128 ADC1 gain bit 0
                     ADC1 gain bit 1
// 0x2000 13 M1129
                      ADC2 gain bit 0
// 0x4000 14 M1130
// 0x8000 15 M1131
                     ADC2 gain bit 1
if( md2_status.acc11c_5 & 0x02)
 mvwprintw( term_status, 3, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
   -2), "Backlight Up");
 mvwprintw( term_status, 3, 1, "%*s", -(LS_DISPLAY_WINDOW_WIDTH
-2), "Backlight Down");
mvwprintw( term_status, 6, 1, "Piezo: %*u",
    LS_DISPLAY_WINDOW_WIDTH-2-8, (int)fscint->position);
wnoutrefresh( term_status);
wnoutrefresh ( term input);
doupdate();
pthread_mutex_unlock( &ncurses_mutex);
#ifdef SHOW_RATE
if ( ++cnt % 1000 == 0) {
  long diff_sec;
```

```
long diff_nsec;
clock_gettime( CLOCK_REALTIME, &ts2);

diff_sec = ts2.tv_sec - ts1.tv_sec;
diff_nsec = ts2.tv_nsec - ts1.tv_nsec;

if( diff_nsec < 0) {
    diff_nsec += 10000000000;
    diff_sec--;
}

lslogging_log_message( "Refresh Rate: %0.1f Hz", (
    double)cnt / (diff_sec + diff_nsec/1000000000.));

cnt = 0;
}
#endif</pre>
```

7.5.4.28 void lspmac_GetAllIVars ()

Request the values of all the I variables.

Definition at line 2061 of file Ispmac.c.

```
static char *cmds = "IO..8191";
lspmac_send_command( VR_DOWNLOAD,
    VR_PMAC_SENDLINE, 0, 0, strlen( cmds), cmds,
    lspmac_GetAllIVarsCB, 0, NULL);
```

7.5.4.29 void lspmac_GetAllIVarsCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Receive the values of all the I variables Update our Postgresql database with the results.

Parameters

in	cmd	The command that gave this response
in	nreceived	Number of bytes received
in	buff	The byte buffer

Definition at line 2044 of file Ispmac.c.

```
{
static char qs[LS_PG_QUERY_STRING_LENGTH];
char *sp;
int i;
for( i=0, sp=strtok(buff, "\r"); sp != NULL; sp=strtok( NULL, "\r"), i++) {
    snprintf( qs, sizeof( qs)-1, "SELECT pmac.md2_ivar_set( %d, '%s')", i, sp);
    qs[sizeof( qs)-1]=0;
    lspg_query_push( NULL, qs);
}
```

7.5.4.30 void Ispmac_GetAllMVars ()

Request the values of all the M variables.

Definition at line 2086 of file Ispmac.c.

```
static char *cmds = "M0..8191->";
lspmac_send_command( VR_DOWNLOAD,
    VR_PMAC_SENDLINE, 0, 0, strlen( cmds), cmds,
    lspmac_GetAllMVarsCB, 0, NULL);
```

7.5.4.31 void lspmac_GetAllMVarsCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Receive the values of all the M variables Update our database with the results.

Parameters

in	cmd	The command that started this
in	nreceived	Number of bytes received
in	buff	Our byte buffer

Definition at line 2069 of file Ispmac.c.

```
static char qs[LS_PG_QUERY_STRING_LENGTH];
char *sp;
int i;
for( i=0, sp=strtok(buff, "\r"); sp != NULL; sp=strtok( NULL, "\r"), i++) {
    snprintf( qs, sizeof( qs)-1, "SELECT pmac.md2_mvar_set( %d, '%s')", i, sp);
    qs[sizeof( qs)-1]=0;
    lspg_query_push( NULL, qs);
}
```

7.5.4.32 int lspmac_getBlPosition (lspmac_bi_t * bip)

get binary input value

Definition at line 1598 of file Ispmac.c.

```
int rtn;
pthread_mutex_lock( &bip->mutex);
rtn = bip->position;
pthread_mutex_unlock( &bip->mutex);
return rtn;
```

7.5.4.33 void Ispmac_Getmem ()

Request a block of double buffer memory.

Definition at line 1128 of file Ispmac.c.

```
int nbytes;
nbytes = (dbmemIn + 1400 > sizeof(dbmem)) ? sizeof(dbmem)
  - dbmemIn : 1400;
lspmac_SockGetmem(dbmemIn, nbytes);
```

7.5.4.34 void lspmac_GetmemReplyCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Service a reply to the getmem command.

Parameters

cmd	Queue item this is a reply to
nreceived	Number of bytes received
buff	Buffer of bytes recieved

Definition at line 1054 of file Ispmac.c.

```
memcpy( & (dbmem[ntohs(cmd->pcmd.wValue)]), buff, nreceived);
dbmemIn += nreceived;
if( dbmemIn >= sizeof( dbmem)) {
    dbmemIn = 0;
}
```

7.5.4.35 double lspmac_getPosition (lspmac_motor_t * mp)

get the motor position (with locking)

Parameters

```
mp the motor object
```

Definition at line 1355 of file Ispmac.c.

```
double rtn;
pthread_mutex_lock( & (mp->mutex));
rtn = mp->position;
pthread_mutex_unlock( & (mp->mutex));
return rtn;
```

7.5.4.36 void lspmac_GetShortReplyCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Receive a reply that does not require multiple buffers.

Parameters

in	cmd	Queue item this is a reply to
in	nreceived	Number of bytes received
in	buff	The buffer of bytes

Definition at line 997 of file Ispmac.c.

```
char *sp;  // pointer to the command this is a reply to
if( nreceived < 1400)
  buff[nreceived]=0;

sp = (char *) (cmd->pcmd.bData);

if( *buff == 0) {
  pthread_mutex_lock( &ncurses_mutex);
  wprintw( term_output, "%s\n", sp);
  pthread_mutex_unlock( &ncurses_mutex);
} else {
  pthread_mutex_lock( &ncurses_mutex);
  wprintw( term_output, "%s: ", sp);
  pthread_mutex_unlock( &ncurses_mutex);
  cleanstr( buff);
}
wnoutrefresh( term_output);
wnoutrefresh( term_input);
doupdate();
memset( cmd->pcmd.bData, 0, sizeof( cmd->pcmd.bData));
```

7.5.4.37 void lspmac_home1_queue (lspmac_motor_t * mp)

Home the motor.

Parameters

in mp motor we are concerned about

Definition at line 1221 of file Ispmac.c.

```
int i;
int motor num;
int coord_num;
char **home;
pthread_mutex_lock( &(mp->mutex));
motor_num = lsredis_get1( mp->motor_num);
coord_num = lsredis_get1( mp->coord_num);
          = lsredis_get_string_array( mp->home);
// Each of the motors should have this defined // but let's not seg fault if home is missing
if ( home == NULL || *home == NULL) {
  //
// Note we are already initialized
' -- +boxe is some
  // so if we are here there is something wrong.
  lslogging_log_message( "lspmac_homel_queue: null or
     empty home strings for motor %s", mp->name);
  pthread_mutex_unlock( & (mp->mutex));
// We've already been called. Don't home again until // we're finish with the last time.
if( mp->homing) {
 pthread_mutex_unlock( &(mp->mutex));
  return;
// Don't go on if any other motors in this coordinate system are homing.
// It's possible to write the homing program to home all the motors in the
     coordinate
// system. TODO (hint hint)
if( coord_num > 0) {
  for( i=0; i<lspmac_nmotors; i++) {</pre>
    if( &(lspmac_motors[i]) == mp)
      continue:
    if( lsredis_getl(lspmac_motors[i].coord_num) ==
    coord_num) {
      int nogo;
      pthread_mutex_lock( &(lspmac_motors[i].mutex));
      //
// Don't go on if
      11
            we are homing
                                     or
                                              ( not in position
               in open loop)
    if( lspmac_motors[i].homing || (((lspmac_motors
[i].status2 & 0x01)==0) && ((lspmac_motors[i].status1 & 0x040000)
    ! = 0)))
        nogo = 1;
      pthread_mutex_unlock( &(lspmac_motors[i].mutex));
       if( nogo) {
        pthread_mutex_unlock( &(mp->mutex));
         return:
      }
    }
  }
mp->homing = 1;
mp->not_done = 1;
                        // set up waiting for cond
mp->motion_seen = 0;
// This opens the control loop.
// The status routine should notice this and the fact that
```

```
// the homing flag is set and call on the home2 routine
//
// Only send the open loop command if we are not in
// open loop mode already. This test might prevent a race condition
// where we've already moved the home2 routine (and queue the homing program motion)
// before the open loop command is dequeued and acted on.
//
if( ~(mp->status1) & 0x040000) {
  lspmac_SockSendDPline( mp->name, "#%d$*",
  motor_num);
}
pthread_mutex_unlock( &(mp->mutex));
lsevents_send_event( "%s Homing", mp->name);
```

7.5.4.38 void lspmac_home2_queue (lspmac_motor_t * mp)

Second stage of homing.

Parameters

in	тр	motor we are concerned about
----	----	------------------------------

Definition at line 1309 of file Ispmac.c.

```
char **spp;
char **home;
// At this point we are in open loop.
// Run the \rm \bar{motor} specific commands
pthread_mutex_lock( & (mp->mutex));
home = lsredis_get_string_array( mp->home);
// We don't have any motors that have a null home text array so
// there is currently no need to worry about this case other than
// not to seg fault
// Also, Only go on if the first homing phase has been started
if( home == NULL || mp->homing != 1) {
  pthread_mutex_unlock( & (mp->mutex));
 return;
for( spp = home; *spp != NULL; spp++) {
  pthread_mutex_lock( &ncurses_mutex);
  wprintw( term_output, "home2 is queuing '%s'\n", *spp);
  wnoutrefresh ( term_output);
  doupdate();
 pthread_mutex_unlock( &ncurses_mutex);
 lspmac_SockSendDPline( mp->name, *spp);
mp \rightarrow homing = 2;
pthread_mutex_unlock( & (mp->mutex));
```

7.5.4.39 void Ispmac_init (int ivarsflag, int mvarsflag)

Initialize this module.

Parameters

in	ivarsflag	Set global flag to harvest i variables
in	mvarsflag	Set global flag to harvest m variables

Definition at line 3534 of file Ispmac.c.

```
int i;
int err;
ENTRY entry_in, *entry_outp;
md2_status_t *p;
pthread_mutexattr_t mutex_initializer;
// Set our global harvest flags
getivars = ivarsflag;
getmvars = mvarsflag;
// Use recursive mutexs
pthread_mutexattr_init( &mutex_initializer);
pthread_mutexattr_settype(&mutex_initializer, PTHREAD_MUTEX_RECURSIVE);
// All important status mutex
pthread_mutex_init( &md2_status_mutex, &mutex_initializer);
// Get the MD2 initialization strings
// lspmac_md2_init = lsredis_get_obj( "md2_pmac.init"); // hard coded now.
// Initialize the motor objects
p = &md2_status;
omega = lspmac_motor_init( &(lspmac_motors
    [ 0]), 0, 0, &p->omega_act_pos, &p->omega_status_1 , &p->omega_status_2, "Omega #1 &1 X", "omega",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    );
alignx = lspmac_motor_init( &(lspmac_motors
    [ 1]), 0, 1, &p->alignx_act_pos, &p->alignx_status_1, &p->alignx_status_2, "Align X #2 &3 X", "align.x", lspmac_moveabs_queue, lspmac_jogabs_queue
    );
aligny = lspmac_motor_init( &(lspmac_motors
    [2]), 0, 2, &p->aligny_act_pos, &p->aligny_status_1
, &p->aligny_status_2, "Align Y #3 &3 Y", "align.y",
    , &p-zaligny_scaca__,
lspmac_moveabs_queue, lspmac_jogabs_queue
);
alignz = lspmac_motor_init( &(lspmac_motors
    [ 3]), 0, 3, &p->alignz_act_pos, &p->alignz_status_1 , &p->alignz_status_2, "Align Z #4 &3 Z", "align.z",
    lspmac_moveabs_queue, lspmac_jogabs_queue
); anal = lspmac_motor_init( &(lspmac_motors
    [ 4]), 0, 4, &p->analyzer_act_pos, &p->analyzer_status_1, &p->analyzer_status_2, "Anal #5", "lightPolar
                                                         "lightPolar",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    zoom
    lspmac_movezoom_queue, lspmac_movezoom_queue
);
apery = lspmac_motor_init( &(lspmac_motors
    [ 6]), 1, 1, &p->aperturey_act_pos, &p->aperturey_status_1
, &p->aperturey_status_2, "Aper Y #7 &5 Y", "appy",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    aperz = lspmac_motor_init( &(lspmac_motors
      [ 7]), 1, 2, &p->aperturez_act_pos, &p->aperturez_status_1
    , &p->aperturez_status_2, "Aper Z #8 &5 Z", "appz",
    lspmac_moveabs_queue, lspmac_jogabs_queue
    [8]), 1, 3, &p->capy_act_pos, &p->capy_status_1, &p->capy_status_2, "Cap Y #9 &5 U", "capy",
    lspmac_moveabs_queue, lspmac_jogabs_queue
```

```
lspmac_moveabs_queue, lspmac_jogabs_queue
);
scint = lspmac_motor_init( &(lspmac_motors
    [10]), 2, 0, &p->scint_act_pos, &p->scint_status_1
, &p->scint_status_2, "Scin Z #11 &5 W", "scint",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    [11]), 2, 1, &p->centerx_act_pos, &p->centerx_status_1
, &p->centerx_status_2, "Cen X #17 &2 X", "centering.x",
    lspmac_moveabs_queue, lspmac_jogabs_queue
    ceny
    [12]), 2, 2, &p->centery_act_pos, &p->centery_status_1
, &p->centery_status_2, "Cen Y #18 &2 Y", "centering.y",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    kappa
    [13]), 2, 3, &p->kappa_act_pos, &p->kappa_status_1
, &p->kappa_status_2, "Kappa #19 &7 X", "kappa",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    14]), 2, 4, &p->phi_act_pos, &p->phi_status_1, &p->phi_status_2, "Phi #20 &7 Y", "phi",
     lspmac_moveabs_queue, lspmac_jogabs_queue
fshut = lspmac_fshut_init( &(lspmac_motors
    [15]));
lspmac_movedac_queue);
blight = lspmac_dac_init( &(lspmac_motors[1
     7]), &p->back_dac,
                              "M1201", "backLight.intensity",
    lspmac_movedac_queue);
fscint = lspmac_dac_init( &(lspmac_motors[1
   8]), &p->scint_piezo, "M1203", "scint.focus",
     lspmac_movedac_queue);
smart_mag_oo = lspmac_bo_init( &(lspmac_motors
[19]), "smartMagnet", "M1100=%d", &(md2_status.acc11c_5), 0x01)
    ,
ght_ud = lspmac_bo_init( & (lspmac_motors
[20]), "backLight", "M1101=%d", & (md2_status.acc11c_5), 0x02)
blight_ud
              = lspmac_bo_init( &(lspmac_motors cryo", "M1102=%d", &(md2_status.accllc_5), 0x04)
    [21]), "cryo",
    dryer
                        "M1103=%d", & (md2_status.acc11c_5), 0x08)
    [22]), "dryer",
              = lspmac_bo_init( &(lspmac_motors
    [23]), "fluo",
                            "M1104=%d", & (md2_status.acc11c_5), 0x10)
flight oo
    ght_oo = lspmac_soft_motor_init( &(
lspmac_motors[24]), "frontLight",
    lspmac_moveabs_frontlight_oo_queue);
    ght_f = lspmac_soft_motor_init( &( lspmac_motors[25]), "backLight.factor",
lspmac_moveabs_blight_factor_queue);
flight_f = lspmac_soft_motor_init( &(
    lspmac_motors[26]), "frontLight.factor",
     lspmac_moveabs_flight_factor_queue);
     ir = lspmac_bi_init( &(lspmac_bis[
   0]), &(md2_status.acc1lc_1),   0x01, "Low Pressure Air OK", "
    Low Pressure Air Failed");
                 = lspmac_bi_init( &(lspmac_bis[
hp air
     1]), & (md2_status.acc11c_1), 0x02, "High Pressure Air OK", "
    High Pressure Air Failed");
cryo_switch
                = lspmac_bi_init( &(lspmac_bis
     [ 2]), &(md2_status.accl1c_1), 0x04, "CryoSwitchChanged",
     "CryoSwitchChanged");
     ht_down = lspmac_bi_init( &(lspmac_bis [ 3]), &(md2_status.accllc_1), 0x08, "Backlight Down",
blight down
     "Backlight Not Down");
      t_up = lspmac_bi_init( &(lspmac_bis
4]), &(md2_status.acc11c_1), 0x10, "Backlight Up",
    [ 4]), &(md2_status.a
"Backlight Not Up");
                  = lspmac_bi_init( &(lspmac_bis
cryo_back
     [ 5]), &(md2_status.acc11c_1), 0x40, "Cryo Back",
    "Cryo Not Back");
fluor_back
               = lspmac_bi_init( &(lspmac_bis
[ 6]), &(md2_status.acc11c_2), 0x01, "Fluor. Det. Parked",
    "Fluor. Det. Not Parked");
sample_detected = lspmac_bi_init( &(lspmac_bis
```

```
[ 7]), & (md2_status.acc11c_2), 0x02, "SamplePresent",
    "SampleAbsent");
etel_ready
                = lspmac_bi_init( &(lspmac_bis
    [8]), &(md2_status.acc11c_2), 0x20, "ETEL Ready",
    "ETEL Not Ready");
               = lspmac_bi_init( &(lspmac_bis
etel on
    [ 9]), &(md2_status.acc11c_2), 0x40, "ETEL On",
    "ETEL Off");
    etel_init_ok
    "ETEL Init Not OK");
"Minikappa Not OK");
smart_mag_on
               = lspmac_bi_init( &(lspmac_bis
    [12]), &(md2_status.acc1lc_3), 0x04, "Smart Magnet On",
"Smart Magnet Not On");
parked = lspmac_bi_init( &(lspmac_bis
[13]), &(md2_status.acc1lc_3), 0x08, "Arm Parked",
arm_parked
    "Arm Not Parked");
"Smart Magnet OK");
"Shutter Not Open");
smart_mag_off
               = lspmac_bi_init( &(lspmac_bis
    [16]), &(md2_status.acc11c_5), 0x01, "Smart Magnet Off",
    "Smart Magnet Not Off");
// Set up hash table
err = hcreate_r( LSPMAC_MAX_MOTORS * 2, &motors_ht)
if( err == 0) {
 lslogging_log_message( "lspmac_init: hcreate_r failed:
    '%s'", strerror( errno));
  exit(-1);
for( i=0; i<lspmac_nmotors; i++) {
  entry_in.key = lspmac_motors[i].name;
  entry_in.data = &(lspmac_motors[i]);
  err = hsearch_r( entry_in, ENTER, &entry_outp, &motors_ht);</pre>
  if( err == 0) {
   lslogging_log_message( "lspmac_init: hsearch_r
failed for motor %s: '%s'", lspmac_motors[i].name, strerror( errno));
    exit(-1);
// Initialize several commands that get called, perhaps, alot
rr_cmd.RequestType = VR_UPLOAD;
memset( rr_cmd.bData, 0, sizeof(rr_cmd.bData));
gb_cmd.RequestType = VR_UPLOAD;
gb_cmd.Request ype = VR_DTBOAP;
gb_cmd.wValue = 0;
gb_cmd.wIndex = 0;
gb_cmd.wLength = htons(1400);
memset( gb_cmd.bData, 0, sizeof(gb_cmd.bData));
cr_cmd.RequestType = VR_UPLOAD;
cr_cmd Request = VR_CTRL_RESPONSE;
cr_cmd wValue = 0;
memset( cr_cmd.bData, 0, sizeof(cr_cmd.bData));
//
// Initialize some mutexs and conditions
pthread_mutex_init( &pmac_queue_mutex, &mutex_initializer);
pthread_cond_init( &pmac_queue_cond, NULL);
lspmac shutter state = 0:
                                                    11
```

```
assume the shutter is now closed: not a big deal if we are wrong
pthread_mutex_init( &lspmac_shutter_mutex, &
    mutex_initializer);
pthread_cond_init( &lspmac_shutter_cond, NULL);
pmacfd.fd = -1;
pthread_mutex_init( &lspmac_moving_mutex, &
    mutex_initializer);
pthread_cond_init( &lspmac_moving_cond, NULL);
pthread_mutex_init( &lspmac_ascii_mutex, &mutex_initializer
pthread_mutex_init( &lspmac_ascii_buffers_mutex, &
    mutex_initializer);
// clear the ascii communications buffers
  uint32_t cc;
  cc = 0;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
   , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
  cc = 0x18;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
lspmac_SockSendDPline( NULL, "I5=0");
lspmac_SockSendDPline( NULL, "ENABLE PLCC 0,2");
lspmac_SockSendDPline( NULL, "DISABLE PLCC 1");
lspmac_SockSendDPline( NULL, "I5=3");
```

7.5.4.40 int $lspmac_jogabs_queue$ ($lspmac_motor_t*mp$, double $requested_position$)

Use jog to move motor to requested position.

Parameters

in	тр	The motor to move
in	requested	Where to move it
	position	

Definition at line 3265 of file Ispmac.c.

7.5.4.41 void lspmac_light_zoom_cb (char * event)

Set the backlight intensity whenever the zoom is changed (and the backlight is up)

Parameters

event Name of the event that calledus		event	Name of the event that calledus
---	--	-------	---------------------------------

Definition at line 3751 of file Ispmac.c.

```
int z;
pthread_mutex_lock( &zoom->mutex);
z = zoom->requested_position;
pthread_mutex_unlock( &zoom->mutex);
```

7.5.4.42 double lspmac_lut (int nlut, double * lut, double x)

Look up table support for motor positions (think x=zoom, y=light intensity) use a lookup table to find the "counts" to move the motor to the requested position The look up table is a simple one dimensional array with the x values as even indicies and the y values as odd indices.

Returns: y value

Parameters

in	nlut	number of entries in lookup table
in	lut	The lookup table: even indicies are the x values, odd are the y's
in	Х	The x value we are looking up.

Definition at line 394 of file Ispmac.c.

```
int i, foundone;
double m;
double y1, y2, x1, x2, y;
foundone = 0;
if ( lut != NULL && nlut > 1) {
  for( i=0; i < 2*nlut; i += 2) {</pre>
    x1 = lut[i];
    y1 = lut[i+1];
    if ( i < 2*nlut - 2) {
 x2 = lut[i+2];
      y2 = lut[i+3];
     // First one too big? Use the y value of the first element
    if(i == 0 \&\& x1 > x) {
      y = y1;
       foundone = 1;
       break;
     // Look for equality
    if(x1 == x) {
       y = y1;
       foundone = 1;
       break;
    // Maybe interpolate
    """
if( (i < 2*nlut-2) && x < x2) {
    m = (y2 - y1) / (x2 - x1);
    y = m*(x - x1) + y1;</pre>
       foundone = 1;
      break;
  if( foundone == 0) {
    // must be bigger than the last entry
```

```
//
//
y = lut[2*(nlut-1) + 1];
}
return y;
}
return 0.0;
```

7.5.4.43 void lspmac_more_ascii_cb (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

we are expecting more characters from the DPRAM ASCII interface

Definition at line 1840 of file Ispmac.c.

```
lspmac_get_ascii( cmd->event);
}
```

7.5.4.44 Ispmac_motor_t* Ispmac_motor_init (Ispmac_motor_t * d, int wy, int wx, int * posp, int * stat1p, int * stat2p, char * wtitle, char * name, int(*)(Ispmac_motor_t *, double) moveAbs, int(*)(Ispmac_motor_t *, double) jogAbs)

Initialize a pmac stepper or servo motor.

Parameters

in,out	d	An uninitialize motor object
in	wy	Curses status window row index
in	WX	Curses status window column index
in	posp	Pointer to position status
in	stat1p	Pointer to 1st status word
in	stat2p	Pointer to 2nd status word
in	wtitle	Title for this motor (to display)
in	name	This motor's name
in	moveAbs	Method to use to move this motor (motion program preferred)
in	jogAbs	Method to use to jog this motor (jog preferred)

Definition at line 3401 of file Ispmac.c.

7.5.4.45 int lspmac_move_or_jog_abs_queue (lspmac motor t * mp, double requested_position, int use_jog)

Move method for normal stepper and servo motor objects Returns non-zero on abort, zero if OK.

- < format string for coordinate system move
- < coordinate system bit
- < the requested position in units of "counts"
- < motor and coordinate system;
- < our axis

Parameters

in	тр	The motor to move
in	requested	Where to move it
	position	
in	use_jog	1 to force jog, 0 for motion prog

Definition at line 3017 of file Ispmac.c.

```
{
char *fmt;
int q100;
int requested_pos_cnts;
int coord_num, motor_num;
char *axis;
double u2c;
double neutral_pos;
double min_pos, max_pos;
int pos_limit_hit, neg_limit_hit, in_position_band;
struct timespec timeout, now;
int err;
pthread_mutex_lock( & (mp->mutex));
neutral_pos;
                = lsredis_getd( mp->max_pos) -
max_pos
   neutral_pos;
                = lsredis_getd(
pos_limit_hit
                                  mp->pos_limit_hit
neg_limit_hit = lsredis_getd(
                                  mp->neg_limit_hit
in_position_band = lsredis_getl( mp->in_position_band
    );
if( u2c == 0.0 || requested_position < min_pos || requested_position >
  // Shouldn't try moving a motor that's in trouble
  pthread_mutex_unlock( & (mp->mutex));
  %s u2c=%f requested position=%f min allowed=%f max allowed=%f", mp->name
  , u2c, requested position, min_pos, max_pos);
lsevents_send_event( "%s Move Aborted", mp->name);
  return 1:
if( (neg_limit_hit && (requested_position < mp->position)) || (pos_limit_hit
    && (requested_position > mp->position))) {
  limit=%d high limit=%d",
                        mp->name, requested_position, mp->position
  , neg_limit_hit, pos_limit_hit);
lsevents_send_event( "%s Move Aborted", mp->name);
  return 2;
mp->requested_position = requested_position;
if( mp->nlut > 0 && mp->lut != NULL) {
  mp->requested_pos_cnts = lspmac_lut( mp->nlut
, mp->lut, requested_position);
} else {
  mp->requested_pos_cnts = u2c * (requested_position +
```

```
neutral_pos);
requested_pos_cnts = mp->requested_pos_cnts;
// Bluff if we are already there
if( (abs( requested_pos_cnts - mp->actual_pos_cnts) * 16 <</pre>
    in_position_band) || (lsredis_getb( mp->active) != 1)) {
  ^{\prime\prime} // Lie and say we moved even though we didn't. Who will know? We are
    within the deadband or not active.
  mp->not_done = 1;
mp->motion_seen = 0;
  mp->not_done
  mp->command_sent = 0;
  lsevents_send_event( "%s Moving", mp->name);
  mp->not_done
  mp->motion_seen = 1;
  mp->command_sent = 1;
  if( lsredis_getb( mp->active) != 1) {
    // fake the motion for simulated motors
    mp->position = requested_position;
   mp->actual_pos_cnts = requested_pos_cnts;
  pthread_mutex_unlock( &(mp->mutex));
  lsevents_send_event( "%s In Position", mp->name);
  return 0;
mp->not_done
mp->motion_seen = 0;
mp->command_sent = 0;
if( use_jog || axis == NULL || *axis == 0) {
 use_jog = 1;
  use_jog = 0;
 q100 = 1 << (coord_num -1);
pthread_mutex_unlock( &(mp->mutex));
if( !use_jog) {
  ^{\prime\prime} // Make sure the coordinate system is not moving something, wait if it is
  pthread_mutex_lock( &lspmac_moving_mutex);
  clock_gettime( CLOCK_REALTIME, &now);
  // TODO: Have all moves estimate how long they'll take and use that here
  timeout.tv_sec = now.tv_sec + 60.0;
                                                    // a long timeout, but
    we might really be moving something that takes this long (or longer)
  timeout.tv_nsec = now.tv_nsec;
  err = 0;
  while( err == 0 && (lspmac_moving_flags & q100) != 0)
    err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
  pthread_mutex_unlock( &lspmac_moving_mutex);
  if( err == ETIMEDOUT) {
    lslogging_log_message( "
    lspmac_move_or_jog_abs_queue: Timed Out. lspmac_moving_flags = %0x", lspmac_moving_flags
    lsevents_send_event( "%s Move Aborted", mp->name);
    return 1;
  // Set the "we are moving this coordinate system" flag
  lspmac_SockSendDPline( NULL, "M5075=(M5075 | %d)",
    q100);
```

```
switch( *axis) {
case 'A':
   fmt = "&%d Q16=%d Q100=%d B146R";
   break;
 case 'B':
  fmt = "&%d Q17=%d Q100=%d B147R";
  case 'C':
   fmt = "&%d Q18=%d Q100=%d B148R";
    break;
    fmt = "&%d Q10=%d Q100=%d B140R";
 case 'Y':
  fmt = "&%d Q11=%d Q100=%d B141R";
    break;
   fmt = "&%d Q12=%d Q100=%d B142R";
    break;
 case 'U':
  fmt = "&%d Q13=%d Q100=%d B143R";
  case 'V':
   fmt = "&%d Q14=%d Q100=%d B144R";
   break;
  case 'W':
   fmt = "&%d Q15=%d Q100=%d B145R";
    break;
  // Make sure the flag has been seen
  clock_gettime( CLOCK_REALTIME, &now);
  timeout.tv_sec = now.tv_sec + 4.0;  // also a long t.

This should really only take a few milliseconds on a slow day
                                                       // also a long timeout.
  timeout.tv_nsec = now.tv_nsec;
  pthread_mutex_lock( &lspmac_moving_mutex);
  while( err == 0 && (lspmac_moving_flags & q100) == 0)
    err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
  pthread_mutex_unlock( &lspmac_moving_mutex);
  if( err == ETIMEDOUT) {
    lslogging_log_message( "
    lspmac_move_or_jog_abs_queue: Did not see flag propagate. Move aborted.");
    lsevents_send_event( "%s Move Aborted", mp->name);
    return 1;
  }
pthread_mutex_lock( & (mp->mutex));
  lspmac_SockSendDPline( mp->name, "#%d j=%d",
    motor_num, requested_pos_cnts);
} else {
  lspmac_SockSendDPline( mp->name, fmt, coord_num,
    requested_pos_cnts, q100);
pthread_mutex_unlock( &(mp->mutex));
free ( axis);
return 0;
```

7.5.4.46 int lspmac_move_or_jog_preset_queue (lspmac_motor_t * mp, char * preset, int use_jog)

move using a preset value returns 0 on success, non-zero on error

Parameters

in	тр	Our motor
in	preset	the name of the preset
	use_jog	[in[1 to force jog, 0 to try motion prog

Definition at line 3226 of file Ispmac.c.

```
double pos;
int err;
int err;
int rtn;

if( preset == NULL || *preset == 0) {
   lsevents_send_event( "%s Move Aborted", mp->name);
   return 0;
}

err = lsredis_find_preset( mp->name, preset, &pos);

if( err != 0)
   rtn = lspmac_move_or_jog_abs_queue( mp, pos,
        use_jog);

else {
   lsevents_send_event( "%s Move Aborted", mp->name);
   rtn = 1;
}
return rtn;
```

7.5.4.47 int lspmac_move_preset_queue (lspmac_motor_t * mp, char * preset_name)

Move a given motor to one of its preset positions.

No movement if the preset is not found.

Parameters

mp Ispmac motor pointer	
preset_name Name of the preset to use	

Definition at line 2393 of file Ispmac.c.

```
double pos;
int err;

lslogging_log_message( "lspmac_move_preset_queue: Called
    with motor %s and preset named '%s'", mp->name, preset_name);

err = lsredis_find_preset( mp->name, preset_name, &pos
    );
if( err == 0)
    return 1;

err = mp->jogAbs( mp, pos);
if( !err)
    lslogging_log_message( "lspmac_move_preset_queue:
        moving %s to preset '%s' (%f)", mp->name, preset_name, pos);
//
// the abort event should have been sent in moveAbs
//
return err;
```

7.5.4.48 int lspmac_moveabs_blight_factor_queue (Ispmac_motor_t * mp, double pos)

Definition at line 2586 of file Ispmac.c.

{

7.5.4.49 int lspmac_moveabs_bo_queue (lspmac motor t * mp, double requested_position)

Move method for binary i/o motor objects.

Parameters

in	тр	A binary i/o motor object
in	requested	a 1 or a 0 request to move
	position	

Definition at line 2467 of file Ispmac.c.

```
pthread_mutex_lock( & (mp->mutex));
mp->requested_position = requested_position == 0.0 ? 0.0 :
    1.0;
mp->requested_pos_cnts = requested_position == 0.0 ? 0 : 1;
mp->not_done = 1;
mp->motion_seen = 0;
lspmac_SockSendDPline( mp->name, mp->write_fmt
    , mp->requested_pos_cnts);

pthread_mutex_unlock( & (mp->mutex));
return 0;
```

7.5.4.50 int lspmac_moveabs_flight_factor_queue (lspmac_motor_t * mp, double pos)

Definition at line 2563 of file Ispmac.c.

```
( zoom));
return 0;
}
return 1;
```

7.5.4.51 int lspmac_moveabs_frontlight_oo_queue (lspmac_motor_t * mp, double pos)

"move" frontlight on/off

Definition at line 2550 of file Ispmac.c.

7.5.4.52 int lspmac_moveabs_fshut_queue (lspmac motor t * mp, double requested_position)

Move method for the fast shutter.

Slightly more complicated than a binary io as some flags need to be set up.

Parameters

тр	The fast shutter motor instance
requested	1 (open) or 0 (close), really
position	

Definition at line 2437 of file Ispmac.c.

```
pthread_mutex_lock( & (mp->mutex));

mp->requested_position = requested_position;
mp->not_done = 1;
mp->motion_seen = 0;
mp->requested_pos_cnts = requested_position;
if( requested_position != 0) {
    //
    // ScanEnable=0, ManualEnable=1, ManualOn=1
    //
    lspmac_SockSendDPline( mp->name, "M1124=0 M1125=1
        M1126=1");
} else {
    //
    // ManualOn=0, ManualEnable=0, ScanEnable=0
    //
    lspmac_SockSendDPline( mp->name, "M1126=0 M1125=0
        M1124=0");
}
pthread_mutex_unlock( & (mp->mutex));
return 0;
```

7.5.4.53 int lspmac_moveabs_queue (lspmac_motor_t * mp, double requested_position)

Use coordinate system motion program, if available, to move motor to requested position.

Parameters

in	тр	The motor to move
in	requested	Where to move it
	position	

Definition at line 3254 of file Ispmac.c.

7.5.4.54 void lspmac_moveabs_timed_queue (Ispmac_motor_t * mp, double start, double delta, double time)

timed motor move

Parameters

тр	Our motor object	
start	Beginning of motion	
delta Distance to move		
time to move it in (secs)		

< Flags needed for wait routine

Definition at line 2493 of file Ispmac.c.

```
// 240
                            LS-CAT Timed X move
//
                   010
                           = Starting X value (cnts)
                         = Delta X value (cnts)
= Time to run between the two points (mSec)
//
                   Q11
                   Q12
                            = Acceleration time (msecs)
                   013
                  Q100 = 1 << (coord sys no - 1)
                // Starting value (counts)
// Delta (counts)
// Time to run (msecs)
// Acceleration time (msecs)
// 1 << (coord sys no - 1)</pre>
int q10;
int q11;
int q12;
int q13;
int q100;
int coord_num; // our coordinate number
double u2c;
double neutral_pos;
double max_accel;
pthread_mutex_lock( &(mp->mutex));
u2c = lsredis_getd( mp->u2c);
max_accel = lsredis_getd( mp->max_accel);
coord_num = lsredis_getl( mp->coord_num);
neutral_pos = lsredis_getd( mp->neutral_pos);
if( u2c == 0.0 || time <= 0.0 || max_accel <= 0.0) {</pre>
   // Shouldn't try moving a motor that has bad motion parameters
   pthread_mutex_unlock( &(mp->mutex));
   return;
mp->not_done
mp->motion_seen = 0;
mp->requested position = start + delta;
mp->requested_pos_cnts = u2c * (mp->requested_position
       + neutral_pos);
```

7.5.4.55 int lspmac_moveabs_wait (lspmac_motor_t * mp, double timeout_secs)

Wait for motor to finish moving.

Assume motion already queued, now just wait

Parameters

тр	The motor object to wait for	
timeout_secs	The number of seconds to wait for. Fractional values fine.	

Definition at line 3280 of file Ispmac.c.

```
struct timespec timeout, now;
double isecs, fsecs;
int err;
^{\prime\prime} // Copy the queue item for the most recent move request
clock_gettime( CLOCK_REALTIME, &now);
fsecs = modf( timeout_secs, &isecs);
timeout.tv_sec = now.tv_sec + (long)floor( isecs);
timeout.tv_nsec = now.tv_nsec + (long)floor( fsecs * 1.0e9);
timeout.tv_sec += timeout.tv_nsec / 1000000000;
timeout.tv_nsec %= 1000000000;
err = 0;
pthread mutex lock( & (mp->mutex));
while( err == 0 && mp->command_sent == 0)
  err = pthread_cond_timedwait( &mp->cond, &mp->mutex, &timeout);
pthread_mutex_unlock( & (mp->mutex));
if( err != 0) {
  if( err != ETIMEDOUT) {
    lslogging_log_message( "lspmac_moveabs_wait:
     unexpected error from timedwait %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
  return 1;
\ensuremath{//} wait for the motion to have started
// This will time out if the motion ends before we can read the status back
\ensuremath{//} hence the added complication of time stamp of the sent packet.
err = 0;
pthread_mutex_lock( &(mp->mutex));
while( err == 0 && mp->motion_seen == 0)
  \verb|err = pthread_cond_timedwait( & (mp->cond), & (mp->mutex), & timeout)|\\
if ( err != 0) {
  if( err != ETIMEDOUT) {
    lslogging_log_message( "lspmac_moveabs_wait:
     unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
  pthread mutex unlock( & (mp->mutex));
  return 1;
```

```
//
// wait for the motion that we know has started to finish
//
err = 0;
while(err == 0 && mp->not_done)
  err = pthread_cond_timedwait( &(mp->cond), &(mp->mutex), &timeout)
  ;

if(err != 0) {
   if(err != ETIMEDOUT) {
      lslogging_log_message( "lspmac_moveabs_wait:
            unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec, timeout.tv_nsec);
   }
   pthread_mutex_unlock( &(mp->mutex));
   return 1;
}

//
// if return code was not 0 then we know we shouldn't wait for not_done flag.
// In this case the motion ended before we read the status registers
//
pthread_mutex_unlock( &(mp->mutex));
return 0;
```

7.5.4.56 int lspmac_movedac_queue (lspmac_motor_t * mp, double requested_position)

Move method for dac motor objects (ie, lights)

Parameters

in	тр	Our motor
in	requested	Desired x postion (look up and send y position)
	position	

Definition at line 2304 of file Ispmac.c.

```
double u2c;
pthread mutex lock( & (mp->mutex));
u2c = lsredis_getd( mp->u2c);
mp->requested_position = requested_position;
if( mp->nlut > 0 && mp->lut != NULL) {
  // u2c scales the lookup table value
  mp->requested_pos_cnts = u2c * lspmac_lut( mp->
    nlut, mp->lut, requested_position);
  lslogging_log_message( "lspmac_movedac_queue: motor %s
   requested position %f requested counts %d u2c %f",
                          mp->name, mp->requested_position
    , mp->requested_pos_cnts, u2c);
  mp->not_done = 1;
  mp->motion_seen = 0;
  lspmac_SockSendDPline( mp->name, "%s=%d", mp->
    dac_mvar, mp->requested_pos_cnts);
pthread_mutex_unlock( &(mp->mutex));
return 0;
```

7.5.4.57 int lspmac_movezoom_queue (lspmac_motor_t * mp, double requested_position)

Move method for the zoom motor.

Parameters

in	тр	the zoom motor
in	requested	our desired zoom
	position	

Definition at line 2337 of file Ispmac.c.

```
int motor_num;
int in_position_band;
lslogging_log_message( "lspmac_movezoom_queue: Here I am
");
pthread_mutex_lock( & (mp->mutex));
            = lsredis_get1( mp->motor_num);
motor_num
in_position_band = lsredis_getl( mp->in_position_band
mp->requested_position = requested_position;
if ( mp->nlut > 0 && mp->lut != NULL) {
  mp->requested_pos_cnts = lspmac_lut( mp->nlut
    , mp->lut, requested_position);
  if( abs( mp->requested_pos_cnts - mp->actual_pos_cnts
    ) * 16 <= in_position_band) {
lslogging_log_message( "lspmac_movezoom_queue:
     Faking move");
    //
// fake the move
                    = 1;
    mp->not_done
    mp->motion_seen = 0;
    pthread_mutex_unlock( &(mp->mutex));
    // Perhaps give someone else a chance to process the move
    pthread_mutex_lock( &(mp->mutex));
    mp->not_done = 0;
mp->motion_seen = 1;
    mp->command_sent = 1;
lsevents_send_event( "zoom In Position");
    pthread_mutex_unlock( & (mp->mutex));
 mp \rightarrow not done = 1:
 mp->motion_seen = 0;
  lspmac_SockSendDPline( mp->name, "#%d j=%d",
    motor_num, mp->requested_pos_cnts);
pthread_mutex_unlock( &(mp->mutex));
lslogging_log_message( "lspmac_movezoom_queue: There you
     were");
return 0;
```

7.5.4.58 void lspmac_next_state ()

State machine logic.

Given the current state, generate the next one

Definition at line 2135 of file Ispmac.c.

```
//
// Connect to the pmac and perhaps initialize it.
// OK, this is slightly more than just the state
// machine logic...
//
```

```
if( ls_pmac_state == LS_PMAC_STATE_DETACHED
  ) {
//
// TODO (eventually)
  // This ip address wont change in a single PMAC installation // We'll need to audit the code if we decide to implement
  // multiple PMACs so might as well wait til then.
  lsConnect( "192.6.94.5");
  // If the connect was successful we can proceed with the initialization
  if( ls_pmac_state != LS_PMAC_STATE_DETACHED
    lspmac_SockFlush();
    // Harvest the I and M variables in case we need them
    // one day.
    if( getmvars) {
  lspmac_GetAllMVars();
      getmvars = 0;
    if( getivars) {
      lspmac_GetAllIVars();
      getivars = 0;
    }
  }
}
// Check the command queue and perhaps go to the "Send Command" state.
if( ls_pmac_state == LS_PMAC_STATE_IDLE) {
  int goodtogo;
  goodtogo = 0;
  pthread_mutex_lock( &lspmac_ascii_mutex);
  if( lspmac_ascii_busy==0 && lspmac_dpascii_on
    != lspmac_dpascii_off)
goodtogo = 1;
  pthread_mutex_unlock( &lspmac_ascii_mutex);
  if ( goodtogo)
    lspmac_SockSendDPqueue();
if( ls_pmac_state == LS_PMAC_STATE_IDLE &&
    ethCmdOn != ethCmdOff)
  ls_pmac_state = LS_PMAC_STATE_SC;
// Set the events flag
// to tell poll what we are waiting for.
switch( ls_pmac_state) {
case LS_PMAC_STATE_DETACHED:
  ^{\prime\prime} // there shouldn't be a valid fd, so ignore the events
  11
  pmacfd.events = 0;
  break;
case LS_PMAC_STATE_IDLE:
  if(ethCmdOn == ethCmdOff) {
    // Anytime we are idle we want to
    // get the status of the PMAC
    lspmac_get_status();
case LS_PMAC_STATE_WACK_NFR:
case LS_PMAC_STATE_WACK:
case LS_PMAC_STATE_WACK_CC:
case LS_PMAC_STATE_WACK_RR:
case LS_PMAC_STATE_WCR:
case LS_PMAC_STATE_WGB:
case LS_PMAC_STATE_GMR:
```

```
pmacfd.events = POLLIN;
  break;
// These states require that we send packets out.
case LS_PMAC_STATE_SC:
case LS_PMAC_STATE_CR:
case LS_PMAC_STATE_RR:
case LS_PMAC_STATE_GB:
  11
  // Sad fact: PMAC will fail to process commands if we send them too
      quickly.
  // We deal with that by waiting a tad before we let poll tell us the PMAC
     socket is ready to write.
  gettimeofday( &now, NULL);
if( ((now.tv_sec * 1000000. + now.tv_usec) - (pmac_time_sent.tv_sec
 * 1000000. + pmac_time_sent.tv_usec)) < PMAC_MIN_CMD_TIME) {</pre>
    pmacfd.events = 0;
   pmacfd.events = POLLOUT;
  }
  break;
}
```

7.5.4.59 void lspmac_pmacmotor_read (lspmac_motor_t * mp)

Read the position and status of a normal PMAC motor.

Parameters

in	тр	Our motor
	F	

Definition at line 1366 of file Ispmac.c.

```
char s[512], *sp;
int homing1, homing2;
double u2c;
double neutral_pos;
int motor_num;
char *fmt;
int status_changed;
if( lsredis_getb( mp->active) != 1)
pthread_mutex_lock( &(mp->mutex));
// if this time and last time were both "in position"
// and the position changed significantly then log the event
// On E omega has been observed to change by 0x10000 on its own
// with no real motion.
if( mp->status2 & 1 && mp->status2 == *mp->status2_p
    && abs( mp->actual_pos_cnts - *mp->actual_pos_cnts_p
    ) > 256)
     lslogging_log_message( "Instantaneous change: %s old status1: %0x,
new status1: %0x, old status2: %0x, new status2: %0x, old cnts: %0x, new cnts:
     %0x",
                           mp->name, mp->status1, *mp->status1_p, mp->status2,
     *mp->status2_p, mp->actual_pos_cnts, *mp->actual_pos_cnts_p);
  // At this point we'll just log the event and return // There is no reason to believe the change is real.
  // There is a non-zero probability that the first value is the bad one and
     any value afterwards will be taken as
  ^{\prime\prime} wrong. Homing (or moving) the motor should fix this. There is a
     non-zero probably that it can happen
  // two or more times in a row after moving.
  // TODO: account for the case where mp->actual_pos_cnts is the bad value.
```

```
// TODO: Is this a problem when the motor is moving? Can we detect it?
  ^{\prime\prime} // TODO: Think of the correct change value here (currently 256) that works
     for all motors
  // or have this value configurable
  pthread_mutex_unlock( & (mp->mutex));
// Send an event if inPosition has changed
if( (mp->status2 & 0x000001) != (*mp->status2_p & 0x000001))
  lsevents_send_event( "%s %s", mp->name, (*mp->
    status2_p & 0x000001) ? "In Position" : "Moving");
// Get some values we might need later
u2c = lsredis_getd( mp->u2c);
motor_num = lsredis_getl( mp->motor_num);
neutral_pos = lsredis_getd( mp->neutral_pos);
// maybe look for omega zero crossing
if( motor_num == 1 && omega_zero_search && *mp->
    actual_pos_cnts_p >=0 && mp->actual_pos_cnts <
  if( omega_zero_velocity > 0.0) {
    secs = *mp->actual_pos_cnts_p / omega_zero_velocity
    nsecs = (*mp->actual_pos_cnts_p / omega_zero_velocity
     - secs) * 1000000000;
    omega_zero_time.tv_sec = lspmac_status_time
    .tv sec - secs;
    omega_zero_time.tv_nsec= lspmac_status_time
     .tv_nsec;
     if( omega_zero_time.tv_nsec < nsecs) {</pre>
      omega_zero_time.tv_sec -= 1;
omega_zero_time.tv_nsec += 1000000000;
    omega_zero_time.tv_nsec -= nsecs;
    lsevents_send_event( "omega crossed zero");
    {\tt lslogging\_log\_message("lspmac\_pmacmotor\_read: omega}
     zero secs %d nsecs %d ozt.tv_sec %ld ozt.tv_nsec %ld, motor cnts %d",
     secs, nsecs, omega_zero_time.tv_sec,
omega_zero_time.tv_nsec, *mp->actual_pos_cnts_p
    );
  omega_zero_search = 0;
// Make local copies so we can inspect them in other threads
// without having to grab the status mutex
if( mp->status1 != *mp->status1_p || mp->status2 != *
   mp->status2_p) {
  mp->status1 = *mp->status1_p;
mp->status2 = *mp->status2_p;
status_changed = 1;
  status_changed = 0;
mp->actual_pos_cnts = *mp->actual_pos_cnts_p;
// See if we are done moving, ie, in position
if( mp->status2 & 0x000001) {
  if( mp->not_done) {
    mp \rightarrow not done = 0;
    pthread_cond_signal(&(mp->cond));
} else if( mp->not_done == 0) {
  mp->not_done = 1;
```

```
// See if the motor is moving
//
                 move timer
                                            homing
                   123456
                                             123456
if( mp->status1 & 0x020000 || mp->status1 & 0x000400) {
 if( mp->motion_seen == 0) {
  mp->motion_seen = 1;
   pthread_cond_signal( &(mp->cond));
mvwprintw(mp->win, 2, 1, "%*d cts", LS_DISPLAY_WINDOW_WIDTH
    -6, mp->actual_pos_cnts);
if ( mp->nlut >0 && mp->lut != NULL) {
 mp->position = lspmac_rlut( mp->nlut, mp->lut, mp
    ->actual_pos_cnts);
} else {
  if ( u2c != 0.0) {
   mp->position = ((mp->actual_pos_cnts / u2c) -
   neutral_pos);
  } else {
   mp->position = mp->actual_pos_cnts;
 }
if( status_changed || fabs(mp->reported_position - mp->
    position) >= lsredis_getd(mp->update_resolution
  fmt = lsredis_getstr(mp->redis_fmt);
  lsredis_setstr( mp->redis_position, fmt, mp->
    position);
  free (fmt);
 mp->reported_position = mp->position;
fmt = lsredis_getstr( mp->printf_fmt);
snprintf( s, sizeof(s)-1, fmt, 8, mp->position);
s[sizeof(s)-1] = 0;
free ( fmt);
// indicate limit problems
lsredis_setstr( mp->pos_limit_hit, mp->statusl
    & 0x200000 ? "1" : "0");
lsredis_setstr( mp->neg_limit_hit, mp->status1
    & 0x400000 ? "1" : "0");
// set flag if we are not homed
homing1 = 0;
                         ~(homed flag)
if( mp->homing == 0 && (~mp->status2 & 0x000400) != 0) {
 homing1 = 1;
// set flag if we are homing and in open loop
homing2 = 0;
                          open loop
if( mp->homing == 1 && (mp->status1 & 0x040000) != 0) {
 homing2 = 1;
// maybe reset homing flag
                         homed flag
                                                         in position flag
if( (mp->homing == 2) && ((mp->status2 & 0x000400) != 0) && ((mp
    ->status2 & 0x000001) != 0)) {
  mp \rightarrow homing = 0;
  lsevents_send_event( "%s Homed", mp->name);
s[sizeof(s)-1] = 0;
mvwprintw( mp->win, 3, 1, "%*s", LS_DISPLAY_WINDOW_WIDTH
    -6, s);
if( status_changed) {
 mvwprintw(mp->win, 4, 1, "%*x", LS_DISPLAY_WINDOW_WIDTH
    -2, mp->status1);
  mvwprintw(mp->win, 5, 1, "%*x", LS_DISPLAY_WINDOW_WIDTH
  -2, mp->status2);
sp = "";
  if ( mp->status2 & 0x000002)
```

```
sp = "Following Warning";
  else if( mp->status2 & 0x000004)
sp = "Following Error";
  else if( mp->status2 & 0x000020)
    sp = "I2T Amp Fault";
  else if ( mp->status2 & 0x000008)
    sp = "Amp. Fault";
  else if( mp->status2 & 0x000800)
    sp = "Stopped on Limit";
  else if( mp->status1 & 0x040000)
    sp = "Open Loop";
else if( ~(mp->status1) & 0x080000)
    sp = "Motor Disabled";
  else if( mp->status1 & 0x000400)
    sp = "Homing";
  else if( (mp->status1 & 0x600000) == 0x600000)
    sp = "Both Limits Tripped";
else if( mp->status1 & 0x200000)
    sp = "Positive Limit";
  else if( mp->status1 & 0x400000)
    sp = "Negative Limit";
  else if( ~(mp->status2) & 0x000400)
    sp = "Not Homed";
  else if( mp->status1 & 0x020000)
sp = "Moving";
  else if( mp->status2 & 0x000001)
  sp = "In Position";
  mvwprintw(mp->win, 6, 1, "%*s", LS_DISPLAY_WINDOW_WIDTH
     -2, sp);
  lsredis_setstr( mp->status_str, sp);
wnoutrefresh( mp->win);
pthread_mutex_unlock( &(mp->mutex));
if( homing1)
  lspmac_home1_queue( mp);
if( homing2)
  lspmac_home2_queue( mp);
lspmac_status_last_time.tv_sec = lspmac_status_time
    .tv_sec;
lspmac_status_last_time.tv_nsec = lspmac_status_time
    .tv_nsec;
```

7.5.4.60 pmac_cmd_queue_t* lspmac_pop_queue()

Remove the oldest queue item.

Used to send command to PMAC. Note that there is a separate reply index to ensure we've know to what command a reply is refering. Returns the item.

Definition at line 668 of file Ispmac.c.

7.5.4.61 pmac cmd queue t* lspmac_pop_reply ()

Remove the next command queue item that is waiting for a reply.

We always need a reply to know we are done with a given command. Returns the item.

Definition at line 688 of file Ispmac.c.

```
pmac_cmd_queue_t *rtn;

pthread_mutex_lock( &pmac_queue_mutex);

if( ethCmdOn == ethCmdReply)
   rtn = NULL;
else
   rtn = &(ethCmdQueue[(ethCmdReply++) %
        PMAC_CMD_QUEUE_LENGTH]);

pthread_mutex_unlock( &pmac_queue_mutex);
return rtn;
```

7.5.4.62 pmac_cmd_queue_t* lspmac_push_queue (pmac_cmd_queue_t * cmd)

Put a new command on the queue.

Pointer is returned so caller can evaluate the time command was actually sent.

Parameters

```
cmd | Command to send to the PMAC
```

Definition at line 644 of file Ispmac.c.

7.5.4.63 void lspmac_Reset ()

Clear the queue and put the PMAC into a known state.

Definition at line 767 of file Ispmac.c.

```
ls_pmac_state = LS_PMAC_STATE_IDLE;
// clear queue
ethCmdReply = ethCmdOn;
ethCmdOff = ethCmdOn;
lspmac_SockFlush();
```

7.5.4.64 void Ispmac_reset_queue ()

Clear the queue as part of PMAC reinitialization.

Definition at line 631 of file Ispmac.c.

```
pthread_mutex_lock( &pmac_queue_mutex);
ethCmdOn = 0;
ethCmdOff = 0;
ethCmdReply = 0;
pthread_mutex_unlock( &pmac_queue_mutex);
}
```

7.5.4.65 double lspmac_rlut (int nlut, double * lut, double y)

Parameters

in	nlut	number of entries in lookup table
in	lut	our lookup table
in	у	the y value for which we need an x

Definition at line 452 of file Ispmac.c.

```
int i, foundone, up;
double m;
double y1, y2, x1, x2, x;
foundone = 0;
if( lut != NULL && nlut > 1) {
  ^{\prime\prime} // are the table values going up or down?
  //
  if( lut[1] < lut[2*nlut-1])</pre>
   up = 1;
  else
   up = 0;
  //
// Linear search
  for( i=0; i < 2*nlut; i += 2) {</pre>
    x1 = lut[i];
y1 = lut[i+1];
    if( i < 2*nlut - 2) {
      x2 = lut[i+2];
      y2 = lut[i+3];
    , // // see if \gamma is before the beginning of the table
    if(i==0 \&\& (up ? y1 > y : y1 < y)) {
      x = x1;
      foundone = 1;
      break;
    // Did we, perhaps, nail it?
    if(y1 == y) {
      x = x1;
      foundone = 1;
      break;
    // Interpolate between the two values (if we've not bumped our heads on
     the end of the table)
    if( (i < 2*nlut-2) && (up ? y < y2 : y > y2)) {
    m = (x2 - x1) / (y2 - y1);
    x = m * (y - y1) + x1;
    foundone = 1;
      break;
    }
  // y is off the charts: just use the last value
  if( foundone == 0 ) {
    x = lut[2*(nlut-1)];
  return x;
```

```
return 0.0;
```

7.5.4.66 void Ispmac_run ()

Start up the Ispmac thread.

Definition at line 4010 of file Ispmac.c.

```
char **inits;
lspmac_motor_t *mp;
char evts[64];
int i;
int active;
int motor_num;
pthread_create( &pmac_thread, NULL, lspmac_worker,
lsevents_add_listener( "CryoSwitchChanged",
    lspmac_cryoSwitchChanged_cb);
ispmac_cryoSwitchChanged_cb);
lsevents_add_listener( "scint Moving",
   lspmac_scint_maybe_move_sample_cb);
lsevents_add_listener( "scint In Position",
   lspmac_scint_maybe_return_sample_cb);
lsevents_add_listener( "scint In Position",
    lspmac_scint_inPosition_cb);
lsevents_add_listener( "scintDried",
    lspmac_scint_dried_cb);
lsevents_add_listener( "backLight 1",
lspmac_backLight_up_cb);
lsevents_add_listener( "backLight 0",
    lspmac_backLight_down_cb);
lsevents_add_listener( "cam.zoom Moving",
    lspmac_light_zoom_cb);
for( i=0; i<lspmac_nmotors; i++) {</pre>
  snprintf( evts, sizeof( evts)-1, "%s command accepted", lspmac_motors
     [i].name);
  evts[sizeof(evts)-1] = 0;
  lsevents_add_listener( evts, lspmac_command_done_cb
    );
lspmac_zoom_lut_setup();
lspmac_flight_lut_setup();
lspmac_blight_lut_setup();
lspmac_fscint_lut_setup();
// Clear the command interfaces
lspmac_SockSendControlCharPrint( NULL, '\x18')
  uint32_t cc;
  cc = 0;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
  cc = 0x18;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
     , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
// Initialize the MD2 pmac (ie, turn on the right plcc's etc)
for( inits = lsredis_get_string_array(lspmac_md2_init); *inits != NULL;
     inits++) {
  lspmac_SockSendDPline( NULL, *inits);
// Initialize the pmac's support for each motor
   (ie, set the various flag for when a motor is active or not)
```

```
for( i=0; i<1spmac_nmotors; i++) {</pre>
 mp = &(lspmac_motors[i]);
active = lsredis_getb( mp->active);
 mp
  motor_num = lsredis_get1( mp->motor_num);
  if ( motor_num >= 1 && motor_num <= 32) {</pre>
    // Set the PMAC to be consistant with redis
    lspmac_SockSendDPline( NULL, "I%d16=%f I%d17=%f
     I%d28=%d", motor_num, lsredis_getd( mp->max_speed), motor_num,
    lsredis_getd( mp->max_accel), motor_num, lsredis_getl
    ( mp->in_position_band));
  // if there is a problem with "active" then don't do anything
  // On the other hand, various combinations of yes/no true/fals 1/0 should
    work
  switch( active) {
  case 1:
   inits = lsredis_get_string_array( mp->active_init
    );
    break;
  case 0:
    inits = lsredis_get_string_array( mp->
    inactive_init);
    break:
  default:
   lslogging_log_message( "lspmac_run: motor %s is
     neither active nor inactive (!?)", mp->name);
    inits = NULL;
 if( inits != NULL) {
  while( *inits != NULL) {
     lspmac_SockSendDPline( NULL, *inits);
  }
```

7.5.4.67 void lspmac_scint_dried_cb (char * event)

Turn off the dryer.

Parameters

event | required by protocol

Definition at line 3827 of file Ispmac.c.

7.5.4.68 void lspmac_scint_inPosition_cb (char * event)

Maybe start drying off the scintilator.

Parameters

event required by protocol

Definition at line 3712 of file Ispmac.c.

{

7.5.4.69 void lspmac_scint_maybe_move_sample_cb (char * event)

Perhaps we need to move the sample out of the way.

Definition at line 3775 of file Ispmac.c.

```
double scint_target;
int err;
double move time;
int mmask;
pthread_mutex_lock( &scint->mutex);
scint_target = scint->requested_position;
pthread_mutex_unlock( &scint->mutex);
// This should be pretty conservative since the out position is around 80
if( scint_target > 10.0) {
  err = lspmac_est_move_time( &move_time, &mmask, alignx, 0, "Back", -2.0, aligny, 0, "Back", 1.0, alignz, 0, "Back", 1.0,
                                  NULL);
    lspmac_abort();
    lsevents_send_event( "Aborting Motion");
    lslogging_log_message( "
    lspmac_scint_maybe_move_sample_cb: Failed move request, aborting motion to keep scint from hitting sample");
}
```

7.5.4.70 void lspmac_scint_maybe_return_sample_cb (char * event)

Perhaps we need to return the sample to the beam.

Definition at line 3803 of file Ispmac.c.

```
double scint_target;
double move_time;
int mmask;

pthread_mutex_lock( &scint->mutex);
scint_target = scint->requested_position;
pthread_mutex_unlock( &scint->mutex);

// This should be pretty conservative since the out position is around 80
//
if( scint_target < 10.0) {
   lspmac_est_move_time( &move_time, &mmask,</pre>
```

```
alignx, 0, "Beam", 0.0,
aligny, 0, "Beam", 0.0,
alignz, 0, "Beam", 0.0,
NULL);
}
```

7.5.4.71 pmac_cmd_queue_t* lspmac_send_command (int rqType, int rq, int wValue, int wIndex, int wLength, char * data, void(*)(pmac_cmd_queue_t *, int, char *) responseCB, int no_reply, char * event)

Compose a packet and send it to the PMAC.

This is the meat of the PMAC communications routines. The queued command is returned.

Parameters

in	rqType	VR_UPLOAD or VR_DOWNLOAD
in	rq	PMAC command (see PMAC User Manual
in	wValue	Command argument 1
in	wIndex	Command argument 2
in	wLength	Length of data array
in	data	Data array (or NULL)
in	responseCB	Function to call when a response is read from the PMAC
in	no_reply	Flag, non-zero means no reply is expected
in	event	base name for events

Definition at line 706 of file Ispmac.c.

```
static pmac_cmd_queue_t cmd;
cmd.pcmd.RequestType = rqType;
cmd.pcmd.RequestType = rqType;
cmd.pcmd.Request = rq;
cmd.pcmd.wValue = htons(wValue);
cmd.pcmd.wIndex = htons(wIndex);
cmd.pcmd.wLength = htons(wLength);
cmd.onResponse = responseCB;
cmd.no_reply = no_reply;
cmd.event = event;
\ensuremath{//} Setting the message buff bData requires a bit more care to avoid over
       filling it
// or sending garbage in the unused bytes.
if( wLength > sizeof( cmd.pcmd.bData)) {
  ^{\prime\prime}/ // Bad things happen if we do not catch this case.
   lslogging_log_message( "Message Length %d longer than
       maximum of %ld, aborting", wLength, sizeof(cmd.pcmd.bData));
   exit( -1);
if ( data == NULL) {
  memset( cmd.pcmd.bData, 0, sizeof( cmd.pcmd.bData));
} else {
   // This could leave bData non-null terminated. I do not know if this is a
   if ( wLength > 0)
   memcpy( cmd.pcmd.bData, data, wLength);
if( wLength < sizeof( cmd.pcmd.bData))</pre>
     memset ( cmd.pcmd.bData + wLength, 0, sizeof ( cmd.pcmd.bData
     ) - wLength);
return lspmac_push_queue( &cmd);
```

7.5.4.72 void lspmac_sendcmd (char * event, void(*)(pmac_cmd_queue_t *, int, char *) responseCB, char * fmt, ...)

PMAC command with call back.

Parameters

in	event	base name for events
in	responseCB	our callback routine
in	fmt	printf style format string

Definition at line 2114 of file Ispmac.c.

7.5.4.73 void lspmac_sendcmd_nocb (char * fmt, ...)

Send a command that does not need to deal with the reply.

Parameters

in	fmt	A printf style format string

Definition at line 2095 of file Ispmac.c.

7.5.4.74 void lspmac_SendControlReplyPrintCB (pmac_cmd_queue_t * cmd, int nreceived, char * buff)

Receive a reply to a control character Print a "printable" version of the character to the terminal Followed by a hex dump of the response.

Parameters

in	cmd	Queue item this is a reply to
in	nreceived	Number of bytes received
in	buff	Buffer of bytes received

Definition at line 1031 of file Ispmac.c.

```
pthread_mutex_lock( &ncurses_mutex);
```

7.5.4.75 void lspmac_Service (struct pollfd * evt)

Service routine for packet coming from the PMAC.

All communications is asynchronous so this is the only place incomming packets are handled

Parameters

in	evt	pollfd object returned by poll
----	-----	--------------------------------

Definition at line 814 of file Ispmac.c.

```
static char *receiveBuffer = NULL; // the buffer inwhich to stick our
    incomming characters
static int receiveBufferSize = 0;
static int receiveBufferIn = 0;
                                               // size of receiveBuffer
                                              // next location to write to in
    receiveBuffer
pmac_cmd_queue_t *cmd;
    command we are servicing
ssize_t nsent, nread;
                                               // nbytes dealt with
                                              // loop counter
int i:
int foundEOCR;
                                               // end of command response flag
if( evt->revents & (POLLERR | POLLHUP | POLLNVAL)) {
  if( evt->fd != -1) {
   close( evt->fd);
   evt->fd = -1;
  ls_pmac_state = LS_PMAC_STATE_DETACHED;
if ( evt->revents & POLLOUT) {
  switch( ls_pmac_state) {
  case LS_PMAC_STATE_DETACHED:
   break;
  case LS_PMAC_STATE_IDLE:
   break;
  case LS_PMAC_STATE_SC:
    cmd = lspmac_pop_queue();
    if( cmd == NULL)
      return;
    if ( cmd->pcmd.Request == VR_PMAC_GETMEM) {
      nsent = send( evt->fd, cmd, pmac_cmd_size, 0);
      if( nsent != pmac_cmd_size) {
       lslogging_log_message( "Could only send %d of %d
     bytes....Not good.", (int)nsent, (int)(pmac_cmd_size));
    } else {
     nsent = send( evt->fd, cmd, pmac_cmd_size + ntohs(cmd->
    pcmd.wLength), 0);
      gettimeofday( &pmac_time_sent, NULL);
      if( nsent != pmac_cmd_size + ntohs(cmd->pcmd.wLength
    )) {
       lslogging_log_message( "Could only send %d of %d
     bytes....Not good.", (int)nsent, (int)(pmac_cmd_size + ntohs(cmd->
    pcmd.wLength)));
    }
    if( cmd->pcmd.Request == VR_PMAC_SENDCTRLCHAR
      ls_pmac_state = LS_PMAC_STATE_WACK_CC
```

```
else if( cmd->pcmd.Request == VR_PMAC_GETMEM)
      ls_pmac_state = LS_PMAC_STATE_GMR;
    else if( cmd->no_reply == 0)
  ls_pmac_state = LS_PMAC_STATE_WACK;
    else
      ls_pmac_state = LS_PMAC_STATE_WACK_NFR
    break;
  case LS PMAC STATE CR:
    nsent = send( evt->fd, &cr_cmd, pmac_cmd_size, 0);
gettimeofday( &pmac_time_sent, NULL);
ls_pmac_state = LS_PMAC_STATE_WCR;
  case LS_PMAC_STATE_RR:
    nsent = send( evt->fd, &rr_cmd, pmac_cmd_size, 0);
    gettimeofday( &pmac_time_sent, NULL);
     ls_pmac_state = LS_PMAC_STATE_WACK_RR;
  case LS_PMAC_STATE_GB:
    nsent = send( evt->fd, &gb_cmd, pmac_cmd_size, 0);
gettimeofday( &pmac_time_sent, NULL);
ls_pmac_state = LS_PMAC_STATE_WGB;
  }
if ( evt->revents & POLLIN) {
  if( receiveBufferSize - receiveBufferIn < 1400) {</pre>
    char *newbuff;
    receiveBufferSize += 1400:
    newbuff = calloc( receiveBufferSize, sizeof( unsigned char));
    if( newbuff == NULL) {
       lslogging_log_message( "lspmac_Service: Out of
     memory");
      exit( -1);
    if( receiveBuffer != NULL) {
  memcpy( newbuff, receiveBuffer, receiveBufferIn);
      free(receiveBuffer);
    receiveBuffer = newbuff;
  nread = read( evt->fd, receiveBuffer + receiveBufferIn, 1400);
  foundEOCR = 0;
  if( ls_pmac_state == LS_PMAC_STATE_GMR) {
    // get memory returns binary stuff, don't try to parse it
    receiveBufferIn += nread;
  } else {
    // other commands end in 6 if OK, 7 if not
    for( i=receiveBufferIn; i<receiveBufferIn+nread; i++) {</pre>
      if ( receiveBuffer[i] == 7) {
         // Error condition
         lspmac_Error( &(receiveBuffer[i]));
         receiveBufferIn = 0;
         return:
       if( receiveBuffer[i] == 6) {
         // End of command response
         foundEOCR = 1;
         receiveBuffer[i] = 0;
         break;
    receiveBufferIn = i;
  cmd = NULL;
  switch( ls_pmac_state) {
case LS_PMAC_STATE_WACK_NFR:
    receiveBuffer[--receiveBufferIn] = 0;
```

```
cmd = lspmac_pop_reply();
    ls_pmac_state = LS_PMAC_STATE_IDLE;
    break;
  case LS_PMAC_STATE_WACK:
    receiveBuffer[--receiveBufferIn] = 0;
ls_pmac_state = LS_PMAC_STATE_RR;
    break;
  case LS_PMAC_STATE_WACK_CC:
    receiveBuffer[--receiveBufferIn] = 0;
ls_pmac_state = LS_PMAC_STATE_CR;
    break;
  case LS_PMAC_STATE_WACK_RR:
    receiveBufferIn -= 2;
     if( receiveBuffer[receiveBufferIn])
       ls_pmac_state = LS_PMAC_STATE_GB;
      ls pmac_state = LS_PMAC_STATE_RR;
    receiveBuffer[receiveBufferIn] = 0;
    break;
  case LS_PMAC_STATE_GMR:
    cmd = lspmac_pop_reply();
    ls_pmac_state = LS_PMAC_STATE_IDLE;
    break;
  case LS_PMAC_STATE_WCR:
    cmd = lspmac_pop_reply();
     ls_pmac_state = LS_PMAC_STATE_IDLE;
    break;
  case LS_PMAC_STATE_WGB:
    if( foundEOCR) {
      cmd = lspmac_pop_reply();
ls_pmac_state = LS_PMAC_STATE_IDLE;
      ls_pmac_state = LS_PMAC_STATE_RR;
    break;
  if( cmd != NULL && cmd->onResponse != NULL) {
     cmd->onResponse( cmd, receiveBufferIn, receiveBuffer);
    receiveBufferIn = 0;
}
```

7.5.4.76 void lspmac_shutter_read (lspmac_motor_t * mp)

Fast shutter read routine The shutter is mildly complicated in that we need to take into account the fact that the shutter can open and close again between status updates.

This means that we need to rely on a PCL program running in the PMAC to monitor the shutter state and let us know that this has happened.

Parameters

in	тр	The motor object associated with the fast shutter

Definition at line 1187 of file Ispmac.c.

```
{
//
// track the shutter state and signal if it has changed
//
pthread_mutex_lock( &lspmac_shutter_mutex);
if( md2_status.fs_has_opened && !
    lspmac_shutter_has_opened && !md2_status.
    fs_is_open) {
    //
    // Here the shutter opened and closed again before we got the memo
    // Treat it as a shutter closed event
    //
    pthread_cond_signal( &lspmac_shutter_cond);
}
lspmac_shutter_has_opened = md2_status.
    fs_has_opened;
if( lspmac_shutter_state != md2_status.
```

7.5.4.77 void lspmac_SockFlush ()

Reset the PMAC socket from the PMAC side.

Puts the PMAC into a known communications state

Definition at line 760 of file Ispmac.c.

```
lspmac_send_command( VR_DOWNLOAD, VR_PMAC_FLUSH
    , 0, 0, 0, NULL, NULL, 1, NULL);
}
```

7.5.4.78 pmac_cmd_queue_t* lspmac_SockGetmem (int offset, int nbytes)

Request a chunk of memory to be returned.

Parameters

in	offset	Offset in PMAC Double Buffer
in	nbytes	Number of bytes to request

Definition at line 1066 of file Ispmac.c.

7.5.4.79 pmac_cmd_queue_t* lspmac_SockSendControlCharPrint (char * event, char c)

Send a control character.

Parameters

in	event	base name for events
	С	The control character to send

Definition at line 1119 of file Ispmac.c.

```
return lspmac_send_command( VR_DOWNLOAD,
    VR_PMAC_SENDCTRLCHAR, c, 0, 0, NULL,
    lspmac_SendControlReplyPrintCB, 0, event);
```

7.5.4.80 void lspmac_SockSendDPControlChar (char * event, char c)

use dpram ascii interface to send a control character

Definition at line 1995 of file Ispmac.c.

7.5.4.81 void lspmac_SockSendDPControlCharCB (pmac cmd queue t * cmd, int nreceived, char * buf)

Definition at line 1988 of file Ispmac.c.

```
if( cmd->event != NULL && *(cmd->event))
   lsevents_send_event( "%s accepted", cmd->event);
}
```

7.5.4.82 void lspmac_SockSendDPline (char * event, char * fmt, ...)

prepare (queue up) a line to send the dpram ascii command interface

Definition at line 1968 of file Ispmac.c.

7.5.4.83 void Ispmac_SockSendDPqueue ()

Definition at line 2004 of file Ispmac.c.

7.5.4.84 pmac_cmd_queue_t* lspmac_SockSendline (char * event, char * fmt, ...)

Send a one line command.

Uses printf style arguments.

Parameters

i	n	event	base name for events
i	n	fmt	Printf style format string

Definition at line 1076 of file Ispmac.c.

7.5.4.85 pmac cmd_queue t* lspmac_SockSendline_nr (char * event, char * fmt, ...)

Send a command and ignore the response.

Parameters

in	event	base name for events
in	fmt	Printf style format string

Definition at line 1099 of file Ispmac.c.

```
va_list arg_ptr;
char s[512];
va_start( arg_ptr, fmt);
vsnprintf( s, sizeof(s)-1, fmt, arg_ptr);
s[sizeof(s)-1] = 0;
va_end( arg_ptr);
lslogging_log_message( s);
```

7.5.4.86 Ispmac_motor_t* Ispmac_soft_motor_init (Ispmac_motor_t * d, char * name, int(*)(Ispmac_motor_t *, double) moveAbs)

Definition at line 3502 of file Ispmac.c.

```
_lspmac_motor_init( d, name);

d->moveAbs = moveAbs;
d->jogAbs = moveAbs;
d->read = lspmac_soft_motor_read;
d->actual_pos_cnts_p = calloc( sizeof(int), 1);
*d->actual_pos_cnts_p = 0;

return d;
}
```

7.5.4.87 void lspmac_soft_motor_read (lspmac_motor_t * p)

Dummy routine to read a soft motor.

Definition at line 3497 of file Ispmac.c.

}

7.5.4.88 int $lspmac_test_preset$ ($lspmac_motor_t*mp$, $char*preset_name$, double tolerance)

see if the motor is within tolerance of the preset 1 means yes, it is 0 mean no it isn't or that the preset was not found Definition at line 2416 of file Ispmac.c.

```
{
double preset_position;
int err;

err = lsredis_find_preset( mp->name, preset_name, &
    preset_position);
if( err == 0)
  return 0;

if( fabs( preset_position - lspmac_getPosition( mp)) <=
    tolerance)
  return 1;

return 0;</pre>
```

7.5.4.89 void lspmac_video_rotate (double secs)

Special motion program to collect centering video.

Definition at line 2610 of file Ispmac.c.

```
double q10;
                          // starting position (counts)
double q11;
                          // delta counts
                          \ensuremath{//} milliseconds to run over delta
double q12;
double u2c;
double neutral_pos;
if( secs <= 0.0)</pre>
  return;
omega zero search = 1:
pthread_mutex_lock( & (omega->mutex));
u2c = lsredis_getd( omega->u2c);
neutral_pos = lsredis_getd( omega->neutral_pos);
q10 = neutral_pos * u2c;
q11 = 360.0 * u2c;
q12 = 1000 * secs;
omega_zero_velocity = 360.0 * u2c / secs; //
      counts/second to back calculate zero crossing time
lspmac_SockSendDPline( omega->name, "&1
    Q10=%.1f Q11=%.1f Q12=%.1f Q13=(I117) Q14=(I116) B240R", q10, q11, q12);
pthread_mutex_unlock( &(omega->mutex));
```

7.5.4.90 void* Ispmac_worker (void * dummy)

Our Ispmac worker thread.

Parameters

Г	in	dummy Unused but required by pthread library

Definition at line 2253 of file Ispmac.c.

```
static int disconnected_notify = 0;
 static int old_state;
old_state = ls_pmac_state;
 while(1) {
          int pollrtn;
             lspmac_next_state();
             if( ls_pmac_state != old_state) {
    // lslogging_log_message( "lspmac_worker: state = %d",
                               ls_pmac_state);
                        old_state = ls_pmac_state;
             if( pmacfd.fd == -1) {
                        if( disconnected_notify == 0)
                                  lslogging_log_message( "lspmac_worker: PMAC not
                                connected");
                          disconnected_notify = 1;
                        // At this point we assume we became disconnected due to something like a hard boot of the MD2 PMAC
                          \ensuremath{//} and hence the entire system needs reinitialization.
                          // It's possible to put in a test here (perhaps using I65) to see if we
                               in fact suffered a reset % \left( 1\right) =\left( 1\right) \left( 1\right) 
                           \ensuremath{//} and need to clear the queue, reinitialize, etc. Or if it was just a
                              networking glitch and do not
                           // need to clear the queue and should instead just charge ahead.
                          lspmac_reset_queue();
                          sleep( 10);
                          \ensuremath{//} This just puts us into a holding pattern until the pmac becomes
                              connected again
                          //
                          continue;
```

```
}
disconnected_notify = 0;

pollrtn = poll( &pmacfd, 1, 10);
if( pollrtn) {
    lspmac_Service( &pmacfd);
}
}
```

7.5.4.91 void lspmac_zoom_lut_setup ()

Set up lookup table for zoom.

Definition at line 3835 of file Ispmac.c.

```
lsredis_obj_t *p;
double neutral_pos;
neutral_pos = lsredis_getd( zoom->neutral_pos);
pthread_mutex_lock( &zoom->mutex);
zoom->nlut = 10:
zoom->lut = calloc( 2 * zoom->nlut, sizeof( double));
if ( zoom->lut == NULL) {
  lslogging_log_message( "lspmac_zoom_lut_setup: out of
      memory");
   exit(-1);
for( i=0; i < zoom->nlut; i++) {
  p = lsredis_get_obj( "cam.zoom.%d.MotorPosition", i+1);
if( p==NULL || strlen( lsredis_getstr(p)) == 0) {
     free( zoom->lut);
zoom->lut = NULL;
zoom->nlut = 0;
     pthread_mutex_unlock( &zoom->mutex);
lslogging_log_message( "lspmac_zoom_lut_setup:
      cannot find MotorPosition element for cam.zoom level %d", i+1);
  zoom->lut[2*i] = i+1;
zoom->lut[2*i+1] = lsredis_getd( p) + neutral_pos;
pthread_mutex_unlock( &zoom->mutex);
```

7.5.5 Variable Documentation

7.5.5.1 Ispmac_motor_t* alignx

Alignment stage X.

Definition at line 100 of file lspmac.c.

7.5.5.2 Ispmac_motor_t* aligny

Alignment stage Y.

Definition at line 101 of file Ispmac.c.

7.5.5.3 Ispmac_motor_t* alignz

Alignment stage X.

Definition at line 102 of file Ispmac.c.

7.5.5.4 Ispmac_motor_t* anal

Polaroid analyzer motor.

Definition at line 103 of file Ispmac.c.

7.5.5.5 Ispmac_motor_t* apery

Aperture Y.

Definition at line 105 of file Ispmac.c.

Aperture Z.

Definition at line 106 of file Ispmac.c.

(whose arm? parked where?)

Definition at line 143 of file Ispmac.c.

7.5.5.8 Ispmac_motor_t* blight

Back Light DAC.

Definition at line 117 of file Ispmac.c.

7.5.5.9 Ispmac_bi_t* blight_down

Backlight is down.

Definition at line 133 of file Ispmac.c.

7.5.5.10 Ispmac_motor_t* blight_f

Back light scale factor.

Definition at line 126 of file Ispmac.c.

Back light Up/Down actuator.

Definition at line 121 of file Ispmac.c.

Backlight is up.

Definition at line 134 of file Ispmac.c.

7.5.5.13 Ispmac_motor_t* capy

Capillary Y.

Definition at line 107 of file Ispmac.c.

7.5.5.14 Ispmac_motor_t* capz

Capillary Z.

Definition at line 108 of file Ispmac.c.

7.5.5.15 Ispmac_motor_t* cenx

Centering Table X.

Definition at line 110 of file Ispmac.c.

Centering Table Y.

Definition at line 111 of file Ispmac.c.

7.5.5.17 pmac_cmd_t cr_cmd [static]

commands to send out "readready", "getbuffer", "controlresponse" (initialized in main)

Definition at line 195 of file Ispmac.c.

7.5.5.18 Ispmac_motor_t* cryo

Move the cryostream towards or away from the crystal.

Definition at line 122 of file Ispmac.c.

7.5.5.19 lspmac_bi_t* cryo_back

cryo is in the back position

Definition at line 135 of file Ispmac.c.

7.5.5.20 lspmac_bi_t* cryo_switch

that little toggle switch for the cryo

Definition at line 132 of file Ispmac.c.

7.5.5.21 unsigned char dbmem[64 *1024] [static]

double buffered memory

Definition at line 184 of file Ispmac.c.

```
7.5.5.22 int dbmemIn = 0 [static]
next location
Definition at line 185 of file Ispmac.c.
7.5.5.23 Ispmac_motor_t* dryer
blow air on the scintilator to dry it off
Definition at line 123 of file Ispmac.c.
7.5.5.24 | Ispmac_bi_t* etel_init_ok
ETEL initialized OK.
Definition at line 140 of file Ispmac.c.
7.5.5.25 | Ispmac_bi_t* etel_on
ETEL is on.
Definition at line 139 of file Ispmac.c.
7.5.5.26 Ispmac bi_t* etel_ready
ETEL is ready.
Definition at line 138 of file Ispmac.c.
7.5.5.27 unsigned int ethCmdOff = 0 [static]
points to current command (or none if == ethCmdOn)
Definition at line 198 of file Ispmac.c.
7.5.5.28 unsigned int ethCmdOn = 0 [static]
points to next empty PMAC command queue position
Definition at line 197 of file Ispmac.c.
7.5.5.29 pmac_cmd_queue_t ethCmdQueue[PMAC_CMD_QUEUE_LENGTH] [static]
PMAC command queue.
Definition at line 196 of file Ispmac.c.
7.5.5.30 unsigned int ethCmdReply = 0 [static]
Used like ethCmdOff only to deal with the pmac reply to a command.
Definition at line 199 of file Ispmac.c.
```

7.5.5.31 Ispmac_motor_t* flight

Front Light DAC.

Definition at line 116 of file Ispmac.c.

7.5.5.32 Ispmac_motor_t* flight_f

Front light scale factor.

Definition at line 127 of file Ispmac.c.

7.5.5.33 Ispmac_motor_t* flight_oo

Turn front light on/off.

Definition at line 125 of file Ispmac.c.

7.5.5.34 Ispmac_motor_t* fluo

Move the fluorescence detector in/out.

Definition at line 124 of file Ispmac.c.

fluor is in the back position

Definition at line 136 of file Ispmac.c.

7.5.5.36 Ispmac_motor_t* fscint

Scintillator Piezo DAC.

Definition at line 118 of file Ispmac.c.

Fast shutter.

Definition at line 115 of file Ispmac.c.

7.5.5.38 pmac_cmd_t gb_cmd [static]

Definition at line 195 of file Ispmac.c.

7.5.5.39 int getivars = 0 [static]

flag set at initialization to send i vars to db

Definition at line 88 of file Ispmac.c.

7.5.5.40 int getmvars = **0** [static]

flag set at initialization to send m vars to db

Definition at line 89 of file Ispmac.c.

7.5.5.41 Ispmac_bi_t* hp_air

High pressure air OK.

Definition at line 131 of file Ispmac.c.

7.5.5.42 Ispmac_motor_t* kappa

Kappa.

Definition at line 112 of file Ispmac.c.

7.5.5.43 Ispmac bi t* Ip_air

Low pressure air OK.

Definition at line 130 of file Ispmac.c.

7.5.5.44 int ls_pmac_state = LS_PMAC_STATE_DETACHED [static]

Current state of the PMAC communications state machine.

Definition at line 58 of file Ispmac.c.

7.5.5.45 | Ispmac_ascii_buffers_t | Ispmac_ascii_buffers [static]

Definition at line 364 of file Ispmac.c.

7.5.5.46 pthread_mutex_t lspmac_ascii_buffers_mutex

Definition at line 365 of file Ispmac.c.

7.5.5.47 int lspmac_ascii_busy = 0 [static]

flag for condition to wait for

Definition at line 75 of file Ispmac.c.

7.5.5.48 pthread_mutex_t lspmac_ascii_mutex [static]

Keep too many processes from sending commands at once.

Definition at line 74 of file Ispmac.c.

7.5.5.49 | Ispmac_bi_t | Ispmac_bis[32]

array of binary inputs

Definition at line 91 of file Ispmac.c.

7.5.5.50 uint32_t lspmac_dpascii_off = 0 [static]

Definition at line 375 of file Ispmac.c.

7.5.5.51 uint32_t lspmac_dpascii_on = 0 [static]

Definition at line 374 of file Ispmac.c.

7.5.5.52 Ispmac_dpascii_queue_t Ispmac_dpascii_queue[LSPMAC_DPASCII_QUEUE_LENGTH] [static]

Definition at line 373 of file Ispmac.c.

7.5.5.53 Ispmac motor_t Ispmac_motors[LSPMAC MAX MOTORS]

All our motors.

Definition at line 95 of file Ispmac.c.

7.5.5.54 pthread_cond_t lspmac_moving_cond

Wait for motor(s) to finish moving condition.

Definition at line 71 of file Ispmac.c.

7.5.5.55 int lspmac_moving_flags

Flag used to implement motor moving condition.

Definition at line 72 of file Ispmac.c.

7.5.5.56 pthread_mutex_t lspmac_moving_mutex

Coordinate moving motors between threads.

Definition at line 70 of file Ispmac.c.

7.5.5.57 int $lspmac_nbis = 0$

number of active binary inputs

Definition at line 92 of file Ispmac.c.

7.5.5.58 int lspmac_nmotors = 0

The number of motors we manage.

Definition at line 96 of file Ispmac.c.

7.5.5.59 pthread_cond_t lspmac_shutter_cond

Allows waiting for the shutter status to change.

Definition at line 69 of file Ispmac.c.

7.5.5.60 int lspmac_shutter_has_opened

Indicates that the shutter had opened, perhaps briefly even if the state did not change.

Definition at line 67 of file Ispmac.c.

7.5.5.61 pthread_mutex_t lspmac_shutter_mutex

Coordinates threads reading shutter status.

Definition at line 68 of file Ispmac.c.

7.5.5.62 int lspmac_shutter_state

State of the shutter, used to detect changes.

Definition at line 66 of file Ispmac.c.

7.5.5.63 struct timespec lspmac_status_last_time [static]

Time the status was read.

Definition at line 81 of file Ispmac.c.

7.5.5.64 struct timespec lspmac_status_time [static]

Time the status was read.

Definition at line 80 of file Ispmac.c.

7.5.5.65 md2_status_t md2_status [static]

Buffer for MD2 Status.

Definition at line 350 of file Ispmac.c.

7.5.5.66 pthread_mutex_t md2_status_mutex

Synchronize reading/writting status buffer.

Definition at line 351 of file Ispmac.c.

Minikappa is OK (whatever that means)

Definition at line 141 of file Ispmac.c.

7.5.5.68 struct hsearch_data motors_ht

A hash table to find motors by name.

Definition at line 97 of file Ispmac.c.

7.5.5.69 struct timeval pmac_time_sent now [static]

used to ensure we do not send commands to the pmac too often. Only needed for non-DB commands.

Definition at line 191 of file Ispmac.c.

```
7.5.5.70 Ispmac_motor_t* omega
```

MD2 omega axis (the air bearing)

Definition at line 99 of file Ispmac.c.

```
7.5.5.71 int omega_zero_search = 0 [static]
```

Indicate we'd really like to know when omega crosses zero.

Definition at line 77 of file Ispmac.c.

7.5.5.72 struct timespec omega_zero_time

Time we believe that omega crossed zero.

Definition at line 79 of file Ispmac.c.

```
7.5.5.73 double omega_zero_velocity = 0 [static]
```

rate (cnts/sec) that omega was traveling when it crossed zero

Definition at line 78 of file Ispmac.c.

```
7.5.5.74 Ispmac_motor_t* phi
```

Phi (not data collection axis)

Definition at line 113 of file Ispmac.c.

```
7.5.5.75 char* pmac_error_strs[] [static]
```

Initial value:

```
"ERR000: Unknown error",
"ERR001: Command not allowed during program execution",
"ERR002: Password error",
"ERR003: Data error or unrecognized command",
"ERR004: Illegal character",
"ERR005: Command not allowed unless buffer is open",
"ERR006: No room in buffer for command",
"ERR007: Buffer already in use",
"ERR008: MACRO auziliary communication error",
"ERR009: Program structure error (e.g. ENDIF without IF)",
"ERR010: Both overtravel limits set for a motor in the C.S.",
"ERR011: Previous move not completed",
"ERR012: A motor in the coordinate system is open-loop",
"ERR013: A motor in the coordinate system is not activated",
"ERR014: No motors in the coordinate system",
"ERR015: Not pointer to valid program buffer",
"ERR016: Running improperly structure program (e.g. missing ENDWHILE)",
"ERR017: Trying to resume after H or Q with motors out of stopped position",
"ERR018: Attempt to perform phase reference during move, move during phase
      reference, or enabling with phase clock error",
"ERRO19: Illegal position-chage command while moves stored in CCBUFFER",
"ERRO20: FSAVE issued on Turbo PMAC with incompatible flash memory",
"ERRO21: FSAVE issued while clearing old flash memory sector",
"ERRO22: FREAD attempted but the flash memory is bad"
```

Decode the errors perhaps returned by the PMAC.

Definition at line 202 of file Ispmac.c.

7.5.5.76 pthread_cond_t pmac_queue_cond

wait for a command to be sent to PMAC before continuing

Definition at line 85 of file Ispmac.c.

7.5.5.77 pthread_mutex_t pmac_queue_mutex

manage access to the pmac command queue

Definition at line 84 of file Ispmac.c.

7.5.5.78 pthread_t pmac_thread [static]

our thread to manage access and communication to the pmac

Definition at line 83 of file Ispmac.c.

7.5.5.79 struct pollfd pmacfd [static]

our poll structure

Definition at line 86 of file Ispmac.c.

7.5.5.80 pmac_cmd_trr_cmd [static]

Definition at line 195 of file Ispmac.c.

7.5.5.81 Ispmac_bi_t* sample_detected

smart magnet detected sample

Definition at line 137 of file Ispmac.c.

7.5.5.82 Ispmac_motor_t* scint

Scintillator Z.

Definition at line 109 of file Ispmac.c.

shutter is open (note in pmc says this is a slow input)

Definition at line 144 of file Ispmac.c.

7.5.5.84 Ispmac_bi_t* smart_mag_err

smart magnet error (coil broken perhaps)

Definition at line 145 of file Ispmac.c.

```
7.5.5.85 | Ispmac_bi_t* smart_mag_off
smart magnet is off
Definition at line 146 of file Ispmac.c.
7.5.5.86 | Ispmac_bi_t* smart_mag_on
smart magnet is on
Definition at line 142 of file Ispmac.c.
7.5.5.87 Ispmac_motor_t* smart_mag_oo
Smart Magnet on/off.
Definition at line 120 of file Ispmac.c.
7.5.5.88 Ispmac motor t* zoom
Optical zoom.
Definition at line 104 of file Ispmac.c.
7.6
       Isredis.c File Reference
Support redis hash synchronization.
#include "pgpmac.h"
Functions

    void <a href="mailto:lsredis_debugCB">lsredis_debugCB</a> (redisAsyncContext *ac, void *reply, void *privdata)

          Log the reply.

    void _lsredis_set_value (lsredis_obj_t *p, char *v)

          set_value and setstr helper funciton p->mutex must be locked before calling

    void lsredis_set_value (lsredis_obj_t *p, char *fmt,...)

          Set the value of a redis object and make it valid.
    • int lsredis_cmpstr (lsredis_obj_t *p, char *s)
    • int lsredis_cmpnstr (lsredis_obj_t *p, char *s, int n)
    • int lsredis_regexec (const regex_t *preg, lsredis_obj_t *p, size_t nmatch, regmatch_t *pmatch, int eflags)

    char * Isredis getstr (Isredis obj t *p)

          return a copy of the key's string value be sure to free the result

    void lsredis_setstr (lsredis_obj_t *p, char *fmt,...)
```

Set the value and update redis.

double lsredis_getd (lsredis_obj_t *p)
 long int lsredis_getl (lsredis_obj_t *p)

int lsredis_getb (lsredis_obj_t *p)char lsredis getc (lsredis obj t *p)

double lsredis_get_or_set_d (lsredis_obj_t *p, double val, int prec)

void lsredis_hgetCB (redisAsyncContext *ac, void *reply, void *privdata)

• long int lsredis_get_or_set_l (lsredis_obj_t *p, long int val)

char ** Isredis_get_string_array (Isredis_obj_t *p)

7.6 Isredis.c File Reference 207

Isredis_obj_t * _lsredis_get_obj (char *key)

Maybe add a new object Used internally for this module Must be called with Isredis_mutex locked.

- Isredis_obj_t * Isredis_get_obj (char *fmt,...)
- void redisDisconnectCB (const redisAsyncContext *ac, int status)

call back in case a redis server becomes disconnected TODO: reconnect

void Isredis addRead (void *data)

hook to mange read events

void lsredis_delRead (void *data)

hook to manage "don't need to read" events

void Isredis_addWrite (void *data)

hook to manage write events

void Isredis delWrite (void *data)

hook to manage "don't need to write anymore" events

void lsredis_cleanup (void *data)

hook to clean up TODO: figure out what we are supposed to do here and do it

void lsredis_subCB (redisAsyncContext *ac, void *reply, void *privdata)

Use the publication to request the new value.

- void lsredis_maybe_add_key (char *k)
- void lsredis_keysCB (redisAsyncContext *ac, void *reply, void *privdata)

Sift through the keys to find ones we like.

- int Isredis find preset (char *base, char *preset name, double *dval)
- void lsredis_set_preset (char *base, char *preset_name, double dval)
- int lsredis_find_preset_index_by_position (lspmac_motor_t *mp)
- void Isredis init (char *pub, char *re, char *head)

Initialize this module, that is, set up the connections.

void lsredis_fd_service (struct pollfd *evt)

service the socket requests

- void lsredis_sig_service (struct pollfd *evt)
- void * Isredis_worker (void *dummy)

subscribe to changes and service sockets

• void Isredis run ()

Variables

- static pthread_t lsredis_thread
- pthread_mutex_t lsredis_mutex = PTHREAD_RECURSIVE_MUTEX_INITIALIZER_NP
- pthread_cond_t lsredis_cond
- int lsredis_running = 0
- static lsredis_obj_t * lsredis_objs = NULL
- · static struct hsearch data Isredis htab
- static redisAsyncContext * subac
- static redisAsyncContext * roac
- static redisAsyncContext * wrac
- static char * Isredis publisher = NULL
- static regex_t lsredis_key_select_regex
- static char * Isredis_head = NULL
- · static struct pollfd subfd
- · static struct pollfd rofd
- static struct pollfd wrfd

7.6.1 Detailed Description

Support redis hash synchronization.

```
\date 2012
\author Keith Brister
\copyright All Rights Reserved
```

Redis support for redis in pgpmac.

Values in redis are assumed to be hashs with at list one field "VALUE". At startup the initialization routine is passed a regular expression to select which keys we'd like to duplicate locally as a Isredis_obj_t. It is assumed that the following construct in redis is used to change a value:

```
MULTI
HSET key VALUE value
PUBLISH publisher key
EXEC
```

Where "publisher" is a unique name in the following format:

```
MD2-*
or UI-*
or REDIS_KV_CONNECTOR
or mk_pgpmac_redis
```

(this last value is used to support the now depreciated px.kvs table in the LS-CAT postgresql server). We assume that all publisher that we are listening to ONLY publish key names that have changed.

When someone else changes a value we invalidate our internal copy and issue a "HGET key VALUE" command. Other threads that request the value of our Isredis_obj_t will pause until the new value has been received and processed.

When a value changes locally this module changes it in redis as shown above. At this point we refuse other publishers attempt to change the value until we've seen all of our PUBLISH messages. That is, we ignore changes that in redis happened before our change.

You'll need an Isredis_obj_t to do anything with redis in the pgpmac project:

```
lsredis_obj_t *lsredis_get_obj( char *fmt, ...) where fmt is a printf style formatting string

During initialization a "head" string is passe

For example, "omega.position" might refer to the
```

To set a redis value use

```
void lsredis_setstr( lsredis_obj_t *p, char *fmt, ...) where fmt is a printf style formatting
```

When a new value is seen we immediately parse it and make it available through the following functions:

```
char *lsredis_getstr( lsredis_obj_t *p) Returns a copy of the VALUE field. Usedouble lsredis_getd( lsredis_obj_t *p) Returns a double. If the value was not long int lsredis_getl( lsredis_obj_t *p) Returns a long int. If the value was returns an array of string pointers. Note that the value was returns an array of string pointers.
```

or NULL if the value could not be parsed

```
int lsredis_getb( lsredis_obj_t *p) Returns 1, 0, or -1 based on the fist of
char lsredis_getc( lsredis_obj_t *p) Returns the first character of VALUE
```

Definition in file Isredis.c.

7.6.2 Function Documentation

7.6.2.1 Isredis obj t* _lsredis_get_obj (char * key)

Maybe add a new object Used internally for this module Must be called with Isredis mutex locked.

Definition at line 488 of file Isredis.c.

```
lsredis_obj_t *p;
regmatch_t pmatch[2];
int err:
ENTRY htab_input, *htab_output;
\ensuremath{//} Dispense with obviously bad keys straight away
// unless p->valid == 0 in which case we call HGET first
// TODO: review logic: is there ever a time when valid is zero for a
     preexisting p and HGET has not been called?
         If not then we should just return p without checking for validity.
if( key == NULL || *key == 0 || strchr( key, ' ') != NULL) {
  lslogging_log_message( "_lsredis_get_obj: bad key '%s'
    ", key == NULL ? "<NULL>" : key);
 return NULL;
// If the key is already there then just return it
htab_input.key = key;
htab_input.data = NULL;
errno = 0;
err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab);
if( err == 0)
 p = NULL;
else
 p = htab_output->data;
if( p != NULL) {
 return p;
} else {
  // make a new one.
  p = calloc( 1, sizeof( lsredis_obj_t));
  if( p == NULL) {
   lslogging_log_message( "_lsredis_get_obj: Out of
    memory");
    exit( -1);
  err = regexec( &lsredis_key_select_regex, key, 2,
  pmatch, 0);
if( err == 0 && pmatch[1].rm_so != -1) {
   p->events_name = strndup( key+pmatch[1].rm_so, pmatch[1].rm_eo
    - pmatch[1].rm_so);
  } else {
   p->events_name = strdup( key);
  if( p->events_name == NULL) {
   lslogging_log_message( "_lsredis_get_obj: Out of
     memory (events_name)");
    exit(-1);
  pthread_mutex_init( &p->mutex, NULL);
  pthread_cond_init( &p->cond, NULL);
  p->value = NULL;
  p->valid = 0;
```

```
lsevents_send_event( "%s Invalid", p->events_name
  p->wait_for_me = 0;
  p->key = strdup( key);
p->hits = 0;
  htab_input.key = p->key;
  htab_input.data = p;
  errno = 0;
  err = hsearch_r( htab_input, ENTER, &htab_output, &lsredis_htab
  if( err == 0) {
   lslogging_log_message( "_lsredis_get_obj: hseach
     error on enter. errno=%d", errno);
  // Shouldn't need the linked list unless we need to rebuild the hash table
     when, for example, we run out of room.
  // TODO: resize hash table when needed.
  p->next = lsredis_objs;
  lsredis_objs = p;
\ensuremath{//} We arrive here with the valid flag lowered. Go ahead and request the
//
redisAsyncCommand( roac, lsredis_hgetCB, p, "HGET %s VALUE"
   , key);
return p;
```

7.6.2.2 void _lsredis_set_value (lsredis_obj_t * p, char * v)

set_value and setstr helper funciton p->mutex must be locked before calling Definition at line 146 of file Isredis.c.

```
if( strlen(v) >= (unsigned int) p->value_length) {
  if( p->value != NULL)
    free( p->value);
  p->value_length = strlen(v) + 256;
p->value = calloc(p->value_length, sizeof(char));
if(p->value == NULL) {
    lslogging_log_message( "_lsredis_set_value: out of
     memory");
    exit( -1);
strncpy( p->value, v, p->value_length - 1);
p->value[p->value_length-1] = 0;
p->dvalue = strtod( p->value, NULL);
p->lvalue = p->dvalue;
if( p->avalue != NULL) {
  int i:
  for( i=0; (p->avalue)[i] != NULL; i++)
    free( (p->avalue)[i]);
  free( p->avalue);
  p->avalue = NULL;
p->avalue = lspg_array2ptrs( p->value);
switch( *(p->value)) {
    case 'T':
case 't':
    case 'Y':
    case 'y':
    case '1':
      p->bvalue = 1;
    case 'F':
    case 'f':
    case 'N':
     case 'n':
```

7.6.2.3 void Isredis_addRead (void * data)

hook to mange read events

Definition at line 618 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

if( (pfd->events & POLLIN) == 0) {
   pfd->events |= POLLIN;
   pthread_kill( lsredis_thread, SIGUSR1);
}
}
```

7.6.2.4 void Isredis_addWrite (void * data)

hook to manage write events

Definition at line 642 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

if( (pfd->events & POLLOUT) == 0) {
   pfd->events |= POLLOUT;
   pthread_kill( lsredis_thread, SIGUSR1);
}
```

7.6.2.5 void lsredis_cleanup (void * data)

hook to clean up TODO: figure out what we are supposed to do here and do it

Definition at line 667 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

pfd->fd = -1;

if( (pfd->events & (POLLOUT | POLLIN)) != 0) {
  pfd->events &= ~(POLLOUT | POLLIN);
  pthread_kill( lsredis_thread, SIGUSR1);
}
```

7.6.2.6 int lsredis_cmpnstr (lsredis_obj_t * p, char * s, int n)

Definition at line 236 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
  pthread_cond_wait( &p->cond, &p->mutex);

rtn = strncmp( p->value, s, n);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.6.2.7 int lsredis_cmpstr (lsredis_obj_t * p, char * s)

Definition at line 225 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = strcmp( p->value, s);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.6.2.8 void lsredis_debugCB (redisAsyncContext * ac, void * reply, void * privdata)

Log the reply.

Definition at line 96 of file Isredis.c.

```
static int indentlevel = 0;
redisReply *r;
int i;
r = (redisReply *)reply;
if( r == NULL) {
 lslogging_log_message( "Null reply. Odd");
  return;
switch( r->type) {
case REDIS_REPLY_STATUS:
 lslogging_log_message( "%*sSTATUS: %s", indentlevel*4,
    "", r->str);
 break;
case REDIS_REPLY_ERROR:
 lslogging_log_message( "%*sERROR: %s", indentlevel*4,
    "", r->str);
 break;
case REDIS_REPLY_INTEGER:
 lslogging_log_message( "%*sInteger: %lld", indentlevel
   *4, "", r->integer);
case REDIS_REPLY_NIL:
 lslogging_log_message( "%*s(nil)", indentlevel*4, "");
 break;
case REDIS_REPLY_STRING:
 lslogging_log_message( "%*sSTRING: %s", indentlevel*4,
    "", r->str);
 break;
case REDIS_REPLY_ARRAY:
  lslogging_log_message( "%*sARRAY of %d elements",
```

```
indentlevel*4, "", (int)r->elements);
indentlevel++;
for( i=0; i<(int)r->elements; i++)
   lsredis_debugCB( ac, r->element[i], NULL);
indentlevel--;
break;

default:
   lslogging_log_message( "%*sUnknown type %d",
   indentlevel*4,"", r->type);
}
```

7.6.2.9 void lsredis_delRead (void * data)

hook to manage "don't need to read" events

Definition at line 630 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

if( (pfd->events & POLLIN) != 0) {
   pfd->events &= ~POLLIN;
   pthread_kill( lsredis_thread, SIGUSR1);
}
```

7.6.2.10 void lsredis_delWrite (void * data)

hook to manage "don't need to write anymore" events

Definition at line 654 of file Isredis.c.

```
struct pollfd *pfd;
pfd = (struct pollfd *)data;

if( (pfd->events & POLLOUT) != 0) {
    pfd->events &= ~POLLOUT;
    pthread_kill( lsredis_thread, SIGUSR1);
}
```

7.6.2.11 void lsredis_fd_service (struct pollfd * evt)

service the socket requests

Definition at line 1028 of file Isredis.c.

```
pthread_mutex_lock( &lsredis_mutex);
if( evt->fd == subac->c.fd)
  if( evt->revents & POLLIN)
    redisAsyncHandleRead( subac);
  if( evt->revents & POLLOUT)
    redisAsyncHandleWrite( subac);
if( evt->fd == roac->c.fd)
  if( evt->revents & POLLIN)
    redisAsyncHandleRead( roac);
  if( evt->revents & POLLOUT)
  redisAsyncHandleWrite( roac);
if ( evt->fd == wrac->c.fd)
  if( evt->revents & POLLIN)
    redisAsyncHandleRead( wrac);
  if( evt->revents & POLLOUT)
    redisAsyncHandleWrite( wrac);
pthread_mutex_unlock( &lsredis_mutex);
```

7.6.2.12 int lsredis_find_preset (char * base, char * preset_name, double * dval)

Definition at line 806 of file Isredis.c.

```
char s[512];
int i;
int err;
ENTRY htab_input, *htab_output;
lsredis_obj_t *p;
for( i=0; i<1024; i++) {</pre>
  snprintf(s, sizeof(s)-1, "%s.%s.presets.%d.name", lsredis_head
     , base, i);
  s[sizeof(s)-1] = 0;
  htab_input.key = s;
htab_input.data = NULL;
  err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab)
    // We've run out of names to look for: done
lslogging_log_message( "lsredis_find_preset: no
  preset for motor %s named '%s'", base, preset_name);
*dval = 0.0;
     return 0;
  \ensuremath{//} Check if we have a match
  p = htab_output->data;
  if( lsredis_cmpstr( p, preset_name) == 0) {
   // got a match, now look for the position
     snprintf(s, sizeof(s)-1, "%s.%s.presets.%d.position", lsredis_head
     , base, i);
     s[sizeof(s)-1] = 0;
     htab_input.key = s;
htab_input.data = NULL;
     err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab
      // Name but not position? odd.
lslogging_log_message( "lsredis_find_preset:
Error, motor %s preset '%s' has no position defined", base, preset_name);
*dval = 0.0;
       return 0;
     p = htab_output->data;
     *dval = lsredis_getd( p);
     return 1;
  }
// How'd we get here?
// did someone really define that many presets? And then looked for one
      that's not there?
*dval = 0;
return 0;
```

7.6.2.13 int lsredis_find_preset_index_by_position (lspmac motor t * mp)

Definition at line 916 of file Isredis.c.

```
lsredis_obj_t *p;
int plength;
int i;
double ur, pos;

p = lsredis_get_obj( "%s.presets.length", mp->name);
plength = lsredis_get_or_set_l(p, 0);

if(plength <= 0) {
    return -1;
}

ur = lsredis_getd( mp->update_resolution);
pos = lspmac_getPosition( mp);

for(i=0; i<plength; i++) {
    p = lsredis_get_obj( "%s.presets.%d.position", mp->name, i);
```

```
if( fabs( pos - lsredis_getd( p)) <= ur) {
    return i;
}
return -1;</pre>
```

7.6.2.14 | Isredis_obj_t* | Isredis_get_obj (char * fmt, ...)

Definition at line 574 of file Isredis.c.

```
lsredis_obj_t *rtn;
va_list arg_ptr;
char k[512];
char *kp;
int nkp;
va_start( arg_ptr, fmt);
vsnprintf(k, sizeof(k)-1, fmt, arg_ptr);
k[sizeof(k)-1] = 0;
va_end( arg_ptr);
nkp = strlen(k) + strlen( lsredis_head) + 16;
                                                                    // 16
is overkill. I know. Get over it.
kp = calloc( nkp, sizeof( char));
if( kp == NULL) {
 lslogging_log_message( "lsredis_get_obj: Out of memory
  exit(-1);
snprintf( kp, nkp-1, "%s.%s", lsredis_head, k);
kp[nkp-1] = 0;
pthread_mutex_lock( &lsredis_mutex);
while( lsredis_running == 0)
  pthread_cond_wait( &lsredis_cond, &lsredis_mutex);
rtn = _lsredis_get_obj( kp);
pthread_mutex_unlock( &lsredis_mutex);
free( kp);
```

7.6.2.15 double $lsredis_get_or_set_d$ ($lsredis_obj_t * p$, double val, int prec)

Definition at line 340 of file Isredis.c.

```
{
long int rtn;
int err;
struct timespec timeout;
clock_gettime( CLOCK_REALTIME, &timeout);
timeout.tv_sec += 2;
pthread_mutex_lock( &p->mutex);
err = 0;
while( err == 0 && p->valid == 0)
 err = pthread_cond_timedwait( &p->cond, &p->mutex, &timeout);
if( err == ETIMEDOUT) {
 rtn = val;
  lsredis_setstr( p, "%.*f", prec, val);
} else {
 rtn = p->lvalue;
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.6.2.16 long int lsredis_get_or_set_l (lsredis_obj_t * p, long int val)

Definition at line 390 of file Isredis.c.

```
long int rtn;
int err;
struct timespec timeout;
clock_gettime( CLOCK_REALTIME, &timeout);
timeout.tv_sec += 2;
pthread_mutex_lock( &p->mutex);
while( err == 0 && p->valid == 0)
  err = pthread_cond_timedwait( &p->cond, &p->mutex, &timeout);
if( err == ETIMEDOUT) {
  lslogging_log_message( "lsredis_get_or_set_1: using
     default value of %ld for redis variable %s", val, p->key);
  rtn = val;
  lsredis_setstr( p, "%ld", val);
} else {
  rtn = p->lvalue;
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.6.2.17 char** lsredis_get_string_array (lsredis_obj_t * p)

Definition at line 415 of file Isredis.c.

```
char **rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->avalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
}
```

7.6.2.18 int lsredis_getb (lsredis_obj_t * p)

Definition at line 428 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->bvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.6.2.19 char lsredis_getc (lsredis_obj_t * p)

Definition at line 441 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->cvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.6.2.20 double lsredis_getd (lsredis_obj_t * p)

Definition at line 364 of file Isredis.c.

```
double rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);
rtn = p->dvalue;
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.6.2.21 long int lsredis_getl (lsredis_obj_t * p)

Definition at line 377 of file Isredis.c.

```
long int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
  pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->lvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.6.2.22 char* lsredis_getstr (lsredis_obj_t * p)

return a copy of the key's string value be sure to free the result

Definition at line 264 of file Isredis.c.

```
char *rtn;

//
// Have to use strdup since we cannot guarantee that p->value won't be freed
    while the caller is still using it
//
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
pthread_cond_wait( &p->cond, &p->mutex);

rtn = strdup(p->value);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.6.2.23 void lsredis_hgetCB (redisAsyncContext * ac, void * reply, void * privdata)

Definition at line 454 of file Isredis.c.

```
{
redisReply *r;
lsredis_obj_t *p;
r = reply;
p = privdata;
// lslogging_log_message( "hgetCB: %s %s", p == NULL ? "<NULL>" : p->key, r->type == REDIS_REPLY_STRING ? r->str : "Non-string value. Why?");
//
// Apparently this item does not exist
^{\prime\prime} // Just set it to an empty string so at least other apps will have the same
      behaviour as us
// TODO: figure out a better way to deal with missing key/values
if( p != NULL && r->type == REDIS_REPLY_NIL) {
  lsredis_setstr( p, "");
  return;
if( p != NULL && r->type == REDIS_REPLY_STRING && r->str != NULL) {
  pthread_mutex_lock( &p->mutex);
  _lsredis_set_value( p, r->str);
  pthread_cond_signal( &p->cond);
  pthread_mutex_unlock( &p->mutex);
```

7.6.2.24 void lsredis_init (char * pub, char * re, char * head)

Initialize this module, that is, set up the connections.

Parameters

pub	Publish under this (unique) name
re	Regular expression to select keys we want to mirror
head	Prepend this (+ a dot) to the beginning of requested objects

Definition at line 949 of file Isredis.c.

```
int err;
int nerrmsq;
char *errmsg;
\ensuremath{//} set up hash map to store redis objects
err = hcreate_r( 8192, &lsredis_htab);
if( err == 0) {
   lslogging_log_message( "lsredis_init: Cannot create
    hash table. Really bad things are going to happen. hcreate_r returned %d", err);
lsredis_head
                = strdup( head);
lsredis_publisher = strdup( pub);
pthread_cond_init( &lsredis_cond, NULL);
subac = redisAsyncConnect("127.0.0.1", 6379);
if( subac->err) {
  lslogging_log_message( "Error: %s", subac->errstr
   );
subfd.fd
                   = subac->c.fd:
subfd.events
                   = 0;
subac->ev.data
                   = &subfd;
```

```
subac->ev.addRead = lsredis_addRead;
subac->ev.delRead = lsredis_delRead;
subac->ev.addWrite = lsredis_addWrite;
subac->ev.delWrite = lsredis_delWrite;
subac->ev.cleanup = lsredis_cleanup;
roac = redisAsyncConnect("127.0.0.1", 6379);
  lslogging_log_message( "Error: %s", roac->errstr);
rofd.fd
                    = roac->c.fd;
                    = 0;
rofd.events
roac->ev.data
                    = &rofd;
roac->ev.addRead = lsredis_addRead;
roac->ev.delRead = lsredis_delRead;
roac->ev.addWrite = lsredis_addWrite;
roac->ev.delWrite = lsredis_delWrite;
roac->ev.cleanup = lsredis_cleanup;
//wrac = redisAsyncConnect("10.1.0.3", 6379);
wrac = redisAsyncConnect("127.0.0.1", 6379);
if( wrac->err) {
  lslogging_log_message( "Error: %s", wrac->errstr);
wrfd.fd
                    = wrac->c.fd;
wrfd.events
                   = 0;
wrac->ev.data
                    = &wrfd;
wrac->ev.addRead = lsredis_addRead;
wrac->ev.delRead = lsredis_delRead;
wrac->ev.addWrite = lsredis_addWrite;
wrac->ev.delWrite = lsredis_delWrite;
wrac->ev.cleanup = lsredis_cleanup;
err = regcomp( &lsredis_key_select_regex, re,
    REG_EXTENDED);
if( err != 0) {
  nerrmsg = regerror( err, &lsredis_key_select_regex,
     NULL, 0);
  if( nerrmsg > 0) {
    errmsg = calloc( nerrmsg, sizeof( char));
    nerrmsg = regerror( err, &lsredis_key_select_regex
     , errmsg, nerrmsg);
    lslogging_log_message( "lsredis_select: %s", errmsg)
     free ( errmsg);
  }
}
```

7.6.2.25 void | sredis_keysCB (redisAsyncContext * ac, void * reply, void * privdata)

Sift through the keys to find ones we like.

Add them to our list of followed objects

Definition at line 785 of file Isredis.c.

```
{
  redisReply *r;
 int i;
  r = reply;
  if( r->type != REDIS_REPLY_ARRAY) {
   lslogging_log_message( "lsredis_keysCB: exepected
      array...");
    lsredis_debugCB( ac, reply, privdata);
   return;
  for( i=0; i< (int)r->elements; i++) {
    if( r->element[i]->type != REDIS_REPLY_STRING) {
     lslogging_log_message( "lsredis_keysCB: exected
     lsredis_debugCB( ac, r->element[i], privdata);
    } else {
     lsredis_maybe_add_key( r->element[i]->str);
 }
}
```

7.6.2.26 void Isredis_maybe_add_key (char * k)

Definition at line 777 of file Isredis.c.

```
if( regexec( &lsredis_key_select_regex, k, 0, NULL, 0
    ) == 0) {
    _lsredis_get_obj( k);
}
```

7.6.2.27 int Isredis_regexec (const regex_t * preg, Isredis_obj_t * p, size_t nmatch, regmatch_t * pmatch, int eflags)

Definition at line 247 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = regexec( preg, p->value, nmatch, pmatch, eflags);
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.6.2.28 void Isredis_run ()

Definition at line 1153 of file Isredis.c.

```
pthread_create( &lsredis_thread, NULL, lsredis_worker
    , NULL);
}
```

7.6.2.29 void Isredis_set_preset (char * base, char * preset_name, double dval)

Definition at line 852 of file Isredis.c.

```
{
char s[512];
int i, plength;
int err;
ENTRY htab_input, *htab_output;
lsredis_obj_t *p;
p = lsredis_get_obj( "%s.%s.presets.length", lsredis_head
    , base);
plength = lsredis_get_or_set_1( p, 0);
for( i=0; i<plength; i++) {</pre>
  snprintf(s, sizeof(s)-1, "%s.%s.presets.%d.name", lsredis_head
    , base, i);
  s[sizeof(s)-1] = 0;
  htab_input.key = s;
htab_input.data = NULL;
  err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab)
  if( err == 0) {
    // Not found? odd. Length Lied.
    // Might as well just stick our preset here.
    p = lsredis_get_obj( "%s", s);
lsredis_setstr( p, "%s", preset_name);
  } else {
```

```
// Check if we have a match
   p = htab_output->data;
  if( lsredis_cmpstr( p, preset_name) == 0) {
    // got a match, now look for the position
    snprintf( s, sizeof( s)-1, "%s.%s.presets.%d.position", lsredis_head
    , base, i);
    s[sizeof(s)-1] = 0;
    htab_input.key = s;
    htab_input.data = NULL;
    err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab
    if( err == 0) {
      // Name but not position? odd.
      p = lsredis_get_obj( "%s", s);
      p = htab_output->data;
    lsredis_setstr( p, "%.3f", dval);
    return;
// OK, our preset was not found, add it
snprintf( s, sizeof( s)-1, "%s.%s.presets.%d.name", lsredis_head,
     base, i);
s[sizeof(s)-1] = 0;
p = lsredis_get_obj( "%s", s);
lsredis_setstr( p, "%s", preset_name);
p = lsredis_get_obj( "%s", s);
lsredis_setstr( p, "%.3f", dval);
p = lsredis_get_obj( "%s.%s.presets.length", lsredis_head
lsredis_setstr( p, "%ld", plength + 1);
```

7.6.2.30 void lsredis_set_value (lsredis_obj_t * p, char * fmt, ...)

Set the value of a redis object and make it valid.

Called by mgetCB to set the value as it is in redis Maybe TODO: we've arbitrarily set the maximum size of a value here. Although I cannot imagine needed bigger values it would not be a big deal to enable it.

Definition at line 207 of file Isredis.c.

```
va_list arg_ptr;
char v[512];

va_start( arg_ptr, fmt);
vsnprintf( v, sizeof(v)-1, fmt, arg_ptr);
va_end( arg_ptr);

v[sizeof(v)-1] = 0;

pthread_mutex_lock( &p->mutex);

_lsredis_set_value( p, v);

pthread_cond_signal( &p->cond);
pthread_mutex_unlock( &p->mutex);
```

7.6.2.31 void lsredis_setstr (lsredis_obj_t * p, char * fmt, ...)

Set the value and update redis.

Note that Isredis_set_value sets the value based on redis while here we set redis based on the value Arbitray maximum string length set here. TODO: Probably this limit should be removed at some point.

redisAsyncCommandArgv used instead of redisAsyncCommand 'cause it's easier (and possible) to deal with strings that would otherwise cause hiredis to emit a bad command, like those containing spaces. < up the count of times we need to see ourselves published before we start listening to others again

- < Unlock to prevent deadlock in case the service routine needs to set our value
- < redisAsyncCommandArgv shouldn't need to access this after it's made up it's packet (before it returns) so we should be OK with this location disappearing soon.

Definition at line 289 of file Isredis.c.

```
{
va_list arg_ptr;
char v[512];
char *argv[4];
va_start( arg_ptr, fmt);
vsnprintf( v, sizeof(v)-1, fmt, arg_ptr);
v[sizeof(v)-1] = 0;
va_end( arg_ptr);
pthread mutex lock( &p->mutex);
// Don't send an update if a good value has not changed
if( p->valid && strcmp( v, p->value) == 0) {
 // nothing to do
  pthread_mutex_unlock( &p->mutex);
  return;
p->wait_for_me++;
pthread_mutex_unlock( &p->mutex);
argv[0] = "HSET";
argv[1] = p->key;
argv[2] = "VALUE";
argv[3] = v;
pthread_mutex_lock( &lsredis_mutex);
while( lsredis_running == 0)
 pthread_cond_wait( &lsredis_cond, &lsredis_mutex);
redisAsyncCommand( wrac, NULL, NULL, "MULTI");
redisAsyncCommandArgv( wrac, NULL, NULL, 4, (const char **)argv, NULL);
redisAsyncCommand( wrac, NULL, NULL, "PUBLISH %s %s", lsredis_publisher
redisAsyncCommand( wrac, NULL, NULL, "EXEC");
pthread_mutex_unlock( &lsredis_mutex);
// Assume redis will take exactly the value we sent it
pthread_mutex_lock( &p->mutex);
_lsredis_set_value( p, v);
pthread_cond_signal( &p->cond);
pthread_mutex_unlock( &p->mutex);
```

7.6.2.32 void Isredis_sig_service (struct pollfd * evt)

Parameters

in	evt The pollfd object that triggered this call	evt	

Definition at line 1052 of file Isredis.c.

```
{
struct signalfd_siginfo fdsi;

//
// Really, we don't care about the signal,
// it's just used to drop out of the poll
// function when there is something for us
// to do.
```

```
read( evt->fd, &fdsi, sizeof( struct signalfd_siginfo));
}
```

7.6.2.33 void | sredis_subCB (redisAsyncContext * ac, void * reply, void * privdata)

Use the publication to request the new value.

Definition at line 685 of file Isredis.c.

```
redisReply *r;
lsredis_obj_t *p;
char *k:
char *publisher;
ENTRY htab_input, *htab_output;
int err;
r = (redisReply *)reply;
// Ignore our psubscribe reply
if( r->type == REDIS_REPLY_ARRAY && r->elements == 3 && r->element[0]->type
    == REDIS_REPLY_STRING && strcmp( r->element[0]->str, "psubscribe")==0)
  return;
// But log other stuff we don't understand
if( r->type != REDIS_REPLY_ARRAY ||
    r->elements != 4 ||
    r->element[3]->type != REDIS_REPLY_STRING ||
    r->element[2]->type != REDIS_REPLY_STRING) {
  lslogging_log_message( "lsredis_subCB: unexpected
    reply");
  lsredis_debugCB( ac, reply, privdata);
  return;
// Ignore obvious junk
k = r \rightarrow element[3] \rightarrow str;
if(k == NULL || *k == 0)
 return;
// see if we care
if( regexec( &lsredis_key_select_regex, k, 0, NULL, 0
  ) == 0) {
//
  // We should know about this one
  htab_input.key = k;
  htab_input.data = NULL;
  errno = 0;
  err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab)
  if( err == 0 && errno == ESRCH)
  p = NULL;
else
  p = htab_output->data;
  if( p == NULL) {
    _lsredis_get_obj( k);
   else {
    // Look who's talk'n
    publisher = r->element[2]->str;
    pthread_mutex_lock( &p->mutex);
    if( p->wait_for_me) {
      // see if we are done waiting
```

```
if( strcmp( publisher, lsredis_publisher) == 0)
      p->wait_for_me--;
    pthread_mutex_unlock( &p->mutex);
     ^{\prime\prime} // Don't get a new value, either we set it last or we are still waiting
   for redis to report
    // our publication
    return;
  }
  // Here we know our value is out of date
  p->valid = 0;
  lsevents_send_event( "%s Invalid", p->events_name
  pthread_mutex_unlock( &p->mutex);
  // We shouldn't get here if wait_for_me is zero and we are the publisher.
  // If somehow we did (ie we did an hset with out incrementing wait_for_me or if we published too many times), it shouldn't hurt to get the value again.
  redisAsyncCommand( roac, lsredis_hgetCB, p, "HGET %s
   VALUE", k);
}
```

7.6.2.34 void* Isredis_worker (void * dummy)

subscribe to changes and service sockets

- < poll timeout, in millisecs (of course)
- < array of pollfd's for the poll function, one entry per connection
- < number of active elements in fda

Definition at line 1071 of file Isredis.c.

```
static int poll_timeout_ms = -1;
static struct pollfd fda[4];
static int nfda = 0;
static sigset_t our_sigset;
int pollrtn;
int i;
pthread_mutex_lock( &lsredis_mutex);
//
// block ordinary signal mechanism
sigemptyset( &our_sigset);
sigaddset( &our_sigset, SIGUSR1);
pthread_sigmask( SIG_BLOCK, &our_sigset, NULL);
// Set up fd mechanism
fda[0].fd = signalfd( -1, &our_sigset, SFD_NONBLOCK);
if(fda[0].fd == -1) {
 char *es;
  es = strerror( errno);
 lslogging_log_message( "lsredis_worker: Signalfd
    trouble '%s'", es);
fda[0].events = POLLIN;
nfda = 1;
lsredis_running = 1;
if( redisAsyncCommand( subac, lsredis_subCB, NULL, "
    PSUBSCRIBE REDIS_KV_CONNECTOR mk_pgpmac_redis UI* MD2-*") == REDIS_ERR) {
  lslogging_log_message( "Error sending PSUBSCRIBE
     command");
redisAsyncCommand( roac, lsredis_keysCB, NULL, "KEYS *");
```

```
pthread_cond_signal( &lsredis_cond);
pthread_mutex_unlock( &lsredis_mutex);
while(1) {
  nfda = 1:
  pthread_mutex_lock( &lsredis_mutex);
  if( subfd.fd != -1) {
  fda[nfda].fd =
     fda[nfda].fd = subfd.fd;
fda[nfda].events = subfd.events;
    fda[nfda].revents = 0;
    nfda++;
  if( rofd.fd != -1) {
  fda[nfda].fd = rofd.fd;
  fda[nfda].events = rofd.events;
  fda[nfda].revents = 0;
   nfda++;
  if( wrfd.fd != -1) {
    fda[nfda].fd = wrfd.fd;
fda[nfda].events = wrfd.events;
     fda[nfda].revents = 0;
  pthread_mutex_unlock( &lsredis_mutex);
  pollrtn = poll( fda, nfda, poll_timeout_ms);
  if( pollrtn && fda[0].revents) {
     lsredis_sig_service( &(fda[0]));
    pollrtn--;
  for( i=1; i<nfda; i++) {</pre>
    if( fda[i].revents) {
       lsredis_fd_service( &(fda[i]));
  }
```

7.6.2.35 void redisDisconnectCB (const redisAsyncContext * ac, int status)

call back in case a redis server becomes disconnected TODO: reconnect Definition at line 610 of file Isredis.c.

7.6.3 Variable Documentation

7.6.3.1 pthread_cond_t lsredis_cond

Definition at line 75 of file Isredis.c.

7.6.3.2 char* Isredis_head = NULL [static]

Definition at line 88 of file Isredis.c.

7.6.3.3 struct hsearch_data lsredis_htab [static]

Definition at line 80 of file Isredis.c.

```
7.6.3.4 regex_t | sredis_key_select_regex [static]
Definition at line 87 of file Isredis.c.
7.6.3.5 pthread_mutex_t Isredis_mutex = PTHREAD_RECURSIVE_MUTEX_INITIALIZER_NP
Definition at line 74 of file Isredis.c.
7.6.3.6 Isredis_obj_t* Isredis_objs = NULL [static]
Definition at line 79 of file Isredis.c.
7.6.3.7 char* lsredis_publisher = NULL [static]
Definition at line 86 of file Isredis.c.
7.6.3.8 int Isredis_running = 0
Definition at line 76 of file Isredis.c.
7.6.3.9 pthread_t Isredis_thread [static]
Definition at line 72 of file Isredis.c.
7.6.3.10 redisAsyncContext* roac [static]
Definition at line 83 of file Isredis.c.
7.6.3.11 struct pollfd rofd [static]
Definition at line 91 of file Isredis.c.
7.6.3.12 redisAsyncContext* subac [static]
Definition at line 82 of file Isredis.c.
7.6.3.13 struct pollfd subfd [static]
Definition at line 90 of file Isredis.c.
7.6.3.14 redisAsyncContext* wrac [static]
Definition at line 84 of file Isredis.c.
7.6.3.15 struct pollfd wrfd [static]
Definition at line 92 of file Isredis.c.
```

7.7 Istest.c File Reference 227

7.7 Istest.c File Reference

```
#include "pgpmac.h"
```

Functions

- · void Istest Ispmac est move time ()
- void Istest_main ()

7.7.1 Function Documentation

7.7.1.1 void lstest_lspmac_est_move_time ()

Definition at line 14 of file Istest.c.

```
{
int err:
double move_time;
double fudge;
int mmask;
fudge = 2.0;
mmask = 0;
err = lspmac_est_move_time( &move_time, &mmask, omega
    , 0, NULL, 360., NULL);
lslogging_log_message( "lstest_lspmac_est_move_time:
     omega 360 move_time=%f err=%d", move_time, err);
if( lspmac_est_move_time_wait( move_time + fudge,
    mmask)) {
  lslogging_log_message( "lstest_lspmac_est_move_time:
     timed out");
  return;
err = lspmac_est_move_time( &move_time, &mmask, aperz
    , 0, "Cover", 0., NULL);
lslogging_log_message( "lstest_lspmac_est_move_time:
     aperz Cover move_time=%f err=%d", move_time, err);
if ( lspmac est move time wait ( move time + fudge,
    mmask)) {
  lslogging_log_message( "lstest_lspmac_est_move_time:
     timed out");
  return;
err = lspmac_est_move_time( &move_time, &mmask, aperz
    , 0, "In", 0., NULL);
lslogging_log_message( "lstest_lspmac_est_move_time:
    aperz In move_time=%f err=%d", move_time, err);
if ( lspmac est move time wait ( move time + fudge,
    mmask)) {
  lslogging_log_message( "lstest_lspmac_est_move_time:
     timed out");
  return;
err = lspmac_est_move_time( &move_time, &mmask, capz,
    0, "Cover", 0., NULL);
lslogging_log_message( "lstest_lspmac_est_move_time:
     capz Cover move_time=%f err=%d", move_time, err);
if ( lspmac_est_move_time_wait ( move_time + fudge,
    mmask)) {
  lslogging_log_message( "lstest_lspmac_est_move_time:
     timed out");
err = lspmac_est_move_time( &move_time, &mmask, capz,
        "In", 0., NULL);
```

```
lslogging_log_message( "lstest_lspmac_est_move_time:
                        move_time=%f err=%d", move_time, err);
   if( lspmac_est_move_time_wait( move_time + fudge,
        mmask)) {
     lslogging_log_message( "lstest_lspmac_est_move_time:
         timed out");
   err = lspmac_est_move_time( &move_time, &mmask, apery
   , 0, "In", 0.0, aperz, 0, "In", 0.0, capz, 0, "In", 0.0, capz, 0, "In", 0.0, scint, 0, "Scintillator", 0.0, NULL); lslogging_log_message( "lstest_lspmac_est_move_time:
         apery In aperz In capy In capz In scint Scintillator move_time=%f err=%d",
        move_time, err);
   if( lspmac_est_move_time_wait( move_time + fudge,
        mmask)) {
     lslogging_log_message( "lstest_lspmac_est_move_time:
         timed out");
     return;
  err = lspmac_est_move_time( &move_time, &mmask, apery , 0, "In", 0.0, aperz, 0, "Cover", 0.0, capy, 0, "In", 0.0, capz, 0 , "Cover", 0.0, scint, 0, "Cover", 0.0, NULL);
   lslogging_log_message( "lstest_lspmac_est_move_time:
         apery Cover aperz Cover capy Cover capz Cover scint Cover move_time=%f err=%d",
        move_time, err);
   if( lspmac_est_move_time_wait( move_time + fudge,
        mmask)) {
     lslogging_log_message( "lstest_lspmac_est_move_time:
         timed out");
   err = lspmac_est_move_time( &move_time, &mmask, apery
        , 1, "In", 0.0, aperz, 1, "In", 0.0, capy, 1, "In", 0.0, capz, 1, "In", 0.0, scint, 1, "Scintillator", 0.0, omega, 0, "manualMount", 0.0, kappa, 0,
  "manualMount", 0.0, NULL);

lslogging_log_message( "lstest_lspmac_est_move_time:
    apery In aperz In capy In capz In scint Scintillator omega manualMount kappa
    Manualmount move_time=%f err=%d", move_time, err);
   if( lspmac_est_move_time_wait( move_time + fudge,
        mmask)) {
     lslogging_log_message( "lstest_lspmac_est_move_time:
        timed out");
     return;
}
7.7.1.2 void lstest_main ( )
```

Definition at line 92 of file Istest.c.

```
lstest_lspmac_est_move_time();
```

Istimer.c File Reference

Support for delayed and periodic events.

```
#include "pgpmac.h"
```

Data Structures

· struct Istimer list struct

Everything we need to know about a timer.

7.8 Istimer.c File Reference 229

Macros

• #define LSTIMER_LIST_LENGTH 1024

We'll allow this many timers. This should be way more than enough.

• #define LSTIMER_RESOLUTION_NSECS 100000

times within this amount in the future are considered "now" and the events should be called

Typedefs

typedef struct lstimer_list_struct lstimer_list_t

Everything we need to know about a timer.

Functions

• void Istimer add timer (char *event, int shots, unsigned long int secs, unsigned long int nsecs)

Create a timer.

• static void service_timers ()

Send events that are past due, due, or just about to be due.

• static void handler (int sig, siginfo_t *si, void *dummy)

Service the signal.

static void * Istimer_worker (void *dummy)

Our worker.

void lstimer_init ()

Initialize the timer list and pthread stuff.

• void lstimer_run ()

Start up our thread.

Variables

• static int Istimer active timers = 0

count of the number timers we are tracking

· static Istimer list t Istimer list [LSTIMER LIST LENGTH]

Our timer list.

· static pthread_t lstimer_thread

the timer thread

• static pthread_mutex_t lstimer_mutex

protect the timer list

· static pthread_cond_t lstimer_cond

allows us to be idle when there is nothing to do

· static timer_t lstimer_timerid

our real time timer

• static int new_timer = 0

indicate that a new timer exists and a call to service_timers is required

7.8.1 Detailed Description

Support for delayed and periodic events.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file Istimer.c.

7.8.2 Macro Definition Documentation

7.8.2.1 #define LSTIMER_LIST_LENGTH 1024

We'll allow this many timers. This should be way more than enough.

Definition at line 11 of file Istimer.c.

7.8.2.2 #define LSTIMER_RESOLUTION_NSECS 100000

times within this amount in the future are considered "now" and the events should be called Definition at line 16 of file Istimer.c.

7.8.3 Typedef Documentation

7.8.3.1 typedef struct lstimer_list_struct lstimer_list_t

Everything we need to know about a timer.

7.8.4 Function Documentation

```
7.8.4.1 static void handler ( int sig, siginfo_t * si, void * dummy ) [static]
```

Service the signal.

Definition at line 174 of file Istimer.c.

```
pthread_mutex_lock( &lstimer_mutex);
service_timers();
pthread_mutex_unlock( &lstimer_mutex);
```

7.8.4.2 void lstimer_add_timer (char * event, int shots, unsigned long int secs, unsigned long int nsecs)

Create a timer.

Parameters

event	event Name of the event to send when the timer goes off	
shots	Number of times to run. 0 means never, -1 means forever	
secs	Number of seconds to wait	
nsecs	Number of nano-seconds to run in addition to secs	

Definition at line 50 of file Istimer.c.

```
{
int i;
struct timespec now;
// Time we were called. Delay is based on call time, not queued time
clock_gettime( CLOCK_REALTIME, &now);
pthread_mutex_lock( &lstimer_mutex);
for( i=0; i<LSTIMER_LIST_LENGTH; i++) {</pre>
 if( lstimer_list[i].shots == 0)
   break;
if( i == LSTIMER_LIST_LENGTH) {
 pthread_mutex_unlock( &lstimer_mutex);
  lslogging_log_message( "lstimer_add_timer: out of
     timers for event: %s, shots: %d, secs: %u, nsecs: %u",
                          event, shots, secs, nsecs);
  return;
strncpy( lstimer_list[i].event, event, LSEVENTS_EVENT_LENGTH
       1);
lstimer_list[i].event[LSEVENTS_EVENT_LENGTH
- 1] = 0;
lstimer_list[i].shots = shots
lstimer_list[i].delay_secs = secs;
                               = shots:
lstimer_list[i].delay_nsecs = nsecs;
lstimer_list[i].next_secs
                               = secs + now.tv_sec + (
    now.tv_nsec + nsecs) / 1000000000;
lstimer_list[i].next_nsecs = (now.tv_nsec + nsecs
    ) % 1000000000;
lstimer_list[i].last_secs = 0;
lstimer_list[i].last_nsecs = 0;
lstimer_list[i].ncalls = 0;
lstimer_list[i].init_secs = now.tv_sec;
lstimer_list[i].init_nsecs = now.tv_nsec;
if( shots != 0) {
  lstimer_active_timers++;
  new_timer++;
pthread_cond_signal( &lstimer_cond);
pthread_mutex_unlock( &lstimer_mutex);
```

7.8.4.3 void Istimer_init ()

Initialize the timer list and pthread stuff.

Definition at line 254 of file Istimer.c.

```
int i;
```

```
for( i=0; i<LSTIMER_LIST_LENGTH; i++) {
   lstimer_list[i].shots = 0;
}

pthread_mutex_init( &lstimer_mutex, NULL);
pthread_cond_init( &lstimer_cond, NULL);</pre>
```

7.8.4.4 void lstimer_run ()

Start up our thread.

Definition at line 268 of file Istimer.c.

```
pthread_create( &lstimer_thread, NULL, lstimer_worker
    , NULL);
}
```

```
7.8.4.5 static void* lstimer_worker ( void * dummy ) [static]
```

Our worker.

The main loop runs when a new timer is added. The service routine deals with maintenance.

Parameters

in	dummy	required by protocol
----	-------	----------------------

Definition at line 184 of file Istimer.c.

```
struct sigevent sev:
struct sigaction sa;
sigset_t mask;
// See example at
     http://www.kernel.org/doc/man-pages/online/pages/man2/timer_create.2.html
// Set up hander
sa.sa_flags = SA_SIGINFO;
sa.sa_sigaction = handler;
sigemptyset(&sa.sa_mask);
if (sigaction(SIGRTMIN, &sa, NULL) == -1) {
   lslogging_log_message( "lstimer_worker: sigaction
     failed");
  exit(-1);
// Create the timer
sev.sigev_notify = SIGEV_SIGNAL;
sev.sigev_signo = SIGRTMIN;
sev.sigev_value.sival_ptr = &lstimer_timerid;
timer_create( CLOCK_REALTIME, &sev, &lstimer_timerid);
// Block timer signal for now since we really
\ensuremath{//} want to be sure we do not own a lock on the timer mutex
// while servicing the signal
sigemptyset ( &mask);
sigaddset( &mask, SIGRTMIN);
while(1) {
  pthread_mutex_lock( &lstimer_mutex);
  while( new_timer == 0)
    pthread_cond_wait( &lstimer_cond, &lstimer_mutex
```

```
// ignore signals so we don't service the signal while we are already in
    the
// service routine
//
sigprocmask( SIG_SETMASK, &mask, NULL);

//
// Setting up the timer interval is in the handler
// so just call it
//
service_timers();

//
// Reset our flag
//
new_timer = 0;
pthread_mutex_unlock( &lstimer_mutex);

// Let the signals rain down
//
sigprocmask( SIG_UNBLOCK, &mask, NULL);
}
```

7.8.4.6 static void service_timers() [static]

Send events that are past due, due, or just about to be due.

Definition at line 102 of file Istimer.c.

```
int
  found_active;
lstimer_list_t *p;
struct timespec now, then, soonest; struct itimerspec its;
^{\prime\prime} Did I remind you not to let this thread own the 1stimer mutex outside of
// service routine when SIGRTMIN is active?
// Call with lstimer_mutex locked
clock_gettime( CLOCK_REALTIME, &now);
//
// Project a tad into the future
then.tv_sec = now.tv_sec + (now.tv_nsec + LSTIMER_RESOLUTION_NSECS ) / 1000000000;
then.tv_nsec = (now.tv_nsec + LSTIMER_RESOLUTION_NSECS
    ) % 1000000000;
found_active = 0;
for( i=0; i<lstimer_active_timers; i++) {
  p = &(lstimer_list[i]);</pre>
  if ( p->shots != 0) {
    found_active++;
     if( p->next_secs < then.tv_sec || (p->next_secs ==
    then.tv_sec && p->next_nsecs <= then.tv_nsec)) {
  lsevents_send_event( p->event);
       // After sending the event, compute the next time we need to do this
       p->last_secs = now.tv_sec;
p->last_nsecs = now.tv_nsec;
       p->ncalls++;
       // Decrement non-infinite loops
       if( p->shots != -1)
         p->shots--;
       if(p\rightarrow shots == 0) {
         // Take this timer out of the mix
         lstimer_active_timers--;
       } else {
```

```
p->next_secs = p->init_secs + (p->ncalls+1)
* p->delay_secs + (p->init_nsecs + (p->ncalls+1)*p->
       delay_nsecs)/1000000000;
           p->next_nsecs = (p->init_nsecs + (p->ncalls
       +1)*p->delay_nsecs) % 1000000000;
       if( found_active == 1) {
         soonest.tv_sec = p->next_secs;
         soonest.tv_nsec = p->next_nsecs;
       } else {
          if( soonest.tv_sec > p->next_secs || (soonest.tv_sec == p->
       next_secs && soonest.tv_nsec > p->next_nsecs)) {
            soonest.tv_sec = p->next_secs;
soonest.tv_nsec = p->next_nsecs;
       }
  if( soonest.tv_sec != 0) {
    its.it_value.tv_sec = soonest.tv_sec;
its.it_value.tv_nsec = soonest.tv_nsec;
its.it_interval.tv_sec = 0;
     its.it_interval.tv_nsec = 0;
     timer_settime( lstimer_timerid, TIMER_ABSTIME, &its, NULL);
7.8.5 Variable Documentation
```

```
7.8.5.1 int lstimer_active_timers = 0 [static]
```

count of the number timers we are tracking

Definition at line 18 of file Istimer.c.

```
7.8.5.2 pthread_cond_t lstimer_cond [static]
```

allows us to be idle when there is nothing to do

Definition at line 40 of file Istimer.c.

```
7.8.5.3 Istimer_list_t | Istimer_list[LSTIMER_LIST_LENGTH] [static]
```

Our timer list.

Definition at line 36 of file Istimer.c.

```
7.8.5.4 pthread_mutex_t lstimer_mutex [static]
```

protect the timer list

Definition at line 39 of file Istimer.c.

```
7.8.5.5 pthread_t lstimer_thread [static]
```

the timer thread

Definition at line 38 of file Istimer.c.

```
7.8.5.6 timer_t lstimer_timerid [static]
```

our real time timer

Definition at line 41 of file Istimer.c.

```
7.8.5.7 int new_timer = 0 [static]
```

indicate that a new timer exists and a call to service_timers is required

Definition at line 42 of file Istimer.c.

7.9 md2cmds.c File Reference

Implements commands to run the md2 diffractometer attached to a PMAC controled by postgresql.

```
#include "pgpmac.h"
```

Data Structures

· struct md2cmds_cmd_kv_struct

Typedefs

 typedef struct md2cmds_cmd_kv_struct md2cmds_cmd_kv_t

Functions

int md2cmds_abort (const char *dummy)

abort the current motion and put the system into a known state /param dummy Unused here

• int md2cmds_center (const char *dummy)

Move centering and alignment tables as requested TODO: Implement.

int md2cmds_collect (const char *dummy)

Collect some data.

• int md2cmds moveAbs (const char *ccmd)

Move a motor to the position requested Returns non zero on error.

int md2cmds_moveRel (const char *ccmd)

Move a motor to the position requested Returns non zero on error.

• int md2cmds_phase_change (const char *ccmd)

Move md2 devices to a preconfigured state.

- int md2cmds_run_cmd (const char *)
- int md2cmds_rotate (const char *dummy)

Spin 360 and make a video (recenter first, maybe)

- int md2cmds set (const char *)
- int md2cmds_test (const char *dummy)

Run the test routine(s)

• int md2cmds_transfer (const char *dummy)

Transfer a sample.

- void md2cmds_home_prep ()
- int md2cmds_home_wait (double timeout_secs)
- void md2cmds_move_prep ()

prepare for new movements

int md2cmds_move_wait (double timeout_secs)

Wait for all the motions requested to complete.

• int md2cmds_is_moving ()

returns non-zero if we think a motor is moving, 0 otherwise

- double md2cmds_prep_axis (lspmac_motor_t *mp, double pos)
- void md2cmds_organs_move_presets (char *pay, char *paz, char *pcy, char *pcz, char *psz)
- int md2cmds phase manualMount ()

Go to the manual mount phase.

int md2cmds phase robotMount ()

Go to robot mount phase.

• int md2cmds_phase_center ()

Go to center phase.

int md2cmds_phase_dataCollection ()

Go to data collection phase.

• int md2cmds phase beamLocation ()

Go to beam location phase.

• int md2cmds phase safe ()

Go to safe phase.

• void md2cmds_mvcenter_move (double cx, double cy, double ax, double ay, double az)

Move the centering and alignment tables.

void md2cmds_maybe_done_moving_cb (char *event)

Track how many motors are moving.

void md2cmds_maybe_done_homing_cb (char *event)

Track motors homing.

- void md2cmds_kappaphi_move (double kappa_deg, double phi_deg)
- void md2cmds_rotate_cb (char *event)

Tell the database about the time we went through omega=zero.

• void md2cmds_maybe_rotate_done_cb (char *event)

Now that we are done with the 360 rotation lets rehome right quick.

void md2cmds_set_scale_cb (char *event)

Fix up xscale and yscale when zoom changes.

• void md2cmds_time_capz_cb (char *event)

Time the capillary motion for the transfer routine.

- int md2cmds_action_queue (double timeout, char *action)
- void md2cmds_action_wait ()

pause until md2cmds_worker has finished running the command

void * md2cmds_worker (void *dummy)

Our worker thread.

- void md2cmds_coordsys_1_stopped_cb (char *event)
- void md2cmds_coordsys_2_stopped_cb (char *event)
- void md2cmds_coordsys_3_stopped_cb (char *event)
- void md2cmds_coordsys_4_stopped_cb (char *event)
- void md2cmds_coordsys_5_stopped_cb (char *event)
- void md2cmds_coordsys_7_stopped_cb (char *event)
- void md2cmds_init ()

Initialize the md2cmds module.

• void md2cmds run ()

Start up the thread.

Variables

```
• pthread_cond_t md2cmds_cond
```

condition to signal when it's time to run an md2 command

pthread_mutex_t md2cmds_mutex

mutex for the condition

- int md2cmds_moving_queue_wait = 0
- pthread_cond_t md2cmds_moving_cond

wait for command to have been dequeued and run

pthread_mutex_t md2cmds_moving_mutex

message passing between md2cmds and pg

• int md2cmds_homing_count = 0

We've asked a motor to home.

· pthread cond t md2cmds homing cond

coordinate homing and homed

pthread_mutex_t md2cmds_homing_mutex

our mutex;

- int md2cmds moving count = 0
- char md2cmds_cmd [MD2CMDS_CMD_LENGTH]

our command;

- Isredis_obj_t * md2cmds_md_status_code
- static pthread_t md2cmds_thread
- static int rotating = 0

flag: when omega is in position after a rotate we want to re-home omega

- static double md2cmds_capz_moving_time = NAN
- static struct hsearch_data md2cmds_hmap
- static regex_t md2cmds_cmd_regex
- static md2cmds_cmd_kv_t md2cmds_cmd_kvs []

7.9.1 Detailed Description

Implements commands to run the md2 diffractometer attached to a PMAC controled by postgresql.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file md2cmds.c.

7.9.2 Typedef Documentation

7.9.2.1 typedef struct md2cmds_cmd_kv_struct md2cmds_cmd_kv_t

7.9.3 Function Documentation

7.9.3.1 int md2cmds_abort (const char * dummy)

abort the current motion and put the system into a known state /param dummy Unused here Definition at line 1653 of file md2cmds.c.

7.9.3.2 int md2cmds_action_queue (double timeout, char * action)

Definition at line 1615 of file md2cmds.c.

```
int rtn;
struct timespec waitforit;
if( timeout < 0.0) {</pre>
 rtn = pthread_mutex_lock( &md2cmds_mutex);
  clock_gettime( CLOCK_REALTIME, &waitforit);
  waitforit.tv_sec += floor(timeout);
  waitforit.tv_nsec += (timeout - waitforit.tv_sec) *1.e9;
  while( waitforit.tv_nsec >= 1000000000) {
    waitforit.tv sec++;
    waitforit.tv_nsec -= 1000000000;
  rtn = pthread_mutex_timedlock( &md2cmds_mutex, &waitforit);
if( rtn == 0) {
  strncpy( md2cmds_cmd, action, MD2CMDS_CMD_LENGTH
  md2cmds_cmd[MD2CMDS_CMD_LENGTH-1] = 0;
  pthread_cond_signal( &md2cmds_cond);
 pthread_mutex_unlock( &md2cmds_mutex);
 else {
  if( rtn == ETIMEDOUT)
```

```
lslogging_log_message( "md2cmds_action_queue: %s not
    queued, operation timed out", action);
else
    lslogging_log_message( "md2cmds_action_queue: %s not
    queued with error code %d", action, rtn);
}
return rtn;
}
```

7.9.3.3 void md2cmds_action_wait ()

pause until md2cmds_worker has finished running the command

Definition at line 1683 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_mutex);
pthread_mutex_unlock( &md2cmds_mutex);
}
```

7.9.3.4 int md2cmds_center (const char * dummy)

Move centering and alignment tables as requested TODO: Implement.

Definition at line 1578 of file md2cmds.c.

```
return 0;
}
```

7.9.3.5 int md2cmds_collect (const char * dummy)

Collect some data.

Parameters

dummy | Unused returns non-zero on error

- < index of shot to be taken
- < Exposure time (saved to compute shutter timeout)
- < start cnts
- < delta cnts
- < omega velocity cnts/msec
- < acceleration time (msec)
- < exposure time (msec)
- < unit to counts conversion
- < nominal zero offset
- < maximum acceleration allowed for omega
- < current kappa position in case we need to move phi only
- < current phi position in case we need to move kappa only
- < setup timeouts for shutter

Definition at line 1114 of file md2cmds.c.

```
long long skey;
double exp_time;
double p170;
double p171;
double p173;
double p175;
double p180;
double u2c;
double neutral_pos;
double max_accel;
double kappa_pos;
double phi_pos;
struct timespec now, timeout;
int err;
u2c = lsredis_getd( omega->u2c);
neutral_pos = lsredis_getd( omega->neutral_pos);
max_accel = lsredis_getd( omega->max_accel);
md2cmds_move_prep();
md2cmds_organs_move_presets( "In", "In", "In", "In
    ", "Cover");
if ( md2cmds_move_wait ( 30.0)) {
  lslogging_log_message( "md2cmds_collect: Timed out
waiting for organs to move. Aborting data collection.");
  lsevents_send_event( "Data Colection Aborted");
  return 1;
// reset shutter has opened flag
lspmac_SockSendDPline( NULL, "P3001=0 P3002=0");
while(1) {
  lspg_nextshot_call();
  lspg_nextshot_wait();
  exp_time = lspg_nextshot.dsexp;
  if( lspg_nextshot.no_rows_returned) {
    lspg_nextshot_done();
    break;
  skey = lspg_nextshot.skey;
lspg_query_push( NULL, "SELECT px.shots_set_state(%1ld,
    'Preparing')", skey);
  if( lspg_nextshot.active) {
        // Don't move if we are within 0.1 microns of our destination
        (fabs( lspg_nextshot.cx - cenx->position) >
        (fabs( lspg_nextshot.cy - ceny->position) >
     0.1) ||
        (fabs( lspg_nextshot.ax - alignx->position
    ) > 0.1) ||
        (fabs( lspg_nextshot.ay - aligny->position
      > 0.1) ||
        (fabs( lspg_nextshot.az - alignz->position
    ) > 0.1)) {
      lslogging_log_message( "md2cmds_collect: moving
     center to cx=%f, cy=%f, ax=%f, ay=%f, az=%f",lspg_nextshot.cx,
    lspg_nextshot.cy, lspg_nextshot.ax, lspg_nextshot
    .ay, lspg_nextshot.az);
      md2cmds_move_prep();
      md2cmds_mvcenter_move( lspq_nextshot.
    cx, lspg_nextshot.cy, lspg_nextshot.ax,
    lspg_nextshot.ay, lspg_nextshot.az);
       if ( md2cmds_move_wait ( 2.0)) {
         lslogging_log_message( "md2cmds_collect: Timed
     out waiting for alignment or centering stage (or both) to stop moving. Aborting data collection.");
        lsevents_send_event( "Data Colection Aborted");
         return 1;
    }
  }
  // Maybe move kappa and/or phi
```

```
if( !lspg_nextshot.dsphi_isnull || !lspg_nextshot
  .dskappa_isnull) {
  kappa_pos = lspg_nextshot.dskappa_isnull ?
lspmac_getPosition( kappa) : lspg_nextshot.
             = lspg_nextshot.dsphi_isnull
  phi_pos
  lspmac_getPosition( phi) : lspg_nextshot.
  dsphi;
  lslogging_log_message( "md2cmds_collect: move
  phy/kappa: kappa=%f phi=%f", kappa_pos, phi_pos);
  md2cmds_move_prep();
  md2cmds_kappaphi_move( kappa_pos, phi_pos);
  if( md2cmds_move_wait( 30.0)) {
    lslogging_log_message( "md2cmds_collect: Timed
   out waiting for kappa or phi (or both) to stop moving. Aborting data collection.
  ");
       lsevents_send_event( "Data Colection Aborted");
  }
}
// Calculate the parameters we'll need to run the scan
p180 = lspg_nextshot.dsexp * 1000.0;
p170 = u2c * (lspg_nextshot.sstart + neutral_pos);
p171 = u2c * lspg_nextshot.dsowidth;
p173 = fabs(p180) < 1.e-4 ? 0.0 : u2c * lspg_nextshot.dsowidth
   / p180;
p175 = p173/max_accel;
// free up access to nextshot
lspg_nextshot_done();
// prepare the database and detector to expose
// On exit we own the diffractometer lock and
// have checked that all is OK with the detector
lspg_seq_run_prep_all( skey,
                           kappa->position,
                           phi->position.
                           cenx->position.
                           ceny->position,
                           alignx->position,
                           aligny->position,
                           alignz->position
                           );
// make sure our opened flag is down
// wait for the p3001=0 command to be noticed
clock_gettime( CLOCK_REALTIME, &now);
timeout.tv_sec = now.tv_sec + 10;
timeout.tv_nsec = now.tv_nsec;
err = 0;
pthread_mutex_lock( &lspmac_shutter_mutex);
while( err == 0 && lspmac_shutter_has_opened == 1)
  err = pthread_cond_timedwait( &lspmac_shutter_cond, &
  lspmac_shutter_mutex, &timeout);
pthread_mutex_unlock( &lspmac_shutter_mutex);
if( err == ETIMEDOUT) {
  pthread_mutex_unlock( &lspmac_shutter_mutex);
  lslogging_log_message( "md2cmds_collect: Timed out
   waiting for shutter to open. Data collection aborted.");
  lsevents_send_event( "Data Collection Aborted");
  return 1;
// Start the exposure
md2cmds_move_prep();
lspmac_SockSendDPline( "Exposure", "&1 P170=%.1f
P171=%.1f P173=%.1f P174=0 P175=%.1f P176=0 P177=1 P178=0 P180=%.1f M431=1 &1B131R",
                                                  p171,
                                      p170,
                                                             p173,
```

```
p180);
// We could look for the "Exposure command accepted" event at this point.
// wait for the shutter to open
clock_gettime( CLOCK_REALTIME, &now);
timeout.tv_sec = now.tv_sec + 10;
timeout.tv_nsec = now.tv_nsec;
pthread_mutex_lock( &lspmac_shutter_mutex);
while( err == 0 && lspmac_shutter_has_opened == 0)
  err = pthread_cond_timedwait( &lspmac_shutter_cond, &
  lspmac_shutter_mutex, &timeout);
if( err == ETIMEDOUT) {
 pthread_mutex_unlock( &lspmac_shutter_mutex);
  lslogging_log_message( "md2cmds_collect: Timed out
 waiting for shutter to open. Data collection aborted.");
lsevents_send_event( "Data Collection Aborted");
 return 1;
// wait for the shutter to close
clock_gettime( CLOCK_REALTIME, &now);
timeout.tv_sec = now.tv_sec + 4 + exp_time;
                                                    // hopefully 4 seconds
   is long enough to never catch a legitimate shutter close and short enough to
   bail when something is really wrong
timeout.tv_nsec = now.tv_nsec;
err = 0;
while( err == 0 && lspmac_shutter_state == 1)
 err = pthread_cond_timedwait( &lspmac_shutter_cond, &
  lspmac_shutter_mutex, &timeout);
pthread_mutex_unlock( &lspmac_shutter_mutex);
if( err == ETIMEDOUT) {
 pthread_mutex_unlock( &lspmac_shutter_mutex);
  lslogging_log_message( "md2cmds_collect: Timed out
   waiting for shutter to close. Data collection aborted.");
  lsevents_send_event( "Data Collection Aborted");
 return 1:
// Signal the detector to start reading out
lspg_query_push( NULL, "SELECT px.unlock_diffractometer()");
// Update the shot status
lspg_query_push( NULL, "SELECT px.shots_set_state(%11d,
   'Writing')", skey);
// reset shutter has opened flag
lspmac_SockSendDPline( NULL, "P3001=0");
//
// Wait for omega to stop moving
if( md2cmds_move_wait( 10.0)) {
 lslogging_log_message( "md2cmds_collect: Giving up
  waiting for omega to stop moving. Data collection aborted.");
lsevents_send_event( "Data Colection Aborted");
 return 1;
// Move the center/alignment stages to the next position
// TODO: position omega for the next shot. During data collection the
   motion program
// makes a good guess but for ortho snaps it is wrong. We should add an
  argument to the motion program
```

```
if( !lspg_nextshot.active2_isnull &&
       lspg_nextshot.active2) {
          (fabs( lspg_nextshot.cx2 - cenx->position)
          (fabs( lspg_nextshot.cy2 - ceny->position)
          (fabs( lspg_nextshot.ax2 - alignx->position
       ) > 0.1) ||
          (fabs( lspg_nextshot.ay2 - aligny->position
       ) > 0.1) ||
          (fabs( lspg_nextshot.az2 - alignz->position
         md2cmds_move_prep();
      md2cmds_mvcenter_move( lspg_nextshot.cx, lspg_nextshot.cy, lspg_nextshot.ax, lspg_nextshot.ay, lspg_nextshot.az);
    }
  lsevents_send_event( "Data Collection Done");
  return 0;
7.9.3.6 void md2cmds_coordsys_1_stopped_cb ( char * event )
Definition at line 1868 of file md2cmds.c.
}
7.9.3.7 void md2cmds_coordsys_2_stopped_cb ( char * event )
Definition at line 1870 of file md2cmds.c.
7.9.3.8 void md2cmds_coordsys_3_stopped_cb ( char * event )
Definition at line 1872 of file md2cmds.c.
}
7.9.3.9 void md2cmds_coordsys_4_stopped_cb ( char * event )
Definition at line 1874 of file md2cmds.c.
}
7.9.3.10 void md2cmds_coordsys_5_stopped_cb ( char * event )
Definition at line 1876 of file md2cmds.c.
}
```

7.9.3.11 void md2cmds_coordsys_7_stopped_cb (char * event)

Definition at line 1878 of file md2cmds.c.

```
}
```

7.9.3.12 void md2cmds_home_prep ()

Definition at line 70 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_homing_mutex);
md2cmds_homing_count = -1;
pthread_mutex_unlock( &md2cmds_homing_mutex);
}
```

7.9.3.13 int md2cmds_home_wait (double timeout_secs)

Definition at line 77 of file md2cmds.c.

```
{
struct timespec timeout, now;
double isecs, fsecs;
clock_gettime( CLOCK_REALTIME, &now);
fsecs = modf( timeout secs, &isecs);
timeout.tv_sec = now.tv_sec + (long)floor(isecs);
timeout.tv_nsec = now.tv_nsec + (long)floor( fsecs * 1.0e9);
timeout.tv_sec += timeout.tv_nsec / 1000000000;
timeout.tv_nsec %= 1000000000;
pthread_mutex_lock( &md2cmds_homing_mutex);
while( err == 0 && md2cmds_homing_count == -1)
  err = pthread_cond_timedwait( &md2cmds_homing_cond, &
    md2cmds_homing_mutex, &timeout);
if( err != 0) {
  if( err != ETIMEDOUT) {
   lslogging_log_message( "md2cmds_home_wait:
    unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
 pthread_mutex_unlock( &md2cmds_homing_mutex);
while( err == 0 && md2cmds_homing_count > 0)
 err = pthread_cond_timedwait( &md2cmds_homing_cond, &
    md2cmds_homing_mutex, &timeout);
pthread_mutex_unlock( &md2cmds_homing_mutex);
if( err != 0) {
  if( err != ETIMEDOUT)
    lslogging_log_message( "md2cmds_home_wait:
    unexpected error from timedwait: %d", err);
  return 1;
return 0;
```

7.9.3.14 void md2cmds_init ()

Initialize the md2cmds module.

Definition at line 1884 of file md2cmds.c.

```
ENTRY hloader, *hrtnval;
int i, err;
pthread mutexattr t mutex initializer;
pthread_mutexattr_init( &mutex_initializer);
\verb|pthread_mutexattr_settype(&mutex_initializer, PTHREAD_MUTEX_RECURSIVE);|
pthread_mutex_init( &md2cmds_mutex, &mutex_initializer);
pthread_cond_init( &md2cmds_cond, NULL);
pthread_mutex_init( &md2cmds_moving_mutex, &
    mutex_initializer);
pthread_cond_init( &md2cmds_moving_cond, NULL);
pthread_mutex_init( &md2cmds_homing_mutex, &
    mutex_initializer);
pthread_cond_init( &md2cmds_homing_cond, NULL);
err = regcomp( &md2cmds_cmd_regex, " *([^ ]+) (([^ ]+)\\ .presets\\..)*([^ ]*) *([^ ]*)", REG_EXTENDED); if( err != 0) {
  int nerrmsg;
  char *errmsg;
  nerrmsg = regerror( err, &md2cmds_cmd_regex, NULL, 0);
  if( nerrmsg > 0) {
    errmsg = calloc( nerrmsg, sizeof( char));
    nerrmsg = regerror( err, &md2cmds_cmd_regex, errmsg,
    nerrmsq);
    lslogging_log_message( "md2cmds_init: %s", errmsg);
    free( errmsg);
md2cmds_md_status_code = lsredis_get_obj
     ( "md2_status_code");
lsredis_setstr( md2cmds_md_status_code, "
hcreate_r( 2 * sizeof(md2cmds_cmd_kvs)/sizeof(md2cmds_cmd_kvs
[0]), &md2cmds_hmap);
for( i=0; i<sizeof(md2cmds_cmd_kvs)/sizeof(md2cmds_cmd_kvs)
     [0]); i++) {
  hloader.key = md2cmds_cmd_kvs[i].k;
hloader.data = md2cmds_cmd_kvs[i].v;
  err = hsearch_r( hloader, ENTER, &hrtnval, &md2cmds_hmap);
  if( err == 0) {
    lslogging_log_message( "md2cmds_init: hsearch_r
     returned an error for item %d: %s", i, strerror( errno));
  }
}
```

7.9.3.15 int md2cmds_is_moving ()

}

returns non-zero if we think a motor is moving, 0 otherwise

Definition at line 176 of file md2cmds.c.

```
int rtn;

pthread_mutex_lock( &md2cmds_moving_mutex);
rtn = md2cmds_moving_count != 0;
pthread_mutex_unlock( &md2cmds_moving_mutex);
return rtn;
}
```

7.9.3.16 void md2cmds_kappaphi_move (double kappa_deg, double phi_deg)

Definition at line 1092 of file md2cmds.c.

7.9.3.17 void md2cmds_maybe_done_homing_cb (char * event)

Track motors homing.

Definition at line 1068 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_homing_mutex);
if( strstr( event, "Homing") == NULL) {
   if( md2cmds_homing_count != -1)
      md2cmds_homing_count = 1;
   else
      md2cmds_homing_count++;
} else {
   if( md2cmds_homing_count > 0)
      md2cmds_homing_count--;
}

if( md2cmds_homing_count != 0)
   lsredis_setstr( md2cmds_md_status_code,
      "%s", "4");

if( md2cmds_homing_count == 0)
   pthread_cond_signal( &md2cmds_homing_cond);

pthread_mutex_unlock( &md2cmds_homing_mutex);
```

7.9.3.18 void md2cmds_maybe_done_moving_cb (char * event)

Track how many motors are moving.

Definition at line 1039 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_moving_mutex);
if( strstr( event, "Moving") != NULL) {
    //
    // -1 is a flag indicating we're expecting some action
    //
    if( md2cmds_moving_count == -1)
        md2cmds_moving_count = 1;
    else
        md2cmds_moving_count++;
} else {
    //
    if( md2cmds_moving_count > 0)
        md2cmds_moving_count--;
}

lsredis_setstr( md2cmds_md_status_code, "
        %s", md2cmds_moving_count ? "4" : "3");

if( md2cmds_moving_count == 0)
    pthread_cond_signal( &md2cmds_moving_cond);
```

```
pthread_mutex_unlock( &md2cmds_moving_mutex);
}
```

7.9.3.19 void md2cmds_maybe_rotate_done_cb (char * event)

Now that we are done with the 360 rotation lets rehome right quick.

Definition at line 1541 of file md2cmds.c.

```
if( rotating) {
  rotating = 0;
   lsevents_send_event( "Rotate Done");
}
```

7.9.3.20 void md2cmds_move_prep ()

prepare for new movements

Definition at line 122 of file md2cmds.c.

```
pthread_mutex_lock( &md2cmds_moving_mutex);
md2cmds_moving_count = -1;
pthread_mutex_unlock( &md2cmds_moving_mutex);
}
```

7.9.3.21 int md2cmds_move_wait (double timeout_secs)

Wait for all the motions requested to complete.

Parameters

```
timeout_secs | Double value of seconds to wait
```

There are two waits involved: First to wait for the first "Moving" to be seen and second to wait for the last "In Position". The timeout specified here is the sum of the two.

returns 0 on success and 1 if we timedout.

Definition at line 139 of file md2cmds.c.

```
return 1;
}

err = 0;
while( err == 0 && md2cmds_moving_count > 0)
    err = pthread_cond_timedwait( &md2cmds_moving_cond, &
        md2cmds_moving_mutex, &timeout);
pthread_mutex_unlock( &md2cmds_moving_mutex);

if( err == ETIMEDOUT)
    return 1;
return 0;
```

7.9.3.22 int md2cmds_moveAbs (const char * ccmd)

Move a motor to the position requested Returns non zero on error.

Parameters

in	ccmd	The full command string to parse, ie, "moveAbs omega 180"
----	------	---

Definition at line 453 of file md2cmds.c.

```
{
char *cmd;
char *ignore;
char *ptr;
char *mtr;
char *pos;
double fpos;
char *endptr;
lspmac_motor_t *mp;
int err;
// ignore nothing
if( ccmd == NULL || *ccmd == 0) {
 return 1;
// operate on a copy of the string since strtok_r will modify its argument
cmd = strdup( ccmd);
// Parse the command string
ignore = strtok_r( cmd, " ", &ptr);
if ( ignore == NULL) {
 lslogging_log_message( "md2cmds_moveAbs: ignoring
blank command '%s'", cmd);
  free( cmd);
 return 1;
// The first string should be "moveAbs" cause that's how we got here.
// Toss it.
mtr = strtok_r( NULL, " ", &ptr);
if ( mtr == NULL) {
 lslogging_log_message( "md2cmds_moveAbs: missing motor
     name");
  free ( cmd);
 return 1;
mp = lspmac_find_motor_by_name( mtr);
if ( mp == NULL) {
 lslogging_log_message( "md2cmds_moveAbs: cannot find
  motor %s", mtr);
  free( cmd);
  return 1;
pos = strtok_r( NULL, " ", &ptr);
if ( pos == NULL) {
 lslogging_log_message( "md2cmds_moveAbs: missing
    position");
  free ( cmd);
  return 1;
```

```
fpos = strtod( pos, &endptr);
if( pos == endptr) {
    //
    // Maybe we have a preset. Give it a whirl
    // In any case we are done here.
    //
    err = lspmac_move_preset_queue( mp, pos);
    free( cmd);
    return err;
}

if( mp != NULL && mp->moveAbs != NULL) {
    wprintw( term_output, "Moving %s to %f\n", mtr, fpos);
    wnoutrefresh( term_output);
    err = mp->moveAbs( mp, fpos);
}

free( cmd);
return err;
```

7.9.3.23 int md2cmds_moveRel (const char * ccmd)

Move a motor to the position requested Returns non zero on error.

Parameters

in	ccmd	The full command string to parse, ie, "moveAbs omega 180"
----	------	---

Definition at line 532 of file md2cmds.c.

```
{
char *cmd;
char *ignore;
char *ptr;
char *mtr;
char *pos;
double fpos;
char *endptr;
lspmac_motor_t *mp;
int err;
// ignore nothing
if( ccmd == NULL || *ccmd == 0) {
 return 1;
// operate on a copy of the string since strtok_r will modify its argument
cmd = strdup( ccmd);
// Parse the command string
ignore = strtok_r( cmd, " ", &ptr);
if( ignore == NULL) {
 lslogging_log_message( "md2cmds_moveAbs: ignoring
blank command '%s'", cmd);
  free( cmd);
  return 1;
// The first string should be "moveAbs" cause that's how we got here.
// Toss it.
mtr = strtok_r( NULL, " ", &ptr);
if ( mtr == NULL) {
  lslogging_log_message( "md2cmds_moveRel: missing motor
    name");
  free ( cmd);
  return 1;
mp = lspmac_find_motor_by_name( mtr);
if ( mp == NULL) {
  lslogging_log_message( "md2cmds_moveRel: cannot find
     motor %s", mtr);
```

```
free ( cmd);
  return 1;
pos = strtok_r( NULL, " ", &ptr);
if ( pos == NULL) {
 lslogging_log_message( "md2cmds_moveRel: missing
     position");
  free( cmd);
  return 1;
fpos = strtod( pos, &endptr);
if ( pos == endptr) {
  \ensuremath{//} No incrementnal position found
  //
Islogging_log_message( "md2cmds_moveRel: no new
   position requested");
  return 1;
if( mp != NULL && mp->moveAbs != NULL) {
  wprintw( term_output, "Moving %s by %f\n", mtr, fpos);
  wnoutrefresh( term_output);
  err = mp->moveAbs( mp, lspmac_getPosition(mp) +
free ( cmd);
return err:
```

7.9.3.24 void md2cmds_mvcenter_move (double cx, double cy, double ax, double ay, double az)

Move the centering and alignment tables.

Parameters

in	СХ	Requested Centering Table X
in	су	Requested Centering Table Y
in	ax	Requested Alignment Table X
in	ay	Requested Alignment Table Y
in	az	Requested Alignment Table Z

Definition at line 1012 of file md2cmds.c.

7.9.3.25 void md2cmds_organs_move_presets (char * pay, char * pay, char * pcy, char * pcz, char * psz)

Definition at line 209 of file md2cmds.c.

```
{
double ay, az, cy, cz, sz;
int cay, caz, ccy, ccz, csz;
int err;
err = lsredis_find_preset( apery->name, pay, &ay)
if( err == 0) {
  lslogging_log_message( "md2cmds_move_organs_presets:
   no preset '%s' for motor '%s'", pay, apery->name);
   return:
err = lsredis_find_preset( aperz->name, paz, &az)
if( err == 0) {
   lslogging_log_message( "md2cmds_move_organs_presets:
   no preset '%s' for motor '%s'", paz, aperz->name);
   return;
err = lsredis_find_preset( capy->name, pcy, &cy);
if( err == 0) {
  lslogging_log_message( "md2cmds_organs_move_presets:
   no preset '%s' for motor '%s'", pcy, capy->name);
err = lsredis_find_preset( capz->name, pcz, &cz);
if( err == 0) {
  l( eff -- 0, {
   lslogging_log_message( "md2cmds_organs_move_presets:
      no preset '%s' for motor '%s'", pcz, capz->name);
err = lsredis_find_preset( scint->name, psz, &sz)
if( err == 0) {
  lslogging_log_message( "md2cmds_organs_move_presets:
    no preset '%s' for motor '%s'", psz, scint->name);
  return;
}
cay = md2cmds_prep_axis( apery, ay);
caz = md2cmds_prep_axis( aperz, az);
ccy = md2cmds_prep_axis( capy, cy);
ccz = md2cmds_prep_axis( capz, cz);
csz = md2cmds_prep_axis( scint, sz);
// 170
                     LS-CAT Move U, V, W, X, Y, Z Absolute
                          Q40 = X Value
Q41 = Y Value
                            Q41
                            042
                                      = 7 Value
                                     = Z Value
= U Value
= V Value
                           043
                            044
                                      = W Value
lspmac_SockSendDPline( "organs", "&5 Q40=0 Q41=%d Q42=%d Q43=%d Q44=%d Q45=%d Q100=16 B170R", cay, caz, ccy, ccz, csz);
```

7.9.3.26 int md2cmds_phase_beamLocation ()

Go to beam location phase.

Definition at line 833 of file md2cmds.c.

```
double move_time;
int mmask, err;
lsevents_send_event( "Mode beamLocation Starting");
// Get ready to move some motors
```

```
//
      md2cmds_move_prep();
      // Move 'em
      //
      err = lspmac_est_move_time( &move_time, &mmask,
                                                                                                                                                                                 position if no preset
                                                                                               //motor jog, preset,
                                                                                                                                  0, NULL,
                                                                                                                                                                                                 0.0,
                                                                                               kappa,
                                                                                                                                   O, NULL,
                                                                                                                                                                                                  0.0,
                                                                                             omega, 0, NULL, 0.0, apery, 0, "In", 0.0, capy, 0, "In", 0.0, capz, 0, "In", 0.0, capz, 0, "In", 0.0, blight, 1, NULL, 0.0, blight_ud, 1, NULL, 0.0, capx, 0, NULL, 0.
                                                                                               omega,
                                                                                                zoom, 0, NULL,
                                                                                                cryo,
                                                                                                                                    1, NULL,
                                                                                                                                                                                                0.0,
                                                                                                fluo,
                                                                                                                                    1, NULL,
                                                                                                                                                                                               0.0,
                                                                                               NULL);
      if( err) {
           lsevents_send_event( "Mode beamLocation Aborted");
             return err;
      err = lspmac_est_move_time_wait( move_time + 2.0,
                mmask);
       if(err){
           lsevents_send_event( "Mode beamLocation Aborted");
             return err;
      //
       // This should be redundant, at least until someone changes a jog=0 to a
                     jog=1 for a real motor
      err = md2cmds_move_wait( move_time + 2.0);
      if( err) {
            lsevents_send_event( "Mode beamLocation Aborted");
             return err;
      lsevents_send_event( "Mode beamLocation Done");
      return 0:
7.9.3.27 int md2cmds_phase_center ( )
Go to center phase.
Definition at line 724 of file md2cmds.c.
                                                                                      {
      double move time;
      int mmask, err:
       lsevents_send_event( "Mode center Starting");
```

```
//
// \ensuremath{\mathsf{Get}} ready to move some motors
//
md2cmds_move_prep();
// Move 'em
err = lspmac_est_move_time( &move_time, &mmask,
                                                                                                                                                                              0, NULL,
0, NULL,
                                                                                                                                        omega,
                                                                                                                                                                                                                                                        0.0,
                                                                                                                                        phi,
                                                                                                                                                                                          0, NULL,
                                                                                                                                                                                                                                                        0.0,
                                                                                                                                                                               0, NULL, 0.0, 0, "In", 0.0, 0, "In", 0.0, 0, "In", 0.0, 0, "In", 0.0, 0, "Cover", 0.0, "Cover
                                                                                                                                        apery,
                                                                                                                                        aperz,
                                                                                                                                         capy,
                                                                                                                                         capz,
                                                                                                                                         scint,
                                                                                                                                        blight_ud, 1, NULL,
                                                                                                                                                                                                                                                        0.0,
                                                                                                                                         zoom, 0, NULL,
                                                                                                                                                                                                                                                        1.0,
                                                                                                                                         cryo,
fluo,
                                                                                                                                                                                           1, NULL,
                                                                                                                                                                                                                                                        0.0,
                                                                                                                                                                                         1, NULL,
                                                                                                                                       NULL);
if( err) {
         lsevents_send_event( "Mode center Aborted");
        return err;
err = lspmac_est_move_time_wait( move_time + 2.0,
if( err) {
        lsevents_send_event( "Mode center Aborted");
        return err;
lsevents_send_event( "Mode center Done");
return 0;
```

7.9.3.28 int md2cmds_phase_change (const char * ccmd)

Move md2 devices to a preconfigured state.

EMBL calls these states "phases" and this language is partially retained here

Parameters

```
ccmd The full text of the command that sent us here
```

Definition at line 947 of file md2cmds.c.

```
char *cmd;
char *ignore;
char *ptr;
char *mode;
int err;

if( ccmd == NULL || *ccmd == 0)
    return 1;

// use a copy as strtok_r modifies the string it is parsing
```

```
11
cmd = strdup( ccmd);
ignore = strtok_r( cmd, " ", &ptr);
if( ignore == NULL) {
  lslogging_log_message( "md2cmds_phase_change: ignoring
     empty command string (how did we let things get this far?");
  free ( cmd);
  return 1;
//
// ignore should point to "mode" cause that's how we got here. Ignore it
mode = strtok_r( NULL, " ", &ptr);
if( mode == NULL) {
  lslogging_log_message( "md2cmds_phase_change: no mode
     specified");
  return 1;
if( md2cmds_is_moving()) {
  int err;
  lspmac_SockSendDPControlChar( "Aborting Motions
   ", '\x01');
err = md2cmds_move_wait( 2.0);
  if( err) {
    lslogging_log_message( "md2cmds_phase_change: Timed
     out waiting for previous moves to finish");
    return 1;
//
// Tangled web. Probably not worth fixing. O(N) but N is 6.
if( strcmp( mode, "manualMount") == 0) {
err = md2cmds_phase_manualMount();
} else if( strcmp( mode, "robotMount") == 0) {
 err = md2cmds_phase_robotMount();
} else if( strcmp( mode, "center") == 0) {
  err = md2cmds_phase_center();
} else if( strcmp( mode, "dataCollection") == 0) {
err = md2cmds_phase_dataCollection();
} else if( strcmp( mode, "beamLocation") == 0) {
  err = md2cmds_phase_beamLocation();
} else if( strcmp( mode, "safe") == 0) {
 err = md2cmds_phase_safe();
free ( cmd);
return err;
```

7.9.3.29 int md2cmds_phase_dataCollection ()

Go to data collection phase.

Definition at line 768 of file md2cmds.c.

```
{
double move_time;
int mmask, err;
lsevents_send_event( "Mode dataCollection Starting");
// Get ready to move some motors
md2cmds_move_prep();
// Move 'em
11
err = lspmac_est_move_time( &move_time, &mmask,
                                       1, "In",
1, "In",
1, "In",
1, "In",
1, "Cover",
                                                       0.0,
                             aperv,
                              aperz,
                              capy,
                                                       0.0,
                              capz,
                                                       0.0,
                              scint.
                                                       0.0.
                             blight, 1, NULL,
blight_ud, 1, NULL,
                                                       0.0,
                                                       0.0,
                              cryo,
                                         1, NULL,
                                                       0.0,
                              fluo,
                                        1, NULL,
                                                      0.0,
                             NULL);
if (err) {
 lsevents_send_event( "Mode dataCollection Aborted");
  return err;
err = lspmac_moveabs_wait( apery, move_time+2);
 lsevents_send_event( "Mode dataCollection Aborted");
  return err;
err = lspmac_moveabs_wait( aperz, move_time+2);
 lsevents_send_event( "Mode dataCollection Aborted");
  return err;
err = lspmac_moveabs_wait( capy, move_time+2);
  lsevents_send_event( "Mode dataCollection Aborted");
  return err;
err = lspmac_moveabs_wait( capz, move_time+2);
if( err) {
  lsevents_send_event( "Mode dataCollection Aborted");
  return err;
err = lspmac_moveabs_wait( scint, move_time+2);
 lsevents_send_event( "Mode dataCollection Aborted");
  return err;
lsevents_send_event( "Mode dataCollection Done");
return 0;
```

7.9.3.30 int md2cmds_phase_manualMount()

Go to the manual mount phase.

Definition at line 613 of file md2cmds.c.

```
double move_time;
int mmask, err;
lsevents_send_event( "Mode manualMount Starting");
// Get ready to move some motors
md2cmds_move_prep();
// Move 'em
//
omega, 0, "manualMophi, 0, NULL, aperz, 1, "Cover", capz, 1, "Cover", blight, 1, NULL, cryo, 1, NULL, fluo, 200m, 0, NULL);
                                                              0.0,
                                                              0.0,
                                                             0.0,
                                                             0.0,
                                                             0.0.
                                                             1.0,
                              NULL);
if( err) {
  lsevents_send_event( "Mode manualMount Aborted");
  return err;
//
// Wait for motion programs
err = lspmac_est_move_time_wait( move_time+2.0,
   mmask);
if(err){
  lsevents_send_event( "Mode manualMount Aborted");
  return err;
//
// Wait for jogs
// We've over estimated the move time since we've already waited a bit.
\ensuremath{//} This would only ever cause problems for really slow motions.
```

```
err = md2cmds_move_wait( move_time+2.0);
if( err) {
   lsevents_send_event( "Mode manualMount Aborted");
   return err;
}
lsevents_send_event( "Mode manualMount Done");
return 0;
```

7.9.3.31 int md2cmds_phase_robotMount()

Go to robot mount phase.

Definition at line 671 of file md2cmds.c.

```
{
double move_time;
int mmask, err;
lsevents_send_event( "Mode robotMount Starting");
// Get ready to move some motors
//
md2cmds_move_prep();
md2cmds_home_prep();
// Move 'em
//
lspmac_home1_queue( kappa);
lspmac_home1_queue( omega);
err = lspmac_est_move_time( &move_time, &mmask, phi, 0, NULL, 0.0, apery, 1, "In", 0.0, aperz, 1, "In", 0.0, capz, 1, "Cover", 0.0, scint, 1, "Cover", 0.0, blight, 1, NULL, 0.0, blight, ud 1, NULL, 0.0, blight, ud 1, NULL, 0.0
                                                               0.0,
                                    blight_ud, 1, NULL,
                                              1, NULL,
1, NULL,
                                    cryo,
                                    fluo,
                                    zoom,
                                                 O, NULL,
                                                                 1.0,
                                    NULL);
err = lspmac_est_move_time_wait( move_time + 2.0,
    mmask);
if( err) {
  lsevents_send_event( "Mode robotMount Aborted");
   return err;
err = md2cmds_move_wait( move_time + 2.0);
  lsevents_send_event( "Mode robotMount Aborted");
   return err;
err = md2cmds_home_wait( 60.0);
if( err) {
```

```
lsevents_send_event( "Mode robotMount Aborted");
  return err;
}
lsevents_send_event( "Mode robotMount Done");
  return 0;
}
```

7.9.3.32 int md2cmds_phase_safe ()

Go to safe phase.

Definition at line 889 of file md2cmds.c.

```
double move_time;
int mmask, err;
lsevents_send_event( "Mode safe Starting");
// Get ready to move some motors
11
md2cmds_move_prep();
11
// Move 'em
11
err = lspmac_est_move_time( &move_time, &mmask,
                              //motor jog, preset,
                                                          position if no preset
                                         0, NULL,
0, NULL,
1, "In",
                              kappa,
                                                               0.0,
                              omega,
                                                               0.0,
                              apery,
                                                               0.0,
                                          1, "In",
1, "Cover",
1, "In",
1, "Cover",
1, "Cover",
                              aperz,
                                                               0.0,
                                                                0.0,
                              capy,
                              capz,
                                                                0.0,
                              scint,
                                           1, NULL,
                              blight,
                                                                0.0,
                              blight_ud, 1, NULL,
                                                                0.0,
                              zoom, 0, NULL, cryo, 1, NULL,
                                                               1.0,
                                                               0.0.
                                         1, NULL,
                              fluo.
                                                              0.0,
                              NULL);
if( err) {
  lsevents_send_event( "Mode safe Aborted");
  return err;
err = lspmac_est_move_time_wait( move_time + 2.0,
   mmask);
if(err){
 lsevents_send_event( "Mode safe Aborted");
 return err;
err = md2cmds_move_wait( move_time + 2.0);
if(err) {
  lsevents_send_event( "Mode safe Aborted");
  return err;
```

```
lsevents_send_event( "Mode safe Done");
return 0;
```

7.9.3.33 double md2cmds_prep_axis ($lspmac_motor_t * mp$, double pos)

Definition at line 187 of file md2cmds.c.

7.9.3.34 int md2cmds_rotate (const char * dummy)

Spin 360 and make a video (recenter first, maybe)

Parameters

dummy Unused returns non-zero on error

Definition at line 1360 of file md2cmds.c.

```
double cx, cy, ax, ay, az, zm;
double bax, bay, baz;
int mmask;
int err;
double move_time;
mmask = 0;
// BLUMax disables scintilator here.
// get the new center information
lspg_getcenter_call();
lspg_getcenter_wait();
// put up the back light
blight_ud->moveAbs( blight_ud, 1);
// Get ready to move our motors
md2cmds_move_prep();
md2cmds_home_prep();
// make sure omega is homed
lspmac_home1_queue( omega);
// Grab the current positions
cx = lspmac_getPosition( cenx);
```

```
cy = lspmac_getPosition( ceny);
ax = lspmac_getPosition( alignx);
ay = lspmac_getPosition( aligny);
az = lspmac_getPosition( alignz);
lslogging_log_message( "md2cmds_rotate: actual positions
     cx %f, cy %f, ax %f, ay %f, az %f", cx, cy, ax, ay, az);
if( lspg_getcenter.no_rows_returned) {
  ^{\prime\prime} // Always specify zoom even if no other center information is found
  11
  zm = 1;
 else {
  lslogging_log_message( "md2cmds_rotate: getcenter
     returned dcx %f, dcy %f, dax %f, day %f, daz %f, zoom %d",
                            lspg_getcenter.dcx, lspg_getcenter
    .dcy, lspg_getcenter.dax, lspg_getcenter.day
    , lspg_getcenter.daz,lspg_getcenter.zoom);
  if( lspg_getcenter.zoom_isnull == 0) {
  zm = lspg_getcenter.zoom;
} else {
    zm = 1.0;
  if( lspg_getcenter.dcx_isnull == 0)
    cx += lspg_getcenter.dcx;
  if( lspg_getcenter.dcy_isnull == 0)
    cy += lspg_getcenter.dcy;
  // Slightly complicated procedure for alignment stage since we might want
     to update
  // the presets. Use the preset Back_Vector to calculate the new Back
     preset from our
  // current position.
  if( lspg_getcenter.dax_isnull == 0) {
  err = lsredis_find_preset( "align.x", "Back_Vector", &
    bax):
    if( err == 0)
      bax = 0.0;
    bax += lspg_getcenter.dax;
    lsredis_set_preset( "align.x", "Back", bax);
    ax += lspg_getcenter.dax;
lsredis_set_preset( "align.x", "Beam", ax);
  if( lspg_getcenter.day_isnull == 0) {
    err = lsredis_find_preset( "align.y", "Back_Vector", &
    bav);
    if(err == 0)
      bay = 0.0;
    bay += lspg_getcenter.day;
    lsredis_set_preset( "align.y", "Back", bay);
    ay += lspg_getcenter.day;
    lsredis_set_preset( "align.y", "Beam", ay);
  if( lspg_getcenter.daz_isnull == 0) {
    err = lsredis_find_preset( "align.z", "Back_Vector", &
    baz);
    if( err == 0)
      baz = 0.0;
    baz += lspg_getcenter.daz;
    lsredis_set_preset( "align.z", "Back", baz);
    az += lspg_getcenter.daz;
lsredis_set_preset( "align.z", "Beam", az);
  lslogging_log_message( "md2cmds_rotate: requested
  positions cx %f, cy %f, ax %f, ay %f, az %f", cx, cy, ax, ay, az);
  lslogging_log_message( "md2cmds_rotate: moving center"
  md2cmds_mvcenter_move( cx, cy, ax, ay, az);
  lslogging_log_message( "md2cmds_rotate: waiting for
     center move");
  lslogging_log_message( "md2cmds_rotate: done waiting")
```

```
lspg_getcenter_done();
if ( lspmac est move time ( &move time, &mmask,
                                cenx, 0, NULL, cx, ceny, 0, NULL, cy,
                                               NULL, cy,
                                alignx, 0,
                                               NULL, ax,
                                aligny, 0,
                                               NULL, ay,
                                alignz, 0,
                                               NULL, az,
                                zoom, 1, NULL, zm,
                                NULL)) {
  lslogging_log_message( "md2cmds_rotate: organ motion
     request failed");
  lsevents_send_event( "Rotate Aborted");
  return 1:
}
if( lspmac_est_move_time_wait( move_time + 2.0,
     mmask)) {
  lslogging_log_message( "md2cmds_rotate: organ motion
     timed out %f seconds", move_time + 2.0);
  lsevents_send_event( "Rotate Aborted");
  return 1;
if( lspmac_moveabs_wait( zoom, move_time + 2.0)) {
  lslogging_log_message( "md2cmds_rotate: zoom timed out
    %f seconds", move_time + 2.0);
  lsevents_send_event( "Rotate Aborted");
  return 1;
if( md2cmds_home_wait( 20.0)) {
  lslogging_log_message( "md2cmds_rotate: homing motors
    timed out. Rotate aborted");
  lsevents_send_event( "Rotate Aborted");
  return 1;
// Report new center positions
cx = lspmac_getPosition( cenx);
cy = lspmac_getPosition( ceny);
ax = lspmac_getPosition( alignx);
ay = lspmac_getPosition( aligny);
lslogging_log_message( "md2cmds_rotate: done with
    applycenter");
apprycenter /,
lspmac_video_rotate( 4.0);
lslogging_log_message( "md2cmds_rotate: starting
      rotation");
rotating = 1;
return 0;
```

7.9.3.35 void md2cmds_rotate_cb (char * event)

Tell the database about the time we went through omega=zero.

This should trigger the video feed server to starting making a movie.

Definition at line 1526 of file md2cmds.c.

```
(int)(lspmac_getPosition( zoom)));
```

7.9.3.36 void md2cmds_run ()

Start up the thread.

Definition at line 1934 of file md2cmds.c.

```
pthread_create( &md2cmds_thread, NULL,
    md2cmds_worker, NULL);
lsevents_add_listener( "omega crossed zero",
    md2cmds_rotate_cb);
lsevents_add_listener( "omega In Position",
md2cmds_maybe_rotate_done_cb);
lsevents_add_listener( ".+ (Moving|In Position)",
    md2cmds_maybe_done_moving_cb);
lsevents_add_listener( "(.+) (Homing|Homed)",
    md2cmds_maybe_done_homing_cb);
lsevents_add_listener( "capz (Moving|In Position)",
     md2cmds_time_capz_cb);
lsevents_add_listener( "Coordsys 1 Stopped",
md2cmds_coordsys_1_stopped_cb);
lsevents_add_listener( "Coordsys 2 Stopped",
    md2cmds_coordsys_2_stopped_cb);
lsevents_add_listener( "Coordsys 3 Stopped",
     md2cmds_coordsys_3_stopped_cb);
lsevents_add_listener( "Coordsys 4 Stopped",
md2cmds_coordsys_4_stopped_cb);
lsevents_add_listener( "Coordsys 5 Stopped",
md2cmds_coordsys_5_stopped_cb);
lsevents_add_listener( "Coordsys 7 Stopped",
     md2cmds_coordsys_7_stopped_cb);
lsevents_add_listener( "cam.zoom Moving",
     md2cmds_set_scale_cb);
```

7.9.3.37 int md2cmds_run_cmd (const char * cmd)

Definition at line 1697 of file md2cmds.c.

```
int err, i;
lspmac_motor_t *mp;
regmatch_t pmatch[16];
char cp[64];
if( strlen(cmd) > sizeof( cp)-1) {
   lslogging_log_message( "md2cmds_set: command too long
     '%s'", cmd);
  return 1;
err = regexec( &md2cmds_cmd_regex, cmd, 16, pmatch, 0);
if (err) {
  lslogging_log_message( "md2cmds_set: no match found
  from '%s'", cmd);
  return 1;
}
for( i=0; i<16; i++) {</pre>
  if( pmatch[i].rm_so == -1)
     continue;
  lslogging_log_message( "md2cmds_run: %d '%.*s'", i,
    pmatch[i].rm_eo - pmatch[i].rm_so, cmd+pmatch[i].rm_so);
}
// get motor name
snprintf(cp, sizeof(cp)-1, "%.*s", pmatch[4].rm_eo - pmatch[4].rm_so, cmd+
    pmatch[4].rm_so);
cp[sizeof(cp)-1] = 0;
mp = lspmac_find_motor_by_name( cp);
```

```
if( mp == NULL) {
    lslogging_log_message( "md2cmds_set: could not find
        motor '%s'", cp);
    return 1;
}

if( pmatch[5].rm_so != -1) {
    if( strncmp( cmd+pmatch[5].rm_so, "home", pmatch[5].rm_eo-pmatch[5].rm_so)
        ==0) {
        lslogging_log_message( "md2cmds_run_cmd: homing
        motor '%s'", cp);
        lspmac_homel_queue( mp);
    } else if( strncmp( cmd+pmatch[5].rm_so, "stop", pmatch[5].rm_eo-pmatch[5].
        rm_so)==0) {
        lslogging_log_message( "md2cmds_run_cmd: stoping
        motor '%s'", cp);
        lspmac_abort();
    }
}

return 0;
```

7.9.3.38 int md2cmds_set (const char * cmd)

Definition at line 1746 of file md2cmds.c.

```
int err;
lsredis_obj_t *p;
lspmac_motor_t *mp;
regmatch_t pmatch[16];
char cp[64];
char *rp;
if( strlen(cmd) > sizeof( cp)-1) {
   lslogging_log_message( "md2cmds_set: command too long
     '%s'", cmd);
  return 1;
lslogging_log_message( "md2cmds_set: recieved '%s'", cmd
err = regexec( &md2cmds_cmd_regex, cmd, 16, pmatch, 0);
if(err) {
 lslogging_log_message( "md2cmds_set: no match found
from '%s'", cmd);
  return 1;
if( pmatch[2].rm_so == -1) {
   lslogging_log_message( "md2cmds_set: could not parse
     preset name from '%s'", cmd);
  return 1;
// get motor name
snprintf(cp, sizeof(cp)-1, "%.*s", pmatch[3].rm_eo - pmatch[3].rm_so, cmd+
    pmatch[3].rm_so);
cp[sizeof(cp)-1] = 0;
mp = lspmac_find_motor_by_name( cp);
if ( mp == NULL) {
  lslogging_log_message( "md2cmds_set: could not find
  motor '%s'", cp);
  return 1;
// get redis preset position name
p = lsredis_get_obj( "%.*s.position", pmatch[2].rm_eo - pmatch
[2].rm_so, cmd+pmatch[2].rm_so);
if( p == NULL) {
  lslogging_log_message( "md2cmds_set: could not find
```

```
preset name in '%s'", cmd);
return 1;
}

rp = lsredis_getstr( mp->redis_position);

//
// set the preset to the current position
//
lsredis_setstr( p, "%s", rp);
lsevents_send_event( "Preset Changed %s", p->events_name
    );

free( rp);
return 0;
```

7.9.3.39 void md2cmds_set_scale_cb (char * event)

Fix up xscale and yscale when zoom changes.

Definition at line 1551 of file md2cmds.c.

```
int mag;
lsredis_obj_t *p1, *p2;
char *vp;

pthread_mutex_lock( &zoom->mutex);
mag = zoom->requested_position;
pthread_mutex_unlock( &zoom->mutex);

p1 = lsredis_get_obj( "cam.xScale");
p2 = lsredis_get_obj( "cam.zoom.%d.ScaleX", mag);

vp = lsredis_getstr( p2);
lsredis_setstr( p1, vp);
free( vp);

p1 = lsredis_get_obj( "cam.yScale");
p2 = lsredis_get_obj( "cam.zoom.%d.ScaleY", mag);

vp = lsredis_getstr( p2);
lsredis_setstr( p1, vp);
free( vp);
```

7.9.3.40 int md2cmds_test (const char * dummy)

Run the test routine(s)

Parameters

dummy Unused

Definition at line 1691 of file md2cmds.c.

```
lstest_main();
return 0;
}
```

7.9.3.41 void md2cmds_time_capz_cb (char * event)

Time the capillary motion for the transfer routine.

< track the time spent moving capz

Definition at line 1585 of file md2cmds.c.

```
static struct timespec capz_timestarted;
struct timespec now;
int nsec, sec;

if ( strstr( event, "Moving") != NULL) {
   clock_gettime( CLOCK_REALTIME, &capz_timestarted);
} else {
   clock_gettime( CLOCK_REALTIME, &now);

   sec = now.tv_sec - capz_timestarted.tv_sec;
   nsec = 0;
   if ( now.tv_nsec > capz_timestarted.tv_nsec) {
      sec--;
      nsec += 1000000000;
   }
   nsec += now.tv_nsec - capz_timestarted.tv_nsec;
   md2cmds_capz_moving_time = sec + nsec / 1000000000.
   ;
}
```

7.9.3.42 int md2cmds_transfer (const char * dummy)

Transfer a sample.

Parameters

dummy Unused

Definition at line 267 of file md2cmds.c.

```
int nextsample, abort_now;
double esttime;
double ax, ay, az, cx, cy, horz, vert, oref;
int err;
nextsample = lspg_nextsample_all( &err);
if(err){
  lslogging_log_message( "md2cmds_transfer: no sample
     requested to be transfered, false alarm");
  return 1;
// BLUMax sets up an abort dialogbox here. Probably we should figure out how
      we are going to handle that.
^{\prime\prime} // Wait for motors to stop
if( md2cmds_is_moving()) {
  lslogging_log_message( "md2cmds_transfer: Waiting for
    previous motion to finish");
  if( md2cmds_move_wait( 30.0)) {
   lslogging_log_message( "md2cmds_transfer: Timed out
     waiting for previous motion to finish. Aborting transfer");
  }
}
// get positions we'll be needed to report to postgres
ax = lspmac_getPosition(alignx);
ay = lspmac_getPosition(aligny);
az = lspmac_getPosition(alignz);
cx = lspmac_getPosition(cenx);
cy = lspmac_getPosition(ceny);
oref = lsredis_getd(lsredis_get
    omega.reference")) * M_PI/180.;
horz = cx * cos(oref) + cy * sin(oref);
vert = cx * sin(oref) - cy * cos(oref);
if( lsredis_getd( capz->u2c) <= 0.0 || lsredis_getd</pre>
     ( capz->max_speed) <= 0.0 || lsredis_getd( capz->
     max_accel) <= 0.0) {
```

```
esttime = 0.0;
} else {
  \ensuremath{//} Here we assume moving the capilary is the rate limiting step in
    preparing the MD2.
  // TODO: look at factors in which something besides the capilary determines
     the time such as if the scintilator is out.
  // pretend we are going to zero instead of the "Out" position. We should
     probably arrange for
  // neutralPosition such that "Out" is zero.
  // This also treats S curve acceleration as taking the same time as linear
     acceleration.
  esttime = lspmac_getPosition( capz)/lsredis_getd
  ( capz->u2c)/(lsredis_getd( capz->max_speed));
  // Time if we moved at constant velocity
  esttime += lsredis_getd( capz->max_speed)/
    lsredis_getd(capz->max_accel);
    // Correction for time spent accelerating
  esttime /= 1000.;
    // convert from milliseconds to seconds
lspg_starttransfer_call( nextsample,
    lspmac_getBIPosition( sample_detected), ax,
    ay, az, horz, vert, esttime);
// put the light down if it's not already
if( lspmac_getBIPosition( blight_down) != 1)
  blight_ud->moveAbs( blight_ud, 0);
// Pull the fluorescence detector out of the way
if( lspmac_getBIPosition( fluor_back) != 1)
  blight_ud->moveAbs( fluo, 0);
//
// Prepare for moving stuff
md2cmds_move_prep();
// Put the organs into position
md2cmds_organs_move_presets( "In", "Cover", "In",
    "Cover", "Cover");
md2cmds_home_prep();
// Home Kappa
lspmac_home1_queue( kappa);
//
// Home omega
lspmac_home1_queue( omega);
// wait for kappa cause we can't home phi until kappa's done
lspmac_moveabs_wait( kappa, 60.0);
// Home phi (whatever that means)
lspmac_homel_queue( phi);
// Now let's get back to postresql (remember our query so long ago?)
lspg_starttransfer_wait();
^{\prime\prime} // It's possible that the sample that's mounted is unknown to the robot.
// If so then we need to abort after we're done moving stuff
if( lspg_starttransfer.no_rows_returned ||
    lspg_starttransfer.starttransfer != 1)
  abort_now = 1;
 abort now = 0;
```

```
lspg_starttransfer_done();
// Wait for the homing routines to finish
if( md2cmds_home_wait( 30.0)) {
  lslogging_log_message( "md2cmds_transfer: homing
  routines taking too long. Aborting transfer.");
lsevents_send_event( "Transfer Aborted");
  return 1:
// Wait for all the motors to stop moving
if( md2cmds_move_wait( 30.0)) {
  lslogging_log_message( "md2cmds_transfer: We got bored
     waiting for the motors to stop. Aborting transfer. Later.");
  lsevents_send_event( "Transfer Aborted");
  return 1;
// TODO: check that all the motors are where we told them to go
if( abort_now) {
  lslogging_log_message( "md2cmds_transfer: Apparently
  there is a sample mounted already but we don't know where it is supposed to go"); lsevents_send_event( "Transfer Aborted");
// refuse to go on if we do not have positive confirmation that the backlight
      is down and the
// fluorescence detector is back
if( lspmac_getBIPosition( blight_down) != 1 ||
  lspmac_getBiPosition( blight_down) := 1 | |
lspmac_getBiPosition( fluor_back) != 1) {
lslogging_log_message( "md2cmds_transfer: It looks
    like either the back light is not down or the fluoescence dectector is not back");
lsevents_send_event( "Transfer Aborted");
  return 1;
^{\prime\prime} // Wait for the robot to unlock the cryo which signals us that we need to // move the cryo back and drop air rights
lspg_waitcryo_all();
// Move the cryo back
cryo->moveAbs( cryo, 1);
lspmac_moveabs_wait( cryo, 10.0);
// simplest query yet!
lspg_query_push( lspg_waitcryo_cb, "SELECT
      px.dropairrights()");
// wait for the result
// TODO: find an easy way out of this in case of error
lspg_getcurrentsampleid_wait_for_id(
     nextsample);
// grab the airrights again
lspg_demandairrights_all();
lsevents_send_event( "Transfer Done");
return 0;
```

7.9.3.43 void* md2cmds_worker (void * dummy)

Our worker thread.

Parameters

dummy

[in] Unused but required by protocol

Definition at line 1811 of file md2cmds.c.

```
ENTRY hsearcher, *hrtnval;
char the Cmd[32], \starsp;
int i, err;
md2cmds_cmd_kv_t *cmdp;
pthread_mutex_lock( &md2cmds_mutex);
while(1) {
  // wait for someone to give us a command (and tell us they did so)
  11
  while( md2cmds_cmd[0] == 0)
    pthread_cond_wait( &md2cmds_cond, &md2cmds_mutex
  // pull out the command name itself from the string we were given
  for( i=0, sp=md2cmds_cmd; i<sizeof( theCmd)-1; i++, sp++) {
   if( *sp == 0 || *sp == ' ') {</pre>
       theCmd[i] = 0;
       break;
     theCmd[i] = *sp;
  theCmd[sizeof(theCmd)-1]=0;
  hsearcher.key = theCmd;
hsearcher.data = NULL;
  errno = 0;
  err = hsearch_r( hsearcher, FIND, &hrtnval, &md2cmds_hmap);
  if( err == 0) {
   lslogging_log_message( "md2cmds_worker: hsearch_r
   failed. theCmd = '%s' from string '%s'", theCmd, md2cmds_cmd);
   md2cmds_cmd[0] = 0;
     continue;
  {\tt lslogging\_log\_message(\ "md2cmds\_worker:\ Found\ command}
  '%s'", theCmd);
if( hrtnval != NULL) {
     cmdp = (md2cmds_cmd_kv_t *)hrtnval;
     err = cmdp->v( md2cmds_cmd);
      lslogging_log_message( "md2cmds_worker: Command
failed: '%s'", md2cmds_cmd);
       // At this point we'd clear the queue but the queue is currently too
      short to bother doing that
  }
  md2cmds\_cmd[0] = 0;
```

7.9.4 Variable Documentation

7.9.4.1 double md2cmds_capz_moving_time = NAN [static]

Definition at line 32 of file md2cmds.c.

7.9.4.2 char md2cmds_cmd[MD2CMDS CMD LENGTH]

our command;

Definition at line 24 of file md2cmds.c.

7.9.4.3 md2cmds_cmd_kv_t md2cmds_cmd_kvs[] [static]

Initial value:

Definition at line 56 of file md2cmds.c.

7.9.4.4 regex_t md2cmds_cmd_regex [static]

Definition at line 36 of file md2cmds.c.

7.9.4.5 pthread_cond_t md2cmds_cond

condition to signal when it's time to run an md2 command Definition at line 10 of file md2cmds.c.

7.9.4.6 struct hsearch_data md2cmds_hmap [static]

Definition at line 34 of file md2cmds.c.

7.9.4.7 pthread_cond_t md2cmds_homing_cond

coordinate homing and homed

Definition at line 18 of file md2cmds.c.

7.9.4.8 int md2cmds_homing_count = 0

We've asked a motor to home.

Definition at line 17 of file md2cmds.c.

7.9.4.9 pthread_mutex_t md2cmds_homing_mutex

our mutex;

Definition at line 19 of file md2cmds.c.

7.9.4.10 | Isredis_obj_t* md2cmds_md_status_code

Definition at line 26 of file md2cmds.c.

7.9.4.11 pthread_cond_t md2cmds_moving_cond

wait for command to have been dequeued and run coordinate call and response

Definition at line 14 of file md2cmds.c.

7.9.4.12 int md2cmds_moving_count = 0

Definition at line 22 of file md2cmds.c.

7.9.4.13 pthread_mutex_t md2cmds_moving_mutex

message passing between md2cmds and pg Definition at line 15 of file md2cmds.c.

7.9.4.14 int md2cmds_moving_queue_wait = 0

Definition at line 13 of file md2cmds.c.

7.9.4.15 pthread_mutex_t md2cmds_mutex

mutex for the condition

Definition at line 11 of file md2cmds.c.

7.9.4.16 pthread_t md2cmds_thread [static]

Definition at line 28 of file md2cmds.c.

7.9.4.17 int rotating = **0** [static]

flag: when omega is in position after a rotate we want to re-home omega Definition at line 30 of file md2cmds.c.

7.10 mk_pgpmac_redis.py File Reference

Namespaces

• namespace mk_pgpmac_redis

Functions

- def mk_pgpmac_redis.active_simulation
- def mk_pgpmac_redis.asis

Variables

- list mk pgpmac redis.head sys.argv[1]
- list mk_pgpmac_redis.pref_ini sys.argv[2]
- list mk_pgpmac_redis.hard_ini sys.argv[3]
- · dictionary mk_pgpmac_redis.motor_dict
- dictionary mk_pgpmac_redis.hard_ini_fields
- · list mk pgpmac redis.motor field lists
- list mk_pgpmac_redis.bi_list ["CryoSwitch"]
- · dictionary mk_pgpmac_redis.motor_presets
- list mk_pgpmac_redis.zoom_settings
- tuple mk_pgpmac_redis.hi iniParser.iniParser(hard_ini)
- list mk_pgpmac_redis.v motor_dict[m]
- string mk_pgpmac_redis.f "HSETNX"
- list mk pgpmac redis.xlate hard ini fields[k]
- tuple mk_pgpmac_redis.pi iniParser.iniParser(pref_ini)
- int mk pgpmac redis.i 0
- tuple mk_pgpmac_redis.ppos pi.get(section, option)
- string mk_pgpmac_redis.fnc "HSETNX"
- tuple mk_pgpmac_redis.b pi.get(section, "LightIntensity")
- tuple mk_pgpmac_redis.p pi.get(section, "MotorPosition")
- tuple mk pgpmac redis.x pi.get(section, "ScaleX")
- tuple mk_pgpmac_redis.y pi.get(section, "ScaleY")

7.11 pgpmac.c File Reference

```
Main for the pgpmac project.
```

```
#include "pgpmac.h"
```

Functions

void stdinService (struct pollfd *evt)

Handle keyboard input.

• void pgpmac_printf (char *fmt,...)

Terminal output routine ala printf.

int main (int argc, char **argv)

Our main routine.

Variables

WINDOW * term output

place to print stuff out

• WINDOW * term_input

place to put the cursor

• WINDOW * term status

shutter, lamp, air, etc status

WINDOW * term_status2

shutter, lamp, air, etc status

pthread_mutex_t ncurses_mutex

allow more than one thread access to the screen

· static struct pollfd stdinfda

Handle input from the keyboard.

• static int running = 1

7.11.1 Detailed Description

Main for the pgpmac project.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file pgpmac.c.

7.11.2 Function Documentation

7.11.2.1 int main (int argc, char ** argv)

Our main routine.

< argument flags

Parameters

in	argc	Number of arguments
in	argv	Vector of argument strings

Definition at line 353 of file pgpmac.c.

```
static struct pollfd fda[3];
                                                // input for poll: room for postgres,
     pmac, and stdin
static int nfd = 0;
                                                   // number of items in fda
static int pollrtn = 0;
static struct option long_options[] = {
    "i-vars", 0, NULL, 'i'},
    { "m-vars", 0, NULL, 'm'},
    { NULL, 0, NULL, 0}
};
int c;
int ivars, mvars;
mvars = 0;
ivars = 0;
                                      // standard loop counter
int i;
while( 1) {
  c=getopt_long( argc, argv, "im", long_options, NULL);
  if( c == -1)
   break;
   switch(c) {
    ivars=1;
     break;
   case 'm':
     mvars=1;
```

```
break;
 }
stdinfda.fd = 0;
stdinfda.events = POLLIN;
                                        // Start ncurses
initscr();
                                        // Line buffering disabled, control
raw();
    chars trapped
keypad( stdscr, TRUE);
                                        // Why is F1 nifty?
refresh():
pthread_mutex_init( &ncurses_mutex, NULL);
                                                   // don't lock
     this mutex yet because we are not multi-threaded until the "_run" functions
// that everyone is initiallized before anyone runs
lslogging_init();
lslogging_run();
lsevents_init();
lsevents run();
lstimer_init();
lstimer_run();
lsredis_init( "MD2-21-ID-E", "redis\\.kvseq|stns\\.2\\.(.+)", "
    stns.2");
lsredis_run();
lspmac init( ivars, mvars);
lspg_init();
md2cmds_init();
term_status = newwin( LS_DISPLAY_WINDOW_HEIGHT
    , LS_DISPLAY_WINDOW_WIDTH, 3*LS_DISPLAY_WINDOW_HEIGHT
    , 0*LS_DISPLAY_WINDOW_WIDTH);
box( term_status, 0, 0);
wnoutrefresh( term_status);
wnoutrefresh( term_status2);
term_output = newwin( 20, 5*LS_DISPLAY_WINDOW_WIDTH
    , 4*LS_DISPLAY_WINDOW_HEIGHT, 0);
scrollok(term_output, 1);
wnoutrefresh(term_output);
term_input = newwin(3,5*LS_DISPLAY_WINDOW_WIDTH
    , 20+4*LS_DISPLAY_WINDOW_HEIGHT, 0);
box(term_input, 0, 0);
mvwprintw(term_input, 1, 1, "PMAC> ");
nodelay(term_input, TRUE);
keypad(term_input, TRUE);
wnoutrefresh( term_input);
doupdate();
lspmac run();
lspg_run();
md2cmds_run();
while( running) {
  // Big loop
  nfd = 0;
  // keyboard
  memcpy( &(fda[nfd++]), &stdinfda, sizeof( struct pollfd));
  if( nfd == 0) {
    ^{\prime\prime} // No connectons yet. Wait a bit and try again.
    sleep( 10);
    // go try to connect again
    continue;
```

```
pollrtn = poll( fda, nfd, 10);

for( i=0; pollrtn>0 && i<nfd; i++) {
    if( fda[i].revents) {
      pollrtn--;
      if( fda[i].fd == 0) {
        stdinService( &fda[i]);
      }
    }
    }
    endwin();
    return 0;</pre>
```

7.11.2.2 void pgpmac_printf (char * fmt, ...)

Terminal output routine ala printf.

Parameters

in	fmt	Printf style formating string

Definition at line 330 of file pgpmac.c.

```
{
  va_list arg_ptr;

pthread_mutex_lock( &ncurses_mutex);

va_start( arg_ptr, fmt);
  vwprintw( term_output, fmt, arg_ptr);
  va_end( arg_ptr);

wnoutrefresh( term_output);
  wnoutrefresh( term_input);
  doupdate();

pthread_mutex_unlock( &ncurses_mutex);
```

7.11.2.3 void stdinService (struct pollfd * evt)

Handle keyboard input.

Parameters

}

- 1			
	in	evt	The pollfd object that caused this call
			The point object that eddeed the oan

Definition at line 254 of file pgpmac.c.

```
{
static char cmds[1024];
static char cntrlcmd[2];
static unsigned int cmds_on = 0;
int ch;

for( ch=wgetch(term_input); ch != ERR && running; ch=wgetch(
    term_input)) {
    // wprintw( term_output, "%04x\n", ch);
    // wnoutrefresh( term_output);

switch( ch) {
    case KEY_F(1):
    case KEY_F(2):
    case KEY_F(3):
```

```
running = 0;
  break;
                  // Control-A
// Control-B
// Control-C
// Control-D
// Control-E
// Control-F
// Control-K
case 0x0001:
case 0x0002:
case 0x0003:
case 0x0004:
case 0x0005:
case 0x0006:
case 0x0007:
                     // Control-G
// Control-O
case 0x000b:
case 0x000f:
                     // Control-P
// Control-Q
// Control-R
case 0x0010:
case 0x0011:
case 0x0012:
case 0x0013:
                      // Control-Q
case 0x0016:
                      // Control-V
 cntrlcmd[0] = ch;
  cntrlcmd[1] = 0;
  lspmac_SockSendline( NULL, cntrlcmd);
          PmacSockSendControlCharPrint(ch);
  break;
case KEY_BACKSPACE:
 cmds[cmds_on] = 0;
  cmds_on == 0 ? 0 : cmds_on--;
case KEY_ENTER:
case 0x000a:
  if( cmds_on > 0 && strlen( cmds) > 0) {
    lspmac_SockSendline( NULL, "%s", cmds);
  memset( cmds, 0, sizeof(cmds));
  cmds_on = 0;
  break;
default:
  if(ch >= 0x20 && ch <= 0x7e) {
   if( cmds_on < sizeof( cmds)-1) {</pre>
      cmds[cmds_on++] = ch;
cmds[cmds_on] = 0;
  break;
if( running) {
  mvwprintw( term_input, 1, 1, "PMAC> %s", cmds);
  wclrtoeol( term_input);
  box( term_input, 0, 0);
  wnoutrefresh( term_input);
  doupdate();
}
```

7.11.3 Variable Documentation

7.11.3.1 pthread_mutex_t ncurses_mutex

allow more than one thread access to the screen

Definition at line 242 of file pgpmac.c.

```
7.11.3.2 intrunning = 1 [static]
```

Definition at line 249 of file pgpmac.c.

7.11.3.3 struct pollfd stdinfda [static]

Handle input from the keyboard.

Definition at line 248 of file pgpmac.c.

7.11.3.4 WINDOW* term_input

place to put the cursor

Definition at line 238 of file pgpmac.c.

7.11.3.5 WINDOW* term_output

place to print stuff out

Definition at line 237 of file pgpmac.c.

7.11.3.6 WINDOW* term_status

shutter, lamp, air, etc status

Definition at line 239 of file pgpmac.c.

7.11.3.7 WINDOW* term_status2

shutter, lamp, air, etc status

Definition at line 240 of file pgpmac.c.

7.12 pgpmac.h File Reference

Headers for the entire pgpmac project.

```
#include <stdint.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netdb.h>
#include <string.h>
#include <netinet/in.h>
#include <errno.h>
#include <poll.h>
#include <libpq-fe.h>
#include <ncurses.h>
#include <math.h>
#include <pthread.h>
#include <signal.h>
#include <sys/signalfd.h>
#include <sys/time.h>
#include <time.h>
#include <getopt.h>
#include <regex.h>
#include <hiredis/hiredis.h>
#include <hiredis/async.h>
#include <search.h>
```

Data Structures

struct lsredis_obj_struct

Redis Object Basic object whose value is sychronized with our redis db.

struct tagEthernetCmd

PMAC ethernet packet definition.

struct lspmac_cmd_queue_struct

PMAC command queue item.

struct lspmac_motor_struct

Motor information.

· struct lspmac_bi_struct

Storage for binary inputs.

struct lspgQueryQueueStruct

Store each query along with it's callback function.

- struct lspg_waitcryo_struct
- · struct lspg getcurrentsampleid struct
- struct lspg_demandairrights_struct
- · struct lspg_getcenter_struct

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies.

• struct lspg_starttransfer_struct

returns 1 if transfer can continue 0 to abort

struct lspg_nextsample_struct

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

struct lspg nextshot struct

Storage definition for nextshot query.

Macros

- #define _GNU_SOURCE
- #define LS_DISPLAY_WINDOW_HEIGHT 8

Number of status box rows.

• #define LS_DISPLAY_WINDOW_WIDTH 24

Number of status box columns.

• #define LS PG QUERY STRING LENGTH 1024

Fixed length postgresql query strings. Queries should all be function calls so this is not as weird as one might think.

#define LSEVENTS_EVENT_LENGTH 256

Fixed length for event names: simplifies string handling.

• #define MD2CMDS_CMD_LENGTH 32

Typedefs

typedef struct lsredis_obj_struct lsredis_obj_t

Redis Object Basic object whose value is sychronized with our redis db.

typedef struct tagEthernetCmd pmac_cmd_t

PMAC ethernet packet definition.

· typedef struct

lspmac_cmd_queue_struct pmac_cmd_queue_t

PMAC command queue item.

· typedef struct Ispmac motor struct Ispmac motor t

Motor information.

typedef struct lspmac_bi_struct lspmac_bi_t

Storage for binary inputs.

typedef struct lspgQueryQueueStruct lspg_query_queue_t
Store each query along with it's callback function.

typedef struct lspg_waitcryo_struct lspg_waitcryo_t

typedef struct
lspg_getcurrentsampleid struct lspg_getcurrentsampleid t

typedef struct

lspg_demandairrights_struct lspg_demandairrights_t

· typedef struct

lspg_getcenter_struct lspg_getcenter_t

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies.

· typedef struct

lspg_starttransfer_struct lspg_starttransfer_t

returns 1 if transfer can continue 0 to abort

· typedef struct

lspg_nextsample_struct lspg_nextsample_t

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

typedef struct lspg_nextshot_struct lspg_nextshot_t

Storage definition for nextshot query.

Functions

double lspmac_getPosition (lspmac_motor_t *)

get the motor position (with locking)

char ** lspg_array2ptrs (char *)

returns a null terminated list of strings parsed from postgresql array

- char ** Isredis_get_string_array (Isredis_obj_t *p)
- void lspmac_SockSendDPline (char *, char *fmt,...)

prepare (queue up) a line to send the dpram ascii command interface

pmac_cmd_queue_t * lspmac_SockSendline (char *, char *,...)

Send a one line command.

- Isredis_obj_t * Isredis_get_obj (char *,...)
- char * lsredis_getstr (lsredis_obj_t *p)

return a copy of the key's string value be sure to free the result

- void PmacSockSendline (char *s)
- unsigned int lspg_nextsample_all (int *err)
- char lsredis_getc (lsredis_obj_t *p)
- long int lsredis_getl (lsredis_obj_t *p)
- void Isevents add listener (char *, void(*cb)(char *))

Add a callback routine to listen for a specific event.

void lsevents_init ()

Initialize this module.

void lsevents_remove_listener (char *, void(*cb)(char *))

Remove a listener previously added with Isevents_add_listener.

void lsevents_run ()

Start up the thread and get out of the way.

void lsevents_send_event (char *,...)

Call the callback routines for the given event.

void Islogging init ()

Initialize the Islogging objects.

void lslogging_log_message (char *fmt,...)

The routine everyone will be talking about.

```
    void lslogging_run ()

      Start up the worker thread.
· void lspg_demandairrights_all ()
      do nothing until we get airrights

    void lspg_getcenter_call ()

      Request a getcenter query.

    void lspg_getcenter_done ()

     Done with getcenter query.

    void lspg_getcenter_wait ()

      Wait for a getcenter guery to return.

    void lspg_getcurrentsampleid_wait_for_id (unsigned int test)

void lspg_init ()
      Initiallize the Ispg module.

    void lspg_nextshot_call ()

      Queue up a nextshot query.
void lspg_nextshot_done ()
      Called when the next shot query has been processed.
void lspg_nextshot_wait ()
      Wait for the next shot query to get processed.
void lspg_query_push (void(*cb)(lspg_query_queue_t *, PGresult *), char *fmt,...)
      Place a query on the queue.
• void lspg_run ()
      Start 'er runnin'.
• void <a href="seg_run_prep_all">lspg_seg_run_prep_all</a> (long long skey, double kappa, double phi, double cx, double cy, double ax,
  double ay, double az)
      Convinence function to call seq run prep.
· void lspg_starttransfer_call (unsigned int nextsample, int sample_detected, double ax, double ay, double az,
  double horz, double vert, double esttime)
• void lspg_starttransfer_done ()

    void lspg_starttransfer_wait()

    void lspg waiteryo all ()

      no need to get fancy with the wait cryo command It should not return until the robot is almost ready for air rights

    void lspg_waitcryo_cb (lspg_query_queue_t *qqp, PGresult *pgr)

void lspg_zoom_lut_call ()

    int lspmac getBIPosition (lspmac bi t*)

     get binary input value

    void lspmac_home1_queue (lspmac_motor_t *mp)

     Home the motor.

    void lspmac home2 queue (lspmac motor t *mp)

      Second stage of homing.
void lspmac_abort ()
     abort motion and try to recover

    void lspmac_init (int, int)

      Initialize this module.

    int lspmac jogabs queue (lspmac motor t *, double)

      Use jog to move motor to requested position.

    int lspmac_move_or_jog_abs_queue (lspmac_motor_t *mp, double requested_position, int use_jo)

      Move method for normal stepper and servo motor objects Returns non-zero on abort, zero if OK.

    int lspmac_move_or_jog_preset_queue (lspmac_motor_t *, char *, int)

      move using a preset value returns 0 on success, non-zero on error

    void lspmac_move_or_jog_queue (lspmac_motor_t *, double, int)
```

```
    int lspmac_move_preset_queue (lspmac_motor_t *mp, char *preset_name)

      Move a given motor to one of its preset positions.
• int lspmac_moveabs_queue (lspmac_motor_t *, double)
      Use coordinate system motion program, if available, to move motor to requested position.
• int Ispmac moveabs wait (Ispmac motor t *mp, double timeout)
      Wait for motor to finish moving.

    void Ispmac run ()

      Start up the Ispmac thread.
• void <a href="mailto:lspmac_video_rotate">lspmac_video_rotate</a> (double secs)
      Special motion program to collect centering video.
• int Isredis cmpnstr (Isredis obj t *p, char *s, int n)
int lsredis_cmpstr (lsredis_obj_t *p, char *s)

    int Isredis find preset (char *base, char *preset name, double *dval)

    int Isredis getb (Isredis obj t*p)

    double Isredis getd (Isredis obj t *p)

    void Isredis init (char *pub, char *re, char *head)

      Initialize this module, that is, set up the connections.

    int lsredis_regexec (const regex_t *preg, lsredis_obj_t *p, size_t nmatch, regmatch_t *pmatch, int eflags)

void lsredis_run ()

    void lsredis_setstr (lsredis_obj_t *p, char *fmt,...)

      Set the value and update redis.

    void <a href="mailto:listimer_add_timer">listimer_add_timer</a> (char *, int, unsigned long int, unsigned long int)

      Create a timer.
· void Istimer init ()
      Initialize the timer list and pthread stuff.
• void Istimer run ()
      Start up our thread.
• void lsupdate_init ()
• void Isupdate run ()

    void md2cmds init ()

      Initialize the md2cmds module.
• void md2cmds run ()
      Start up the thread.

    void pgpmac_printf (char *fmt,...)

      Terminal output routine ala printf.

    void lstest main ()

• int lspmac_est_move_time (double *est_time, int *mmask, lspmac_motor_t *mp_1, int jog_1, char *preset-
  _1, double end_point_1,...)
      Move the motors and estimate the time it'll take to finish the job.
• int lspmac_est_move_time_wait (double move_time, int mmask)
      wait for motion to stop returns non-zero if the wait timed out

    void lsredis_set_preset (char *base, char *preset_name, double dval)

    lsredis_obj_t * _lsredis_get_obj (char *key)

      Maybe add a new object Used internally for this module Must be called with Isredis_mutex locked.
• Ispmac_motor_t * Ispmac_find_motor_by_name (char *name)

    int lsredis_find_preset_index_by_position (lspmac_motor_t *mp)

• void Ispmac_SockSendDPControlChar (char *event, char c)
      use dpram ascii interface to send a control character
```

Variables

```
    lspg_waitcryo_t lspg_waitcryo

     signal the robot

    lspg_getcurrentsampleid_t lspg_getcurrentsampleid

     our currentsample id

    lspg_demandairrights_t lspg_demandairrights

     our demandairrights object

    lspg_getcenter_t lspg_getcenter

     the getcenter object

    lspg_starttransfer_t lspg_starttransfer

     start a sample transfer

    lspg_nextsample_t lspg_nextsample

     the very next sample

    lspg_nextshot_t lspg_nextshot

     the nextshot object

    lspmac_motor_t lspmac_motors []

     All our motors.
• Ispmac_motor_t * omega
     MD2 omega axis (the air bearing)
lspmac_motor_t * alignx
     Alignment stage X.
Ispmac_motor_t * aligny
     Alignment stage Y.
lspmac_motor_t * alignz
     Alignment stage X.

    Ispmac motor t * anal

     Polaroid analyzer motor.
lspmac_motor_t * zoom
     Optical zoom.
Ispmac_motor_t * apery
     Aperture Y.
Ispmac_motor_t * aperz
     Aperture Z.
Ispmac_motor_t * capy
     Capillary Y.
• Ispmac_motor_t * capz
     Capillary Z.
Ispmac_motor_t * scint
     Scintillator Z.
Ispmac_motor_t * cenx
     Centering Table X.
Ispmac_motor_t * ceny
     Centering Table Y.
Ispmac_motor_t * kappa
     Карра.
lspmac_motor_t * phi
     Phi (not data collection axis)

    Ispmac motor t * fshut

     Fast shutter.

    lspmac_motor_t * flight
```

```
Front Light DAC.
Ispmac_motor_t * blight
     Back Light DAC.
• Ispmac motor t * fscint
     Scintillator Piezo DAC.
• Ispmac_motor_t * smart_mag_oo
     Smart Magnet on/off.
• Ispmac motor t * blight ud
     Back light Up/Down actuator.
Ispmac_motor_t * cryo
     Move the cryostream towards or away from the crystal.
Ispmac_motor_t * dryer
     blow air on the scintilator to dry it off
• Ispmac_motor_t * fluo
     Move the fluorescence detector in/out.
lspmac_motor_t * flight_oo
     Turn front light on/off.
• Ispmac_motor_t * blight_f
     Back light scale factor.
lspmac_motor_t * flight_f
     Front light scale factor.
• int lspmac_nmotors
     The number of motors we manage.
lspmac_bi_t * lp_air
     Low pressure air OK.
• lspmac_bi_t * hp_air
     High pressure air OK.

    Ispmac_bi_t * cryo_switch

     that little toggle switch for the cryo
• Ispmac bi t * blight down
     Backlight is down.
lspmac_bi_t * blight_up
     Backlight is up.
Ispmac_bi_t * cryo_back
     cryo is in the back position
lspmac_bi_t * fluor_back
     fluor is in the back position
• lspmac_bi_t * sample_detected
     smart magnet detected sample
lspmac_bi_t * etel_ready
     ETEL is ready.
• Ispmac_bi_t * etel_on
     ETEL is on.
lspmac_bi_t * etel_init_ok
     ETEL initialized OK.
lspmac_bi_t * minikappa_ok
     Minikappa is OK (whatever that means)
lspmac_bi_t * smart_mag_on
     smart magnet is on
lspmac_bi_t * arm_parked
```

(whose arm? parked where?)

```
lspmac_bi_t * shutter_open
     shutter is open (note in pmc says this is a slow input)

    Ispmac bi t * smart mag off

     smart magnet is off
lspmac_bi_t * smart_mag_err
     smart magnet error (coil broken perhaps)
• struct timespec omega_zero_time
     Time we believe that omega crossed zero.
WINDOW * term_output
     place to print stuff out

    WINDOW * term input

     place to put the cursor
• WINDOW * term status
     shutter, lamp, air, etc status
WINDOW * term_status2
     shutter, lamp, air, etc status
pthread_mutex_t ncurses_mutex
     allow more than one thread access to the screen

    pthread_cond_t md2cmds_cond

     condition to signal when it's time to run an md2 command

    pthread_mutex_t md2cmds_mutex

     mutex for the condition
pthread_cond_t md2cmds_pg_cond
• pthread_mutex_t md2cmds_pg_mutex

    pthread_mutex_t pmac_queue_mutex

     manage access to the pmac command queue
• pthread_cond_t pmac_queue_cond
     wait for a command to be sent to PMAC before continuing
pthread_mutex_t lspmac_shutter_mutex
     Coordinates threads reading shutter status.
• pthread_cond_t lspmac_shutter_cond
     Allows waiting for the shutter status to change.

    int lspmac_shutter_state

     State of the shutter, used to detect changes.
int lspmac_shutter_has_opened
     Indicates that the shutter had opened, perhaps briefly even if the state did not change.

    pthread_mutex_t lspmac_moving_mutex

     Coordinate moving motors between threads.

    pthread_cond_t lspmac_moving_cond

     Wait for motor(s) to finish moving condition.

    int lspmac_moving_flags

     Flag used to implement motor moving condition.

    pthread_mutex_t md2_status_mutex

     Synchronize reading/writting status buffer.

    char md2cmds cmd []

     our command;

    Isredis_obj_t * md2cmds_md_status_code

    pthread mutex t Isredis mutex
```

pthread_cond_t lsredis_cond

int lsredis_running

7.12.1 Detailed Description

Headers for the entire pgpmac project.

Date

2012

Author

Keith Brister

Copyright

All Rights Reserved

Definition in file pgpmac.h.

7.12.2 Macro Definition Documentation

7.12.2.1 #define _GNU_SOURCE

Definition at line 7 of file pgpmac.h.

7.12.2.2 #define LS_DISPLAY_WINDOW_HEIGHT 8

Number of status box rows.

Definition at line 57 of file pgpmac.h.

7.12.2.3 #define LS_DISPLAY_WINDOW_WIDTH 24

Number of status box columns.

Definition at line 61 of file pgpmac.h.

7.12.2.4 #define LS_PG_QUERY_STRING_LENGTH 1024

Fixed length postgresql query strings. Queries should all be function calls so this is not as weird as one might think. Definition at line 64 of file pgpmac.h.

7.12.2.5 #define LSEVENTS_EVENT_LENGTH 256

Fixed length for event names: simplifies string handling.

Definition at line 67 of file pgpmac.h.

7.12.2.6 #define MD2CMDS_CMD_LENGTH 32

Definition at line 487 of file pgpmac.h.

7.12.3 Typedef Documentation

7.12.3.1 typedef struct lspg_demandairrights_struct lspg_demandairrights_t

7.12.3.2 typedef struct lspg_getcenter_struct lspg_getcenter_t

Storage for getcenter query Used for the md2 ROTATE command that generates the centering movies.

7.12.3.3 typedef struct lspg_getcurrentsampleid_struct lspg_getcurrentsampleid_t

7.12.3.4 typedef struct lspg_nextsample_struct lspg_nextsample_t

Returns the next sample number Just a 32 bit int (Ha!, take that, nextshot!)

7.12.3.5 typedef struct lspg_nextshot_struct lspg_nextshot_t

Storage definition for nextshot query.

The next shot query returns all the information needed to collect the next data frame. Since SQL allows for null fields independently from blank strings a separate integer is used as a flag for this case. This adds to the program complexity but allows for some important cases. Suck it up.definition of the next image to be taken (and the one after that, too!)

7.12.3.6 typedef struct lspgQueryQueueStruct lspg_query_queue_t

Store each query along with it's callback function.

All calls are asynchronous

7.12.3.7 typedef struct lspg_starttransfer_struct lspg_starttransfer_t

returns 1 if transfer can continue 0 to abort

7.12.3.8 typedef struct lspg waitcryo struct lspg waitcryo t

7.12.3.9 typedef struct lspmac_bi_struct lspmac_bi_t

Storage for binary inputs.

7.12.3.10 typedef struct lspmac_motor_struct lspmac_motor_t

Motor information.

A catchall for motors and motor like objects. Not all members are used by all objects.

7.12.3.11 typedef struct Isredis_obj_struct Isredis_obj_t

Redis Object Basic object whose value is sychronized with our redis db.

7.12.3.12 typedef struct Ispmac_cmd_queue_struct pmac_cmd_queue_t

PMAC command queue item.

Command queue items are fixed length to simplify memory management.

7.12.3.13 typedef struct tagEthernetCmd pmac_cmd_t

PMAC ethernet packet definition.

Taken directly from the Delta Tau documentation.

7.12.4 Function Documentation

```
7.12.4.1 | Isredis_obj_t*_Isredis_get_obj ( char * key )
```

Maybe add a new object Used internally for this module Must be called with Isredis mutex locked.

Definition at line 488 of file Isredis.c.

```
lsredis_obj_t *p;
regmatch_t pmatch[2];
int err;
ENTRY htab_input, *htab_output;
// Dispense with obviously bad keys straight away
// unless p->valid == 0 in which case we call \frac{1}{1} first
// TODO: review logic: is there ever a time when valid is zero for a
    preexisting p and HGET has not been called?
//
         If not then we should just return p without checking for validity.
if( key == NULL || *key == 0 || strchr( key, ' ') != NULL) {
  lslogging_log_message( "_lsredis_get_obj: bad key '%s'
    ", key == NULL ? "<NULL>" : key);
  return NULL;
// If the key is already there then just return it
htab_input.key = key;
htab_input.data = NULL;
errno = 0;
err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab);
if( err == 0)
 p = NULL;
else
 p = htab_output->data;
if( p != NULL) {
  return p;
} else {
  // make a new one.
  p = calloc( 1, sizeof( lsredis_obj_t));
if( p == NULL) {
   lslogging_log_message( "_lsredis_get_obj: Out of
    memory");
    exit(-1);
  err = regexec( &lsredis_key_select_regex, key, 2,
   pmatch, 0);
  if( err == 0 && pmatch[1].rm_so != -1)
   p->events_name = strndup( key+pmatch[1].rm_so, pmatch[1].rm_eo
     - pmatch[1].rm_so);
  } else {
    p->events_name = strdup( key);
  if( p->events_name == NULL) {
    lslogging_log_message( "_lsredis_get_obj: Out of
     memory (events_name)");
    exit(-1);
  pthread_mutex_init( &p->mutex, NULL);
  pthread_cond_init( &p->cond, NULL);
  p->value = NULL;
p->valid = 0;
  lsevents_send_event( "%s Invalid", p->events_name
   );
  p->wait_for_me = 0;
  p->key = strdup( key);
```

```
p->hits = 0;
 htab_input.key = p->key;
 htab_input.data = p;
  errno = 0;
  err = hsearch_r( htab_input, ENTER, &htab_output, &lsredis_htab
  if( err == 0) {
    islogging_log_message( "_lsredis_get_obj: hseach
error on enter. errno=%d", errno);
  // Shouldn't need the linked list unless we need to rebuild the hash table
     when, for example, we run out of room.
  // TODO: resize hash table when needed.
 p->next = lsredis_objs;
  lsredis_objs = p;
// We arrive here with the valid flag lowered. Go ahead and request the
     latest value.
redisAsyncCommand( roac, lsredis_hgetCB, p, "HGET %s VALUE"
return p;
```

7.12.4.2 void lsevents_add_listener (char * event, void(*)(char *) cb)

Add a callback routine to listen for a specific event.

Parameters

event	the name of the event to listen for
cb	the routine to call

Definition at line 72 of file Isevents.c.

```
lsevents_listener_t *new;
int err;
char *errbuf;
int nerrbuf;
new = calloc( 1, sizeof( lsevents_listener_t));
if ( new == NULL) {
  lslogging_log_message( "lsevents_add_listener: out of
  memory");
  exit( -1);
err = regcomp( &new->re, event, REG_EXTENDED | REG_NOSUB);
if ( err != 0) {
  nerrbuf = regerror( err, &new->re, NULL, 0);
  errbuf = calloc( nerrbuf, sizeof( char));
  if( errbuf == NULL) {
    lslogging_log_message( "lsevents_add_listener: out
  of memory (re)");
    exit( -1);
  regerror( err, &new->re, errbuf, nerrbuf);
lslogging_log_message( "lsevents_add_listener: %s",
    errbuf);
  free( errbuf);
free( new);
  return;
new->raw_regexp = strdup( event);
new->cb = cb;
pthread_mutex_lock( &lsevents_listener_mutex);
new->next = lsevents_listeners_p;
```

```
lsevents_listeners_p = new;
pthread_mutex_unlock( &lsevents_listener_mutex);

lslogging_log_message( "lsevents_add_listener: added listener for event %s", event);
}
```

7.12.4.3 void lsevents_init ()

Initialize this module.

Definition at line 211 of file Isevents.c.

```
pthread_mutex_init( &lsevents_queue_mutex, NULL);
pthread_cond_init( &lsevents_queue_cond, NULL);
pthread_mutex_init( &lsevents_listener_mutex, NULL);
}
```

7.12.4.4 void Isevents_remove_listener (char * event, void(*)(char *) cb)

Remove a listener previously added with Isevents_add_listener.

Parameters

event	The name of the event
cb	The callback routine to remove

Definition at line 117 of file Isevents.c.

```
lsevents_listener_t *last, *current;
// Find the listener to remove
// and unlink it from the list
pthread_mutex_lock( &lsevents_listener_mutex);
for( current = lsevents_listeners_p; current != NULL;
  current = current->next) {
if( strcmp( last->raw_regexp, event) == 0 && last->cb == cb) {
    if ( last == NULL) {
     lsevents_listeners_p = current->next;
     last->next = current->next;
    break:
  }
pthread_mutex_unlock( &lsevents_listener_mutex);
//
// Now remove it
if ( current != NULL) {
 if( current->raw_regexp != NULL)
    free( current->raw_regexp);
  free(current);
```

7.12.4.5 void Isevents_run ()

Start up the thread and get out of the way.

Definition at line 219 of file Isevents.c.

```
pthread_create( &lsevents_thread, NULL, lsevents_worker
    , NULL);
```

7.12.4.6 void Isevents_send_event (char * fmt, ...)

Call the callback routines for the given event.

Parameters

fmt	a printf style formating string
	list of arguments specified by the format string

Definition at line 45 of file Isevents.c.

7.12.4.7 void Islogging_init ()

Initialize the Islogging objects.

Definition at line 37 of file Islogging.c.

7.12.4.8 void lslogging_log_message (char * fmt, ...)

The routine everyone will be talking about.

Parameters

fmt	A printf style formating string.
	The arguments specified by fmt

Definition at line 48 of file Islogging.c.

```
char msg[LSLOGGING_MSG_LENGTH];
struct timespec theTime;
va_list arg_ptr;
unsigned int on;
clock_gettime( CLOCK_REALTIME, &theTime);
va_start( arg_ptr, fmt);
vsnprintf( msg, sizeof(msg)-1, fmt, arg_ptr);
va_end( arg_ptr);
msg[sizeof(msg)-1]=0;
pthread_mutex_lock( &lslogging_mutex);
on = (lslogging_on++) % LSLOGGING_QUEUE_LENGTH
strncpy( lslogging_queue[on].lmsg, msg, LSLOGGING_MSG_LENGTH
      - 1);
{\tt lslogging\_queue[on].lmsg[LSLOGGING\_MSG\_LENGTH]}
    -1] = 0;
memcpy( &(lslogging_queue[on].ltime), &theTime, sizeof(theTime
    ));
pthread_cond_signal( &lslogging_cond);
pthread_mutex_unlock( &lslogging_mutex);
```

7.12.4.9 void Islogging_run ()

Start up the worker thread.

Definition at line 114 of file Islogging.c.

7.12.4.10 char** lspg_array2ptrs (char *)

returns a null terminated list of strings parsed from postgresql array

Definition at line 160 of file lspg.c.

```
mxsz = strlen(a) + 1;
// This is the accumulation string to make up the array elements
acums = (char *)calloc( mxsz, sizeof( char));
if ( acums == NULL) {
  lslogging_log_message( "lspg_array2ptrs: out of memory
     (acums)");
  exit(1);
\ensuremath{//} allocate storage for the pointer array and the null terminator
rtn = (char **)calloc( n+1, sizeof( char *));
if( rtn == NULL) {
 exit( 1);
rtni = 0;
// Go through and create the individual strings
sp = acums;
*sp = 0;
inquote = 0;
havebackslash = 0;
for( i=1; a[i] != 0; i++) {
  switch( a[i]) {
case '"':
     ...vebackslash) {
// a quoted quote. Cool
//
    if( havebackslash) {
      *(sp++) = a[i];
      *sp = 0;
      havebackslash = 0;
    } else {
      // Toggle the flag
      inquote = 1 - inquote;
    break;
  case '\\':
    if( havebackslash) {
     *(sp++) = a[i];
      *sp = 0;
     havebackslash = 0;
    } else {
     havebackslash = 1;
    break;
    if( inquote || havebackslash) {
     *(sp++) = a[i];
*sp = 0;
      havebackslash = 0;
      rtn[rtni++] = strdup( acums);
      sp = acums;
    break:
    if( inquote || havebackslash) {
     *(sp++) = a[i];
*sp = 0;
      havebackslash = 0;
    } else {
      rtn[rtni++] = strdup(acums);
rtn[rtni] = NULL;
      free( acums);
      return( rtn);
    break;
  default:
   *(sp++) = a[i];
    *sp = 0;
    havebackslash = 0;
// Getting here means the final '}' was missing
// Probably we should throw an error or log it or something.
\ensuremath{//} Through out the last entry since this there is not resonable expectation
     that
```

```
\ensuremath{//} we should be parsing it anyway.
  rtn[rtni] = NULL;
  free( acums);
  return( rtn);
7.12.4.11 void lspg_demandairrights_all ( )
do nothing until we get airrights
Definition at line 655 of file lspg.c.
   lspg_demandairrights_call();
  lspg_demandairrights_wait();
// there is no "done" version
7.12.4.12 void lspg_getcenter_call ( )
Request a getcenter query.
Definition at line 1276 of file Ispg.c.
  pthread_mutex_lock( &lspg_getcenter.mutex);
lspg_getcenter.new_value_ready = 0;
  pthread_mutex_unlock( &lspg_getcenter.mutex);
  lspg_query_push( lspg_getcenter_cb, "SELECT *
    FROM px.getcenter2()");
7.12.4.13 void lspg_getcenter_done ( )
Done with getcenter query.
Definition at line 1294 of file lspg.c.
  pthread_mutex_unlock( &(lspg_getcenter.mutex));
7.12.4.14 void lspg_getcenter_wait ( )
Wait for a getcenter query to return.
Definition at line 1286 of file lspg.c.
  pthread_mutex_lock( &(lspg_getcenter.mutex));
while( lspg_getcenter.new_value_ready == 0)
   pthread_cond_wait( &(lspg_getcenter.cond), &(
        lspg_getcenter.mutex));
```

7.12.4.15 void lspg_getcurrentsampleid_wait_for_id (unsigned int test)

Definition at line 492 of file lspg.c.

```
pthread_mutex_lock( &lspg_getcurrentsampleid.mutex
    );
while( lspg_getcurrentsampleid.getcurrentsampleid
    != test)
pthread_cond_wait( &lspg_getcurrentsampleid.cond
    , &lspg_getcurrentsampleid.mutex);

pthread_mutex_unlock( &lspg_getcurrentsampleid.mutex
    );
```

7.12.4.16 void lspg_init()

Initiallize the Ispg module.

Definition at line 1951 of file lspg.c.

```
pthread_mutex_init( &lspg_queue_mutex, NULL);
pthread_cond_init( &lspg_queue_cond, NULL);

lspg_demandairrights_init();
lspg_getcenter_init();
lspg_getcurrentsampleid_init();
lspg_lock_detector_init();
lspg_lock_diffractometer_init();
lspg_nextsample_init();
lspg_nextshot_init();
lspg_seq_run_prep_init();
lspg_seq_run_prep_init();
lspg_starttransfer_init();
lspg_wait_for_detector_init();
lspg_wait_roy_init();
```

7.12.4.17 unsigned int lspg_nextsample_all (int * err)

Definition at line 567 of file lspg.c.

```
unsigned int rtn;
lspg_nextsample_call();
lspg_nextsample_wait();

if( lspg_nextsample.no_rows_returned) {
   rtn = 0;
   *err = 1;
} else {
   if( lspg_nextsample.nextsample_isnull) {
      rtn = 0;
      *err = 1;
} else {
      rtn = lspg_nextsample.nextsample;
      *err = 0;
}
} lspg_nextsample_done();
return rtn;
```

7.12.4.18 void lspg_nextshot_call ()

Queue up a nextshot query.

Definition at line 923 of file lspg.c.

7.12.4.19 void lspg_nextshot_done ()

Called when the next shot query has been processed.

Definition at line 941 of file lspg.c.

```
pthread_mutex_unlock( &(lspg_nextshot.mutex));
}
```

7.12.4.20 void lspg_nextshot_wait ()

Wait for the next shot query to get processed.

Definition at line 933 of file lspg.c.

```
pthread_mutex_lock( &(lspg_nextshot.mutex));
while( lspg_nextshot.new_value_ready == 0)
pthread_cond_wait( &(lspg_nextshot.cond), &(lspg_nextshot.mutex));
```

7.12.4.21 void lspg_query_push (void(*)(lspg_query_queue_t *, PGresult *) cb, char * fmt, ...)

Place a query on the queue.

Parameters

in	cb	Our callback function that deals with the response
in	fmt	Printf style function to generate the query

Definition at line 127 of file Ispg.c.

```
int idx;
va_list arg_ptr;
pthread_mutex_lock( &lspg_queue_mutex);

//
// Pause the thread while we service the queue
//
while( (lspg_query_queue_on + 1) %
        LS_PG_QUERY_QUEUE_LENGTH == lspg_query_queue_off %
        LS_PG_QUERY_QUEUE_LENGTH) {
    pthread_cond_wait( &lspg_queue_cond, &lspg_queue_mutex
    );
}

idx = lspg_query_queue_on % LS_PG_QUERY_QUEUE_LENGTH
    ;

va_start( arg_ptr, fmt);
vsnprintf( lspg_query_queue[idx].qs,
        LS_PG_QUERY_STRING_LENGTH-1, fmt, arg_ptr);
va_end( arg_ptr);

lspg_query_queue[idx].qs[LS_PG_QUERY_STRING_LENGTH
```

```
- 1] = 0;
lspg_query_queue[idx].onResponse = cb;
lspg_query_queue_on++;
pthread_kill( lspg_thread, SIGUSR1);
pthread_mutex_unlock( &lspg_queue_mutex);
;
```

7.12.4.22 void lspg_run ()

Start 'er runnin'.

Definition at line 1970 of file lspg.c.

7.12.4.23 void lspg_seq_run_prep_all (long long *skey*, double *kappa*, double *phi*, double *cx*, double *cy*, double *ax*, double *ay*, double *az*)

Convinence function to call seq run prep.

Parameters

in	skey	px.shots key for this image
in	kappa	current kappa postion
in	phi	current phi postition
in	CX	current center table x
in	су	current center table y
in	ax	current alignment table x
in	ay	current alignment table y
in	az	current alignment table z

Definition at line 1194 of file lspg.c.

7.12.4.24 void lspg_starttransfer_call (unsigned int *nextsample*, int *sample_detected*, double *ax*, double *ay*, double *az*, double *horz*, double *vert*, double *esttime*)

Definition at line 401 of file lspg.c.

```
pthread_mutex_lock( &(lspg_starttransfer.mutex));
  lspg_starttransfer.new_value_ready = 0;
  pthread_mutex_unlock( &(lspg_starttransfer.mutex));
  lspg_query_push( lspg_starttransfer_cb, "
      SELECT px.starttransfer( %d, %d, %.3f, %.3f, %.3f, %.3f, %.3f, %.3f",
                   nextsample, sample_detected, ax, ay, az, horz
      , vert, esttime);
7.12.4.25 void lspg_starttransfer_done ( )
Definition at line 416 of file lspg.c.
 pthread_mutex_unlock( &(lspg_starttransfer.mutex));
7.12.4.26 void lspg_starttransfer_wait ( )
Definition at line 410 of file lspg.c.
  pthread_mutex_lock( &(lspg_starttransfer.mutex));
  while( lspg_starttransfer.new_value_ready ==
       0)
    pthread_cond_wait( &(lspg_starttransfer.cond), &(
   lspg_starttransfer.mutex));
7.12.4.27 void lspg_waitcryo_all ( )
no need to get fancy with the wait cryo command It should not return until the robot is almost ready for air rights
Definition at line 606 of file lspg.c.
  pthread_mutex_lock( &lspg_waitcryo.mutex);
  lspg_waitcryo.new_value_ready = 0;
  lspg_query_push( lspg_waitcryo_cb, "SELECT
       px.waitcryo())");
  while( lspg_waitcryo.new_value_ready == 0)
    pthread_cond_wait( &lspg_waitcryo.cond, &lspg_waitcryo
  pthread_mutex_unlock( &lspg_waitcryo.mutex);
7.12.4.28 void lspg_waitcryo_cb ( lspg_query_queue_t * qqp, PGresult * pgr )
Definition at line 596 of file lspg.c.
  pthread_mutex_lock( &lspg_waitcryo.mutex);
  lspg_waitcryo.new_value_ready = 1;
  pthread_cond_signal( &lspg_waitcryo.cond);
  pthread_mutex_unlock( &lspg_waitcryo.mutex);
```

```
7.12.4.29 void lspg_zoom_lut_call ( )
7.12.4.30 void lspmac_abort ( )
```

abort motion and try to recover

Definition at line 2031 of file Ispmac.c.

7.12.4.31 int lspmac_est_move_time (double * est_time, int * mmask, lspmac_motor_t * mp_1, int jog_1, char * preset_1, double end_point_1, ...)

Move the motors and estimate the time it'll take to finish the job.

Returns the estimate time and the coordinate system mask to waite for

Parameters

est_time	Returns number of seconds we estimate the move(s) will take
mmask	Mask of coordinate systems we are trying to move, excluding jogs. Used to wait for motions to
	complete
mp_1	Pointer to first motor
jog_1	1 to force a jog, 0 to try a motion program DO NOT MIX JOGS AND MOTION PROGRAMS IN
	THE SAME COORDINATE SYSTEM!
preset_1	Name of preset we'd like to move to or NULL if end_point_1 should be used instead
end_point_1	End point for the first motor. Ignored if preset_1 is non null and identifies a valid preset for this
	motor
	Perhaps more quads of motors, jog flags, preset names, and end points. End is a NULL motor
	pointer MUST END ARG LIST WITH NULL

- < units to counts
- < The total distance we need to go
- < Our maximum velocity
- < Our maximum acceleration
- < Total time for this motor
- < coordinate system motion flags

Definition at line 2650 of file Ispmac.c.

```
static char axes[] = "XYZUVWABC";
static int qs[9];
static lspmac_combined_move_t motions[32];

int j;
va_list arg_ptr;
lspmac_motor_t *mp;
double ep, maybe_ep;
char *ps;
double
min_pos,
max_pos,
neutral_pos,
u2c,
D,
```

```
V,
  A,
 Tt;
int err;
int jog;
int i:
int m5075;
// reset our coordinate flags and command strings
for( i=0; i<32; i++) {</pre>
 motions[i].moveme = 0;
m5075 = 0;
// Initialze first iteration
//
*est\_time = 0.0;
mp = mp_1;
ps = preset_1;
ep = end_point_1;
jog = jog_1;
va_start( arg_ptr, end_point_1);
while(1) {
                                      Constant
                                      Velocity
                                      Time (Ct)
      e :
      0
      С
      i :
      t :
      y :_
                  -->I
                             |<-- Acceleration Time (At)</pre>
                                 Total Time (Tt) ---->|
          Assumption 1: We can replace S curve acceleration with linear
     acceleration
          for the purposes of distance and time calculations for the timeout
          period that we are attempting to calculate here.
          Ct = Constant Velocity Time. The time spent at constant velocity.
          At = Acceleration Time. Time spent accelerating at either end of
     the ramp, that is,
          1/2 the total time spent accelerating and decelerating.
          D = the total distance we need to travel
          {\tt V} = {\tt constant} \ {\tt velocity}. \ {\tt Here} \ {\tt we} \ {\tt use} \ {\tt the} \ {\tt motor's} \ {\tt maximum} \ {\tt velocity}.
          A = the motor acceleration, Here it's the maximum acceleration.
          V = A * At
          or At = V/A
          The Total Time (Tt) is
          Tt = Ct + 2 * At
          If we had infinite acceleration the total time would be \ensuremath{\text{D/V}}. To
     account for finite acceleration we just need to
          adjust this for the average velocity while accelerating (0.5 \forall).
     This neatly adds a single V/A term:
                 Tt = D/V + V/A
           When the distance is short, we need a different calculation:
          D = 0.5 * A * T1^2 + 0.5 * A * T2^2 (T1 = acceleration time and
     T2 = deceleration time)
           or, since total time Tt = T1 + T2 and T1 = T2,
          D = A * (0.5*Tt)^2
```

```
Tt = 2 * sqrt(D/A)
        (2)
        When we accelerate to the maximum speed the time it takes is V/A so
   the distance we travel (Da) is
        Da = 0.5 * A * (V/A)^2
       Da = 0.5 * V^2 / A
       So when D > 2 * Da, or
       D > V^2 / A
        we need to use equation (1) otherwise we need to use equation (2)
Tt = 0.0;
if( mp != NULL && mp->max_speed != NULL && mp->max_accel
 != NULL && mp->u2c != NULL) {
 // \ensuremath{//} get the real endpoint if a preset was mentioned
  if( ps != NULL && *ps != 0) {
   err = lsredis_find_preset( mp->name, ps, &
  maybe_ep);
    if( err != 0)
     ep = maybe_ep;
 u2c = lsredis_getd( mp->u2c);
  if( u2c <= 0.0)</pre>
    continue;
  ^{\prime\prime} // For look up tables user units are (or should be) counts and u2c should
  be 1
  if ( mp->nlut > 0 && mp->lut != NULL) {
   u2c = 1.0;
  D = lspmac_lut( mp->nlut, mp->lut, ep) - lspmac_lut( mp->nlut, mp->lut, lspmac_getPosition( mp));
  } else {
   D = ep - lspmac_getPosition( mp);
  // User units
 V = lsredis_getd( mp->max_speed) / u2c * 1000.;
  // User units per second
  A = lsredis_getd( mp->max_accel) / u2c * 1000. *
  1000;
             // User units per second per second
 neutral_pos = lsredis_getd( mp->neutral_pos);
min_pos = lsredis_getd( mp->min_pos) - neutral_pos
           = lsredis_getd( mp->max_pos) - neutral_pos
  max_pos
  if( ep < min_pos || ep > max_pos) {
   lslogging_log_message( "lspmac_est_move_time:
   Motor %s Requested position %f out of range: min=%f, max=%f", mp->name, ep,
  min_pos, max_pos);
   lsevents_send_event( "%s Move Aborted", mp->name
   return 1;
  }
  // Don't bother with motors without velocity or acceleration defined
  if( V > 0.0 && A > 0.0) {
    if( fabs(D) > V*V/A) {
      // Normal ramp up, constant velocity, and ramp down
      Tt = fabs(D)/V + V/A;
    } else {
```

```
// Never reach constantant velocity, just ramp up a bit and back down
    Tt = 2.0 * sqrt(fabs(D)/A);
  }
 lslogging_log_message( "lspmac_est_move_time:
Motor: %s D: %f VV/A: %f Tt: %f", mp->name, D, V*V/A, Tt);
  // TODO: insert move time based for DAC or BO motor like objects;
  // For now assume 100 msec;
  Tt = 0.1;
// Perhaps flag a coordinate system
// We can move a motor that's not in a coordinate system but we cannot
 move a motor that is but does not
// have an axis defined if we are also moving one that does. It's a
 limitation, I guess.
if ( jog != 1 &&
    mp->coord_num != NULL && lsredis_getl( mp->
coord_num) > 0 && lsredis_getl( mp->coord_num) <=</pre>
    mp->motor_num != NULL && lsredis_getl( mp->
motor_num) > 0 && mp->axis != NULL && lsredis_getc( mp
->axis) != 0) {
  int axis:
  int motor num:
  motor_num = lsredis_get1( mp->motor_num);
  axis = lsredis_getc( mp->axis);
  for( j=0; j<sizeof(axes); j++) {
  if( axis == axes[j])</pre>
      break;
  if( j < sizeof( axes)) {</pre>
    // Store the motion request for a normal PMAC motor
    int cn;
    int in_position_band;
    cn = lsredis_getl( mp->coord_num);
    in_position_band = lsredis_get1( mp->in_position_band
);
    motions[motor_num - 1].coord_num = cn;
motions[motor_num - 1].axis = j;
    motions[motor_num - 1].Delta
                                         = D * u2c;
     ^{\prime\prime} // Don't ask to run a motion program if we are already where we want
 to be
     // Deadband is 10 counts except for zoom which is 100.
    // We use Ixx28 In-Position Band which has units of 1/16 count
    if( abs(motions[motor_num - 1].Delta)*16 >= in_position_band) {
      m5075 |= 1 << (cn - 1);
motions[motor_num - 1].moveme
    }
} else {
  ^{\prime\prime} // Here we are dealling with a DAC or BO motor or just want to jog.
  if( mp->jogAbs( mp, ep)) {
    lslogging_log_message( "lspmac_est_move_time:
 motor %s failed to queue move of distance %f from %f", mp->name, D,
lspmac_getPosition(mp));
    lsevents_send_event( "Move Aborted");
    return 1;
  }
// Update the estimated time
*est_time = *est_time < Tt ? Tt : *est_time;
lslogging_log_message( "lspmac_est_move_time:
    est_time=%f", *est_time);
```

```
}
  mp = va_arg( arg_ptr, lspmac_motor_t *);
  if ( mp == NULL)
   break;
  jog = va_arg( arg_ptr, int);
 ps = va_arg( arg_ptr, char *);
ep = va_arg( arg_ptr, double);
va_end( arg_ptr);
// Call the motion program(s)
 char s[256];
  int foundone;
  int err;
  int moving_flags;
  struct timespec timeout;
  if ( m5075 != 0) {
    *mmask |= m5075; // Tell the caller about our new mask
    pthread_mutex_lock( &lspmac_moving_mutex);
    if( (lspmac_moving_flags & m5075) != m5075)
      lspmac_SockSendDPline( NULL, "M5075=(M5075 | %d)",
     m5075);
    clock_gettime( CLOCK_REALTIME, &timeout);
    timeout.tv_sec += 2;
                                 // 2 seconds should be more than enough time to
     set the flags
    err = 0;
    while( err == 0 && (lspmac_moving_flags & m5075) !=
    m5075)
     err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
moving_flags = lspmac_moving_flags;
    pthread_mutex_unlock( &lspmac_moving_mutex);
    if( err == ETIMEDOUT) {
       lslogging_log_message( "lspmac_est_move_time:
     Timed out waiting for moving flags. lspmac_moving_flags = %0x", moving_flags); lsevents_send_event( "%s Move Aborted Combined
     Motors");
      return 1;
    }
  for( i=1; i<=16; i++) {</pre>
    //
// Loop over coordinate systems
    foundone = 0;
    for( j=0; j<9; j++)
  qs[j] = 0;</pre>
    for( j=0; j<31; j++) {</pre>
       // Loop over motors
      if( motions[j].moveme && motions[j].coord_num == i) {
        if( abs(motions[j].Delta) > 0) {
   qs[(int)(motions[j].axis)] = motions[j].Delta;
           foundone=1:
        }
      }
    if( foundone) {
    sprintf( s, "&%d Q40=%d Q41=%d Q42=%d Q43=%d Q44=%d Q45=%d Q46=%d
     Q47=%d Q48=%d Q49=%.1f Q100=%d B180R",
    i, qs[0], qs[1], qs[2], qs[3], qs[4], qs[5], qs[6], qs[7], qs[8], *est_time * 1000., 1 << (i-1));
      lspmac_SockSendDPline( NULL, s);
    }
return 0;
```

7.12.4.32 int lspmac_est_move_time_wait (double move_time, int mmask)

wait for motion to stop returns non-zero if the wait timed out

Parameters

move_time	The time out in seconds
mmask	A coordinate system mask to wait for

Both values are returned from Ispmac est move time

Definition at line 2983 of file Ispmac.c.

Definition at line 3962 of file Ispmac.c.

7.12.4.34 int lspmac_getBIPosition (lspmac_bi_t *)

get binary input value

Definition at line 1598 of file Ispmac.c.

{

```
int rtn;
pthread_mutex_lock( &bip->mutex);
rtn = bip->position;
pthread_mutex_unlock( &bip->mutex);
return rtn;
```

7.12.4.35 double $lspmac_getPosition$ ($lspmac_motor t * mp$)

get the motor position (with locking)

Parameters

mp the motor object

Definition at line 1355 of file Ispmac.c.

```
double rtn;
pthread_mutex_lock( &(mp->mutex));
rtn = mp->position;
pthread_mutex_unlock( &(mp->mutex));
return rtn;
```

7.12.4.36 void lspmac_home1_queue (lspmac_motor_t * mp)

Home the motor.

Parameters

```
in mp motor we are concerned about
```

Definition at line 1221 of file Ispmac.c.

```
int i:
int motor num;
int coord_num;
pthread_mutex_lock( &(mp->mutex));
motor_num = lsredis_getl( mp->motor_num);
coord_num = lsredis_getl( mp->coord_num);
           = lsredis_get_string_array( mp->home);
// Each of the motors should have this defined
// but let's not seg fault if home is missing
if ( home == NULL | | *home == NULL) {
  // Note we are already initialized
  \ensuremath{//} so if we are here there is something wrong.
  lslogging_log_message( "lspmac_home1_queue: null or
     empty home strings for motor %s", mp->name);
  pthread_mutex_unlock( & (mp->mutex));
// We've already been called. Don't home again until // we're finish with the last time.
if( mp->homing) {
  pthread_mutex_unlock( & (mp->mutex));
  return;
//
```

```
// Don't go on if any other motors in this coordinate system are homing.
// It's possible to write the homing program to home all the motors in the
     coordinate
// system. TODO (hint hint)
if( coord_num > 0) {
  for( i=0; i<lspmac_nmotors; i++) {</pre>
    if( &(lspmac_motors[i]) == mp)
      continue;
    if( lsredis_getl(lspmac_motors[i].coord_num) ==
    coord_num) {
      int nogo;
      nogo = 0;
      pthread_mutex_lock( &(lspmac_motors[i].mutex));
       // Don't go on if
      //
            we are homing
                                    or
                                             ( not in position
     while
              in open loop)
       if( lspmac_motors[i].homing || (((lspmac_motors
     [i].status2 & 0x01)==0) && ((lspmac_motors[i].status1 & 0x040000)
    != 0)))
        nogo = 1:
      pthread_mutex_unlock( &(lspmac_motors[i].mutex));
       if( nogo) {
        pthread_mutex_unlock( & (mp->mutex));
         return;
      }
    }
  }
mp->homing
mp->not_done = 1;
                        // set up waiting for cond
mp->motion_seen = 0;
// This opens the control loop.
// The status routine should notice this and the fact that
// the homing flag is set and call on the home2 routine
// Only send the open loop command if we are not in
// open loop mode already. This test might prevent a race condition // where we've already moved the home2 routine (and queue the homing program
     motion)
// before the open loop command is dequeued and acted on.
if( ~(mp->status1) & 0x040000) {
  lspmac_SockSendDPline( mp->name, "#%d$*",
    motor_num);
pthread_mutex_unlock( & (mp->mutex));
lsevents_send_event( "%s Homing", mp->name);
```

7.12.4.37 void lspmac_home2_queue (lspmac_motor_t * mp)

Second stage of homing.

Parameters

in	тр	motor we are concerned about

Definition at line 1309 of file Ispmac.c.

```
char **spp;
char **home;

//
// At this point we are in open loop.
// Run the motor specific commands
//
pthread_mutex_lock( &(mp->mutex));
home = lsredis_get_string_array( mp->home);
```

```
// We don't have any motors that have a null home text array so
// there is currently no need to worry about this case other than
// not to seg fault
// Also, Only go on if the first homing phase has been started
if( home == NULL || mp->homing != 1) {
 pthread_mutex_unlock( &(mp->mutex));
  return;
}
for( spp = home; *spp != NULL; spp++) {
  pthread_mutex_lock( &ncurses_mutex);
  wprintw( term_output, "home2 is queuing '%s'\n", *spp);
  wnoutrefresh( term_output);
  doupdate();
  pthread_mutex_unlock( &ncurses_mutex);
  lspmac_SockSendDPline( mp->name, *spp);
mp->homing = 2;
pthread_mutex_unlock( & (mp->mutex));
```

7.12.4.38 void Ispmac_init (int, int)

Initialize this module.

Definition at line 3534 of file Ispmac.c.

```
{
int i:
int err:
ENTRY entry_in, *entry_outp;
md2_status_t *p;
pthread_mutexattr_t mutex_initializer;
// Set our global harvest flags
getivars = ivarsflag;
getmvars = mvarsflag;
// Use recursive mutexs
pthread_mutexattr_init( &mutex_initializer);
\verb|pthread_mutexattr_settype| ( &mutex_initializer, PTHREAD_MUTEX_RECURSIVE); \\
// All important status mutex
pthread_mutex_init( &md2_status_mutex, &mutex_initializer);
// Get the MD2 initialization strings
    lspmac_md2_init = lsredis_get_obj( "md2_pmac.init"); // hard coded now.
// Initialize the motor objects
p = &md2_status;
omega = lspmac_motor_init( &(lspmac_motors
     [ 0]), 0, 0, &p->omega_act_pos, &p->omega_status_1, &p->omega_status_2, "Omega #1 &1 X", "omega",
     lspmac_moveabs_queue, lspmac_jogabs_queue
     );
alignx = lspmac_motor_init( &(lspmac_motors
    [ 1]), 0, 1, &p->alignx_act_pos, &p->alignx_status_1 , &p->alignx_status_2, "Align X #2 &3 X", "align.x",
     lspmac_moveabs_queue, lspmac_jogabs_queue
);
aligny = lspmac_motor_init( &(lspmac_motors
     [ 2]), 0, 2, &p->aligny_act_pos, &p->aligny_status_1
, &p->aligny_status_2, "Align Y #3 &3 Y", "align.y",
     lspmac_moveabs_queue, lspmac_jogabs_queue
);
alignz = lspmac_motor_init( &(lspmac_motors
[ 3]), 0, 3, &p->alignz_act_pos, &p->alignz_status_1
, &p->alignz_status_2, "Align Z #4 &3 Z", "align.z",
```

```
);
anal = lspmac_motor_init( &(lspmac_motors
    [ 4]), 0, 4, &p->analyzer_act_pos, &p->analyzer_status_1, &p->analyzer_status_2, "Anal #5", "lightPolar
                                                             "lightPolar",
     lspmac_moveabs_queue, lspmac_jogabs_queue
coom = lspmac_motor_init( &(lspmac_motors)
    [5]), 1, 0, &p->zoom_act_pos, &p->zoom_status_1, &p->zoom_status_2, "Zoom #6 &4 Z", "cam.zoom",
     lspmac_movezoom_queue, lspmac_movezoom_queue
);
apery = lspmac_motor_init( &(lspmac_motors
    [ 6]), 1, 1, &p->aperturey_act_pos, &p->aperturey_status_1, &p->aperturey_status_2, "Aper Y #7 &5 Y", "appy",
     lspmac_moveabs_queue, lspmac_jogabs_queue
);
aperz = lspmac_motor_init( &(lspmac_motors
    [ 7]), 1, 2, &p->aperturez_act_pos, &p->aperturez_status_1, &p->aperturez_status_2, "Aper Z #8 &5 Z", "appz",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    );
y = lspmac_motor_init( &(lspmac_motors
y = ot pos, &p-)
    [ 8]), 1, 3, &p->capy_act_pos, &p->capy_status_1, &p->capy_status_2, "Cap Y #9 &5 U", "capy",
     lspmac_moveabs_queue, lspmac_jogabs_queue
);
capz = lspmac_motor_init( &(lspmac_motors
    [ 9]), 1, 4, &p->capz_act_pos, &p->capz_status_1, &p->capz_status_2, "Cap Z #10 &5 V", "capz",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    scint
    [10]), 2, 0, &p->scint_act_pos, &p->scint_status_1, &p->scint_status_2, "Scin Z #11 &5 W", "scint",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    cenx
    [11]), &p->centerx_act_pos, &p->centerx_status_1
, &p->centerx_status_2, "Cen X #17 &2 X", "centering.x",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    [12]), 2, 2, &p->centery_act_pos, &p->centery_status_1
, &p->centery_status_2, "Cen Y #18 &2 Y", "centering.y",
     lspmac_moveabs_queue, lspmac_jogabs_queue
);
kappa = lspmac_motor_init( &(lspmac_motors
    [13]), 2, 3, &p->kappa_act_pos, &p->kappa_status_1, &p->kappa_status_2, "Kappa #19 &7 X", "kappa",
     lspmac_moveabs_queue, lspmac_jogabs_queue
    14]), 2, 4, &p->phi_act_pos, &p->phi_status_1, &p->phi_status_2, "Phi #20 &7 Y", "phi",
     lspmac_moveabs_queue, lspmac_jogabs_queue
fshut = lspmac_fshut_init( &(lspmac_motors
    [15]));
flight = lspmac_dac_init( &(lspmac_motors[1
    6]), &p->front_dac, "M1200", "frontLight.intensity",
     lspmac_movedac_queue);
blight = lspmac_dac_init( &(lspmac_motors[1
     7]), &p->back_dac,
                               "M1201", "backLight.intensity",
     lspmac_movedac_queue);
fscint = lspmac_dac_init( &(lspmac_motors[1
   8]), &p->scint_piezo, "M1203", "scint.focus",
     lspmac_movedac_queue);
smart_mag_oo = lspmac_bo_init( &(lspmac_motors
[19]), "smartMagnet", "M1100=%d", &(md2_status.acc11c_5), 0x01)
    ,
ght_ud = lspmac_bo_init( &(lspmac_motors
[20]), "backLight", "M1101=%d", &(md2_status.acc11c_5), 0x02)
blight ud
               = lspmac_bo_init( &(lspmac_motors
    [21]), "cryo",
                              "M1102=%d", &(md2_status.acc11c_5), 0x04)
              = lspmac_bo_init( &(lspmac_motors dryer", "M1103=%d", &(md2_status.acc11c_5), 0x08)
    [22]), "dryer",
    [23]), "fluo",
                              "M1104=%d", & (md2_status.acc11c_5), 0x10)
    ,
ght_oo = lspmac_soft_motor_init( &(
lspmac_motors[24]), "frontLight",
flight_oo
     lspmac_moveabs_frontlight_oo_queue);
```

```
blight_f
                 = lspmac_soft_motor_init( &(
     lspmac_motors[25]), "backLight.factor",
     lspmac_moveabs_blight_factor_queue);
    ght_f = lspmac_soft_motor_init( &(
lspmac_motors[26]), "frontLight.factor",
flight_f
     lspmac_moveabs_flight_factor_queue);
                   = lspmac_bi_init( &(lspmac_bis[
     0]), &(md2_status.acc11c_1), 0x01, "Low Pressure Air OK", "
    Low Pressure Air Failed");
     ir = lspmac_bi_init( &(lspmac_bis[
1]), &(md2_status.acc11c_1), 0x02, "High Pressure Air OK", "
hp_air
     High Pressure Air Failed");
cryo_switch
                   = lspmac_bi_init( &(lspmac_bis
     [ 2]), &(md2_status.acc11c_1), 0x04, "CryoSwitchChanged",
     "CryoSwitchChanged");
     ht_down = lspmac_bi_init( &(lspmac_bis
[ 3]), &(md2_status.accllc_1), 0x08, "Backlight Down",
blight_down
     "Backlight Not Down");
                   = lspmac_bi_init( &(lspmac_bis
blight_up
     [ 4]), &(md2_status.acc11c_1), 0x10, "Backlight Up",
     "Backlight Not Up");
cryo_back = lspmac_bi_init( & (lspmac_bis
      [ 5]), & (md2_status.accllc_1), 0x40, "Cryo Back",
     "Cryo Not Back");
fluor_back
                = lspmac_bi_init( &(lspmac_bis
     [ 6]), &(md2_status.acc11c_2), 0x01, "Fluor. Det. Parked",
     "Fluor. Det. Not Parked");
sample_detected = lspmac_bi_init( &(lspmac_bis
        [ 7]), &(md2_status.accllc_2),        0x02, "SamplePresent",
     "SampleAbsent");
etel_ready = lspmac_bi_init( &(lspmac_bis
    [ 8]), &(md2_status.acc11c_2), 0x20, "ETEL Ready",
                   = lspmac_bi_init( &(lspmac_bis
     "ETEL Not Ready");
     _on = lspmac_bi_init( &(lspmac_bis [ 9]), &(md2_status.accl1c_2), 0x40, "ETEL On",
etel_on
     "ETEL Off");
                   = lspmac_bi_init( &(lspmac_bis
etel_init_ok
     [10]), & (md2_status.acc11c_2), 0x80, "ETEL Init OK",
     "ETEL Init Not OK");
     kappa_ok = lspmac_bi_init( &(lspmac_bis
[11]), &(md2_status.accllc_3), 0x01, "Minikappa OK",
minikappa_ok
     "Minikappa Not OK");
t_mag_on = lspmac_bi_init( &(lspmac_bis
smart_mag_on
     [12]), & (md2_status.acc11c_3), 0x04, "Smart Magnet On",
     "Smart Magnet Not On");
     parked = lspmac_bi_init( &(lspmac_bis
[13]), &(md2_status.accl1c_3), 0x08, "Arm Parked",
arm_parked
     "Arm Not Parked");
smart_mag_err = lspmac_bi_init( &(lspmac_bis
     [14]), & (md2_status.acc11c_3), 0x10, "Smart Magnet Error",
     "Smart Magnet OK");
shutter_open
                   = lspmac_bi_init( &(lspmac_bis
     [15]), & (md2_status.accllc_3), 0x100, "Shutter Open", "Shutter Not Open");
smart_mag_off
    ct_mag_off = lspmac_bi_init( &(lspmac_bis [16]), &(md2_status.acc11c_5), 0x01, "Smart Magnet Off",
     "Smart Magnet Not Off");
// Set up hash table
err = hcreate_r( LSPMAC_MAX_MOTORS * 2, &motors_ht)
if( err == 0) {
  lslogging_log_message( "lspmac_init: hcreate_r failed:
    '%s'", strerror( errno));
  exit(-1);
for( i=0; i<lspmac_nmotors; i++) {</pre>
  entry_in.key = lspmac_motors[i].name;
entry_in.data = &(lspmac_motors[i]);
  err = hsearch_r( entry_in, ENTER, &entry_outp, &motors_ht);
  if( err == 0) {
    l(eif == 0, {
    lslogging_log_message( "lspmac_init: hsearch_r
    failed for motor %s: '%s'", lspmac_motors[i].name, strerror( errno));
     exit(-1);
// Initialize several commands that get called, perhaps, alot
rr_cmd.RequestType = VR_UPLOAD;
```

```
= VR_PMAC_READREADY;
= 0;
= 0;
= htons(2);
rr_cmd.Request
rr_cmd.wValue
rr_cmd.wIndex
rr_cmd.wLength
memset( rr_cmd.bData, 0, sizeof(rr_cmd.bData));
gb_cmd.RequestType = VR_UPLOAD;
gb_cmd.Request = VR_PMAC_GETBUFFER;
gb_cmd.wValue
                    = 0;
                 = 0;
= htons(1400);
gb_cmd.wIndex
gb_cmd.wLength
memset( gb_cmd.bData, 0, sizeof(gb_cmd.bData));
cr_cmd.RequestType = VR_UPLOAD;
cr_cmd.Request = VR_CTRL_RESPONSE;
                    = 0;
                 = 0;
= 0;
= htons(1400);
^. sizeof(c
cr_cmd.wValue
cr_cmd.wIndex
cr cmd.wLength
memset( cr_cmd.bData, 0, sizeof(cr_cmd.bData));
//
// Initialize some mutexs and conditions
pthread_mutex_init( &pmac_queue_mutex, &mutex_initializer);
pthread_cond_init( &pmac_queue_cond, NULL);
lspmac_shutter_state = 0;
     assume the shutter is now closed: not a big deal if we are wrong
pthread_mutex_init( &lspmac_shutter_mutex, &
    mutex_initializer);
pthread_cond_init( &lspmac_shutter_cond, NULL);
pmacfd.fd = -1;
pthread_mutex_init( &lspmac_moving_mutex, &
    mutex initializer);
pthread_cond_init( &lspmac_moving_cond, NULL);
pthread_mutex_init( &lspmac_ascii_mutex, &mutex_initializer
pthread_mutex_init( &lspmac_ascii_buffers_mutex, &
    mutex_initializer);
// clear the ascii communications buffers
  uint32_t cc;
  cc = 0;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
lspmac_SockSendDPline( NULL, "I5=0");
lspmac_SockSendDPline( NULL, "ENABLE PLCC 0,2");
lspmac_SockSendDPline( NULL, "DISABLE PLCC 1");
lspmac_SockSendDPline( NULL, "I5=3");
```

7.12.4.39 int lspmac_jogabs_queue (lspmac_motor_t * , double)

Use jog to move motor to requested position.

Definition at line 3265 of file Ispmac.c.

7.12.4.40 int lspmac_move_or_jog_abs_queue (lspmac_motor_t * mp, double requested_position, int use_jo)

Move method for normal stepper and servo motor objects Returns non-zero on abort, zero if OK.

- < format string for coordinate system move
- < coordinate system bit
- < the requested position in units of "counts"
- < motor and coordinate system;
- < our axis

Parameters

in	тр	The motor to move
in	requested	Where to move it
	position	
in	use_jo	1 to force jog, 0 for motion prog

Definition at line 3017 of file Ispmac.c.

```
char *fmt;
int q100;
int requested_pos_cnts;
int coord_num, motor_num;
char *axis;
double u2c;
double neutral_pos;
double min_pos, max_pos;
int pos_limit_hit, neg_limit_hit, in_position_band;
struct timespec timeout, now;
int err;
pthread_mutex_lock( &(mp->mutex));
              = lsredis_getd( mp->u2c);
neutral_pos;
              = lsredis_getd( mp->max_pos) -
max_pos
   neutral_pos;
pos_limit_hit = lsredis_getd( mp->pos_limit_hit
   );
neg_limit_hit = lsredis_getd( mp->neg_limit_hit
in_position_band = lsredis_getl( mp->in_position_band
if( u2c == 0.0 || requested_position < min_pos || requested_position >
   max_pos) {
  // Shouldn't try moving a motor that's in trouble
  pthread mutex unlock( & (mp->mutex));
  %s u2c=%f requested position=%f min allowed=%f max allowed=%f", mp->name
    , u2c, requested_position, min_pos, max_pos);
  lsevents_send_event( "%s Move Aborted", mp->name);
  return 1;
if( (neg_limit_hit && (requested_position < mp->position)) || (pos_limit_hit
    && (requested_position > mp->position))) {
  limit=%d high limit=%d",
                      mp->name, requested_position, mp->position
    , neg_limit_hit, pos_limit_hit);
  lsevents_send_event( "%s Move Aborted", mp->name);
  return 2;
```

```
mp->requested_position = requested_position;
if (mp->nlut > 0 && mp->lut != NULL) {
   mp->requested_pos_cnts = lspmac_lut ( mp->nlut
   , mp->lut, requested_position);
} else {
 mp->requested_pos_cnts = u2c * (requested_position +
   neutral_pos);
requested_pos_cnts = mp->requested_pos_cnts;
// Bluff if we are already there
if( (abs( requested_pos_cnts - mp->actual_pos_cnts) * 16 <</pre>
    in_position_band) || (lsredis_getb( mp->active) != 1)) {
  // Lie and say we moved even though we didn't. Who will know? We are
    within the deadband or not active.
  mp->not_done = 1;
mp->motion_seen = 0;
  mp->command_sent = 0;
  lsevents_send_event( "%s Moving", mp->name);
 mp->not_done = 0;
mp->motion_seen = 1;
  mp->command_sent = 1;
  if( lsredis_getb( mp->active) != 1) {
    \ensuremath{//} fake the motion for simulated motors
    mp->position = requested_position;
   mp->actual_pos_cnts = requested_pos_cnts;
  pthread_mutex_unlock( &(mp->mutex));
  lsevents_send_event( "%s In Position", mp->name);
mp->not_done = 1;
mp->motion_seen = 0;
mp->command_sent = 0;
if( use_jog || axis == NULL || *axis == 0) {
 use_jog = 1;
} else {
 use_jog = 0;
 q100 = 1 << (coord_num -1);
pthread_mutex_unlock( & (mp->mutex));
if( !use_jog) {
  // Make sure the coordinate system is not moving something, wait if it is
  pthread_mutex_lock( &lspmac_moving_mutex);
  clock_gettime( CLOCK_REALTIME, &now);
  // TODO: Have all moves estimate how long they'll take and use that here
  timeout.tv_sec = now.tv_sec + 60.0;
                                                      // a long timeout, but
     we might really be moving something that takes this long (or longer)
  timeout.tv_nsec = now.tv_nsec;
  err = 0:
  while( err == 0 && (lspmac_moving_flags & q100) != 0)
   err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
  pthread_mutex_unlock( &lspmac_moving_mutex);
  if( err == ETIMEDOUT) {
    lslogging_log_message( "
    lspmac_move_or_jog_abs_queue: Timed Out. lspmac_moving_flags = %0x", lspmac_moving_flags
    lsevents_send_event( "%s Move Aborted", mp->name);
    return 1;
```

```
// // Set the "we are moving this coordinate system" flag
  lspmac_SockSendDPline( NULL, "M5075=(M5075 | %d)",
    q100);
  switch( *axis) {
  case 'A':
   fmt = "&%d Q16=%d Q100=%d B146R";
   break:
  case 'B':
  fmt = "&%d Q17=%d Q100=%d B147R";
    break;
  case 'C':
  fmt = "&%d Q18=%d Q100=%d B148R";
    break;
   fmt = "&%d Q10=%d Q100=%d B140R";
    break;
 case 'Y':
  fmt = "&%d Q11=%d Q100=%d B141R";
   break;
  case 'Z':
   fmt = "&%d Q12=%d Q100=%d B142R";
    break:
 case 'U':
  fmt = "&%d Q13=%d Q100=%d B143R";
    break;
  case 'V':
   fmt = "&%d Q14=%d Q100=%d B144R";
    break;
  case 'W':
   fmt = "&%d Q15=%d Q100=%d B145R";
   break;
  // Make sure the flag has been seen
  clock_gettime( CLOCK_REALTIME, &now);
  timeout.tv_sec = now.tv_sec + 4.0;
                                                      // also a long timeout.
      This should really only take a few milliseconds on a slow day
  timeout.tv_nsec = now.tv_nsec;
  pthread_mutex_lock( &lspmac_moving_mutex);
  while( err == 0 && (lspmac_moving_flags & q100) == 0)
    err = pthread_cond_timedwait( &lspmac_moving_cond, &
    lspmac_moving_mutex, &timeout);
  pthread_mutex_unlock( &lspmac_moving_mutex);
  if( err == ETIMEDOUT) {
    lslogging_log_message( "
    lspmac_move_or_jog_abs_queue: Did not see flag propagate. Move aborted.");
lsevents_send_event( "%s Move Aborted", mp->name);
    return 1;
}
pthread_mutex_lock( &(mp->mutex));
if( use_jog) {
  lspmac_SockSendDPline( mp->name, "#%d j=%d",
    motor_num, requested_pos_cnts);
} else {
  lspmac_SockSendDPline( mp->name, fmt, coord_num,
    requested_pos_cnts, q100);
pthread_mutex_unlock( &(mp->mutex));
free (axis):
return 0;
```

7.12.4.41 int lspmac_move_or_jog_preset_queue (lspmac_motor_t * , char * , int)

move using a preset value returns 0 on success, non-zero on error

Definition at line 3226 of file Ispmac.c.

```
double pos;
int err;
int err;
int rtn;

if( preset == NULL || *preset == 0) {
   lsevents_send_event( "%s Move Aborted", mp->name);
   return 0;
}

err = lsredis_find_preset( mp->name, preset, &pos);

if( err != 0)
   rtn = lspmac_move_or_jog_abs_queue( mp, pos,
        use_jog);
else {
   lsevents_send_event( "%s Move Aborted", mp->name);
   rtn = 1;
}
return rtn;
```

7.12.4.42 void lspmac_move_or_jog_queue (lspmac_motor_t * , double , int)

7.12.4.43 int lspmac_move_preset_queue (lspmac_motor_t * mp, char * preset_name)

Move a given motor to one of its preset positions.

No movement if the preset is not found.

Parameters

тр	Ispmac motor pointer
preset_name	Name of the preset to use

Definition at line 2393 of file Ispmac.c.

```
double pos;
int err;

lslogging_log_message( "lspmac_move_preset_queue: Called
    with motor %s and preset named '%s'", mp->name, preset_name);

err = lsredis_find_preset( mp->name, preset_name, &pos
    );
if( err == 0)
    return 1;

err = mp->jogAbs( mp, pos);
if(!err)
    lslogging_log_message( "lspmac_move_preset_queue:
        moving %s to preset '%s' (%f)", mp->name, preset_name, pos);
//
// the abort event should have been sent in moveAbs
//
return err;
```

7.12.4.44 int lspmac_moveabs_queue (lspmac_motor_t * , double)

Use coordinate system motion program, if available, to move motor to requested position.

Definition at line 3254 of file Ispmac.c.

```
return lspmac_move_or_jog_abs_queue( mp,
    requested_position, 0);
```

7.12.4.45 int lspmac_moveabs_wait (lspmac_motor_t * mp, double timeout_secs)

Wait for motor to finish moving.

Assume motion already queued, now just wait

Parameters

тр	The motor object to wait for
timeout_secs	The number of seconds to wait for. Fractional values fine.

Definition at line 3280 of file Ispmac.c.

```
struct timespec timeout, now;
double isecs, fsecs;
^{\prime\prime} // Copy the queue item for the most recent move request
clock_gettime( CLOCK_REALTIME, &now);
fsecs = modf( timeout_secs, &isecs);
timeout.tv_sec = now.tv_sec + (long)floor( isecs);
timeout.tv_nsec = now.tv_nsec + (long)floor( fsecs * 1.0e9);
timeout.tv_sec += timeout.tv_nsec / 1000000000;
timeout.tv_nsec %= 1000000000;
err = 0;
pthread_mutex_lock( & (mp->mutex));
while( err == 0 && mp->command_sent == 0)
  err = pthread_cond_timedwait( &mp->cond, &mp->mutex, &timeout);
pthread_mutex_unlock( &(mp->mutex));
if( err != 0) {
  if( err != ETIMEDOUT) {
    lslogging_log_message( "lspmac_moveabs_wait:
     unexpected error from timedwait %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
  return 1;
// wait for the motion to have started
// This will time out if the motion ends before we can read the status back
// hence the added complication of time stamp of the sent packet.
err = 0;
pthread_mutex_lock( &(mp->mutex));
while( err == 0 && mp->motion_seen == 0)
 err = pthread_cond_timedwait( &(mp->cond), &(mp->mutex), &timeout)
if( err != 0) {
  if( err != ETIMEDOUT) {
    lslogging_log_message( "lspmac_moveabs_wait:
     unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
    timeout.tv_nsec);
  pthread_mutex_unlock( & (mp->mutex));
  return 1;
// wait for the motion that we know has started to finish \ensuremath{//}
err = 0;
while( err == 0 && mp->not_done)
  err = pthread_cond_timedwait( &(mp->cond), &(mp->mutex), &timeout)
```

```
if( err != 0) {
   if( err != ETIMEDOUT) {
        lslogging_log_message( "lspmac_moveabs_wait:
        unexpected error from timedwait: %d tv_sec %ld tv_nsec %ld", err, timeout.tv_sec,
        timeout.tv_nsec);
   }
   pthread_mutex_unlock( &(mp->mutex));
   return 1;
}

//

// if return code was not 0 then we know we shouldn't wait for not_done flag.
// In this case the motion ended before we read the status registers
//
   pthread_mutex_unlock( &(mp->mutex));
   return 0;
```

7.12.4.46 void Ispmac_run ()

;

Start up the Ispmac thread.

Definition at line 4010 of file Ispmac.c.

```
char **inits;
lspmac motor t *mp;
char evts[64];
int i;
int active;
int motor_num;
pthread create ( &pmac thread, NULL, 1spmac worker,
     NULL);
lsevents_add_listener( "CryoSwitchChanged",
lsevents_add_listener( "scint Moving",
  lspmac_cryoSwitchChanged_cb);
lsevents_add_listener( "scint Moving",
  lspmac_scint_maybe_move_sample_cb);
lsevents_add_listener( "scint In Position",
     lspmac_scint_maybe_return_sample_cb);
lsevents_add_listener( "scint In Position",
     lspmac_scint_inPosition_cb);
lsevents_add_listener( "scintDried",
    lspmac_scint_dried_cb);
lsevents_add_listener( "backLight 1",
lspmac_backLight_up_cb);
lsevents_add_listener( "backLight 0",
lspmac_backLight_down_cb);
lsevents_add_listener( "cam.zoom Moving",
     lspmac_light_zoom_cb);
for( i=0; i<lspmac_nmotors; i++) {</pre>
  snprintf( evts, sizeof( evts)-1, "%s command accepted", lspmac_motors
   evts[sizeof(evts)-1] = 0;
   lsevents_add_listener( evts, lspmac_command_done_cb
     );
}
lspmac_zoom_lut_setup();
lspmac_flight_lut_setup();
lspmac_blight_lut_setup();
lspmac_fscint_lut_setup();
// Clear the command interfaces
lspmac_SockSendControlCharPrint( NULL, '\x18')
     ;
  uint32_t cc;
   cc = 0;
  lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
   , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
   cc = 0x18;
```

```
lspmac_send_command( VR_UPLOAD, VR_PMAC_SETMEM
    , 0x0e9e, 0, 4, (char *)&cc, NULL, 1, NULL);
// Initialize the MD2 pmac (ie, turn on the right plcc's etc)
for( inits = lsredis_get_string_array(lspmac_md2_init); *inits != NULL;
     inits++) {
  lspmac_SockSendDPline( NULL, *inits);
// Initialize the pmac's support for each motor
// (ie, set the various flag for when a motor is active or not)
for( i=0; i<lspmac_nmotors; i++) {</pre>
  mp = &(lspmac_motors[i]);
active = lsredis_getb( mp->active);
motor_num = lsredis_getl( mp->motor_num);
  mp
  if( motor_num >= 1 && motor_num <= 32) {</pre>
    // Set the PMAC to be consistant with redis
    lspmac_SockSendDPline( NULL, "I%d16=%f I%d17=%f
    ( mp->in_position_band));
  // if there is a problem with "active" then \operatorname{don't} do anything
  // On the other hand, various combinations of yes/no true/fals 1/0 should
     work
  switch( active) {
  case 1:
    inits = lsredis_get_string_array( mp->active_init
    );
    break:
    inits = lsredis_get_string_array( mp->
    inactive_init);
    break;
    lslogging_log_message( "lspmac_run: motor %s is
     neither active nor inactive (!?)", mp->name);
    inits = NULL;
  if( inits != NULL) {
    while( *inits != NULL) {
     lspmac_SockSendDPline( NULL, *inits);
      inits++;
    }
  }
}
```

7.12.4.47 void lspmac_SockSendDPControlChar (char * event, char c)

use dpram ascii interface to send a control character

Definition at line 1995 of file Ispmac.c.

```
7.12.4.48 void lspmac_SockSendDPline ( char * , char * fmt, ... )
```

prepare (queue up) a line to send the dpram ascii command interface

Definition at line 1968 of file Ispmac.c.

```
va_list arg_ptr;
uint32_t index;
char *pl;

pthread_mutex_lock( &lspmac_ascii_mutex);
index = lspmac_dpascii_on++ % LSPMAC_DPASCII_QUEUE_LENGTH
    ;

pl = lspmac_dpascii_queue[index].pl;

va_start( arg_ptr, fmt);
vsnprintf( pl, 159, fmt, arg_ptr);
pl[159] = 0;
va_end( arg_ptr);

lspmac_dpascii_queue[index].event = event;
pthread_mutex_unlock( &lspmac_ascii_mutex);
```

7.12.4.49 pmac_cmd_queue_t* lspmac_SockSendline (char * event, char * fmt, ...)

Send a one line command.

Uses printf style arguments.

Parameters

in	event	base name for events
in	fmt	Printf style format string

Definition at line 1076 of file lspmac.c.

```
va_list arg_ptr;
char payload[1400];

va_start( arg_ptr, fmt);
vsnprintf( payload, sizeof(payload)-1, fmt, arg_ptr);
payload[ sizeof(payload)-1] = 0;
va_end( arg_ptr);

lslogging_log_message( payload);

return lspmac_send_command( VR_DOWNLOAD,
    VR_PMAC_SENDLINE, 0, 0, strlen( payload), payload,
    lspmac_GetShortReplyCB, 0, event);
```

7.12.4.50 void lspmac_video_rotate (double secs)

Special motion program to collect centering video.

Definition at line 2610 of file Ispmac.c.

7.12.4.51 int lsredis_cmpnstr (lsredis_obj_t * p, char * s, int n)

Definition at line 236 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
  pthread_cond_wait( &p->cond, &p->mutex);

rtn = strncmp( p->value, s, n);
pthread_mutex_unlock( &p->mutex);
return rtn;
}
```

7.12.4.52 int lsredis_cmpstr ($lsredis_obj_t * p$, char * s)

Definition at line 225 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = strcmp( p->value, s);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.12.4.53 int lsredis_find_preset (char * base, char * preset_name, double * dval)

Definition at line 806 of file Isredis.c.

```
lslogging_log_message( "lsredis_find_preset: no
    preset for motor %s named '%s'", base, preset_name);
*dval = 0.0;
    return 0;
  // Check if we have a match
  p = htab_output->data;
  if( lsredis_cmpstr( p, preset_name) == 0) {
   // got a match, now look for the position
   snprintf( s, sizeof( s)-1, "%s.%s.presets.%d.position", lsredis_head
     , base, i);
     s[sizeof(s)-1] = 0;
     htab_input.key = s;
     htab_input.data = NULL;
     err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab
     if( err == 0) {
      // Name but not position? odd.
      lslogging_log_message( "lsredis_find_preset:
Error, motor %s preset '%s' has no position defined", base, preset_name);
      *dval = 0.0;
      return 0;
    p = htab_output->data;
    *dval = lsredis_getd( p);
    return 1;
  }
// How'd we get here?
// did someone really define that many presets? And then looked for one
     that's not there?
*dval = 0;
return 0;
```

7.12.4.54 int lsredis_find_preset_index_by_position (lspmac_motor_t * mp)

Definition at line 916 of file Isredis.c.

```
lsredis_obj_t *p;
int plength;
int i;
double ur, pos;
p = lsredis_get_obj( "%s.presets.length", mp->name);
plength = lsredis_get_or_set_l( p, 0);
if( plength <= 0) {</pre>
 return -1;
ur = lsredis_getd( mp->update_resolution);
pos = lspmac_getPosition( mp);
for( i=0; i<plength; i++) {</pre>
 p = lsredis_get_obj( "%s.presets.%d.position", mp->name,
  if( fabs( pos - lsredis_getd( p)) <= ur) {</pre>
    return i;
 }
return -1;
```

7.12.4.55 | Isredis_obj_t* | Isredis_get_obj (char * , ...)

Definition at line 574 of file Isredis.c.

```
lsredis_obj_t *rtn;
va_list arg_ptr;
char k[512];
char *kp;
int nkp;
```

```
va_start( arg_ptr, fmt);
vsnprintf( k, sizeof(k)-1, fmt, arg_ptr);
k[sizeof(k)-1] = 0;
va_end( arg_ptr);
nkp = strlen(k) + strlen( lsredis_head) + 16;
                                                          // 16
    is overkill. I know. Get over it.
kp = calloc( nkp, sizeof( char));
if ( kp == NULL) {
  lslogging_log_message( "lsredis_get_obj: Out of memory
");
  exit( -1);
snprintf( kp, nkp-1, "%s.%s", lsredis_head, k);
kp[nkp-1] = 0;
pthread_mutex_lock( &lsredis_mutex);
while( lsredis_running == 0)
 pthread_cond_wait( &lsredis_cond, &lsredis_mutex);
rtn = _lsredis_get_obj( kp);
pthread_mutex_unlock( &lsredis_mutex);
free ( kp);
return rtn;
```

7.12.4.56 char** lsredis_get_string_array (lsredis_obj_t * p)

Definition at line 415 of file Isredis.c.

```
char **rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->avalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.12.4.57 int lsredis_getb (lsredis_obj_t * p)

Definition at line 428 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->bvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.12.4.58 char lsredis_getc (lsredis_obj_t * p)

Definition at line 441 of file Isredis.c.

```
int rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);
```

```
rtn = p->cvalue;
pthread_mutex_unlock( &p->mutex);
return rtn;
}
```

7.12.4.59 double $| sredis_getd (| sredis_getb | t * p) |$

Definition at line 364 of file Isredis.c.

```
double rtn;
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);
rtn = p->dvalue;
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.12.4.60 long int lsredis_getl (lsredis_obj_t * p)

Definition at line 377 of file Isredis.c.

```
long int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = p->lvalue;
pthread_mutex_unlock( &p->mutex);

return rtn;
}
```

7.12.4.61 char* lsredis_getstr (lsredis_obj_t * p)

return a copy of the key's string value be sure to free the result

Definition at line 264 of file Isredis.c.

```
char *rtn;

//
// Have to use strdup since we cannot guarantee that p->value won't be freed
    while the caller is still using it
//
pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
    pthread_cond_wait( &p->cond, &p->mutex);

rtn = strdup(p->value);
pthread_mutex_unlock( &p->mutex);
return rtn;
```

7.12.4.62 void lsredis_init (char * pub, char * re, char * head)

Initialize this module, that is, set up the connections.

Parameters

pub	Publish under this (unique) name
re	Regular expression to select keys we want to mirror
head	Prepend this (+ a dot) to the beginning of requested objects

Definition at line 949 of file Isredis.c.

```
int nerrmsg;
char *errmsg;
// set up hash map to store redis objects
err = hcreate_r( 8192, &lsredis_htab);
if( err == 0) {
   lslogging_log_message( "lsredis_init: Cannot create
     hash table. Really bad things are going to happen. hcreate_r returned %d", err);
lsredis_head = strdup( head);
lsredis_publisher = strdup( pub);
pthread_cond_init( &lsredis_cond, NULL);
subac = redisAsyncConnect("127.0.0.1", 6379);
if( subac->err) {
  lslogging_log_message( "Error: %s", subac->errstr
    );
subfd.fd
                     = subac->c.fd;
                   = 0;
= &subfd;
subfd.events
subac->ev.data
subac->ev.addRead = lsredis_addRead;
subac->ev.delRead = lsredis_delRead;
subac->ev.addWrite = lsredis_addWrite;
subac->ev.delWrite = lsredis_delWrite;
subac->ev.cleanup = lsredis_cleanup;
roac = redisAsyncConnect("127.0.0.1", 6379);
if( roac->err) {
  lslogging_log_message( "Error: %s", roac->errstr);
rofd.fd
                    = roac->c.fd;
                 = 0;
= &rofd;
rofd.events
roac->ev.data
roac->ev.addRead = lsredis_addRead;
roac->ev.delRead = lsredis_delRead;
roac->ev.addWrite = lsredis_addWrite;
roac->ev.delWrite = lsredis_delWrite;
roac->ev.cleanup = lsredis_cleanup;
//wrac = redisAsyncConnect("10.1.0.3", 6379);
wrac = redisAsyncConnect("127.0.0.1", 6379);
if( wrac->err) {
  lslogging_log_message( "Error: %s", wrac->errstr);
                 = wrac->c.fd;
= 0;
= &wrfd;
wrfd.fd
wrfd.events
wrac->ev.data
wrac->ev.addRead = lsredis_addRead;
wrac->ev.delRead = lsredis_delRead;
wrac->ev.addWrite = lsredis_addWrite;
wrac->ev.delWrite = lsredis_delWrite;
wrac->ev.cleanup = lsredis_cleanup;
err = regcomp( &lsredis_key_select_regex, re,
    REG_EXTENDED);
if( err != 0) {
  nerrmsg = regerror( err, &lsredis_key_select_regex,
     NULL, 0);
  if( nerrmsg > 0) {
    errmsg = calloc( nerrmsg, sizeof( char));
    nerrmsg = regerror( err, &lsredis_key_select_regex
    , errmsg, nerrmsg);
lslogging_log_message( "lsredis_select: %s", errmsg)
     free( errmsg);
```

```
}
}
}
```

7.12.4.63 int Isredis_regexec (const regex_t * preg, Isredis_obj_t * p, size_t nmatch, regmatch_t * pmatch, int eflags)

Definition at line 247 of file Isredis.c.

```
int rtn;

pthread_mutex_lock( &p->mutex);
while( p->valid == 0)
   pthread_cond_wait( &p->cond, &p->mutex);

rtn = regexec( preg, p->value, nmatch, pmatch, eflags);

pthread_mutex_unlock( &p->mutex);

return rtn;
```

7.12.4.64 void Isredis_run ()

Definition at line 1153 of file Isredis.c.

```
pthread_create( &lsredis_thread, NULL, lsredis_worker
    , NULL);
}
```

7.12.4.65 void Isredis_set_preset (char * base, char * preset_name, double dval)

Definition at line 852 of file Isredis.c.

```
{
char s[512];
int i, plength;
int err;
ENTRY htab_input, *htab_output;
lsredis_obj_t *p;
p = lsredis_get_obj( "%s.%s.presets.length", lsredis_head
    , base);
plength = lsredis_get_or_set_l( p, 0);
for( i=0; i<plength; i++) {</pre>
  snprintf( s, sizeof( s)-1, "%s.%s.presets.%d.name", lsredis_head
    , base, i);
  s[sizeof(s)-1] = 0;
  htab_input.key = s;
htab_input.data = NULL;
  err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab)
  if( err == 0) {
    //
// Not found? odd. Length Lied.
    // Might as well just stick our preset here.
    p = lsredis_get_obj( "%s", s);
lsredis_setstr( p, "%s", preset_name);
  } else {
    // Check if we have a match
   p = htab_output->data;
  if( lsredis_cmpstr( p, preset_name) == 0) {
    ^{\prime\prime} // got a match, now look for the position
    snprintf( s, sizeof( s)-1, "%s.%s.presets.%d.position", lsredis_head
```

```
, base, i);
    s[sizeof(s)-1] = 0;
    htab_input.key = s;
    htab_input.data = NULL;
    err = hsearch_r( htab_input, FIND, &htab_output, &lsredis_htab
    if( err == 0) {
       // Name but not position? odd.
      p = lsredis_get_obj( "%s", s);
      p = htab_output->data;
    lsredis_setstr( p, "%.3f", dval);
// OK, our preset was not found, add it
snprintf( s, sizeof( s)-1, "%s.%s.presets.%d.name", lsredis_head,
base, i);
s[sizeof(s)-1] = 0;
p = lsredis_get_obj( "%s", s);
lsredis_setstr( p, "%s", preset_name);
p = lsredis_get_obj( "%s", s);
lsredis_setstr( p, "%.3f", dval);
p = lsredis_get_obj( "%s.%s.presets.length", lsredis_head
     , base);
lsredis_setstr( p, "%ld", plength + 1);
```

7.12.4.66 void Isredis_setstr (Isredis_obj_t * p, char * fmt, ...)

Set the value and update redis.

Note that Isredis_set_value sets the value based on redis while here we set redis based on the value Arbitray maximum string length set here. TODO: Probably this limit should be removed at some point.

redisAsyncCommandArgv used instead of redisAsyncCommand 'cause it's easier (and possible) to deal with strings that would otherwise cause hiredis to emit a bad command, like those containing spaces. < up the count of times we need to see ourselves published before we start listening to others again

< Unlock to prevent deadlock in case the service routine needs to set our value

< redisAsyncCommandArgv shouldn't need to access this after it's made up it's packet (before it returns) so we should be OK with this location disappearing soon.

Definition at line 289 of file Isredis.c.

```
va_list arg_ptr;
char v[512];
char *argv[4];

va_start( arg_ptr, fmt);
vsnprintf( v, sizeof(v)-1, fmt, arg_ptr);
v[sizeof(v)-1] = 0;
va_end( arg_ptr);

pthread_mutex_lock( &p->mutex);

//
// Don't send an update if a good value has not changed
//
if( p->valid && strcmp( v, p->value) == 0) {
    // nothing to do
    pthread_mutex_unlock( &p->mutex);
    return;
}

p->wait_for_me++;
pthread_mutex_unlock( &p->mutex);

argv[0] = "HSET";
```

```
argv[1] = p->key;
argv[2] = "VALUE";
argv[3] = v;
  pthread_mutex_lock( &lsredis_mutex);
  while( lsredis_running == 0)
    pthread_cond_wait( &lsredis_cond, &lsredis_mutex);
  redisAsyncCommand( wrac, NULL, NULL, "MULTI");
redisAsyncCommandArgv( wrac, NULL, NULL, 4, (const char **)argv, NULL);
  redisAsyncCommand( wrac, NULL, NULL, "PUBLISH %s %s", lsredis_publisher
       , p->key);
  redisAsyncCommand( wrac, NULL, NULL, "EXEC");
  pthread_mutex_unlock( &lsredis_mutex);
  // Assume redis will take exactly the value we sent it
  pthread_mutex_lock( &p->mutex);
  _lsredis_set_value( p, v);
pthread_cond_signal( &p->cond);
  pthread_mutex_unlock( &p->mutex);
7.12.4.67 void Istest_main ( )
Definition at line 92 of file Istest.c.
  lstest_lspmac_est_move_time();
```

7.12.4.68 void lstimer_add_timer (char * event, int shots, unsigned long int secs, unsigned long int nsecs)

Create a timer.

Parameters

event	Name of the event to send when the timer goes off
shots	Number of times to run. 0 means never, -1 means forever
secs	Number of seconds to wait
nsecs	Number of nano-seconds to run in addition to secs

Definition at line 50 of file Istimer.c.

```
strncpy( lstimer_list[i].event, event, LSEVENTS_EVENT_LENGTH
  lstimer_list[i].event[LSEVENTS_EVENT_LENGTH
       -1] = 0;
  = shots;
  lstimer_list[i].delay_nsecs = nsecs;
  lstimer_list[i].next_secs = secs + now.tv_sec + now.tv_nsec + nsecs) / 10000000000;
lstimer_list[i].next_nsecs = (now.tv_nsec + nsecs ) % 10000000000;
                                   = secs + now.tv_sec + (
                                 = 0;
  lstimer_list[i].last_secs
  lstimer_list[i].last_nsecs = 0;
  lstimer_list[i].ncalls = 0;
lstimer_list[i].init_secs = now.tv_sec;
  lstimer_list[i].init_nsecs = now.tv_nsec;
  if( shots != 0) {
    lstimer_active_timers++;
    new_timer++;
  pthread_cond_signal( &lstimer_cond);
  pthread_mutex_unlock( &lstimer_mutex);
7.12.4.69 void Istimer_init ( )
Initialize the timer list and pthread stuff.
```

Definition at line 254 of file Istimer.c.

```
{
for( i=0; i<LSTIMER_LIST_LENGTH; i++) {</pre>
   lstimer_list[i].shots = 0;
pthread_mutex_init( &lstimer_mutex, NULL);
pthread_cond_init( &lstimer_cond, NULL);
```

7.12.4.70 void Istimer_run ()

Start up our thread.

Definition at line 268 of file Istimer.c.

```
pthread_create( &lstimer_thread, NULL, lstimer_worker
   , NULL);
```

```
7.12.4.71 void lsupdate_init ( )
```

7.12.4.72 void lsupdate_run ()

7.12.4.73 void md2cmds_init ()

Initialize the md2cmds module.

Definition at line 1884 of file md2cmds.c.

```
ENTRY hloader, *hrtnval;
```

```
int i, err;
 pthread_mutexattr_t mutex_initializer;
 pthread_mutexattr_init( &mutex_initializer);
 pthread_mutexattr_settype( &mutex_initializer, PTHREAD_MUTEX_RECURSIVE);
 pthread_mutex_init( &md2cmds_mutex, &mutex_initializer);
 pthread_cond_init( &md2cmds_cond, NULL);
 pthread_mutex_init( &md2cmds_moving_mutex, &
     mutex_initializer);
 pthread_cond_init( &md2cmds_moving_cond, NULL);
 pthread_mutex_init( &md2cmds_homing_mutex, &
     mutex_initializer);
 pthread_cond_init( &md2cmds_homing_cond, NULL);
 int nerrmsg;
   char *errmsq;
   nerrmsg = regerror( err, &md2cmds_cmd_regex, NULL, 0);
    if( nerrmsg > 0) {
     errmsg = calloc( nerrmsg, sizeof( char));
     nerrmsg = regerror( err, &md2cmds_cmd_regex, errmsg,
     nerrmsg);
     lslogging_log_message( "md2cmds_init: %s", errmsg);
     free ( errmsg);
 md2cmds_md_status_code = lsredis_get_obj
      ( "md2_status_code");
  lsredis_setstr( md2cmds_md_status_code, "
     7");
 hcreate_r( 2 * sizeof(md2cmds_cmd_kvs)/sizeof(md2cmds_cmd_kvs
     [0]), &md2cmds_hmap);
  for( i=0; i<sizeof(md2cmds_cmd_kvs)/sizeof(md2cmds_cmd_kvs</pre>
     [0]); i++) {
   hloader.key = md2cmds_cmd_kvs[i].k;
hloader.data = md2cmds_cmd_kvs[i].v;
   err = hsearch_r( hloader, ENTER, &hrtnval, &md2cmds_hmap);
   if( err == 0) {
     lslogging_log_message( "md2cmds_init: hsearch_r
      returned an error for item %d: %s", i, strerror(errno));
}
```

7.12.4.74 void md2cmds_run ()

Start up the thread.

Definition at line 1934 of file md2cmds.c.

```
pthread_create( &md2cmds_thread, NULL,
    md2cmds_worker, NULL);
lsevents_add_listener( "omega crossed zero",
md2cmds_rotate_cb);
lsevents_add_listener( "omega In Position",
    md2cmds_maybe_rotate_done_cb);
lsevents_add_listener( ".+ (Moving|In Position)",
    md2cmds_maybe_done_moving_cb);
lsevents_add_listener( "(.+) (Homing|Homed)",
md2cmds_maybe_done_homing_cb);
lsevents_add_listener( "capz (Moving|In Position)",
    md2cmds_time_capz_cb);
lsevents_add_listener( "Coordsys 1 Stopped",
    md2cmds_coordsys_1_stopped_cb);
lsevents_add_listener( "Coordsys 2 Stopped",
    md2cmds_coordsys_2_stopped_cb);
lsevents_add_listener( "Coordsys 3 Stopped",
    md2cmds_coordsys_3_stopped_cb);
lsevents_add_listener( "Coordsys 4 Stopped",
    md2cmds_coordsys_4_stopped_cb);
```

```
lsevents_add_listener( "Coordsys 5 Stopped",
    md2cmds_coordsys_5_stopped_cb);
lsevents_add_listener( "Coordsys 7 Stopped",
    md2cmds_coordsys_7_stopped_cb);
lsevents_add_listener( "cam.zoom Moving",
    md2cmds_set_scale_cb);
```

7.12.4.75 void pgpmac_printf (char * fmt, ...)

Terminal output routine ala printf.

Parameters

in	fmt	Printf style formating string

Definition at line 330 of file pgpmac.c.

```
va_list arg_ptr;
pthread_mutex_lock( &ncurses_mutex);
va_start( arg_ptr, fmt);
vwprintw( term_output, fmt, arg_ptr);
va_end( arg_ptr);
wnoutrefresh( term_output);
wnoutrefresh( term_input);
doupdate();
pthread_mutex_unlock( &ncurses_mutex);
```

7.12.4.76 void PmacSockSendline (char *s)

7.12.5 Variable Documentation

7.12.5.1 Ispmac_motor_t* alignx

Alignment stage X.

Definition at line 100 of file Ispmac.c.

7.12.5.2 Ispmac_motor_t* aligny

Alignment stage Y.

Definition at line 101 of file Ispmac.c.

7.12.5.3 Ispmac_motor_t* alignz

Alignment stage X.

Definition at line 102 of file Ispmac.c.

7.12.5.4 Ispmac_motor_t* anal

Polaroid analyzer motor.

Definition at line 103 of file Ispmac.c.

328 File Documentation

7.12.5.5 Ispmac_motor_t* apery

Aperture Y.

Definition at line 105 of file Ispmac.c.

7.12.5.6 Ispmac_motor_t* aperz

Aperture Z.

Definition at line 106 of file Ispmac.c.

7.12.5.7 Ispmac_bi_t* arm_parked

(whose arm? parked where?)

Definition at line 143 of file Ispmac.c.

Back Light DAC.

Definition at line 117 of file Ispmac.c.

7.12.5.9 Ispmac bi t* blight_down

Backlight is down.

Definition at line 133 of file Ispmac.c.

7.12.5.10 Ispmac_motor_t* blight_f

Back light scale factor.

Definition at line 126 of file Ispmac.c.

Back light Up/Down actuator.

Definition at line 121 of file Ispmac.c.

Backlight is up.

Definition at line 134 of file Ispmac.c.

Capillary Y.

Definition at line 107 of file Ispmac.c.

7.12.5.14 Ispmac_motor_t* capz

Capillary Z.

Definition at line 108 of file Ispmac.c.

7.12.5.15 Ispmac_motor_t* cenx

Centering Table X.

Definition at line 110 of file Ispmac.c.

Centering Table Y.

Definition at line 111 of file Ispmac.c.

7.12.5.17 Ispmac_motor_t* cryo

Move the cryostream towards or away from the crystal.

Definition at line 122 of file Ispmac.c.

7.12.5.18 Ispmac_bi_t* cryo_back

cryo is in the back position

Definition at line 135 of file Ispmac.c.

7.12.5.19 | Ispmac_bi_t* cryo_switch

that little toggle switch for the cryo

Definition at line 132 of file Ispmac.c.

7.12.5.20 Ispmac_motor_t* dryer

blow air on the scintilator to dry it off

Definition at line 123 of file Ispmac.c.

ETEL initialized OK.

Definition at line 140 of file Ispmac.c.

ETEL is on.

Definition at line 139 of file Ispmac.c.

330 File Documentation

7.12.5.23 Ispmac_bi_t* etel_ready

ETEL is ready.

Definition at line 138 of file Ispmac.c.

Front Light DAC.

Definition at line 116 of file Ispmac.c.

Front light scale factor.

Definition at line 127 of file Ispmac.c.

Turn front light on/off.

Definition at line 125 of file Ispmac.c.

7.12.5.27 Ispmac_motor_t* fluo

Move the fluorescence detector in/out.

Definition at line 124 of file Ispmac.c.

7.12.5.28 Ispmac_bi_t* fluor_back

fluor is in the back position

Definition at line 136 of file Ispmac.c.

Scintillator Piezo DAC.

Definition at line 118 of file Ispmac.c.

Fast shutter.

Definition at line 115 of file Ispmac.c.

High pressure air OK.

Definition at line 131 of file Ispmac.c.

7.12.5.32 Ispmac_motor_t* kappa

Kappa.

Definition at line 112 of file Ispmac.c.

7.12.5.33 Ispmac_bi_t* lp_air

Low pressure air OK.

Definition at line 130 of file Ispmac.c.

7.12.5.34 lspg_demandairrights_t lspg_demandairrights

our demandairrights object

Definition at line 65 of file lspg.c.

7.12.5.35 lspg_getcenter_t lspg_getcenter

the getcenter object

Definition at line 64 of file lspg.c.

our currentsample id

Definition at line 66 of file lspg.c.

7.12.5.37 | Ispg_nextsample_t | Ispg_nextsample

the very next sample

Definition at line 62 of file lspg.c.

7.12.5.38 lspg_nextshot_t lspg_nextshot

the nextshot object

Definition at line 63 of file lspg.c.

start a sample transfer

Definition at line 67 of file lspg.c.

7.12.5.40 lspg_waitcryo_t lspg_waitcryo

signal the robot

Definition at line 68 of file lspg.c.

332 File Documentation

7.12.5.41 | Ispmac_motor_t | Ispmac_motors[]

All our motors.

Definition at line 95 of file Ispmac.c.

7.12.5.42 pthread_cond_t lspmac_moving_cond

Wait for motor(s) to finish moving condition.

Definition at line 71 of file Ispmac.c.

7.12.5.43 int lspmac_moving_flags

Flag used to implement motor moving condition.

Definition at line 72 of file Ispmac.c.

7.12.5.44 pthread_mutex_t lspmac_moving_mutex

Coordinate moving motors between threads.

Definition at line 70 of file Ispmac.c.

7.12.5.45 int lspmac_nmotors

The number of motors we manage.

Definition at line 96 of file Ispmac.c.

7.12.5.46 pthread_cond_t lspmac_shutter_cond

Allows waiting for the shutter status to change.

Definition at line 69 of file Ispmac.c.

7.12.5.47 int lspmac_shutter_has_opened

Indicates that the shutter had opened, perhaps briefly even if the state did not change.

Definition at line 67 of file Ispmac.c.

7.12.5.48 pthread_mutex_t lspmac_shutter_mutex

Coordinates threads reading shutter status.

Definition at line 68 of file Ispmac.c.

7.12.5.49 int lspmac_shutter_state

State of the shutter, used to detect changes.

Definition at line 66 of file Ispmac.c.

7.12.5.50 pthread_cond_t lsredis_cond

Definition at line 75 of file Isredis.c.

7.12.5.51 pthread_mutex_t lsredis_mutex

Definition at line 74 of file Isredis.c.

7.12.5.52 int Isredis_running

Definition at line 76 of file Isredis.c.

7.12.5.53 pthread_mutex_t md2_status_mutex

Synchronize reading/writting status buffer.

Definition at line 351 of file Ispmac.c.

7.12.5.54 char md2cmds_cmd[]

our command;

Definition at line 24 of file md2cmds.c.

7.12.5.55 pthread_cond_t md2cmds_cond

condition to signal when it's time to run an md2 command

Definition at line 10 of file md2cmds.c.

7.12.5.56 | Isredis_obj_t* md2cmds_md_status_code

Definition at line 26 of file md2cmds.c.

7.12.5.57 pthread_mutex_t md2cmds_mutex

mutex for the condition

Definition at line 11 of file md2cmds.c.

7.12.5.58 pthread_cond_t md2cmds_pg_cond

7.12.5.59 pthread_mutex_t md2cmds_pg_mutex

7.12.5.60 | Ispmac_bi_t* minikappa_ok

Minikappa is OK (whatever that means)

Definition at line 141 of file Ispmac.c.

7.12.5.61 pthread_mutex_t ncurses_mutex

allow more than one thread access to the screen

Definition at line 242 of file pgpmac.c.

334 File Documentation

7.12.5.62 Ispmac_motor_t* omega

MD2 omega axis (the air bearing)

Definition at line 99 of file Ispmac.c.

7.12.5.63 struct timespec omega_zero_time

Time we believe that omega crossed zero.

Definition at line 79 of file Ispmac.c.

Phi (not data collection axis)

Definition at line 113 of file Ispmac.c.

7.12.5.65 pthread_cond_t pmac_queue_cond

wait for a command to be sent to PMAC before continuing

Definition at line 85 of file Ispmac.c.

7.12.5.66 pthread_mutex_t pmac_queue_mutex

manage access to the pmac command queue

Definition at line 84 of file Ispmac.c.

smart magnet detected sample

Definition at line 137 of file Ispmac.c.

7.12.5.68 Ispmac_motor_t* scint

Scintillator Z.

Definition at line 109 of file Ispmac.c.

shutter is open (note in pmc says this is a slow input)

Definition at line 144 of file Ispmac.c.

smart magnet error (coil broken perhaps)

Definition at line 145 of file Ispmac.c.

smart magnet is off

Definition at line 146 of file Ispmac.c.

smart magnet is on

Definition at line 142 of file Ispmac.c.

Smart Magnet on/off.

Definition at line 120 of file Ispmac.c.

7.12.5.74 WINDOW* term_input

place to put the cursor

Definition at line 238 of file pgpmac.c.

7.12.5.75 WINDOW* term_output

place to print stuff out

Definition at line 237 of file pgpmac.c.

7.12.5.76 WINDOW* term_status

shutter, lamp, air, etc status

Definition at line 239 of file pgpmac.c.

7.12.5.77 WINDOW* term_status2

shutter, lamp, air, etc status

Definition at line 240 of file pgpmac.c.

Optical zoom.

Definition at line 104 of file Ispmac.c.

Index

_GNU_SOURCE	pgpmac.h, 327
pgpmac.h, 284	aligny_act_pos
init	md2StatusStruct, 62
iniParser::iniParser, 16	aligny_status_1
_lspmac_motor_init	md2StatusStruct, 62
Ispmac.c, 136	aligny_status_2
_lsredis_get_obj	md2StatusStruct, 62
Isredis.c, 209	alignz
pgpmac.h, 286	Ispmac.c, 196
_lsredis_set_value	pgpmac.h, 327
Isredis.c, 210	alignz act pos
	md2StatusStruct, 62
acc11c_1	alignz_status_1
md2StatusStruct, 61	md2StatusStruct, 62
acc11c_2	alignz_status_2
md2StatusStruct, 61	md2StatusStruct, 62
acc11c_3	anal
md2StatusStruct, 61	Ispmac.c, 196
acc11c_5	pgpmac.h, 327
md2StatusStruct, 61	analyzer_act_pos
acc11c_6	md2StatusStruct, 62
md2StatusStruct, 61	•
active	analyzer_status_1
lspg_nextshot_struct, 29	md2StatusStruct, 62
lspmac_motor_struct, 49	analyzer_status_2
active2	md2StatusStruct, 62
lspg_nextshot_struct, 29	aperturey_act_pos
active2_isnull	md2StatusStruct, 62
lspg_nextshot_struct, 30	aperturey_status_1
active_init	md2StatusStruct, 63
Ispmac_motor_struct, 49	aperturey_status_2
active_isnull	md2StatusStruct, 63
lspg_nextshot_struct, 30	aperturez_act_pos
active_simulation	md2StatusStruct, 63
mk_pgpmac_redis, 12	aperturez_status_1
actual_pos_cnts	md2StatusStruct, 63
Ispmac_motor_struct, 49	aperturez_status_2
actual_pos_cnts_p	md2StatusStruct, 63
Ispmac_motor_struct, 49	apery
alignx	Ispmac.c, 197
Ispmac.c, 196	pgpmac.h, 327
pgpmac.h, 327	aperz
alignx act pos	Ispmac.c, 197
md2StatusStruct, 61	pgpmac.h, 328
alignx_status_1	arm_parked
md2StatusStruct, 62	Ispmac.c, 197
alignx_status_2	pgpmac.h, 328
md2StatusStruct, 62	asis
aligny	mk_pgpmac_redis, 12
Ispmac.c, 196	avalue
•	

Isredis_obj_struct, 55	md2StatusStruct, 63
ax	capy_status_1
lspg_nextshot_struct, 30	md2StatusStruct, 63
ax2	capy_status_2
lspg_nextshot_struct, 30	md2StatusStruct, 63
ax2_isnull	capz
lspg_nextshot_struct, 30	Ispmac.c, 198
ax_isnull	pgpmac.h, 328
lspg_nextshot_struct, 30	capz_act_pos
axis	md2StatusStruct, 63
lspmac_combined_move_struct, 45	capz_status_1
lspmac_motor_struct, 49	md2StatusStruct, 63
ay	capz_status_2
lspg_nextshot_struct, 30	md2StatusStruct, 63
ay2	cb
lspg_nextshot_struct, 30 ay2_isnull	lsevents_listener_struct, 18
• —	centerx_act_pos
lspg_nextshot_struct, 30 ay_isnull	md2StatusStruct, 64
lspg_nextshot_struct, 30	centerx_status_1
az	md2StatusStruct, 64
lspg_nextshot_struct, 30	centerx_status_2
az2	md2StatusStruct, 64
lspg_nextshot_struct, 31	centery_act_pos
az2 isnull	md2StatusStruct, 64
lspg_nextshot_struct, 31	centery_status_1
az isnull	md2StatusStruct, 64
lspg_nextshot_struct, 31	centery_status_2
	md2StatusStruct, 64
b	Cenx
mk_pgpmac_redis, 12	Ispmac.c, 198
bData	pgpmac.h, 329
tagEthernetCmd, 68	ceny
back_dac	lspmac.c, 198 pgpmac.h, 329
md2StatusStruct, 63	changeEventOff
bi_list	Ispmac_bi_struct, 43
mk_pgpmac_redis, 12	changeEventOn
blight	Ispmac bi struct, 43
Ispmac.c, 197	cleanstr
pgpmac.h, 328	Ispmac.c, 136
blight_down	command_buf
Ispmac.c, 197	Ispmac_ascii_buffers_struct, 42
pgpmac.h, 328	command_buf_cc
blight_f	Ispmac_ascii_buffers_struct, 42
Ispmac.c, 197	command sent
pgpmac.h, 328	Ispmac motor struct, 49
blight_ud	command str
Ispmac.c, 197	Ispmac_ascii_buffers_struct, 42
pgpmac.h, 328	cond
blight_up lspmac.c, 197	lspg_demandairrights_struct, 20
·	Ispg_getcenter_struct, 21
pgpmac.h, 328 bvalue	lspg_getcurrentsampleid_struct, 23
Isredis_obj_struct, 55	lspg_lock_detector_struct, 24
1510a15_00j_5t1 a0t, 50	lspg_lock_diffractometer_struct, 25
сару	
	lspg_nextsample_struct, 26
Ispmac.c, 197	lspg_nextsample_struct, 26 lspg_nextshot_struct, 31
lspmac.c, 197 pgpmac.h, 328	. — . —
·	lspg_nextshot_struct, 31

lspg_wait_for_detector_struct, 40	dcy
lspg_waitcryo_struct, 40	lspg_getcenter_struct, 22
Ispmac_motor_struct, 49	dcy_isnull
Isredis_obj_struct, 55	lspg_getcenter_struct, 22
coord_num	delay_nsecs
Ispmac_combined_move_struct, 45	Istimer_list_struct, 58
lspmac_motor_struct, 49	delay_secs
cr_cmd	Istimer_list_struct, 58
Ispmac.c, 198	Delta
cryo	Ispmac_combined_move_struct, 46
Ispmac.c, 198	dryer
pgpmac.h, 329	Ispmac.c, 199
cryo_back	pgpmac.h, 329
Ispmac.c, 198	dsdir
pgpmac.h, 329	lspg_nextshot_struct, 32
cryo_switch	dsdir_isnull
Ispmac.c, 198	lspg_nextshot_struct, 32
pgpmac.h, 329	dsdist
cvalue	lspg_nextshot_struct, 32
Isredis_obj_struct, 56	dsdist2
CX	lspg_nextshot_struct, 32
lspg_nextshot_struct, 31	dsdist2_isnull
cx2	lspg_nextshot_struct, 32
lspg_nextshot_struct, 31	dsdist_isnull
cx2_isnull	Ispg_nextshot_struct, 32
lspg_nextshot_struct, 31	dsexp
cx_isnull	lspg_nextshot_struct, 32
lspg_nextshot_struct, 31	dsexp2
су	lspg_nextshot_struct, 32
lspg_nextshot_struct, 31	dsexp2_isnull
cy2	lspg_nextshot_struct, 33
lspg_nextshot_struct, 31	dsexp_isnull
cy2_isnull	lspg_nextshot_struct, 33
lspg_nextshot_struct, 32	dshpid
cy_isnull	Ispg nextshot struct, 33
lspg_nextshot_struct, 32	dshpid_isnull
dac myar	lspg_nextshot_struct, 33
dac_mvar lspmac_motor_struct, 49	dskappa
dax	lspg_nextshot_struct, 33
lspg_getcenter_struct, 21	dskappa2
dax_isnull	lspg_nextshot_struct, 33
lspg_getcenter_struct, 21	dskappa2_isnull
day	Ispg_nextshot_struct, 33
lspg_getcenter_struct, 21	dskappa_isnull
day_isnull	lspg_nextshot_struct, 33
lspg_getcenter_struct, 22	dsnrg
daz	lspg_nextshot_struct, 33
Ispg_getcenter_struct, 22	dsnrg2
daz isnull	lspg_nextshot_struct, 33
lspg_getcenter_struct, 22	dsnrg2_isnull
dbmem	lspg_nextshot_struct, 34
Ispmac.c, 198	dsnrg_isnull
dbmemIn	lspg_nextshot_struct, 34
Ispmac.c, 198	dsomega
dcx	lspg_nextshot_struct, 34
lspg_getcenter_struct, 22	dsomega2
dcx_isnull	lspg_nextshot_struct, 34
lspg_getcenter_struct, 22	dsomega2_isnull
.5pg_gottooou dot;	

lspg_nextshot_struct, 34	etel_on
dsomega_isnull	Ispmac.c, 199
lspg_nextshot_struct, 34	pgpmac.h, 329
dsoscaxis	etel_ready
lspg_nextshot_struct, 34	Ispmac.c, 199
dsoscaxis2	pgpmac.h, 329
lspg_nextshot_struct, 34	ethCmdOff
dsoscaxis2_isnull	Ispmac.c, 199
	ethCmdOn
lspg_nextshot_struct, 34	
dsoscaxis_isnull	Ispmac.c, 199
lspg_nextshot_struct, 34	ethCmdQueue
dsowidth	Ispmac.c, 199
lspg_nextshot_struct, 34	ethCmdReply
dsowidth2	Ispmac.c, 199
lspg_nextshot_struct, 35	event
dsowidth2_isnull	lspmac_cmd_queue_struct, 45
lspg_nextshot_struct, 35	Ispmac_dpascii_queue_struct, 46
dsowidth isnull	Istimer_list_struct, 58
_	
lspg_nextshot_struct, 35	events_name
dsphi	Isredis_obj_struct, 56
lspg_nextshot_struct, 35	evp
dsphi2	lsevents_queue_struct, 19
lspg_nextshot_struct, 35	
dsphi2 isnull	f
lspg_nextshot_struct, 35	iniParser::iniParser, 17
dsphi_isnull	mk_pgpmac_redis, 12
• —	first time
lspg_nextshot_struct, 35	Ispmac_bi_struct, 43
dspid	flight
lspg_nextshot_struct, 35	
dspid_isnull	Ispmac.c, 199
lspg_nextshot_struct, 35	pgpmac.h, 330
dummy1	flight_f
md2StatusStruct, 64	Ispmac.c, 200
dummy2	pgpmac.h, 330
md2StatusStruct, 64	flight_oo
dummy3	Ispmac.c, 200
•	pgpmac.h, 330
md2StatusStruct, 64	fluo
dummy4	Ispmac.c, 200
md2StatusStruct, 64	•
dummy5	pgpmac.h, 330
md2StatusStruct, 64	fluor_back
dummy6	Ispmac.c, 200
md2StatusStruct, 64	pgpmac.h, 330
dummy7	fnc
md2StatusStruct, 65	mk_pgpmac_redis, 12
	front dac
dummy8	md2StatusStruct, 65
md2StatusStruct, 65	fs_has_opened
dummy9	·
md2StatusStruct, 65	md2StatusStruct, 65
dummyA	fs_has_opened_globally
md2StatusStruct, 65	md2StatusStruct, 65
dummyB	fs_is_open
md2StatusStruct, 65	md2StatusStruct, 65
dvalue	fscint
	Ispmac.c, 200
Isredis_obj_struct, 56	pgpmac.h, 330
etel_init_ok	fshut
Ispmac.c, 199	
ISDITIAC.C. 199	
pgpmac.h, 329	Ispmac.c, 200 pgpmac.h, 330

gb_cmd	init_nsecs
Ispmac.c, 200	lstimer_list_struct, 58
get	init_secs
iniParser::iniParser, 16	Istimer_list_struct, 58
getcurrentsampleid	ip
lspg_getcurrentsampleid_struct, 23	iniParser, 11
getcurrentsampleid_isnull	
lspg_getcurrentsampleid_struct, 24	jogAbs
getivars	Ispmac_motor_struct, 50
Ispmac.c, 200	, – –
getmvars	k
Ispmac.c, 200	md2cmds cmd kv struct, 59
15pmao.0, 200	kappa
handler	Ispmac.c, 201
Istimer.c, 230	pgpmac.h, 330
hard ini	kappa_act_pos
mk_pgpmac_redis, 12	md2StatusStruct, 65
hard ini fields	kappa_status_1
	md2StatusStruct, 65
mk_pgpmac_redis, 13	kappa status 2
has_option	md2StatusStruct, 65
iniParser::iniParser, 16	
has_section	key
iniParser::iniParser, 16	Isredis_obj_struct, 56
head	LC DC STATE IDLE
mk_pgpmac_redis, 13	LS_PG_STATE_IDLE
hex_dump	lspg.c, 85
Ispmac.c, 137	LS_PG_STATE_INIT
hi	Ispg.c, 85
mk_pgpmac_redis, 13	LS_PG_STATE_RECV
hits	lspg.c, 85
Isredis_obj_struct, 56	LS_PG_STATE_RESET
home	lspg.c, 85
Ispmac motor struct, 50	LS_PG_STATE_SEND
homing	lspg.c, 86
lspmac_motor_struct, 50	LS_PMAC_STATE_CR
hp_air	Ispmac.c, 132
Ispmac.c, 201	LS_PMAC_STATE_GB
pgpmac.h, 330	Ispmac.c, 132
P.Spr. storm,	LS_PMAC_STATE_GMR
i	Ispmac.c, 132
mk_pgpmac_redis, 13	LS PMAC STATE IDLE
in_position_band	Ispmac.c, 132
Ispmac_motor_struct, 50	LS PMAC STATE RESET
inactive init	Ispmac.c, 132
Ispmac motor struct, 50	LS PMAC STATE RR
iniParser, 11	Ispmac.c, 132
ip, 11	LS PMAC STATE SC
iniParser.iniParser, 15	lspmac.c, 133
iniParser.py, 69	LS PMAC STATE WACK
iniParser::iniParser	Ispmac.c, 133
	LS PMAC STATE WCR
init, 16	
f, 17	Ispmac.c, 133
get, 16	LS_PMAC_STATE_WGB
has_option, 16	Ispmac.c, 133
has_section, 16	LSLOGGING_FILE_NAME
options, 16	Islogging.c, 77
read, 16	LSPMAC_MAX_MOTORS
sd, 17	Ispmac.c, 133
sections, 17	LSPMAC_PRESET_REGEX

Ispmac.c, 133	lsevents_queue_off
LSTIMER_LIST_LENGTH	Isevents.c, 75
Istimer.c, 230	lsevents_queue_on
last_nsecs	Isevents.c, 75
Istimer_list_struct, 58	lsevents_queue_struct, 18
last_secs	evp, 19
Istimer_list_struct, 58	lsevents_queue_t
Imsg	Isevents.c, 71
Islogging_queue_struct, 19	Isevents remove listener
lp_air	Isevents.c, 72
Ispmac.c, 201	pgpmac.h, 288
pgpmac.h, 331	Isevents run
ls_pg_state	Isevents.c, 73
Ispg.c, 120	pgpmac.h, 288
ls_pmac_state	Isevents_send_event
Ispmac.c, 201	Isevents.c, 73
IsConnect	pgpmac.h, 289
Ispmac.c, 137	Isevents thread
Isevents.c, 69	lsevents.c, 75
Isevents add listener, 71	Isevents worker
	_
Isevents_init, 72	Isevents.c, 73
Isevents_listener_mutex, 74	Islogging.c, 75
Isevents_listener_t, 71	LSLOGGING_FILE_NAME, 77
lsevents_listeners_p, 74	lslogging_cond, 79
Isevents_queue, 74	Islogging_event_cb, 77
Isevents_queue_cond, 75	lslogging_file, 79
Isevents_queue_mutex, 75	Islogging_init, 77
Isevents_queue_off, 75	Islogging_log_message, 77
lsevents_queue_on, 75	Islogging_mutex, 79
lsevents_queue_t, 71	Islogging_off, 79
Isevents_remove_listener, 72	lslogging_on, 79
Isevents_run, 73	Islogging_queue, 79
Isevents_send_event, 73	Islogging_queue_t, 77
Isevents_thread, 75	Islogging_run, 78
Isevents_worker, 73	Islogging_thread, 79
lsevents_add_listener	Islogging_worker, 78
Isevents.c, 71	lslogging_cond
pgpmac.h, 287	Islogging.c, 79
lsevents_init	lslogging_event_cb
Isevents.c, 72	Islogging.c, 77
pgpmac.h, 288	lslogging_file
lsevents_listener_mutex	Islogging.c, 79
Isevents.c, 74	lslogging_init
lsevents_listener_struct, 17	Islogging.c, 77
cb, 18	pgpmac.h, 289
next, 18	Islogging_log_message
raw_regexp, 18	Islogging.c, 77
re, 18	pgpmac.h, 289
lsevents_listener_t	Islogging_mutex
Isevents.c, 71	Islogging.c, 79
lsevents_listeners_p	Islogging_off
Isevents.c, 74	Islogging.c, 79
Isevents_queue	Islogging_on
Isevents.c, 74	Islogging.c, 79
lsevents_queue_cond	Islogging_queue
Isevents.c, 75	Islogging_queue
lsevents_queue_mutex	Islogging_queue_struct, 19
Isevents.c, 75	Imsg, 19

Itime, 19	lspg_lock_diffractometer_wait, 97
lslogging_queue_t	lspg_next_state, 97
Islogging.c, 77	lspg_nextaction_cb, 98
lslogging_run	lspg_nextsample, 121
Islogging.c, 78	lspg_nextsample_all, 98
pgpmac.h, 290	lspg_nextsample_call, 99
lslogging_thread	lspg_nextsample_cb, 99
Islogging.c, 79	lspg_nextsample_done, 100
lslogging_worker	lspg_nextsample_init, 100
Islogging.c, 78	lspg_nextsample_wait, 100
lspg.c, 80	lspg_nextshot, 121
LS_PG_STATE_IDLE, 85	lspg_nextshot_call, 100
LS_PG_STATE_INIT, 85	lspg_nextshot_cb, 100
LS_PG_STATE_RECV, 85	lspg_nextshot_done, 104
LS_PG_STATE_RESET, 85	lspg_nextshot_init, 104
LS_PG_STATE_SEND, 86	lspg_nextshot_wait, 105
ls_pg_state, 120	lspg_notice_processor, 105
lspg_allkvs_cb, 86	lspg_pg_connect, 105
lspg_array2ptrs, 87	lspg_pg_service, 106
lspg_check_preset_in_position_cb, 88	lspg_preset_changed_cb, 108
lspg_cmd_cb, 89	lspg_query_next, 108
lspg_connectPoll_response, 120	lspg_query_push, 108
lspg_demandairrights, 120	lspg_query_queue, 121
lspg_demandairrights_all, 89	lspg_query_queue_off, 121
lspg_demandairrights_call, 89	lspg_query_queue_on, 121
lspg_demandairrights_cb, 90	lspg_query_queue_reply, 121
lspg_demandairrights_init, 90	lspg_query_reply_next, 109
lspg_demandairrights_wait, 90	lspg_query_reply_peek, 109
lspg_flush, 90	lspg_queue_cond, 121
lspg_getcenter, 120	lspg_queue_mutex, 121
lspg_getcenter_all, 91	lspg_receive, 110
lspg_getcenter_call, 91	lspg_resetPoll_response, 122
lspg_getcenter_cb, 91	lspg_run, 110
lspg_getcenter_done, 92	lspg_sample_detector_cb, 111
lspg_getcenter_init, 92	lspg_send_next_query, 111
lspg_getcenter_wait, 92	lspg_seq_run_prep, 122
lspg_getcurrentsampleid, 120	lspg_seq_run_prep_all, 112
lspg_getcurrentsampleid_call, 93	lspg_seq_run_prep_call, 112
lspg_getcurrentsampleid_cb, 93	lspg_seq_run_prep_cb, 113
lspg_getcurrentsampleid_init, 93	lspg_seq_run_prep_done, 113
lspg_getcurrentsampleid_read, 94	lspg_seq_run_prep_init, 113
lspg_getcurrentsampleid_wait_for_id, 94	lspg_seq_run_prep_t, 86
lspg_init, 94	lspg_seq_run_prep_wait, 113
lspg_lock_detector, 120	lspg_set_scale_cb, 113
lspg_lock_detector_all, 94	lspg_sig_service, 114
lspg_lock_detector_call, 95	lspg_starttransfer, 122
lspg_lock_detector_cb, 95	lspg_starttransfer_all, 114
lspg_lock_detector_done, 95	lspg_starttransfer_call, 115
lspg_lock_detector_init, 95	lspg_starttransfer_cb, 115
lspg_lock_detector_t, 86	lspg_starttransfer_done, 115
lspg_lock_detector_wait, 95	lspg_starttransfer_init, 115
Ispg_lock_diffractometer, 121	lspg_starttransfer_wait, 116
lspg_lock_diffractometer_all, 96	Ispg_thread, 122
lspg_lock_diffractometer_call, 96	lspg_unset_current_preset_moving_cb, 116
lspg_lock_diffractometer_cb, 96	Ispg_update_kvs_cb, 116
lspg_lock_diffractometer_done, 96	lspg_wait_for_detector, 122
lspg_lock_diffractometer_init, 97	lspg_wait_for_detector_all, 117
lspg_lock_diffractometer_t, 86	lspg_wait_for_detector_call, 117

	lspg_wait_for_detector_cb, 117		pgpmac.h, 292
	lspg_wait_for_detector_done, 118	lspg_	_getcenter_init
	lspg_wait_for_detector_init, 118		lspg.c, 92
	lspg_wait_for_detector_t, 86	lspg_	_getcenter_struct, 20
	lspg_wait_for_detector_wait, 118		cond, 21
	lspg_waitcryo, 122		dax, 21
	lspg_waitcryo_all, 118		dax_isnull, 21
	lspg_waitcryo_cb, 119		day, 21
	lspg_waitcryo_init, 119		day_isnull, 22
	lspg_worker, 119		daz, <mark>22</mark>
	lspgfd, 122		daz_isnull, 22
	now, 122		dcx, 22
	q, 122		dcx_isnull, 22
lspg_	_allkvs_cb		dcy, 22
	lspg.c, 86		dcy_isnull, 22
lspg_	_array2ptrs		mutex, 22
	lspg.c, 87		new_value_ready, 22
	pgpmac.h, 290		no_rows_returned, 22
lspg_	_check_preset_in_position_cb		zoom, 23
	lspg.c, 88		zoom_isnull, 23
	_cmd_cb	lspg_	_getcenter_t
	lspg.c, 89		pgpmac.h, 285
lspg_	_connectPoll_response	lspg_	_getcenter_wait
	lspg.c, 120		lspg.c, 92
lspg_	_demandairrights		pgpmac.h, 292
	lspg.c, 120	lspg_	_getcurrentsampleid
	pgpmac.h, 331		lspg.c, 120
lspg_	_demandairrights_all		pgpmac.h, 331
	lspg.c, 89	lspg_	_getcurrentsampleid_call
	pgpmac.h, 292		lspg.c, 93
lspg_	_demandairrights_call	lspg_	_getcurrentsampleid_cb
	lspg.c, 89		lspg.c, 93
lspg_	_demandairrights_cb	lspg_	_getcurrentsampleid_init
	lspg.c, 90		lspg.c, 93
	demandairrightsinit	lspg	_getcurrentsampleid_read
	lspg.c, 90		Ispg.c, 94
lspg_	_demandairrightsstruct, 20	lspg_	_getcurrentsampleid_struct, 23
	cond, 20		cond, 23
	mutex, 20		getcurrentsampleid, 23
	new_value_ready, 20		getcurrentsampleid_isnull, 24
	_demandairrightst		mutex, 24
	pgpmac.h, 285		new_value_ready, 24
	_demandairrightswait		no_rows_returned, 24
	lspg.c, 90		_getcurrentsampleid_t
	_flush		pgpmac.h, 285
	lspg.c, 90		_getcurrentsampleid_wait_for_id
	getcenter		Ispg.c, 94
	lspg.c, 120		pgpmac.h, 292
	pgpmac.h, 331	lspg_	_init
	_getcenter_all		Ispg.c, 94
	lspg.c, 91		pgpmac.h, 293
	_getcenter_call		_lockdetector
	lspg.c, 91		lspg.c, 120
	pgpmac.h, 292		_lockdetectorall
	_getcenter_cb		Ispg.c, 94
	lspg.c, 91	lspg_	_lockdetectorcall
	_getcenter_done		lspg.c, 95
	lspg.c, 92	lspg_	_lockdetectorcb

lspg.c, 95	lspg_nextsample_t
lspg_lock_detector_done	pgpmac.h, 285
Ispg.c, 95	lspg_nextsample_wait
lspg_lock_detector_init	lspg.c, 100
lspg.c, 95	lspg_nextshot
lspg_lock_detector_struct, 24	lspg.c, 121
cond, 24	pgpmac.h, 331
mutex, 24	lspg_nextshot_call
new_value_ready, 25	lspg.c, 100
lspg_lock_detector_t	pgpmac.h, 293
lspg.c, 86	lspg_nextshot_cb
lspg_lock_detector_wait	lspg.c, 100
lspg.c, 95	lspg_nextshot_done
lspg_lock_diffractometer	lspg.c, 104
lspg.c, 121	pgpmac.h, 294
lspg_lock_diffractometer_all	lspg_nextshot_init
lspg.c, 96	lspg.c, 104
lspg_lock_diffractometer_call	lspg_nextshot_struct, 27
lspg.c, 96	active, 29
lspg_lock_diffractometer_cb	active2, 29
lspg.c, 96	active2_isnull, 30
lspg_lock_diffractometer_done	active_isnull, 30
lspg.c, 96	ax, <mark>30</mark>
lspg_lock_diffractometer_init	ax2, 30
lspg.c, 97	ax2_isnull, 30
lspg_lock_diffractometer_struct, 25	ax_isnull, 30
cond, 25	ay, <mark>30</mark>
mutex, 25	ay2, <mark>30</mark>
new_value_ready, 25	ay2_isnull, 30
lspg_lock_diffractometer_t	ay_isnull, 30
lspg.c, 86	az, <mark>30</mark>
lspg_lock_diffractometer_wait	az2, <mark>31</mark>
lspg.c, 97	az2_isnull, 31
lspg_next_state	az_isnull, 31
Ispg.c, 97	cond, 31
lspg_nextaction_cb	cx, 31
Ispg.c, 98	cx2, 31
lspg_nextsample	cx2 isnull, 31
lspg.c, 121	cx_isnull, 31
pgpmac.h, 331	cy, 31
lspg_nextsample_all	cy2, <mark>31</mark>
lspg.c, 98	cy2_isnull, 32
pgpmac.h, 293	cy_isnull, 32
Ispg nextsample call	dsdir, 32
lspg.c, 99	dsdir isnull, 32
lspg_nextsample_cb	dsdist, 32
lspg.c, 99	dsdist2, 32
lspg_nextsample_done	dsdist2_isnull, 32
Ispg.c, 100	dsdist_isnull, 32
Ispg_nextsample_init	dsexp, 32
Ispg.c, 100	dsexp, 32 dsexp2, 32
• -	•
lspg_nextsample_struct, 25	dsexp2_isnull, 33
cond, 26	dsexp_isnull, 33
mutex, 26	dshpid, 33
new_value_ready, 26	dshpid_isnull, 33
nextsample, 26	dskappa, 33
nextsample_isnull, 26	dskappa2, 33
no_rows_returned, 26	dskappa2_isnull, 33

dskappa_isnull, 33	lspg.c, 108
dsnrg, <mark>33</mark>	pgpmac.h, 294
dsnrg2, <mark>33</mark>	lspg_query_queue
dsnrg2_isnull, 34	lspg.c, 121
dsnrg_isnull, 34	lspg_query_queue_off
dsomega, 34	lspg.c, 121
dsomega2, 34	lspg_query_queue_on
dsomega2_isnull, 34	lspg.c, 121
dsomega_isnull, 34	lspg_query_queue_reply
dsoscaxis, 34	lspg.c, 121
dsoscaxis2, 34	lspg_query_queue_t
dsoscaxis2_isnull, 34	pgpmac.h, 285
dsoscaxis_isnull, 34	lspg_query_reply_next
dsowidth, 34	lspg.c, 109
dsowidth2, 35	lspg_query_reply_peek
dsowidth2_isnull, 35	lspg.c, 109
dsowidth_isnull, 35	lspg_queue_cond
dsphi, 35	Ispg.c, 121
dsphi2, 35	Ispg_queue_mutex
dsphi2 isnull, 35	lspg.c, 121
dsphi_isnull, 35	Ispg_receive
dspid, 35	lspg.c, 110
dspid_isnull, 35	Ispg resetPoll response
. —	
mutex, 35	lspg.c, 122
new_value_ready, 36	lspg_run
no_rows_returned, 36	lspg.c, 110
sfn, 36	pgpmac.h, 295
sfn_isnull, 36	lspg_sample_detector_cb
sindex, 36	lspg.c, 111
sindex2, 36	lspg_send_next_query
sindex2_isnull, 36	lspg.c, 111
sindex_isnull, 36	lspg_seq_run_prep
skey, 36	lspg.c, 122
skey_isnull, 36	lspg_seq_run_prep_all
sstart, 37	lspg.c, 112
sstart2, 37	pgpmac.h, 295
sstart2_isnull, 37	lspg_seq_run_prep_call
sstart_isnull, 37	lspg.c, 112
stype, 37	lspg_seq_run_prep_cb
stype2, 37	lspg.c, 113
stype2_isnull, 37	lspg_seq_run_prep_done
stype_isnull, 37	lspg.c, 113
lspg_nextshot_t	lspg_seq_run_prep_init
pgpmac.h, 285	lspg.c, 113
lspg_nextshot_wait	lspg_seq_run_prep_struct, 37
lspg.c, 105	cond, 38
pgpmac.h, 294	mutex, 38
lspg_notice_processor	new_value_ready, 38
Ispg.c, 105	Ispg_seq_run_prep_t
lspg_pg_connect	lspg.c, 86
lspg.c, 105	lspg_seq_run_prep_wait
lspg_pg_service	Ispg.c, 113
Ispg_c, 106	lspg_set_scale_cb
lspg_preset_changed_cb	lspg.c, 113
Ispg_preset_changed_cb	Ispg_sig_service
Ispg_query_next	Ispg_sig_service
Ispg.c, 108	lspg_starttransfer
lspg_query_push	lspg.c, 122

pgpmac.h, 331	pgpmac.h, 296
lspg_starttransfer_all	lspg_waitcryo_init
Ispg.c, 114	lspg.c, 119
lspg_starttransfer_call	lspg_waitcryo_struct, 40
lspg.c, 115	cond, 40
pgpmac.h, 295	mutex, 40
lspg_starttransfer_cb	new_value_ready, 41
lspg.c, 115	lspg_waitcryo_t
lspg_starttransfer_done	pgpmac.h, 285
lspg.c, 115	lspg_worker
pgpmac.h, 296	lspg.c, 119
lspg_starttransfer_init	lspg_zoom_lut_call
lspg.c, 115	pgpmac.h, 296
lspg_starttransfer_struct, 38	lspgQueryQueueStruct, 41
cond, 39	onResponse, 41
mutex, 39	qs, 41
new_value_ready, 39	Ispgfd
no rows returned, 39	lspg.c, 122
starttransfer, 39	Ispmac.c, 123
lspg_starttransfer_t	_lspmac_motor_init, 136
pgpmac.h, 285	alignx, 196
lspg_starttransfer_wait	aligny, 196
Ispg.c, 116	alignz, 196
pgpmac.h, 296	anal, 196
Ispg_thread	apery, 197
Ispg_tiread	apery, 197 aperz, 197
	•
lspg_unset_current_preset_moving_cb	arm_parked, 197
Ispg.c, 116	blight, 197
lspg_update_kvs_cb	blight_down, 197
lspg.c, 116	blight_f, 197
lspg_wait_for_detector	blight_ud, 197
lspg.c, 122	blight_up, 197
lspg_wait_for_detector_all	capy, 197
Ispg.c, 117	capz, 198
lspg_wait_for_detector_call	cenx, 198
lspg.c, 117	ceny, 198
lspg_wait_for_detector_cb	cleanstr, 136
lspg.c, 117	cr_cmd, 198
lspg_wait_for_detector_done	cryo, 198
lspg.c, 118	cryo_back, 198
lspg_wait_for_detector_init	cryo_switch, 198
lspg.c, 118	dbmem, 198
lspg_wait_for_detector_struct, 39	dbmemIn, 198
cond, 40	dryer, 199
mutex, 40	etel_init_ok, 199
new value ready, 40	etel_on, 199
lspg_wait_for_detector_t	etel ready, 199
Ispg.c, 86	ethCmdOff, 199
lspg_wait_for_detector_wait	ethCmdOn, 199
Ispg.c, 118	ethCmdQueue, 199
lspg_waitcryo	ethCmdReply, 199
Ispg_c, 122	flight, 199
pgpmac.h, 331	flight_f, 200
lspg_waitcryo_all	flight oo, 200
Ispg_c, 118	fluo, 200
pgpmac.h, 296	fluor_back, 200
lspg_waitcryo_cb	fscint, 200
lspg.c, 119	fshut, 200

gb_cmd, 200	lspmac_dac_read, 142
getivars, 200	lspmac_dpascii_off, 201
getmvars, 200	lspmac_dpascii_on, 202
hex_dump, 137	lspmac_dpascii_queue, 202
hp_air, 201	lspmac_dpascii_queue_t, 135
kappa, 201	lspmac_est_move_time, 143
LS_PMAC_STATE_CR, 132	lspmac_est_move_time_wait, 148
LS_PMAC_STATE_GB, 132	lspmac_find_motor_by_name, 148
LS_PMAC_STATE_GMR, 132	lspmac_flight_lut_setup, 149
LS_PMAC_STATE_IDLE, 132	lspmac_fscint_lut_setup, 149
LS_PMAC_STATE_RR, 132	lspmac_fshut_init, 149
LS_PMAC_STATE_SC, 133	Ispmac_get_ascii, 150
LS_PMAC_STATE_WACK, 133	lspmac_get_ascii_cb, 150
LS_PMAC_STATE_WCR, 133	lspmac_get_status, 152
LS_PMAC_STATE_WGB, 133	lspmac_get_status_cb, 152
LSPMAC_MAX_MOTORS, 133	Ispmac_getBIPosition, 156
LSPMAC_PRESET_REGEX, 133	Ispmac_getPosition, 157
lp_air, 201	lspmac_home1_queue, 157
ls_pmac_state, 201	lspmac_home2_queue, 159
IsConnect, 137	lspmac_init, 159
Ispmac_Error, 142	lspmac_jogabs_queue, 163
Ispmac_GetAllIVars, 155	lspmac_light_zoom_cb, 163
lspmac_GetAllIVarsCB, 155	lspmac_lut, 164
Ispmac_GetAllMVars, 155	lspmac_more_ascii_cb, 165
lspmac_GetAllMVarsCB, 155	lspmac_motor_init, 165
Ispmac_GetShortReplyCB, 157	Ispmac_motors, 202
Ispmac_Getmem, 156	lspmac_move_or_jog_abs_queue, 165
Ispmac_GetmemReplyCB, 156	lspmac_move_or_jog_preset_queue, 168
Ispmac_Reset, 181	lspmac_move_preset_queue, 169
Ispmac_SendControlReplyPrintCB, 187	lspmac_moveabs_blight_factor_queue, 169
Ispmac_Service, 188	lspmac_moveabs_bo_queue, 170
Ispmac_SockFlush, 191	lspmac_moveabs_flight_factor_queue, 170
Ispmac_SockGetmem, 191	lspmac_moveabs_frontlight_oo_queue, 171
Ispmac_SockSendControlCharPrint, 191	lspmac_moveabs_fshut_queue, 171
Ispmac_SockSendDPControlChar, 191	lspmac_moveabs_queue, 171
Ispmac_SockSendDPControlCharCB, 192	lspmac_moveabs_timed_queue, 172
Ispmac_SockSendDPline, 192	lspmac_moveabs_wait, 173
Ispmac_SockSendDPqueue, 192	Ispmac_movedac_queue, 174
Ispmac_SockSendline, 193	Ispmac_movezoom_queue, 174
Ispmac_SockSendline_nr, 193	Ispmac_moving_cond, 202
lspmac_abort, 138	lspmac_moving_flags, 202
Ispmac_ascii_buffers, 201	Ispmac_moving_mutex, 202
Ispmac_ascii_buffers_mutex, 201	Ispmac_nbis, 202
Ispmac_ascii_buffers_t, 135	lspmac_next_state, 175
Ispmac_ascii_busy, 201	Ispmac_nmotors, 202
Ispmac_ascii_mutex, 201	lspmac_pmacmotor_read, 177
Ispmac_asciicmdCB, 138	lspmac_pop_queue, 180
lspmac_backLight_down_cb, 139	lspmac_pop_reply, 180
lspmac_backLight_up_cb, 139	lspmac_push_queue, 181
Ispmac_bi_init, 139	Ispmac_reset_queue, 181
Ispmac_bis, 201	lspmac_rlut, 182
Ispmac_blight_lut_setup, 139	lspmac_run, 183
Ispmac_bo_init, 140	Ispmac_scint_dried_cb, 184
Ispmac_bo_read, 140	Ispmac_scint_inPosition_cb, 184
Ispmac_combined_move_t, 135	Ispmac_scint_maybe_move_sample_cb, 185
lspmac_command_done_cb, 141	lspmac_scint_maybe_return_sample_cb, 185
Ispmac_cryoSwitchChanged_cb, 141	Ispmac_send_command, 186
Ispmac_dac_init, 141	Ispmac_sendcmd, 186

Ispmac_sendcmd_nocb, 187	VR_UPLOAD, 135
Ispmac_shutter_cond, 202	zoom, 206
lspmac_shutter_has_opened, 202	Ispmac_Error
lspmac_shutter_mutex, 203	Ispmac.c, 142
lspmac_shutter_read, 190	lspmac_GetAllIVars
Ispmac_shutter_state, 203	Ispmac.c, 155
lspmac_soft_motor_init, 194	Ispmac_GetAllIVarsCB
lspmac_soft_motor_read, 194	Ispmac.c, 155
lspmac_status_last_time, 203	Ispmac_GetAllMVars
Ispmac_status_time, 203	Ispmac.c, 155
Ispmac_test_preset, 194	Ispmac_GetAllMVarsCB
Ispmac_video_rotate, 194	Ispmac.c, 155
Ispmac_worker, 195	lspmac_GetShortReplyCB
Ispmac_zoom_lut_setup, 196	Ispmac.c, 157
md2_status, 203	Ispmac_Getmem
md2_status_mutex, 203	Ispmac.c, 156
md2_status_t, 136	Ispmac_GetmemReplyCB
minikappa_ok, 203	Ispmac.c, 156
motors_ht, 203	Ispmac Reset
now, 203	Ispmac.c, 181
omega, 204	Ispmac SendControlReplyPrintCB
omega_zero_search, 204	Ispmac.c, 187
omega_zero_time, 204	Ispmac_Service
omega_zero_velocity, 204	Ispmac.c, 188
PMAC_MIN_CMD_TIME, 134	Ispmac_SockFlush
PMACPORT, 134	Ispmac.c, 191
phi, 204	Ispmac_SockGetmem
•	•
pmac_cmd_size, 133	Ispmac.c, 191
pmac_error_strs, 204	Ispmac_SockSendControlCharPrint
pmac_queue_cond, 205	Ispmac.c, 191
pmac_queue_mutex, 205	Ispmac_SockSendDPControlChar
pmac_thread, 205	Ispmac.c, 191
pmacfd, 205	pgpmac.h, 315
rr_cmd, 205	Ispmac_SockSendDPControlCharCB
sample_detected, 205	Ispmac.c, 192
scint, 205	Ispmac_SockSendDPline
shutter_open, 205	Ispmac.c, 192
smart_mag_err, 205	pgpmac.h, 315
smart_mag_off, 205	Ispmac_SockSendDPqueue
smart_mag_on, 206	Ispmac.c, 192
smart_mag_oo, 206	Ispmac_SockSendline
VR_CTRL_RESPONSE, 134	Ispmac.c, 193
VR_DOWNLOAD, 134	pgpmac.h, 316
VR_FWDOWNLOAD, 134	lspmac_SockSendline_nr
VR_IPADDRESS, 134	Ispmac.c, 193
VR_PMAC_FLUSH, 134	lspmac_abort
VR_PMAC_GETBUFFER, 134	Ispmac.c, 138
VR_PMAC_GETLINE, 134	pgpmac.h, 297
VR_PMAC_GETMEM, 134	lspmac_ascii_buffers
VR_PMAC_GETRESPONSE, 134	Ispmac.c, 201
VR_PMAC_PORT, 135	lspmac_ascii_buffers_mutex
VR_PMAC_READREADY, 135	Ispmac.c, 201
VR_PMAC_SENDLINE, 135	lspmac_ascii_buffers_struct, 42
VR_PMAC_SETBIT, 135	command_buf, 42
VR_PMAC_SETBITS, 135	command_buf_cc, 42
VR_PMAC_SETMEM, 135	command_str, 42
VR_PMAC_WRITEBUFFER, 135	response_buf, 42
VR_PMAC_WRITEERROR, 135	response_n, 42

response_str, 42	Ispmac.c, 202
lspmac_ascii_buffers_t	Ispmac_dpascii_queue
Ispmac.c, 135	Ispmac.c, 202
lspmac_ascii_busy	Ispmac_dpascii_queue_struct, 46
Ispmac.c, 201	event, 46
lspmac_ascii_mutex	pl, 46
Ispmac.c, 201	lspmac_dpascii_queue_t
lspmac_asciicmdCB	Ispmac.c, 135
Ispmac.c, 138	lspmac_est_move_time
lspmac_backLight_down_cb	Ispmac.c, 143
Ispmac.c, 139	pgpmac.h, 297
lspmac_backLight_up_cb	lspmac_est_move_time_wait
Ispmac.c, 139	Ispmac.c, 148
lspmac_bi_init	pgpmac.h, 301
Ispmac.c, 139	lspmac_find_motor_by_name
Ispmac_bi_struct, 42	Ispmac.c, 148
changeEventOff, 43	pgpmac.h, 302
changeEventOn, 43	lspmac_flight_lut_setup
first_time, 43	Ispmac.c, 149
mask, 43	lspmac_fscint_lut_setup
mutex, 43	Ispmac.c, 149
position, 44	lspmac_fshut_init
previous, 44	Ispmac.c, 149
ptr, 44	lspmac_get_ascii
lspmac_bi_t	Ispmac.c, 150
pgpmac.h, 285	lspmac_get_ascii_cb
Ispmac_bis	Ispmac.c, 150
lspmac.c, 201	Ispmac_get_status
Ispmac_blight_lut_setup	Ispmac.c, 152
Ispmac.c, 139	Ispmac_get_status_cb
Ispmac_bo_init	Ispmac.c, 152
Ispmac.c, 140	•
•	Ispmac_getBIPosition Ispmac.c, 156
lspmac_bo_read	
Ispmac.c, 140	pgpmac.h, 302
Ispmac_cmd_queue_struct, 44	Ispmac_getPosition
event, 45	Ispmac.c, 157
no_reply, 45	pgpmac.h, 303
onResponse, 45	lspmac_home1_queue
pcmd, 45	Ispmac.c, 157
time_sent, 45	pgpmac.h, 303
lspmac_combined_move_struct, 45	lspmac_home2_queue
axis, 45	Ispmac.c, 159
coord_num, 45	pgpmac.h, 304
Delta, 46	Ispmac_init
moveme, 46	Ispmac.c, 159
lspmac_combined_move_t	pgpmac.h, 305
Ispmac.c, 135	lspmac_jogabs_queue
lspmac_command_done_cb	Ispmac.c, 163
Ispmac.c, 141	pgpmac.h, 308
lspmac_cryoSwitchChanged_cb	lspmac_light_zoom_cb
Ispmac.c, 141	Ispmac.c, 163
Ispmac_dac_init	lspmac_lut
Ispmac.c, 141	Ispmac.c, 164
lspmac_dac_read	lspmac_more_ascii_cb
Ispmac.c, 142	Ispmac.c, 165
lspmac_dpascii_off	Ispmac_motor_init
Ispmac.c, 201	Ispmac.c, 165
lspmac_dpascii_on	lspmac_motor_struct, 46

active, 49	Ispmac.c, 165
active_init, 49	pgpmac.h, 308
actual_pos_cnts, 49	lspmac_move_or_jog_preset_queue
actual_pos_cnts_p, 49	Ispmac.c, 168
axis, 49	pgpmac.h, 311
command_sent, 49	lspmac_move_or_jog_queue
cond, 49	pgpmac.h, 312
coord_num, 49	lspmac_move_preset_queue
dac_mvar, 49	Ispmac.c, 169
home, 50	pgpmac.h, 312
homing, 50	lspmac_moveabs_blight_factor_queue
in_position_band, 50	Ispmac.c, 169
inactive_init, 50	lspmac_moveabs_bo_queue
jogAbs, 50	Ispmac.c, 170
lut, 50	lspmac_moveabs_flight_factor_queue
max_accel, 50	Ispmac.c, 170
max_pos, 50	lspmac_moveabs_frontlight_oo_queue
max_speed, 50	Ispmac.c, 171
min_pos, 51	lspmac_moveabs_fshut_queue
motion_seen, 51	Ispmac.c, 171
motor_num, 51	lspmac_moveabs_queue
moveAbs, 51	Ispmac.c, 171
mutex, 51	pgpmac.h, 312
name, 51	lspmac_moveabs_timed_queue
neg_limit_hit, 51	Ispmac.c, 172
neutral_pos, 51	lspmac_moveabs_wait
nlut, 51	Ispmac.c, 173
not_done, 52	pgpmac.h, 313
pos_limit_hit, 52	lspmac_movedac_queue
position, 52	Ispmac.c, 174
pq, 52	lspmac_movezoom_queue
precision, 52	Ispmac.c, 174
printf_fmt, 52	lspmac_moving_cond
read, 52	Ispmac.c, 202
read_mask, 52	pgpmac.h, 332
read_ptr, 52	lspmac_moving_flags
redis_fmt, 53	Ispmac.c, 202
redis_position, 53	pgpmac.h, 332
reported_pg_position, 53	lspmac_moving_mutex
reported_position, 53	Ispmac.c, 202
requested_pos_cnts, 53	pgpmac.h, 332
requested_position, 53	lspmac_nbis
status1, 53	Ispmac.c, 202
status1_p, 53	lspmac_next_state
status2, 53	Ispmac.c, 175
status2_p, 54	lspmac_nmotors
status_str, 54	Ispmac.c, 202
u2c, 54	pgpmac.h, 332
unit, 54	lspmac_pmacmotor_read
update_resolution, 54	Ispmac.c, 177
win, 54	lspmac_pop_queue
write_fmt, 54	Ispmac.c, 180
Ispmac_motor_t	lspmac_pop_reply
pgpmac.h, 285	Ispmac.c, 180
Ispmac_motors	lspmac_push_queue
Ispmac.c, 202	Ispmac.c, 181
pgpmac.h, 331	Ispmac_reset_queue
Ispmac_move_or_jog_abs_queue	Ispmac.c, 181
	,

lspmac_rlut	Isredis_cond, 225
Ispmac.c, 182	Isredis_debugCB, 212
lspmac_run	Isredis_delRead, 213
Ispmac.c, 183	Isredis_delWrite, 213
pgpmac.h, 314	Isredis_fd_service, 213
Ispmac_scint_dried_cb	Isredis_find_preset, 213
Ispmac.c, 184	Isredis_find_preset_index_by_position, 214
Ispmac_scint_inPosition_cb	Isredis_get_obj, 215
Ispmac.c, 184	lsredis_get_or_set_d, 215
lspmac_scint_maybe_move_sample_cb	lsredis_get_or_set_l, 215
Ispmac.c, 185	Isredis get string array, 216
lspmac_scint_maybe_return_sample_cb	Isredis_getb, 216
Ispmac.c, 185	Isredis_getc, 216
lspmac_send_command	Isredis_getd, 217
Ispmac.c, 186	Isredis_getl, 217
lspmac_sendcmd	Isredis_getstr, 217
Ispmac.c, 186	Isredis head, 225
lspmac_sendcmd_nocb	Isredis_hgetCB, 217
Ispmac.c, 187	Isredis_htab, 225
lspmac_shutter_cond	Isredis_init, 218
Ispmac.c, 202	Isredis key select regex, 225
pgpmac.h, 332	Isredis_keysCB, 219
lspmac_shutter_has_opened	Isredis_maybe_add_key, 219
Ispmac.c, 202	Isredis mutex, 226
pgpmac.h, 332	Isredis_objs, 226
lspmac_shutter_mutex	Isredis_publisher, 226
lspmac.c, 203	Isredis_regexec, 220
pgpmac.h, 332	Isredis_run, 220
Ispmac_shutter_read	Isredis_running, 226
Ispmac.c, 190	Isredis_set_preset, 220
Ispmac_shutter_state	Isredis_set_value, 221
Ispmac.c, 203	Isredis_setstr, 221
pgpmac.h, 332	Isredis_sig_service, 222
Ispmac soft motor init	Isredis subCB, 223
Ispmac.c, 194	Isredis_thread, 226
Ispmac_soft_motor_read	Isredis_worker, 224
Ispmac.c, 194	redisDisconnectCB, 225
Ispmac_status_last_time	roac, 226
Ispmac.c, 203	rofd, 226
Ispmac_status_time	subac, 226
Ispmac.c, 203	subfd, 226
Ispmac test preset	wrac, 226
Ispmac.c, 194	wrfd, 226
Ispmac_video_rotate	Isredis addRead
Ispmac.c, 194	Isredis.c, 211
pgpmac.h, 316	Isredis.c, 211 Isredis_addWrite
Ispmac worker	Isredis.c, 211
Ispmac.c, 195	Isredis_cleanup
•	Isredis.c, 211
Ispmac_zoom_lut_setup Ispmac.c, 196	Isredis_cmpnstr
•	
Isredis.c, 206	Isredis.c, 211
_lsredis_get_obj, 209	pgpmac.h, 317
_lsredis_set_value, 210	Isredis_cmpstr
Isredis_addRead, 211	Isredis.c, 212
Isredis_addWrite, 211	pgpmac.h, 317
Isredis_cleanup, 211	Isredis_cond
Isredis_cmpnstr, 211	Isredis.c, 225
Isredis_cmpstr, 212	pgpmac.h, 332

Isredis_debugCB	avalue, 55
Isredis.c, 212	bvalue, 55
Isredis_delRead	cond, 55
Isredis.c, 213	cvalue, 56
Isredis_delWrite	dvalue, 56
Isredis.c, 213	events_name, 56
Isredis_fd_service	hits, 56
Isredis.c, 213	key, 56
lsredis_find_preset	Ivalue, 56
Isredis.c, 213	mutex, 56
pgpmac.h, 317	next, 56
Isredis_find_preset_index_by_position	valid, 56
Isredis.c, 214	value, 57
pgpmac.h, 318	value_length, 57
Isredis_get_obj	wait_for_me, 57
Isredis.c, 215	Isredis_obj_t
pgpmac.h, 318	pgpmac.h, 285
Isredis_get_or_set_d	Isredis objs
Isredis.c, 215	Isredis_objs
Isredis.c, 210	Isredis_publisher
Isredis.c, 215	Isredis.c, 226
	•
Isredis_get_string_array	Isredis_regexec
Isredis.c, 216	Isredis.c, 220
pgpmac.h, 319	pgpmac.h, 322
Isredis_getb	Isredis_run
Isredis.c, 216	Isredis.c, 220
pgpmac.h, 319	pgpmac.h, 322
Isredis_getc	Isredis_running
Isredis.c, 216	Isredis.c, 226
pgpmac.h, 319	pgpmac.h, 333
lsredis_getd	Isredis_set_preset
Isredis.c, 217	Isredis.c, 220
pgpmac.h, 320	pgpmac.h, 322
Isredis_getl	Isredis_set_value
Isredis.c, 217	Isredis.c, 221
pgpmac.h, 320	Isredis_setstr
Isredis_getstr	Isredis.c, 221
Isredis.c, 217	pgpmac.h, 323
pgpmac.h, 320	Isredis_sig_service
Isredis head	Isredis.c, 222
Isredis.c, 225	Isredis subCB
lsredis_hgetCB	Isredis.c, 223
Isredis.c, 217	Isredis thread
Isredis htab	Isredis.c, 226
Isredis.c, 225	Isredis worker
Isredis init	Isredis_worker
Isredis.c, 218	Istest.c, 227
pgpmac.h, 320	lstest_lspmac_est_move_time, 227
Isredis_key_select_regex	Istest_main, 228
Isredis.c, 225	lstest_lspmac_est_move_time
Isredis_keysCB	Istest.c, 227
Isredis.c, 219	Istest_main
lsredis_maybe_add_key	Istest.c, 228
Isredis.c, 219	pgpmac.h, 324
Isredis_mutex	Istimer.c, 228
Isredis.c, 226	handler, 230
pgpmac.h, 333	LSTIMER_LIST_LENGTH, 230
Isredis_obj_struct, 54	Istimer_active_timers, 234

lstimer_add_timer, 230	lsredis_obj_struct, 56
Istimer_cond, 234	MESSAGE SAGE LENGTH
Istimer_init, 231	MD2CMDS_CMD_LENGTH
Istimer_list, 234	pgpmac.h, 284
Istimer_list_t, 230	main
Istimer_mutex, 234	pgpmac.c, 272
Istimer_run, 232	mask
lstimer_thread, 234	lspmac_bi_struct, 43
Istimer_timerid, 234	max_accel
lstimer_worker, 232	lspmac_motor_struct, 50
new_timer, 235	max_pos
service_timers, 233	lspmac_motor_struct, 50
Istimer_active_timers	max_speed
Istimer.c, 234	Ispmac_motor_struct, 50
lstimer_add_timer	md2_status
Istimer.c, 230	Ispmac.c, 203
pgpmac.h, 324	md2_status_mutex lspmac.c, 203
lstimer_cond	· ·
Istimer.c, 234	pgpmac.h, 333
Istimer_init	md2_status_t
Istimer.c, 231	Ispmac.c, 136
pgpmac.h, 325	md2StatusStruct, 60
Istimer_list	acc11c_1, 61
Istimer.c, 234	acc11c_2, 61
Istimer_list_struct, 57	acc11c_3, 61
delay_nsecs, 58	acc11c_5, 61
delay_secs, 58	acc11c_6, 61
event, 58	alignx_act_pos, 61
init_nsecs, 58	alignx_status_1, 62
init_secs, 58	alignx_status_2, 62
last_nsecs, 58	aligny_act_pos, 62
last secs, 58	aligny_status_1, 62
ncalls, 58	aligny_status_2, 62
next_nsecs, 59	alignz_act_pos, 62
next secs, 59	alignz_status_1, 62
shots, 59	alignz_status_2, 62
Istimer_list_t	analyzer_act_pos, 62
Istimer.c, 230	analyzer_status_1, 62
Istimer_mutex	analyzer_status_2, 62
Istimer.c, 234	aperturey_act_pos, 62
Istimer_run	aperturey_status_1, 63
Istimer.c, 232	aperturey_status_2, 63
pgpmac.h, 325	aperturez_act_pos, 63
Istimer thread	aperturez_status_1, 63
Istimer.c, 234	aperturez_status_2, 63
Istimer timerid	back_dac, 63
Istimer.c, 234	capy_act_pos, 63
Istimer worker	capy_status_1, 63
Istimer.c, 232	capy_status_2, 63
	capz_act_pos, 63
Isupdate_init	capz_status_1, 63
pgpmac.h, 325 Isupdate_run	capz_status_2, 63
• —	centerx_act_pos, 64
pgpmac.h, 325 Itime	centerx_status_1, 64
	centery_status_2, 64
Islogging_queue_struct, 19	centery_act_pos, 64
lut	centery_status_1, 64
lspmac_motor_struct, 50	centery_status_2, 64
Ivalue	dummy1, 64

	dummy2, 64	md2cmds_is_moving, 245
	dummy3, 64	md2cmds_kappaphi_move, 245
	dummy4, 64	md2cmds_maybe_done_homing_cb, 246
	dummy5, 64	md2cmds_maybe_done_moving_cb, 246
	dummy6, 64	md2cmds_maybe_rotate_done_cb, 247
	dummy7, 65	md2cmds_mdysc_rotate_done_ds, 247
	dummy8, 65	md2cmds_move_prep, 247
	dummy9, 65	md2cmds move wait, 247
	dummyA, 65	md2cmds_move_wait, 247 md2cmds moveAbs, 248
	•	- · · · · · · · · · · · · · · · · · · ·
	dummyB, 65	md2cmds_moveRel, 249 md2cmds moving cond, 269
	front_dac, 65	_
	fs_has_opened, 65	md2cmds_moving_count, 270
	fs_has_opened_globally, 65	md2cmds_moving_mutex, 270
	fs_is_open, 65	md2cmds_moving_queue_wait, 270
	kappa_act_pos, 65	md2cmds_mutex, 270
	kappa_status_1, 65	md2cmds_mvcenter_move, 250
	kappa_status_2, 65	md2cmds_organs_move_presets, 250
	moving_flags, 66	md2cmds_phase_beamLocation, 251
	number_passes, 66	md2cmds_phase_center, 252
	omega_act_pos, 66	md2cmds_phase_change, 253
	omega_status_1, 66	md2cmds_phase_dataCollection, 254
	omega_status_2, 66	md2cmds_phase_manualMount, 255
	phi_act_pos, 66	md2cmds_phase_robotMount, 257
	phi_status_1, 66	md2cmds_phase_safe, 258
	phi_status_2, 66	md2cmds_prep_axis, 259
	phiscan, 66	md2cmds_rotate, 259
	scint_act_pos, 66	md2cmds_rotate_cb, 261
	scint_piezo, 66	md2cmds_run, 262
	scint_status_1, 66	md2cmds_run_cmd, 262
	scint_status_2, 67	md2cmds_set, 263
	zoom_act_pos, 67	md2cmds_set_scale_cb, 264
	zoom_status_1, 67	md2cmds_test, 264
	zoom_status_2, 67	md2cmds_thread, 270
md2	cmds.c, 235	md2cmds_time_capz_cb, 264
	md2cmds_abort, 238	md2cmds_transfer, 265
	md2cmds_action_queue, 238	md2cmds_worker, 267
	md2cmds_action_wait, 239	rotating, 270
	md2cmds_capz_moving_time, 268	md2cmds_abort
	md2cmds_center, 239	md2cmds.c, 238
	md2cmds_cmd, 268	md2cmds_action_queue
	md2cmds_cmd_kv_t, 238	md2cmds.c, 238
	md2cmds_cmd_kvs, 269	md2cmds_action_wait
	md2cmds_cmd_regex, 269	md2cmds.c, 239
	md2cmds_collect, 239	md2cmds_capz_moving_time
	md2cmds_cond, 269	md2cmds.c, 268
	md2cmds_coordsys_1_stopped_cb, 243	md2cmds_center
	md2cmds_coordsys_2_stopped_cb, 243	md2cmds.c, 239
	md2cmds_coordsys_3_stopped_cb, 243	md2cmds_cmd
	md2cmds_coordsys_4_stopped_cb, 243	md2cmds.c, 268
	md2cmds_coordsys_5_stopped_cb, 243	pgpmac.h, 333
	md2cmds_coordsys_7_stopped_cb, 243	md2cmds_cmd_kv_struct, 59
	md2cmds_hmap, 269	k, 59
	md2cmds_home_prep, 244	v, 59
	md2cmds_home_wait, 244	md2cmds_cmd_kv_t
	md2cmds_homing_cond, 269	md2cmds.c, 238
	md2cmds_homing_count, 269	md2cmds_cmd_kvs
	md2cmds_homing_mutex, 269	md2cmds.c, 269
	md2cmds_init, 244	md2cmds_cmd_regex

md2cmds.c, 269	md2cmds_moving_mutex
md2cmds_collect	md2cmds.c, 270
md2cmds.c, 239	md2cmds_moving_queue_wait
md2cmds_cond	md2cmds.c, 270
md2cmds.c, 269	md2cmds_mutex
pgpmac.h, 333	md2cmds.c, 270
md2cmds_coordsys_1_stopped_cb	pgpmac.h, 333
md2cmds.c, 243	md2cmds_mvcenter_move
md2cmds_coordsys_2_stopped_cb	md2cmds.c, 250
md2cmds.c, 243	md2cmds_organs_move_presets
md2cmds_coordsys_3_stopped_cb	md2cmds.c, 250
md2cmds.c, 243	md2cmds_pg_cond
md2cmds_coordsys_4_stopped_cb	pgpmac.h, 333
md2cmds.c, 243	md2cmds_pg_mutex
md2cmds_coordsys_5_stopped_cb	pgpmac.h, 333
md2cmds.c, 243	md2cmds_phase_beamLocation
md2cmds_coordsys_7_stopped_cb	md2cmds.c, 251
md2cmds.c, 243	md2cmds_phase_center
md2cmds_hmap	md2cmds.c, 252
md2cmds.c, 269	md2cmds_phase_change
md2cmds_home_prep	md2cmds.c, 253
md2cmds.c, 244	md2cmds_phase_dataCollection
md2cmds_home_wait	md2cmds.c, 254
md2cmds.c, 244	md2cmds_phase_manualMount
md2cmds_homing_cond	md2cmds.c, 255
md2cmds.c, 269	md2cmds_phase_robotMount
md2cmds_homing_count	md2cmds.c, 257
md2cmds.c, 269	md2cmds_phase_safe
md2cmds_homing_mutex	md2cmds.c, 258
md2cmds.c, 269	md2cmds_prep_axis
md2cmds init	md2cmds.c, 259
md2cmds.c, 244	md2cmds_rotate
pgpmac.h, 325	md2cmds.c, 259
md2cmds is moving	md2cmds rotate cb
md2cmds.c, 245	md2cmds.c, 261
md2cmds_kappaphi_move	md2cmds run
md2cmds.c, 245	md2cmds.c, 262
md2cmds_maybe_done_homing_cb	pgpmac.h, 326
md2cmds.c, 246	md2cmds_run_cmd
md2cmds_maybe_done_moving_cb	md2cmds.c, 262
md2cmds.c, 246	md2cmds set
md2cmds_maybe_rotate_done_cb	md2cmds.c, 263
md2cmds.c, 247	md2cmds_set_scale_cb
md2cmds.c, 247	md2cmds.c, 264
md2cmds.c, 269	md2cmds test
	_
pgpmac.h, 333	md2cmds.c, 264
md2cmds_move_prep	md2cmds_thread
md2cmds.c, 247	md2cmds.c, 270
md2cmds_move_wait	md2cmds_time_capz_cb
md2cmds.c, 247	md2cmds.c, 264
md2cmds_moveAbs	md2cmds_transfer
md2cmds.c, 248	md2cmds.c, 265
md2cmds_moveRel	md2cmds_worker
md2cmds.c, 249	md2cmds.c, 267
md2cmds_moving_cond	min_pos
md2cmds.c, 269	lspmac_motor_struct, 51
md2cmds_moving_count	minikappa_ok
md2cmds.c, 270	Ispmac.c, 203

pgpmac.h, 333	Isredis obj struct, 56
mk_pgpmac_redis, 11	1010010_00j_01100t; 00
active_simulation, 12	name
asis, 12	Ispmac_motor_struct, 51
b, 12	ncalls
bi_list, 12	Istimer_list_struct, 58
f, 12	ncurses_mutex
fnc, 12	pgpmac.c, 275
hard_ini, 12	pgpmac.h, 333
hard_ini_fields, 13	neg_limit_hit
head, 13	Ispmac_motor_struct, 51
hi, 1 <mark>3</mark>	neutral_pos
i, 13	lspmac_motor_struct, 51
motor_dict, 13	new_timer
motor_field_lists, 13	Istimer.c, 235
motor_presets, 13	new_value_ready
p, 13	lspg_demandairrights_struct, 20
pi, 13	lspg_getcenter_struct, 22
ppos, 13	lspg_getcurrentsampleid_struct, 24
pref_ini, 14	lspg_lock_detector_struct, 25
v, 14	lspg_lock_diffractometer_struct, 25
x, 14	lspg_nextsample_struct, 26
xlate, 14	lspg_nextshot_struct, 36
y, 14	lspg_seq_run_prep_struct, 38
zoom_settings, 14	lspg_starttransfer_struct, 39
mk_pgpmac_redis.py, 270	lspg_wait_for_detector_struct, 40
motion_seen	lspg_waitcryo_struct, 41
Ispmac_motor_struct, 51	next
motor_dict	lsevents_listener_struct, 18 lsredis_obj_struct, 56
mk_pgpmac_redis, 13	next nsecs
motor_field_lists	Istimer_list_struct, 59
mk_pgpmac_redis, 13	next secs
motor_num	Istimer_list_struct, 59
Ispmac_motor_struct, 51	nextsample
motor_presets	lspg_nextsample_struct, 26
mk_pgpmac_redis, 13	nextsample_isnull
motors_ht	lspg_nextsample_struct, 26
Ispmac.c, 203	nlut
moveAbs	Ispmac_motor_struct, 51
Ispmac_motor_struct, 51	no_reply
moveme	lspmac_cmd_queue_struct, 45
Ispmac_combined_move_struct, 46	no_rows_returned
moving_flags	lspg_getcenter_struct, 22
md2StatusStruct, 66	lspg_getcurrentsampleid_struct, 24
mutex	lspg_nextsample_struct, 26
lspg_demandairrights_struct, 20	lspg_nextshot_struct, 36
lspg_getcenter_struct, 22	lspg_starttransfer_struct, 39
lspg_getcurrentsampleid_struct, 24	not_done
lspg_lock_detector_struct, 24	Ispmac_motor_struct, 52
lspg_lock_diffractometer_struct, 25	now
lspg_nextsample_struct, 26	lspg.c, 122
Ispg_nextshot_struct, 35	Ispmac.c, 203
lspg_seq_run_prep_struct, 38	number_passes
Ispg_starttransfer_struct, 39	md2StatusStruct, 66
Ispg_wait_for_detector_struct, 40	omega
lspg_waitcryo_struct, 40	omega
Ispmac_bi_struct, 43 Ispmac_motor_struct, 51	Ispmac.c, 204
ispinac_motor_struct, 31	pgpmac.h, 333

omega_act_pos	cryo_switch, 329
md2StatusStruct, 66	dryer, 329
omega_status_1	etel_init_ok, 329
md2StatusStruct, 66	etel_on, 329
omega_status_2	etel_ready, 329
md2StatusStruct, 66	flight, 330
omega_zero_search	flight_f, 330
Ispmac.c, 204	flight_oo, 330
omega_zero_time	fluo, 330
Ispmac.c, 204	fluor_back, 330
pgpmac.h, 334	fscint, 330
omega_zero_velocity	fshut, 330
Ispmac.c, 204	hp_air, 330
onResponse	kappa, 330
IspgQueryQueueStruct, 41	lp_air, 331
lspmac_cmd_queue_struct, 45	Isevents_add_listener, 287
options	Isevents_init, 288
iniParser::iniParser, 16	Isevents remove listener, 288
,	Isevents_run, 288
p	Isevents_send_event, 289
mk_pgpmac_redis, 13	
PMAC_MIN_CMD_TIME	Islogging_init, 289
Ispmac.c, 134	Islogging_log_message, 289
PMACPORT	lslogging_run, 290
Ispmac.c, 134	lspg_array2ptrs, 290
pcmd	lspg_demandairrights, 331
Ispmac_cmd_queue_struct, 45	lspg_demandairrights_all, 292
pgpmac.c, 271	lspg_demandairrights_t, 285
main, 272	lspg_getcenter, 331
ncurses_mutex, 275	lspg_getcenter_call, 292
pgpmac_printf, 274	lspg_getcenter_done, 292
running, 275	lspg_getcenter_t, 285
stdinService, 274	lspg_getcenter_wait, 292
stdinfda, 275	lspg_getcurrentsampleid, 331
term_input, 275	lspg_getcurrentsampleid_t, 285
term_output, 276	lspg_getcurrentsampleid_wait_for_id, 292
term status, 276	lspg_init, 293
term_status2, 276	lspg_nextsample, 331
pgpmac.h, 276	lspg_nextsample_all, 293
GNU SOURCE, 284	lspg_nextsample_t, 285
_GNO_SOONCE, 284 _Isredis_get_obj, 286	Ispg_nextshot, 331
	lspg_nextshot_call, 293
alignx, 327	Ispg nextshot done, 294
aligny, 327 alignz, 327	Ispg_nextshot_t, 285
	Ispg nextshot wait, 294
anal, 327	Ispg_query_push, 294
apery, 327	Ispg_query_queue_t, 285
aperz, 328	
arm_parked, 328	lspg_run, 295
blight, 328	lspg_seq_run_prep_all, 295
blight_down, 328	lspg_starttransfer, 331
blight_f, 328	lspg_starttransfer_call, 295
blight_ud, 328	lspg_starttransfer_done, 296
blight_up, 328	lspg_starttransfer_t, 285
capy, 328	lspg_starttransfer_wait, 296
capz, 328	lspg_waitcryo, 331
cenx, 329	lspg_waitcryo_all, 296
ceny, 329	lspg_waitcryo_cb, 296
cryo, 329	lspg_waitcryo_t, 285
cryo_back, 329	lspg_zoom_lut_call, 296

lspmac_SockSendDPControlChar, 315	MD2CMDS_CMD_LENGTH, 284
Ispmac_SockSendDPline, 315	md2_status_mutex, 333
Ispmac_SockSendline, 316	md2cmds_cmd, 333
Ispmac_abort, 297	md2cmds_cond, 333
lspmac_bi_t, 285	md2cmds_init, 325
Ispmac_est_move_time, 297	md2cmds_md_status_code, 333
Ispmac_est_move_time_wait, 301	md2cmds_mutex, 333
lspmac_find_motor_by_name, 302	md2cmds_pg_cond, 333
Ispmac_getBIPosition, 302	md2cmds_pg_mutex, 333
Ispmac_getPosition, 303	md2cmds_run, 326
Ispmac_home1_queue, 303	minikappa_ok, 333
lspmac_home2_queue, 304	ncurses_mutex, 333
Ispmac_init, 305	omega, 333
lspmac_jogabs_queue, 308	omega_zero_time, 334
lspmac_motor_t, 285	pgpmac_printf, 327
Ispmac_motors, 331	phi, 334
lspmac_move_or_jog_abs_queue, 308	pmac_cmd_queue_t, 285
<pre>lspmac_move_or_jog_preset_queue, 311</pre>	pmac_cmd_t, 285
lspmac_move_or_jog_queue, 312	pmac_queue_cond, 334
Ispmac_move_preset_queue, 312	pmac_queue_mutex, 334
lspmac_moveabs_queue, 312	PmacSockSendline, 327
Ispmac_moveabs_wait, 313	sample_detected, 334
Ispmac_moving_cond, 332	scint, 334
lspmac_moving_flags, 332	shutter_open, 334
Ispmac_moving_mutex, 332	smart_mag_err, 334
Ispmac_nmotors, 332	smart_mag_off, 334
Ispmac_run, 314	smart_mag_on, 335
Ispmac_shutter_cond, 332	smart_mag_oo, 335
Ispmac_shutter_has_opened, 332	term_input, 335
Ispmac_shutter_mutex, 332	term_output, 335
Ispmac_shutter_state, 332	term_status, 335
Ispmac_video_rotate, 316	term_status2, 335
Isredis_cmpnstr, 317	zoom, 335
Isredis_cmpstr, 317	pgpmac_printf
Isredis_cond, 332	pgpmac.c, 274
Isredis_find_preset, 317	pgpmac.h, 327
Isredis_find_preset_index_by_position, 318	phi
Isredis_get_obj, 318	Ispmac.c, 204
Isredis_get_string_array, 319	pgpmac.h, 334
Isredis_getb, 319	phi_act_pos
Isredis_getc, 319	md2StatusStruct, 66
Isredis_getd, 320	phi_status_1
Isredis_getI, 320	md2StatusStruct, 66
Isredis_getstr, 320	phi_status_2
Isredis_init, 320	md2StatusStruct, 66
Isredis_mutex, 333	phiscan
Isredis_obj_t, 285	md2StatusStruct, 66
Isredis_regexec, 322	pi
Isredis_run, 322	mk_pgpmac_redis, 13
Isredis_running, 333	pl
Isredis_set_preset, 322	Ispmac_dpascii_queue_struct, 46
Isredis_setstr, 323	pmac_cmd_queue_t
Istest_main, 324	pgpmac.h, 285
Istimer_add_timer, 324	pmac_cmd_size
Istimer_init, 325	Ispmac.c, 133
Istimer_run, 325	pmac_cmd_t
Isupdate_init, 325	pgpmac.h, 285
lsupdate_run, 325	pmac_error_strs

Janmaa a 204	Paguant
Ispmac.c, 204	Request
pmac_queue_cond	tagEthernetCmd, 68
Ispmac.c, 205	RequestType
pgpmac.h, 334	tagEthernetCmd, 68
pmac_queue_mutex	requested_pos_cnts
Ispmac.c, 205	lspmac_motor_struct, 53
pgpmac.h, 334	requested_position
pmac_thread	lspmac_motor_struct, 53
Ispmac.c, 205	response_buf
PmacSockSendline	lspmac_ascii_buffers_struct, 42
pgpmac.h, 327	response_n
pmacfd	lspmac_ascii_buffers_struct, 42
Ispmac.c, 205	response_str
pos_limit_hit	lspmac_ascii_buffers_struct, 42
lspmac_motor_struct, 52	roac
position	Isredis.c, 226
lspmac_bi_struct, 44	rofd
Ispmac_motor_struct, 52	Isredis.c, 226
ppos	rotating
mk_pgpmac_redis, 13	md2cmds.c, 270
pq	rr_cmd
Ispmac_motor_struct, 52	Ispmac.c, 205
precision	running
Ispmac_motor_struct, 52	pgpmac.c, 275
pref_ini	pgp
mk_pgpmac_redis, 14	sample_detected
previous	Ispmac.c, 205
lspmac_bi_struct, 44	pgpmac.h, 334
printf_fmt	scint
. –	Ispmac.c, 205
lspmac_motor_struct, 52	pgpmac.h, 334
ptr	scint_act_pos
lspmac_bi_struct, 44	md2StatusStruct, 66
2	scint_piezo
q long o 100	md2StatusStruct, 66
lspg.c, 122	scint_status_1
qs	md2StatusStruct, 66
lspgQueryQueueStruct, 41	scint_status_2
raw rodovn	md2StatusStruct, 67
raw_regexp	
Isevents_listener_struct, 18	sd
re	iniParser::iniParser, 17
lsevents_listener_struct, 18	sections
read	iniParser::iniParser, 17
iniParser::iniParser, 16	service_timers
lspmac_motor_struct, 52	Istimer.c, 233
read_mask	sfn
Ispmac_motor_struct, 52	lspg_nextshot_struct, 36
read_ptr	sfn_isnull
Ispmac_motor_struct, 52	lspg_nextshot_struct, 36
redis_fmt	shots
lspmac_motor_struct, 53	Istimer_list_struct, 59
redis_position	shutter_open
Ispmac_motor_struct, 53	Ispmac.c, 205
redisDisconnectCB	pgpmac.h, 334
Isredis.c, 225	sindex
reported_pg_position	lspg_nextshot_struct, 36
Ispmac_motor_struct, 53	sindex2
reported_position	lspg_nextshot_struct, 36
Ispmac_motor_struct, 53	sindex2 isnull
• – – ′	-

Ispg_nextshot_struct, 36 sindex_isnull	RequestType, 68 wIndex, 68 wLength, 68
lspg_nextshot_struct, 36 skey	wValue, 68
lspg_nextshot_struct, 36	term_input
skey_isnull	pgpmac.c, 275
lspg_nextshot_struct, 36	pgpmac.h, 335
smart_mag_err	term_output
Ispmac.c, 205	pgpmac.c, 276
pgpmac.h, 334	pgpmac.h, 335
smart_mag_off	term_status
Ispmac.c, 205	pgpmac.c, 276
pgpmac.h, 334	pgpmac.h, 335
smart_mag_on	term_status2
Ispmac.c, 206	pgpmac.c, 276
pgpmac.h, 335	pgpmac.h, 335
smart_mag_oo	time_sent
Ispmac.c, 206	lspmac_cmd_queue_struct, 45
pgpmac.h, 335	
sstart	u2c
lspg_nextshot_struct, 37	lspmac_motor_struct, 54
sstart2	unit
lspg_nextshot_struct, 37	Ispmac_motor_struct, 54
sstart2_isnull	update_resolution
lspg_nextshot_struct, 37	Ispmac_motor_struct, 54
sstart_isnull	1 = = /
lspg_nextshot_struct, 37	V
starttransfer	md2cmds_cmd_kv_struct, 59
	mk_pgpmac_redis, 14
lspg_starttransfer_struct, 39	VR_CTRL_RESPONSE
status1	Ispmac.c, 134
lspmac_motor_struct, 53	VR DOWNLOAD
status1_p	Ispmac.c, 134
lspmac_motor_struct, 53	VR FWDOWNLOAD
status2	Ispmac.c, 134
lspmac_motor_struct, 53	VR IPADDRESS
status2_p	Ispmac.c, 134
Ispmac_motor_struct, 54	VR_PMAC_FLUSH
status_str	
Ispmac_motor_struct, 54	Ispmac.c, 134
stdinService	VR_PMAC_GETBUFFER
pgpmac.c, 274	Ispmac.c, 134
stdinfda	VR_PMAC_GETLINE
pgpmac.c, 275	Ispmac.c, 134
stype	VR_PMAC_GETMEM
lspg_nextshot_struct, 37	Ispmac.c, 134
stype2	VR_PMAC_GETRESPONSE
lspg_nextshot_struct, 37	Ispmac.c, 134
stype2_isnull	VR_PMAC_PORT
lspg_nextshot_struct, 37	Ispmac.c, 135
stype_isnull	VR_PMAC_READREADY
lspg_nextshot_struct, 37	Ispmac.c, 135
subac	VR_PMAC_SENDCTRLCHAR
Isredis.c, 226	Ispmac.c, 135
subfd	VR_PMAC_SENDLINE
Isredis.c, 226	Ispmac.c, 135
	VR_PMAC_SETBIT
tagEthernetCmd, 67	Ispmac.c, 135
bData, 68	VR_PMAC_SETBITS
Request, 68	 Ispmac.c, 135
•	•

```
VR_PMAC_SETMEM
    Ispmac.c, 135
VR_PMAC_WRITEBUFFER
    Ispmac.c, 135
VR_PMAC_WRITEERROR
    Ispmac.c, 135
VR_UPLOAD
    Ispmac.c, 135
valid
    Isredis_obj_struct, 56
value
    Isredis_obj_struct, 57
value_length
    Isredis_obj_struct, 57
wIndex
    tagEthernetCmd, 68
wLength
    tagEthernetCmd, 68
wValue
    tagEthernetCmd, 68
wait_for_me
    Isredis_obj_struct, 57
win
    Ispmac_motor_struct, 54
wrac
    Isredis.c, 226
wrfd
    Isredis.c, 226
write fmt
    Ispmac_motor_struct, 54
Х
    mk_pgpmac_redis, 14
xlate
    mk_pgpmac_redis, 14
У
    mk_pgpmac_redis, 14
zoom
    lspg_getcenter_struct, 23
    Ispmac.c, 206
    pgpmac.h, 335
zoom_act_pos
    md2StatusStruct, 67
zoom isnull
    lspg_getcenter_struct, 23
zoom_settings
    mk_pgpmac_redis, 14
zoom_status_1
    md2StatusStruct, 67
zoom_status_2
    md2StatusStruct, 67
```