APOLLO V2 · BUTTON · CELL RENDER

variant = Default · state = Default · size = sm

Resolved from `Button.component.json` against `tokens.json`, light mode. Surfaces the size=sm typography surprise (text-base, not text-sm), the 14 px `iconSize` hardcode, and the WCAG touch-target shortfall flagged in `a11y.touchTargetCompliance.nonCompliant`.

VISUAL

resting · clipsContent = true

Button

state = default · 1:1

RESOLVED CSS

```
/* Apollo v2 Button — variant=Default, state=Default, size=sm */
.btn[data-variant="default"][data-size="sm"] {
  display:         inline-flex;
  align-items:     center;
  justify-content: center;
  gap:             4px;     /* {spacing.1} */
  height:          40px;    /* {height.h-10} */
  padding:         8px 24px; /* {spacing.2} {spacing.6} */

  border:          none;
  border-radius:   9999px;  /* {border-radius.rounded-full} */
  overflow:        hidden;  /* clipsContent=true on Default variant
(SP-7) */

  background:      #5a35c0; /* {color.base.primary} */
  color:           #ffffff; /* {color.base.primary-foreground} */

  font-family:    "Open Sans", sans-serif;
  font-weight:    600;
  font-size:      16px;    /* text-BASE/24, not text-sm — GAP-1
surprise */
  line-height:    24px;
  letter-spacing: 0;

  opacity:        1;       /* {opacity.opacity-100} */
  cursor:         pointer;
  /* focus-ring: n/a — state ≠ Focus */
}
.btn > .icon { width: 14px; height: 14px; } /* hardcoded — no w-3-5
token in Apollo v2 */
```

PROPERTY	TOKEN REFERENCE	RESOLVED VALUE
fill	{color.base.primary}	#5a35c0
text-color	{color.base.primary-foreground}	#ffffff
border	bindings.border.Default.$all	none
radius	{border-radius.rounded-full}	9999px pill · universal
height	{height.h-10}	40px
padding-x	{spacing.6}	24px
padding-y	{spacing.2}	8px
gap	{spacing.1}	4px
typography	{typography.text-base-leading-normal-semibold}	Open Sans 600 · 16/24 surprise · GAP-1
iconSize	— (raw value)	14px hardcoded · no w-3-5 token
opacity	{opacity.opacity-100}	1
focus-ring	—	n/a (state ≠ Focus)
clipsContent	Default variant	true overflow: hidden
touch target	a11y.minTouchTarget = 44 × 44	40 × 40 WCAG 2.5.5 ✗

AUDIT SIGNALS 4

GAP-1	size=sm typography is text-base (16/24), not text-sm (14/20). Closed 2026-05-15 via cell `37:1616`. Apollo v2 maps the `sm` size to the larger body type than the size token suggests — name says small, type says base. Logged inline in `bindings.size.sm.$typographyNote`. Render reflects the resolved mapping verbatim.
GAP-7 / SP-4	`iconSize: 14px` is hardcoded. Apollo v2 has no width/w-* token at 14 px (the scale jumps `w-3` =12 → `w-4` =16). Two source-DS resolutions: (a) add a `w-3-5` token, or (b) rebind to the closest existing token. Tracked as audit-findings-for-source.md · Finding 4. Bundle preserves the raw value as-extracted.
a11y	Touch target below WCAG 2.5.5. 40 × 40 px ships under the 44 × 44 floor. `a11y.touchTargetCompliance.nonCompliant` lists `sm` alongside `xs`, `icon-xs`, `icon-sm`, and all `Link-*` sizes. Use `size=default` or larger on primary touch surfaces. Bundle surfaces the audit signal; the renderer does not paper over it.
SP-7	Default variant has `clipsContent: true`. Per `layout.clipsContent`, only the Default variant clips overflow on its container — other variants don't. Captured as `overflow: hidden` in the resolved CSS. Confirm this still matches per-cell expectations when the full 264-cell extract lands.

Notes. exposedProps defaults leave showLeftIcon / showRightIcon / showKbdGroup off and buttonText = "Button". State=Default omits the focus ring and uses the base primary fill, not primary-hover / primary-active. Pill radius (9999 px) holds across every cell of the matrix per skill rule 4.