APOLLO V2 · BUTTON · CELL RENDER

variant = Default · state = Default · size = icon-lg

Resolved from `Button.component.json` against `tokens.json`, light mode.
Icon-only cell — single fixed slot, no label, all slot booleans disabled.
Surfaces the `icon-lg` width-via-height-token anomaly and the non-uniform `iconSize` across the icon-* sizes (24 px here vs 16 px at `size=icon`).

VISUAL

resting · clipsContent = true

48 × 48 · touch-target ✓

state = default · 1:1

RESOLVED CSS

```
/* Apollo v2 Button — variant=Default, state=Default, size=icon-lg */
.btn[data-variant="default"][data-size="icon-lg"] {
  display:         inline-flex;
  align-items:     center;
  justify-content: center;
  gap:             0;        /* gap=null — single slot */

  height:          48px;     /* {height.h-12} */
  width:           48px;     /* bound to {height.h-12} — NOT a w-*
token (anomaly) */
  padding:         0;        /* padding-x=0, padding-y=0 */

  border:          none;
  border-radius:   9999px;   /* {border-radius.rounded-full} */
  overflow:        hidden;   /* clipsContent=true on Default variant
(SP-7) */

  background:      #5a35c0;  /* {color.base.primary} */
  color:           #ffffff;  /* {color.base.primary-foreground} — icon
stroke */

  opacity:         1;        /* {opacity.opacity-100} */
  cursor:          pointer;
  /* typography: null — icon-only, no label */
  /* focus-ring: n/a — state ≠ Focus */
}
.btn > .icon { width: 24px; height: 24px; } /* {width.w-6} ·
$bindingStatus: partial */
```

PROPERTY	TOKEN REFERENCE	RESOLVED VALUE
fill	{color.base.primary}	#5a35c0
text/icon-color	{color.base.primary-foreground}	#ffffff
border	bindings.border.Default.$all	none
radius	{border-radius.rounded-full}	9999px pill · universal
height	{height.h-12}	48px
width	{height.h-12}	48px bound-via-height-token
padding-x / padding-y	— (zero)	0 / 0
gap	null	— single slot
typography	null	— no label
iconSize	{width.w-6}	24px $bindingStatus: partial
opacity	{opacity.opacity-100}	1
focus-ring	—	n/a (state ≠ Focus)
clipsContent	Default variant	true overflow: hidden
touch target	a11y.minTouchTarget = 44 × 44	48 × 48 WCAG 2.5.5 ✓

ICON-* SIZE SCALING — NOTE THE ICONSIZE JUMP

icon-xs	icon-sm	icon	icon-lg ← this cell
36 × 36	40 × 40	44 × 44	48 × 48
icon: 12 px	icon: 16 px	icon: 16 px — same as icon-sm	icon: 24 px — +50 %

AUDIT SIGNALS 4

SP-4	`width` bound to `{height.h-12}`, not a width token. Other icon-* sizes hardcode `width` as raw pixels; `icon-lg` alone references a *height* token for its width. Semantically inconsistent — should bind to `{width.w-11}`'s 48 px sibling (not present in current `tokens.json`, would need a `w-12` addition). Logged in `bindings.size.icon-lg.$widthNote`.
SP-4	`iconSize` partially bound. `$iconSizeBindingStatus: "partial"`. Cell emits raw `24px`; matching tokens exist (`{width.w-6}` or `{height.h-6}`) but neither is referenced at the node level. GAP-7 candidate.
surprise	iconSize scaling across icon-* is non-uniform. `icon-xs` =12, `icon-sm` =16, `icon` =16, `icon-lg` =24. Going from `icon` to `icon-lg` jumps the icon +50 %, while the container grows only +9 %. `icon` and `icon-sm` share an icon size despite different containers. Logged in `$step2_known_gaps.GAP-1` closure note.
SP-7	Default variant has `clipsContent: true`. Captured as `overflow: hidden` on the container. Only the Default variant clips — for icon-only cells the overflow rarely matters visually, but keeping it preserves round-trip fidelity with the source DS.

Notes. variantConstraints for size ∈ {icon, icon-xs, icon-sm, icon-lg} disable buttonText / showLeftIcon / showRightIcon / showKbdGroup — the slot is single, fixed, and not user-swappable through props. Lucide CircleArrowLeft stands in as a representative payload; renderer applies stroke via currentColor.