APOLLO V2 · BUTTON · CELL RENDER

variant = Outline · state = Loading · size = default

Resolved from `Button.component.json` against `tokens.json`, light mode. State=Loading triggers the SP-5 slot swap (`leftIcon` → fixed Spinner) and the SP-3 double-prevention contract (`aria-busy="true"` + non-interactive). `showLeftIcon` is suppressed from the prop interface in this state.

VISUAL

attr: aria-busy="true" · disabled

state = loading · aria-busy · 1:1

RESOLVED CSS

```
/* Apollo v2 Button — variant=Outline, state=Loading, size=default */
.btn[data-variant="outline"][data-size="default"][aria-busy="true"] {
  display:         inline-flex;
  align-items:     center;
  justify-content: center;
  gap:             6px;        /* {spacing.1-5} */
  height:          44px;       /* {height.h-11} */
  padding:         8px 32px;   /* {spacing.2} {spacing.8} — asymmetric
(SP-7) */

  border:          1px solid #5a35c0;
                         /* {border-width.border} · solid ·
{color.base.primary} (Outline.Loading) */
  border-radius:   9999px;     /* {border-radius.rounded-full} */

  background:      #fafafa;    /* {color.custom.background-dark-input-
30} */
  color:           #4a2ba3;    /* {color.base.primary-hover}
(Outline.Loading text-color) */

  font-family:    "Open Sans", sans-serif;
  font-weight:    600;
  font-size:      18px;       /* text.lg.font-size */
  line-height:    28px;       /* text.lg.line-height */

  opacity:        1;          /* {opacity.opacity-100} */
  cursor:         progress;
  pointer-events: none;       /* double-prevention contract (a11y) */
  /* focus-ring: n/a — state ≠ Focus */
}
.btn > .spinner {
  width:  16px; height: 16px;  /* {height.h-4} */
  animation: spin 1s linear infinite;   /* Lucide LoaderCircle — fixed
via SP-5 */
}
```

SLOT SWAP — SP-5 SWAPDEFAULTS['STATE=LOADING']

LEFTICON · DEFAULT

~~Lucide / CircleArrowLeft~~

exposedBy: showLeftIcon · swappable by user

REPLACED →
state=Loading

LEFTICON · LOADING SWAP

Spinner (Lucide / LoaderCircle, animation: spin)

exposedBy: null — fixed instance, prop is suppressed

PROPERTY	TOKEN REFERENCE	RESOLVED VALUE
fill	{color.custom.background-dark-input-30}	#fafafa
border.width	{border-width.border}	1px
border.color (Loading)	{color.base.primary}	#5a35c0
text-color (Loading)	{color.base.primary-hover}	#4a2ba3 GAP-2 patched
radius	{border-radius.rounded-full}	9999px pill · universal
height	{height.h-11}	44px
padding-x	{spacing.8}	32px
padding-y	{spacing.2}	8px asymmetric · SP-7
gap	{spacing.1-5}	6px
typography	{typography.text-lg-leading-normal-semibold}	Open Sans 600 · 18/28
iconSize	{height.h-4}	16px spinner sized to icon slot
leftIcon slot	SP-5 swapDefaults['state=Loading']	Lucide / LoaderCircle · spin fixed · exposedBy: null
opacity	{opacity.opacity-100}	1
focus-ring	—	n/a (state ≠ Focus)
clipsContent	— (variant ≠ Default)	false
a11y contract	loadingDoublePreventionContract	aria-busy="true" + non-interactive enforced
touch target	a11y.minTouchTarget	44 × 44 WCAG 2.5.5 ✓

AUDIT SIGNALS 5

SP-5	leftIcon slot is replaced by a fixed Spinner instance in Loading. `swapDefaults['state=Loading']` swaps in `Lucide LoaderCircle` with `animation: spin`. `exposedBy: null` — the `showLeftIcon` prop is suppressed from the interface; the spinner is always rendered. Render reflects this verbatim.
GAP-2	Loading fills/text patched in v0.2.0. Outline `fill.Loading` stays at the default `{color.custom.background-dark-input-30}`; `text-color.Loading` = `{color.base.primary-hover}`. Border holds at `{color.base.primary}` per the GAP-5 per-state border map. Hover/Pressed for Outline still `$tbdStep3` (not this cell).
a11y	Double-prevention contract enforced. HTML `disabled` + `aria-busy="true"` + `pointer-events: none`. Per `a11y.loadingDoublePreventionContract`, the consumer MUST disable click + set `aria-busy`. Added `aria-live="polite"` so the busy state is announced.
SP-7	Asymmetric padding preserved. `padding: 8px 32px` (not `padding: 32px`). The bundle captures padding per side rather than via Tailwind `p-` shorthand. The smoke-test self-correction on cell `37:930` proved this capture is load-bearing.
motion	`prefers-reduced-motion` respected. The spinner slows to a 4 s rotation rather than stopping outright — the spec doesn't define a reduced-motion variant for Lucide LoaderCircle, so the renderer keeps a slow signal of activity rather than freezing. Not a bundle rule; a renderer-side choice.

Notes. exposedProps in this state: buttonText = "Button"; showLeftIcon suppressed; showRightIcon / showKbdGroup retain their false defaults. Pill radius (9999 px) holds across every cell of the matrix per skill rule 4.