

VFPxWorkbookXlsx Documentation

Class for Reading/Writing XLSX Format Files

Overview

VFPxWorkbookXlsx class was written to remove the need to automate an installed version of Microsoft Excel 2010 or higher in order to be able to create XLSX format spreadsheets with cell formatting and formulas. Several methods are provided to write a table or grid to a workbook sheet.

Additionally, VFPxWorkbookXlsx class has the ability to read an existing XLSX file and load the workbook into the internal working cursors (all cursors are preceded with 'xl_'); methods are provided to return the cell values and formatting. The field types are determined from the cell formatting. These cursors can then be queried to be able to extract the worksheet cell information. All cursors are now contained in a private DataSession of the VFPxWorkbookXlsx class.

Support for Visual FoxPro versions 8.0 and 9.0 are provided; earlier versions are not supported due the inclusion of TRY-CATCH commands (if these code locations are refactored then the class should support earlier versions of VFP; note that the use of TRY-CATCH is also a design solution in some cases to catch XML errors due to non-existing nodes or for the datasession determination). The class is implemented as a Label baseclass so that when added to a container such as a form, the class name is provided in the Caption property for visual identification in the Design-time editor of VFP (Visible property is set to False).

VFPxWorkbookXlsx class has the following features:

- Assign values to cells
 - Numeric
 - Boolean
 - Date
 - Date-time
 - Character
- Cell numeric formatting
 - Number
 - Decimal places
 - Currency
 - Date layout
 - Date-time layout
 - Support for custom defined numeric formatting
- Apply formatting to the cells
 - Borders (top, left side, right side, and bottom)
 - Borders (left-to-right slant and right-to-left slant)
 - Border thickness, type (i.e., single, double, etc.)
 - Border color
 - Background color
 - Font name, size, and style
 - Word-wrapping
 - Text/numeric alignment
- Formula assignment to cells

- Merging and unmerging of cells
- Row height and column width
- Multiple sheets
 - Assign/rename sheet names
- Sheet Print setup
 - Orientation
 - Page scaling or sheets to a page count (horizontal and vertical)
 - Paper size (standard and custom)
- Sheet headers and footers for printing
 - First page, odd/even pages
 - Left section, center section and right section texts
 - Font support
- Workbook properties
 - Author/Creator
 - Company Name
- Read existing XLSX workbooks
 - Load into working cursors
 - Set cell datatypes based on cell format
- Write tables or grids directly to XLSX workbooks via a single method
 - Support for multiple sheets
 - Column width of sheets set by column width of grid

Defined Numeric Formatting

Most of the standard numeric formatting is supported by this class; the following #DEFINEs are provided for the supported format codes.

#DEFINE Name	Format Code
CELL_FORMAT_INTEGER	0
CELL_FORMAT_FLOAT	0.00
CELL_FORMAT_COMMA_INTEGER	#,##0
CELL_FORMAT_COMMA_FLOAT	#,##0.00
CELL_FORMAT_CURRENCY_PAREN	\$#,##0.00;(\$#,##0.00)
CELL_FORMAT_CURRENCY_RED_PAREN	\$#,##0.00;[Red](\$#,##0.00)
CELL_FORMAT_PERCENT_INTEGER	###%
CELL_FORMAT_PERCENT_FLOAT	###.00%
CELL_FORMAT_EXPONENT	0.00E+00
CELL_FORMAT_FRACTION_1	# ?/?
CELL_FORMAT_FRACTION_2	# ??/??
CELL_FORMAT_DATE_MMDDYY	mm-dd-yy
CELL_FORMAT_DATE_DMMMYY	d-mmm-yy
CELL_FORMAT_DATE_DMMM	d-mmm
CELL_FORMAT_DATE_MMMYY	mmm-yy
CELL_FORMAT_TIME_HMMAMPM	h:mm AM/PM
CELL_FORMAT_TIME_HMMSSAMPM	h:mm:ss AM/PM
CELL_FORMAT_TIME_HMM	h:mm
CELL_FORMAT_TIME_HMMSS	h:mm:ss
CELL_FORMAT_DATETIME_MDYYHMM	m/d/yy h:mm
CELL_FORMAT_DATETIME_DMMMYYYY_TTAM	[\$-409]dd/mmm/yyyy\ h:mm\ AM/PM;@
CELL_FORMAT_DATETIME_DMMMYYYY_TT24	dd/mmm/yyyy\ h:mm;@
CELL_FORMAT_DATETIME_MMMDDYYYY_TTAM	[\$-409]mmm\ d\,\ yyyy\ h:mm\ AM/PM;@
CELL_FORMAT_DATETIME_MMMDDYYYY_TT24	[\$-409]mmm\ d\,\ yyyy\ h:mm;@
CELL_FORMAT_DATETIME_MDYY_TTAM	m/d/yy\ h:mm\ AM/PM;@
CELL_FORMAT_DATETIME_MDYY_TT24	m/d/yy\ h:mm;@
CELL_FORMAT_COMMA_INTEGER_PAREN	#,##0;(#,##0)
CELL_FORMAT_COMMA_INTEGER_RED_PAREN	#,##0;[Red](#,##0)
CELL_FORMAT_COMMA_FLOAT_PAREN	#,##0.00;(#,##0.00)
CELL_FORMAT_COMMA_FLOAT_RED_PAREN	#,##0.00;[Red](#,##0.00)

#DEFINE Name	Format Code
CELL_FORMAT_TIME_MMSS	mm:ss
CELL_FORMAT_TIME_H_MMSS	[h]:mm:ss
CELL_FORMAT_CURRENCY_RED	\$#,##0.00;[Red]\$#,##0.00

Custom Defined Numeric Formatting

Additional custom numeric formatting can be defined as needed using the method:

[this](#). AddNumericFormat(tcFormatCode)

This method will break-down the format into its components in order to support the number of decimals being set for a cell. This allows for the numeric format to be independent of the number of decimals; otherwise, a different numeric format would have to be defined just for a different number of decimals to be shown. However, this method requires the developer to supply the fully defined format based on all rules for numeric formats.

A newer method is provided that breaks down the format into the various parts and then will construct the numeric format which is hopefully easier to use for creating custom numeric formats. The parameters are:

[this](#). AddCustomNumericFormat(tcPosSect, tcNegSect, tcZeroSect, tcTextSect, tlApplyDec)

Up to four sections of format codes can be specified. The format codes, separated by semi-colons, define the formats for positive numbers (tcPosSect), negative numbers (tcNegSect), zero values (tcZeroSect), and text (tcTextSect), in that order. If only two sections are specified, the first is used for positive numbers and zeros, and the second is used for negative numbers. If only one section is specified, it is used for all numbers. If a semi-colon is part of the section code it will result in the method considering it an error and will not include the format.

A representation of the numeric format is as follows:

```

      |Format for positive numbers      |Format for zeros
      |_____|                          |_____|
    #,###.00_);[Red](#,###.00);0.00;"sales"@
      |_____|                          |_____|
    Format for negative numbers          Format for text
  
```

The first section, "tcPosSect - Format for positive numbers", is the format code that applies to the cell when the cell value contains a positive number.

The second section, "tcNegSect - Format for negative numbers", is the format code that applies to the cell when the cell value contains a negative number.

The third section, "tcZeroSect - Format for zeros", is the format code that applies to the cell when the cell value is zero.

The fourth, and last, section, "tcTextSect - Format for text", is the format code that applies to the cell when the cell value is text.

The & (ampersand) text operator is used to join, or concatenate, two values.

The following table describes the different symbols that are available for use in custom number formats.

Format Symbol	Description and Result
0	Digit placeholder. [Example: If the value 8.9 is to be displayed as 8.90, use the format #.00]
#	Digit placeholder. This symbol follows the same rules as the 0 symbol. However, the application shall not display extra zeros when the number typed has fewer digits on either side of the decimal than there are # symbols in the format. [Example: If the custom format is ###, and 8.9 is in the cell, the number 8.9 is displayed]
?	Digit placeholder. This symbol follows the same rules as the 0 symbol. However, the application shall put a space for insignificant zeros on either side of the decimal point so that decimal points are aligned in the column. [Example: The custom format 0.0? aligns the decimal points for the numbers 8.9 and 88.99 in a column]
. (period)	Decimal point.
%	Percentage. If the cell contains a number between 0 and 1, and the custom format 0% is used, the application shall multiply the number by 100 and add the percentage symbol in the cell.
, (comma)	Thousands separator. The application shall separate thousands by commas if the format contains a comma that is enclosed by number signs (#) or by zeros. A comma that follows a placeholder scales the number by one thousand. [Example: If the format is #.0,, and the cell value is 12,200,000 then the number 12.2 is displayed]
E- E+ e- e+	Scientific format. The application shall display a number to the right of the "E" symbol that corresponds to the number of places that the decimal point was moved. [Example: If the format is 0.00E+00, and the value 12,200,000 is in the cell, the number 1.22E+07 is displayed. If the number format is #0.0E+0, then the number 12.2E+6 is displayed.]
\$-+():space	Displays the symbol. If it is desired to display a character that differs from one of these symbols, precede the character with a backslash (\). Alternatively, enclose the character in quotation marks. [Example: If the number format is (000), and the value 12 is in the cell, the number (012) is displayed]

Format Symbol	Description and Result
/	If this symbol is preceded and followed by a number symbol (0, #, and ?), it is interpreted as the fraction format symbol and will display the number in the format of a fraction. Otherwise, it is interpreted as the forward slash character and is displayed as such.
\	Displays the next character in the format. The application shall not display the backslash. [Example: If the number format is 0\! , and the value 3 is in the cell, the value 3! is displayed]
*	Repeats the next character in the format enough times to fill the column to its current width. There shall not be more than one asterisk in one section of the format. If more than one asterisk appears in one section of the format, all but the last asterisk shall be ignored. [Example: if the number format is 0*x, and the value 3 is in the cell, the value 3xxxxxx is displayed. The number of x characters that are displayed in the cell varies based on the width of the column]
_ (underline)	Skips the width of the next character. This is useful for lining up negative and positive values in different cells of the same column. [Example: The number format _(0.0_);(0.0) aligns the numbers 2.3 and -4.5 in the column even though the negative number is enclosed by parentheses]
"text"	Displays whatever text is inside the quotation marks. [Example: The format 0.00 "dollars" displays 1.23 dollars when the value 1.23 is in the cell]
@	Text placeholder. If text is typed in the cell, the text from the cell is placed in the format where the at symbol (@) appears. [Example: If the number format is "Bob "@ Smith" (including quotation marks), and the value "John" is in the cell, the value Bob John Smith is displayed]

Cell Styles (new with Release 18)

Formatting for a cell that includes font, indentation, borders, fill, etc. in a XLSX file is defined in a style definition internally. This internal style definition is then assigned to individual cells. If one cell is formatted bold and a second cell is formatted non-bold, then there would be two different styles defined. Additionally, there would be two different font definitions defined. Each time a new font definition, border definition, fill definition, etc., is added, a new style has to be defined. Then this style is used to define the formatting for a given cell.

The previous methods for assigning cell formatting took care of when to create a new style definition or when to add to an existing style definition. But this choice of design causes a lot of overhead in the cell formatting assignment process. In order to reduce this overhead, I have added new methods for managing the cell formatting process using the style as the base. This is a similar approach to cell formatting that is used in the Apache Foundation POI Java Classes. The older cell formatting methods will remain in the class but will not be enhanced anymore and should be considered as *depreicated code*.

The first of the style methods is the `CreateCellStyle()` method. This method creates a base style entry that can be enhanced with the different formatting choices: font, fill, border, etc. A series of methods that begin with `AddStyle...` are used to assign the different formatting requirements to a style definition. Once a style is defined, it can then be assigned to an individual cell via the `SetCellStyle()` method or to a series of cells via the `SetCellStyleRange()` method. Changes to a style definition will automatically be reflected in all cells that reference the style definition.

An example of using style based formatting is as follows (see `Demo()` method):

```
InStyle1 = this.CreateFormatStyle(InWB)           && Create the base style definition
this.AddStyleBorders(InWB, InStyle1, 63, BORDER_STYLE_THIN, RGB(16,100,200))
this.AddStyleFont(InWB, InStyle1, "Times New Roman", 14, False, False, RGB(0,0,255))
this.SetCellStyleRange(InWB, InSh1, 2, 1, 2, 9, InStyle1) && Assign formatting style to cells
```

SpreadSheet Headers/Footers

This class supports writing headers and footers for individual spreadsheets which includes different first page, different odd/even pages, and same all pages. The placement of the text can be left section, center section, and/or right section. Font support is also provided. The following method must be first called to set the header/footer properties before assigning any text:

```
this.SetHeaderFooterSetup(tnWB, tnSheet, tIAlignMargin, tIDiffFirstPg,
                          tIDiffOddEven, tIScaleWDoc)
```

After setting the header/footer properties, the following method is called to set the text (see the method below for more details):

```
this.SetHeaderFooterText(tnWB, tnSheet, tnPage, tnSection, tcText, tcFontName,
                        tnFontSize, tnFontEffect, tnFontColor)
```

The default font handling is for the entire section text; there is not direct support for different formatting within a section text. However, this can be encoded within the section text by the developer. Special symbol inclusion (such as page number, number of pages, etc.) in the text is

also not directly supported; but, these can be added by the developer into the header text as well. An example of placing the text into a header or footer as:

Page # of ## *Where # is the current page number; ## is total page count*

Can be done with the following text assigned to a header/footer section:

"Page &P of &N"

Where &P is the code for current page, and &N is the code for page count.

Additional embedded formatting commands are available. These are:

Embedded Code	Explanation / Meaning
&P	Code for "current page #"
&N	Code for "total pages"
&font size	Code for "text font size", where font size is a font size in points.
&K	Code for "text font color" RGB Color is specified as RRGGBB which is appended to end of code; example red is: &KFF0000
&S	Code for "text strikethrough" on / off
&X	Code for "text super script" on / off
&Y	Code for "text subscript" on / off
&D	Code for "date"
&T	Code for "time"
&U	Code for "text single underline"
&E	Code for "double underline"
&Z	Code for "this workbook's file path"
&F	Code for "this workbook's file name"
&A	Code for "sheet tab name"
&+	Code for add to page #.
&-	Code for subtract from page #.
&"font name, style"	Code for "text font name" and "text font style", where font name and font style are strings specifying the name and style of the font, separated by a comma. When a hyphen appears in font name, it means "none specified".

Embedded Code	Explanation / Meaning
& b	Code for "bold font style"
& B	Also means "bold font style".
& r	Code for "regular font style"
& i	Code for "italic font style"
& I	Also means "italic font style"
& b i	Code for "bold italic font style"

Font formatting will apply to all text following the embedded command until a new embedded font formatting command is encountered.

Properties

CodePage

Description	CodePage to use for the Strings cursor
Default Value	VFP default value

CompanyName

Description	Company name in workbook properties
Default Value	VFPxWorkbookXLSX

CreatorName

Description	Creator in workbook properties
Default Value	VFPxWorkbookXLSX

DeclareWinAPI

Description	Boolean to declare the needed Win32 API functions called in Init()
Default Value	False

Debug

Description	Sets debugging mode
Default Value	False

DefaultSheetName

Description	Default sheet name
Default Value	Sheet

ErrorLevelId (new with Release 18)

Description	Error level Id that has occurred (see OnErrorMessage() event for id values assigned)
Default Value	0 [no errors]

ExcelXlsxRelease

Description	Release version of class
-------------	--------------------------

Default Value	Sheet
---------------	-------

SaveCurrencyAsNumeric (new with Release 18)

Description	Indicates whether to save a currency value as a currency value or as a numeric value [Boolean]
-------------	--

Default Value	False
---------------	-------

Subject

Description	Subject in workbook properties
-------------	--------------------------------

Default Value	<none>
---------------	--------

TrueFalseValue

Description	The value to display in the cell for a boolean field type; pipe delimited list of the true value followed by the false value
-------------	--

Default Value	Yes No
---------------	--------

Title

Description	Title in workbook properties
-------------	------------------------------

Default Value	<none>
---------------	--------

UserName

Description	Name of person stored in XLSX document as last edit
-------------	---

Default Value	VFPxWorkbookXLSX
---------------	------------------

Events

OnDestroy

Description: Called by Destroy Event; for placing user code

Parameters:
None

OnInit

Description: Called by Init Event; for placing user code

Parameters:
None

OnShowErrorMessage (new with Release 18)

Description: Called for displaying a user message when an error occurs. Use BINDEVENTS to bind to this event.

Parameters:
tnErrorId

Error Id.

The following errors occur during opening of a workbook

- 1 OpenXlsxWorkbook() - must include file name to open
- 2 OpenXlsxWorkbook() - error assigned by TRY-CATCH
- 3 OpenXlsxWorkbook() - missing workbook.xml
- 4 OpenXlsxWorkbook() - missing workbook.xml.rels
- 5 OpenXlsxWorkbook() - missing styles.xml
- 6 OpenXlsxWorkbook() - missing sharedStrings.xml
- 7 OpenXlsxWorkbook() - error during shared string loading
- 8 OpenXlsxWorkbook() - missing sheet or invalid sheet <id>
- 9 OpenXlsxWorkbook() - error reading data; error assigned by TRY-CATCH

The following errors occur during saving of a workbook

- 10 CreateExcelFile - unable to delete existing file; error assigned by TRY-CATCH
- 11 CreateExcelFile - Failed to create Zip file
- 12 CreateExcelFile - Failed to add contents to Zip file
- 13 CreateExcelFile - Rename failed (changing from zip to xlsx extension)
- 14 WriteSheetXMLs - Failed to create a sheet; error assigned by TRY-CATCH
- 15 WriteStringsXML – Failed to create sharedstrings.xml; error assigned by TRY-CATCH
- 16 WriteRelationshipsXML – Unable to create workbook.xml.rels; error assigned by TRY-CATCH

- 17 WriteStylesXML - Unable to create styles.xml; error assigned by TRY-CATCH
- 18 WriteSupportXMLs - Unable to create workbook supporting XMLs; error assigned by TRY-CATCH

The following are general errors

- 99 Occurs when failure to open the workbook via ShellExecute API command

tcErrMsg Error message text

OnShowStatusMessage (new with Release 18)

Description: Called for displaying a user message during the opening of an existing workbook (xlsx) file. Use BINDEVENTS to bind to this event.

Parameters:

tnMode	Mode of the current processing; 1 indicates opening an xlsx file and 2 indicates saving an xlsx file
tnStage	Stage of the process
tnTotStages	Total number of stages to process (passed only on the first call)

Comments: The following is a listing of the values

When nMode = 1
nStage = 0; start of open
nStage = 1; reading shared strings XML
nStage = 2; reading styles XML
nStage = 3; reading relationships XML
nStage = 4; reading sheets XML
nStage = 5; reading named ranges
nStage = 6; reading external references
nStage = -1; end of open

When nMode = 2
nStage = 0; start of save
nStage = 1; indicates saving supporting XMLs
nStage = 2; indicates saving strings XML
nStage = 3; indicates saving styles XML
nStage = 4; indicates saving workbook
nStage = 5; indicates saving relationship XML
nStage = 6+; indicates saving sheets
nStage = -1; end of close

Methods – Managing Workbooks

CreateWorkbook

Description: Creates a new workbook

Parameters:

tcName Full path and file name of Excel Xlsx Workbook to create

Return Value:

Id of Sheet

0 if failure

DeleteAllWorkbooks

Description: Deletes all workbook Ids

Parameters:

None

Return Value:

None

DeleteWorkbook

Description: Deletes the workbook Id

Parameters:

tnWB Id to workbook

Return Value:

True on success

False on failure

GetNumberOfSheets (new with Release 18)

Description: Returns the number of defined sheets for the given workbook id.

Parameters:

tnWB Id to workbook

Return Value:

Number of sheets

GetWorkbook

Description: Gets the workbook Id

Parameters:

tcName file name of Excel Xlsx Workbook to return

Return Value:

Id of workbook

Zero if failure

GetWorkbookFileName (new with Release 16)

Description: Gets the workbook file name

Parameters:

tnWB workbook number returned by CreateWorkbook()

Return Value:

File name of the workbook

Empty string if failure

OpenCreatedXlsxFile (new with Release 16)

Description: Opens the selected workbook in the default program via ShellExecute Win API

Parameters:

txWB	Integer: workbook number returned by CreateWorkbook() String: workbook file name (full path)
------	---

Return Value:

False	Failed to open or find workbook
True	Default

OpenXlsxWorkbook

Description: Opens the passed XLSX workbook and loads the internal cursors with the content

Parameters:

tcFileName	File name with full path of the XLSX file to open
tlForceTextFormat	If True, then cell values are forced to Text format [optional]

Return Value:

Id of workbook
Zero if failure

SaveWorkbook

Description: Saves the selected workbook to xlsx file format based on the name set at creation of the workbook

Parameters:

tnWB	Id to workbook
------	----------------

Return Value:

True on success
False on failure

SaveWorkbookAs

Description: Saves the selected workbook to xlsx file format with the supplied file name; resets the workbook file name for future saves

Parameters:

tnWB	Id to workbook
tcWBName	File path and file name to save-as

Return Value:

True on success
False on failure

Methods – Managing Sheets

AddSheet (parameter change with Release 16)

Description: Adds a new sheet to the workbook

Parameters:

tnWB	Id to workbook to add sheet to
tcSheetName	Name of the sheet to be added; limited to 30 characters
tnState	Visibility of sheet [optional parameter, defaults to Visible]; select value from #DEFINES VISIBLE_SHEET_STATE HIDDEN_SHEET_STATE VERYHIDDEN_SHEET_STATE

Return Value:

Id of Sheet
0 if failure

DeleteSheet

Description: Deletes the workbook sheet

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook

Return Value:

True on success
False on failure

GetColumnWidth

Description: Returns the width of the selected column

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnColumn	Column index to reset width

Return Value:

Width of column; -1 is returned if a column width is not explicitly set
NULL on failure or sheet does not exist

GetLastColumnInRow

Description: Returns the max column number for a given row in a sheet

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnRow	Row number

Return Value:

Integer value of maximum column number in row; zero if none.

GetLastRowNumber

Description: Returns the last row number in the sheet

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

Integer value of last row number; zero if none.

GetMaxColumnNumber

Description: Returns the max column number for a sheet

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

Integer value of maximum column number in sheet across all rows; zero if none.

GetRowMaxColumn (new with Release 18)

Description: Returns the max column number for a given row in a given sheet

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Row number to return

Return Value:

Integer value of maximum column number in row; zero if none.

GetSheetName (new with Release 16)

Description: Returns the sheet name

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

Name of sheet or empty string if not found

GetWorkbookSheets

Description: Gets the sheet information for a workbook

Parameters:

tnWB	Id to workbook
------	----------------

Return Value:

Sheet list object:

loSheets.Count	Count of sheets
loSheets.List[n, 1]	Sheet Id
loSheets.List[n, 2]	Sheet Name

RenameSheet

Description: Renames the selected sheet in the workbook

Parameters:

tnWB	Id to workbook
txSheet	Sheet to remove; can be either the sheet Id or the sheet name
tcSheetName	New name for the sheet; limited to 30 characters

Return Value:

True on success
False on failure

SetSheetVisibility (new with Release 16)

Description: Set the selected sheet visibility in the workbook

Parameters:

tnWB	Id to workbook
txSheet	Sheet to remove; can be either the sheet Id or the sheet name
tnState	Visibility of sheet; select value from #DEFINEs SHEET_STATE_VISIBLE SHEET_STATE_HIDDEN SHEET_STATE_VERYHIDDEN

Return Value:

True on success
False on failure

Methods – Assigning Cell Values

ClearCellValue

Description: Clears the value from the selected cell

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Numeric cell value for row
tnCellCol	Numeric cell value for column

Return Value:

True on success
False on failure

SetCellFormula

Description: Sets the cell formula

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tcCellFormula	Formula to add; you must format the formula with cell references and preceeded with an equals sign; i.e., =SUM(A1:A10)

Return Value:

True on success
False on failure

SetCellValue

Description: Sets the cell value. The data type is set by the data type of the value to be set (determined via VARTYPE() function)

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
txCellValue	Value to set; supported data types include (#DEFINEs): DATA_TYPE_CHAR DATA_TYPE_DATE DATA_TYPE_DATETIME DATA_TYPE_CURRENCY DATA_TYPE_FLOAT DATA_TYPE_INT DATA_TYPE_GENERAL (this is set to an empty string)

Return Value:

True on success
False on failure

Methods – Returning Cell Values

GetCellDataType

Description: Returns the cell data type; this is based on the character expression or the cell format.

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Numeric cell value for row
tnCellCol	Numeric cell value for column

Return Value:

Data type for the cell; see SetCellValue() method for a list of data type #DEFINEs.

GetCellFormula

Description: Returns the cell formula expression

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Numeric cell value for row
tnCellCol	Numeric cell value for column

Return Value:

Formula expression for the cell

GetCellValue

Description: Returns the value from the selected cell

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Numeric cell value for row
tnCellCol	Numeric cell value for column

Return Value:

Cell value set to the data type of the cell

GetSheetRowValues

Description: Returns the cell values for the given row

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Numeric cell value for row

Return Value:

Return object:

loRow.Count	Number of columns returned in row
loRow.Values[nCol, 1]	Cell value set to data type of the cell
loRow.Values[nCol, 2]	Cell data type

A **NULL** value for a column indicates a value is not set. If a failure occurs (sheet or column does not exist, then a **NULL** is returned).

IsCellFormula

Description: Determines if the cell contains a formula

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row number
tnCellCol	Cell column number

Return Value:

True if the cell contains a formula; otherwise false.

Methods – Style Formatting

AddStyleBorders (new with Release 18)

Description: Adds to the style definition cell border formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tnBorders	Cell Border to draw; this is a addition of the appropriate border side to set; to set all sides: BORDER_LEFT + BORDER_RIGHT + BORDER_TOP + BORDER_BOTTOM + BORDER_DIAGDOWN + BORDER_DIAGUP
tcBorderStyle	Style of border to draw; the following styles are available: BORDER_STYLE_THIN BORDER_STYLE_HAIR BORDER_STYLE_DOTTED BORDER_STYLE_DASHDOTDOT BORDER_STYLE_DASHDOT BORDER_STYLE_DASHED BORDER_STYLE_THIN BORDER_STYLE_MEDIUMDASHDOTDOT BORDER_STYLE_SLANTDASHDOT BORDER_STYLE_MEDIUMDASHDOT BORDER_STYLE_MEDIUMDASHED BORDER_STYLE_MEDIUM BORDER_STYLE_THICK BORDER_STYLE_DOUBLE
tnBorderColor	The color to draw the border in RGB() value

Return Value:

True on success; false on failure to assign

AddStyleFill (new with Release 18)

Description: Adds to the style definition cell fill formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tnFColor	Fill foreground color; RGB(N,N,N)
tnBColor	Fill background color; RGB(N,N,N)
tcPatternType	Fill pattern type; based on #DEFINEs FILL_STYLE_NONE FILL_STYLE_SOLID FILL_STYLE_GRAY125

Return Value:

True on success; false on failure to assign

AddStyleFont (new with Release 18)

Description: Adds to the style definition cell font formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tcFName	Font name
tnFSize	Font size
tlBold	Boolean to indicate bold font
tlItalic	Boolean to indicate italic font
tnFColor	Font foreground color; RGB(N,N,N)
tcULine	Boolean to indicate underline
tlStrikThr	Boolean to indicate strikethrough
tcVPos	Verical position of text (from #DEFINEs) FONT_VERTICAL_BASELINE FONT_VERTICAL_SUBSCRIPT FONT_VERTICAL_SUPERSCRIPT

Return Value:

True on success; false on failure to assign

AddStyleHorizAlignment (new with Release 18)

Description: Adds to the style definition cell horizontal alignment formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tcHorizAlign	Assigned by the following #DEFINEs CELL_HORIZ_ALIGN_LEFT CELL_HORIZ_ALIGN_RIGHT CELL_HORIZ_ALIGN_CENTER

Return Value:

True on success; false on failure to assign

AddStyleIndent (new with Release 18)

Description: Adds to the style definition cell indent formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tnIndent	The amount of indent to apply

Return Value:

True on success; false on failure to assign

AddStyleNumericFormat (new with Release 18)

Description: Adds to the style definition cell numeric formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tnNumFmtId	Value of numeric format (from #DEFINEs) CELL_FORMAT_INTEGER CELL_FORMAT_FLOAT CELL_FORMAT_COMMA_INTEGER CELL_FORMAT_COMMA_FLOAT CELL_FORMAT_CURRENCY_PAREN CELL_FORMAT_CURRENCY_RED_PAREN CELL_FORMAT_CURR_EURO_RED CELL_FORMAT_CURR_POUNDS_RED CELL_FORMAT_PERCENT_INTEGER

CELL_FORMAT_PERCENT_FLOAT
CELL_FORMAT_EXPONENT
CELL_FORMAT_FRACTION_1
CELL_FORMAT_FRACTION_2
CELL_FORMAT_DATE_MMDDYY
CELL_FORMAT_DATE_DMMYY
CELL_FORMAT_DATE_DMMM
CELL_FORMAT_DATE_MMMYY
CELL_FORMAT_TIME_HMMAMP
CELL_FORMAT_TIME_HMMSSAMP
CELL_FORMAT_TIME_HMM
CELL_FORMAT_TIME_HMMSS
CELL_FORMAT_DATETIME_MDYYHMM
CELL_FORMAT_DATETIME_DMMMMYYYY_TTAM
CELL_FORMAT_DATETIME_DMMMMYYYY_TT24
CELL_FORMAT_DATETIME_MMMDDYYYY_TTAM
CELL_FORMAT_DATETIME_MMMDDYYYY_TT24
CELL_FORMAT_DATETIME_MDYY_TTAM
CELL_FORMAT_DATETIME_MDYY_TT24
CELL_FORMAT_COMMA_INTEGER_PAREN
CELL_FORMAT_COMMA_INTEGER_RED_PAREN
CELL_FORMAT_COMMA_FLOAT_PAREN
CELL_FORMAT_COMMA_FLOAT_RED_PAREN
CELL_FORMAT_TIME_MMSS
CELL_FORMAT_TIME_H_MMSS
CELL_FORMAT_CURRENCY_RED

Return Value:

True on success; false on failure to assign

AddStyleTextRotation (new with Release 18)

Description: Adds to the style definition cell text rotation formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tnRotation	Rotation angle to set the text (value between -90 and 90 degrees)

Return Value:

True on success; false on failure to assign

AddStyleVertAlignment (new with Release 18)

Description: Adds to the style definition cell vertical alignment formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tcVertAlign	Assigned by the following #DEFINEs CELL_VERT_ALIGN_TOP CELL_VERT_ALIGN_BOTTOM CELL_VERT_ALIGN_CENTER

Return Value:

True on success; false on failure to assign

AddStyleWordWrap (new with Release 18)

Description: Adds to the style definition cell word wrap formatting

Parameters:

tnWB	Id to workbook
tnCellXfsId	Id to the format style
tlWordWrap	True - set wordwrapping on; False - set wordwrapping off

Return Value:

True on success; false on failure to assign

CreateFormatStyle (new with Release 18)

Description: Creates a new formatting style definition to be applied to cells

Parameters:

tnWB	Id to workbook
------	----------------

Return Value:

Id value of new style

GetCellStyle (new with Release 18)

Description: Returns the assigned cell style Id value

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Id value of new style

SetCellStyle (new with Release 18)

Description: Sets the cell style Id to a selected cell

Parameters:

tnWB	Id to workbook
------	----------------

Return Value:

Id value of new style

SetCellStyleRange (new with Release 18)

Description: Sets the cell style Id to a selected cell range of rows/columns

Parameters:

tnWB	Id to workbook
------	----------------

Return Value:

Id value of new style

Methods – Returning Cell Formatting

GetCellAlignment

Description: Returns the cell alignment

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Return object:

loReturn.HorzAlign	Horizontal alignment value
loReturn.VertAlign	Vertical alignment value

See method SetCellAlignment() for the #DEFINE values

GetCellBorders

Description: Returns the cell border info

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Return object:

loBdrInfo.LeftStyle	Left border style
loBdrInfo.LeftColor	Left border color (integer)
loBdrInfo.Index	Left border color index (integer) [changed]
loBdrInfo.Tint	Left border color tint (integer) [changed]
loBdrInfo.Theme	Left border color theme (integer) [changed]
loBdrInfo.RightStyle	Right border style
loBdrInfo.RightColor	Right border color (integer)
loBdrInfo.RightIndex	Right border color index (integer) [changed]
loBdrInfo.RightTint	Right border color tint (integer) [changed]
loBdrInfo.RightTheme	Right border color theme (integer) [changed]

loBdrInfo.TopStyle	Top border style
loBdrInfo.TopColor	Top border color (integer)
loBdrInfo.TopIndex	Top border color index (integer) [changed]
loBdrInfo.TopTint	Top border color tint (integer) [changed]
loBdrInfo.TopTheme	Top border color theme (integer) [changed]
loBdrInfo.BotStyle	Bottom border style
loBdrInfo.BotColor	Bottom border color (integer)
loBdrInfo.BotIndex	Bottom border color index (integer) [changed]
loBdrInfo.BotTint	Bottom border color tint (integer) [changed]
loBdrInfo.BotTheme	Bottom border color theme (integer) [changed]
loBdrInfo.DiagStyle	Diagonal style
loBdrInfo.DiagColor	Diagonal color (integer)
loBdrInfo.DiagIndex	Diagonal border color index (integer) [changed]
loBdrInfo.DiagTint	Diagonal border color tint (integer) [changed]
loBdrInfo.DiagTheme	Diagonal border color theme (integer) [changed]
loBdrInfo.DiagDn	Integer value for down setting [changed]
loBdrInfo.DiagUp	Integer value for up setting [changed]

See method SetCelBorder() for the #DEFINE values

GetCellFill

Description: Returns the fill info for the cell

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

loFillInfo.FgColor	Fill foreground color (integer)
loFillInfo.BgColor	Fill background color (integer)
loFillInfo.PatType	Fill pattern type
loFillInfo.Theme	Fill color theme (integer)
loFillInfo.Tint	Fill color tint (integer)
loFillInfo.FgIndexed	Fill foreground color index value (integer)
loFillInfo.BgIndexed	Fill background color index value (integer)

NULL if cell fill is not defined.

GetCellFont

Description: Returns the cell font settings

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Return object:

loFontInfo.FontName	Font name
loFontInfo.FontSize	Font size (integer)
loFontInfo.FontBold	Boolean; True bold is set, False bold is not set
loFontInfo.FontItalic	Boolean; True italic is set, False italic is not set
loFontInfo.ForeColor	Font forecolor (integer)
loFontInfo.FontUnderline	Boolean; True underline is set, False underline is not set
loFontInfo.FontStrikeThr	Boolean; True strike-through is set, False strike-through is not set
loFontInfo.FontVerticalPos	Verical position of text (set SetCellFont() method for #DEFINE values)

NULL if cell is not defined.

GetCellIndent

Description: Returns the cell indentation

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Indentation amount; returns -1 if cell does not exist

GetCellTextRotation (new with Release 17)

Description: Returns the cell text rotation

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Text rotation amount (value between -90 and 90 degrees); returns 99 if incorrect parameters are sent.

GetCellWordWrap

Description: Returns the cell word wrap setting

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Boolean value; True wordwrap is set, False wordwrap is not set.

Methods – Assigning Cell Formatting

AddIndexColor (new with Release 18)

Description: Adds a new indexed color definition to the workbook

Parameters:

tnWB	Id to workbook
tnRGBColor	RGB() color value to add

Return Value:

Index value assigned to color

AddMruColor (new with Release 18)

Description: Adds a custom defined MRU color to the workbook

Parameters:

tnWB	Id to workbook
tnRGBColor	RGB() color value to add

Return Value:

MRU index value assigned to color

CellFormatPainter (new with Release 18)

Description: Copies the selected cell format to the specified range of cells

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnSrcRow	Row of cell containing the format that is to be copied
tnSrcCol	Column of cell containing the format that is to be copied
tnBegRow	Row to begin the cell format copy to
tnBegCol	Column to begin the cell format copy to
tnEndRow	Row to end the cell format copy to
tnEndCol	Column to end the cell format copy to

Return Value:

True on success
False on failure

MergeCells

Description: Provides for merging cells into a single cell

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnBegRow	Row to begin the cell merge
tnBegCol	Column to begin the cell merge
tnEndRow	Row to end the cell merge
tnEndCol	Column to end the cell merge

Return Value:

True on success
False on failure

SetCellAlignment (depricated with Release 18)

Description: Sets the cell alignment (vertical and horizontal)

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tcHorizAlign	Horizontal alignment (from #DEFINES) CELL_HORIZONTAL_ALIGN_LEFT CELL_HORIZONTAL_ALIGN_RIGHT CELL_HORIZONTAL_ALIGN_CENTER
tcVertAlign	Vertical alignment (from #DEFINES) CELL_VERTICAL_ALIGN_TOP CELL_VERTICAL_ALIGN_BOTTOM CELL_VERTICAL_ALIGN_CENTER

Return Value:

True on success
False on failure

SetCellBorder (depricated with Release 18)

Description: Sets the cell border; each border is drawn with the same style and color

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tnBorders	Cell Border to draw; this is a addition of the appropriate border side to set; to set all sides: BORDER_LEFT + BORDER_RIGHT + BORDER_TOP + BORDER_BOTTOM + BORDER_DIAGDOWN + BORDER_DIAGUP
tcBorderStyle	Style of border to draw; the following styles are available: BORDER_STYLE_THIN BORDER_STYLE_HAIR BORDER_STYLE_DOTTED BORDER_STYLE_DASHDOTDOT BORDER_STYLE_DASHDOT BORDER_STYLE_DASHED BORDER_STYLE_THIN BORDER_STYLE_MEDIUMDASHDOTDOT BORDER_STYLE_SLANTDASHDOT BORDER_STYLE_MEDIUMDASHDOT BORDER_STYLE_MEDIUMDASHED BORDER_STYLE_MEDIUM BORDER_STYLE_THICK BORDER_STYLE_DOUBLE
tnBorderColor	The color to draw the border in RGB() value

Return Value:

True on success

False on failure

SetCellBorderEx (depricated with Release 18)

Description: Sets the cell border; each border can have a different style or color

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tcLeftStyle	Left border style
tnLeftColor	Left border color
tcRightStyle	Right border style
tnRightColor	Right border color
tcTopStyle	Top border style
tnTopColor	Top border color
tcbotStyle	bot border style
tnbotColor	bot border color
tcdiagStyle	diag border style
tndiagColor	diag border color
tndiagDownUp	diag border drawn down/up

Return Value:

True on success
False on failure

SetCellBorderRange (depricated with Release 18)

Description: Sets the cell border for a range of cells; each border is drawn with the same style and color

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnBegRow	Cell beginning row (integer)
tnBegCol	Cell beginning column (integer)
tnEndRow	Cell ending row (integer)
tnEndCol	Cell ending column (integer)
tnBorders	Border to draw; this is a combination of the following by adding: BORDER_LEFT + BORDER_RIGHT + BORDER_TOP + BORDER_BOTTOM + BORDER_DOWN + BORDER_UP
tcBorderStyle	Style of border to draw; the following styles are available: BORDER_STYLE_THIN BORDER_STYLE_HAIR BORDER_STYLE_DOTTED BORDER_STYLE_DASHDOTDOT BORDER_STYLE_DASHDOT BORDER_STYLE_DASHED BORDER_STYLE_THIN BORDER_STYLE_MEDIUMDASHDOTDOT BORDER_STYLE_SLANTDASHDOT BORDER_STYLE_MEDIUMDASHDOT BORDER_STYLE_MEDIUMDASHED BORDER_STYLE_MEDIUM BORDER_STYLE_THICK BORDER_STYLE_DOUBLE
tnBorderColor	The color to draw the border in RGB() value

Return Value:

True on success
False on failure

SetCellFill (depricated with Release 18)

Description: Sets the cell fill color (background)

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tnFColor	Fill foreground color; RGB(N,N,N) [changed]
tnBColor	Fill background color; RGB(N,N,N) [changed]
tcPatternType	Fill pattern type [changed]

Return Value:

True on success
False on failure

SetCellFillRange (depricated with Release 18)

Description: Sets the cell fill color (background) for a range of cells

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnBegRow	Cell beginning row (integer)
tnBegCol	Cell beginning column (integer)
tnEndRow	Cell ending row (integer)
tnEndCol	Cell ending column (integer)
tnFColor	Fill foreground color; RGB(N,N,N) [changed]
tnBColor	Fill background color; RGB(N,N,N) [changed]
tcPatternType	Fill pattern type [changed]

Return Value:

True on success
False on failure

SetCellFont (depricated with Release 18)

Description: Sets the cell format

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tcFName	Font name
tnFSize	Font size
tlBold	Boolean to indicate bold font
tlItalic	Boolean to indicate italic font
tnFColor	Font foreground color; RGB(N,N,N)
tcULine	Boolean to indicate underline
tlStrikThr	Boolean to indicate strikethrough
tcVPos	Verical position of text (from #DEFINEs) FONT_VERTICAL_BASELINE FONT_VERTICAL_SUBSCRIPT FONT_VERTICAL_SUPERSCRIPT

Return Value:

True on success
False on failure

SetCellFontRange (depricated with Release 18)

Description: Sets the cell format for a range of cells

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnBegRow	Cell beginning row (integer)
tnBegCol	Cell beginning column (integer)
tnEndRow	Cell ending row (integer)
tnEndCol	Cell ending column (integer)
tcFName	Font name
tnFSize	Font size
tlBold	Boolean to indicate bold font
tlItalic	Boolean to indicate italic font
tnFColor	Font foreground color; RGB(N,N,N)
tcULine	Boolean to indicate underline
tlStrikThr	Boolean to indicate strikethrough
tcVPos	Verical position of text (see SetCellFont() method for values)

Return Value:

True on success
False on failure

SetCellIndent (depricated with Release 18)

Description: Sets the cell indentation

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Row to begin the cell merge
tnCellCol	Column to begin the cell merge
tnIndent	Cell indentation value

Return Value:

True if set; False if not set

SetCellNumberDecimals (depricated with Release 18)

Description: sets the number of decimals to be displayed (used with SetCellNumberFormat)

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tnNumDecimals	Number of decimals to be displayed

Return Value:

True on success
False on failure

SetCellNumberFormat (depricated with Release 18)

Description: Sets the numeric format for the cell value

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tnNumFormat	Value of numeric format (from #DEFINEs)

CELL_FORMAT_INTEGER
CELL_FORMAT_FLOAT
CELL_FORMAT_COMMA_INTEGER
CELL_FORMAT_COMMA_FLOAT
CELL_FORMAT_CURRENCY_PAREN
CELL_FORMAT_CURRENCY_RED_PAREN
CELL_FORMAT_PERCENT_INTEGER
CELL_FORMAT_PERCENT_FLOAT
CELL_FORMAT_EXPONENT
CELL_FORMAT_FRACTION_1
CELL_FORMAT_FRACTION_2
CELL_FORMAT_DATE_MMDDYY
CELL_FORMAT_DATE_DMMYY
CELL_FORMAT_DATE_DMMM
CELL_FORMAT_DATE_MMMYY
CELL_FORMAT_TIME_HMMAMP
CELL_FORMAT_TIME_HMMSSAMP
CELL_FORMAT_TIME_HMM
CELL_FORMAT_TIME_HMMSS
CELL_FORMAT_DATETIME_MDYYHMM

CELL_FORMAT_DATETIME_DDMMYYYY_TTAM
CELL_FORMAT_DATETIME_DDMMYYYY_TT24
CELL_FORMAT_DATETIME_MMMDDYYYY_TTAM
CELL_FORMAT_DATETIME_MMMDDYYYY_TT24
CELL_FORMAT_DATETIME_MDYY_TTAM
CELL_FORMAT_DATETIME_MDYY_TT24
CELL_FORMAT_COMMA_INTEGER_PAREN
CELL_FORMAT_COMMA_INTEGER_RED_PAREN
CELL_FORMAT_COMMA_FLOAT_PAREN
CELL_FORMAT_COMMA_FLOAT_RED_PAREN
CELL_FORMAT_TIME_MMSS
CELL_FORMAT_TIME_H_MMSS
CELL_FORMAT_CURRENCY_RED

Return Value:

True on success

False on failure

SetCellNumberFormatRange (depricated with Release 18)

Description: Sets the numeric format for a range of cell values

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnBegRow	Cell beginning row (integer)
tnBegCol	Cell beginning column (integer)
tnEndRow	Cell ending row (integer)
tnEndCol	Cell ending column (integer)
tnNumFormat	Value of numeric format (see SetCellNumberFormat() method for list of values)

Return Value:

True on success

False on failure

SetCellTextRotation (depricated with Release 18)

Description: Sets the cell text rotation

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Row to begin the cell merge
tnCellCol	Column to begin the cell merge
tnRotation	Rotation angle to set the text (value between -90 and 90 degrees)

Return Value:

True on success
False on failure

SetCellWordWrap (depricated with Release 18)

Description: Sets the cell word-wrap value

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)
tlWordWrap	True - set wordwrapping on; False - set wordwrapping off

Return Value:

True on success
False on failure

SetCellWordWrapRange (depricated with Release 18)

Description: Sets the cell word-wrap value for a range of cells

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnBegRow	Cell beginning row (integer)
tnBegCol	Cell beginning column (integer)
tnEndRow	Cell ending row (integer)
tnEndCol	Cell ending column (integer)
tlWordWrap	True - set wordwrapping on; False - set wordwrapping off

Return Value:

True on success
False on failure

UnMergedCells

Description: Removes the merged cells restoring to individual cells

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnBegRow	Row to begin the cell merge
tnBegCol	Column to begin the cell merge
tnEndRow	Row to end the cell merge
tnEndCol	Column to end the cell merge

Return Value:

True on success
False on failure

Methods – In-Line Text Formatting

AddInlineFontObject (new with Release 17)

Description: Adds an in-line character definition to the base in-line font definition object

Parameters:

toInline	In-Line Text object
tnBeg	Beginning position for text format in text string
tnLen	Length of text for format in text string
tcFontName	Font name for in-line text
tnFontSize	Font size for in-line text
tnFontColor	Font color for in-line text
tlFontBold	Font bold for in-line text
lFontItalic	Font italic for in-line text
tcULine	Font underline for in-line text
tlStrkThru	Font strike-through for in-line text
tlSubscript	Font subscript for in-line text
tlSuperscript	Font superscript for in-line text

Return Value:

In-Line Character format object added to the In-Line Text object:

- loCharacter.BegPos
- loCharacter.Length
- loCharacter.FontName
- loCharacter.FontSize
- loCharacter.FontBold
- loCharacter.FontItalic
- loCharacter.FontColor
- loCharacter.Underline
- loCharacter.StrikeThru
- loCharacter.SubScript
- loCharacter.SuperScript

CreateInlineFormatText (new with Release 17)

Description: Creates the base in-line font object for assigning a text string in a cell to have its characters to be individually formatted

Parameters:

tnWB	Id to workbook
tcCellText	Full text for the cell value

Return Value:

loInline.Workbook	Id to workbook
loInline.StringId	Internal String Id for text string (initially set to NULL)
loInline.StringValue	String value to be assigned to cell
loInline.Count	Count of in-line character format expressions (initially zero)
loInline.Characters[1]	Array of in-line character format expressions (set to NULL)

Null value if cell text not assigned.

GetInlineFormatText (new with Release 17)

Description: Gets the in-line formatted text definition for a cell text string

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row number
tnCellCol	Cell column number

Return Value:

loInline.Workbook	Id to workbook
loInline.StringId	Internal String Id for text string
loInline.StringValue	String value assigned to cell
loInline.Count	Count of in-line character format expressions
loInline.Characters[n]	Array of in-line character format expressions
loInline.Characters[n].BegPos	nth Beginning position of in-line character format
loInline.Characters[n].Length	nth Length of of in-line character format
loInline.Characters[n].FontName	nth Font name of in-line character format
loInline.Characters[n].FontSize	nth Font size of in-line character format
loInline.Characters[n].FontBold	nth Font bold setting of in-line character format
loInline.Characters[n].FontItalic	nth Font italic setting of in-line character format
loInline.Characters[n].FontColor	nth Font color setting of in-line character format

<code>loInline.Characters[n].Underline</code>	nth Font underline setting of in-line character format
<code>loInline.Characters[n].StrikeThru</code>	nth Font Strike Through setting of in-line character format
<code>loInline.Characters[n].SubScript</code>	nth Font sub-script setting of in-line character format
<code>loInline.Characters[n].SuperScript</code>	nth Font super-script setting of in-line character format

Null value if cell text is not assigned to an in-line format.

SetCellInLineFormatText (new with Release 17)

Description: Saves an in-line text definition for a text string to a cell

Parameters:

<code>tnWB</code>	Id to workbook
<code>tnSh</code>	Id to sheet in workbook
<code>tnCellRow</code>	Cell row number
<code>tnCellCol</code>	Cell column number
<code>toInline</code>	In-Line Text object

Return Value:

True on success; False on failure (this value will be returned if the `toInline.Workbook` value does not match the `tnWB` value)

Comments:

If the `toInline.Workbook` value does not match the `tnWB` value, False will be returned (no assignment). You can use the same `loInline` object to assign the same in-line formatted text to multiple spreadsheet cells within the same workbook (i.e., different sheets).

Methods – Numeric Cell Formats

AddCustomNumericFormat

Description: Adds a new definition for a numeric format

Parameters:

tcPosSect	Format for positive numbers; is the format code that applies to the cell when the cell value contains a positive number. [required]
tcNegSect	Format for negative numbers; is the format code that applies to the cell when the cell value contains a negative number. [optional]
tcZeroSect	Format for zeros; is the format code that applies to the cell when the cell value is zero. [optional]
tcTextSect	Format for text; is the format code that applies to the cell when the cell value is text. [optional]
tlApplyDec	Flag to set the number of decimals as determined by the method SetCellNumberDecimals(); defaults to False [optional]

Return Value:

Id of format
0 on failure

AddNumericFormat

Description: Adds a new definition for a numeric format (full format must be specified)
[retained for backward compatibility]

Parameters:

tcFormatCode Numeric format to be added

Return Value:

Id of format
0 on failure

GetCellNumberFormat

Description: Returns the format code for the selected cell

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Number format code
Zero if none or failure

GetCellNumberFormatText (new with Release 18)

Description: Returns the format text for the selected cell

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row (integer)
tnCellCol	Cell column (integer)

Return Value:

Number format text string
Empty string if none or failure

GetCustomNumericFormat

Description: Returns the specified numeric custom format code

Parameters:

tnWB	Id to workbook [changed]
tnFormatCode	Format Id to return

Return Value:

Numeric Format code; empty string if none.

Methods – Cell Validations and Named Ranges

AddNamedRange (new with Release 16)

Description: Removes any cell validations

Parameters:

tnWB	Id to workbook
tnSheet	Sheet index of the named range
tcName	Range name
tnScope	Scope of named range; use value from #DEFINEs <code>SCOPE_WB_NAMED_RANGE</code> <code>SCOPE_SH_NAMED_RANGE</code>
tcComment	Comment for named range
tnBegRow	Named range cell beginning row number
tnBegCol	Named range cell beginning column number
tnEndRow	Named range cell ending row number
tnEndCol	Named range cell ending column number

Return Value:

Range name (replaces spaces with underscore character)
Empty string on failure

ClearCellValidation (new with Release 16)

Description: Removes any cell validations

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row number
tnCellCol	Cell column number

Return Value:

True on success
False on failure

ClearNamedRange (new with Release 16)

Description: Removes the named range from the workbook

Parameters:

tnWB	Id to workbook
tcName	Range name

Return Value:

True on success
False on failure

GetCellValidation (new with Release 16)

Description: Gets the cell validation formula settings

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row number
tnCellCol	Cell column number

Return Value:

Validation Object, loValidation with the following properties:

- loValiation.Type
- loValiation.Style
- loValiation.Operator
- loValiation.AllowBlank
- loValiation.ShowInputMsg
- loValiation.ShowErrMsg
- loValiation.ErrMsg
- loValiation.ErrTitle
- loValiation.Prompt
- loValiation.Formula1
- loValiation.Formula2

GetValidation (new with Release 16)

Description: Returns an object with the validation definition

Parameters:

tnValidNdx	Validation index
------------	------------------

Return Value:

Validation Object, loValidation with the following properties:

- loValiation.Type
- loValiation.Style
- loValiation.Operator
- loValiation.AllowBlank
- loValiation.ShowInputMsg
- loValiation.ShowErrMsg
- loValiation.ErrMsg
- loValiation.ErrTitle
- loValiation.Prompt
- loValiation.Formula1
- loValiation.Formula2

GetValidationList (new with Release 16)

Description: Returns an object with the list of validations for the workbook/sheet

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook

Return Value:

Validation Object, loValidation with the following properties:

- loValiation.Count
- loValiation.List[1, 1] = Validation Type
- loValiation.List[1, 2] = Validation Index

SetCellValidation (new with Release 16)

Description: Sets cell validation

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnCellRow	Cell row number
tnCellCol	Cell column number
tnType	Cell validation type; use #DEFINEs for value <div> <div>NONE_VALID_TYPE</div> <div>DATE_VALID_TYPE</div> <div>WHOLE_VALID_TYPE</div> <div>TIME_VALID_TYPE</div> <div>DECIMAL_VALID_TYPE</div> <div>TXTLEN_VALID_TYPE</div> <div>LIST_VALID_TYPE</div> <div>CUSTOM_VALID_TYPE</div> </div>
tnStyle	Cell validation style [optional; defaults to none] ; use #DEFINEs for value <div> <div>STOP_VALID_STYLE</div> <div>WARN_VALID_STYLE</div> <div>INFO_VALID_STYLE</div> </div>
tnOperator	Cell validation operator [optional; defaults to none] ; use #DEFINEs for value <div> <div>BETWEEN_VALID_OPER</div> <div>LESSTHAN_VALID_OPER</div> <div>NOTBETW_VALID_OPER</div> <div>LESSOREQUAL_VALID_OPER</div> <div>EQUAL_VALID_OPER</div> <div>GREATTHAN_VALID_OPER</div> <div>NOTEQUAL_VALID_OPER</div> <div>GREATOREQUAL_VALID_OPER</div> </div>
tlAllowBlank	Boolean to indicate if cell value can be blank [default true]
tShowInputMsg	Boolean to show input message [default true]
tlShowErrMsg	Boolean to show error message [default true]
tcErrMsg	Cell error message to display to user; limited to 100 characters [optional; defaults to none]
tcErrTitle	Cell error title on message displayed; limited to 100 characters [optional; defaults to none]
tcPrompt	Cell prompt information to user; limited to 100 characters [optional; defaults to none]
tcFormula	Cell validation formula; limited to 254 characters; a list of allowed values is separated by commas

Return Value:

True on success
False on failure

Methods – Set Sheet Formatting

FreezePanes

Description: Provides for freezing the upper rows and left columns for scrolling

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnTopRowCount	Number of rows to freeze at the top
tnSideColCount	Number of columns to freeze at the left

Return Value:

True on success
False on failure

ResetColumnWidth

Description: Resets the column width to the default of Excel

Parameters:

tnWB	Id to workbook
tnSh	Id to sheet in workbook
tnColumn	Column index to reset width

Return Value:

True on success
False on failure

SetColumnBestFit

Description: Sets the column width to best fit (this method is not yet fully working and is not currently saved in the sheet).

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnColumn	Column index (integer) to set to best fit
tlBestFit	Boolean value; True set to best fit, False do not set

Return Value:

True on success
False on failure

SetColumnWidth

Description: Sets the selected column width

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnColumn	Column index (integer) to set the width of
tnWidth	Value to set the column width to

Return Value:

True on success
False on failure

SetColumnWidthRange

Description: Sets the column width for a range of columns

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnBegCol	Beginning column index (integer) to set the width of
tnEndCol	Ending column index (integer) to set the width of
tnWidth	Value to set the column width to

Return Value:

True on success
False on failure

SetHeaderFooterSetup

Description: Sets the properties for the header /footer in the sheet (Align to margins, different first page, different odd/even pages, and scale with print). This method must be set before calling SetHeaderFooterText() method.

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tlAlignMargin	Boolean; True – align with margins, False – fixed position
tlDiffFirstPg	Boolean; True – different first page, False – same as odd page
tlDiffOddEven	Boolean; True – different odd/even pages, False – same as odd page
tlScaleWDoc	Boolean; True – scale size with sheet scalling factor; False – fixed

Return Value:

True on success
False on failure

SetHeaderFooterText

Description: Sets the header text

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnPage	Page to apply header/footer text; i.e., first page, odd page, or even page; use #DEFINEs values (use same page for same odd and even pages) <div>HEADERFOOTER_FIRST_PAGE HEADERFOOTER_EVEN_PAGE HEADERFOOTER_ODD_PAGE HEADERFOOTER_SAME_PAGE</div>
tnSection	Position of the text (i.e., Left, Center, or Right); use #DEFINEs values <div>HEADERFOOTER_POS_FTR_LEFT HEADERFOOTER_POS_HDR_LEFT HEADERFOOTER_POS_FTR_CENTER HEADERFOOTER_POS_HDR_CENTER HEADERFOOTER_POS_FTR_RIGHT HEADERFOOTER_POS_HDR_RIGHT</div>
tcText	Header text
tcFontName	Font name of header/footer text [optional]
tnFontSize	Font size of header/footer text [optional]
tnFontStyle	Font effect of header/footer text [optional]; i.e., normal, italic, or bold; use #DEFINEs values <div>HEADERFOOTER_FONT_STYLE_NORMAL HEADERFOOTER_FONT_STYLE_ITALIC HEADERFOOTER_FONT_STYLE_BOLD HEADERFOOTER_FONT_STYLE_BOLDITALIC</div>

Return Value:

True on success
False on failure

SetRowHeight

Description: Sets the selected row height

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnRow	Row index (integer) to set the height of
tnHeight	Value to set the row height to

Return Value:

- True on success
- False on failure

SetRowHeightRange

Description: Sets the selected row height

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnBegRow	Beginning row index (integer) to set the height of
tnEndRow	Ending row index (integer) to set the height of
tnHeight	Value to set the row height to

Return Value:

- True on success
- False on failure

UnFreezePanes

Description: Removes all of the panes that are frozen (top and side)

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

- True on success
- False on failure

Methods – Sheet Printer Setup

GetCustomPaperSize

Description: Gets the values for the custom paper size

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

Return object:

loReturn.PaperWidth	Paper width value
loReturn.PapeHeight	Paper height value
loReturn.PaperDimen	Paper width/height unit of measurement (in or mm)

GetPaperSize

Description: Gets the paper size for the selected sheet

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

Paper size value (see SetPaperSize() method for a list of values)
-1 on failure or none set

GetPrintOrientation

Description: Gets the print orientation for the sheet output

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

Printer orientation; numeric value (see the #DEFINE list of values)
Zero on failure or none set

GetSheetScale

Description: Gets the sheet printing scale

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

Printer scale value (numeric)
-1 on failure or none set

SetCustomPaperSize

Description: Sets the paper size based on custom dimensions

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnWidth	Paper width (numeric value)
tnHeight	Paper height (numeric value)
tcDimen	Unit of measurement (in or mm)

Return Value:

True on success
False on failure

SetPaperSize

Description: Sets the paper size for the selected sheet

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnPaperSize	The paper size to set (see the #DEFINEs list of values)

PAPERSIZE_LTR	PAPERSIZE_A5_TRANSVERSE
PAPERSIZE_LTR_SMALL	PAPERSIZE_JIS_B5_TRANSVERSE
PAPERSIZE_TABLOID	PAPERSIZE_A3_EXTRA
PAPERSIZE_LEDGER	PAPERSIZE_A5_EXTRA
PAPERSIZE_LEGAL	PAPERSIZE_ISO_B5_EXTRA
PAPERSIZE_STATEMENT	PAPERSIZE_A2
PAPERSIZE_EXECUTIVE	PAPERSIZE_A3_TRANSVERSE
PAPERSIZE_A3	PAPERSIZE_A3_EXTRA_TRANSVERSE
PAPERSIZE_A4	PAPERSIZE_JPN_DOUBLE
PAPERSIZE_A4_SMALL	PAPERSIZE_A6
PAPERSIZE_A5	PAPERSIZE_JPN_ENV_KAKU1
PAPERSIZE_B4	PAPERSIZE_JPN_ENV_KAKU2
PAPERSIZE_B5	PAPERSIZE_JPN_ENV_CHOU3
PAPERSIZE_FOLIO	PAPERSIZE_JPN_ENV_CHOU4
PAPERSIZE_QUARTO	PAPERSIZE_LTR_ROT
PAPERSIZE_STD10X14	PAPERSIZE_A3_ROT
PAPERSIZE_STD11X17	PAPERSIZE_A4_ROT
PAPERSIZE_NOTE	PAPERSIZE_A5_ROT
PAPERSIZE_9ENV	PAPERSIZE_B4_JIS_ROT
PAPERSIZE_10ENV	PAPERSIZE_B5_JIS_ROT
PAPERSIZE_11ENV	PAPERSIZE_JPN_POSTCARD
PAPERSIZE_12ENV	PAPERSIZE_DOUBLE_JPN
PAPERSIZE_14ENV	PAPERSIZE_A6_ROT
PAPERSIZE_C	PAPERSIZE_JPN_ENV_KAKU2_ROT
PAPERSIZE_D	PAPERSIZE_JPN_ENV_KAKU3_ROT
PAPERSIZE_E	PAPERSIZE_JPN_ENV_CHOU3_ROT
PAPERSIZE_DL_ENV	PAPERSIZE_JPN_ENV_CHOU4_ROT
PAPERSIZE_C5_ENV	PAPERSIZE_B6_JIS
PAPERSIZE_C3_ENV	PAPERSIZE_B6_JIS_ROT
PAPERSIZE_C4_ENV	PAPERSIZE_12X11
PAPERSIZE_C6_ENV	PAPERSIZE_JPN_ENV_YOU4
PAPERSIZE_C65_ENV	PAPERSIZE_JPN_ENV_YOU4_ROT
PAPERSIZE_B4_ENV	PAPERSIZE_PRC_16K
PAPERSIZE_B5_ENV	PAPERSIZE_PRC_32K
PAPERSIZE_B6_ENV	PAPERSIZE_PRC_32K_BIG
PAPERSIZE_ITALY_ENV	PAPERSIZE_PRC_ENV_1
PAPERSIZE_MONARCH_ENV	PAPERSIZE_PRC_ENV_2
PAPERSIZE_6_3_4_ENV	PAPERSIZE_PRC_ENV_3
PAPERSIZE_US_STD_FANFOLD	PAPERSIZE_PRC_ENV_4
PAPERSIZE_GERMAN_STD_FANFOLD	PAPERSIZE_PRC_ENV_5
PAPERSIZE_GERMAN_LGL_FANFOLD	PAPERSIZE_PRC_ENV_6
PAPERSIZE_ISO_B4	PAPERSIZE_PRC_ENV_7
PAPERSIZE_JPN_DBL_POSTCARD	PAPERSIZE_PRC_ENV_8
PAPERSIZE_STD_PAPER9X11	PAPERSIZE_PRC_ENV_9
PAPERSIZE_STD_PAPER10X11	PAPERSIZE_PRC_ENV_10
PAPERSIZE_STD_PAPER15X11	PAPERSIZE_PRC_16K_ROT
PAPERSIZE_INVOICE_ENV	PAPERSIZE_PRC_32K_ROT

PAPERSI ZE_LTR_XTRA_PAPER
PAPERSI ZE_LEGAL_XTRA_PAPER
PAPERSI ZE_TABLOID_XTRA_PAPER
PAPERSI ZE_A4_XTRA_PAPER
PAPERSI ZE_LTR_TRANSVERSE
PAPERSI ZE_A4_TRANSVERSE
PAPERSI ZE_LTR_XTRA_TRANSV
PAPERSI ZE_SUPER_A4
PAPERSI ZE_SUPERB_A3
PAPERSI ZE_LTR_PLUS
PAPERSI ZE_A4_PLUS

PAPERSI ZE_PRC_32K_BIG_ROT
PAPERSI ZE_PRC_ENV_1_ROT
PAPERSI ZE_PRC_ENV_2_ROT
PAPERSI ZE_PRC_ENV_3_ROT
PAPERSI ZE_PRC_ENV_4_ROT
PAPERSI ZE_PRC_ENV_5_ROT
PAPERSI ZE_PRC_ENV_6_ROT
PAPERSI ZE_PRC_ENV_7_ROT
PAPERSI ZE_PRC_ENV_8_ROT
PAPERSI ZE_PRC_ENV_9_ROT
PAPERSI ZE_PRC_ENV_10_ROT

Return Value:

True on success

False on failure

SetPrintFitToHeight

Description: Number of vertical pages to fit on

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnFitToHeight	Number of pages to fit to height

Return Value:

True on success

False on failure

SetPrintFitToWidth

Description: Number of horizontal pages to fit on

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnFitToWidth	Number of pages to fit to width

Return Value:

True on success

False on failure

SetPrintOrientation

Description: Sets the printer orientation for sheet output

Parameters:

tnWB	Id to workbook	
tnSheet	Id to sheet in workbook	
tnOrientation	The printer orientation to set	PORTRAIT_PRINT_ORIENTATION LANDSCAPE_PRINT_ORIENTATION

Return Value:

True on success; False on failure

SetSheetMargins

Description: Sets the margins of the sheet

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook
tnLeft	Value for left margin
tnRight	Value for right margin
tnTop	Value for top margin
tnbot	Value for bot margin
tnHeader	Value for header margin
tnFooter	Value for footer margin

Return Value:

True on success; False on failure

SetSheetScale

Description: Sets the print scale; must be between 10 and 400; i.e. 10=10%, 50=50%, 100=100%, 175=175%, etc.

Parameters:

tnWB	Id to workbook
tnSheet	Id to sheet in workbook

Return Value:

True on success; False on failure

Methods – Direct VFP Table Support

SaveGridToWorkbook (parameter change with Release 16)

Description: Saves the passed grid to a workbook in xlsx file format. Uses the grid column widths to set the workbook column widths. Adds a new sheet for each passed grid if the same workbook name.

Parameters:

toGrid	Object reference to the grid to be saved
txWB	Integer value: Workbook integer value as returned by CreateWorkbook() method; String value: Workbook file name to be created
tlFreeze	[optional] Boolean to set the FreezePanels on the first row; defaults to True
tlSaveWB	[optional] Boolean to save the workbook to file; defaults to True
tcSheetName	[optional] Name of sheet to add; defaults to table alias

Return Value:

Return object:

loReturn.Workbook	Workbook Id; zero on failure
loReturn.Sheet	Sheet Id; zero on failure

SaveTableToWorkbook (parameter change with Release 16)

Description: Saves the passed table to a workbook in xlsx file format. Adds a new sheet for each passed table if the same workbook name.

Parameters:

tcAlias	This can be the table alias (table already opened) or this can be the full path and name to a table
txWB	Integer value: Workbook integer value as returned by CreateWorkbook(); String value: Workbook file name to be created
tlFreeze	[optional] Boolean to set the FreezePanels on the first row; defaults to True
tlSaveWB	[optional] Boolean to save the workbook to file; defaults to True
tcSheetName	[optional] Name of sheet to add; defaults to table alias

Return Value:

Return object:

loReturn.Workbook	Workbook Id; zero on failure
loReturn.Sheet	Sheet Id; zero on failure

Methods – Support

ColumnAsciiToIndex

Description: Converts a Excel notation column reference (ASCII character) to an numeric (integer) column reference

Parameters:
tcCol ASCII value of column

Return Value:
Integer of column index

ColumnIndexToAscii

Description: Converts a numeric (integer) column reference to an ASCII character column reference

Parameters:
tnCol Integer value of column to convert to ASCII

Return Value:
ASCII equivalent of column index

ConvertPixelsToExcelUnits

Description: Converts pixels in VFP to Excel units for column widths

Parameters:
tnCol Pixel value

Return Value:
Excel value

DebugOutput

Description: used for debugging

Parameters:
None

Return Value:

None

Demo

Description: Demo code examples of the various features of this class

Parameters:
None

Return Value:
None

ParseString

Description: Replacement for GETWORDNUM function (fixes problem of parsing a string that has a null value for one of the tokens)


Parameters:

tcText	Text string to parse
tnPos	The token to be returned in the string
tcDelimiter	The delimiter for the string


Return Value:
The text token.

Entity Diagrams


Sheet/Cell Data Schema



Cell Formatting Schema



Sheet Formatting Schema



Validation Schema

