

VFPxWorkbookXlsx Release Notes

Class for Reading/Writing XLSX Format Files

Release 10

VFPxWorkbookXlsx class Release 10 is being released in order to correct several identified bugs by users. Additionally new methods are provided for page layout of the sheets. A new method is also released for defining custom numeric formats.

There were a number of bug fixes that was identified and now fixed in this release which is the main purpose of releasing this class at time.

Additionally, there is a new method for reading an existing XLSX file into the working cursors and then supporting methods to extract the individual cell values and formatting. However, this XLSX read method is still in development and not yet ready for use. This is the method `OpenXlsxWorkbook()` – only use if you want to try it but the method will not necessarily read all the numeric or date values correctly at this point. I did not want to hold this release of VFPxWorkbookXlsx class for the completion of the reading of the XLSX file due to the other bug fixes.

Release 11

Release 11 is released to correct several identified bugs by users and to provide a first working release of reading an existing XLSX file into the class. Methods are provided to retrieve the sheet data and cell data/formatting. Methods are also provided to read a XLSX file directly to a cursor or table. Changes can be made to the cells and then re-saved to the existing file or to a new file.

The color determination of cell formatting is not yet accurate; I am not yet sure if I am reading the value incorrectly or writing the value incorrectly. This is still 'work in progress' as the color written seems to be the inverse of the original color (Red and Blue values reversed).

The data environment for the class is now private per the instance of the class. This keeps the cursor names from possible naming conflicts with other applications. The switching of data environments between the host form and this class is managed by VFPxWorkbookXlsx. VFPxWorkbookXlsx identifies the 'default' data session based on the assigned data session of the host form. If VFPxWorkbookXlsx is created as an instance independent of a form (i.e., via `NEWOBJECT()` command), then the default data session is `Id=1`.

Release 12

Release 12 is released to correct the incorrect color being written and read by the class for cell formatting.

Release 13

Release 13 is released to correct some bugs in using a class defined private data session for the cursors and the use of some currencies other than USD (in particular Euro and British Pounds). The work for the these currencies was provided by Richard Kaye. Richard also provided feedback on

some of the data session errors that are corrected. Also added support for logical data types – this data type was overlooked when writing the SetCellValue() method. The boolean values written to the xlsx file are controlled by the property TrueFalseValue which is a pipe separated string of the true and false value; by default the value is “Yes|No”.

Release 14

Release 14 is released to restore the SET DELETED setting after performing a workbook save. The previous behavior was to set it to OFF; now it restores to the setting prior to calling the save method.

Release 15

Release 15 is released to fix a stupid bug – the DataSession was not being set to the class session for the SetCellWordWrap() method. Most likely a code completion error in using intellisense and selecting the wrong method in the drop down list. Thanks to Benny Thomas for finding this problem.

Release 16

Release 16 is released to fix bugs and change the private DataSession behavior as well as adding some more functionality.

There were several DEFINES that were repeated names and now corrected. Corrected a bug in the Set...Range methods where the default DataSession was not reset in the event a set returned not set. Corrected the value assignment for a General field type (pointed out by Doug Hennig) to be an empty string; i.e. “”; I made this assignment in the method SetCellValue based on the value data type.

The intent of the private DataSession was to prevent the collision of using the same cursor name in the class and by others in their forms/classes. My naming convention for cursors is to prefix them with a c underscore; i.e., c_strings. This naming convention could be used by others as well. So I attempted to prevent this by a private DataSession. But this has proven to be troublesome in having to constantly switch to the private DataSession and then back to the default DataSession. The most particular problem was when a grid is to be outputted to a spreadsheet. Having the cursors in their own DataSession and the grid's cursorsource in another DataSession causes the grid to loose its CursorSource setting. Additionally, there are performance delays in the constant switching of DataSessions. So in short, I have decided to remove the private DataSession and rename the working cursors with an xl_ prefix. Hopefully, this naming convenion is not being commonly used by others in cursor or alias naming.

The following methods have been added:

GetWorkbookFileName()	ClearNamedRange()
OpenCreatedXlsxFile()	GetCellValidation()
GetSheetName()	GetValidation()
SetSheetVisibility()	GetValidationList()
AddNamedRange()	SetCellValidation()
ClearCellValidation()	

Release 17

Release 17 is released to fix issues with opening existing workbooks. There were errors associated with extracting the cell formatting. To resolve this I decided to re-write the extraction code and remove the usage of the MS DOM XML parser. Instead, I wrote my own XML parser methods in pure VFP code. This has the advantage of lower memory overhead. In doing this I restructured the cursors for holding the format information. They are actually now in line with the data structures in the styles.xml that is used by the workbook. This restructuring of code should also have the benefit of faster writing of workbooks as there are now considerably less SEEKs being performed to retrieve the cell formatting during the save workbook method.

Additionally, the methods that has color definition for cell fonts, fills, and borders changed to account for the property "indexed". From the documentation, "*ECMA-376, 4th Edition, Office Open XML Formats – Fundamentals and Markup Language Reference*", the "indexed" property is retained for backward compatibility. However, apparently Microsoft Excel will save color definitions with this property (I am testing with version 2010) so I am not sure how far backward compatibility it is. Anyway, the open methods now account for this color property. This necessitated the changing of some methods that impact color definitions.

This restructuring of code also necessitated the changes to the parameters of some of the methods. These include the following methods:

GetCellBorders()	Return object changed
GetCellFill()	Return object changed; previously was a single color value, now it is returned as an object with property values
GetCustomNumericFormat()	New parameter added; Workbook Id
SetCellFill()	New/changed parameters; Color now split by FgColor (foreground) and BgColor (background) values and added pattern type for fill
SetCellFillRange()	New/changed parameters; Color now split by FgColor (foreground) and BgColor (background) values

The following methods have been added:

SetDefaultBorder()	Allows user to set the default border to be used globally in the workbook.
SetDefaultFill()	Allows user to set the default cell fill to be used globally in the workbook.
SetDefaultFont()	Allows user to set the default cell font/size to be used globally in the workbook.
GetCellIndent()	Gets the cell indentation amount.
SetCellIndent()	Sets the cell indentation amount.
GetCellTextRotation()	Gets the cell text rotation amount.
SetCellTextRotation()	Sets the cell text rotation amount.
AddInLineFontObject()	Adds an in-line character definition to the base in-line font definition object.
CreateInLineFormatText()	Creates the base in-line font object for assigning a text string in a cell to have its characters to be individually formatted (works with method AddInLineFontObject()).
GetInLineFormatText()	Gets the in-line font definition for a cell text string.
SetCellInLineFormatText ()	Saves an in-line font definition for a text string in a cell.

Release 18

Release 18 is released to add new methods and fix bugs. Also, included in this release are improvements in speed for creating spreadsheets with cell formatting. I have also started the ground-work for maintaining all content in an existing spreadsheet such as images, external referenced spreadsheets, shapes, etc.; however, this feature is not yet ready for this release (I have elected to release this code without this in order for more users to gain benefit from other improvements).

The following properties have been added:

SaveCurrencyAsNumeric	Indicates whether to save a currency value as a currency value or as a numeric value. Boolean value (default is False). Feature request by Tony Federer.
-----------------------	--

The following methods have been added:

AddIndexColor()	Adds a new indexed color definition to a workbook
AddMruColor()	Adds a new MRU color definition to a workbook
CellFormatPainter()	Copies the formatting of a source cell to a range of cells. This is faster than formatting individually each cell.
GetCellNumberFormatText()	Returns the cell numeric format as a text string
GetNumberOfSheets()	Returns the number of sheets for the given workbook.
GetRowMaxColumn()	Returns the maximum row column for the given row

The following methods have been added for managing cell styles (see section on Cell Styles in the documentation):

AddStyleBorders()	Adds to a cell style the cell border definition
AddStyleFill()	Adds to a cell style the cell fill definition
AddStyleFont()	Adds to a cell style the cell font definition
AddStyleHorizAlignment()	Adds to a cell style the cell horizontal alignment definition
AddStyleVertAlignment()	Adds to a cell style the cell vertical alignment definition
AddStyleIndent()	Adds to a cell style the cell indent definition

AddStyleNumericFormat()	Adds to a cell style the cell numeric format definition
AddStyleTextRotation()	Adds to a cell style the cell text rotation definition
AddStyleWordWrap()	Adds to a cell style the cell wordwrap definition
CreateFormatStyle()	Creates a new formatting style definition to be applied to cells
GetCellStyle()	Returns the selected cell style definition Id
SetCellStyle()	Sets the selected cell style definition Id
SetCellStyleRange()	Sets a range of cells the cell style definition Id

The following events have been added:

OnShowErrorMessage()	Allows BINDEVENTS to be used to bind to the event in order to display a user an error message
OnShowStatusMessage()	Allows BINDEVENTS to be used to bind to the event in order to display a user progress message during open and save spreadsheet methods

The following enhancements have been added:

Speed improvements	The protected method GetNextId() has been changed for speed enhancements. Previously a call to this method would perform a SQL – Select on the passed cursor to determine the last used Id value; now these values are stored as properties and accessed via a ASCAN() call. The basis for this enhancement was from Tony Federer.
Cell limits checking	Methods that assign cell values or formatting now enforce row and column max limits
String limits checking	Character string limits for assigning to cell values and to header values are now enforced

Set currency value to cell	Value can be saved as a currency or as a numeric value (float) based on setting for property SaveCurrencyAsNumeric (default is currency)
Named Ranges	Named Ranges are now supported when opening an existing workbook
CELL_FORMAT_CURR_EURO_RED	New currency format for Euro with negative values in red
CELL_FORMAT_CURR_POUNDS_RED	New currency format for Pounds with negative values in red

The following bugs have been fixed:

Setting the cell format to the class defined `CELL_FORMAT_CURRENCY_RED` numeric format would not format the decimals correctly and set a period at the end of each value displayed. Corrected; this class defined format now restricts the number of decimal places to two. The internal numeric format code `CELL_FORMAT_CURRENCY_RED` has been changed to include parenthesis for negative amounts in addition to the red color.

When document properties were set these were being stored as text without conversion to XML format into the spreadsheet. Characters such as ‘&’ would cause an error in the spreadsheet due to invalid character in the XML value. These are now stored after conversion to XML format.

The method `SaveTableToWorkbook()` did not save the table records based on the current index set; this is now corrected to save the table records based on index order. This change was contributed by Tony Federer.

`SaveWorkbook()` method now includes a SET SAFETY OFF and restore of previous setting to prevent unwanted file prompts. This change was contributed by Tony Federer.

The protected method `GetXMLString()` now removes ASCII characters 0 through 31 except for 9 (TAB), 10 (LF) and 13 (CR). This change was contributed by Tony Federer.

Spreadsheets that had a very large number of columns was failing in the method `ColumnIndexToAscii()` due to the code logic. The logic is now changed to support the max column width allowed by specification.

How the cell numeric formatting was being saved has been changed to streamline the read of a cell formatting and the assigning of a cell formatting; earlier method introduced problems during reading of cell numeric formatting for existing workbooks.

When adding a Named Range for just a column or just a row, the code would incorrectly add a 0 reference for the row when only a column is referenced or when only a row is referenced; now fixed.

The following method parameter defaults have been changed:

SetCellFill() and
SetCellFillRange()

These methods previously required the tnBColor (background color) value to be specified; this is now defaulted to RGB(255,255,255) if not specified.

Release 19

Release 19 is released to fix bugs in two methods. I had added events for allowing progress to be displayed. In the methods SaveTableToWorkbook() and SaveGridToWorkbook() I had added these events with the first name of the event that I set; however, later I decided to change the name of the event and missed updating the name in these two events. The event names has been changed.

In changing the event names in these two methods, I have added a new tnMode value which is 3. The definition of this mode is as follows:

tnMode = 3; saving an xlsx file
tnStage = 0; start of write of data to cell values
tnStage = 1-n; indicates saving cell values
tnStage = -1; end of write of data

In the first call (tnStage=0), the total number of rows is also sent as a parameter.

Release 20

Release 20 is released to fix a typo bug pointed out by rkaye (on VFPx).

Release 21

Release 21 is released to fix the conversion of a string to an XML string and reverse. I ran into this bug this afternoon in some of my own work. In the protected method GetXMLString() I changed the method of converting a string to xml representation using a DOM processor; specifically

```
this.oXDOM = CREATEOBJECT('MSXML2.DOMDocument')
```

This is initialized in Init() method and if fails (MSXML not installed) then I revert to the older VFP code. Then I use createTextNode method to create the xml string. This works except again for embedded double-quotes which are retained and not converted to " which I would have expected to have been converted. I also changed to now explicitly change double-quotes and remove any ASCII character below 32 decimal (except for 9, 10, and 13) whether using the DOM or previous VFP code.

I also found a potential infinite loop in the GetStringXML() method. If the string had an embedded coded value of &#nnn; where nnn is greater than 255, then this method went into an infinite loop. I found a case where the nnn value was greater than 255. I have now changed this method to now skip the conversion of this coded value and continue processing. The DOM based method of converting correctly handles the conversion.

Release 22

Release 22 is released to fix read problems for international characters (or in general double-byte characters). I needed to translate the strings from UTF-8 representation to double-byte. This was brought to my attention by Lubos Kopečný where he was experiencing incorrect strings when reading an existing xlsx file. I believe I have this now corrected. Another fix in this conversion was for the use of higher ASCII characters such as the registration mark or copyright mark – these were not displaying correctly (had an extra character); with this fix these characters now also display correctly.