



VWAV2

A/V INPUT

VW / AUDI 16:9 NAVI+

Without TV Tuner

NAV TV (Europe) LTD



NAV TV (Europe) LTD

Distribution Centre
Unit 21B Vale Business Park
Llandow, Vale of Glamorgan
CF71 7PF

Telephone: + 44 (0)8445 783 783
Fax: + 44 (0)1446 77 22 47
technical@nav.tv

Disclaimer
NAV TV (Europe) Ltd is not liable for any incidental, consequential or indirect damages. In case of erratic behavior of the vehicle's electrical system please disconnect the NAV TV product and contact our technical support Team. NAV TV (Europe) Ltd does not assume liability for any diagnostic fees.

e11*72/245*95/54*3583*00
RoHS 2002/95/EC—2002/96/EC

LOCATION & REMOVAL

Installation is made at the front unit.

Please note that the removal of units may differ between models

To remove Head Unit, most units require VW/AUDI "removal keys"



INSTALLATION

Plug in the supplied VWAV2 18pin (AMP) plug into the black socket on the Head Unit, see fig 001 & 002 (2)

Insert your Video lead into the socket on the Interface, see fig 002 (3)

Insert your Audio leads to RED/BLACK cable sockets on the VWAV2 loom, see fig 002 (4)

Connect the RED cable to a suitable 12v+ ignition/ accessory supply then connect the BLACK to a suitable 12v- Ground

The A/V source can be viewed via the TV or AUX button on the unit **provided the source is switched on.**



fig 001



fig 002

OPERATING INSTRUCTIONS

The additional A/V source you have added can be viewed via the TV tuner menu and aux options.

