QueueMetrics <b/og>

QueueMetrics Configuration and Usage APIs

FEB 11, 2025

Share

API JSON report user agent

QueueMetrics Configuration and Usage APIs

QueueMetrics is a powerful call center monitoring and reporting software that provides detailed analytics for call centers. One of its key features is the JSON API, which allows developers to integrate QueueMetrics with other systems or build custom applications. This guide provides a comprehensive overview of how to work with the JSON API for QueueMetrics.

An API (Application Programming Interface) lets one software program request data or services from another software program. For example, when you use an app like

a weather app, the app uses an API to ask a weather service for the current weather data, then displays it for you.

JSON (JavaScript Object Notation) is a way to format data so that it's easy for both humans and computers to read. It's like sending a neatly written message that both you and the computer can understand. JSON is used to send data back and forth between systems in a clear and simple way.

Which functions does the QueueMetrics API perform?

QueueMetrics uses the JSON API request in order to:

- Read and update the system configuration - Configuration API e.g., exporting, creating, and updating agents, queues, DNIS, etc.
- Export the results of most analyses in a format that is immediately usable by other software. Reports API.
- Perform actions programmatically, like, for example, creating queues and agents. RealTime API.

Working with the API request

The easiest way to interact with the JSON interface is to do it from the command line using 'curl' or with dialplan. All QueueMetrics JSON calls require a valid login and password, that must be passed as an HTTP basic auth.

Sending Requests

Use tools like curl, or libraries in your programming language to send HTTP requests.

Example and explanation using curl:

```
curl -X POST \
     -H "Content-Type: application/json" \
     -u "username:password" \
     -d '{"agent": "Agent/1001", "queues": ["4001"]}' \
     https://your-queuemetrics-instance-url/jsonEditorApi.do/
```

- username and password will use the "robot" user credentials
- for agent use the agent code: Ex. "Agent/101"

Handling Responses

Responses are typically in JSON format.

Check the status field for success or error indicators

Example error response:

```
{
  "status": "ERR",
  "message": "Invalid authentication credentials."
}
```

Some Example of API request

Get List of Agents

```
curl --user robot:robot -i -H "Content-Type: application/json" \
     -X GET http://YourQueuemetrics/queuemetrics/agent/jsonEditorApi.do
```

Result of API:

```
user@machine:~$ curl  --user robot:robot -H "Content-Type: application/json" -X GET http://10.10.5.162:80/queuemetrics/agent/jsonEditorApi.do
[ {
  "nome_agente" : "agent/101",
  "group_name" : "",
  "real_name" : "",
  "current_terminal" : "",
  "vnc_url" : "",
  "payroll_code" : "",
  "supervised_by" : "0",
  "descr_agente" : "John Doe (101)",
  "xmpp_address" : "agent101@chatserver",
  "PK_ID" : "71",
  "group_icon" : "",
  "group_by" : "0",
  "chiave_agente" : "",
  "location" : "1",
  "loc_name" : "Main"
}, {
  "nome_agente" : "agent/102",
  "group_name" : "",
  "real_name" : "",
  "current_terminal" : "",
  "vnc_url" : "http://mike.boo.workstation/vnc",
  "payroll_code" : "",
  "supervised_by" : "0",
  "descr_agente" : "Mike Boo (102)",
  "xmpp_address" : "",
  "PK_ID" : "72",
  "group_icon" : "",
  "group_by" : "0",
  "chiave_agente" : "",
  "location" : "3",
  "loc_name" : "Other"
}, {
```

Create a Json file for a specific Agent

```
curl --user robot:robot -i \
     -H "Content-Type: application/json" \
```

```
-X GET http://YourQueuemetrics/queuemetrics/agent/71/jsonEditorApi.do
-o agent.json
```

Result of API request:

```
user@machine:~$ curl  --user robot:robot -H "Content-Type: application/json" -X GET http://[redacted]/queuemetrics/agent/71/jsonEditorApi.do -o agent71.json
  % Total    % Received % Xferd  Average Speed   Time    Time     Time  Current
                                 Dload  Upload   Total   Spent    Left  Speed
100  1065  100  1065    0     0  22991      0 --:--:-- --:--:-- --:--:-- 23152
user@machine:~$ cat agent71.json
{
  "aliases" : "",
  "auto_answer" : "0",
  "chiave_agente" : "",
  "current_terminal" : "",
  "default_server" : "",
  "delete_protection" : "0",
  "descr_agente" : "John Doe (101)",
  "external_reference" : "",
  "group_by" : "0",
  "group_by__DECODED" : "",
  "id_agente" : "71",
  "location" : "1",
  "location__DECODED" : "Main",
  "ltCodeAssociate" : [ [ "inbound", "00 All", "Main", "*" ], [ "inbound", "Sample Queue 300", "Main", "300" ], [ "inbound", "Sample Queue 301", "Main", "301" ] ],
  "nome_agente" : "agent/101",
  "nomedata_insert" : "demoadmin, 18/06/2007, 22:28",
  "nomedata_update" : "demoadmin, 28/09/2015, 12:58",
  "payroll_code" : "",
  "sip_login" : "",
  "sip_pwd" : "",
  "sip_realm" : "",
  "sip_uri" : "",
  "supervised_by" : "0",
  "supervised_by__DECODED" : "",
  "sys_dt_creazione" : "2007-06-18 22:28:20",
  "sys_dt_modifica" : "2015-09-28 12:58:18",
  "sys_optilock" : "25895",
  "sys_user_creazione" : "32",
  "sys_user_modifica" : "32",
  "update_protection" : "0",
  "vnc_url" : "",
  "xmpp_address" : "agent101@chatserver"
```

Create a new agent using a json file

After editing the JSON file with the new agent parameters and creating the new_agent.json file:

```
user@machine:~$ cat new_agent.json
{
  "aliases" : "",
  "auto_answer" : "0",
  "chiave_agente" : "",
  "current_terminal" : "",
  "default_server" : "",
  "delete_protection" : "0",
  "descr_agente" : "Test (105)",
  "external_reference" : "",
  "group_by" : "0",
  "group_by__DECODED" : "",
  "id_agente" : "71",
  "location" : "1",
  "location__DECODED" : "Main",
  "ltCodeAssociate" : [ [ "inbound", "00 All", "Main", "*" ], [ "inbound", "Sample Queue 300", "Main", "300" ], [ "inbound", "Sample Queue 301", "Main", "301" ] ],
  "nome_agente" : "agent/105",
  "nomedata_insert" : "demoadmin, 18/06/2007, 22:28",
  "nomedata_update" : "demoadmin, 28/09/2015, 12:58",
  "payroll_code" : "",
  "sip_login" : "",
  "sip_pwd" : "",
  "sip_realm" : "",
  "sip_uri" : "",
  "supervised_by" : "0",
  "supervised_by__DECODED" : "",
  "sys_dt_creazione" : "2007-06-18 22:28:20",
  "sys_dt_modifica" : "2015-09-28 12:58:18",
  "sys_optilock" : "25895",
  "sys_user_creazione" : "32",
  "sys_user_modifica" : "32",
  "update_protection" : "0",
  "vnc_url" : "",
  "xmpp_address" : "agent105@chatserver"
}
```

Using this API request will create the new agent:

```
curl --user robot:robot -i -H "Content-Type: application/json" \
     -X POST -d @new_agent.json \
     http://YourQueuemetrics/queuemetrics/agent/-/jsonEditorApi.do
```

Result of API request:

```
user@machine:~$ curl  --user robot:robot -i -H "Content-Type: application/json" -X POST -d @new_agent.json http://10.10.5.162:80/queuemetrics/agent/-/jsonEditorApi.do
HTTP/1.1 200
Server: nginx
Date: Tue, 11 Feb 2025 13:28:35 GMT
Content-Type: application/json;charset=UTF-8
Content-Length: 891
Connection: keep-alive
Keep-Alive: timeout=20
Set-Cookie: JSESSIONID=7768E12671357EA56A19B4697D964E80; Path=/queuemetrics; HttpOnly
X-Robots-Tag: noindex

{
  "aliases" : "",
  "auto_answer" : "0",
  "chiave_agente" : "",
  "current_terminal" : "",
  "default_server" : "",
  "delete_protection" : "0",
  "descr_agente" : "Test (105)",
  "external_reference" : "",
  "group_by" : "0",
  "group_by__DECODED" : "",
  "id_agente" : "85",
  "location" : "1",
  "location__DECODED" : "Main",
  "ltCodeAssociate" : [ ],
  "nome_agente" : "agent/105",
  "nomedata_insert" : "robot, 11/02/2025, 14:28",
  "nomedata_update" : "",
  "payroll_code" : "",
  "sip_login" : "",
  "sip_pwd" : "",
  "sip_realm" : "",
  "sip_uri" : "",
  "supervised_by" : "0",
  "supervised_by__DECODED" : "",
  "sys_dt_creazione" : "2025-02-11 14:28:35",
  "sys_dt_modifica" : "0000-00-00 00:00:00",
  "sys_optilock" : "77297",
  "sys_user_creazione" : "35",
  "sys_user_modifica" : "0",
  "update_protection" : "0",
  "vnc_url" : "",
  "xmpp_address" : "agent105@chatserver"
```

In our documentation you can find the other items that you can edit.

Retrieve data from datablock

```
curl --user robot:robot -i \
     -H "Content-Type: application/json" \
     -X GET \
     "http://YourQueuemetrics/queuemetrics/QmStats/jsonStatsApi.do?queues=5
```

Result of API request:

```
user@machine: $ curl --user robot:robot -i -H "Content-Type: application/json" -X GET "http://10.10.5.162:80/queuemetrics/QmStats/jsonStatsApi.do?queues=500&from=2025-02-01.00:00:00&t
o=2025-02-10.00:00:00&block=DetailsDO.CallsOkRaw"
HTTP/1.1 200
Server: nginx
Date: Tue, 11 Feb 2025 14:07:12 GMT
Content-Type: application/json;charset=UTF-8
Content-Length: 734
Connection: keep-alive
Keep-Alive: timeout=20
Set-Cookie: JSESSIONID=1ABADA1DBF29C379C621A1E6338B53B3; Path=/queuemetrics; HttpOnly
X-Robots-Tag: noindex

{
  "result" : [ [ "Status", "OK" ], [ "Description", "" ], [ "Time elapsed (ms)", 49 ], [ "QM Version", "24.11.4" ] ],
  "DetailsDO.CallsOkRaw" : [ [ "CALLOK_callid", "CALLOK_from", "CALLOK_tstEnd", "CALLOK_waitLen", "CALLOK_callLen", "CALLOK_reason", "CALLOK_agent", "CALLOK_transfer", "CALLOK_queue",
 "CALLOK_tstEnter", "CALLOK_attempts", "CALLOK_url", "CALLOK_server", "CALLOK_stints", "CALLOK_oPos", "CALLOK_dnis", "CALLOK_ivr", "CALLOK_stcode", "CALLOK_lastAtt", "CALLOK_haveAtt",
 "CALLOK_attAA", "CALLOK_bridged", "CALLOK_mohEvts", "CALLOK_mohDur", "CALLOK_ivrWait", "CALLOK_tstStart", "CALLOK_ivrTime", "CALLOK_calltag", "CALLOK_featuresnum", "CALLOK_variablesn
um", "CALLOK_events", "CALLOK_features", "CALLOK_variables" ] ]
```

Retrieve Realtime Live data

```
curl --user robot:robot -i \
     -H "Content-Type: application/json" \
     -X GET \
     "http://YourQueuemetrics/queuemetrics/QmRealtime/jsonStatsApi.do?queue
```

Result of API request:

```
user@machine:~$ curl  --user robot:robot -i -H "Content-Type: application/json" -X GET "http://10.10.5.162:80/queuemetrics/QmRealtime/jsonStatsApi.do?queues=999&block=RealtimeDO.RtAge
ntsRaw&block=RealtimeDO.RtCallsRaw"
HTTP/1.1 200
Server: nginx
Date: Tue, 11 Feb 2025 14:09:13 GMT
Content-Type: application/json;charset=UTF-8
Content-Length: 880
Connection: keep-alive
Keep-Alive: timeout=20
Set-Cookie: JSESSIONID=3879396898E4C2B03944D33622025E0D; Path=/queuemetrics; HttpOnly
X-Robots-Tag: noindex

{
  "result" : [ [ "Status", "OK" ], [ "Description", "" ], [ "Time elapsed (ms)", 58 ], [ "QM Version", "24.11.4" ] ],
  "RealtimeDO.RtCallsRaw" : [ [ "RT_queue", "RT_callId", "RT_entered", "RT_answered", "RT_status", "RT_agent", "RT_caller", "RT_attm_term", "RT_attm_time", "RT_attempts", "RT_url", "R
T_stcode", "RT_serverId", "RT_lastAtt", "RT_haveAtt", "RT_attAA", "RT_bridged", "RT_mohEvts", "RT_mohDur", "RT_mohSince", "RT_dnis", "RT_oPos", "RT_ivr", "RT_tstStart", "RT_ivrTime" ]
 ],
  "RealtimeDO.RtAgentsRaw" : [ [ "ACB_queue", "ACB_agent", "ACB_logon", "ACB_extension", "ACB_onPause", "ACB_curPauseCode", "ACB_curPauseTst", "ACB_pausetime", "ACB_pausesess", "ACB_o
bPauseList", "ACB_serverId", "ACB_lstCallQueue", "ACB_lstCallCaller", "ACB_lstCallTst", "ACB_lstCallivr", "ACB_lstCallWaitLen", "ACB_lstCallLen", "ACB_freeSincePauOrCallTst", "ACB_inC
urrStatusSinceTst" ] ]
```

Troubleshooting

Below are some common issues you might encounter.

Authentication Failures

Issue: Incorrect credentials

Example response:

```
user@machine:~$
user@machine:~$ curl  --user ot:robot -H "Content-Type: application/json" -X GET http://10.10.5.162:80/queuemetrics/agent/jsonEditorApi.do
User not found: 'ot'user@machine:~$
user@machine:~$ curl  --user robot:bot -H "Content-Type: application/json" -X GET http://10.10.5.162:80/queuemetrics/agent/jsonEditorApi.do
user@machine:~$
```

Solution

Check the –user parameter to ensure that it is enabled and the credentials are correct.

Missing Robot Key

Issue: The user does not have a robot key.

Example response:

```
user@machine:~$ curl  --user robot:robot -H "Content-Type: application/json" -X GET http://10.10.5.162:80/queuemetrics/agent/jsonEditorApi.do
The user must be holding the key ROBOT in order to access the report modeuser@machine:~$
```

Solution

Assign a robot key to the user.

More info about User keys here.

Incorrect Address or Port

Issue: The provided address or port is incorrect.

Example response:

```
user@machine:~$ curl  --user robot:robot -H "Content-Type: application/json" -X GET http://10.10.5.152:80/queuemetrics/agent/jsonEditorApi.do
<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
<html><head>
<title>404 Not Found</title>
</head><body>
<h1>Not Found</h1>
<p>The requested URL was not found on this server.</p>
</body></html>
```

Solution

Verify the address and/or port configuration.

Invalid Parameters

Issue: The queue name is used instead of the queue number.

Example response:

```
user@machine: $ curl --user robot:robot -i -H "Content-Type: application/json" -X GET "http://10.10.5.162:80/queuemetrics/QmStats/jsonStatsApi.do?queues=6nfrom=2000-01-01.00:00:00&to=
2022-01-01.00:00:00&block=DetailsDO.CallsOkRaw"
HTTP/1.1 200
Server: nginx
Date: Tue, 11 Feb 2025 13:19:36 GMT
Content-Type: application/json;charset=UTF-8
Content-Length: 4033
Connection: keep-alive
Keep-Alive: timeout=20
Set-Cookie: JSESSIONID=6E1C15424A4773583D5A600A5ED9297A; Path=/queuemetrics; HttpOnly
X-Robots-Tag: noindex

{
  "result" : [ [ "Status", "ERR" ], [ "Description", "-- Inner Exception --\nException: it.loway.tpf.common.exceptions.TechException\n\nStack trace:\nDate error: either date is invali
d (from: null to Sat Jan 01 00:00:00 CET 2022 - format: 'yyyy-MM-dd.HH:mm:ss')\n\tat it.loway.app.queuemetrics.autenticazione.preparaParametriReport.calculatePeriodoTemporale(preparaP
arametriReport.java:412)\n\tat it.loway.app.queuemetrics.autenticazione.preparaParametriReport.setPeriodoTemporale(preparaParametriReport.java:327)\n\tat it.loway.app.queuemetrics.aut
enticazione.preparaParametriReport.doRun(preparaParametriReport.java:100)\n\tat it.loway.tpf.transaction.servlets.ClassRunnerLite.runClass(ClassRunnerLite.java:56)\n\tat it.loway.tpf.
transaction.servlets.ClassRunnerLite.runClass(ClassRunnerLite.java:43)\n\tat it.loway.tpf.transaction.servlets.ClassRunnerLite.runClasses(ClassRunnerLite.java:37)\n\tat it.loway.app.q
ueuemetrics.xmlrpc.services.AnyService.runClasses(AnyService.java:100)\n\tat it.loway.app.queuemetrics.xmlrpc.services.QmStatsService.stats(QmStatsService.java:94)\n\tat it.loway.app.
queuemetrics.xmlrpc.services.QmStatsService.fromJson(QmStatsService.java:44)\n\tat it.loway.app.queuemetrics.xmlrpc.JsonStatsServer.doRun(JsonStatsServer.java:80)\n\tat it.loway.tpf.t
ransaction.servlets.LowayTransactionController.runVerb(LowayTransactionController.java:140)\n\tat it.loway.tpf.transaction.servlets.LowayTransactionController.processClassicSynchroniz
edRequest(LowayTransactionController.java:513)\n\tat it.loway.tpf.transaction.servlets.LowayTransactionController.serveRequest(LowayTransactionController.java:367)\n\tat it.loway.tpf.
transaction.servlets.LowayTransactionController.serveRequestWrapper(LowayTransactionController.java:262)\n\tat it.loway.tpf.transaction.servlets.LowayTransactionController.doGet(Loway
TransactionController.java:84)\n\tat javax.servlet.http.HttpServlet.service(HttpServlet.java:489)\n\tat javax.servlet.http.HttpServlet.service(HttpServlet.java:583)\n\tat org.apache.c
atalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:212)\n\tat org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:156)\n
\tat org.apache.tomcat.websocket.server.WsFilter.doFilter(WsFilter.java:51)\n\tat org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:181)\n\t
at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:156)\n\tat org.apache.catalina.core.StandardWrapperValve.invoke(StandardWrapperValve.java:168)\
n\tat org.apache.catalina.core.StandardContextValve.invoke(StandardContextValve.java:90)\n\tat org.apache.catalina.authenticator.AuthenticatorBase.invoke(AuthenticatorBase.java:483)\n
\tat org.apache.catalina.core.StandardHostValve.invoke(StandardHostValve.java:130)\n\tat org.apache.catalina.valves.ErrorReportValve.invoke(ErrorReportValve.java:93)\n\tat org.apache.
catalina.valves.AbstractAccessLogValve.invoke(AbstractAccessLogValve.java:679)\n\tat org.apache.catalina.core.StandardEngineValve.invoke(StandardEngineValve.java:74)\n\tat org.apache.
catalina.connector.CoyoteAdapter.service(CoyoteAdapter.java:346)\n\tat org.apache.coyote.http11.Http11Processor.service(Http11Processor.java:617)\n\tat org.apache.coyote.AbstractProce
ssorLight.process(AbstractProcessorLight.java:63)\n\tat org.apache.coyote.AbstractProtocol$ConnectionHandler.process(AbstractProtocol.java:934)\n\tat org.apache.tomcat.util.net.NioEnd
point$SocketProcessor.doRun(NioEndpoint.java:1698)\n\tat org.apache.tomcat.util.net.SocketProcessorBase.run(SocketProcessorBase.java:52)\n\tat org.apache.tomcat.util.threads.ThreadPoo
lExecutor.runWorker(ThreadPoolExecutor.java:1191)\n\tat org.apache.tomcat.util.threads.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:659)\n\tat org.apache.tomcat.util.threads.
TaskThread$WrappingRunnable.run(TaskThread.java:63)\n\tat java.lang.Thread.run(Thread.java:750)\n-- End Inner Exception --\n" ], [ "Time elapsed (ms)", 1 ], [ "QM Version", "24.11.4"
] ]
```

Solution

Check the parameters of the API request, to ensure they are correctly formatted.

Note that:

- Use the queue number instead of the queue name.
- If specifying multiple queues, use the `--data-urlencode` parameter.

Example

```
--data-urlencode "queues=500|501|502"
```

```
curl --user robot:robot -i \
     -H "Content-Type: application/json" \
     -X GET \
     "http://YourQueuemetrics/queuemetrics/QmStats/jsonStatsApi.do" \
     --data-urlencode "queues=500|501|502" \
     --data-urlencode "from=2000-01-01.00:00:00" \
     --data-urlencode "to=2022-01-01.00:00:00" \
     --data-urlencode "block=DetailsDO.CallsOkRaw"
```

No data in the replay

Issue: The url request is correct, but the replay doesn't show any data.
Example response:

```
user@machine: $ curl --user robot:robot -i -H "Content-Type: application/json" -X GET "http://10.10.5.162:80/queuemetrics/QmStats/jsonStatsApi.do?queues=600&from=2000-01-01.00:00:00&to=2022-01-01.00:00:00&block=DetailsDO.CallsOkRaw"
HTTP/1.1 200
Server: nginx
Date: Tue, 11 Feb 2025 13:20:55 GMT
Content-Type: application/json;charset=UTF-8
Content-Length: 734
Connection: keep-alive
Keep-Alive: timeout=20
Set-Cookie: JSESSIONID=900F84D046665FAD19D405A424E4F3C1; Path=/queuemetrics; HttpOnly
X-Robots-Tag: noindex

{
  "result" : [ [ "Status", "OK" ], [ "Description", "" ], [ "Time elapsed (ms)", 27 ], [ "QM Version", "24.11.4" ] ],
  "DetailsDO.CallsOkRaw" : [ [ "CALLOK_callid", "CALLOK_from", "CALLOK_tstEnd", "CALLOK_waitLen", "CALLOK_callLen", "CALLOK_reason", "CALLOK_agent", "CALLOK_transfer", "CALLOK_queue",
 "CALLOK_tstEnter", "CALLOK_attempts", "CALLOK_url", "CALLOK_server", "CALLOK_stints", "CALLOK_oPos", "CALLOK_dnis", "CALLOK_ivr", "CALLOK_stcode", "CALLOK_lastAtt", "CALLOK_haveAtt",
 "CALLOK_attAA", "CALLOK_bridged", "CALLOK_mohEvts", "CALLOK_mohDur", "CALLOK_ivrWait", "CALLOK_tstStart", "CALLOK_ivrTime", "CALLOK_calltag", "CALLOK_featuresnum", "CALLOK_variablesnum", "CALLOK_events", "CALLOK_features", "CALLOK_variables" ] ]
```

Solution

Make sure the date `from=2000-01-01...` and datablock parameters `block=Detail...` of the request are correct.

About QueueMetrics

QueueMetrics is a highly scalable monitoring software that lets you track agent productivity, payrolls, measure targets, conversion rates, queues/ACDs, IVRs, music-on-hold, generate outbound campaign statistics and monitor realtime processes with customizable wallboards.

You can measure all activities in your contact center with more than 200 different metrics and manage realtime processes with live alarms and full control on calls and extensions, including whisper, spy and barge modes.

QueueMetrics is available on premise or as a cloud hosted service, and it is compatible with FreePBX, Grandstream, Issabel, MiRTA, Enswitch, Yeastar S PBX, VitalPBX, FusionPBX and many other Asterisk- and Freeswitch-based systems. It also supports Microsoft Teams telephony.

For more technical information please refer to the User Manual.

Visit www.queuemetrics.com for a free 15-day full-featured trial.

BACK

Find a Tag

TAGS

AMO API ActiveDirectory Allison Smith Asterisk Asterisk PBX Asterisk tools AudioVault CCaaS CallCabinet Clojure CommCon Cronjob Debian Docker Elixir FreePBX FreePBX16 FreeSwitch FusionPBX Grandstream Graph API JSON LetsEncrypt MiRTA PBX Microsoft Teams Nginx OpenLDAP PBXact QA QAP QueueMetrics QueueMetrics agent page QueueMetrics-Live RPM SMPT Salesforce Slack UCM Ubuntu VitalPBX WebRTC WombatDialer Yeastar advanced agent agent configuration agent management agent page agents agents set up ami assisted manual outbound automation backup benefits caddy call back call center call center management call center monitoring call center remote monitoring call center software call management call resolution call tracking callcenter caller setting cloud cloud callcenter cloud pbx cloud solution configuration configuration support contact center contact centre contactcenter covid crm data database debug debugging tutorial dimensioning export report filtering firefox first steps gap gentoo homepage hosted solution how to create a report https icon installation installation guide integrated softphone integration ivr jmx jvm kiosk known numbers ldap live log4j login logs lost calls memo migration missed reloads missing monitoring music on hold music on hold tracking new release notification on premise outbound outbound campaign parking calls parking lot tracking paths tracking pause pause code payroll pbx pbx commands performance pjsip qloader qloaderd quality quality assessment queue queue configuration queue management queue stats analysis queue_log recall recall scheduling recordings remote working report rtc saas scheduled job security sending data to QueueMetrics setup sla smart tv smart working softphone sso survey system requirements task tcpdump transfers translation troubleshooting tutorial uniloader unitracker user user configuration user keys video tutorial vip callers visibility keys voip wallboard wallboardcache yum upgrade

Loway

Copyright ©Loway 2026 · all rights reserved · Terms of service · Privacy policy

All trademarks, service marks, trade names, product names and logos appearing on the site are the property of their respective owners, including in some instances Loway. Any rights not expressly granted herein are reserved.