

# Report Three: Software Validation

Corina Ciobanu      Iskander Orazbekov      Mir Sahin  
Paul Grigoras      Radu Baltean-Lugoian

December 11, 2011

## Abstract

**proTrade** is a tennis trading environment which delivers the information a trader requires to place bets. Betting functionality, linked to the user's bank account is also provided. Testing and validation are crucial in order to deliver a reliable and secure application and have been used extensively.

## Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
<b>2</b>	<b>Testing</b>	<b>3</b>
2.1	Unit Testing . . . . .	3
2.2	Acceptance Testing . . . . .	4
2.3	Regression Testing . . . . .	5
2.4	Integration Testing . . . . .	5
2.4.1	Betfair API . . . . .	5
2.4.2	SWT (?) . . . . .	6
2.4.3	SWTChart . . . . .	6
2.5	Continuous Integration . . . . .	6
2.6	Measuring Test Coverage . . . . .	7
2.7	Code Sanity Measures . . . . .	8

2.8	Logging . . . . .	8
2.9	Test Guided Design . . . . .	8
2.10	At which development stages did you use tests . . . . .	9
2.11	Which portions of your code base were tested in this manner . .	9
2.12	what bugs did testing reveal . . . . .	9
<b>3</b>	<b>General Validation</b>	<b>9</b>
3.1	User interface design validation . . . . .	9
3.1.1	Feedback experienced users . . . . .	10
3.1.2	Feedback unexperienced users . . . . .	10
3.2	Did you use lint or similar tools? . . . . .	10
3.3	Did you conduct a manual code inspection (not by the person who wrote the code)? . . . . .	11
3.4	Did you exert your software to stress testing? . . . . .	11
3.5	Did you test the GUIs of your software? . . . . .	11
<b>4</b>	<b>Managerial Documentation</b>	<b>11</b>

# 1 Introduction

Tennis trading is a steadily growing market on the Betfair Exchange, with more than 70% of bets being placed in-play. In order to maintain market liquidity, exchanges must attract customers for example, by supplying them with better tools. By providing more information and better visualization techniques such a tool can help the trader improve his understanding and predict the market evolution, which should (potentially) lead to an increased profit.

For tennis in particular, the information required to predict/understand the market evolution is the score, player statistics, potentially a live video feed of the match and, of course, the market data (evolution of betting odds). Ideally, this is desired for both historical and live matches.

At the moment, no application provides all this information. A number of solutions exist which allow visualization of historical market data, but they generally lack the more specific, tennis related data. For example in Fracsoft

() market data is not correlated with match data (scores, player statistics). BetAngel() provides some tennis related data and prediction, but relies on the user to input the score, by pushing buttons, which is not suited for the speed at which the market can move. Ideally all the information should be automatically provided.

**proTrade** means to fill this gap, by providing all the information, betting and prediction functionalities for both historical and live matches, in an entirely automated fashion.

Due to the ambitious nature of the project and the high risk associated with some user actions (e.g. placing bets with real money) in order to ensure reliability and stability testing and other validation methods have been used extensively.

## 2 Testing

Testing has been used throughout all stages of the project starting with iteration 4 and more extensively with the introduction of the Continuous Integration server in iteration 5.

As suggested in [1] we have used the tests to guide our design, based on the principle that if a project is well designed it should be easy to write meaningful tests for it.

**Unit testing** has been used to rapidly test small portions of code while **acceptance tests** have been used to test a system feature from front to back. **TDD tests** (tests written before features) are expected to fail when they are written and should pass once the feature has been completely implemented. Once it passes, a test is transferred to the regression suite. Naturally, a failing **regression test** indicates a break in previous functionality (regression).

### 2.1 Unit Testing

Because of the ease of use, unit testing has been adopted early on in the development process and it has been of great use in identifying bugs and ensuring correctness of the Match API which manages match data such as score and statistics.

Since tennis scoring rules are peculiar (for example points are counted 15, 30, 40, AD instead of just 1,2,3,4) and tests are particularly easy to write we adopted a TDD approach. For example a simple initial test was written to check the correct outcome of adding four consecutive points to one of the players. This should lead to him winning the game and the points score being reset. Furthermore

the other player's score should always be zero. The code for this is presented in 1.

```
1  @Test
2  public void fortyZeroWin () {
3      int expectedPoints [] = {15,30,40};
4      for (int i=0;i<3;i++){
5          score.addPlayerTwoPoint ();
6          assertGameScoreIs (0,0);
7          assertPointsScoreIs (0, expectedPoints [i]);
8      }
9      score.addPlayerTwoPoint ();
10     assertGameScoreIs (0,1);
11     assertPointsScoreIs (0,0);
12 }
```

Listing 1: Initial failing test for score. The initialisation of the score object is handled in an abstract super class which also provides `assertSetScoreIs()` and `assertGamesScoreIs()`.

Having first written the test and ensured it failed, we then proceeded to implementing the methods that would make it pass. We adopted this approach for the whole Match API and for the Prediction API (used to predict the evolution of a match based on current score and player statistics).

This approach helped us identify numerous bugs early on and guided us towards a better overall design of the APIs.

*\*\*e.g. a function for correctly setting a set score to a certain value was not initially provided, but since while writing the tests the need for such a function became obvious, it was included and tested\*\** *\*\* separate tests that measure progress from tests that catch regression \*\**

## 2.2 Acceptance Testing

Acceptance tests were designed separately and were meant to test a particular function of the system, starting from the front-end (e.g. finding a pushing a button on the UI) to the back-end (e.g. connecting to the Betfair API to authorize a login request).

For performance reasons these were ran separately from unit tests since the UI operations tend to be slow.

For example the test in 2 checks the login functionality: the user should fill in their Betfair account and password and click on the login button. The login attempt is checked against the Betfair API and a label is updated to indicate success or failure. Obviously, an attempt to login with the test account should result in a success message being displayed.

```

1      @Test
2      public void correctLoginSuccess() throws Exception {
3          SWTBotText username = bot.text("username");
4          username.setText(Main.getTestUsername());
5          SWTBotText password = bot.text("password");
6          password.setText(Main.getTestPassword());
7          loginButton.click();
8          SWTBotLabel success = bot.label(LoginShell.SUCCESS);
9          assertNotNull(success);
10     }

```

Listing 2: Initial failing test for the login window. The username and password for the test account are read and decrypted from a local config file by the Main class. Using the UI bot we then fill the data in on the login window and click the login button.

We have adopted a similar approach for all features.

However, due to limitations in the SWTBot API some features have proven impossible to test. For example we have not found a way to test the functions of a context menu (pop up) or a progress bar.

**\*\* new acceptance tests will not pass until the feature is implemented**

acceptance tests for completed features catch regressions and should always pass (might take longer to run)

once an acceptance test has passed, if it fails again that means a regression (the existing code has been broken)

SWTBot **\*\***

## 2.3 Regression Testing

## 2.4 Integration Testing

Integration testing is used to check how our code works with the code from outside the team, which we cannot change (provided by various libraries). These tests ensure the code we built on top of external APIs works as expected and quickly identify any configuration issues.

Since the project depends on a number of external service providers (in particular Betfair and SWTChart) integration tests are vital. This has been achieved by testing the abstractions we have built on top of these APIs and used by our project:

### **2.4.1 Betfair API**

The Betfair API is organised in three services: global, UK Exchange and AUS Exchange, each with a Web Service Description Language (WSDL) file. Our application only uses the first 2 services, accessed through Axis-generated Java classes, archived in generated.jar library.

Any connection to Betfair and use of the API is handled by classes in the `src.model.connection` package. Moreover, to ensure both services (Global and UK Exchange) only have one point of access, all the required functionality has been encapsulated in two classes - `BetfairExchangeHandler` and `BetfairConnectionHandler`. Hence, integration tests for these classes ensure the connection to the Betfair API works properly.

### **2.4.2 SWT (?)**

How does SWT work?...

Since our project is not very large, we have considered acceptance tests are good/strong enough to test integration with the SWT platform/library.

### **2.4.3 SWTChart**

How does SWTChart work?..

To ease our use of the SWTChart library and the ability/.. to add specific features required by our application, we have extended the `Chart` class of the SWTChart library. Hence, integration tests for this class ensure the library integrates smoothly into the entire application.

## **2.5 Continuous Integration**

Since the beginning of iteration 5 a continuous integration has been installed on a virtual machine provided by the Computing Support Group, which emulates a dual core, 1GB, 64bit machine. We have decided to use Hudson, which comes with a plugin for running UI tests. These are different than normal tests since they require a display and cannot run on a headless server, unless some in memory display mechanism is provided. There are two alternatives: `xvfb` and hudson's plugin. Since we initially assumed `xvfb` would be harder to setup Hudson provides easy integration with git. The CI server is set to poll the repository and, when changes are detected, checks out a fresh copy and runs our normal build script.




Figure 1: Build trend summary. Vast majority of builds are well under 10 minutes. Outlying values were caused by a network outage.

## 2.6 Measuring Test Coverage

Since we did not adopt a TDD approach from the very beginning, it was important to obtain an overview of the parts of the code that need to be tested. Starting with iteration 5 we have used Cobertura, an open source tool which provides neat test coverage reports for Java programs.

To facilitate report generation, a single ant task has been set up to compile the code with the debug info (vital for Cobertura to indicate line numbers and measure coverage), run all the tests (unit, acceptance, integration) and generate human readable reports which provide an indication of the current test coverage as well as branch coverage and complexity measures.

This data enabled us to identify lines which were not touched by tests. This is usually fixed by writing another test to cover the specific path, but it can also be the case that the functionality is actually never required, in which case it is completely removed. Again this illustrates how tests have been used to ensure a neat design/code etc.

Branch coverage indicates when tests do not cover particular cases and has proven useful with regards to particularly tricky conditionals.

Cobertura also generates cyclomatic complexity values for each class/package, measuring the number of independent paths through the control flow graph of the code. Since it has been shown that high values are usually an indication of error prone code[2] this measurement is used to check code sanity.




Figure 2: Coverage report generated by Cobertura indicates test coverage at package level, branch coverage and cyclomatic complexity.




Figure 3: Branch coverage indicates specific condition coverage.

## 2.7 Code Sanity Measures

We have used PMD to generate code sanity reports.

## 2.8 Logging

## 2.9 Test Guided Design

Refactoring





plish their work/wish/.. To the purpose of validating our user interface design, feedback has been collected from a number of different persons with or without experience in using trading applications.

### **3.1.1 Feedback experienced users**

Firstly, we have had constant feedback from our supervisor, who is familiar with the game of tennis and tennis betting and who understands the needs of a professional trader. He has guided us through the process and has pointed out a number of possible UI improvements along the way (such as positioning different components, displaying different data on the graph), which we have accomplished.

Secondly, we have had meetings with PhD students, who are themselves developing trading applications. They gave us valuable feedback regarding market information display and the best way to present it to a specialized user. Hence, our initial interface has been adapted to accommodate their suggestions (e.g. displaying some additional market statistics) - supported by our supervisor.

Finally, to collect feedback from other points of view as well, our supervisor arranged for us to meet the head of research of Betfair. He has approved(?) of our application's general interface and pointed out a few possible issues (such as synchronizing all the playback data), which are now fixed(?).

### **3.1.2 Feedback unexperienced users**

To test how easy it is for users to understand the information presented by our application and how "natural" to find the required functionalities, we have collected feedback from a few colleagues, without previous experience with tennis trading applications. (??? - what did they say?)

Overall, the interface of our application has been validated by the users, with some improvement suggestions which we have considered and implemented.

## **3.2 Did you use lint or similar tools?**

We used PMD and Cobertura report to check code "sanity".

### 3.3 Did you conduct a manual code inspection (not by the person who wrote the code)?

We also used a review mechanism in which, normally, code has been inspected by at least two team members.

### 3.4 Did you exert your software to stress testing?

No - should do.

### 3.5 Did you test the GUIs of your software?

Yes, as explained above we have test the UI through our acceptance tests. Also visual inspection by team members was used to ensure no layouts are messed up.

yeees

## 4 Managerial Documentation

to give a formal account of group management and group activities: Collaboration tools used (eg svn)

git, github Management policies (eg code change/validation policies) Management of knowledge transfer within the group

dropbox, google docs A table of the group meetings - including dates, format and which members attended A table of the hours spent per week on which tasks or activities by each member on the project The Log-Book

Evaluation Criteria for Report Three: the same as for Reports One and Two.

## References

- [1] Steeve Freeman, Nat Pryce, *Growing Object-Oriented Software, Guided by Tests*, Addison-Wesley 2010
- [2] Robert Chatley's course on Software Engineering Methods [http://en.wikipedia.org/wiki/Cyclomatic\\_complexity](http://en.wikipedia.org/wiki/Cyclomatic_complexity), Imperial College London

- [3] Jonathan Rasmusson, *The Agile Samurai*, Pragmatic Bookshelf, October 2010.
- [4] Jeff Langr and Tim Ottinger, *Agile in a Flash*, Pragmatic Bookshelf, January 2011.
- [5] Robert Chatley's course on Software Engineering Methods <http://www.doc.ic.ac.uk/~rbc/302/>, Imperial College London