

: C

1.							
1		T=0.2m	m	8.0	1-1		
2		0.4		33.60	1-2		
3		()		168.0	1-3	()	
4		6		16.8	1-4	6	
5			m	20.0	1-5		
6		l=0.2m	EA	24	1-6		
7	()	D16 Type-I	ton	0.007	1-7	() Type-I	
2.							
8		12.0T		1	-1	(L=30km) 12.0T	10.2t
9			EA	1	-2		
3. ()							
10	()	25-21-8		35	-1	() 25-21-080	
11		#6-100×100		168.0	-2	#6-100*100	
12		D16 (SD400)	ton	0.007	-3	(SD400)-	
13	.	30km	ton	77	-4	, / 30km	.

: C
: L , B , T , A , V , W , N

			()					
1 : NO.0~NO.2+2 (L=42.0m, B=4.0m, T=0.2m)								
1-1		T=0.2m	NO.0, NO.2+2	$L = B=4.0m \times 2 \text{ ()} =$	8.0	m	.	
1-2		0.4	NO.0~NO.2+2	$V = L=42.0m \times B=4.0m \times T=0.2m =$	33.60		.	
1-3		()	NO.0~NO.2+2	$A = L=42.0m \times B=4.0m =$	168.0		.	
1-4		6	NO.0~NO.2+2	$A = L=42.0m \times T=0.2m \times 2 \text{ ()} =$	16.8			
1-5			NO.0~NO.2+2	$L = (L=42.0m \div 8.0m) - 1) \times B=4.0m = 5 \times 4.0m =$	20.0	m		
1-6		l=0.2m	NO.0, NO.2+2	$N = (B=4.0m \div 0.3m - 1) \times 2 = 12EA \times 2 =$	24	EA	.	
1-7	()	D16 Type-I	NO.0, NO.2+2	$W = 0.00156t/m(D16) \times l=0.2m \times 24EA =$	0.007	ton		
1-8	()	25-21-8	NO.0~NO.2+2	$V = A=168.0 \times T=0.2m =$	33.60			
1-9		#6-100×100	NO.0~NO.2+2	$A = L=42.0m \times B=4.0m =$	168.0			
1-10		.	NO.0~NO.2+2	$W = V=33.60 \times 2.3t/ =$	77.28	ton		
()								
-1		12.0T	-	$0.4 + . 1 \text{ (30km) } =$	1			10.2t
-2			-	$1 1 =$	1	EA		
(. .)								
-1	()	25-21-8		$V = 33.60 \times (1 + 2\%) = 34.27 \rightarrow =$	35			
-2		#6-100×100		$A = 168.0 \text{ ()} =$	168.0			
-3		D16 (SD400)		$W = 0.007t \times (1 + 3\%) =$	0.007	ton		
-4	.	30km		$W = 77.28t \rightarrow =$	77	ton		.