



dsstruct

January 12, 2017

Abstract

Get the structure of a list of datasets This task is part of the daltools package

1 Instruments/Modes

Instrument	Mode
------------	------

2 Use

3 Description

Get the structure of a list of datasets

This task outputs a high level (syntax orientated) description of the given dataset. The syntax of the output is essentially the same as that expected by dsvalidate and dsverify.

The output has the form:

dataset i {dataset items_i }_i

where,

{dataset items_i } is a list of one or more of

{name_i } {attribute_i } {block_i }

where {block_i } has the form

block i {block items_i }_i

{block items_i } is a list of one or more of



`jattributei jarrayi jtablei`

where `jarrayi` has the form

`array j jarray itemsi i`

where `array` is a list of one or more or

`jattributei`

For example, if a dataset is created with the following code

```
#include <Dal.h>

int
main()
{
  DataSet* set = dataSetServer -> open( "test.dat", Dal::Create );
  Attribute* att = set -> addAttribute( "att1", "an attribute", "mm" );
  *att = 123;

  Table* tab = set -> addTable( "table1", 10, "a table" );
  Column* col = tab -> addColumn( "col1", Column::Int32, "a column" );
  att = col -> addAttribute( "TLMAX", "std attribute", "Nm" );
  *att = 1000;

  dataSetServer -> close( set );
}
```

i.e. creates a dataset with name "test.dat" containing a dataset attribute called att1, ...

then the command `dsstruct -set=test.dat` produces the following output:

```
dataset
<
name "test.dat"
attribute
<
name "ATT1"
type Int
value "123"
>
table
<
name "table1"
rows 10
column
<
name "col1"
type Int32
```



```
attribute
<
name "TLMAX"
type Int
value "1000"
>
>
>
>
```

If the output is redirected to the file check.ds (easily achieved e.g. use the command `dsstruct -set=test.dat > check.ds`)

then the command `dsverify -file=check.ds` or `dsvalidate -sets=test.dat -template=check.sc`

can be used to check the validity of the dataset test.dat.

4 Parameters

This section documents the parameters recognized by this task (if any).

Parameter	Mand	Type	Default	Constraints
sets	yes	StringList		

List of sets on which to run dsstruct

5 Errors

This section documents warnings and errors generated by this task (if any). Note that warnings and errors can also be generated in the SAS infrastructure libraries, in which case they would not be documented here. Refer to the index of all errors and warnings available in the HTML version of the SAS documentation.

6 Input Files

- 1.

7 Output Files

- 1.



8 Algorithm

9 Comments

-

10 Future developments

References