Sliding-window SR and CR configuration

Updated 9 November 2026. Recommendations are shared across each indicated mass range.

Massa [GeV]	Inviluppo 95% [GeV]	Finestra allineata [GeV]	SR effettiva [GeV]	Bin SR	CR scelte	Intervalli CR [GeV]	Pilota	Envelope raccomandato in SR
0.4	0.34023 - 0.43196	0.340 - 0.435	0.340 - 0.435	19	charmonium, omega_phi	2.800 - 4.000 U 0.650 - 1.155	sì	
0.5	0.41766 - 0.54369	0.415 - 0.545	0.415 - 0.545	26	charmonium, omega_phi	2.800 - 4.000 U 0.650 - 1.155	-	C2+L3 o C3+L3
0.6	0.49313 - 0.65505	0.490 - 0.660	0.490 - 0.650	32	charmonium, omega_phi	2.800 - 4.000 U 0.650 - 1.155	-	
1.2	0.95528 - 1.31680	0.955 - 1.320	1.155 - 1.320	33	charmonium, omega_phi	2.800 - 4.000 U 0.650 - 1.155	sì	
1.3	1.03360 - 1.42619	1.030 - 1.430	1.155 - 1.430	55	charmonium, omega_phi	2.800 - 4.000 U 0.650 - 1.155	-	
1.4	1.11221 - 1.53537	1.110 - 1.540	1.155 - 1.540	77	charmonium	2.800 - 4.000	-	
1.5	1.19111 - 1.64434	1.190 - 1.645	1.190 - 1.645	91	charmonium	2.800 - 4.000	sì	
1.6	1.27027 - 1.75312	1.270 - 1.755	1.270 - 1.755	97	charmonium	2.800 - 4.000	-	
1.7	1.34968 - 1.86172	1.345 - 1.865	1.345 - 1.865	104	charmonium	2.800 - 4.000	-	
1.8	1.42931 - 1.97016	1.425 - 1.975	1.425 - 1.975	110	charmonium	2.800 - 4.000	sì	
1.9	1.50915 - 2.07843	1.505 - 2.080	1.505 - 2.080	115	charmonium	2.800 - 4.000	-	
2.0	1.58918 - 2.18655	1.585 - 2.190	1.585 - 2.190	121	charmonium	2.800 - 4.000	-	
2.1	1.66940 - 2.29453	1.665 - 2.295	1.665 - 2.295	126	charmonium	2.800 - 4.000	sì	
2.2	1.74978 - 2.40237	1.745 - 2.405	1.745 - 2.405	132	charmonium	2.800 - 4.000	-	
2.3	1.83031 - 2.51009	1.830 - 2.515	1.830 - 2.515	137	charmonium	2.800 - 4.000	-	
2.4	1.91099 - 2.61768	1.910 - 2.620	1.910 - 2.620	142	charmonium	2.800 - 4.000	sì	
2.5	1.99179 - 2.72516	1.990 - 2.730	1.990 - 2.730	148	charmonium	2.800 - 4.000	-	
2.6	2.07271 - 2.83253	2.070 - 2.835	2.070 - 2.800	146	charmonium	2.800 - 4.000	-	
2.7	2.15374 - 2.93980	2.150 - 2.940	2.150 - 2.800	130	charmonium	2.800 - 4.000	sì	
4.1	3.29426 - 4.43322	3.290 - 4.435	4.000 - 4.435	87	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
4.2	3.37586 - 4.53943	3.375 - 4.540	4.000 - 4.540	108	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
4.3	3.45744 - 4.64560	3.455 - 4.650	4.000 - 4.650	130	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	sì	-
4.4	3.53901 - 4.75172	3.535 - 4.755	4.000 - 4.755	151	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
4.5	3.62055 - 4.85810	3.620 - 4.860	4.000 - 4.860	172	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
4.6	3.69968 - 4.96587	3.695 - 4.970	4.000 - 4.970	194	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	sì	-

(*) C4+L4 is adopted for the simultaneous SR+CR fits between phi and J/psi (1.2-2.7 GeV). With median expected signal injected and only CMS_eff_trigger_e fixed to its injected value of zero, 6400/6400 toys pass the existing two-branch validity criteria. 30/32 central bias estimates lie within +/-0.2; C4 at 1.9 GeV gives +0.203 and L4 at 2.6 GeV gives +0.214. Pointwise 95% bootstrap intervals retain finite-toy uncertainty. This is a diagnostic with known trigger efficiency. The nominal fits retain the measured trigger uncertainty and profile it. Coverage at 1.4 GeV with the trigger profiled is still being checked, so adoption of this envelope does not establish coverage.

Sliding-window SR and CR configuration

Updated 9 November 2026. Recommendations are shared across each indicated mass range.

Massa [GeV]	Inviluppo 95% [GeV]	Finestra allineata [GeV]	SR effettiva [GeV]	Bin SR	CR scelte	Intervalli CR [GeV]	Pilota	Envelope raccomandato in SR
4.7	3.77638 - 5.07361	3.775 - 5.075	4.000 - 5.075	215	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
4.8	3.85292 - 5.18135	3.850 - 5.185	4.000 - 5.185	237	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
4.9	3.92929 - 5.28907	3.925 - 5.290	4.000 - 5.290	258	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	sì	-
5.0	4.00550 - 5.39678	4.005 - 5.400	4.005 - 5.400	279	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
5.1	4.08155 - 5.50448	4.080 - 5.505	4.080 - 5.505	285	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
5.2	4.15743 - 5.61217	4.155 - 5.615	4.155 - 5.615	292	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	sì	-
5.3	4.23314 - 5.71985	4.230 - 5.720	4.230 - 5.720	298	charmonium, upsilon	2.800 - 4.000 U 9.095 - 10.505	-	-
5.4	4.30868 - 5.82751	4.305 - 5.830	4.305 - 5.830	305	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
5.5	4.38404 - 5.93517	4.380 - 5.940	4.380 - 5.940	312	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	sì	-
5.6	4.45923 - 6.04282	4.455 - 6.045	4.455 - 6.045	318	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
5.7	4.53424 - 6.15045	4.530 - 6.155	4.530 - 6.155	325	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
5.8	4.60906 - 6.25808	4.605 - 6.260	4.605 - 6.260	331	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	sì	-
5.9	4.68370 - 6.36570	4.680 - 6.370	4.680 - 6.370	338	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
6.0	4.75815 - 6.47331	4.755 - 6.475	4.755 - 6.475	344	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
6.1	4.83242 - 6.58091	4.830 - 6.585	4.830 - 6.585	351	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	sì	-
6.2	4.90649 - 6.68850	4.905 - 6.690	4.905 - 6.690	357	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
6.3	4.98036 - 6.79609	4.980 - 6.800	4.980 - 6.800	364	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
6.4	5.05404 - 6.90367	5.050 - 6.905	5.050 - 6.905	371	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	sì	-
6.5	5.12752 - 7.01124	5.125 - 7.015	5.125 - 7.015	378	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
6.6	5.20079 - 7.11880	5.200 - 7.120	5.200 - 7.120	384	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	-	-
6.7	5.27386 - 7.22636	5.270 - 7.230	5.270 - 7.230	392	upsilon, charmonium	9.095 - 10.505 U 2.800 - 4.000	sì	-
6.8	5.34672 - 7.33391	5.345 - 7.335	5.345 - 7.335	398	upsilon	9.095 - 10.505	-	-
6.9	5.41936 - 7.44145	5.415 - 7.445	5.415 - 7.445	406	upsilon	9.095 - 10.505	-	-
7.0	5.49180 - 7.54899	5.490 - 7.550	5.490 - 7.550	412	upsilon	9.095 - 10.505	sì	-
7.1	5.56401 - 7.65653	5.560 - 7.660	5.560 - 7.660	420	upsilon	9.095 - 10.505	-	-

(*) C4+L4 is adopted for the simultaneous SR+CR fits between phi and J/psi (1.2-2.7 GeV). With median expected signal injected and only CMS_eff_trigger_e fixed to its injected value of zero, 6400/6400 toys pass the existing two-branch validity criteria. 30/32 central bias estimates lie within +/-0.2; C4 at 1.9 GeV gives +0.203 and L4 at 2.6 GeV gives +0.214. Pointwise 95% bootstrap intervals retain finite-toy uncertainty. This is a diagnostic with known trigger efficiency. The nominal fits retain the measured trigger uncertainty and profile it. Coverage at 1.4 GeV with the trigger profiled is still being checked, so adoption of this envelope does not establish coverage.

Sliding-window SR and CR configuration

Updated 9 November 2026. Recommendations are shared across each indicated mass range.

Massa [GeV]	Inviluppo 95% [GeV]	Finestra allineata [GeV]	SR effettiva [GeV]	Bin SR	CR scelte	Intervalli CR [GeV]	Pilota	Envelope raccomandato in SR
7.2	5.63600 - 7.76405	5.635 - 7.765	5.635 - 7.765	426	upsilon	9.095 - 10.505	-	-
7.3	5.70777 - 7.87157	5.705 - 7.875	5.705 - 7.875	434	upsilon	9.095 - 10.505	sì	-
7.4	5.77480 - 7.97909	5.770 - 7.980	5.770 - 7.980	442	upsilon	9.095 - 10.505	-	-
7.5	5.84092 - 8.08671	5.840 - 8.090	5.840 - 8.090	450	upsilon	9.095 - 10.505	-	-
7.6	5.90654 - 8.19748	5.905 - 8.200	5.905 - 8.200	459	upsilon	9.095 - 10.505	sì	-
7.7	5.97165 - 8.30835	5.970 - 8.310	5.970 - 8.310	468	upsilon	9.095 - 10.505	-	-
7.8	6.03624 - 8.41932	6.035 - 8.420	6.035 - 8.420	477	upsilon	9.095 - 10.505	-	-
7.9	6.10029 - 8.53039	6.100 - 8.535	6.100 - 8.535	487	upsilon	9.095 - 10.505	sì	-
8.0	6.16379 - 8.64158	6.160 - 8.645	6.160 - 8.645	497	upsilon	9.095 - 10.505	sì	-
8.1	6.22674 - 8.75286	6.225 - 8.755	6.225 - 8.755	506	upsilon	9.095 - 10.505	-	-
8.2	6.28911 - 8.86426	6.285 - 8.865	6.285 - 8.865	516	upsilon	9.095 - 10.505	sì	-
8.3	6.35088 - 8.97576	6.350 - 8.980	6.350 - 8.980	526	upsilon	9.095 - 10.505	-	-
8.4	6.41206 - 9.08737	6.410 - 9.090	6.410 - 9.090	536	upsilon	9.095 - 10.505	-	-
8.5	6.47261 - 9.19910	6.470 - 9.200	6.470 - 9.095	525	upsilon	9.095 - 10.505	sì	-
8.6	6.53253 - 9.31093	6.530 - 9.315	6.530 - 9.095	513	upsilon	9.095 - 10.505	-	-
8.7	6.59180 - 9.42288	6.590 - 9.425	6.590 - 9.095	501	upsilon	9.095 - 10.505	-	-
8.8	6.65040 - 9.53495	6.650 - 9.535	6.650 - 9.095	489	upsilon	9.095 - 10.505	sì	-
8.9	6.70831 - 9.64713	6.705 - 9.650	6.705 - 9.095	478	upsilon	9.095 - 10.505	-	-
9.0	6.76552 - 9.75943	6.765 - 9.760	6.765 - 9.095	466	upsilon	9.095 - 10.505	sì	-

(*) C4+L4 is adopted for the simultaneous SR+CR fits between phi and J/psi (1.2-2.7 GeV). With median expected signal injected and only CMS_eff_trigger_e fixed to its injected value of zero, 6400/6400 toys pass the existing two-branch validity criteria. 30/32 central bias estimates lie within +/-0.2; C4 at 1.9 GeV gives +0.203 and L4 at 2.6 GeV gives +0.214. Pointwise 95% bootstrap intervals retain finite-toy uncertainty. This is a diagnostic with known trigger efficiency. The nominal fits retain the measured trigger uncertainty and profile it. Coverage at 1.4 GeV with the trigger profiled is still being checked, so adoption of this envelope does not establish coverage.