MTAOS handling of rejected commands

This notebook is used for the level 3 integration tests from test plan LVV-P81 (https://jira.lsstcorp.org/secure/Tests.jspa#/testPlan/LVV-P81) as part of test cylce LVV-C176 (https://jira.lsstcorp.org/secure/Tests.jspa#/testCycle/LVV-C176). The following tests are currently run as part of this notebook:

- LVV-T2193 (https://jira.lsstcorp.org/secure/Tests.jspa#/testCase/LVV-T2193)

Execution steps are separated by horizontal lines. Upon completion, save the notebook and its output as a pdf file to be attached to the test execution in JIRA.

Last updated by E. Dennihy 20211020

Load all the needed libraries. Get the remotes ready Code in the notebook including section: "Check the summary state of each CSC".

```
In [1]:  %load_ext autoreload
         %autoreload 2
```

```
In [2]:  import rubin_jupyter_utils.lab.notebook as nb
         nb.utils.get_node()
```

```
/tmp/ipykernel_39099/1665379685.py:2: DeprecationWarning: Call to deprecate
d function (or staticmethod) get_node. (Please use lsst.rsp.get_node())
  nb.utils.get_node()
```
```
Out[2]:  'yagan03'
```

```
In [3]:  import os
         import sys
         import asyncio
         import logging

         import pandas as pd
         import numpy as np

         from matplotlib import pyplot as plt

         from lsst.ts import salobj
         from lsst.ts.observatory.control.maintel import MTCS, ComCam
         from lsst.ts.observatory.control import RotType
```
```
lsst.ts.utils.tai INFO: Update leap second table
lsst.ts.utils.tai INFO: current_tai uses the system TAI clock
```

```
In [4]:  logging.basicConfig(format="%(name)s:%(message)s", level=logging.DEBUG)
```

In [5]:
```python
log = logging.getLogger("setup")
log.level = logging.DEBUG
```

In [6]:
```python
domain = salobj.Domain()
```

In [7]:
```python
mtcs = MTCS(domain=domain, log=log)
mtcs.set_rem_loglevel(40)
```

```
setup.MTCS DEBUG: mtmount: Adding all resources.
setup.MTCS DEBUG: mtptg: Adding all resources.
setup.MTCS DEBUG: mtaos: Adding all resources.
setup.MTCS DEBUG: mtm1m3: Adding all resources.
setup.MTCS DEBUG: mtm2: Adding all resources.
setup.MTCS DEBUG: mthexapod_1: Adding all resources.
setup.MTCS DEBUG: mthexapod_2: Adding all resources.
setup.MTCS DEBUG: mtrotator: Adding all resources.
setup.MTCS DEBUG: mtdome: Adding all resources.
setup.MTCS DEBUG: mtdometrajectory: Adding all resources.
```

In [8]:
```python
await mtcs.start_task
```

```
MTHexapod INFO: Read historical data in 0.07 sec
MTHexapod INFO: Read historical data in 0.08 sec
```
Out[8]:
```
[None, None, None, None, None, None, None, None, None, None]
```

```
MTHexapod.electrical WARNING: tel_electrical DDS read queue is filling:
16 of 100 elements
```

Ready M1M3: Raise mirror, turn on FB, clear forces

Need to have M1M3 LUT use its inclinometer.

Ready M2: Turn on FB, clear forces

Need to have M2 LUT use its inclinometer

Get camera hexapod ready: check config; make sure LUT is on, and has valid inputs; make sure hex is at LUT position

---

Get M2 hexapod ready: check config; make sure LUT is on, and has valid inputs; make sure hex is at LUT position

Slew to the next target. Choose a target such that the rotator stays within a couple of degrees of its initial position. This is because the CCW is not running (MTmount in simulation mode).

In [9]:
```
target = await mtcs.find_target(el=60, az=120, mag_limit=8)
print(target)
```

WARNING: AstropyDeprecationWarning: Transforming a frame instance to a frame class (as opposed to another frame instance) will not be supported in the future. Either explicitly instantiate the target frame, or first convert the source frame instance to a `astropy.coordinates.SkyCoord` and use its `transform_to()` method. [astropy.coordinates.baseframe]
astroquery WARNING: AstropyDeprecationWarning: Transforming a frame instance to a frame class (as opposed to another frame instance) will not be supported in the future. Either explicitly instantiate the target frame, or first convert the source frame instance to a `astropy.coordinates.SkyCoord` and use its `transform_to()` method.
MTHexapod.application WARNING: tel_application DDS read queue is filling: 16 of 100 elements
MTHexapod.actuators WARNING: tel_actuators DDS read queue is filling: 30 of 100 elements
MTHexapod.actuators WARNING: tel_actuators DDS read queue is filling: 14 of 100 elements
HD 48728

In [10]:
```
await mtcs.slew_object(target, rot_type=RotType.PhysicalSky, rot=1.9)
```

setup.MTCS INFO: Slewing to HD 48728: 06 42 49.7585 -40 51 19.553
setup.MTCS DEBUG: Setting rotator physical position to 1.9 deg. Rotator will track sky.
setup.MTCS DEBUG: Wait 5.0s for rotator to settle down.
setup.MTCS DEBUG: Workaround for rotator trajectory problem. Moving rotator to its current position: 1.64
setup.MTCS DEBUG: Wait for MTRotator in position event.
setup.MTCS DEBUG: MTRotator in position: True.
setup.MTCS DEBUG: MTRotator already in position. Handling potential race condition.
setup.MTCS INFO: MTRotator in position: False.
setup.MTCS INFO: MTRotator in position: True.
setup.MTCS DEBUG: MTRotator in position True. Waiting settle time 5.0s
setup.MTCS DEBUG: Sending slew command.
setup.MTCS DEBUG: Scheduling check coroutines
setup.MTCS DEBUG: process as completed...
setup.MTCS DEBUG: Monitor position started.
setup.MTCS DEBUG: Waiting for Target event from mtmount.
setup.MTCS DEBUG: mtmount: <State.ENABLED: 2>
setup.MTCS DEBUG: mtptg: <State.ENABLED: 2>
setup.MTCS DEBUG: mtaos: <State.ENABLED: 2>
setup.MTCS DEBUG: mtm1m3: <State.ENABLED: 2>
setup.MTCS DEBUG: mtm2: <State.ENABLED: 2>

```
setup.MTCS DEBUG: mthexapod_1: <State.ENABLED: 2>
setup.MTCS DEBUG: mthexapod_2: <State.ENABLED: 2>
setup.MTCS DEBUG: mtrotator: <State.ENABLED: 2>
setup.MTCS DEBUG: mtdome: <State.ENABLED: 2>
setup.MTCS DEBUG: mtdometrajectory: <State.ENABLED: 2>
setup.MTCS DEBUG: Wait for mtmount in position events.
setup.MTCS DEBUG: Wait for dome in position event.
setup.MTCS DEBUG: Wait for MTRotator in position event.
setup.MTCS DEBUG: MTRotator in position: True.
setup.MTCS DEBUG: MTRotator already in position. Handling potential race
condition.
setup.MTCS DEBUG: Wait for MTMount elevation in position event.
setup.MTCS DEBUG: MTMount elevation in position: True.
setup.MTCS DEBUG: MTMount elevation already in position. Handling potent
ial race condition.
setup.MTCS DEBUG: Wait for MTMount azimuth in position event.
setup.MTCS DEBUG: MTMount azimuth in position: True.
setup.MTCS DEBUG: MTMount azimuth already in position. Handling potentia
l race condition.
setup.MTCS DEBUG: Mount target: private_revCode: bdcb00ba, private_sndSt
amp: 1654014823.3561058, private_rcvStamp: 1654014823.3564584, private_s
eqNum: 19828, private_identity: MTMount, private_origin: 28805, elevatio
n: 60.45201677471103, elevationVelocity: 0.0031088342953463277, azimuth:
120.50702340074912, azimuthVelocity: 0.0011268561580526151, taiTime: 165
4014823.4151304, trackId: 1, tracksys: SIDEREAL, radesys: ICRS, priorit
y: 0
setup.MTCS INFO: MTMount elevation in position: False.
setup.MTCS INFO: MTMount azimuth in position: False.
setup.MTCS INFO: MTMount elevation in position: True.
setup.MTCS DEBUG: MTMount elevation in position True. Waiting settle tim
e 3.0s
setup.MTCS DEBUG: [Tel]: Az = +119.899[  +0.6]; El = +060.407[  +0.0] [R
ot]: +001.636[  -0.0] [Dome] Az = +000.000; El = +000.000
setup.MTCS DEBUG: Dome azimuth in position.
setup.MTCS DEBUG: Dome elevation in position.
setup.MTCS INFO: MTRotator in position: False.
setup.MTCS INFO: MTRotator in position: True.
setup.MTCS DEBUG: MTRotator in position True. Waiting settle time 3.0s
setup.MTCS INFO: MTMount azimuth in position: True.
setup.MTCS DEBUG: MTMount azimuth in position True. Waiting settle time
3.0s
```

clear all corrections using cmd_resetCorrection

```
In [11]:   await mtcs.rem.mtaos.cmd_resetCorrection.start()

Out[11]:   <ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc420f4ccd0>

In [12]:   await mtcs.rem.mtaos.cmd_issueCorrection.start(timeout=60.)
```

Out[12]: `<ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc4107597c0>`

Add 1um of z7 to the system via OFC, issue the corrections.

Compare the corrections sent vs forces and position changes applied. This is currently done in a separate notebook or on Chronograf.

In [13]:
```python
wavefront_errors = np.zeros(19)
```

In [14]:
```python
wavefront_errors[3]=1.0
```

In [15]:
```python
await mtcs.rem.mtaos.cmd_addAberration.set_start(wf=wavefront_errors, timeou
```

Out[15]: `<ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc4107592e0>`

In [16]:
```python
await mtcs.rem.mtaos.cmd_issueCorrection.start(timeout=60.)
```

Out[16]: `<ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc420c6f400>`

Make plots using telemetry from each component to verify the changes in the DOFs. This step does not currently involve running any commands in this notebook. This step must be verified using a separate noteboook.

Put M2 hexapod in DISABLED state (so that we can test command rejection).

In [17]:
```python
await mtcs.set_state(salobj.State.DISABLED, components=["mthexapod_2"])
```
```
setup.MTCS DEBUG: [mthexapod_2]::[<State.ENABLED: 2>, <State.DISABLED: 1
>]
setup.MTCS INFO: All components in <State.DISABLED: 1>.
```

Add 1um of z7 to the system via OFC. Expect m2 hexapod corrections are rejected, and all other corrections applied, then undone.

In [18]:
```python
await mtcs.rem.mtaos.cmd_addAberration.set_start(wf=wavefront_errors, timeou
```

Out[18]: `<ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc40fee6ca0>`

In [19]:
```python
await mtcs.rem.mtaos.cmd_issueCorrection.start(timeout=60.)
```

```
       —————————————————————————————————————————————————————————————————————
       AckError                                        Traceback (most recent call last)
       Input In [19], in <cell line: 1>()
       ----> 1 await mtcs.rem.mtaos.cmd_issueCorrection.start(timeout=60.)

       File /opt/lsst/software/stack/conda/miniconda3-py38_4.9.2/envs/lsst-scipipe
       -3.0.0/lib/python3.8/site-packages/lsst/ts/salobj/topics/remote_command.py:
       485, in RemoteCommand.start(self, data, timeout, wait_done)
           481 cmd_info = CommandInfo(
           482     remote_command=self, seq_num=seq_num, wait_done=wait_done
           483 )
           484 self.salinfo._running_cmds[seq_num] = cmd_info
       --> 485 return await cmd_info.next_ackcmd(timeout=timeout)

       File /opt/lsst/software/stack/conda/miniconda3-py38_4.9.2/envs/lsst-scipipe
       -3.0.0/lib/python3.8/site-packages/lsst/ts/salobj/topics/remote_command.py:
       195, in CommandInfo.next_ackcmd(self, timeout)
           193     ackcmd = await self._wait_task
           194     if ackcmd.ack in self.failed_ack_codes:
       --> 195         raise base.AckError(msg="Command failed", ackcmd=ackcmd)
           196     return ackcmd
           197 except asyncio.TimeoutError:

       AckError: msg='Command failed', ackcmd=(ackcmd private_seqNum=743583437, ac
       k=<SalRetCode.CMD_FAILED: -302>, error=1, result="Failed: Failed to apply c
       orrection to: ['m2hex']. ")
       MTHexapod.electrical WARNING: tel_electrical DDS read queue is filling:
       11 of 100 elements
       MTHexapod.application WARNING: tel_application DDS read queue is fillin
       g: 11 of 100 elements
```

Re-enable M2 hexapod Make it ready for AOS

In [20]:
```
await mtcs.set_state(salobj.State.ENABLED, components=["mthexapod_2"])
```
```
setup.MTCS DEBUG: [mthexapod_2]::[<State.DISABLED: 1>, <State.ENABLED: 2
>]
setup.MTCS INFO: All components in <State.ENABLED: 2>.
```

Re-issue the correction.

In [21]:
```
await mtcs.rem.mtaos.cmd_addAberration.set_start(wf=wavefront_errors, timeou
```
Out[21]:
```
<ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc42966ab50>
```

In [22]:
```
await mtcs.rem.mtaos.cmd_issueCorrection.start(timeout=60.)
```
Out[22]:
```
<ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc4909d7d90>
```

Reject the latest corrections.

```
In [23]: await mtcs.rem.mtaos.cmd_rejectCorrection.start()
```

```
Out[23]: <ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc4292f6730>
```

```
In [24]: await mtcs.rem.mtaos.cmd_issueCorrection.start(timeout=60.)
```

```
Out[24]: <ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc42979c670>
```

Add 2um of z7 via OFC

```
In [25]: wavefront_errors[3] = 2.0
```

```
In [26]: wavefront_errors
```

```
Out[26]: array([0., 0., 0., 2., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0., 0.,
                0., 0.])
```

```
In [27]: await mtcs.rem.mtaos.cmd_addAberration.set_start(wf=wavefront_errors, timeou
```

```
Out[27]: <ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc410710c70>
```

```
In [28]: await mtcs.rem.mtaos.cmd_issueCorrection.start(timeout=60.)
```

```
Out[28]: <ddsutil.MTAOS_ackcmd_fd03e870 at 0x7fc42966a7c0>
```

Stop Tracking

```
In [29]: await mtcs.stop_tracking()
```

```
setup.MTCS DEBUG: Stop tracking.
```

Wrap up. Put each component to the following states: mtaos --> standby m1m3 -->
standby m2 --> standby camera hex --> standby m2 hex --> standby

```
In [ ]: await mtcs.set_state(salobj.State.STANDBY, components=["mtaos"])
```

```
In [ ]: await mtcs.lower_m1m3()
```

```
In [ ]: await mtcs.set_state(salobj.State.STANDBY, components=["mtm1m3"])
```

```
In [ ]: await mtcs.set_state(salobj.State.STANDBY, components=["mtm2"])
```

```
In [ ]: await mtcs.set_state(salobj.State.STANDBY, components=["mthexapod_1"])
```

```
In [ ]: await mtcs.set_state(salobj.State.STANDBY, components=["mthexapod_2"])
```

```
In [ ]:  await mtcs.standby()
```

```
In [ ]:
```