



Node Monitor User Guide

Release 6.x

Contents

1	Prefa						
	1.1	About the Vortex OpenSplice Node Monitor User Guide					
	1.2	Conventions					
2	Intro	oduction 2					
	2.1	Supported Platforms					
3	Start	ing and Stopping Node Monitor 3					
	3.1	Linux					
	3.2	Windows					
4	Conf	iguring Node Monitor					
	4.1	Setting up the configuration file					
	4.2	Default configuration file (application.conf)4					
5	Data	Data Available through Node Monitor					
	5.1	CPU Information					
	5.2	Operating System Information					
	5.3	Network Information					
	5.4	Network Interface Information					
	5.5	Process Information					
	5.6	Network Interface Statistics					
	5.7	Memory Statistics					
	5.8	CPU statistics					
	5.9	Process Memory Statistics:					
	5.10	Process CPU Statistics					
6	Refe	ces 9					
7	Cont	Contacts & Notices					
	7.1	Contacts					
	7.2	Notices 10					

Preface

1.1 About the Vortex OpenSplice Node Monitor User Guide

The *Vortex OpenSplice Node Monitor User Guide* provides the information needed by anyone who wants to monitor the statistics about the performance of a system.

This Guide contains:

- a list of supported platforms
- instructions for starting and stopping the Node Monitor
- descriptions of the Node Monitor configuration options
- a categorized list of the types of data that can be accessed with the Node Monitor

1.2 Conventions

The icons shown below are used in the Vortex product documentation to help readers to quickly identify information relevant to their specific use of OpenSplice.

Icon	Meaning
\triangle	Item of special significance or where caution needs to be taken.
i	Item contains helpful hint or special information.
Windows	Information applies to Windows (e.g. XP, 2003, Windows 7) only.
Unix	Information applies to Unix-based systems (e.g. Solaris) only.
Linux	Information applies to Linux-based systems (e.g. Ubuntu) only.
С	C language specific.
C ++	C++ language specific.
C#	C# language specific.
Java	Java language specific.

Introduction

Node Monitor is a Vortex OpenSplice application implemented in the Java language which is installed as part of Vortex OpenSplice.

It is possible to use Node Monitor on platforms where both Vortex OpenSplice and the *Sigar API* can be installed. See Supported Platforms below for detailed information.

Node Monitor publishes the following system-monitoring data into the OpenSplice backbone:

- CPU information and statistics
- · Memory statistics
- · Network interface information and statistics
- Operating System information
- Process information and statistics

Refer to Data Available through Node Monitor for complete list of data that can be obtained from Node Monitor.

2.1 Supported Platforms

- x86 / Linux kernel 2.6 and up (32/64-bit)
- x86 / Microsoft Windows 2003 Server/XP/7 (32/64-bit)

Starting and Stopping Node Monitor

The Vortex OpenSplice environment must be set up correctly before starting the Node Monitor. Please refer to the *Vortex OpenSplice Getting Started Guide* for detailed information about how to install and configure Vortex OpenSplice.

3.1 Linux

Source the release.com file from the shell command line to set up the Vortex OpenSplice environment.

To start Node Monitor, enter the following command in the shell:



> ./nodemon

3.2 Windows

To start Node Monitor, open an Vortex OpenSplice Command Prompt and enter the following command:



> nodemon.bat

Configuring Node Monitor

4.1 Setting up the configuration file

It is possible to control the frequency of the information and metrics that are pushed to the Vortex OpenSplice backbone. Setting the interval to -1 for a specific category will disable the push of monitoring data for that category.

To override the default configuration, create your own application.conf file in the same directory where you start the Node Monitor.

4.1.1 Configuration parameters

domain	Domain ID of the OpenSplice system.		
partition	Partition name to which monitoring data will be published. Default is NODE_INFO. Do		
	not change this when using with Vortex Insight!		
historyDepth	History depth for HistoryQosPolicy1 to keep all history.		
cpuInfo	CPU information interval in milliseconds1 to disable.		
cpuStats	CPU statistics interval in milliseconds1 to disable.		
memStats	Memory statistics interval in milliseconds1 to disable.		
netInfo	Memory statistics interval in milliseconds. −1 to disable.		
netInterfaceI	Network interface information interval in milliseconds. −1 to disable.		
netInterfaceSt	Nestwork interface statistics interval in milliseconds1 to disable.		
operatingSyste	PrOperating system information interval in milliseconds1 to disable.		
processInfo	Process information interval in milliseconds1 to disable.		
processCPUStat	Process CPU statistics interval in milliseconds. −1 to disable.		
processMemory	StPatocess memory statistics interval in milliseconds1 to disable.		

4.2 Default configuration file (application.conf)

```
# define default scope variables to be used for setting the value of
other parameters.
default {
  domain = 0
  partition = NODE_INFO
  historyDepth = 10
  interval {
    information = 60000
    statistics = 2000
  }
}

opensplice {
  hm {
    nodeinfoservice{
```

```
domain = ${default.domain}
   partition = ${default.partition}
   historyDepth = ${default.historyDepth}
   interval {
     cpuInfo = ${default.interval.information}
     cpuStats = ${default.interval.statistics}
     memStats = ${default.interval.statistics}
     netInfo = ${default.interval.information}
     netInterfaceInfo = ${default.interval.information}
     netInterfaceStats = ${default.interval.statistics}
     operatingSystemInfo = ${default.interval.information}
     processCPUStats = ${default.interval.statistics}
     processInfo = ${default.interval.information}
     processMemoryStats = ${default.interval.statistics}
 }
}
```

Data Available through Node Monitor

5.1 CPU Information

- Vendor
- · CPU Model
- CPU Frequency
- · Cache size
- Number of cores on the CPU

5.2 Operating System Information

- OS name
- Distribution name (e.g. Ubuntu 12.04)
- Architecture of the OS
- Linux kernel image version
- · Vendor and vendor version
- Data model (32/64 bit etc.)
- Endianness

5.3 Network Information

- · Primary interface primary address primary MAC address and primary netmask
- Domain name
- Default gateway default gateway interface
- Primary DNS and secondary DNS

5.4 Network Interface Information

- Interface name
- Interface type (e.g. Ethernet Loopback)
- MAC address
- Destination

- · Broadcast
- Netmask
- MTU

5.5 Process Information

- Process ID
- Name
- · Current working directory
- Priority
- Number of threads in the process
- OSPL environment variables (e.g. OSPL_URI, OSPL_HOME, etc.)

5.6 Network Interface Statistics

- RX values: bytes packets errors dropped overruns and frame
- TX values: bytes packets errors dropped overruns collisions and carrier

5.7 Memory Statistics

- Total system memory
- Total used system memory
- Total free system memory
- · Actual total used system memory
- · Actual total free system memory
- Total swap size
- Total used swap size
- Total free swap size
- RAM size in MB

5.8 CPU statistics

- · Load and load average
- Total number of processes in idle state
- Total number of processes in running state
- Total number of processes in sleeping state
- Total number of zombie processes
- Total number of processes
- Total number of threads

5.9 Process Memory Statistics:

- Process ID
- Resident memory size used in Bytes
- Shared memory size used in Bytes
- Number of minor page faults
- Number of major page faults
- Total number of page faults (Major + Minor)
- Virtual memory size used in Bytes

5.10 Process CPU Statistics

- Process ID
- Percent CPU used
- Start time in milliseconds (Epoch time)
- Total CPU time in milliseconds (User + System)
- User CPU time in milliseconds
- System CPU time in milliseconds

	The state of the s		
data[5].switch	PROCESS_CPU_STATS		
data[5].processCPUStats.procld	15927		
data[5].processCPUStats.percent	0.024975024975025		
data[5].processCPUStats.startTime	1402582003000		
data[5].processCPUStats.totalCPUTime	17220		
data[5].processCPUStats.userCPUTime	13060		
data[5].processCPUStats.sysCPUTime	4160		
data[6].switch	PROCESS_MEM_STATS		
data[6].processMemStats.procld	15969		
data[6].processMemStats.resident	60477440		
data[6].processMemStats.share	15241216 15969		
data[6].processMemStats.minorFaults	19708		
data[6].processMemStats.majorFaults	46		
data[6].processMemStats.pageFaults	19754		
data[6] processMemStats size	1793462272		

Figure 5.1: Example Process Memory & CPU statistics

6 References

Sigar API

https://github.com/hyperic/sigar

Contacts & Notices

7.1 Contacts

ADLINK Technology Corporation

400 TradeCenter Suite 5900 Woburn, MA 01801 USA

Tel: +1 781 569 5819

ADLINK Technology Limited

The Edge 5th Avenue Team Valley Gateshead NE11 0XA

Tel: +44 (0)191 497 9900

ADLINK Technology SARL

28 rue Jean Rostand 91400 Orsay France

Tel: +33 (1) 69 015354

Web: http://ist.adlinktech.com/ Contact: http://ist.adlinktech.com E-mail: ist_info@adlinktech.com

LinkedIn: https://www.linkedin.com/company/79111/

Twitter: https://twitter.com/ADLINKTech_usa

Facebook: https://www.facebook.com/ADLINKTECH

7.2 Notices

Copyright © 2019 ADLINK Technology Limited. All rights reserved.

This document may be reproduced in whole but not in part. The information contained in this document is subject to change without notice and is made available in good faith without liability on the part of ADLINK Technology Limited. All trademarks acknowledged.

7.2. Notices