

```
dharanidhar@LAPTOP-2REPPLIJ:~$ nano command_exec.c
dharanidhar@LAPTOP-2REPPLIJ:~$ ls
a.out  arithmetic  command_exec  dir2  execworking  filename.c  p3  p4.c.save  process.c  process_states  test
add    arithmetic  command_exec.c  exec  file.txt      fork        p4  process   'process2.c\'  process_states.c  test.c
dharanidhar@LAPTOP-2REPPLIJ:~$ cat command_exec.c
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <stdlib.h>

int main()
{
    char cmd[20];
    pid_t pid;

    printf("Enter Linux command: ");
    scanf("%s", cmd);

    pid = fork();

    if (pid == 0)
    {
        printf("Child PID : %d\n", getpid());

        execlp(cmd, cmd, NULL);

        printf("Invalid Command!\n");
        exit(1);
    }
    else if (pid > 0)
    {
        printf("Parent PID : %d\n", getpid());

        wait(NULL);

        printf("Child process completed.\n");
    }
    else
    {
        printf("Fork failed!\n");
    }
}
```

```

else
{
    printf("Fork failed!\n");
}

return 0;
}

```

```

dharanidhar@LAPTOP-2REPPLIJ:~$ gcc command_exec.c -o command_exec

```

```

dharanidhar@LAPTOP-2REPPLIJ:~$ ls

```

a.out	arithmetic	command_exec	dir2	execworking	filename.c	p3	p4.c.save	process.c	process_states	test
add	arithmetic	command_exec.c	exec	file.txt	fork	p4	process	'process2.c\'	process_states.c	test.c

```

dharanidhar@LAPTOP-2REPPLIJ:~$ ./command_exec

```

```

Enter Linux command: date

```

```

Parent PID : 1982

```

```

Child PID : 1985

```

```

Fri Aug 21 06:48:27 UTC 2026

```

```

Child process completed.

```

```

dharanidhar@LAPTOP-2REPPLIJ:~$ ls

```

a.out	arithmetic	command_exec	dir2	execworking	filename.c	p3	p4.c.save	process.c	process_states	test
add	arithmetic	command_exec.c	exec	file.txt	fork	p4	process	'process2.c\'	process_states.c	test.c

```

dharanidhar@LAPTOP-2REPPLIJ:~$ ^C

```

```

dharanidhar@LAPTOP-2REPPLIJ:~$ ./command_exec

```

```

Enter Linux command: ls

```

```

Parent PID : 2033

```

```

Child PID : 2038

```

a.out	arithmetic	command_exec	dir2	execworking	filename.c	p3	p4.c.save	process.c	process_states	test
add	arithmetic	command_exec.c	exec	file.txt	fork	p4	process	'process2.c\'	process_states.c	test.c

```

Child process completed.

```

```

dharanidhar@LAPTOP-2REPPLIJ:~$ ./command_exec

```

```

Enter Linux command: pwd

```

```

Parent PID : 2047

```

```

Child PID : 2050

```

```

/home/dharanidhar

```

```

Child process completed.

```

```

dharanidhar@LAPTOP-2REPPLIJ:~$ ./command_exec

```

```

Enter Linux command: day

```

```

Parent PID : 2055

```

```

Child PID : 2058

```

```

Invalid Command!

```

```

Child process completed.

```

```

dharanidhar@LAPTOP-2REPPLIJ:~$ |

```