

# Predicting Basketball Hall of Fame Membership

---

COMP9417 - Machine Learning and Data Mining: Project

Chi-Chun Tiao

June 9, 2013

## 1. INTRODUCTION

Enshrinement into the Naismith Memorial Basketball Hall of Fame is an honour bestowed upon exceptional basketball players, coaches, referees, executives and other major contributors to the sport across the world. As one might expect, the population of inductees is dominated by members in the players category - 158 members in the players category out of a total of 326 members as of the enshrinement class of 2013[1]. Of the 158 players in the Hall of Fame, 103 played in the National Basketball Association (NBA), easily rendering it the league with the most players in the Hall of Fame<sup>1</sup>. As such, we shall limit our discussion to individuals who have played in the NBA.<sup>2</sup>

Unlike other major sport's Hall of Fames where sportswriter voters openly debate their choices, the Naismith Hall of Fame has an opaque and closely held selection process[2]. As a consequence of the screening committee's lack of transparency, the criteria for induction is vague at best and discussion regarding the merits of players is subjective. It would be useful to form an objective basis upon which a player's merits can be analysed and used to predict whether he will be inducted into the Hall of Fame. The goal of this project is to develop such a method using machine learning techniques.

---

<sup>1</sup>Other inductees of this category include college, international and female players, etc., most of whom have their own shrines already: The College Experience (NCAA), the FIBA Hall (international) and the WBHOF (women's).

<sup>2</sup>Indeed, this inevitably places prejudice against players who had decorated international or college careers, but relatively short or less impressive stints in the NBA, but might nevertheless be considered worthy of Hall of Fame induction.

Currently, some popular methods used include the *Keltner List*, a less objective but systematic method adopted from baseball (as many advanced basketball metrics often are) and also a logistic regression model[4], developed by *Basketball Reference*, a site that provides comprehensive basketball statistics. However, no attempts have been made to develop a machine learning model (to the best of my knowledge). Work has been done to solve the same problem in baseball using a Radial Basis Function Network by Smith, Lloyd and Downey, James (2009)[5], and some of the methods here shall be based upon this.

In this project, I strive to harness the capabilities and advantages of machine learning methods to build a model with better predictive accuracy than that of the aforementioned methods, by experimenting with various different datasets, features and learning algorithms. This report documents the methods employed, work done to collect and preprocess the data, experimentations involved and analysis of the various results.

## 2. EXPERIMENTATION

### 2.1. DOMAIN-SPECIFIC FEATURES

In the initial stages of this project, simple basketball statistics were incorporated as features into the training set, alongside other metrics that indicate the relative merit of particular players with respect to other players who played in the league in his time:

- Points Per Game
- Career Points
- Most Valuable Player Awards
- Assists Per Game
- Career Assists
- All-Star Game Appearances
- Rebounds Per Game
- Career Rebounds
- Year Played in the League

Taking into account the fact that a player must be fully retired for five years before being eligible for induction[?] and that the inaugural NBA All-Star Game took place in 1951, we used data from players who debuted in the league during or after the 1951-52 season and retired before the 2008-09 season. This not only avoids differences in basketball eras but ensures comprehensive statistics for each player (no missing or incomplete features for any instance) since all the above statistics were being recorded in that time period. Other key statistics such as *steals*, *blocks* and *field goal percentage* were not incorporated for this very reason, as many players either did not have these statistics recorded at all or only had it recorded for some seasons. Other metrics like player's *draft pick*, *weight* and *height* were also considered but these failed to improve performance as shall be discussed later.

In an effort to improve predictive accuracy on this model built on a relatively small number of features, several advanced basketball statistics were considered. Namely, *win shares*, a metric adopted from baseball that is designed to estimate a player's contribution to his team winning, which is made up of two other metrics, *defensive win shares* and *offensive win shares*, each of which considers a players offensive and defensive contributions respectively. Since

it has been said that certain players are inducted into the Hall of Fame based but on their defensive prowess, which may not reflect well on a stat sheet, I decided it would be beneficial to incorporate both defensive and offensive win shares. Another statistic considered was the *Player Efficiency Rating (PER)*, a rather arcane but popular metric which summarises a player's performance and contributions into a one number using a very detailed formula. Finally, the statistics *effective field goal percentage (eFG%)* and *True Shooting Percentage (TS%)* were considered, both of which incorporate 3-point and 2-point field goals, the former of which adjusts for the fact that a 3-point field goal is worth one more point than a 2-point field goal and the latter also considers free throw percentage.

The last metric considered was the number of *NBA Championship Titles* the player has won and the player's *longest stint with any team*. The latter is potentially interesting and valuable as this could serve as an indication that he was a franchise player, an elite status bestowed upon (usually) the best players on their respective teams, whom the franchise is built around. Unfortunately, this was not experimented with due to the difficulty in obtaining this feature but is definitely further work that could be undertaken.

As noted earlier, since many statistics were not being recorded prior to the 1973-74 season, we cannot simply incorporate these advanced basketball metrics into our model as most rely on these missing statistics. Luckily, *Basketball Reference* provides a complete system with estimations to account for missing statistics in particular eras, the formulae for which are quite detailed. The method for calculating win shares and player efficiency rating can be found at <http://www.basketball-reference.com/about/ws.html> and <http://www.basketball-reference.com/about/per.html>.

## 2.2. DATA COLLECTION AND PREPARATION

A considerable challenge faced in this project was the absence of a readily available data repository relevant to the problem, so a substantial amount of work was devoted overcoming this by web data extraction (scraping) and parsing data into a format that could be analysed with machine learning software. The documentation of the data collection process is kept as brief as possible since while part of the overall machine learning and data mining process, it has little to do with machine learning itself.

At first, official NBA stats portal <http://stats.nba.com/> seemed like a promising avenue for data collection. However, not only were there no datasets available for download, the site did not provide any APIs. To avoid resorting to scraping the pages, I inspected the source of the site's pages to find ways to access the backend scripts that drove the site's data and was able to find Javascript sources that provided results in a friendly Javascript Object Notation (JSON) format. Since each source only provided a subset of features for the particular player queried, I was required the cross reference these data sources to create a complete set of features for each player. The data sources and the respective features is provides are described below:

- <http://stats.nba.com/stats/commonallplayers> - *List of all NBA players*
- [http://stats.nba.com/stats/commonplayerinfo/?PlayerID=<player\\_id>](http://stats.nba.com/stats/commonplayerinfo/?PlayerID=<player_id>) - *All-Star Appearances (Not available for active players), Position*
- [http://stats.nba.com/feeds/players/profile/<player\\_id>\\_Profile.js](http://stats.nba.com/feeds/players/profile/<player_id>_Profile.js) - *Draft Pick, Weight, Height*
- [http://stats.nba.com/feeds/players/awards/<player\\_id>\\_Award.js](http://stats.nba.com/feeds/players/awards/<player_id>_Award.js) - *Most Valuable Player Awards, Hall of Fame Inductee*
- <http://stats.nba.com/stats/playerprofile> - *Points Per Game, Assists Per Game, Rebounds Per Game, Career Points, Career Assists, Career Rebounds*

At this stage of the data collection process, I hadn't conceived of using the advanced statistics described in the previous section, so these features seemed to be enough to get started on preliminary experimentation. This data source obviously failed to yield the number of championship titles, the aforementioned advanced statistics and the full set of simple statistics that were required to calculate complex metrics like the PER. This posed a problem after no further improvements could be obtained with the original dataset and its limited feature space and an alternative data source was required.

Since Basketball Reference provides all of the aforementioned features, with all of the advanced metrics already calculated (and much more), I finally resorted extracting data from its web pages since there was no API or datasets available for download. The list of players and their respective identifiers were obtained from [http://www.basketball-reference.com/players/<first\\_letter\\_last\\_name>](http://www.basketball-reference.com/players/<first_letter_last_name>) and a players complete profile could be obtained from [http://www.basketball-reference.com/players/<first\\_letter\\_last\\_name>/<identifier>.html](http://www.basketball-reference.com/players/<first_letter_last_name>/<identifier>.html).

The upside of this was that unlike the official NBA stats portal where it was necessary to piece together data from different sources, it was possible to obtain all the information required from a single page. Using the Python library Beautiful Soup, I was able to extract all the required features for every player. Additional statistics were also obtained in case they were required, such as statistics from Playoff games, All-Star Games, etc. This data source seemed far more comprehensive, and appeared to also include players from the American Basketball Association (ABA), which was later merged with the NBA in 1976. This also meant a larger training set to work with.

Furthermore, the Most Valuable Player Award data is expressed in terms of cumulative award shares for the player's career, which is calculated by the number of points a player received for a particular award over the total points of all first-place votes[?] - far more useful than merely the raw number of MVP awards in the case of players such as Jason Kidd, who has never won the award but has been a serious contender in many seasons due to his stellar performance.

Both of the aforementioned datasets have been saved in the ubiquitous JSON format and is included with the submission files. Both datasets can also be parsed into Weka's ARFF or vectorised to work with the Python machine learning library scikit-learn with the provided scripts.

### 2.3. TRAINING THE MODEL

In the initial experiment, the original dataset described in the previous section was used and trained on using different learning algorithms with Weka, *Logistic Regression*, *Multilayer Perceptrons*, *Decision Trees* and *Radial Basis Function Networks*, using the default parameters for each respective algorithm.

The performance of these algorithms were estimated with 10-fold cross-validation repeated 10 times and the predictive accuracy of models were compared using a paired *t*-test. Surprisingly, the logistic regression model outperformed all other models, but not by a statistically significant amount, with the exception of the tree learner. As seen in table 2.1, the percentage of correct classifications under these data schemes were all estimated to be above 97%.

Table 2.1: Predictive Accuracy (Percent Correct)

Dataset	Logistic	RBF Network	Multilayer Perceptron	Decision Tree (J48)
Initial NBA Data	98.08±0.83	97.79±1.01	97.83±0.83	97.41±0.93 •

◦, • statistically significant improvement or degradation

The suspiciously (and somewhat deceptively) good predictive accuracy attained by these learning schemes might be explained by the skewness of the training set toward negative examples. Indeed, the prestigious honour of enshrinement into the Hall of Fame is only bestowed upon a very select few individuals - 85 out of the 1591 players (4.2%) in the training set, so in fact one could attain 95.8% predictive accuracy simply by classifying all instances as negative!

Consequently, it is necessary to consider other cost-sensitive metrics to evaluate the performance of the learning schemes, the key one being *recall*.

Table 2.2: Recall

Dataset	Logistic	RBF Network	Multilayer Perceptron	Decision Tree (J48)
Initial NBA Data	0.67±0.16	0.70±0.16	0.65±0.16	0.60±0.18

◦, • statistically significant improvement or degradation

In table 2.2, we indeed see that the employed learning schemes did not have high recall, so 30-40% of actual Hall of Fame members were being misclassified as not being in the Hall of Fame, with the RBF network model yielding the highest recall<sup>3</sup>.

<sup>3</sup>Obviously, it was also important not to now compromise the prestige of the Hall of Fame by classifying instances as positive too liberally.

Table 2.3: Confusion Matrix

		Predicted		Total
		HOF	not HOF	
Actual	HOF	57	23	80
	not HOF	16	1779	1795
Total		73	1802	1875

Table 2.3 shows the confusion matrix for the RBF network model. Further work was done on this model in an effort to minimise the false negatives and thereby increase recall. The first attempt was to optimise the parameters of the model using the `CVParameterSelection` meta-classifier in Weka, namely, number of clusters, minimum standard deviation for the clusters, and the random seed to be used by  $k$ -means. Additionally, I tried to use Weka's feature selection options to either eliminate features that yielded little information gain, or otherwise transform the possibly correlated features into linearly uncorrelated variables features using principle component analyses. Unfortunately, these efforts were mostly in vain, as these had little to no effect on the predictive accuracy of the model or its ability to correctly classify positive instances. Some minor improvements were obtained, however, with a cost-sensitive meta-classifiers using two different methods: reweighting training instances according to the total cost assigned to each class and predicting the class with minimum expected misclassification cost[?]. The respective results of which can be seen in table 2.4.

Table 2.4: Confusion Matrix

		Predicted		Total			Predicted		Total
		HOF	not HOF				HOF	not HOF	
Actual	HOF	61	19	80	Actual	HOF	59	21	80
	not HOF	24	1771	1795		not HOF	21	1774	1795
Total		85	1790	1875	Total		80	1795	1875

(a) reweighted training instances                      (b) minimize expected misclassification cost

This was a good improvement, but I wanted to see if further advances could be made. Unfortunately, as mentioned in the data preparation section, this initial experiment only used the very basic set of features and more features were required at this point to make progress on this problem.

## 2.4. PREDICTIONS

## 3. CONCLUSION

## A. APPENDIX

## REFERENCES

- [1] *"Hall of Famers"* Retrieved 6 June 2013 from Naismith Memorial Basketball Hall of Fame: <http://www.hoophall.com/hall-of-famers-index/>
- [2] Aschburner, Steve. (12 August 2012) *"Hall of Fame selection process leaves much to be desired"*. Retrieved 6 June 2012 from NBA: [http://www.nba.com/2010/news/features/steve\\_aschburner/08/12/hall.process/index.html](http://www.nba.com/2010/news/features/steve_aschburner/08/12/hall.process/index.html)
- [3] Ziller, Tom. (30 March 2010) *"Fans to Vote for Basketball Hall of Fame Inductees"*. Retrieved 1 June 2013 from AOL News: <http://nba.fanhouse.com/2010/03/30/fans-to-vote-for-basketball-hall-of-fame-inductees/>
- [4] *"Hall of Fame Probability"*. Retrieved 1 June 2013 from Basketball Reference: [http://www.basketball-reference.com/about/hof\\_prob.html](http://www.basketball-reference.com/about/hof_prob.html)
- [5] Smith, Lloyd and Downey, James (2009) *"Predicting Baseball Hall of Fame Membership using a Radial Basis Function Network,"* Journal of Quantitative Analysis in Sports: Vol. 5: Iss. 1, Article 6.