| Section | Synopsis | References |
|--------------|---|---------------------|
| 705.28 | Revised text into list format with revised title to "Power Source Output Maximum Current." | FR-9399, SR-8388 |
| 705.28 | Revised to add three exceptions for clarity. | FR-9399, SR-8388 |
| 705.30 | Relocated sections from former 705.12(C), (D), and (E), deleted former 705.30(G), and revised 705.30(F) "Transformers" installation requirements into list format. | FR-9402, SR-8397 |
| 705.32 | Revised text for ground-fault protection to make it "ac circuit" specific for clarity and alignment with other sections. | FR-9404, SR-8398 |
| 705.40 | Revised to align with section title being specific to primary source and added word "interactive" for clarity. | FR-9407, SR-8399 |
| 705.50 | Revised text to better reflect how microgrids operate and added Informational Notes regarding microgrids using multiple sources and for Article 517 for health care facilities. | FR-9411, SR-8403 |
| 705.76 | Added section for microgrid control systems (MCS) that correlates with the current state of the industry and available standards. | FR-9507, SR-8407 |
| 705.80 | Added section covering interconnected power production sources that are operating in island mode. | FR-9414, SR-8408 |
| 705.81 | Added section requiring power sources in island mode be controlled. | FR-9414, SR-8409 |
| 705.82 | Added section on 120-volt supplies from 710.15(C). | FR-9414. |
| 706.1 | Revised text and order of Informational Notes and revised Informational Note No. 1 to align with the scope of Article 480. | FR-9074, SR-8116 |
| 706.6 | Revised to incorporate applications for outdoor systems and microgrids where there may be multiple ESS on same premises. | FR-9078 |
| 706.7 | Revised title to add "Commissioning" and revised text into subsections. (A) requires ESS to be commissioned upon installation. | FR-9079 |
| 706.7(A) | Revised to require ESS to be commissioned upon installation in other than one- and two-family dwellings. | FR-9079, SR-8086 |
| 706.15 | Revised text to be able to disconnect ESS from all other wiring and comply with emergency shutdown requirements for one- and two-family dwellings. | FR-9086 |
| 706.16(E) | Revised text to correlate with the deletion of Article 712. | SR-8467 |
| 706.20(A) | Revised Informational Note No. 1 to include reference to NFPA 855. | FR-9089 |
| 706.31(A) | Revised text to align with similar requirements in Article 690 and added Informational Note regarding integral fault protection. | FR-9090, SR-8091 |
| 706, Part V | Revised title to use acronym and revised Informational Note to reflect Part V of Article 706. | FR-9617 |
| 706.40 | Revised to remove reference to Article 692 when dealing with flow batteries and added Informational Note referencing NFPA 855 for installation requirements of flow batteries. | FR-9133 |
| 706.50 | Revised to remove reference to Part III of Article 705 and added requirement to comply with Parts I, II, III, and IV of Article 706. | FR-9134, SR-8092 |
| 706.51 | Added section for flywheel ESS (FESS). | FR-9196 |
| 708.2 | Added section for reconditioned equipment. | SR-8034 |
| 708.7 | Added section for cybersecurity with COPS. | FR-8914 |
| 708.8(A) | Added Informational Note No. 2 referencing 708.7 for cybersecurity assessments. | FR-8917 |
| 708.14 | Revised text to clarify that a 2-hour listed fire-resistive cable system or a 2-hour electrical circuit protected system meets the requirement. | FR-8931 |
| 708.20(F)(1) | Revised to replace "service" with "power source". | FR-8937 |
| 708.22(B) | Revised title to remove listed functions and place them into enforceable text. | SR-8037 |
| 708.24(A) | Revised to add listing requirements for transfer switches and to clarify cross reference. | FR-8939, SR-8040 |
| 708.24(D) | Revised title to "Redundant Transfer Equipment" and revised text to describe the functionality that is needed when emergency loads are supplied by a single feeder. | SR-8041 |