| Section | Synopsis | References |
|----------------------|--|---------------------------------|
| 520.54(K) | Revised to replace "qualified personnel" with defined term qualified persons. | SR-8515 |
| 520.62 | Revised to incorporate listing requirements. | FR-8005 |
| 520.68(D) | Added section for special-purpose multi-circuit cable systems. | FR-8007, SCR-60 |
| 522.22 | Revised Note 1 in Table 522.22 with enforceable language. | SR-8715 |
| 525.3 | Deleted former 525.3(B) and (C) and relocated requirement from former 525.3(D) into 525.3(B). | FR-8017, FR-8019, FR-8021 |
| 525.31 | Revised to remove non-modifying language. | FR-8023 |
| Article 530 | Revised and restructured article extensively to incorporate new technology and to apply to studios in facilities and locations staffed by qualified persons. Revised article title to replace "and Similar Locations" with "and Remote Locations." | FR-8211, SR-8529 |
| 540.50 | Deleted section. | FR-8220, FR-8221 |
| 545.22 | Revised to clarify the feeder requirements for relocatable structures to be consistent with Article 550 and to add reference to 590.4(B) in Informational Note. | SR-8603 |
| 545.22(D) | Revised to divide into subsections for clarity. | FR-7705 |
| 547.1 | Revised article into Part delineations and renumbered sections accordingly. | FR-7816 |
| 547.20 | Revised text into list format and added Part II of Article 502 to the 547.1 allowable wiring methods. | FR-7746, FR-7816, SR-8605 |
| 547.26 | Revised to not permit NM cable concealed within walls or above ceilings and added Informational Note. | FR-7748 |
| 547.27 | Revised to require an insulated equipment grounding conductor if it is separate and not part of a cable assembly. | FR-7789 |
| 547.28 | Revised list item (1) to replace "having" with "requiring" an equipotential plane. | SR-8619 |
| 547.41(B)(2) and (3) | Revised to remove redundant language. | FR-7750, FR-7754 |
| 547.44(B) | Revised Informational Note No. 1 and No. 2 references and clarified the bonding termination locations of the equipotential plane conductor. | FR-7771, FR-7756, SCR-124 |
| 550.10(I) | Revised to add additional raceway types and use defined terms. | FR-7763, SR-8630 |
| 550.13(B) | Revised for clarity and usability for GFCI protection. | SR-8633 |
| 550.15 | Revised to clarify the intent to avoid terminating dissimilar metals. | FR-7786, SR-8640 |
| 550.16(A)(1) | Revised to add "equipment" in front of "grounding." | FR-7792 |
| 550.16(C)(1) | Revised to add "solid, insulated, or bare" for applicability. | FR-7794 |
| 550.25 | Revised to consolidate text and provide reference to Article 100. | FR-7797 |
| 550.32(A) | Revised to replace "within 30 ft" with "within sight from the mobile home it serves." | FR-7832, SCR-92 |
| 550.33(A) | Added section for feeder equipment to address disconnecting means and renumbered former 550.33(A) to (B). | FR-7874, SR-8651 |
| 551.3 | Added section around electrical datum plane distances. | FR-7873 |
| 551.30(A) | Revised to require the connection of electrical system from a generator be capable of providing an effective ground-fault return path when operational. | FR-7841 |
| 551.31(D) | Revised to replace "power supply" with "feeder" to correlate with the revised definition for feeder assembly. | SR-8656 |
| 551.40(A) | Revised to add the term "nominal" for consistency. | FR-7842 |
| 551.40(C) | Revised to replace "power supply" with "feeder." | SR-8658 |