

# Image Retrieval Using Pretrained Models

Quang-Vinh Dinh  
Ph.D. in Computer Science

# Outline

- **Vector and Matrix**
- **Cosine Similarity**
- **Implementation**
- **Case Studies**

# Vector & Matrix

## Vector

$n$  is a natural number

$\mathcal{R}$  is a set of real numbers

$\vec{v}$  has a length of  $n$  and contain real numbers

$$\vec{v} \in \mathcal{R}^n$$

$$\vec{v} = \begin{bmatrix} v_1 \\ v_2 \\ v_3 \end{bmatrix} \in \begin{bmatrix} \mathcal{R} \\ \mathcal{R} \\ \mathcal{R} \end{bmatrix} = \mathcal{R}^3$$

## Matrix

Matrix  $A$  has the shape of rectangle

Has  $m$  rows and  $n$  columns

Use capital letter

$$A \in \mathcal{R}^{m \times n}$$

$$A = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \\ a_{31} & a_{32} \end{bmatrix} \in \begin{bmatrix} \mathcal{R} & \mathcal{R} \\ \mathcal{R} & \mathcal{R} \\ \mathcal{R} & \mathcal{R} \end{bmatrix} = \mathcal{R}^{3 \times 2}$$

# Vector Operations

## Addition

$$\vec{v} = \begin{bmatrix} v_1 \\ \dots \\ v_3 \end{bmatrix} \quad \vec{u} = \begin{bmatrix} u_1 \\ \dots \\ u_3 \end{bmatrix}$$

$$\vec{v} + \vec{u} = \begin{bmatrix} v_1 \\ \dots \\ v_3 \end{bmatrix} + \begin{bmatrix} u_1 \\ \dots \\ u_3 \end{bmatrix} = \begin{bmatrix} v_1 + u_1 \\ \dots \\ v_3 + u_3 \end{bmatrix}$$

```
1  def add_vectors(vector1, vector2):
2      '''
3          Add corresponding elements between two vectors
4          vector1 and vector2 are with list type
5          output is a vector (list)
6      '''
7
8      return [v1+v2 for v1, v2 in zip(vector1, vector2)]
9
10 # Test case
11 vector1 = [1, 2, 3]
12 vector2 = [4, 5, 6]
13
14 output = add_vectors(vector1, vector2)
15 print(output)
```

[5, 7, 9]

# Vector Operations

## Subtraction

$$\vec{v} = \begin{bmatrix} v_1 \\ \dots \\ v_n \end{bmatrix} \quad \vec{u} = \begin{bmatrix} u_1 \\ \dots \\ u_n \end{bmatrix}$$

$$\vec{v} - \vec{u} = \begin{bmatrix} v_1 \\ \dots \\ v_n \end{bmatrix} - \begin{bmatrix} u_1 \\ \dots \\ u_n \end{bmatrix} = \begin{bmatrix} v_1 - u_1 \\ \dots \\ v_n - u_n \end{bmatrix}$$

## Multiply with a number

$$\alpha \vec{u} = \alpha \begin{bmatrix} u_1 \\ \dots \\ u_n \end{bmatrix} = \begin{bmatrix} \alpha u_1 \\ \dots \\ \alpha u_n \end{bmatrix}$$

## Length of a vector

$$\|\vec{u}\| = \sqrt{u_1^2 + \dots + u_n^2}$$

# Vector Operations

## Dot product

$$\vec{v} = \begin{bmatrix} v_1 \\ \dots \\ v_n \end{bmatrix} \quad \vec{u} = \begin{bmatrix} u_1 \\ \dots \\ u_n \end{bmatrix}$$

$$\vec{v} \cdot \vec{u} = v_1 \times u_1 + \dots + v_n \times u_n$$

```
1 def dot_product(vector1, vector2):  
2     '''  
3     Compute dot product between two vectors  
4     Output is a floating-point number  
5     '''  
6  
7     return sum([v1*v2 for v1, v2 in zip(vector1, vector2)])  
8  
9 # test case  
10 vector1 = [1, 2, 3]  
11 vector2 = [2, 3, 4]  
12  
13 ouptut = dot_product(vector1, vector2)  
14 print(ouptut)
```

20

# Vector Operations

## Hadamard product

$$\vec{v} = \begin{bmatrix} v_1 \\ \dots \\ v_n \end{bmatrix} \quad \vec{u} = \begin{bmatrix} u_1 \\ \dots \\ u_n \end{bmatrix}$$

$$\vec{v} \odot \vec{u} = \begin{bmatrix} v_1 \\ \dots \\ v_n \end{bmatrix} \odot \begin{bmatrix} u_1 \\ \dots \\ u_n \end{bmatrix} = \begin{bmatrix} v_1 \times u_1 \\ \dots \\ v_n \times u_n \end{bmatrix}$$

```
1 def Hadamard_product(vector1, vector2):  
2     '''  
3     Compute Hadamard product between two vectors  
4     Output is a vector  
5     '''  
6     return [v1*v2 for v1, v2 in zip(vector1, vector2)]  
7  
8 # test case  
9 vector1 = [1, 2]  
10 vector2 = [3, 4]  
11  
12 output = Hadamard_product(vector1, vector2)  
13 print(output)
```

[3, 8]

# Matrix Operations

$$A = \begin{bmatrix} a_{11} & \dots & a_{1n} \\ \dots & \dots & \dots \\ a_{m1} & \dots & a_{mn} \end{bmatrix} \quad B = \begin{bmatrix} b_{11} & \dots & b_{1n} \\ \dots & \dots & \dots \\ b_{m1} & \dots & b_{mn} \end{bmatrix}$$

## Addition

$$A + B = \begin{bmatrix} (a_{11} + b_{11}) & \dots & (a_{1n} + b_{1n}) \\ \dots & \dots & \dots \\ (a_{m1} + b_{m1}) & \dots & (a_{mn} + b_{mn}) \end{bmatrix}$$

## Subtraction

$$A - B = \begin{bmatrix} (a_{11} - b_{11}) & \dots & (a_{1n} - b_{1n}) \\ \dots & \dots & \dots \\ (a_{m1} - b_{m1}) & \dots & (a_{mn} - b_{mn}) \end{bmatrix}$$



# Matrix Operations

## Multiplication

$$A = \begin{bmatrix} a_{11} & \dots & a_{1n} \\ \dots & \dots & \dots \\ a_{m1} & \dots & a_{mn} \end{bmatrix} \quad B = \begin{bmatrix} b_{11} & \dots & b_{1k} \\ \dots & \dots & \dots \\ b_{n1} & \dots & b_{nk} \end{bmatrix}$$
$$A \in \mathcal{R}^{m \times n} \quad B \in \mathcal{R}^{n \times k}$$

$$C = AB$$
$$C \in \mathcal{R}^{m \times k}$$
$$c_{ij} = \sum_{l=1}^n a_{il} b_{lj}$$

$$\begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \\ a_{31} & a_{32} \end{bmatrix} \begin{bmatrix} b_{11} & b_{12} \\ b_{21} & b_{22} \end{bmatrix} = \begin{bmatrix} a_{11}b_{11} + a_{12}b_{21} & a_{11}b_{12} + a_{12}b_{22} \\ a_{21}b_{11} + a_{22}b_{21} & a_{21}b_{12} + a_{22}b_{22} \\ a_{31}b_{11} + a_{32}b_{21} & a_{31}b_{12} + a_{32}b_{22} \end{bmatrix}$$

# Matrix Operations

## Multiplication

$$A = \begin{bmatrix} a_{11} & \dots & a_{1n} \\ \dots & \dots & \dots \\ a_{m1} & \dots & a_{mn} \end{bmatrix} \quad \vec{x} = \begin{bmatrix} x_1 \\ \dots \\ x_n \end{bmatrix}$$

$$A \in \mathcal{R}^{m \times n}$$

$$C = A\vec{x}$$

$$c_i = \sum_{l=1}^n a_{il}x_l$$

## Example

$$\begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \\ a_{31} & a_{32} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} a_{11}x_1 + a_{12}x_2 \\ a_{21}x_1 + a_{22}x_2 \\ a_{31}x_1 + a_{32}x_2 \end{bmatrix}$$

# Matrix Operations

## Multiplication

$$A = \begin{bmatrix} a_{11} & \dots & a_{1n} \\ \dots & \dots & \dots \\ a_{m1} & \dots & a_{mn} \end{bmatrix} \quad B = \begin{bmatrix} b_{11} & \dots & b_{1k} \\ \dots & \dots & \dots \\ b_{n1} & \dots & b_{nk} \end{bmatrix}$$
$$A \in \mathcal{R}^{m \times n} \quad B \in \mathcal{R}^{n \times k}$$

$$C = AB$$
$$c_{ij} = \sum_{l=1}^n a_{il} b_{lj}$$

```
1 def matrix_multiplication(matrix1, matrix2):
2     '''
3     This function does the multiplication between two matrices.
4     #columns of matrix1 == #rows of matrix2
5     '''
6     matrix1_nrows = len(matrix1)
7     matrix1_ncols = len(matrix1[0])
8
9     matrix2_nrows = len(matrix2)
10    matrix2_ncols = len(matrix2[0])
11
12    # tạo matrix kết quả
13    result = [[0]*matrix2_ncols for i in range(matrix1_nrows)]
14
15    for i in range(matrix1_nrows):
16        for j in range(matrix2_ncols):
17            for k in range(matrix2_nrows):
18                result[i][j] += matrix1[i][k] * matrix2[k][j]
19
20    return result
21
22    # test case
23    # 3x3 matrix
24    matrix1 = [[1, 2, 3],
25               [4, 5, 6],
26               [7, 8, 9]]
27
28    # 3x4 matrix
29    matrix2 = [[1, 1, 2, 1],
30               [1, 2, 1, 1],
31               [1, 1, 1, 2]]
32
33    result = matrix_multiplication(matrix1, matrix2)
34    print(result[0])
35    print(result[1])
36    print(result[2])
```

```
[6, 8, 7, 9]
[15, 20, 19, 21]
[24, 32, 31, 33]
```

# Matrix Operations

## Transpose

$$A = \begin{bmatrix} a_{11} & \dots & a_{1n} \\ \dots & \dots & \dots \\ a_{m1} & \dots & a_{mn} \end{bmatrix}$$

$$A^T = \begin{bmatrix} a_{11} & \dots & a_{m1} \\ \dots & \dots & \dots \\ a_{1n} & \dots & a_{mn} \end{bmatrix}$$

## Example

$$\begin{bmatrix} \alpha_1 & \alpha_2 & \alpha_3 \\ \beta_1 & \beta_2 & \beta_3 \end{bmatrix}^T = \begin{bmatrix} \alpha_1 & \beta_1 \\ \alpha_2 & \beta_2 \\ \alpha_3 & \beta_3 \end{bmatrix}$$

# Applications

## Phép nhân giữa ma trận và vector

$$A = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \quad x = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} \quad b = \begin{bmatrix} b_1 \\ b_2 \end{bmatrix}$$

$$Ax = b$$


$$\begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} a_{11}x_1 + a_{12}x_2 \\ a_{21}x_1 + a_{22}x_2 \end{bmatrix} = \begin{bmatrix} b_1 \\ b_2 \end{bmatrix}$$

Ma trận A biến đổi/dịch chuyển x sang b

Giá trị từng phần tử của b là tổ hợp tuyến tính của tất cả các phần tử của x


$$b_1 = a_{11}x_1 + a_{12}x_2$$

$$b_2 = a_{21}x_1 + a_{22}x_2$$



# Applications

**Ma trận A dịch chuyển điểm  $x$  đối xứng qua trục  $x_1$**



**Ứng dụng lật ảnh đối xứng qua trục ngang**

Giá trị màu (red, green, blue) của điểm  $p$

Các thuộc tính của pixel  $p(\underbrace{x_1, x_2}_{\text{Tọa độ điểm } p}, \underbrace{r, g, b}_{\text{Giá trị màu}})$

Tọa độ điểm  $p$

Dịch chuyển pixel  $(x_1, x_2)$  theo  $A = \begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix}$




Ảnh gốc



Ảnh kết quả

# Applications

**Ma trận A dịch chuyển điểm x đối xứng qua trục  $x_2$**



**Ứng dụng lật ảnh đối xứng qua trục đứng**

Giá trị màu (red, green, blue) của điểm  $p$

Các thuộc tính của pixel  $p(\underbrace{x_1, x_2}_{\text{Tọa độ điểm } p}, \underbrace{r, g, b}_{\text{Giá trị màu}})$

Tọa độ điểm  $p$

Dịch chuyển pixel  $(x_1, x_2)$  theo  $A = \begin{bmatrix} -1 & 0 \\ 0 & 1 \end{bmatrix}$




Ảnh gốc




Ảnh kết quả

# Dot Product

$$\vec{x}_1 = \begin{pmatrix} 1 \\ 0 \end{pmatrix} \quad \vec{x}_2 = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$



$$\vec{v}_1 = \begin{pmatrix} v_{1_1} \\ v_{1_2} \end{pmatrix} \quad \vec{v}_2 = \begin{pmatrix} v_{2_1} \\ v_{2_2} \end{pmatrix}$$





# Tách ma trận

**Mục đích:** Đưa ma trận  $Q$  về dạng  $U\Sigma$  sao cho các vector (cột) trong  $U$  có độ dài bằng 1.

**Công thức**

$$\begin{pmatrix} a & c \\ b & d \end{pmatrix} = \begin{pmatrix} \frac{a}{\sqrt{a^2 + b^2}} & \frac{c}{\sqrt{c^2 + d^2}} \\ \frac{b}{\sqrt{a^2 + b^2}} & \frac{d}{\sqrt{c^2 + d^2}} \end{pmatrix} \begin{pmatrix} \sqrt{a^2 + b^2} & 0 \\ 0 & \sqrt{c^2 + d^2} \end{pmatrix}$$

**Ví dụ**

$$\begin{aligned} \begin{pmatrix} 3 & 2 \\ 4 & 0 \end{pmatrix} &= \begin{pmatrix} \frac{3}{\sqrt{3^2 + 4^2}} & \frac{2}{\sqrt{2^2 + 0}} \\ \frac{4}{\sqrt{3^2 + 4^2}} & 0 \end{pmatrix} \begin{pmatrix} \sqrt{3^2 + 4^2} & 0 \\ 0 & \sqrt{2^2 + 0} \end{pmatrix} \\ &= \begin{pmatrix} \frac{3}{5} & 1 \\ \frac{4}{5} & 0 \end{pmatrix} \begin{pmatrix} 5 & 0 \\ 0 & 2 \end{pmatrix} \end{aligned}$$

Cách tính tương tự khi  $Q$  có kích thước khác

# Singular Value Decomposition

Tìm độ dài hình chiếu của  $\vec{a}$  lên  $\vec{v}_1$  và  $\vec{v}_2$

$$q_1 = \vec{a} \cdot \vec{v}_1 = (a_1 \ a_2)^T \begin{pmatrix} v_{1_1} \\ v_{1_2} \end{pmatrix}$$

$$q_1 = \vec{a} \cdot \vec{v}_2 = (a_1 \ a_2)^T \begin{pmatrix} v_{2_1} \\ v_{2_2} \end{pmatrix}$$

Viết lại dạng ma trận cho ngắn gọn

$$\begin{aligned} \vec{a} \cdot V &= (a_1 \ a_2)^T \begin{pmatrix} v_{1_1} & v_{2_1} \\ v_{1_2} & v_{2_2} \end{pmatrix} \\ &= (q_1 \ q_2) \end{aligned}$$

Nếu có thêm  $\vec{b}$

$$\begin{pmatrix} \textcolor{red}{a}_1 & \textcolor{red}{a}_2 \\ \textcolor{green}{b}_1 & \textcolor{green}{b}_2 \end{pmatrix}^T \begin{pmatrix} v_{1_1} & v_{2_1} \\ v_{1_2} & v_{2_2} \end{pmatrix} = \begin{pmatrix} q_{1a} & q_{2a} \\ q_{1b} & q_{2b} \end{pmatrix}$$

Ma trận  
các điểm

Ma trận  
các trục

Ma trận độ  
dài hình chiếu

Giả sử  $V$  là ma trận trực giao

$$AV = Q$$

$$A = QV^{-1} = QV^T \quad \text{chuyển vế } V$$

$$A = QV^{-1} = U\Sigma V^T \quad \text{tách } Q$$

Tổng quát

$$A = U\Sigma V^T$$

$A$  là ma trận  $n \times d$ , có  $n$  điểm và mỗi điểm có  $d$  phần tử

$U$  là ma trận  $n \times n$  chứa độ dài hình chiếu, trong đó các vector cột có chiều dài bằng 1

$\Sigma$  là ma trận đường chéo ( $n \times d$ ), xác định độ dài của các vector

$V$  là ma trận  $d \times d$  chứa các trục

Trong Python tính SVD với  
hàm **numpy.linalg.svd**

# Ứng dụng SVD cho foreground removal

Idea: Mỗi hình trong video được xem như một vector. Từ video  $\rightarrow A$ . Sau đó tính SVD cho  $A$ .

Chỉ dùng  $r$  giá trị lớn nhất trong  $\Sigma$  ( $r$  trực chứa thông tin quan trọng và phổ biến nhất).

Tính lại  $A$  với  $\Sigma$  mới



Hình gốc



Hình với  $\Sigma$  mới



Hình gốc



Hình với  $\Sigma$  mới



Hình gốc



Hình với  $\Sigma$  mới



Hình gốc



Hình với  $\Sigma$  mới

# Outline

- **Vector and Matrix**
- **Cosine Similarity**
- **Implementation**
- **Case Studies**

# Cosine similarity

**Cosine similarity (cs)** được dùng để đo mức độ giống nhau/tương đồng giữa hai vector

Gọi  $\vec{x}$  và  $\vec{y}$  là hai vector, cs được tính như sau

$$cs(\vec{x}, \vec{y}) = \frac{\vec{x} \cdot \vec{y}}{\|\vec{x}\| \|\vec{y}\|} = \frac{\sum_1^n x_i y_i}{\sqrt{\sum_1^n x_i^2} \sqrt{\sum_1^n y_i^2}}$$

**Tính chất 1:**  $cs(\vec{x}, \vec{y}) = cs(a\vec{x}, b\vec{y})$

$$\begin{aligned} cs(a\vec{x}, b\vec{y}) &= \frac{a\vec{x} \cdot b\vec{y}}{\|a\vec{x}\| \|b\vec{y}\|} = \frac{\sum_1^n ax_i by_i}{\sqrt{\sum_1^n a^2 x_i^2} \sqrt{\sum_1^n b^2 y_i^2}} \\ &= \frac{ab \sum_1^n x_i y_i}{\sqrt{a^2 \sum_1^n x_i^2} \sqrt{b^2 \sum_1^n y_i^2}} \\ &= \frac{\sum_1^n x_i y_i}{\sqrt{\sum_1^n x_i^2} \sqrt{\sum_1^n y_i^2}} = cs(\vec{x}, \vec{y}) \end{aligned}$$

**Tính chất 2:**  $cs(\vec{x}, \vec{y}) \neq cs(\vec{x} + c, \vec{y} + d)$

**Ví dụ:**  $\vec{x} = [4, 2, 1, 2]^T$

$$\vec{y} = [1, 2, 2, 0]^T$$

$$\vec{u} = 2\vec{x} = [8, 4, 2, 4]^T$$

$$\vec{v} = 3\vec{y} = [3, 6, 6, 0]^T$$

$$\begin{aligned} cs(\vec{x}, \vec{y}) &= \frac{4*1+2*2+1*2+2*0}{\sqrt{4^2+2^2+1^2+2^2} \sqrt{1^2+2^2+2^2+0}} \\ &= \frac{10}{\sqrt{25}\sqrt{9}} = \frac{10}{15} = 0.67 \end{aligned}$$

$$\begin{aligned} cs(\vec{u}, \vec{v}) &= \frac{8*3+4*6+2*6+4*0}{\sqrt{8^2+4^2+2^2+4^2} \sqrt{3^2+6^2+6^2+0}} \\ &= \frac{60}{\sqrt{100}\sqrt{81}} = \frac{60}{90} = 0.67 \\ &= cs(\vec{x}, \vec{y}) \end{aligned}$$

## Image Retrieval


Query 2



Query 1



= 2 \*



Hai hình query cho cùng kết quả như nhau

Query 1




Query 2




= 50 +

Query 1



Result 1



Result 2

Result 1  $\neq$  Result 2



# Cosine similarity

## ❖ Code

```
1 import math
2
3 def cosine_similarity(vector1, vector2):
4     '''
5     Compute dot product between two vectors
6     Output is a floating-point number
7     '''
8
9     sumxy = sum([v1*v2 for v1, v2 in zip(vector1, vector2)])
10    sumxx = sum([v1*v2 for v1, v2 in zip(vector1, vector1)])
11    sumyy = sum([v1*v2 for v1, v2 in zip(vector2, vector2)])
12
13    return sumxy/math.sqrt(sumxx*sumyy)
14
15 # test case
16 vector1 = [5, 3, 2, 7]
17 vector2 = [2, 9, 4, 1]
18
19 output = cosine_similarity(vector1,vector2)
20 print(output)
```

0.552005787925351



# Outline

- **Vector and Matrix**
- **Cosine Similarity**
- **Implementation**
- **Case Studies**

# Image Retrieval

## ❖ Database

### Query Images



```
1 import numpy as np
2 from tensorflow.keras.preprocessing import image as kimage
3 from tqdm import tqdm
4
5 images = []
6 lists = [i for i in range(9908)]
7
8 for index in tqdm(lists):
9     img = kimage.load_img('images_mr/%d.jpg' % (index), target_size=(86, 128))
10    img_np = kimage.img_to_array(img)
11    images.append(img_np)
12
13 images_np = np.array(images)
14 print(images_np.shape)
```

 $(9908, 86, 128, 3)$


# Image Retrieval

## ❖ Database Preparation



$$p \in [0, 255]$$

float32



uint8



## ❖ Database Preparation

[illegible]

(9908, 86, 128, 3)

# Image Retrieval

## ❖ Database Preparation

```
1 import numpy as np
2
3 data = np.load('images_mr.npy', allow_pickle=True)
4 print(data.shape)
5 print(type(data[0,0,0,0]))
6
7 data = data.astype(np.float32)
8 print(type(data[0,0,0,0]))
9
10 print(np.amin(data))
11 print(np.amax(data))
```

```
(9908, 86, 128, 3)
<class 'numpy.uint8'>
<class 'numpy.float32'>
0.0
255.0
```

# Image Retrieval

## ❖ Using absolute difference

### Database





# Image Retrieval

## ❖ Using cosine similarity

### Database







# Image Retrieval

## ❖ Doing

Query




VGG16  
(Top=False)



Database



VGG16  
(Top=False)



# Image Retrieval

## ❖ Doing


Query



(1, 86, 128, 3)



VGG16  
(Top=False)



(1, 2, 4, 512)

```
# load query
query = kimage.load_img(PATH+'q2.jpg', target_size=(86, 128))
query_np = kimage.img_to_array(query)
query_np = np.expand_dims(query_np, axis=0)
query_np = preprocess_input(query_np)


pred_query = model.predict(query_np)
print(pred_query.shape)
```

(1, 2, 4, 512)

# Image Retrieval

## ❖ Doing

Database



```
PATH = '/content/gdrive/My Drive/data/image_retrieval2/'  
data = np.load(PATH+'images_mr.npy', allow_pickle=True)  
data = data.astype(np.float32)  
  
data = preprocess_input(data)  
pred_data = model.predict(data)  
print(pred_data.shape)
```

(9908, 2, 4, 512)

# Image Retrieval

## ❖ Cost Functions

### Absolute Difference

$$cs(\vec{x}, \vec{y}) = \sum_1^n |x_i - y_i|$$

```
data_abs = tf.math.abs(data1_tile - data2)
errors = tf.math.reduce_sum(data_abs, axis=1)
```

### Cosine Similarity


$$cs(\vec{x}, \vec{y}) = \frac{\vec{x} \cdot \vec{y}}{\|\vec{x}\| \|\vec{y}\|} = \frac{\sum_1^n x_i y_i}{\sqrt{\sum_1^n x_i^2} \sqrt{\sum_1^n y_i^2}}$$

```
data1 = np.reshape(data1, (1, -1))
data2 = np.reshape(data2, (N, -1))
sims = cosine_similarity(data1, data2)
```

# Image Retrieval

## ❖ Save features

### Database



# Image Retrieval

## ❖ Pre-trained models with different sizes

### Database



# Outline

- **Vector and Matrix**
- **Cosine Similarity**
- **Implementation**
- **Case Studies**

# Mean

## Data

$$X = \{X_1, \dots, X_N\}$$

## Given the data

$$X = \{2, 8, 5, 4, 1, 8\}$$

$$N = 6$$

## Formula

$$\mu = \frac{1}{N} \sum_{i=1}^N X_i$$

$$\begin{aligned} \mu &= \frac{1}{N} \sum_{i=1}^N X_i = \frac{1}{6} (2 + 8 + 5 + 4 + 1 + 8) \\ &= \frac{18}{6} = 3 \end{aligned}$$



# Mean

## ❖ Code

```
1. def calculate_mean(numbers): #1
2.     s = sum(numbers) #2
3.     N = len(numbers) #3
4.     mean = s/N #4
5.     return mean #5
6.
7. # Tạo mảng donations đại diện cho số tiền quyên góp trong 12 ngày
8. donations = [100, 60, 70, 900, 100, 200, 500, 500, 503, 600, 1000, 1200]
9.
10. mean_value = calculate_mean(donations)
11. print('Trung bình số tiền quyên góp là: ', mean_value)
```

#1. Đặt tên là calculate\_mean(), hàm này sẽ nhận đối số numbers, là chuỗi các số cần tính trung bình.

#2. Sử dụng hàm sum() để tính tổng dãy số cho trước.

#3. Sử dụng hàm len() để tính chiều dài của dãy số cần tính.

#4. Tính trung bình của dãy số trên bằng cách lấy tổng chia cho chiều dài.

#5. Cuối cùng ta cho hàm trả về giá trị mean tính được.

# Median

## Data

$$X = \{X_1, \dots, X_N\}$$

## Formula

Step 1: Sort  $X \rightarrow S$

Step 2

If  $N$  is odd, then  $m = S_{\left(\frac{N+1}{2}\right)}$

If  $N$  is even, then  $m = \left(S_{\left(\frac{N}{2}\right)} + S_{\left(\frac{N}{2}+1\right)}\right) / 2$

## Given the data

$$X = \{2, 8, 5, 4, 1\}$$

$$N = 5$$

Step 1

$$S = \{1, 2, 4, 5, 8\}$$

1   2   3   4   5

Step 2;  $N = 5$

$$k = \frac{N + 1}{2} = 3$$

$$m = S_k = 4$$

# Median

## Data

$$X = \{X_1, \dots, X_N\}$$

## Formula

Step 1: Sort  $X \rightarrow S$

Step 2

If  $N$  is odd, then  $m = S_{\left(\frac{N+1}{2}\right)}$

If  $N$  is even, then  $m = \left(S_{\left(\frac{N}{2}\right)} + S_{\left(\frac{N}{2}+1\right)}\right) / 2$

## Given the data

$$X = \{2, 8, 5, 4, 1, 8\}$$

$$N = 6$$

Step 1

$$S = \{1, 2, 4, 5, 8, 8\}$$

1   2   3   4   5   6

Step 2;  $N = 6$

$$\begin{aligned} m &= \frac{S_3 + S_4}{2} \\ &= \frac{4 + 5}{2} = 4.5 \end{aligned}$$

# Median

## ❖ Code

```
1.  def calculate_median(numbers): #1
2.      N = len(numbers) #2
3.      numbers.sort() #3
4.      if N%2 == 0: #4
5.          m1 = N/2
6.          m2 = (N/2) + 1
7.          m1 = int(m1)-1
8.          m2 = int(m2)-1
9.          median = (numbers[m1] + numbers[m2])/2
10.     else: #5
11.         m = (N+1)/2
12.         m = int(m)-1
13.         median = numbers[m]
14.     return median #6
```

# Mean and Median

## ❖ Comparison

### ❖ Noise

#### Data

$$X = \{X_1, \dots, X_N\}$$

#### Formula

$$\mu = \frac{1}{N} \sum_{i=1}^N X_i$$

#### Formula

Step 1: Sort  $X \rightarrow S$

Step 2

If  $N$  is odd, then  $m = S_{\left(\frac{N+1}{2}\right)}$

If  $N$  is even, then  $m = \left(S_{\left(\frac{N}{2}\right)} + S_{\left(\frac{N}{2}+1\right)}\right) / 2$

# Mean and Median

## ❖ Comparison

### ❖ Image denoising

#### Data

$$X = \{X_1, \dots, X_N\}$$

#### Formula

$$\mu = \frac{1}{N} \sum_{i=1}^N X_i$$

#### Formula

Step 1: Sort  $X \rightarrow S$

Step 2

If  $N$  is odd, then  $m = S_{\left(\frac{N+1}{2}\right)}$

If  $N$  is even, then  $m = \left(S_{\left(\frac{N}{2}\right)} + S_{\left(\frac{N}{2}+1\right)}\right) / 2$


# Mode

## ❖ Code

```
1. # import packages Counter để đếm số lần xuất hiện của mỗi giá trị trong chuỗi
2. from collections import Counter
3.
4. # data
5. points = [7, 8, 9, 2, 10, 9, 9, 9, 9, 4, 5, 6, 1, 5, 6, 7, 8, 6, 1, 10]
6.
7. def calculate_mode(numbers): #1
8.     c = Counter(numbers)      #2
9.     mode = c.most_common(1)   #3
10.    return mode[0][0]          #4
11.
12. print('Mode của chuỗi số đã cho: ', calculate_mode(points))
```

# Range

## ❖ Procedure



```
1. def find_range(numbers):          #1
2.     lowest = min(numbers)         #2
3.     highest = max(numbers)        #3
4.     r = highest-lowest             #4
5.     print('Lowest: {0}\tHighest: {1}\tRange: {2}'.format(lowest, highest, r))
6.
7. # data
8. points = [7, 8, 9, 2, 10, 9, 9, 9, 9, 4, 5, 6, 1, 5, 6, 7, 8, 6, 1, 10, 6, 6]
9. find_range(points)
```



# Variance

**Formula:**  $X_{norm} = \frac{X - \mu}{\sigma}$

**mean**  $\mu = \frac{1}{n} \sum_{k=1}^n x_i$

**variance**  $var(X) = \frac{1}{n} \sum_{k=1}^n (x_i - \mu)^2$

**Standard deviation**  $\sigma = \sqrt{var(X)}$

**Example:**  $X = \{5, 3, 6, 7, 4\}$

$$\mu = \frac{1}{5} \sum_{k=1}^n (5 + 3 + 6 + 7 + 4) = \frac{25}{5} = 5$$

$$\begin{aligned} var(X) &= \frac{1}{5} [(5 - 5)^2 + (3 - 5)^2 + (6 - 5)^2 + \\ &\quad (7 - 5)^2 + (4 - 5)^2] \\ &= \frac{1}{5} (0 + 4 + 1 + 4 + 1) = 2 \end{aligned}$$

$$\sigma = \sqrt{var(X)} = 1.41$$

$$X_{norm} = \frac{X - 5}{1.41} = \{5, 3, 6, 7, 4\}$$

**Variance  $var(X)$  xác định độ phân tán dữ liệu so với giá trị trung bình  $\mu$**

**mean**  $\mu = \frac{1}{n} \sum_{k=1}^n x_i$

**variance**  $var(X) = \frac{1}{n} \sum_{k=1}^n (x_i - \mu)^2$

**standard deviation**  $std(X) = \sqrt{var(X)}$

**Ví dụ:**  $X = \{5, 3, 6, 7, 4\}$


$$\mu = \frac{1}{5} \sum_{k=1}^n (5 + 3 + 6 + 7 + 4) = \frac{25}{5} = 5$$

$$var(X) = \frac{1}{5} [(5 - 5)^2 + (3 - 5)^2 + (6 - 5)^2 + (7 - 5)^2 + (4 - 5)^2]$$

$$= \frac{1}{5} (0 + 4 + 1 + 4 + 1) = 2$$

$$std(X) = \sqrt{var(X)} = 1.41$$

**Quan sát một mảng các giá trị pixel.**



# Variance

Ứng dụng tính chất của variance (~standard deviation) để tìm texture cho một hình



Ảnh gốc

Tính standard deviation  
cục bộ cho từng pixel.



Ảnh thông tin texture

# Variance

## ❖ Code

```
def calculate_mean(numbers): #1
    s = sum(numbers)
    N = len(numbers)
    mean = s/N
    return mean

def caculate_variance(numbers): #2
    mean = calculate_mean(numbers) #3

    diff = [] #4
    for num in numbers:
        diff.append(num-mean)

    squared_diff = [] #5
    for d in diff:
        squared_diff.append(d**2)
    sum_squared_diff = sum(squared_diff)
    variance = sum_squared_diff/len(numbers)

    return variance
```

# Hệ số tương quan (correlation coefficient)

**Công thức:** Gọi  $x, y$  là hai biến ngẫu nhiên

$$\begin{aligned}\rho_{xy} &= \frac{E[(x - \mu_x)(y - \mu_y)]}{\sqrt{\text{var}(x)}\sqrt{\text{var}(y)}} \\ &= \frac{n(\sum_i x_i y_i) - (\sum_i x_i)(\sum_i y_i)}{\sqrt{n \sum_i x_i^2 - (\sum_i x_i)^2} \sqrt{n \sum_i y_i^2 - (\sum_i y_i)^2}}\end{aligned}$$

**Tính chất 1**

$$\begin{array}{ccc} -1 & \leq & \rho_{xy} \leq 1 \\ \longleftarrow & & \longrightarrow \\ \text{Tương quan} & & \text{Tương quan} \\ \text{nghịch} & & \text{thuận} \end{array}$$

**Tính chất 2**

$$\rho_{xy} = \rho_{uv}$$

trong đó

$$\begin{aligned}u &= ax + b \\ v &= cy + d\end{aligned}$$

**Ví dụ 1**

$$x = [7, 18, 29, 2, 10, 9, 9]$$

$$y = [1, 6, 12, 8, 6, 21, 10]$$

$$\begin{aligned}\rho_{xy} &= \frac{E[(x - \mu_x)(y - \mu_y)]}{\sqrt{\text{var}(x)}\sqrt{\text{var}(y)}} \\ &= \frac{n * 818 - 84 * 64}{\sqrt{n * 1480 - 7056} \sqrt{n * 822 - 4096}} = 0.149\end{aligned}$$

**Ví dụ 2**

$$u = 2 * x - 14 = [0, 22, 44, -10, 6, 4, 4]$$

$$v = y + 2 = [3, 8, 14, 10, 8, 23, 12]$$

$$\begin{aligned}\rho_{uv} &= \frac{E[(u - \mu_u)(v - \mu_v)]}{\sqrt{\text{var}(u)}\sqrt{\text{var}(v)}} \\ &= \frac{n * 880 - 70 * 78}{\sqrt{n * 2588 - 4900} \sqrt{n * 1106 - 6084}} = 0.149\end{aligned}$$

# Correlation Coefficient

```
def find_corr_x_y(x,y):                                     #1
    n = len(x)                                             #2
    prod = []
    for xi,yi in zip(x,y):                                #3
        prod.append(xi*yi)

    sum_prod_x_y = sum(prod)                               #4

    sum_x = sum(x)
    sum_y = sum(y)

    squared_sum_x = sum_x**2
    squared_sum_y = sum_y**2

    x_square = []
    for xi in x:
        x_square.append(xi**2)
    x_square_sum = sum(x_square)

    y_square=[]
    for yi in y:
        y_square.append(yi**2)
    y_square_sum = sum(y_square)

    # Use formula to calculate correlation                  #5
    numerator = n*sum_prod_x_y - sum_x*sum_y
    denominator_term1 = n*x_square_sum - squared_sum_x
    denominator_term2 = n*y_square_sum - squared_sum_y
    denominator = (denominator_term1*denominator_term2)**0.5
    correlation = numerator/denominator

    return correlation
```

# Image Retrieval

## ❖ Cost Functions

```
from scipy.stats.stats import pearsonr

sim_list = []
for i in range(9908):
    sim = pearsonr(pred_query[0], pred_data[i])
    sim_list.append(sim)
print(len(sim_list))
```

9908





