Data preparation, screening and human verification

Journal source records
65,290 | 88 journals | 1989–2025

Conference source records
23,793 | 22 programs | 2005–2026

Data cleaning
1,486 duplicate indices excluded
After deduplication: 63,804
1 insufficient abstract excluded

Data cleaning
21 duplicate indices excluded
After deduplication: 23,772
No insufficient abstract exclusions

Eligible journal records
J = 63,803

Eligible conference abstracts
C = 23,772

Dual-model title and abstract screening
Same codebook and seven labels; INDIVIDUAL or CLUSTER = RCT

Both classify as RCT
J = 382
C = 531

One classifies as RCT
J = 70
C = 55

Both classify as non-RCT
J = 63,351
C = 23,186

Human verification: all
J: 382 reviewed
372 RCT; 10 non-RCT
C: 531 reviewed
527 RCT; 4 non-RCT

Human review: all
J: 70 reviewed
10 RCT; 60 non-RCT
C: 55 reviewed
28 RCT; 27 non-RCT

Targeted human sample
Score / keyword candidate pools
J 286: 2 RCT; 284 non-RCT
C 288: 4 RCT; 284 non-RCT
Additional review: J 1 non-RCT
Unreviewed remain excluded:
J 63,064; C 22,898

RCTs

RCTs

RCTs

Final human-confirmed RCT reports
J: 372 + 10 + 2 = 384 / 63,803 eligible records
C: 527 + 28 + 4 = 559 / 23,772 eligible abstracts

Descriptive analyses and rates
Overall, annual, period, journal and format
Use all eligible records as denominators

Conference–journal linkage
559 eligible conference reports
against all 63,803 eligible journal records

Verification source worklist: 1,622; after cleaning: 1,612 (J 738; C 874). Disputed cases received author adjudication.
The additional journal non-RCT is outside that sample. J = journal records; C = conference abstracts.
This is the final analytical data flow; original model calls covered the complete source extracts.
Targeted negative-sample verification does not estimate whole-pool sensitivity or NPV.