



PUC Minas

Apache PIG




Diego Roberto Gonçalves de Pontes

Apache PIG

- Plataforma para Análise de Grandes Volumes de Dados.
 - Linguagem de alto nível: Pig Latin
 - Infraestrutura de execução de programas
- Funcionalidades
 - Geração automática de programas
 - MapReduce
 - Otimização de execução
 - Compilação em tempo de execução

Apache PIG

- “Problema: Suponha que você tenha dados dos seus usuários em um arquivo, logs de acesso a sites em outro, e você quer saber quais são os 5 sites mais visitados por usuários com idades entre 18 e 25 anos.”



Código MapReduce

```
import java.io.IOException;
import java.util.ArrayList;
import java.util.Iterator;
import java.util.List;

import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.LongWritable;
import org.apache.hadoop.io.Text;
import org.apache.hadoop.io.Writable;
import org.apache.hadoop.io.WritableComparable;
import org.apache.hadoop.mapred.FileInputFormat;
import org.apache.hadoop.mapred.FileOutputFormat;
import org.apache.hadoop.mapred.JobConf;
import org.apache.hadoop.mapred.KeyValueTextInputFormat;
import org.apache.hadoop.mapred.Mapper;
import org.apache.hadoop.mapred.MapReduceBase;
import org.apache.hadoop.mapred.OutputCollector;
import org.apache.hadoop.mapred.RecordReader;
import org.apache.hadoop.mapred.Reducer;
import org.apache.hadoop.mapred.Reporter;
import org.apache.hadoop.mapred.SequenceFileInputFormat;
import org.apache.hadoop.mapred.SequenceFileOutputFormat;
import org.apache.hadoop.mapred.TextInputFormat;
import org.apache.hadoop.mapred.JobControl.Job;
import org.apache.hadoop.mapred.JobControl.JobControl;
import org.apache.hadoop.mapred.lib.IdentityMapper;

public class MRExample {
    public static class LoadPages extends MapReduceBase
        implements Mapper<LongWritable, Text, Text, Text> {

        public void map(LongWritable k, Text val,
            OutputCollector<Text, Text> oc,
            Reporter reporter) throws IOException {
            // Pull the key out
            String line = val.toString();
            int firstComma = line.indexOf(',');
            String key = line.substring(0, firstComma);
            String value = line.substring(firstComma + 1);
            Text outKey = new Text(key);
            // Prepend an index to the value so we know which file
            // it came from.
            Text outVal = new Text("1 * " + value);
            oc.collect(outKey, outVal);
        }

        public static class LoadAndFilterUsers extends MapReduceBase
            implements Mapper<LongWritable, Text, Text, Text> {

        public void map(LongWritable k, Text val,
            OutputCollector<Text, Text> oc,
            Reporter reporter) throws IOException {
            // Pull the key out
            String line = val.toString();
            int firstComma = line.indexOf(',');
            String value = line.substring(firstComma + 1);
            int age = Integer.parseInt(value);
            if (age < 18 || age > 25) return;
            String key = line.substring(0, firstComma);
            Text outKey = new Text(key);
            // Prepend an index to the value so we know which file
            // it came from.
            Text outVal = new Text("2 * " + value);
            oc.collect(outKey, outVal);
        }

        public static class Join extends MapReduceBase
            implements Reducer<Text, Text, Text, Text> {

        public void reduce(Text key,
            Iterator<Text> iter,
            OutputCollector<Text, Text> oc,
            Reporter reporter) throws IOException {
            // For each value, figure out which file it's from and
            // accordingly.
            List<String> first = new ArrayList<String>();
            List<String> second = new ArrayList<String>();

            while (iter.hasNext()) {
                Text t = iter.next();
            }
        }
    }
}
```

```
        reporter.setStatus("OK");
    }

    // Do the cross product and collect the values
    for (String s1 : first) {
        for (String s2 : second) {
            String outVal = key + "," + s1 + "," + s2;
            oc.collect(null, new Text(outVal));
            reporter.setStatus("OK");
        }
    }
}

public static class LoadJoined extends MapReduceBase
    implements Mapper<Text, Text, Text, LongWritable> {

    public void map(
        Text k,
        Text val,
        OutputCollector<Text, LongWritable> oc,
        Reporter reporter) throws IOException {
        // Find the url
        String line = val.toString();
        int firstComma = line.indexOf(',');
        int secondComma = line.indexOf(',', firstComma);
        String key = line.substring(firstComma, secondComma);
        // drop the rest of the record, I don't need it anymore,
        // just pass a 1 for the combiner/reducer to sum instead.
        Text outKey = new Text(key);
        oc.collect(outKey, new LongWritable(1L));
    }

    public static class ReduceUrls extends MapReduceBase
        implements Reducer<Text, LongWritable, WritableComparable,
        Writable> {

        public void reduce(
            Text key,
            Iterator<LongWritable> iter,
            OutputCollector<WritableComparable, Writable> oc,
            Reporter reporter) throws IOException {
            // Add up all the values we see

            long sum = 0;
            while (iter.hasNext()) {
                sum += iter.next().get();
                reporter.setStatus("OK");
            }

            oc.collect(key, new LongWritable(sum));
        }

        public static class LoadClicks extends MapReduceBase
            implements Mapper<WritableComparable, Writable, LongWritable,
            Text> {

        public void map(
            WritableComparable key,
            Writable val,
            OutputCollector<LongWritable, Text> oc,
            Reporter reporter) throws IOException {
            oc.collect((LongWritable)val, (Text)key);
        }

        public static class LimitClicks extends MapReduceBase
            implements Reducer<LongWritable, Text, LongWritable, Text> {

            int count = 0;

            public void reduce(
                LongWritable key,
                Iterator<Text> iter,
                OutputCollector<LongWritable, Text> oc,
                Reporter reporter) throws IOException {

                // Only output the first 100 records
                while (count < 100 && iter.hasNext()) {
                    oc.collect(key, iter.next());
                    count++;
                }
            }
        }
    }
}
```

```
        lp.setOutputKeyClass(Text.class);
        lp.setOutputValueClass(Text.class);
        lp.setMapperClass(LoadPages.class);
        FileInputFormat.addInputPath(lp, new
            Path("/user/gates/pages*"));
        FileOutputFormat.setOutputPath(lp,
            new Path("/user/gates/tmp/indexed_pages*"));
        lp.setNumReduceTasks(0);
        Job loadPages = new Job(lp);

        JobConf lfu = new JobConf(MRExample.class);
        lfu.setJobName("Load and Filter Users");
        lfu.setInputFormat(TextInputFormat.class);
        lfu.setOutputKeyClass(Text.class);
        lfu.setOutputValueClass(Text.class);
        lfu.setMapperClass(LoadAndFilterUsers.class);
        FileInputFormat.addInputPath(lfu, new
            Path("/user/gates/users*"));
        FileOutputFormat.setOutputPath(lfu,
            new Path("/user/gates/tmp/filtered_users*"));
        lfu.setNumReduceTasks(0);
        Job loadUsers = new Job(lfu);

        JobConf join = new JobConf(MRExample.class);
        join.setJobName("Join Users and Pages");
        join.setInputFormat(KeyValueTextInputFormat.class);
        join.setOutputKeyClass(Text.class);
        join.setOutputValueClass(Text.class);
        join.setMapperClass(IdentityMapper.class);
        join.setReducerClass(Join.class);
        FileInputFormat.addInputPath(join, new
            Path("/user/gates/tmp/indexed_pages*"));
        FileInputFormat.addInputPath(join, new
            Path("/user/gates/tmp/filtered_users*"));
        FileOutputFormat.setOutputPath(join, new
            Path("/user/gates/tmp/joined*"));
        join.setNumReduceTasks(50);
        Job joinJob = new Job(join);
        joinJob.addDependingJob(loadPages);
        joinJob.addDependingJob(loadUsers);

        JobConf group = new JobConf(MRExample.class);
        group.setJobName("Group URLs");
        group.setInputFormat(KeyValueTextInputFormat.class);
        group.setOutputKeyClass(Text.class);
        group.setOutputValueClass(LongWritable.class);
        group.setOutputFormat(SequenceFileOutputFormat.class);
        group.setMapperClass(LoadJoined.class);
        group.setCombinerClass(ReduceUrls.class);
        group.setReducerClass(ReduceUrls.class);
        FileInputFormat.addInputPath(group, new
            Path("/user/gates/tmp/joined*"));
        FileOutputFormat.setOutputPath(group, new
            Path("/user/gates/tmp/grouped*"));
        group.setNumReduceTasks(50);
        Job groupJob = new Job(group);
        groupJob.addDependingJob(joinJob);

        JobConf top100 = new JobConf(MRExample.class);
        top100.setJobName("Top 100 sites");
        top100.setInputFormat(SequenceFileInputFormat.class);
        top100.setOutputKeyClass(LongWritable.class);
        top100.setOutputValueClass(Text.class);
        top100.setMapperClass(LoadClicks.class);
        top100.setOutputFormat(SequenceFileOutputFormat.class);
        top100.setMapperClass(LoadClicks.class);
        top100.setCombinerClass(LimitClicks.class);
        top100.setReducerClass(LimitClicks.class);
        FileInputFormat.addInputPath(top100, new
            Path("/user/gates/tmp/grouped*"));
        FileOutputFormat.setOutputPath(top100, new
            Path("/user/gates/top100sitesforusers18to25*"));
        top100.setNumReduceTasks(1);
        Job limit = new Job(top100);
        limit.addDependingJob(groupJob);

        JobControl jc = new JobControl("Find top 100 sites for users
            18 to 25");
        jc.addJob(loadPages);
        jc.addJob(loadUsers);
        jc.addJob(joinJob);
        jc.addJob(groupJob);
    }
}
```



Mesmo código em Pig Latin

```
Users = load `users' as (name, age);  
Fltrd = filter Users by age >= 18 and age <= 25;  
Pages = load `pages' as (user, url);  
Jnd = join Fltrd by name, Pages by user;  
Grpd = group Jnd by url;  
Smmd = foreach Grpd generate group,  
COUNT(Jnd) as clicks;  
Srtd = order Smmd by clicks desc;  
Top5 = limit Srtd 5;  
store Top5 into `top5sites';
```

Execução

- Ao executar o script Pig, a plataforma se encarrega de:
- fazer o parse do arquivo
- verificar erros de sintaxe
- otimizar o código do script
- criar um plano de execução — quais tarefas Map e Reduce serão necessárias e qual a melhor ordem para executá-las?
- enviar todos os arquivos necessários para o HDFS
- monitorar os processos em execução

Onde é usado:

- Processamento de logs de servidores web
- Construção de modelos de predição de comportamento de usuários
- Processamento de imagens
- Construção de índices de páginas da web
- Pesquisa em conjuntos de dados “brutos”

Código PIG – Filmes 5 estrelas por ordem de lançamento

```
ratings = LOAD '/user/maria_dev/ml-100k/u.data' AS (userID:int, movieID:int, rating:int, ratingTime:int);

metadata = LOAD '/user/maria_dev/ml-100k/u.item' USING PigStorage('|')
  AS (movieID:int, movieTitle:chararray, releaseDate:chararray, videoRealese:chararray, imdblink:chararray)

nameLookup = FOREACH metadata GENERATE movieID, movieTitle,
  ToUnixTime(ToDate(releaseDate, 'dd-MMM-yyyy')) AS releaseTime;

ratingsByMovie = GROUP ratings BY movieID;
avgRatings = FOREACH ratingsByMovie GENERATE group as movieID, AVG(ratings.rating) as avgRating;
fiveStarMovies = FILTER avgRatings BY avgRating > 4.0;
fiveStarsWithData = JOIN fiveStarMovies BY movieID, nameLookup BY movieID;
oldestFiveStarMovies = ORDER fiveStarsWithData BY nameLookup::releaseTime;
DUMP oldestFiveStarMovies;
```


Saída

```
2024-07-20 01:02:56,917 [main] INFO org.apache.hadoop.mapreduce.lib.input.FileInputFormat - Total input files to process : 1
2024-07-20 01:02:56,917 [main] INFO org.apache.pig.backend.hadoop.executionengine.util.MapRedUtil - Total input paths to process : 1
(493,4.15,493,Thin Man, The (1934),-1136073600)
(604,4.012345679012346,604,It Happened One Night (1934),-1136073600)
(615,4.0508474576271185,615,39 Steps, The (1935),-1104537600)
(1203,4.0476190476190474,1203,Top Hat (1935),-1104537600)
(613,4.037037037037037,613,My Man Godfrey (1936),-1073001600)
(633,4.057971014492754,633,Christmas Carol, A (1938),-1009843200)
(132,4.0772357723577235,132,Wizard of Oz, The (1939),-978307200)
(1122,5.0,1122,They Made Me a Criminal (1939),-978307200)
(136,4.123809523809523,136,Mr. Smith Goes to Washington (1939),-978307200)
(478,4.115384615384615,478,Philadelphia Story, The (1940),-946771200)
(524,4.021739130434782,524,Great Dictator, The (1940),-946771200)
(484,4.2101449275362315,484,Maltese Falcon, The (1941),-915148800)
(134,4.292929292929293,134,Citizen Kane (1941),-915148800)
(483,4.45679012345679,483,Casablanca (1942),-883612800)
(659,4.078260869565217,659,Arsenic and Old Lace (1944),-820540800)
(611,4.1,611,Laura (1944),-820540800)
```

Exemplo Filmes100Mais

```
ratings = LOAD '/user/maria_dev/ml-100k/u.data' AS (userID:int, movieID:int, rating:int, ratingTime:int);

metadata = LOAD '/user/maria_dev/ml-100k/u.item' USING PigStorage('|')
           AS (movieID:int, movieTitle:chararray, releaseDate:chararray, videoRelease:chararray, imdbLink:chararray);

-- Contar o número de avaliações por filme
ratingsByMovie = GROUP ratings BY movieID;
movieRatingCount = FOREACH ratingsByMovie GENERATE group AS movieID, COUNT(ratings) AS ratingCount;

-- Filtrar filmes com mais de 100 avaliações
popularMovies = FILTER movieRatingCount BY ratingCount > 100;

-- Juntar com metadados para obter títulos
popularMoviesWithData = JOIN popularMovies BY movieID, metadata BY movieID;

-- Ordenar por contagem de avaliações
orderedPopularMovies = ORDER popularMoviesWithData BY ratingCount DESC;

-- Exibir resultado
DUMP orderedPopularMovies;
```

Exemplo FilmesRecentes

```
ratings = LOAD '/user/maria_dev/u.data' AS (userID:int, movieID:int, rating:int, ratingTime:int);

metadata = LOAD '/user/maria_dev/u.item' USING PigStorage('|')
           AS (movieID:int, movieTitle:chararray, releaseDate:chararray, videoRelease:chararray, imdbLink:chararray);

-- Converter datas e filtrar lançamentos dos últimos 5 anos
recentMovies = FOREACH metadata GENERATE movieID, movieTitle,
                                         ToUnixTime(ToDate(releaseDate, 'dd-MMM-yyyy')) AS releaseTime;
recentMoviesFiltered = FILTER recentMovies BY releaseTime >= ToUnixTime(ToDate('01-JAN-2015', 'dd-MMM-yyyy'));

-- Agrupar avaliações por filme
ratingsByMovie = GROUP ratings BY movieID;
avgRatings = FOREACH ratingsByMovie GENERATE group AS movieID, AVG(ratings.rating) AS avgRating;

-- Filtrar filmes com média de avaliação superior a 4
highRatedMovies = FILTER avgRatings BY avgRating > 4.0;

-- Juntar dados de avaliações com metadados
highRatedRecentMovies = JOIN highRatedMovies BY movieID, recentMoviesFiltered BY movieID;

-- Ordenar por data de lançamento
orderedHighRatedRecentMovies = ORDER highRatedRecentMovies BY releaseTime DESC;

-- Exibir resultado
DUMP orderedHighRatedRecentMovies;
```



PUC Minas