

Commercial & Industrial ESS

Air-cooled Energy Cube Storage Solution

105kW/241kWh



High level of integration

Highly integrated, small footprint
A single cabinet covers an area of less than 2



Safe and reliable

High strength cabinet
Active safety protection system



Strong expansibility

Flexible capacity expansion and on-demand configuration
Supports simultaneous use of multiple devices



Intelligent control strategy

Cloud remote operation and maintenance, 7x24 hours real-time monitoring
Adaptive charging and discharging strategy, improve economic benefits

Product Parameter

The new upgrade of Energy Cube 3.0 can provide users with a better energy storage experience, optimize the internal structure design on the basis of the highly integrated system, select high-quality batteries and integrate the battery management system, energy control system, AC/DC bidirectional converter, temperature control and fire control system into one. It has the advantages of high efficiency, low noise, safety, reliability and easy expansion, and higher safety and redundancy design, so that it can meet the energy storage application needs of charging stations, commercial buildings, manufacturing and other scenarios.

DC Parameter			
Battery Type	LFP	Operating Voltage Range	672V-864V
Combination Mode	1P240S	Cooling Mode	forced air cooling
Rated Capacity	314Ah	Cycle Number	6,000 times
Rated Energy	241kWh	Fire Protection System	Aerosol Extinguishing
Rated Voltage	768V	Detector Type	Temperature /Smoke Sensor /
Rated Power	105kW		WaterLeak
Rated charge and discharge ratio	0.5P		

AC Parameter	
Rated AC power	105kW
Rated voltage	230V/400V
Grid Frequency	50Hz/60Hz±2.5Hz
Maximum output current	167A
Power factor	0.99

System Parameter	
Operating environment	--20°C~50°C(> 45°C derating)
Noise	≤75dB
Size (W*D* H)mm	1200*1553*2310
Weight	About 2.4t
Waterproof class	IP54
Allowable relative humidity	0-95% (no condensation)
Allowable altitude	≤2000m (degraded above 2000m)
Communication interface	CAN, Ethernet
Communication protocol	ModbusTCP/RTU
system operation mode	Peak shaving, valley filing, demand control, economic operation mode, reactive power regulation, power grid dispatching interface
Certification	Remote scheduling interface, local data storage, anti-backflow function IEC62619;UL1973;UL9540A