

NEXGUARD

AI-Powered Military Base Security, Surveillance & Infrastructure Resilience System

Project Category: IoT + Artificial Intelligence + Edge Computing + Multi-Sensor
Fusion + Smart Surveillance + Structural Health Monitoring + Resilient
Communications + Black Box Incident Recording

Prepared By: Ertiza Azamain Luban

Prototype Type: Demonstration-Scale Full-Base Prototype

Report Date: September 2026

1. EXECUTIVE SUMMARY

NEXGUARD is an integrated AI-assisted security, surveillance, safety, infrastructure-monitoring and incident-recording platform designed to monitor a complete military-base environment through distributed sensors, cameras, edge computing, artificial intelligence and resilient communications.

The system divides the base into six major functional zones: Outer Perimeter; Jungle / Remote Terrain; Camps / Outposts; Internal Base; HQ / Command Center; and Critical Buildings.

Sensors and cameras continuously collect information from these areas. ESP32-based sensor nodes perform local acquisition and basic preprocessing. Remote telemetry can be transmitted through LoRa, while cameras and other high-bandwidth systems can use the local Ethernet/Wi-Fi network.

At the center of the system is the NVIDIA Jetson Orin Nano Super, which functions as the primary edge-AI computer for the prototype.

The core intelligence pipeline is: Sense → AI Monitor → Verify → Fuse → Assess → Alert → Record → Replay.

The AI Monitoring layer analyzes camera data, thermal patterns, motion events, environmental conditions, structural vibration and system-health information. These inputs can then be combined through a Multi-Sensor AI Fusion Engine to create more meaningful and explainable events.

The Black Box acts as the system memory by recording timestamps, telemetry, alerts, system-health data and incident metadata so that an event can later be reconstructed. The structural/seismic subsystem is limited to critical-building resilience and structural-health monitoring; it is not the primary mission of the overall security system.

PROJECT PHILOSOPHY: The system does not simply collect data. It senses, monitors with AI, correlates, prioritizes, records and explains.

2. PROJECT OBJECTIVES

- Create one platform capable of combining security, environmental, structural and infrastructure information.
- Use AI to analyze camera and sensor information and identify unusual patterns.
- Correlate multiple independent information sources rather than relying on isolated triggers.
- Maintain local monitoring and recording during temporary network or Internet failures.
- Preserve an auditable record of important events and enable incident replay.
- Monitor critical buildings for structural, environmental and power-related anomalies.
- Present the overall base through an interactive C2 dashboard and 3D digital twin.

3. WHAT PROBLEM DOES NEXGUARD SOLVE?

- Independent sensors create fragmented information.
- Single-sensor alarms can generate excessive false positives.
- Remote zones may have limited connectivity or power.
- Infrastructure conditions may not be monitored alongside security events.
- Historical events may be difficult to reconstruct.
- Operators may not have one unified view of the entire system.

NEXGUARD addresses these limitations by integrating sensing, AI Monitoring, sensor fusion, risk assessment, operator visualization and Black Box recording into one architecture.

4. FULL-BASE COVERAGE

Zone	Primary Purpose	Main Hardware	AI Role
Outer Perimeter	Defensive movement/event awareness	IP/IR Camera, AMG8833, HB100X, ESP32, LoRa	Visual + thermal + motion correlation
Jungle / Remote	Low-power remote anomaly monitoring	PIR, HB100X, DHT22, ESP32, LoRa, solar/battery	Pattern analysis and anomaly detection
Camps / Outposts	Local security + safety	Camera, PIR, DHT22, MQ-2, ESP32, relay, alarm	Visual + motion + environmental fusion
Internal Base	Internal-area monitoring	IP Cameras, motion sensing, ESP32, LAN	Video analytics + anomaly monitoring
HQ / C2	Central AI processing and visualization	Jetson, C2 display, local network, Black Box	Primary AI and fusion processing
Critical Buildings	Structural + environmental resilience	ADXL355, DHT22, AMG8833, MQ-2, camera, UPS	Structural/environmental anomaly analysis

5. COMPLETE HARDWARE INVENTORY

Component	What it is	Why used	Main job	Where used
ESP32 DevKitC WROOM-32E	Microcontroller	Controls sensor nodes	Read, filter, transmit	Remote nodes / buildings
NVIDIA Jetson Orin Nano Super	Edge-AI computer	Central processing	Vision + analytics + fusion	HQ/C2
ADXL355	3-axis accelerometer	Structural monitoring	Vibration analysis	Critical buildings
AMG8833	IR thermal array	Thermal verification	Heat-pattern sensing	Perimeter / buildings
DHT22	Temp/humidity sensor	Environmental context	Temperature/humidity	Remote / camps / buildings
MQ-2	Gas/smoke prototype sensor	Safety monitoring	Smoke/gas indication	Camps / buildings
HC-SR501 PIR	PIR motion sensor	Low-power sensing	Motion trigger	Jungle / camps
HB100X	Microwave Doppler sensor	Additional motion evidence	Motion indication	Remote / perimeter prototype
Outdoor IP/IR Camera	Network camera	Visual monitoring	Video + AI input	Outdoor/base areas
SX1278 LoRa	Radio module	Remote telemetry	Low-bandwidth communication	Remote nodes
DS3231 RTC	Real-time clock	Accurate timestamps	Event timing	Black Box / nodes
MicroSD + 128GB	Local storage	Offline recording	Event/data storage	Nodes / Black Box
Relay	Switching module	Safety outputs	Approved device switching	Camps / buildings
Alarm/Strobe	Local indicator	Emergency notification	Audio/visual indication	Selected zones
Solar + Battery	Independent power	Remote autonomy	Power sensor nodes	Remote zones
Ethernet/Wi-Fi equipment	Network infrastructure	Data transfer	Camera/C2 networking	Base / HQ
UPS	Backup power	Continuity	Critical system backup	HQ / critical buildings
Enclosure/PCB/Wiring	Physical integration	Protection	Complete node assembly	All zones

6. ZONE-BY-ZONE SENSOR ASSIGNMENT

Zone	Sensors / Hardware	Function
Outer Perimeter	IP/IR Camera + AMG8833 + HB100X + ESP32 + LoRa	Visual, thermal and motion evidence; local node processing and remote telemetry
Jungle / Remote	PIR + HB100X + DHT22 + ESP32 + LoRa + Solar/Battery	Low-power remote monitoring and environmental context
Camps / Outposts	Camera + PIR + DHT22 + MQ-2 + Relay + Alarm	Local security and safety monitoring
Internal Base	Cameras + motion/presence + ESP32 + LAN	Internal-area surveillance and event awareness
HQ / C2	Jetson + network + Black Box + C2 display	AI processing, data fusion and visualization

Zone	Sensors / Hardware	Function
Critical Buildings	ADXL355 + DHT22 + MQ-2 + AMG8833 + Camera + UPS monitor	Structural, thermal, environmental and safety monitoring

7. HOW NEXGUARD WORKS

Real World → Sensors/Cameras → ESP32 Nodes → Local Filtering → LoRa/Ethernet/Wi-Fi → Jetson Edge AI → AI Monitoring → Sensor Fusion → Risk/Decision Engine → C2 Dashboard → Authorized Safety Response → Black Box → Incident Replay

The key design principle is that raw sensor triggers are not automatically treated as final conclusions. Instead, data are filtered, analyzed, correlated and presented with evidence so that operators can understand why an event was generated.

8. AI MONITORING LAYER

AI Monitoring is a central component of NEXGUARD. It is intentionally modular so that different analytical engines can be developed, tested and improved independently.

AI Vision Monitoring

- Processes camera streams on the Jetson.
- Can identify visual events, scene changes and anomalies.
- Can produce event metadata and selected evidence frames/clips.

AI Thermal Monitoring

- Analyzes AMG8833 thermal patterns.
- Looks for unusual local heat signatures and temporal changes.
- Provides supporting evidence for visual events.

AI Motion Analysis

- Uses PIR, microwave motion indication and camera-based motion information.
- Correlates timing and repeated activity patterns.

AI Environmental Monitoring

- Analyzes temperature, humidity and prototype smoke/gas signals.
- Builds normal environmental baselines and detects deviations.

AI Structural Monitoring

- Analyzes ADXL355 vibration measurements relative to a building baseline.
- Designed for selected critical buildings rather than base-wide earthquake surveillance.

AI System-Health Monitoring

- Monitors node availability, battery, storage, network and sensor status.
- Can generate system-health anomalies when a node behaves unexpectedly.


9. AI ANOMALY DETECTION

The prototype should collect normal operating data first. That normal data becomes a baseline. New readings are then compared against the baseline so the system can distinguish ordinary variation from significant deviation.



10. AI SENSOR FUSION ENGINE

Sensor fusion is one of the strongest features of the platform. It combines independent sources rather than evaluating each source in isolation.



The exact confidence model and thresholds must be experimentally developed and validated. No accuracy number should be claimed before testing.

11. EXPLAINABLE AI ALERTS

Instead of presenting only “ALERT”, the dashboard should show the evidence behind the event.

Field	Example
Event	Perimeter Anomaly
Evidence	Motion detected; visual change detected; thermal change detected; signals correlated in time
Confidence	High
Zone	Outer Perimeter
Node	NODE-03
Time	22:41:17

12. RISK / DECISION ENGINE

Recommended prototype states:

- NORMAL - no meaningful abnormality.
- ENVIRONMENTAL ANOMALY - environmental or infrastructure deviation.
- VERIFIED SAFETY EVENT - multiple sources provide correlated evidence.

- CRITICAL EMERGENCY - high-confidence, safety-critical event requiring immediate operator attention.

This is a decision-support layer. Critical physical actions remain subject to predefined safety rules and appropriate human authorization.

13. RESILIENT COMMUNICATION

Local Ethernet/Wi-Fi is intended primarily for cameras, Jetson, C2 and other high-bandwidth data. LoRa is intended primarily for low-bandwidth remote telemetry. The architecture is local-first so that loss of an external Internet connection does not automatically stop monitoring or recording.

Internet unavailable
Sensor → ESP32 → Local processing → Local storage → Local alert

Connection restored
Stored data → Store-and-forward → Central synchronization

14. CYBERSECURITY ARCHITECTURE

- Device identity for each node.
- Authentication of trusted devices.
- Message integrity checks.
- Authenticated encrypted communications appropriate to the final implementation.
- Role-based access control.
- Audit logging of important operator actions.
- Controlled firmware/software update process.

Exact cryptographic algorithms, key-management mechanisms and security certification should be specified separately for a real operational system.

15. BLACK BOX ARCHITECTURE

The Black Box is the permanent memory layer of NEXGUARD.

- Timestamps
- Sensor telemetry
- AI events
- Alerts
- Camera-event metadata
- Thermal events
- Structural measurements
- Network status
- Power status
- System health
- Operator acknowledgement

DS3231 provides the local time reference, while MicroSD and 128GB storage provide local persistence.

16. TAMPER-EVIDENT LOGGING

EVENT 001 → hash → EVENT 002 → hash → EVENT 003 → hash → EVENT 004

A future implementation can use hash chaining so that unauthorized modification of historical event records can be detected. This improves integrity but should not be described as absolutely tamper-proof.

17. INCIDENT REPLAY

Each significant incident should receive an Incident ID and a timeline that reconstructs the event.

```
T - 30 sec Normal
T - 10 sec Sensor deviation
T - 5 sec Camera anomaly
T AI fusion
T + 2 sec Operator alert
T + ... Operator acknowledgement
```

18. 3D DIGITAL BASE TWIN

The command interface can display a simplified 3D representation of the base using HTML, CSS, JavaScript, Three.js and WebGL.

- Base zones
- Buildings
- Sensor nodes
- Cameras
- Event markers
- Network state
- Power state
- AI alerts
- System-health indicators
- Incident history

19. AI-POWERED C2 DASHBOARD

- LIVE BASE VIEW - current status of all zones.
- AI MONITOR - current AI-generated events.
- SENSOR PANEL - live sensor readings.
- CAMERA PANEL - camera feeds and event snapshots.
- SYSTEM HEALTH - power, network, storage and node status.
- BLACK BOX - historical records.
- INCIDENT REPLAY - event timeline.
- 3D DIGITAL TWIN - spatial visualization.

20. SYSTEM SELF-DIAGNOSTICS

NEXGUARD should monitor its own health. A typical node heartbeat can contain node ID, battery, sensor status, storage, network state, last-seen time and firmware state.

```
NODE-07
Sensor Status: OK
Battery: 84%
Network: OK
Storage: 71%
```

21. STRUCTURAL & INFRASTRUCTURE RESILIENCE

Selected critical buildings can contain ADXL355, DHT22, MQ-2, AMG8833, an IP camera, ESP32 and UPS/power monitoring. The objective is to detect abnormal building/environment conditions and support maintenance and safety. Seismic sensing is a building-resilience feature, not the primary mission of the complete system.

22. CONCRETE PROTOTYPE IMPLEMENTATION PLAN

Phase	Deliverable
1	Create small six-zone physical demonstration environment
2	Build one standard ESP32 sensor node
3	Develop ESP32 firmware: acquisition, filtering, health, events, communication
4	Add DS3231 + MicroSD Black Box
5	Add SX1278 LoRa communication
6	Set up Jetson backend and local database
7	Implement AI Vision, Thermal, Sensor and Structural modules
8	Create normal baselines and anomaly detection
9	Build AI Sensor Fusion Engine
10	Build Risk / Decision Engine
11	Build C2 dashboard
12	Add Three.js 3D digital twin
13	Add incident logging and replay
14	Implement offline store-and-forward
15	Implement self-diagnostics and full integration

23. STANDARD SENSOR NODE IMPLEMENTATION

Sensor → ESP32 → Filtering → Event Generation → Local Logging → LoRa/LAN/Wi-Fi

The node firmware should validate readings, perform simple filtering, identify obvious sensor faults, create structured event packets and send periodic health information.

24. ESP32 FIRMWARE RESPONSIBILITIES

- Read sensors
- Validate readings
- Filter obvious noise
- Generate event records
- Monitor node health
- Timestamp records
- Write fallback data

- Transmit telemetry

Example event packet:
NODE_ID: NODE-03
ZONE: JUNGLE
TIME: 22:41:17
SENSOR: PIR
VALUE: MOTION
BATTERY: 84%
STATUS: EVENT

25. JETSON BACKEND IMPLEMENTATION

A practical prototype software stack can use Linux, Python, OpenCV, an AI inference framework, FastAPI or Flask, WebSockets, a local database and structured logging.

IP Camera → RTSP/Network Stream → Jetson → OpenCV → AI Model → Event Metadata → Fusion Engine

26. SOFTWARE ARCHITECTURE

```
NEXGUARD/  
├── firmware/  
│   ├── esp32_node/  
│   ├── sensor_drivers/  
│   └── communication/  
├── backend/  
│   ├── api/  
│   ├── events/  
│   ├── fusion/  
│   ├── risk_engine/  
│   ├── black_box/  
│   └── database/  
├── ai/  
│   ├── vision/  
│   ├── thermal/  
│   ├── anomaly/  
│   ├── structural/  
│   └── system_health/  
├── dashboard/  
├── simulator/  
├── tests/  
└── docs/
```

27. DATA ARCHITECTURE

Logical Table	Main Fields
nodes	node_id, zone, status, battery, last_seen, firmware
sensor_readings	timestamp, node_id, sensor_id, value, unit
events	event_id, timestamp, zone, type, severity, confidence, status
incidents	incident_id, start_time, end_time, event_ids, operator_ack
system_health	timestamp, network, power, storage, ai_status, node_count

28. SIMULATOR-FIRST DEVELOPMENT

Before connecting all physical sensors, create a software simulator that produces normal and abnormal sensor values. This allows AI, fusion, risk, dashboard and Black Box modules to be tested before the complete hardware build is finished.

Normal: PIR=0, Temperature=28.4C, Humidity=67%, Thermal=Normal, Vibration=Normal
Simulated Event: PIR=1, Camera Event=1, Thermal=Abnormal

29. MINIMUM VIABLE PROTOTYPE

Component	Qty
ESP32	2
PIR	2
DHT22	1
MQ-2	1
AMG8833	1
ADXL355	1
SX1278	2
DS3231	1
MicroSD	1
IP Camera	1
Jetson	1
Relay	1
Buzzer/LED	1

The MVP should demonstrate one remote sensor node + one critical-building node + one camera + Jetson + AI + dashboard + Black Box.

30. TESTING AND VALIDATION PLAN

Test	Purpose	Expected Evidence
Motion Test	PIR + camera correlation	Event generated and correlated
Thermal Test	Controlled heat source	Thermal change recorded
Smoke Test	Safe controlled smoke	Safety event logged
Gas Sensor Test	Controlled demonstration source	MQ-2 response recorded
Structural Test	Controlled vibration/tilt	ADXL355 deviation recorded
Network Failure	Disconnect communication	Local operation continues
Power Failure	Test UPS/local storage	Black Box survives interruption
Node Failure	Turn off one node	Self-diagnostic identifies failure
Black Box Recovery	Recover stored event	Event remains readable
AI False-Positive Test	Normal + abnormal scenarios	Measured false-positive rate

31. PERFORMANCE METRICS

Metric	Meaning
Detection Rate	Percentage of test events detected
False Alarm Rate	Incorrect alert percentage
Detection Latency	Event-to-alert delay
AI Inference Time	Processing duration
Packet Loss	Lost telemetry
Uptime	Operational percentage
Recovery Time	Failure recovery duration
Storage Integrity	Data recovery reliability
Node Availability	Working nodes
AI Precision / Recall	Model classification performance

All performance values must be measured experimentally. The prototype should not claim 100% accuracy, zero latency or guaranteed detection.

32. PROTOTYPE BILL OF MATERIALS

Item	Qty	Approx. Unit	Approx. Subtotal
NVIDIA Jetson Orin Nano Super	1	BDT 30,587	BDT 30,587
ESP32 DevKitC WROOM-32E	6	BDT 2,450	BDT 14,700
ADXL355	2	≈ BDT 5,140	≈ BDT 10,280
AMG8833	4	≈ BDT 3,344	≈ BDT 13,376
DHT22	6	BDT 260	BDT 1,560
MQ-2	6	BDT 139	BDT 834
HC-SR501 PIR	8	BDT 93	BDT 744
HB100X	4	≈ BDT 990	≈ BDT 3,960
Outdoor IP/IR Camera	6	BDT 5,100	BDT 30,600
SX1278 LoRa	12	BDT 859	BDT 10,308
DS3231 RTC	6	BDT 244	BDT 1,464
MicroSD Module	6	BDT 90	BDT 540
128GB microSD	6	≈ BDT 1,500*	≈ BDT 9,000
Relay	6	BDT 80	BDT 480
Solar + Battery Set	6	≈ BDT 5,000*	≈ BDT 30,000
Alarm/Strobe	6	≈ BDT 1,200*	≈ BDT 7,200

Estimated Core Hardware Total: ≈ BDT 165,600

33. INFRASTRUCTURE COST

Component	Estimated Cost
Enclosure + PCB + Wiring	BDT 25,000
Network / PoE Accessories	BDT 20,000
C2 Monitor	BDT 15,000
UPS / Power Conditioning	BDT 12,000
Mounting / Weatherproof Hardware	BDT 8,000
Infrastructure Estimate	≈ BDT 80,000

34. FULL PROTOTYPE BUDGET

Core hardware: ≈ BDT 165,600
Infrastructure: ≈ BDT 80,000
Estimated prototype total: ≈ BDT 245,600
15% contingency: ≈ BDT 36,800
Recommended working budget: ≈ BDT 282,500

This is a demonstration-scale planning budget, not a real military procurement quotation. Real deployment cost depends on area, sensor density, redundancy, networking, certified equipment, power infrastructure, installation, civil works, maintenance, environmental conditions and procurement requirements.

35. APPROXIMATE COST BY SYSTEM LAYER

System Layer	Approximate Budget
Sensor Nodes	BDT 45k-60k
Cameras	≈ BDT 30.6k
LoRa Communication	≈ BDT 10k+
Edge AI	≈ BDT 30.6k
Black Box	≈ BDT 11k
Solar + Battery	≈ BDT 30k
C2 + Network	≈ BDT 35k-50k
Mechanical Integration	≈ BDT 33k
Contingency	≈ BDT 37k

36. PRICING NOTES

- ESP32 DevKitC WROOM-32E: planning reference ≈ BDT 2,450.
- SX1278 LoRa: planning reference ≈ BDT 859.
- DHT22: planning reference ≈ BDT 260.
- MQ-2: planning reference ≈ BDT 139.
- HC-SR501: planning reference ≈ BDT 93.
- DS3231: planning reference ≈ BDT 244.
- MicroSD module: planning reference ≈ BDT 90.
- 1-channel relay: planning reference ≈ BDT 80.
- Example 4MP Hikvision outdoor IP/IR camera: planning reference ≈ BDT 5,100.
- ADXL355, AMG8833 and Jetson values are international/manufacturer-distributor planning references converted for budgeting.

* 128GB storage, solar/battery set and alarm/strobe figures are estimated allowances and can vary significantly by brand, specification, availability, shipping, exchange rate and import costs.

37. IMPORTANT HARDWARE LIMITATIONS

- AMG8833 is a localized thermal-array sensor, not a long-range thermal surveillance camera.
- HB100X is a prototype microwave motion sensor, not a military-grade long-range radar.
- MQ-2 is a prototype gas/smoke sensor, not certified CBRN detection equipment.
- ESP32 is intended here for prototyping; certified field deployments may require different hardware.
- Jetson Orin Nano Super Developer Kit is development/prototyping hardware, not a military-certified computer.
- AI performance must be experimentally measured.
- Real deployment requires professional engineering and environmental analysis.

38. FUTURE UPGRADE ROADMAP

Version 1 - Demonstration Prototype

- ESP32
- LoRa

- Cameras
- Jetson
- AI Monitoring
- Black Box
- 3D dashboard

Version 2 - Advanced Prototype

- Industrial environmental sensors
- Improved camera AI
- Stronger sensor fusion
- Centralized storage
- Improved cybersecurity
- Automated diagnostics

Version 3 - Research Platform

- Predictive maintenance
- Advanced anomaly models
- Structural digital models
- Larger digital twin
- Redundant communications
- Industrial thermal imaging
- Advanced environmental sensing
- Secure device identity

39. MAIN PROJECT INNOVATIONS


Innovation	Value
AI Monitoring Layer	Continuous intelligent analysis of sensor and camera information
Multi-Sensor AI Fusion	Correlates independent evidence sources
Black Box	Preserves important events and telemetry
Incident Replay	Reconstructs event timelines
3D Digital Twin	Provides spatial visualization of the base
Self-Diagnostics	Monitors the health of the monitoring system itself
Structural Resilience	Adds critical-building structural and environmental monitoring
Offline Capability	Maintains local monitoring and recording during connectivity loss
Explainable AI	Shows the evidence behind important events
Modular Architecture	Allows additional sensors and AI modules to be added later

40. FINAL SYSTEM OPERATION

REAL WORLD → SENSORS + CAMERAS → ESP32 NODES → LOCAL FILTERING → LORA / ETHERNET / WI-FI → JETSON EDGE AI → AI MONITORING → VISION / THERMAL / MOTION / ENVIRONMENT / STRUCTURAL AI → ANOMALY DETECTION →

41. FINAL SYSTEM DIAGRAM

End-to-end prototype architecture - sensors, AI monitoring, fusion, C2, Black Box and offline continuity



42. FINAL PROJECT STATEMENT

NEXGUARD is a conceptual AI-powered full-base defensive security, surveillance, safety, infrastructure-monitoring and incident-recording platform. Its strength is not any individual component, but the integration of distributed sensors, AI Monitoring, edge computing, sensor fusion, resilient communication, system-health monitoring, digital visualization and Black Box recording into one continuous information cycle.

The fundamental operating philosophy is: SENSE → AI MONITOR → VERIFY → FUSE → ASSESS → ALERT → RECORD → REPLAY.

43. CONCLUSION

NEXGUARD demonstrates how IoT, Artificial Intelligence, edge computing, distributed sensing, resilient communications, structural monitoring and digital visualization can be combined into one intelligent defensive monitoring architecture.

The system senses the environment. AI monitors the collected information. The fusion engine correlates independent evidence. The decision layer evaluates the event. The operator receives an explainable alert. The Black Box records the event. The Incident Replay system reconstructs what happened. The 3D Digital Twin presents the overall situation in an intuitive digital environment.

FINAL IDEA: A SYSTEM THAT CAN SENSE, UNDERSTAND, VERIFY, REMEMBER AND EXPLAIN.