

Scientific Programming

Practical 9

Introduction

Luca Bianco - Academic Year 2017-18
luca.bianco@fmach.it

Numpy

Numpy is a fundamental library for **high performance scientific computations**. It provides fast and memory efficient data structures like **ndarray** with broadcasting capabilities, standard mathematical functions that can be applied on the arrays avoiding loops, linear algebra functions, I/O methods and it is well integrated with programming languages like C.

```
import numpy as np
```

ndarray

Numpy ndarray is an N-dimensional array object designed to contain homogeneous data (i.e. all data must have the same type)

They have two information:

- a **shape**

- and

- a **dtype**

```
import numpy as np

A = np.array([[1,2.1,3], [4, 4.3, 5.1]])

print(A)
print(type(A))
print(A.shape)
print(A.dtype)

[[ 1.  2.1  3. ]
 [ 4.  4.3  5.1]]
<class 'numpy.ndarray'>
(2, 3)
float64
```

ndarray

Numpy ndarray is an N-dimensional array object designed to contain homogeneous data (i.e. all data must have the same type)

```
Original lists:  
[0.0, 1.0, 1.4142135623730951, 1.7320508075688772, 2.0]  
[0.0, 1.0, 1.2599210498948732, 1.4422495703074083, 1.5874010519681994]
```

```
Numpy ndarray:  
[ 0.          1.          1.41421356  1.73205081  2.          ]
```

```
The shape: (5,)  
The dimensionality: 1  
The type: float64
```

```
The 2D array:  
[[ 0.          1.          1.41421356  1.73205081  2.          ]  
 [ 0.          1.          1.25992105  1.44224957  1.58740105]]
```

```
The shape: (2, 5)  
The dimensionality: 2  
The type: float64
```

```
import numpy as np  
import math  
  
mysqrt = [math.sqrt(x) for x in range(0,5)]  
mycrt = [x**(1/3) for x in range(0,5)]  
print("Original lists:")  
print(mysqrt)  
print(mycrt)  
print("")  
npData = np.array(mysqrt)  
print("Numpy ndarray:")  
print(npData)  
print("")  
print("The shape:", npData.shape)  
print("The dimensionality:", npData.ndim)  
print("The type:", npData.dtype)  
print("")  
twoDarray = np.array([mysqrt, mycrt])  
print("The 2D array:")  
print(twoDarray)  
print("")  
print("The shape:", twoDarray.shape)  
print("The dimensionality:", twoDarray.ndim)  
print("The type:", twoDarray.dtype)
```

ndarray

Zeros, ones and diagonals...

1. Array: `np.zeros(N)` or matrix: `np.zeros((N,M))`
2. Array: `np.ones(N)` or matrix: `np.ones((N,M))`
3. Matrix: `np.eye(N)`

```
Zero array (1x3)
[ 0.  0.  0.]
```

```
Zero matrix (4x3)
[[ 0.  0.  0.]
 [ 0.  0.  0.]
 [ 0.  0.  0.]
 [ 0.  0.  0.]]
```

```
Ones array (1x3)
[ 1.  1.  1.]
```

```
Ones matrix (3x2)
[[ 1.  1.]
 [ 1.  1.]
 [ 1.  1.]]
```

```
Diagonal matrix
[[ 1.  0.  0.  0.]
 [ 0.  1.  0.  0.]
 [ 0.  0.  1.  0.]
 [ 0.  0.  0.  1.]]
```

```
Range 0-4
[0 1 2 3 4]
A diagonal matrix:
[[0 0 0 0 0]
 [0 1 0 0 0]
 [0 0 2 0 0]
 [0 0 0 3 0]
 [0 0 0 0 4]]
It's shape:
(5, 5)
```

```
import numpy as np

zeros = np.zeros(3)
zMat = np.zeros((4,3))
ones = np.ones(3)
oMat = np.ones((3,2))
diag = np.eye(4)
rng = np.arange(5) #5 excluded!

print("Zero array (1x3)")
print(zeros)
print("")
print("Zero matrix (4x3)")
print(zMat)
print("")
print("Ones array (1x3)")
print(ones)
print("")
print("Ones matrix (3x2)")
print(oMat)
print("")
print("Diagonal matrix")
print(diag)
print("")
print("Range 0-4")
print(rng)
print("A diagonal matrix:")
dm = np.diag(rng)
print(dm)
print("It's shape:")
print(dm.shape)
```

ndarray

Zeros, ones and diagonals...

Numpy has its own **range** method that is called `np.arange(N)`. Evenly spaced values in a range can be obtained also with `np.linspace(S,E, num=N, endpoint=True/False)` to obtain N linearly spaced values from S to E (included, unless endpoint = False is specified).


ndarray

Create a random array of 1000 values drawn from:


1. a gaussian distribution with $\sigma = 20$ and $\mu = 2$
2. a uniform distribution from 0 to 5
3. a binomial distribution with $p = 0.5$ and $n = 12$

Random values


Gaussian(20,2):



Uniform(0,5):



Binomial(12,0.5):



```
import numpy as np
import matplotlib.pyplot as plt

#get the gaussian random array
g = np.random.normal(20,2, 1000)
#get the uniform random array with values in [0,5]
u = np.random.uniform(0,5, 1000)
#get the binomial random array
b = np.random.binomial(12,0.5, 1000)

print("Gaussian(20,2):")
plt.hist(g, bins = 30)
plt.show()
print("")
print("Uniform(0,5):")
plt.close()
plt.hist(u, bins = 10)
plt.show()
print("")
print("Binomial(12,0.5):")
plt.close()
plt.hist(b, bins = 10)
plt.show()
```

random seed

Random values

```
import numpy as np

u = np.random.uniform(0,1,3)
u1 = np.random.uniform(0,1,3)
u2 = np.random.uniform(0,1,3)

print(" u: {}\n u1:{}\n u2:{}".format(u,u1,u2))

print("")
print("With random seed reinit.")
np.random.seed(0)
u = np.random.uniform(0,1,3)
np.random.seed(0)
u1 = np.random.uniform(0,1,3)
np.random.seed(0)
u2 = np.random.uniform(0,1,3)

print(" u: {}\n u1:{}\n u2:{}".format(u,u1,u2))
```

```
u: [ 0.1855235  0.98513018  0.91982263]
u1:[ 0.91378198  0.44407375  0.78036964]
u2:[ 0.64288027  0.32220978  0.42408156]
```

With random seed reinit.

```
u: [ 0.5488135  0.71518937  0.60276338]
u1:[ 0.5488135  0.71518937  0.60276338]
u2:[ 0.5488135  0.71518937  0.60276338]
```


Numpy ↔ Pandas

```
{'two': 2, 'three': 3, 'one': 1, 'four': 4}
```

```
<class 'pandas.core.series.Series'>
```

```
<class 'numpy.ndarray'>
```

Numpy matrix

```
[[0 0 0 0 0 0]
 [0 1 0 0 0 0]
 [0 0 2 0 0 0]
 [0 0 0 3 0 0]
 [0 0 0 0 4 0]
 [0 0 0 0 0 5]]
```

Pandas DataFrame

	0	1	2	3	4	5
0	0	0	0	0	0	0
1	0	1	0	0	0	0
2	0	0	2	0	0	0
3	0	0	0	3	0	0
4	0	0	0	0	4	0
5	0	0	0	0	0	5

Reindexed DataFrame

	a1	b2	c3	d4	e5	f6
A	0	0	0	0	0	0
B	0	1	0	0	0	0
C	0	0	2	0	0	0
D	0	0	0	3	0	0
E	0	0	0	0	4	0
F	0	0	0	0	0	5

```
import pandas as pd
import numpy as np
```

```
myDict = {"one" : 1, "two" : 2, "three" : 3, "four" : 4}
```

```
mySeries = pd.Series(myDict)
```

```
print(myDict)
print("")
print(type(mySeries))
print("")
print(type(mySeries.values))
print("")
```

```
myMat = np.diag(np.arange(6))
myDF = pd.DataFrame(myMat)
print("Numpy matrix")
print(myMat)
print("")
print("Pandas DataFrame")
print(myDF)
print("")
print("Reindexed DataFrame")
myDF = pd.DataFrame(myMat, index = list("ABCDEF"),
                    columns = ['a1', 'b2', 'c3', 'd4', 'e5', 'f6'])
print(myDF)
```

Reshaping

ndarrays can be reshaped...

```
import numpy as np

myA = np.arange(10)

myB = myA.reshape(2,7)
print(myB)
```

```
-----
ValueError                                Traceback (most recent call last)
<ipython-input-9-2936ce504f51> in <module>()
      3 myA = np.arange(10)
      4
----> 5 myB = myA.reshape(2,7)
      6 print(myB)
```

ValueError: cannot reshape array of size 10 into shape (2,7)

```
import numpy as np

myA = np.arange(10)

print("The array:")
print(myA)
print("")
myB = myA.reshape((2,5))
print("Reshaped:")
print(myB)

myC = myB.ravel()
print("")
print("Back to array:")
print(myC)
```

The array:
[0 1 2 3 4 5 6 7 8 9]

Reshaped:
[[0 1 2 3 4]
 [5 6 7 8 9]]

Back to array:
[0 1 2 3 4 5 6 7 8 9]

Looping through arrays

`np.ndarray.flat`

```
[ 0  1  2  3  4  5  6  7  8  9 10 11]
```

Matrix:

```
[[ 0  1  2]
```

```
 [ 3  4  5]
```

```
 [ 6  7  8]
```

```
 [ 9 10 11]]
```

Looping through elements:

Element: 0

Element: 1

Element: 2

Element: 3

Element: 4

Element: 5

Element: 6

Element: 7

Element: 8

Element: 9

Element: 10

Element: 11

Looping row by row:

Row: [0 1 2]

el: 0

el: 1

el: 2

Row: [3 4 5]

el: 3

el: 4

el: 5

Row: [6 7 8]

el: 6

el: 7

el: 8

Row: [9 10 11]

el: 9

el: 10

el: 11

```
import numpy as np
```

```
myA = np.arange(12)
```

```
print(myA)
```

```
print("")
```

```
print("Matrix:")
```

```
myA = myA.reshape((4,3))
```

```
print(myA)
```

```
print("Looping through elements:")
```

```
for el in myA.flat:
```

```
    print("Element:", el)
```

```
print("Looping row by row:")
```

```
for el in myA:
```


```
    print("Row: ", el)
```

```
    for j in el:
```

```
        print("\tel:", j)
```

N-Dimensions

Note that `np.ndarray[0,:,:]` is the whole first matrix. `np.ndarray[:,0,:]` is all the first rows, while `np.ndarray[:, :,0]` is all the first columns. Regarding slicing and indexing, the same reasoning applies to n-dimensional matrices. For example, `myB` below is a 3x3x3 matrix.



```
[[3 7 9 3]
 [5 2 4 7]
 [6 8 8 1]]
```

```
myA[2,2] = 8
myA[1,3] = 7
myA[0,3] = 3
second row: [5 2 4 7]
```

```
3D matrix
- shape: (3, 3, 3)
[[[6 7 7]
  [8 1 5]
  [9 8 9]]
```

```
[[4 3 0]
 [3 5 0]
 [2 3 8]]
```

```
[[1 3 3]
 [3 7 0]
 [1 9 9]]]
```

```
myB[0,2,2] = 9
Second matrix:
[[4 3 0]
 [3 5 0]
 [2 3 8]]
Third row of second matrix:
[2 3 8]
Second column of second matrix:
[3 5 3]
```

```
import numpy as np
```

```
myA = np.random.randint(0,10, size = (3,4))
print(myA)
print("")
print("myA[2,2] = ", myA[2,2])
print("myA[1,3] = ", myA[1,3])
print("myA[0,3] = ", myA[0,3])
print("second row:", myA[1,:])
print("")
print("3D matrix ",)
myB = np.random.randint(0,10, size = (3,3,3))
print("- shape:", myB.shape)
print(myB)
print("")
print("myB[0,2,2] = ", myB[0,2,2])
print("Second matrix:")
print(myB[1,:,:])
print("Third row of second matrix:")
print(myB[1,2,:])
print("Second column of second matrix:")
print(myB[1,:,1])
```

Operator broadcasting

```

B + C
[[[ 6  4  4]
  [10 11 11]
  [10 12  8]]

  [[ 5  8 13]
  [14  7  7]
  [11 13 13]]

  [[ 7 10 11]
   [ 8  6  9]
   [ 9 13  8]]]

B
[[[2 0 0]
  [4 5 5]
  [6 8 4]]

  [[1 4 9]
   [8 1 1]
   [7 9 9]]

  [[3 6 7]
   [2 0 3]
   [5 9 4]]]
Sub array B - 20
[[[-18 -20  0]
  [-16 -15  5]
   [ 6  8  4]]

  [[-19 -16  9]
   [-12 -19  1]
   [ 7  9  9]]

  [[-17 -14  7]
   [-18 -20  3]
   [ 5  9  4]]]

```

```

Matrix A 3x2
[[0 4]
 [7 3]
 [2 7]]

```

```

Matrix B 3x3x3
[[[2 0 0]
  [4 5 5]
  [6 8 4]]

  [[1 4 9]
   [8 1 1]
   [7 9 9]]

  [[3 6 7]
   [2 0 3]
   [5 9 4]]]

```

```

Matrix C 3x1
[[4]
 [6]
 [4]]

```

```

A squared
[[ 0 16]
 [49  9]
 [ 4 49]]

```

```

A square-rooted
[[ 0.          2.          ]
 [ 2.64575131  1.73205081]
 [ 1.41421356  2.64575131]]

```

```

B square-rooted
[[[ 1.41421356  0.          0.          ]
  [ 2.          2.23606798  2.23606798]
  [ 2.44948974  2.82842712  2.          ]]]

```

```

[[[ 1.          2.          3.          ]
  [ 2.82842712  1.          1.          ]
  [ 2.64575131  3.          3.          ]]]

```

```

[[[ 1.73205081  2.44948974  2.64575131]
  [ 1.41421356  0.          1.73205081]
  [ 2.23606798  3.          2.          ]]]

```

```

A + C
[[ 4  8]
 [13  9]
 [ 6 11]]

```

```
import numpy as np
```

```

A = np.random.randint(0,10, size = (3,2))
B = np.random.randint(0,10, size = (3,3,3))
C = np.random.randint(0,10, size = (3,1))

```

```

print("Matrix A 3x2")
print(A)
print("")
print("Matrix B 3x3x3")
print(B)
print("")
print("Matrix C 3x1")
print(C)
print("")
print("A squared")
print(A**2)
print("")
print("A square-rooted")
print(np.sqrt(A))

```

```

print("")
print("B square-rooted")
print(np.sqrt(B))

```

```

print("A + C ")
print(A + C)
print("")

```

```

print("B + C ")
print(B + C)

```

```

print("")
print("B")
print(B)
print("Sub array B - 20")
B[:, 0:2 , 0:2 ] -= 20
print(B)

```


Linear algebra

```
import numpy as np
from numpy import linalg

A = np.random.randint(0,10, size = (4,4))
print("Matrix A:")
print(A)
print("")
print("inv(A)")
A_1 = linalg.inv(A)
print(A_1)
print("")
print(np.dot(A,A_1))
```

Matrix A:
[[3 7 5 5]
[0 1 5 9]
[3 0 5 0]
[1 2 4 2]]

```
inv(A)
[[ 0.23121387  0.05780347  0.38150289 -0.83815029]
 [ 0.09537572 -0.10115607 -0.16763006  0.21676301]
 [-0.13872832 -0.03468208 -0.02890173  0.50289017]
 [ 0.06647399  0.1416185   0.03468208 -0.30346821]]

[[ 1.00000000e+00  0.00000000e+00  2.77555756e-17  0.00000000e+00]
 [ 0.00000000e+00  1.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  1.00000000e+00  0.00000000e+00]
 [-2.77555756e-17  0.00000000e+00  6.93889390e-17  1.00000000e+00]]
```

```
import numpy as np
```

```
a = np.array([1, 2, 3, 1, 2, 3,1, 1 ,1])
A = a.reshape((3,3))
B = np.random.randint(0,10, size = (3,2))
```

```
print("A (3x3)")
print(A)
print("")
print("B (3x2)")
print(B)
print("")
print("AxB (3x2)")
print(A.dot(B))
print("")
print("A transposed:")
print(A.T)
```



A (3x3)
[[1 2 3]
[1 2 3]
[1 1 1]]

B (3x2)
[[4 3]
[4 4]
[8 4]]

AxB (3x2)
[[36 23]
[36 23]
[16 11]]

A transposed:
[[1 1 1]
[2 2 1]
[3 3 1]]

<https://docs.scipy.org/doc/numpy-1.13.0/reference/index.html>

 SciPy.org 

SciPy.org Docs NumPy v1.13 Manual index next previous

NumPy Reference

Release: 1.13
Date: June 10, 2017

This reference manual details functions, modules, and objects included in NumPy, describing what they are and what they do. For learning how to use NumPy, see also [NumPy User Guide](#).

- Array objects
 - The N-dimensional array (`ndarray`)
 - Scalars
 - Data type objects (`dtype`)
 - Indexing
 - Iterating Over Arrays
 - Standard array subclasses
 - Masked arrays
 - The Array Interface
 - Datetimes and Timedeltas
- Universal functions (`ufunc`)
 - Broadcasting
 - Output type determination
 - Use of internal buffers
 - Error handling
 - Casting Rules
 - Overriding Ufunc behavior
 - `ufunc`
 - Available ufuncs
- Routines
 - Array creation routines
 - Array manipulation routines

Table Of Contents

- [NumPy Reference](#)
 - [Acknowledgements](#)

Previous topic
[Beyond the Basics](#)
Next topic
[Array objects](#)

Exercises

1. Write a function that converts a numpy ndarray of temperatures expressed in Degrees Celsius into Degrees Fahrenheit. The formula to convert a temperature C in Celsius into F in Fahrenheit is the following:

$$F = C * 9/5 + 32$$

Write then a function that converts a numpy ndarray of temperatures in Fahrenheit into Celsius.

Finally:

1. apply the Celsius to Fahrenheit conversion on an ndarray containing the following October's minimum and maximum temperatures in Trento: tmin = [12, 11, 11, 8, 9, 10, 3, 8, 4, 5, 10, 9, 8, 9, 8, 7, 6, 4, 5, 6, 9, 9, 3, 3, 5] and tmax = [15, 22, 18, 20, 22, 22, 20, 21, 21, 21, 21, 23, 24, 24, 24, 25, 22, 22, 20, 20, 19, 15, 20, 23, 19];
2. check that both functions work correctly by converting the values from Celsius to Fahrenheit and back to Celsius;
3. plot the minimum and maximum temperatures in celsius on the same graph. Since the temperatures refer to the first 25 days of the month of October, the x coordinate can be a range(1,26);

Show/Hide Solution

2. Solve the following system of linear equations:

$$\begin{cases} 3x - 4y + 2z - 5w = -9 \\ -4x + 4y + 10z + w = 32 \\ -x + 2y + -7z - w = -7 \\ x + y + z + w = 1 \end{cases}$$