

Assignment 6 - Game-playing System

February 26, 2024

1 Assignment 6 - Game-playing System

- Student 1 - Luca Modica
- Student 2 - Hugo Alves Henriques E Silva

```
[51]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import pandas as pd
from icecream import ic

sns.set_style()
%matplotlib inline
np.random.seed(0)
```

1.1 Game setup

```
[52]: class TicTacToe:
    def __init__(self, size):
        self.size = size
        self.board = [' ' for _ in range(size*size)]
        self.current_player = 'X'

    def print_board(self):
        hline = ('-----'*(self.size)).replace("-", "", self.size)
        print(hline)
        for i in range(0, self.size*self.size, self.size):
            print('|', end='')
            for j in range(self.size):
                print(' ', self.board[i + j], '|', end='')
            print('\n', end='')
            print(hline, end='')
            if i != (self.size*self.size) - self.size:
                print('\n', end='')
```

```

def make_move(self, position):
    if position < self.size*self.size and self.board[position] == ' ':
        self.board[position] = self.current_player
        self.current_player = 'O' if self.current_player == 'X' else 'X'
    else:
        print('Invalid move. Try again.')

    return self.clone()

def get_winner(self):
    winning_combinations = []
    for i in range(self.size):
        winning_combinations.append([j for j in range(i*self.size, (i+1)*self.
↪size)]) # rows
        winning_combinations.append([j for j in range(i, self.size*self.size,
↪self.size)]) # columns
        winning_combinations.append([i for i in range(0, self.size*self.size, self.
↪size+1)]) # diagonal 1
        winning_combinations.append([i for i in range(self.size-1, self.size*self.
↪size-self.size+1, self.size-1)]) # diagonal 2

    for combination in winning_combinations:
        if all(self.board[i] == self.board[combination[0]] and self.board[i] != ' '
↪' for i in combination):
            return self.board[combination[0]]

    if ' ' not in self.board:
        return 'Draw'

    # no winner yet
    return None

def is_game_over(self):
    return self.get_winner() in ['X', 'O', 'Draw']

def clone(self):
    clone_game = TicTacToe(self.size)
    clone_game.board = self.board.copy()
    clone_game.current_player = self.current_player
    return clone_game

def get_legal_moves(self):
    return [i for i in range(self.size*self.size) if self.board[i] == ' ']

def is_winning_move(self, move):
    clone_game = self.clone()

```

```

clone_game.make_move(move)
return clone_game.get_winner() == self.current_player

def get_random_move(self):
    # If there's a winning move, take it
    for move in self.get_legal_moves():
        if self.is_winning_move(move):
            return move

    return np.random.choice(self.get_legal_moves())

def __repr__(self) -> str:
    return f'TicTacToe({self.size}, {self.board}, {self.current_player})'

```

```

[53]: game = TicTacToe(3)

print('Welcome to Tic Tac Toe!')
game.make_move(0)
game.make_move(1)
game.make_move(2)
game.make_move(4)
game.make_move(3)
game.make_move(5)
game.make_move(7)
game.make_move(6)
game.make_move(8)

print('\n')
game.print_board()
print('\n')
game.get_winner()

```

Welcome to Tic Tac Toe!

```

-----
|  X  |  0  |  X  |
-----
|  X  |  0  |  0  |
-----
|  0  |  X  |  X  |
-----

```

```
[53]: 'Draw'
```

1.2 Game strategy setup

```
[54]: import math
from typing import Literal

class MCTSNode:
    def __init__(self, game_state: TicTacToe, parent=None, move=None):
        self.game_state = game_state # An instance of TicTacToe representing
        ↪ the state
        self.parent = parent
        self.move = move # The move (index in the board list) that led to this
        ↪ state
        self.children: list[MCTSNode] = []
        self.visits = 0
        self.wins = 0

    def add_child(self, child):
        self.children.append(child)

    def select_child(self):
        return max(self.children, key=lambda child: child.uct_score())

    def expand(self):
        # Assume game_state has a method get_legal_moves() that returns all
        ↪ possible moves
        legal_moves = self.game_state.get_legal_moves()
        for move in legal_moves:
            # Assume applying a move returns a new game state
            new_game_state = self.game_state.clone()
            new_game_state.make_move(move)
            new_node = MCTSNode(new_game_state, self, move)
            self.add_child(new_node)

    def simulate(self) -> Literal['X', 'O', 'Draw']:
        current_state = self.game_state.clone()
        while not current_state.is_game_over():
            move = current_state.get_random_move()
            current_state.make_move(move)

        return current_state.get_winner()

    def backpropagate(self, simulation_result):
        self.visits += 1
        if simulation_result == 'Draw':
            self.wins += 0.5
        elif (simulation_result == 'X' and self.game_state.current_player ==
        ↪ 'O') or \
```

```

        (simulation_result == '0' and self.game_state.current_player ==
↪ 'X'): # AI won
            self.wins += 1
        else: # AI lost
            self.wins -= 1

        if self.parent:
            self.parent.backpropagate(simulation_result)

    def uct_score(self, C=math.sqrt(2)):
        if self.visits == 0:
            return float('inf') # Ensure unvisited nodes are prioritized
        parent_visits = self.parent.visits if self.parent else 1 # Use 1 as a
↪ fallback for the root
        return (self.wins / self.visits) + C * math.sqrt(math.
↪ log(parent_visits) / self.visits)

    def __repr__(self) -> str:
        return f"MCTSNode(move={self.move}, visits={self.visits}, wins={self.
↪ wins}, children={len(self.children)})"

```

```

[55]: def select_node(node: MCTSNode):
    """
    Traverse the tree from the given node down to a leaf node using the
↪ select_child method.
    This involves choosing the child with the highest UCB1 score at each step.
    """
    current_node = node
    while current_node.children:
        current_node = current_node.select_child()
    return current_node

def run_mcts(root_node, iterations=100):
    for _ in range(iterations):
        # Selection step
        leaf_node = select_node(root_node)

        # Check if the game at the leaf node is not over
        if not leaf_node.game_state.is_game_over():
            # Expansion step
            leaf_node.expand()

            # Choose a child node from the newly expanded ones for simulation
            # This step assumes there's at least one child after expansion
            if leaf_node.children:
                selected_child = leaf_node.select_child()
            else:

```

```

        selected_child = leaf_node
    else:
        selected_child = leaf_node

    # Simulation step
    simulation_result = selected_child.simulate()

    # Backpropagation step
    selected_child.backpropagate(simulation_result)

```

1.3 Strategy test and evaluation

```

[59]: from IPython.display import clear_output

def play_game(grid_size=3, mcts_iterations=10000):
    game = TicTacToe(grid_size)
    current_player = "Human"
    root_node = None

    while not game.get_winner():
        clear_output(wait=True)

        if current_player == "Human":
            print("Current Board State:")
            game.print_board()
            print('\n')
            print("Your turn, Human!")
            is_valid_move = False
            while not is_valid_move:
                move = int(input("Enter your move (0-8): "))
                if move not in game.get_legal_moves():
                    print("Invalid move. Try again.")
                else:
                    game.make_move(move)
                    is_valid_move = True

            current_player = "AI"
        else:
            print("AI's turn. AI is calculating its move...\n")
            root_node = MCTSNode(game.clone(), parent=None)
            run_mcts(root_node, iterations=mcts_iterations)
            best_node = max(root_node.children, key=lambda child: child.wins/
↪child.visits)
            game.make_move(best_node.move)

            current_player = "Human"

```

```

    if game.get_winner():
        print('\n')
        game.print_board()
        print('\n')
        if game.get_winner() == 'Draw':
            print("It's a draw!")
        else:
            print(f"{game.get_winner()} wins!")
        break

```

```
play_game(grid_size=3, mcts_iterations=10000)
```

Current Board State:

```

-----
| 0 | 0 |   |
-----
| X | X | 0 |
-----
| 0 | X | X |
-----

```

Your turn, Human!

```

-----
| 0 | 0 | X |
-----
| X | X | 0 |
-----
| 0 | X | X |
-----

```

It's a draw!