

---

## Table of Contents

[TIP8419 - Algebra Linear e Multilinear] .....	1
MATRIX OPERATIONS .....	2
TENSOR OPERATIONS .....	2
MATRIX PRODUCTS .....	3
TENSOR FACTORS ESTIMATION .....	4
TENSOR RESHAPE AND N-PRODUCT .....	6
TENSOR DECOMPOSTIONS .....	7
SAVE DATA TO TXT FILE .....	10
PLACE HOLDER SECTION .....	11

## [TIP8419 - Algebra Linear e Multilinear]

Author: Lucas Abdalah

ND is a package developped for the Multilinear Algebra Course It is a shortcut for N-d array in reference to the homonym library in python

### CONTENT

#### MATRIX OPERATIONS

ND.VEC - Vectorize a `matrix`.

#### TENSOR OPERATIONS

ND.RANDN\_COMPLEX - Complex-valued

array from normal distribution.

ND.NMSE - Normalized

mean square error (NMSE) of a tensor.

ND.SLICEORT - Verify the orthogonality between the slices of a tensor

#### MATRIX PRODUCTS

ND.HADAMARD\_ - Hadamard product with two matrices.

ND.KRON\_ - Kronecker product with two matrices.

ND.KR\_ - Khatri-Rao product with two matrices.

#### TENSOR FACTORS ESTIMATION

ND.LSKRF - Least-Squares Khatri-Rao Factorization (LSKRF)

ND.LSKRONF - Least-Squares

Kronecker Product Factorization (LSKRONF)

ND.KPSVD - Kronecker

Product Singular Value Decomposition (KPSVD)

#### TENSOR RESHAPE AND N-PRODUCT

ND.UNFOLD - Unfold a tensor into N-mode tensor (matrix)

ND.FOLD - Fold a N-mode tensor (matrix) into a tensor

ND.N\_MODE - Compute the N-

mode product bewteen a tensor and factor matrices

#### TENSOR DECOMPOSTIONS

---

```

    ND.HOSVD          - Perform
the High Order Singular Value Decomposition (HOSVD) of a tensor,
truncated or full version
    ND.HOOI           - Perform
the High Order Orthogonal Iteration (HOOI) of a tensor,
truncated or full version
    ND.MLSKRF         - Perform the Multidimensional Least-
Squares Khatri-Rao Factorization (MLSKRF) of a tensor
    ND.MLSKRONF        - Perform the Multidimensional Least-
Squares Kronecker Factorization (MLS-KronF) of a tensor

SAVE DATA TO TXT FILE
    ND.MAT2TXT         - Write a matrix X into a txt file
    ND.TENSOR2TXT      - Write a 3D tensor X into a txt file

PARAFAC/CP

classdef nd

methods(Static)

```

## MATRIX OPERATIONS

```

function y = vec(x)
    % ND.VEC - Vectorize a matrix.
    %   y = vec(x) draws a vector from a given matrix.
    %
    %   See also.
    y = x(:);
end

```

## TENSOR OPERATIONS

```

function C = randn_complex(M, varargin)
    % ND.RANDN_COMPLEX - Complex-valued array from normal
distribution.
    %   C = nd.randn_complex(M,N) draws a complex-valued array from
normal
    %       distribution.
    %
    %   See also.
    C = complex(randn(M,varargin{:})), randn(M, varargin{:}));
end

```

```

function [X_nmse, X_nmse_dB] = nmse(X, X_hat)
    % ND.NMSE - Normalized mean square error (NMSE) of a tensor.
    %   [X_nmse, X_nmse_dB] = nd.nmse(X, X_hat) compute the NMSE of
two arrays
    %
    %   See also.
    X_nmse = frob(X - X_hat)^2/(frob(X)^2);
    X_nmse_dB = 20*log10(X_nmse);

```

---

```

end

function f_ord = sliceort(Xten)
% ND.SLICEORT - Verify the orthogonality between slices of a
tensor, by summing the
% the scalar between all the slices.
%
% f_ord = sliceort(Xten) compute scalar product between tensor
slices
%
% See also.
size_Xten = size(Xten);
f_ord = [];

for kk_xT = 1:size_Xten(3)
    for kk_x = 1:size_Xten(3)
        if kk_xT ~= kk_x
            f_ord(end+1) =
nd.vec(Xten(:, :, kk_xT))' * nd.vec(Xten(:, :, kk_x)) ;
        end
    end
end
f_ord = sum(f_ord);
end

```

## MATRIX PRODUCTS

```

function [C, elapsedTime] = hadamard_(A, B)
% ND.HADAMARD_ Hadamard product with two matrices.
% C = nd.hadamard_(A, B) compute the hadamard product.
%
% [C, elapsedTime] = nd.hadamard_(A, B) compute the hadamard
product elapsed time.
%
% See also.
tic;

C = A.*B;

elapsedTime = toc;
end

function [C, elapsedTime] = kron_(A, B)
% ND.KRON_ Kronecker product with two matrices.
% C = nd.kron_(A, B) compute the Kronecker product.
%
% [C, elapsedTime] = nd.kron_(A, B) compute the Kronecker
product elapsed time.
%
% See also.
tic;

```

---

```

    % [M_rows, N_columns] = size(B);
    % C = repelem(A, M_rows, N_columns).*repmat(B,[size(A)]);

    C = kron(A,B);

    elapsedTime = toc;
end

function [C, elapsedTime] = kr_(A, B)
% ND.KR_ Khatri-Rao product with two matrices.
% C = nd.kr_(A, B) compute the Khatri-Rao product.
%
% [C, elapsedTime] = nd.kr_(A, B) compute the Khatri-Rao
% product elapsed time.
%
% See also.
tic;

N = size(A,2);
if N == size(B,2)
    P = reshape(A,1,[],N);
    Q = reshape(B,[],1,N);
    C = P.*Q;
    C = reshape(C,[],N);
else
    error('number of columns should be equal')
end

elapsedTime = toc;
end

```

## TENSOR FACTORS ESTIMATION

```

function [Ahat,Bhat] = lskrf(X, M, N)
% ND.LSKRF Least-Squares Khatri-Rao Factorization (LSKRF)
% [Ahat,Bhat] = nd.lskrf(X, M, N) compute the LSKRF.
%
% See also.
[iX, jX] = size(X);

if iX == M*N % Verify the input dimensions
    Ahat = complex(zeros(M,jX),0);
    Bhat = complex(zeros(N,jX),0);

    for jj = 1:jX
        [U,S,V] = svd(reshape(X(:,jj), [N M]));
        Ahat(:,jj) = sqrt(S(1,1)).*conj(V(:,1));
        Bhat(:,jj) = sqrt(S(1,1)).*U(:,1);
    end
else
    error('number of rows of X should be equal to size M*N');
end

```

---

```

        end

    end

    function [Ahat,Bhat] = lskronf(X, Ma, Na, Mb, Nb)
    % ND.LSKRONF Least-Squares Kronecker Product Factorization
    (LSKRONF)
    % [Ahat,Bhat] = nd.lskronf(X, Ma, Na, Mb, Nb) compute the
    LSKRONF.
    %
    % See also.
    [Mx,Nx] = size(X);

    if Ma*Mb == Mx && Na*Nb == Nx % Verify the input dimensions
        Xhat = complex(zeros(Mb*Nb,Ma*Na),0);
        X_b = mat2cell(X, repelem(Mx/Ma,Ma), repelem(Nx/Na,Na));

        itCol = 1;
        for jj = 1:Na
            for ii = 1:Ma
                Xhat(:,itCol) = nd.vec(cell2mat(X_b(ii,jj)));
                itCol = itCol + 1;
            end
        end

        [U,S,V] = svd(Xhat);
        Ahat = reshape(sqrt(S(1,1)).*conj(V(:,1)),[Ma Na]);
        Bhat = reshape(sqrt(S(1,1)).*U(:,1), [Mb Nb]);

    else
        error('size of X(Mx, Nx) should match with Mc=Ma*Mb and
        Nc=Na*Nb, A(Ma, Na) and B(Mb, Nb)');
    end
end

function [U,S,V,rkp] = kpsvd(X, Xstruct)
% ND.KPSVD Kronecker Product Singular Value Decomposition (KPSVD)
% [U,S,V,rkp] = nd.kpsvd(X, Xstruct) compute the KPSVD.
%
% See also.
[Mx,Nx] = size(X);

if Xstruct(1)*Xstruct(3) == Mx && Xstruct(2)*Xstruct(4) ==
Nx % Verify the input dimensions
    Xhat =
complex(zeros(Xstruct(3)*Xstruct(4),Xstruct(1)*Xstruct(2)),0);
    X_b = mat2cell(X, repelem(Mx/Xstruct(1),Xstruct(1)),
repelem(Nx/Xstruct(2),Xstruct(2)));

    itCol = 1;
    for jj = 1:Xstruct(2)
        for ii = 1:Xstruct(1)

```

---

---

```

        Xhat(:,itCol) = nd.vec(cell2mat(X_b(ii,jj)));
        itCol = itCol + 1;
    end
    end
    [U,S,V] = svd(Xhat');
    rkp = rank(S);
else
    error('size of X(Mx, Nx) should match with
Mc=Xstruct(1)*Xstruct(3) and Nc=Xstruct(2)*Xstruct(4), for
A(Xstruct(1), Xstruct(2)) and B(Xstruct(3), Xstruct(4))');
end
end

end

```

## TENSOR RESHAPE AND N-PRODUCT

```

function Xn = unfold(Xten,N_mode)
% ND.UNFOLD  Unfold a tensor into N-mode tensor (matrix)
%   Xn = unfold(Xten,N_mode) compute into N-mode tensor
%
%   See also.
Xten_Size = size(Xten);
reSort = 1:1:numel(Xten_Size); % prod(size(Xten_Size))
reSort(N_mode) = [];
Xn = reshape(permute(Xten,[N_mode reSort]), ...
    [], ...
    prod(Xten_Size)/Xten_Size(N_mode));
end

function Xten = fold(Xn,Xten_Size,N_mode)
% ND.FOLD  Fold a N-mode tensor (matrix) into a tensor
%   Xn = fold(Xn,Xten_Size,N_mode) fold a Xn into X tensor
%
%   See also.
reSort = 1:1:numel(Xten_Size);
reSort(N_mode) = [];
reSort = [N_mode reSort];
Xten = reshape(Xn,Xten_Size(reSort));

switch N_mode
    case 1
        Xten = permute(Xten,reSort);
    otherwise
        reSort = 1:numel(Xten_Size);
        for ii = 2:N_mode
            reSort([ii-1, ii]) = reSort([ii, ii-1]);
        end
        Xten = permute(Xten,reSort);
    end
end
end

```

---

```

function Yten = N_mode(Xten,factors,N_mode)
% ND.N_MODE Compute the N-mode product bewteen a tensor and
factor matrices
% Yten = N_mode(Xten,factors,N_mode) N-mode product bewteen a
tensor and matrices
%
% See also.
if nargin < 3
    N_mode = 1:numel(factors);
end
Xten_Size = size(Xten);
for nIt = N_mode
    [Xten_Size(nIt), ~] = size(cell2mat(factors(nIt)));
    Yten =
nd.fold(cell2mat(factors(nIt))*nd.unfold(Xten,nIt), ...
        Xten_Size, ...
        nIt);
end
end

```

## TENSOR DECOMPOSTIONS

```

function [S,U] = hosvd(ten, Atype, ranksInput)
% ND.HOSVD Perform the High Order Singular Value Decomposition
(HOSVD)
% of a tensor, truncated or full version.
% [S,U] = hosvd(ten, 'trunc') compute the truncated-HOSVD
% [S,U] = hosvd(ten, 'full') compute the full-HOSVD
%
% See also.
N = numel(size(ten));
U = cell(N, 1);

switch Atype
case 'trunc'
    for i = 1:N
        [Ur, Sr, ~] = svd(nd.unfold(ten,i));
        if nargin < 3
            Ur = Ur(:,1:rank(Sr));
        else
            Ur = Ur(:,1:ranksInput(i));
        end
        U{i} = Ur;
    end
case 'full'
    for i = 1:N
        [Ur,~,~] = svd(nd.unfold(ten,i));
        U{i} = Ur;
    end
end
S = nd.N_mode(ten, (cellfun(@(x) x',
U, 'UniformOutput', false)));
U = cellfun(@(x) x, U, 'UniformOutput', false);

```

---

```

end

function [S, U, it] = hooi(ten, Atype, maxIt, ranksInput)
% ND.HOOI Perform the High Order Orthogonal Iteration (HOOI)
% of a tensor, truncated or full version.
%
% [S,U] = hooi(ten, 'trunc') compute the truncated-HOOI
% [S,U] = hooi(ten, 'full') compute the full-HOOI
%
% See also.
N = numel(size(ten));
[~, U_ten] = nd.hosvd(ten, 'full');

if nargin < 3
    maxIt = 20;
end

switch Atype
case 'trunc'
    for it = 1:maxIt
        for ii = 1:N
            N_mode = 1:N;
            N_mode(ii) = [];
            Un = nd.N_mode(ten, U_ten, N_mode);
            [Ur, Sr, ~] = svd(nd.unfold(Un,ii));
            if nargin < 3
                U{ii} = Ur(:,1:rank(Sr));
            else
                U{ii} = Ur(:,1:ranksInput(ii));
            end
        end
    end
case 'full'
    for it = 1:maxIt
        for ii = 1:N
            N_mode = 1:N;
            N_mode(ii) = [];
            Un = nd.N_mode(ten, U_ten, N_mode);
            [Usvd,~,~] = svd(nd.unfold(Un,ii));
            U{ii} = Usvd;
        end
    end
end

S = nd.N_mode(ten, cellfun(@(x) x', U, 'UniformOutput',
false));
end

function factors = mlskrf(X, N_mode, order)
% ND.MLSKRF Perform the Multidimensional Least-Squares Khatri-Rao
% Factorization (MLSKRF) of a tensor.
%
% factors = mlskrf(X, N_mode, order) compute the MLSKRF of a
tensor

```

---



---

```

%
% See also.
[~,R] = size(X);
factors = cell(N_mode, 1);
factors_r = cell(R, N_mode);
for rr = 1:R
    [Sr,Ur] = nd.hosvd(reshape(X(:,rr), flip(order)), 'full');
    for nn = 1:N_mode
        sr = (Sr(1)^(1/N_mode));
        ur = Ur{N_mode-nn+1}(:,1);
        factors_r{rr,nn} = sr*ur;
    end
end
for n = 1:N_mode
    factors{n} = reshape(cell2mat(factors_r(:,n)) ,[order(n)
R]);
end
end

function Ahat = mlskronf(X, rowsInput, colsInput, Atype)
% ND.MLSKRONF Perform the Multidimensional Least-Squares
Kronecker
% Factorization (MLS-KronF) of a tensor.
%
% factors = mlskronf(X, rowsInput, colsInput, Atype) compute the
MLSKRF of a tensor
%
% See also.
dim = {repelem(rowsInput(2)*rowsInput(3), 1, rowsInput(1));
repelem(colsInput(2)*colsInput(3), 1, colsInput(1))};
Xb = mat2cell(X,dim{1},dim{2});
Inv = {flip(rowsInput), flip(colsInput)};
K = 1;

for jA = 1:colsInput(1)
    for iA = 1:rowsInput(1)
        dim = {repelem(rowsInput(3), 1, rowsInput(2)),
repelem(colsInput(3), 1, colsInput(2))};
        X_bc = mat2cell(cell2mat(Xb(iA,jA)), dim{1}, dim{2});
        for jB = 1:colsInput(2)
            for iB = 1:rowsInput(2)
                vb(:,iB,jB) = nd.vec(cell2mat(X_bc(iB,jB)));
            end
        end
        Xhat(:,K) = reshape(vb,[],1);
        K = K + 1;
    end
end

switch Atype
case 'hosvd'
    [S,U] = nd.hosvd(reshape(Xhat, flip(rowsInput.*
colsInput)), 'full');
case 'hooi'

```

---

---

```

        [S,U] = nd.hooi(reshape(Xhat, flip(rowsInput.*
colsInput)), 'full');
    end

    UN = length(U);

    for u = 1:UN
        Ahat{UN - u + 1} = reshape((S(1)^(1/length(U)))*U{u}(:,1),
[Inv{1}(u) Inv{2}(u)]);
    end
end

```

## SAVE DATA TO TXT FILE

```

function mat2txt(file, X, permission, header)
% ND.MAT2TXT Write a matrix X into a txt file
% mat2txt(file, X, 'w', header) - Overwrite the file
% mat2txt(file, X, 'a', header) - Append to the file end
%
% See also.
[I, J] = size(X);
fileID = fopen(file, permission);
fprintf(fileID, [repelem('-', strlength(header)+3), '\n',
header, ...
        '\n', repelem('-', strlength(header)+3), '\n']);
fprintf(fileID, 'X(%d, %d)\n', I, J);
for ii = 1:I
    for jj = 1:J
        fprintf(fileID, ' %2.0f', X(ii,jj));
    end
    fprintf(fileID, ';\n');
end
fprintf(fileID, '\n');
fclose(fileID);
end

```

```

function tensor2txt(file, X, permission, header)
% ND.TENSOR2TXT Write a 3D tensor X into a txt file
% tensor2txt(file, X, 'w', header) - Overwrite the file
% tensor2txt(file, X, 'a', header) - Append to the file end
%
% See also.
[I, J, K] = size(X);

fileID = fopen(file, permission);

fprintf(fileID, [repelem('-', strlength(header)+3), '\n',
header, ...
        '\n', repelem('-', strlength(header)+3), '\n']);

for kk = 1:K
    fprintf(fileID, 'X(:, :, %d)\n', kk);
end

```

---

```
        for ii = 1:I
            for jj = 1:J
                fprintf(fileID, ' %2.0f', X(ii,jj,kk));
            end
            fprintf(fileID, ';\n');
        end
        fprintf(fileID, '\n');
    end
    fclose(fileID);
end
```

## PLACE HOLDER SECTION

```
end
```

```
end
```

```
ans =
```

```
    nd with no properties.
```

*Published with MATLAB® R2021a*