


KEEL K AND FINGER F PROFILES (X, Z), Y ±10

PT	X	Z
K1	24	-9.4
K2	56	-9.4
K3	56	-17
K4	30	-17
K5	24	-13
F1	48	-9.4
F2	54	-9.4
F3	66	-0.5
F4	108	-0.5
F5	108	-6
F6	64	-17
F7	48	-17

FEATURES (in order)


1. Disc Ø31 along X, x 0 to 4; C0.6 on the front edge.
2. Housing: box x 0 to 42, y ±18.4, z -9.4 to 21.4; C3 on the edges parallel to Y; plus a cylinder R18 about Y at (x, z) = (42, 6).
3. Keel K1 to K5 and finger F1 to F7, each extruded y ±10.
4. Pocket P (sheet TAL-001) with its servo frame origin P0 at (42, 0, 6): servo +Z (shaft) along +Y, servo +X along +X, servo +Y along -Z.
5. Servo entry from the top: cut box x 6.5 to 52.5, y ±16.2, z -6.7 up (opens the top over the whole servo). In the -Y wall: back pad channel x 11.8 to 22.4, y -18 to -16.2, z -3.5 up; notch through the wall x 24.4 to 45.3, z 6 up (joins the plug window and the idler hole).
6. Side windows: hex window H(9, 33, 6, 7) through Y (TAL-002).
7. Grip notches: 6X triangle (x, 0) (x+1.5, -1.6) (x+3, 0), x = 72, 78 … 102, through Y.
8. Roll horn (sheet 2): Ø7 centre, x -1 to 7. 4X Ø3.2 on Ø13.86 PCD at 45°, x -1 to 3.5, counterbore Ø6.5 from x 3.5 to 7 (M3 × 6 from inside the housing).
9. Case screw holes (TAL-002, seat 17.3): +Y face at x 13, z -4.2 and 16.2; -Y face at x 9.2, z -4.2 and 16.2.

NOTES


- All dimensions mm. Third-angle projection. Do not scale the drawing.
- Part frame = the frame the part is built in, in talos_arm.py (given on each sheet).
- Printed tolerance +/-0.2 unless noted; servo pocket clearances are already included.
- Fit the jaw servo from the top, shaft to +Y, before its horns and plugs; then 4X M2 × 5 case screws.
- The jaw servo's bus plugs come out through the -Y housing wall.
- Print: standing on the roll-horn disc; no support (one 32 mm bridge at the front of the servo opening); use a brim, the part is 108 tall.

THIRD ANGLE PROJECTION

WORK SET B: forearm, wrist, gripper, moving jaw, idler plates	
PROJECT TALOS 5-axis arm	EST. MASS 29 g
PART Gripper body (with fixed jaw) (part sheet 1 of 2)	SCALE 1:1
PART NO. TAL-106	UNITS / REV mm / A
QTY / ARM 1	DATE 2026-11-06
MATERIAL PLA, 20 % infill, 3 perimeters	SHEET 16 of 21



LEFT



ISOMETRIC (NOT TO SCALE)


LEFT VIEW AND SECTION A-A

Left view: the disc face (roll horn side), seen from -X.

A-A: plane y 4.9 through two roll horn screws (cutting line on sheet 1, top view), looking toward +Y.

NOTES

- All dimensions mm. Third-angle projection. Do not scale the drawing.



SECTION A-A SCALE 3:2

THIRD ANGLE PROJECTION

WORK SET B: forearm, wrist, gripper, moving jaw, idler plates	
PROJECT TALOS 5-axis arm	EST. MASS -
PART Gripper body (with fixed jaw) (part sheet 2 of 2)	SCALE 2:1
PART NO. TAL-106	UNITS / REV mm / A
QTY / ARM 1	DATE 2026-11-06
MATERIAL PLA, 20 % infill, 3 perimeters	SHEET 17 of 21