**SAMPLE GUIDELINE ON WIDGET TESTING**

1. INTRODUCTION

Widget testing is the systematic evaluation of widgets before release. This sample document exists only to test the ingestion code. It has numbered sections, several pages and a few paragraphs per section so that chunking has something to do.

1.1 Scope

This guideline applies to all widgets of type A and type B. Type C widgets are covered by a separate document and are out of scope here. The scope statement is intentionally short.

2. PRINCIPLES

2.1 Sample Size

The sample size should be large enough to detect a defect rate of five percent with ninety percent power. A minimum of thirty widgets per batch is required for type A widgets. For type B widgets a minimum of fifty widgets per batch applies.

Sample size calculations should be documented before testing starts and should not be changed after the first results are known. Any deviation must be justified in the test report.

2.2 Primary and Secondary Variables

The primary variable is the defect rate. Secondary variables include the mean weight and the colour deviation. There should generally be only one primary variable.

3. REPORTING

Each test campaign ends with a report. The report lists the batch, the sample size, the defect rate with a confidence interval and the decision. The report is signed by the responsible tester and archived for ten years.

3.1 Archiving

Reports are archived electronically. Paper copies are not required. Access to the archive is restricted to the quality department.

3.2 Deviations

Deviations from this guideline are recorded in a deviation log. Each entry names the deviation, the reason and the corrective action. The log is reviewed quarterly.

ANNEX 1

Glossary. Widget: a manufactured item of type A, B or C. Batch: a set of widgets produced under the same conditions. Defect: a widget that fails at least one acceptance criterion.